



PERMIT TO OPERATE AN AIR CONTAMINANT SOURCE

Date of Issuance 07/07/95 Application No. 1576001579F002

Effective Date 07/07/95 Permit Fee \$000

This document constitutes issuance to:

COUNTYWIDE LANDFILL, INC.
3919 GRACEMONT AVE. SW
EAST SPARTA OHIO 44626

of a permit to operate for:

LANDFILL OPERATIONS
LANDFILL OPERATIONS

The following terms and conditions are hereby expressly incorporated into this permit to operate:

1. This permit to operate shall be effective until 07/06/98
You will be contacted approximately six months prior to this date regarding the renewal of this permit. If you are not contacted, please write to the appropriate Ohio EPA field office.
2. The above-described source is and shall remain in full compliance with all applicable State and federal laws and regulations and the terms and conditions of this permit.
3. Prior to any modification of this source, as defined in rule 3745-31-01 of the Ohio Administrative Code (OAC), a permit to install must be granted by the Ohio EPA pursuant to OAC Chapter 3745-31.
4. The Director of the Ohio EPA or an authorized representative may, subject to the safety requirements of the permit holder, enter upon the premises of this source at any time for purposes of making inspections, conducting tests, examining records or reports pertaining to any emission of air contaminants, and determining compliance with any applicable State and federal air pollution laws and regulations and the terms and conditions of this permit.
5. A permit fee in the amount specified above must be remitted within 15 days from the issuance date of this permit.
6. Any transferee of this permit shall assume the responsibilities of the prior permit holder. The appropriate Ohio EPA field office must be notified in writing of any transfer of this permit.
7. This source and any associated air pollution control system(s) shall be maintained regularly in accordance with good engineering practices in order to minimize air contaminant emissions. Any malfunction of this source or any associated air pollution control system(s) shall be reported immediately to the appropriate Ohio EPA field office in accordance with OAC rule 3745-15-06. Except as provided in that rule, any scheduled maintenance or malfunction necessitating the shutdown or bypassing of any air pollution control system(s) shall be accompanied by the shutdown of this source.
8. Any unauthorized or emergency release of an air contaminant from this source which, due to the toxic or hazardous nature of the material, may pose a threat to public health, or otherwise endanger the safety or welfare of the public, shall be reported immediately to the appropriate Ohio EPA field office (during normal business hours) or to the Ohio EPA's Emergency Response Group (1-800-282-9378). (Additional reporting may be required pursuant to the federal Comprehensive Environmental Response, Compensation, and Liability Act.)
9. The appropriate Ohio EPA field office is:
AIR POLLUTION CNTRL DIV. CANTON CITY HEALTH DEPT. -
CITY HALL 420 MARKET AVE. NORTH
CANTON, OH 44702-1544 (216)-489-3385
10. If this term and condition is checked, the permit holder is subject to the attached special terms and conditions.

OHIO ENVIRONMENTAL PROTECTION AGENCY

Director

APPLICATION NUMBER: 15 76 00 1579 F002
FACILITY NAME: COUNTYWIDE LANDFILL, INC.
EQUIPMENT DESCRIPTION: LANDFILL OPERATIONS
COMPANY ID: LANDFILL OPERATIONS

SPECIAL TERMS AND CONDITIONS

1. The following rules of the Ohio Administrative Code establish the applicable emission limitation's and/or control requirements for this Ohio EPA Emission Unit:

3745-15-07	3745-19-04
3745-17-07	3745-31-05
3745-17-08	

(This condition in no way limits the applicability of other requirements of the Ohio Administrative Code to this Ohio EPA Emission Unit.)

2. This facility will not accept NESHAP regulated asbestos containing material.
3. This facility will ensure solid wastes are deposited, spread, and compacted in such a manner as to minimize or prevent visible emissions of dust. This facility will require all truckloads of solid waste to be unloaded in a manner which will minimize the drop height of the solid wastes. Any dusty materials or wastes likely to become airborne, will be watered as necessary prior to or during operations in order to minimize or eliminate visible emissions of fugitive dust, but any watering will avoid free liquids and runoff. No dusty material will be dumped during periods of high wind speed (> 20 MPH) unless treated to prevent it from becoming airborne. A wind speed indicator will be installed and maintained to determine whether the wind speed is in excess of the 20 mph limit.
4. All vehicles hauling wastes will be closed, covered, or tarped coming to or leaving the facility in order to minimize visible emission of fugitive dusts and to eliminate load loss.
5. Any dusty material to be stored prior to disposal will be watered, as necessary, or have a temporary soil cover in order to minimize or eliminate visible emissions or fugitive dust.
6. There will be no open burning on a site.
7. Visible particulate emissions of fugitive dust from the deposition, spreading and compacting of solid wastes will not exceed twenty (20) per cent opacity for a three-minute average. Test Method Nine (9) as set forth in the "Appendix on Test Methods" in 40 CFR, Part 60, "Standards of Performance for new Stationary Sources" will be used to determine compliance with the following two modifications:
 - (a) The data reduction and average opacity calculation will be based upon sets of twelve consecutive visible particulate emission observations recorded at fifteen-second intervals.
 - (b) Opacity observations will be made from a position that provides the observer a clear view of the source and the fugitive dust with the sun behind the observer. A position at least fifteen feet from the source is recommended. To the extent possible, the line of sight should be approximately perpendicular to the flow of fugitive dust and to the longer axis of the emissions. Opacity observations will be made for the point of highest opacity within the fugitive dust. Since the highest opacity usually occurs immediately above or downwind of the source, the observer should normally concentrate on the area(s) of the plume close to the source.
8. The "Dusty Load Handling Procedures" described in the January 31, 1995 letter from Mr. Greg Terwilliger of Countywide Landfill Inc. to Mr. Rick Miller of the Canton Air Agency, will be employed to minimize or eliminate fugitive dust emissions.