



State of Ohio Environmental Protection Agency

RE: FINAL PERMIT TO INSTALL CERTIFIED MAIL
MONTGOMERY COUNTY

Street Address:

122 S. Front Street

Lazarus Gov. Center TELE: (614) 644-3020 FAX: (614) 644-2329

Mailing Address:

Lazarus Gov. Center
P.O. Box 1049

Application No: 08-04141

DATE: 8/15/2000

Brainerd Industries Inc
Doug Russell
1723 Webster St
Dayton, OH 45404-0000

Enclosed please find an Ohio EPA Permit to Install which will allow you to install the described source(s) in a manner indicated in the permit. Because this permit contains several conditions and restrictions, I urge you to read it carefully.

The Ohio EPA is urging companies to investigate pollution prevention and energy conservation. Not only will this reduce pollution and energy consumption, but it can also save you money. If you would like to learn ways you can save money while protecting the environment, please contact our Office of Pollution Prevention at (614) 644-3469.

You are hereby notified that this action by the Director is final and may be appealed to the Ohio Environmental Review Appeals Commission pursuant to Chapter 3745.04 of the Ohio Revised Code. The appeal must be in writing and set forth the action complained of and the grounds upon which the appeal is based. It must be filed within thirty (30) days after the notice of the Directors action. A copy of the appeal must be served on the Director of the Ohio Environmental Protection Agency within three (3) days of filing with the Commission. An appeal may be filed with the Environmental Review Appeals Commission at the following address:

Environmental Review Appeals Commission
236 East Town Street, Room 300
Columbus, Ohio 43215

Very truly yours,

Thomas G. Rigo, Manager
Field Operations and Permit Section
Division of Air Pollution Control

CC: USEPA

RAPCA



Permit To Install

STATE OF OHIO ENVIRONMENTAL PROTECTION AGENCY

FINAL PERMIT TO INSTALL 08-04141

Application Number: 08-04141
APS Premise Number: 0857041258
Permit Fee: **\$800**
Name of Facility: Brainerd Industries Inc
Person to Contact: Doug Russell
Address: 1723 Webster St
Dayton, OH 45404-0000

Location of proposed air contaminant source(s) [emissions unit(s)]:
1723 Webster St
Dayton, Ohio

Description of proposed emissions unit(s):
4 silk screen presses to replace 4 existing presses.

The above named entity is hereby granted a Permit to Install for the above described emissions unit(s) pursuant to Chapter 3745-31 of the Ohio Administrative Code. Issuance of this permit does not constitute expressed or implied approval or agreement that, if constructed or modified in accordance with the plans included in the application, the above described emissions unit(s) of environmental pollutants will operate in compliance with applicable State and Federal laws and regulations, and does not constitute expressed or implied assurance that if constructed or modified in accordance with those plans and specifications, the above described emissions unit(s) of pollutants will be granted the necessary permits to operate (air) or NPDES permits as applicable.

This permit is granted subject to the conditions attached hereto.

Ohio Environmental Protection Agency



Director

Part I - GENERAL TERMS AND CONDITIONS

A. Permit to Install General Terms and Conditions

1. Compliance Requirements

The emissions unit(s) identified in this Permit to Install shall remain in full compliance with all applicable State laws and regulations and the terms and conditions of this permit.

2. Reporting Requirements Related to Monitoring and Recordkeeping Requirements

The permittee shall submit required reports in the following manner:

- a. Reports of any required monitoring and/or recordkeeping information shall be submitted to the appropriate Ohio EPA District Office or local air agency.
- b. Except as otherwise may be provided in the terms and conditions for a specific emissions unit, quarterly written reports of (a) any deviations (excursions) from emission limitations, operational restrictions, and control device operating parameter limitations that have been detected by the testing, monitoring, and recordkeeping requirements specified in this permit, (b) the probable cause of such deviations, and (c) any corrective actions or preventive measures which have been or will be taken, shall be submitted to the appropriate Ohio EPA District Office or local air agency. If no deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted quarterly, i.e., by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters. (These quarterly reports shall exclude deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06.)

3. Records Retention Requirements

Each record of any monitoring data, testing data, and support information required pursuant to this permit shall be retained for a period of five years from the date the record was created. Support information shall include, but not be limited to, all calibration and maintenance records and all original strip-chart recordings for continuous monitoring instrumentation, and copies of all reports required by this permit. Such records may be maintained in computerized form.

4. Inspections and Information Requests

The Director of the Ohio EPA, or an authorized representative of the Director, may, subject to the safety requirements of the permittee and without undue delay, enter upon the premises of this source at any reasonable time for purposes of making inspections, conducting tests, examining records or reports pertaining to any emission of air contaminants, and determining compliance with any applicable State air pollution laws and regulations and the terms and conditions of this permit. The permittee shall furnish to the Director of the Ohio EPA, or an authorized

representative of the Director, upon receipt of a written request and within a reasonable time, any information that may be requested to determine whether cause exists for modifying, reopening or revoking this permit or to determine compliance with this permit. Upon verbal or written request, the permittee shall also furnish to the Director of the Ohio EPA, or an authorized representative of the Director, copies of records required to be kept by this permit.

5. Scheduled Maintenance/Malfunction Reporting

Any scheduled maintenance of air pollution control equipment shall be performed in accordance with paragraph (A) of OAC rule 3745-15-06. The malfunction of any emissions units or any associated air pollution control system(s) shall be reported to the appropriate Ohio EPA District Office or local air agency in accordance with paragraph (B) of OAC rule 3745-15-06. Except as provided in that rule, any scheduled maintenance or malfunction necessitating the shutdown or bypassing of any air pollution control system(s) shall be accompanied by the shutdown of the emissions unit(s) that is (are) served by such control system(s).

6. Permit Transfers

Any transferee of this permit shall assume the responsibilities of the prior permit holder. The appropriate Ohio EPA District Office or local air agency must be notified in writing of any transfer of this permit.

7. Air Pollution Nuisance

The air contaminants emitted by the emissions units covered by this permit shall not cause a public nuisance, in violation of OAC rule 3745-15-07.

8. Termination of Permit to Install

This Permit to Install shall terminate within eighteen months of the effective date of the Permit to Install if the owner or operator has not undertaken a continuing program of installation or modification or has not entered into a binding contractual obligation to undertake and complete within a reasonable time a continuing program of installation or modification. This deadline may be extended by up to 12 months if application is made to the Director within a reasonable time before the termination date and the party shows good cause for any such extension.

9. Construction of New Sources(s)

The proposed emissions unit(s) shall be constructed in strict accordance with the plans and application submitted for this permit to the Director of the Ohio Environmental Protection Agency. There may be no deviation from the approved plans without the express, written approval of the Agency. Any deviations from the approved plans or the above conditions may lead to such sanctions and penalties as provided under Ohio law. Approval of these plans does not constitute an assurance that the proposed facilities will operate in compliance with all Ohio laws and regulations. Additional facilities shall be installed upon orders of the Ohio

Environmental Protection Agency if the proposed sources are inadequate or cannot meet applicable standards.

If the construction of the proposed emissions unit(s) has already begun or has been completed prior to the date the Director of the Environmental Protection Agency approves the permit application and plans, the approval does not constitute expressed or implied assurance that the proposed facility has been constructed in accordance with the approved plans. The action of beginning and/or completing construction prior to obtaining the Director's approval constitutes a violation of OAC rule 3745-31-02. Furthermore, issuance of the Permit to Install does not constitute an assurance that the proposed source will operate in compliance with all Ohio laws and regulations. Approval of the plans in any case is not to be construed as an approval of the facility as constructed and/or completed. Moreover, issuance of the Permit to Install is not to be construed as a waiver of any rights that the Ohio Environmental Protection Agency (or other persons) may have against the applicant for starting construction prior to the effective date of the permit. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed facilities prove to be inadequate or cannot meet applicable standards.

10. Public Disclosure

The facility is hereby notified that this permit, and all agency records concerning the operation of this permitted source, are subject to public disclosure in accordance with OAC rule 3745-49-03.

11. Applicability

This Permit to Install is applicable only to the emissions unit(s) identified in the Permit to Install. Separate application must be made to the Director for the installation or modification of any other emissions unit(s).

12. Best Available Technology

As specified in OAC Rule 3745-31-05, all new sources must employ Best Available Technology (BAT). Compliance with the terms and conditions of this permit will fulfill this requirement.

13. Source Operation and Operating Permit Requirements After Completion of Construction

This facility is permitted to operate each source described by this Permit to Install for a period of up to one year from the date the source commenced operation. This permission to operate is granted only if the facility complies with all requirements contained in this permit and all applicable air pollution laws, regulations, and policies. Pursuant to OAC Chapter 3745-35, the permittee shall submit a complete operating permit application within thirty (30) days after commencing operation of the emissions unit(s) covered by this permit.

Brainerd Industries Inc
PTI Application: 08-04141
Issued: 8/15/2000

Facility ID: 0857041258

14. Construction Compliance Certification

The applicant shall provide Ohio EPA with a written certification (see enclosed form) that the facility has been constructed in accordance with the Permit to Install application and the terms and conditions of the Permit to Install. The certification shall be provided to Ohio EPA upon completion of construction but prior to startup of the source.

15. Fees

The permittee shall pay fees to the Director of the Ohio EPA in accordance with ORC section 3745.11 and OAC Chapter 3745-78. The permittee shall pay all applicable Permit to Install fees within 30 days after the issuance of this Permit to Install.

B. Permit to Install Summary of Allowable Emissions

The following information summarizes the total allowable emissions, by pollutant, based on the individual allowable emissions of each air contaminant source identified in this permit.

SUMMARY (for informational purposes only)
TOTAL PERMIT TO INSTALL ALLOWABLE EMISSIONS

<u>Pollutant</u>	<u>Tons Per Year</u>
VOC	11.77

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

- 1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P033 - SuperMec silk screen press #8 for aluminum or plastic parts	OAC rule 3745-31-05 (A)(3)	0.61 pounds VOC/hour and 14.64 pounds VOC/day, excluding cleanup.
		2.94 TPY VOC, including cleanup.
	OAC rule 3745-21-07 (G)(2)	The emission limitations specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05 (A)(3).

2. Additional Terms and Conditions

- 2.a The 0.61 lb/hour and 14.64 lbs/day VOC limits for emissions unit P033 have been established for PTI purposes to reflect the potential to emit for this emissions unit. Therefore, it is not necessary to establish record keeping and/or reporting requirements to ensure compliance with these limits.

B. Operational Restrictions

NONE

C. Monitoring and/or Recordkeeping Requirements

- 1. The permittee shall collect and record the following information each month for(emissions unit P033) for

the purpose of determining annual VOC emissions:

- a. the name and identification of each ink and cleanup material employed.
 - b. the VOC content of each ink and cleanup material, in pounds per gallon;
 - c. The number of gallons of each ink and cleanup material employed;
 - d. The total VOC emissions from all inks and cleanup materials employed, in pounds or tons; and,
 - e. The total VOC emissions from all inks and cleanup materials for each emissions unit
2. The permit to install for this emissions unit (P033) was evaluated based on the actual materials (typically coatings and cleanup materials) and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant(s):

Pollutant: aliphatic dibasic acid esters

TLV (mg/m³): 10 mg/m³

Maximum Hourly Emission Rate (lbs/hr): 0.49 lbs/hr

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m³): 24.82 ug/m³

MAGLC (ug/m³): 240 ug/m³

Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

- a. changes in the composition of the materials used (typically for coatings or cleanup materials), or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value previously modeled;
- b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and
- c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01(VV)(1)(a)(ii), and a modification of the existing permit to install will not be required. If the change(s) is (are) defined as a modification under other provisions of the modification definition (other than (VV)(1)(a)(ii)), then the permittee shall obtain a final permit to install prior to the change.

The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy:"

- a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
- b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and
- c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

D. Reporting Requirements

1. The permittee shall submit annual reports to the Director (the appropriate Ohio EPA District Office or local air agency) which specify the total VOC emissions, in tons, the total coating usage, in gallons, and the total cleanup material usage, in gallons. These reports shall be submitted by January 31 of each year and shall cover the previous calendar year.

Brainerd Industries Inc
PTI Application: 08 04141
Issued

Facility ID: 0857041258

Emissions Unit ID: **P033**

E. Testing Requirements

Compliance with the emission limitation(s) in Section A.I. of these terms and conditions shall be determined in accordance with the following method(s):

a. Emission Limitation

0.61 lb/hour VOC, excluding cleanup

Applicable Compliance Method

Compliance shall be determined by multiplying the maximum hourly ink usage by the maximum allowable VOC content of all inks employed.

$$(4.9 \text{ lbs VOC/gallon}) (0.125 \text{ gallon/hour}) = 0.61 \text{ lbs VOC/hour}$$

b. Emission Limitation

14.64 lbs. VOC/day, excluding cleanup

Applicable Compliance Method

The 14.64 lbs. VOC/day limit was developed by multiplying the hourly allowable emission rate of 0.61 lb./hour by the maximum daily operating schedule of 24 hours/day.

c. Emission Limitation

2.94 TPY VOC, including cleanup

Applicable Compliance Method

Compliance shall be based upon record keeping as specified in C.1. and shall be the summation of the daily controlled organic emissions for the calendar year and divided by 2000 lbs/ton.

F. Miscellaneous Requirements

NONE

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P034 - SuperMec silk screen press #9 for plastic or aluminum parts	OAC rule 3745-31-05	0.61 pounds VOC/hour and 14.64 pounds VOC/day, excluding cleanup. 2.94 TPY VOC, including cleanup.
	OAC rule 3745-21-07 (G)(2)	The emission limitations specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05 (A)(3)

2. Additional Terms and Conditions

- 2.a The 0.61 lb/hour and 14.64 lbs/day VOC limits for emissions unit P034 have been established for PTI purposes to reflect the potential to emit for this emissions unit. Therefore, it is not necessary to establish record keeping and/or reporting requirements to ensure compliance with these limits.

B. Operational Restrictions

NONE

C. Monitoring and/or Recordkeeping Requirements

1. The permittee shall collect and record the following information each month for (emissions unit P034) for the purpose of determining annual VOC emissions:
 - a. the name and identification of each ink and cleanup material employed.
 - b. the VOC content of each ink and cleanup material, in pounds per gallon;
 - b. The number of gallons of each ink and cleanup material employed;
 - c. The total VOC emissions from all inks and cleanup materials employed, in pounds or tons; and,
 - d. The total VOC emissions from all inks and cleanup materials for each emissions unit
2. The permit to install for this emissions unit (P034) was evaluated based on the actual materials (typically coatings and cleanup materials) and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant(s):

Pollutant: aliphatic dibasic acid esters

TLV (mg/m³): 10 mg/m³

Maximum Hourly Emission Rate (lbs/hr): 0.49 lbs/hr

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m³): 24.82 ug/m³

MAGLC (ug/m³): 240 ug/m³

Physical changes to or changes in the method of operation of the emissions unit after its

installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

- a. changes in the composition of the materials used (typically for coatings or cleanup materials), or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value previously modeled;
- b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and
- c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01(VV)(1)(a)(ii), and a modification of the existing permit to install will not be required. If the change(s) is (are) defined as a modification under other provisions of the modification definition (other than (VV)(1)(a)(ii)), then the permittee shall obtain a final permit to install prior to the change.

The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy:"

- a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
- b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and
- c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

D. Reporting Requirements

Brainerd Industries Inc
PTI Application: 08-04141
Issued

Facility ID: 0857041258

Emissions Unit ID: **P034**

1. The permittee shall submit annual reports to the Director (the appropriate Ohio EPA District Office or local air agency) which specify the total VOC emissions, in tons, the total coating usage, in gallons, and the total cleanup material usage, in gallons. These reports shall be submitted by January 31 of each year and shall cover the previous calendar year.

E. Testing Requirements

Compliance with the emission limitation(s) in Section A.I. of these terms and conditions shall be determined in accordance with the following method(s):

b. Emission Limitation

0.61 lb/hour VOC, excluding cleanup

Applicable Compliance Method

Compliance shall be determined by multiplying the maximum hourly ink usage by the maximum allowable VOC content of all inks employed.

$(4.9 \text{ lbs VOC/gallon}) (0.125 \text{ gallon/hour}) = 0.61 \text{ lbs VOC/hour}$

c. Emission Limitation

14.64 lbs. VOC/day, excluding cleanup

Applicable Compliance Method

The 14.64 lbs. VOC/day limit was developed by multiplying the hourly allowable emission rate of 0.61 lb./hour by the maximum daily operating schedule of 24 hours/day.

c. Emission Limitation

2.94 TPY VOC, including cleanup

Applicable Compliance Method

Compliance shall be based upon record keeping as specified in C.1. and shall be the summation of the daily controlled organic emissions for the calendar year and divided by 2000 lbs/ton.

F. Miscellaneous Requirements

NONE

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

- 1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P035 - SuperMec silk screen press #10 for plastic or aluminum parts	OAC rule 3745-31-05	0.61 pounds VOC/hour and 14.64 pounds VOC/day, excluding cleanup.
	OAC rule 3745-21-07 (G)(2)	2.94 TPY VOC, including cleanup.
		The emission limitations specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05 (A)(3)

2. Additional Terms and Conditions

- 2.a The 0.61 lb/hour and 14.64 lbs/day VOC limits for emissions unit P035 have been established for PTI purposes to reflect the potential to emit for this emissions unit. Therefore, it is not necessary to establish record keeping and/or reporting requirements to ensure compliance with these limits.

B. Operational Restrictions

NONE

18

Brain

PTI A

Issued: 8/15/2000

Emissions Unit ID: **P035**

C. Monitoring and/or Recordkeeping Requirements

1. The permittee shall collect and record the following information each month for (emissions unit P035) for the purpose of determining annual VOC emissions:
 - a. the name and identification of each ink and cleanup material employed.
 - b. the VOC content of each ink and cleanup material, in pounds per gallon;
 - c. The number of gallons of each ink and cleanup material employed;
 - d. The total VOC emissions from all inks and cleanup materials employed, in pounds or tons; and,
 - e. The total VOC emissions from all inks and cleanup materials for each emissions unit

2. The permit to install for this emissions unit (P035) was evaluated based on the actual materials (typically coatings and cleanup materials) and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant(s):

Pollutant: aliphatic dibasic acid esters

TLV (mg/m³): 10 mg/m³

Maximum Hourly Emission Rate (lbs/hr): 0.49 lbs/hr

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m³): 24.82 ug/m³

MAGLC (ug/m³): 240 ug/m³

Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will

Emissions Unit ID: **P035**

still be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

- a. changes in the composition of the materials used (typically for coatings or cleanup materials), or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value previously modeled;
- b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and
- c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01(VV)(1)(a)(ii), and a modification of the existing permit to install will not be required. If the change(s) is (are) defined as a modification under other provisions of the modification definition (other than (VV)(1)(a)(ii)), then the permittee shall obtain a final permit to install prior to the change.

The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy:"

- a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
- b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and
- c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

D. Reporting Requirements

1. The permittee shall submit annual reports to the Director (the appropriate Ohio EPA District Office or local air agency) which specify the total VOC emissions, in tons, the total coating usage, in gallons, and the total cleanup material usage, in gallons. These reports

shall be submitted by January 31 of each year and shall cover the previous calendar year.

E. Testing Requirements

Compliance with the emission limitation(s) in Section A.I. of these terms and conditions shall be determined in accordance with the following method(s):

b. Emission Limitation

0.61 lb/hour VOC, excluding cleanup

Applicable Compliance Method

Compliance shall be determined by multiplying the maximum hourly ink usage by the maximum allowable VOC content of all inks employed.

$(4.9 \text{ lbs VOC/gallon}) (0.125 \text{ gallon/hour}) = 0.61 \text{ lbs VOC/hour}$

c. Emission Limitation

14.64 lbs. VOC/day, excluding cleanup

Applicable Compliance Method

The 14.64 lbs. VOC/day limit was developed by multiplying the hourly allowable emission rate of 0.61 lb./hour by the maximum daily operating schedule of 24 hours/day.

c. Emission Limitation

2.94 TPY VOC, including cleanup

Applicable Compliance Method

Compliance shall be based upon record keeping as specified in C.1. and shall be the summation of the daily controlled organic emissions for the calendar year and divided by 2000 lbs/ton.

F. Miscellaneous Requirements

NONE

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P036 - SuperMec silk screen press #11 for plastic or aluminum parts	OAC rule 3745-31-05	- 0.61 pounds VOC/hour and 14.64 pounds VOC/day, excluding cleanup.
	OAC rule 3745-21-07 (G)(2)	2.94 TPY VOC, including cleanup.
		. The emission limitations specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05 (A)(3)

2. Additional Terms and Conditions

- 2.a The 0.61 lb/hour and 14.64 lbs/day VOC limits for emissions unit P036 have been established for PTI purposes to reflect the potential to emit for this emissions unit. Therefore, it is not necessary to establish record keeping and/or reporting requirements to ensure compliance with these limits.

B. Operational Restrictions

NONE

C. Monitoring and/or Recordkeeping Requirements

1. The permittee shall collect and record the following information each month for (emissions unit P036) for the purpose of determining annual VOC emissions:
 - a. the name and identification of each ink and cleanup material employed.
 - b. the VOC content of each ink and cleanup material, in pounds per gallon;
 - c. The number of gallons of each ink and cleanup material employed;
 - d. The total VOC emissions from all inks and cleanup materials employed, in pounds or tons; and,
 - b. The total VOC emissions from all inks and cleanup materials for each emissions unit
2. The permit to install for this emissions unit (P036) was evaluated based on the actual materials (typically coatings and cleanup materials) and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant(s):

Pollutant: aliphatic dibasic acid esters

TLV (mg/m³): 10 mg/m³

Maximum Hourly Emission Rate (lbs/hr): 0.49 lbs/hr

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m³): 24.82 ug/m³

MAGLC (ug/m³): 240 ug/m³

Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will

still be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

- a. changes in the composition of the materials used (typically for coatings or cleanup materials), or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value previously modeled;
- b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and
- c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01(VV)(1)(a)(ii), and a modification of the existing permit to install will not be required. If the change(s) is (are) defined as a modification under other provisions of the modification definition (other than (VV)(1)(a)(ii)), then the permittee shall obtain a final permit to install prior to the change.

The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy:"

- a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
- b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and
- c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

D. Reporting Requirements

1. The permittee shall submit annual reports to the Director (the appropriate Ohio EPA District Office or local air agency) which specify the total VOC emissions, in tons, the total coating usage,

Brainerd Industries Inc
PTI Application: 08 04141
Issued

Facility ID: 0857041258

Emissions Unit ID: **P036**

in gallons, and the total cleanup material usage, in gallons. These reports shall be submitted by January 31 of each year and shall cover the previous calendar year.

E. Testing Requirements

Compliance with the emission limitation(s) in Section A.I. of these terms and conditions shall be determined in accordance with the following method(s):

b. Emission Limitation

0.61 lb/hour VOC, excluding cleanup

Applicable Compliance Method

Compliance shall be determined by multiplying the maximum hourly ink usage by the maximum allowable VOC content of all inks employed.

$(4.9 \text{ lbs VOC/gallon}) (0.125 \text{ gallon/hour}) = 0.61 \text{ lbs VOC/hour}$

c. Emission Limitation

14.64 lbs. VOC/day, excluding cleanup

Applicable Compliance Method

The 14.64 lbs. VOC/day limit was developed by multiplying the hourly allowable emission rate of 0.61 lb./hour by the maximum daily operating schedule of 24 hours/day.

c. Emission Limitation

2.94 TPY VOC, including cleanup

Applicable Compliance Method

Compliance shall be based upon record keeping as specified in C.1. and shall be the summation of the daily controlled organic emissions for the calendar year and divided by 2000 lbs/ton.

F. Miscellaneous Requirements

NONE

NEW SOURCE REVIEW FORM B

PTI Number: 08-04141 Facility ID: 0857041258

FACILITY NAME Brainerd Industries Inc

FACILITY DESCRIPTION 4 silk screen presses to replace 8 existing CITY/TWP Davton

Emissions Unit ID: P036

SIC CODE 3449 SCC CODE 4-02-999-95 EMISSIONS UNIT ID P033

EMISSIONS UNIT DESCRIPTION SuperMec silk screen press for aluminum or plastic parts

DATE INSTALLED waiting on issuance of PTI

EMISSIONS: (Click on bubble help for Air Quality Descriptions)

Pollutants	Air Quality Description	Actual Emissions Rate		PTI Allowable	
		Short Term Rate	Tons Per Year	Short Term Rate	Tons Per Year
Particulate Matter					
PM ₁₀					
Sulfur Dioxide					
Organic Compounds		9.76 lbs./day	1.22 TPY	14.64 lbs/day	2.94 TPY
Nitrogen Oxides					
Carbon Monoxide					
Lead					
Other: Air Toxics					

APPLICABLE FEDERAL RULES:

NSPS? No NESHAP? No PSD? No OFFSET POLICY? No

WHAT IS THE BAT DETERMINATION, AND WHAT IS THE BASIS FOR THE DETERMINATION?

Enter Determination Compliance with the applicable OAC rules and specified allowable mass emission rates; record keeping ; and reporting.

IS THIS SOURCE SUBJECT TO THE AIR TOXICS POLICY? YES

OPTIONAL: WHAT IS THE CAPITAL COST OF CONTROL EQUIPMENT? \$

TOXIC AIR CONTAMINANTS

Ohio EPA's air toxics policy applies to contaminants for which the American Conference of Governmental Industrial Hygienists (ACGIH) has a listed threshold limit value.

AIR TOXICS MODELING PERFORMED*? X YES NO

IDENTIFY THE AIR CONTAMINANTS: cyclohexanone, 2-butoxyethanol, dipropylene glycol methyl ether, diethylene glycol butyl ether, aliphatic dibasic acid esters

NEW SOURCE REVIEW FORM B

PTI Number: 08-04141 Facility ID: 0857041258

FACILITY NAME Brainerd Industries Inc

FACILITY DESCRIPTION 4 silk screen presses to replace 8 existing CITY/TWP Davton

Emissions Unit ID: P036

SIC CODE 3449 SCC CODE 4-02-999-95 EMISSIONS UNIT ID P034

EMISSIONS UNIT DESCRIPTION SuperMec silk screen press for plastic or aluminum parts

DATE INSTALLED waiting on issuance of PTI

EMISSIONS: (Click on bubble help for Air Quality Descriptions)

Pollutants	Air Quality Description	Actual Emissions Rate		PTI Allowable	
		Short Term Rate	Tons Per Year	Short Term Rate	Tons Per Year
Particulate Matter					
PM ₁₀					
Sulfur Dioxide					
Organic Compounds		9.76 lbs./day	1.22 TPY	14.64 lbs./day	2.94 TPY
Nitrogen Oxides					
Carbon Monoxide					
Lead					
Other: Air Toxics					

APPLICABLE FEDERAL RULES:

NSPS? No NESHAP? No PSD? No OFFSET POLICY? No

WHAT IS THE BAT DETERMINATION, AND WHAT IS THE BASIS FOR THE DETERMINATION?

Enter Determination Compliance with the applicable OAC rules and specified allowable mass emission rates; record keeping ; and reporting.

IS THIS SOURCE SUBJECT TO THE AIR TOXICS POLICY? Yes
OPTIONAL: WHAT IS THE CAPITAL COST OF CONTROL EQUIPMENT? \$

TOXIC AIR CONTAMINANTS

Ohio EPA's air toxics policy applies to contaminants for which the American Conference of Governmental Industrial Hygienists (ACGIH) has a listed threshold limit value.

AIR TOXICS MODELING PERFORMED*? X YES NO

IDENTIFY THE AIR CONTAMINANTS: cyclohexanone, 2-butoxyethanol, dipropylene glycol methyl ether, diethylene glycol butyl ether, aliphatic dibasic acid esters

NEW SC

PTI Num

FACILITY

Emissions Unit ID: **P036**

FACILITY DESCRIPTION 4 silk screen presses to replace 8 existing presses.

CITY/TWP Dayton

SIC CODE 3449

SCC CODE 4-02-999-95

EMISSIONS UNIT ID

P035

EMISSIONS UNIT DESCRIPTION SuperMec silk screen press for plastic or aluminum parts

DATE INSTALLED

Waiting on issuance of PTI

EMISSIONS: (Click on bubble help for Air Quality Descriptions)

Pollutants	Air Quality Description	Actual Emissions Rate		PTI Allowable	
		Short Term Rate	Tons Per Year	Short Term Rate	Tons Per Year
Particulate Matter					
PM ₁₀					
Sulfur Dioxide					
Organic Compounds		9.76 lbs/day	1.22 TPY	14.64 lbs./day	2.94 TPY
Nitrogen Oxides					
Carbon Monoxide					
Lead					
Other: Air Toxics					

APPLICABLE FEDERAL RULES:

NSPS? No

NESHAP? No

PSD? No

OFFSET POLICY? No

WHAT IS THE BAT DETERMINATION, AND WHAT IS THE BASIS FOR THE DETERMINATION?

Enter Determination Compliance with the applicable OAC rules and specified allowable mass emission rates; record keeping ; and reporting.

IS THIS SOURCE SUBJECT TO THE AIR TOXICS POLICY? YES

OPTIONAL: WHAT IS THE CAPITAL COST OF CONTROL EQUIPMENT? \$

TOXIC AIR CONTAMINANTS

Ohio EPA's air toxics policy applies to contaminants for which the American Conference of Governmental Industrial Hygienists (ACGIH) has a listed threshold limit value.

AIR TOXICS MODELING PERFORMED*? X YES NO

IDENTIFY THE AIR CONTAMINANTS: cyclohexanone, 2-butoxyethanol, dipropylene glycol methyl ether, diethylene glycol butyl ether, aliphatic dibasic acid esters

NEW SOURCE REVIEW FORM B

PTI Number: 08-04141

Facility ID: 0857041258

FACILITY NAME Brainerd Industries Inc

FACILITY DESCRIPTION 4 silk screen presses to replace 8 existing CITY/TWP Davton

Emissions Unit ID: **P036**

Ohio EPA Permit to Install Information Form please describe below any documentation which is being submitted with this recommendation (must be sent the same day). Electronic items should be submitted with the e-mail transmitting the PTI terms, and in software that CO can utilize. If mailing any hard copy, this section must be printed as a cover page. All items must be clearly labeled indicating the PTI name and number. Submit **hard copy items to Pam McGraner**, AQM&P, DAPC, Central Office, and **electronic files to airpti@epa.state.oh.us**

Please fill out the following. If the checkbox does not work, replace it with an 'X'

	<u>Electronic</u>	<u>Additional information File Name Convention (your PTI # plus this letter)</u>	<u>Hard Copy</u>	<u>None</u>
<u>Calculations (required)</u>	<input checked="" type="checkbox"/>	0000000c.wpd	<input type="checkbox"/>	
<u>Modeling form/results</u>	<input type="checkbox"/>	0000000s.wpd	<input checked="" type="checkbox"/>	<input type="checkbox"/>
<u>PTI Application (complete or partial)*</u>	<input type="checkbox"/>	0000000a.wpd	<input type="checkbox"/>	<input checked="" type="checkbox"/>
<u>BAT Study</u>	<input type="checkbox"/>	0000000b.wpd	<input type="checkbox"/>	<input checked="" type="checkbox"/>
<u>Other/misc.</u>	<input type="checkbox"/>	0000000t.wpd	<input type="checkbox"/>	<input checked="" type="checkbox"/>

* Mandatory for netting, PSD, nonattainment NSR, 112(g), 21-07(G)(9)(g) and 21-09(U)(2)(f) - 2 complete copies.

Please complete (see comment bubble to the left for additional instructions):

NSR Discussion

Brainerd Industries Inc. has submitted a PTI application for four (4) silk screen print ing presses at their facility in Dayton, Montgomery County. These presses will eventually replace 8 silk screen printing presses already in use at the facility. Of the eight presses currently employed, four print on plastic and four print on aluminum. The new presses will be able to print on both materials.

The applicable rule for the silk screen presses is OAC rule 3745-21-07 (G)(2). Hourly and daily limits have been established based on the potential to emit for each press. The maximum hourly ink usage multiplied by the highest OC content of all inks employed on the press determined the hourly emission rate. The daily emission rates are the hourly emission rates multiplied by a maximum operating schedule of 24 hours/day. Therefore, record keeping and reporting requirements are not necessary to ensure compliance with the hourly and daily emission limitations. The annual emission rates include both the ink and cleanup usage.

The presses, P033-P036, emit fugitive emissions from the inks used in the silk screening process. Because the majority of the product from the presses is air dried, it is assumed that 100% of the VOC's emitted at press are lost as fugitive emissions. The process does not have a vapor collection system or a stack associated with these units. The facility also does not have a building exhaust system to be used as an emission point for the VOC's. Per Bill Spires at OEPA, the emissions from these sources are to be modeled using the Screen3 Volume Source Model.

Several HAP's are contained in the inks used by these sources: hexane, dipropylene glycol methyl ether, diethylene glycol butyl ether. The cleanup solvent contains hexane, but the potential emissions do not exceed one ton per year. The other chemicals are HAP's because they contain ethylene glycol as part of their chemical infrastructure. The HAP's, hexane and the compounds containing ethylene glycol, all passed the Screen3 Volume modeling.

NEW SOURCE REVIEW FORM B

PTI Number: 08-04141

Facility ID: 0857041258

FACILITY NAME Brainerd Industries Inc

FACILITY DESCRIPTION 4 silk screen presses to replace 8 existing CITY/TWP Davton

Emissions Unit ID: **P036**

BAT is compliance with the applicable OAC rules and specified allowable mass emission rates; record keeping; and reporting.

Please complete for these type permits (For PSD/NSR Permit, place mouse over this text):

Synthetic Minor Determination and/or Netting Determination
Permit To Install ENTER PTI NUMBER HERE

- A. Source Description
- B. Facility Emissions and Attainment Status
- C. Source Emissions
- D. Conclusion

PLEASE PROVIDE ADDITIONAL NOTES OR COMMENTS AS NECESSARY:

NONE

Please complete:

SUMMARY (for informational purposes only)

TOTAL PERMIT TO INSTALL ALLOWABLE EMISSIONS

<u>Pollutant</u>	<u>Tons Per Year</u>
VOC	11.77