



State of Ohio Environmental Protection Agency

Street Address:

Lazarus Gov. Center
122 S. Front Street
Columbus, OH 43215

TELE: (614) 644-3020 FAX: (614) 644-2329

Mailing Address:

Lazarus Gov. Center
P.O. Box 1049
Columbus, OH 43216-1049

**RE: FINAL PERMIT TO INSTALL
HAMILTON COUNTY
Application No: 14-04749**

CERTIFIED MAIL

X	TOXIC REVIEW
	PSD
X	SYNTHETIC MINOR
	CEMS
	MACT
	NSPS
	NESHAPS
	NETTING
	MAJOR NON-ATTAINMENT
X	MODELING SUBMITTED
	GASOLINE DISPENSING FACILITY

DATE: February 16, 2000

Schmitt Marble, Inc.
Carl Ahrens
100 Commerce Boulevard
Loveland, OH 45140

Enclosed please find an Ohio EPA Permit to Install which will allow you to install the described source(s) in a manner indicated in the permit. Because this permit contains several conditions and restrictions, I urge you to read it carefully.

The Ohio EPA is urging companies to investigate pollution prevention and energy conservation. Not only will this reduce pollution and energy consumption, buy it can also save you money. If you would like to learn ways you can save money while protecting the environment, please contact our Office of Pollution Prevention at (614) 644-3469.

You are hereby notified that this action by the Director is final and may be appealed to the Ohio Environmental Review Appeals Commission pursuant to Chapter 3745.04 of the Ohio Revised Code. The appeal must be in writing and set forth the action complained of and the grounds upon which the appeal is based. It must be filed within thirty (30) days after the notice of the Directors action. A copy of the appeal must be served on the Director of the Ohio Environmental Protection Agency within three (3) days of filing with the Commission. An appeal may be filed with the Environmental Review Appeals Commission at the following address:

Environmental Review Appeals Commission
236 East Town Street, Room 300
Columbus, Ohio 43215

Very truly yours,

Thomas G. Rigo, Manager
Field Operations and Permit Section
Division of Air Pollution Control

cc: USEPA
HAMILTON COUNTY DEPT. OF ENV SERVICES



Permit To Install

Issue Date: February 16, 2000

Terms and Conditions

Effective Date: February 16, 2000

FINAL PERMIT TO INSTALL 14-04749

Application Number: 14-04749

APS Premise Number: 1431273332

Permit Fee: **\$400**

Name of Facility: Schmitt Marble, Inc.

Person to Contact: Carl Ahrens

Address: 100 Commerce Boulevard
Loveland, OH 45140

Location of proposed air contaminant source(s) [emissions unit(s)]:

**100 Commerce Boulevard
Loveland, Ohio**

Description of proposed emissions unit(s):

2 GEL COAT SPRAY BOOTHS.

The above named entity is hereby granted a Permit to Install for the above described emissions unit(s) pursuant to Chapter 3745-31 of the Ohio Administrative Code. Issuance of this permit does not constitute expressed or implied approval or agreement that, if constructed or modified in accordance with the plans included in the application, the above described emissions unit(s) of environmental pollutants will operate in compliance with applicable State and Federal laws and regulations, and does not constitute expressed or implied assurance that if constructed or modified in accordance with those plans and specifications, the above described emissions unit(s) of pollutants will be granted the necessary permits to operate (air) or NPDES permits as applicable.

This permit is granted subject to the conditions attached hereto.

Ohio Environmental Protection Agency

Director

Part I - GENERAL TERMS AND CONDITIONS

A. Permit to Install General Terms and Conditions

1. Compliance Requirements

The emissions unit(s) identified in this Permit to Install shall remain in full compliance with all applicable State laws and regulations and the terms and conditions of this permit.

2. Reporting Requirements Related to Monitoring and Recordkeeping Requirements

The permittee shall submit required reports in the following manner:

- a. Reports of any required monitoring and/or recordkeeping information shall be submitted to the appropriate Ohio EPA District Office or local air agency.
- b. Except as otherwise may be provided in the terms and conditions for a specific emissions unit, quarterly written reports of (a) any deviations (excursions) from emission limitations, operational restrictions, and control device operating parameter limitations that have been detected by the testing, monitoring, and recordkeeping requirements specified in this permit, (b) the probable cause of such deviations, and (c) any corrective actions or preventive measures which have been or will be taken, shall be submitted to the appropriate Ohio EPA District Office or local air agency. If no deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted quarterly, i.e., by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters. (These quarterly reports shall exclude deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06.)

3. Records Retention Requirements

Each record of any monitoring data, testing data, and support information required pursuant to this permit shall be retained for a period of five years from the date the record was created. Support information shall include, but not be limited to, all calibration and maintenance records and all original strip-chart recordings for continuous monitoring instrumentation, and copies of all reports required by this permit. Such records may be maintained in computerized form.

4. Inspections and Information Requests

The Director of the Ohio EPA, or an authorized representative of the Director, may, subject to the safety requirements of the permittee and without undue delay, enter upon the premises of this source at any reasonable time for purposes of making inspections, conducting tests, examining records or reports pertaining to any emission of air contaminants, and determining compliance with any applicable State air pollution laws and regulations and the terms and conditions of this permit. The permittee shall furnish to the Director of the Ohio EPA, or an authorized representative of the

Director, upon receipt of a written request and within a reasonable time, any information that may be requested to determine whether cause exists for modifying, reopening or revoking this permit or to determine compliance with this permit. Upon verbal or written request, the permittee shall also furnish to the Director of the Ohio EPA, or an authorized representative of the Director, copies of records required to be kept by this permit.

5. Scheduled Maintenance/Malfunction Reporting

Any scheduled maintenance of air pollution control equipment shall be performed in accordance with paragraph (A) of OAC rule 3745-15-06. The malfunction of any emissions units or any associated air pollution control system(s) shall be reported to the appropriate Ohio EPA District Office or local air agency in accordance with paragraph (B) of OAC rule 3745-15-06. Except as provided in that rule, any scheduled maintenance or malfunction necessitating the shutdown or bypassing of any air pollution control system(s) shall be accompanied by the shutdown of the emissions unit(s) that is (are) served by such control system(s).

6. Permit Transfers

Any transferee of this permit shall assume the responsibilities of the prior permit holder. The appropriate Ohio EPA District Office or local air agency must be notified in writing of any transfer of this permit.

7. Air Pollution Nuisance

The air contaminants emitted by the emissions units covered by this permit shall not cause a public nuisance, in violation of OAC rule 3745-15-07.

8. Termination of Permit to Install

This Permit to Install shall terminate within eighteen months of the effective date of the Permit to Install if the owner or operator has not undertaken a continuing program of installation or modification or has not entered into a binding contractual obligation to undertake and complete within a reasonable time a continuing program of installation or modification. This deadline may be extended by up to 12 months if application is made to the Director within a reasonable time before the termination date and the party shows good cause for any such extension.

9. Construction of New Sources(s)

The proposed emissions unit(s) shall be constructed in strict accordance with the plans and application submitted for this permit to the Director of the Ohio Environmental Protection Agency. There may be no deviation from the approved plans without the express, written approval of the Agency. Any deviations from the approved plans or the above conditions may lead to such sanctions and penalties as provided under Ohio law. Approval of these plans does not constitute an assurance that the proposed facilities will operate in compliance with all Ohio laws and regulations. Additional

facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed sources are inadequate or cannot meet applicable standards.

If the construction of the proposed emissions unit(s) has already begun or has been completed prior to the date the Director of the Environmental Protection Agency approves the permit application and plans, the approval does not constitute expressed or implied assurance that the proposed facility has been constructed in accordance with the approved plans. The action of beginning and/or completing construction prior to obtaining the Director's approval constitutes a violation of OAC rule 3745-31-02. Furthermore, issuance of the Permit to Install does not constitute an assurance that the proposed source will operate in compliance with all Ohio laws and regulations. Approval of the plans in any case is not to be construed as an approval of the facility as constructed and/or completed. Moreover, issuance of the Permit to Install is not to be construed as a waiver of any rights that the Ohio Environmental Protection Agency (or other persons) may have against the applicant for starting construction prior to the effective date of the permit. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed facilities prove to be inadequate or cannot meet applicable standards.

10. Public Disclosure

The facility is hereby notified that this permit, and all agency records concerning the operation of this permitted source, are subject to public disclosure in accordance with OAC rule 3745-49-03.

11. Applicability

This Permit to Install is applicable only to the emissions unit(s) identified in the Permit to Install. Separate application must be made to the Director for the installation or modification of any other emissions unit(s).

12. Best Available Technology

As specified in OAC Rule 3745-31-05, all new sources must employ Best Available Technology (BAT). Compliance with the terms and conditions of this permit will fulfill this requirement.

13. Source Operation and Operating Permit Requirements After Completion of Construction

This facility is permitted to operate each source described by this Permit to Install for a period of up to one year from the date the source commenced operation. This permission to operate is granted only if the facility complies with all requirements contained in this permit and all applicable air pollution laws, regulations, and policies. Pursuant to OAC Chapter 3745-35, the permittee shall submit a complete operating permit application within thirty (30) days after commencing operation of the emissions unit(s) covered by this permit.

14. Construction Compliance Certification

The applicant shall provide Ohio EPA with a written certification (see enclosed form) that the facility has been constructed in accordance with the Permit to Install application and the terms and conditions of the Permit to Install. The certification shall be provided to Ohio EPA upon completion of construction but prior to startup of the source.

15. Fees

The permittee shall pay fees to the Director of the Ohio EPA in accordance with ORC section 3745.11 and OAC Chapter 3745-78. The permittee shall pay all applicable Permit to Install fees within 30 days after the issuance of this Permit to Install.

B. Permit to Install Summary of Allowable Emissions

The following information summarizes the total allowable emissions, by pollutant, based on the individual allowable emissions of each air contaminant source identified in this permit.

**SUMMARY (for informational purposes only)
TOTAL PERMIT TO INSTALL ALLOWABLE EMISSIONS**

<u>Pollutant</u>	<u>Tons Per Year</u>
OC	8.6

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>A p p l i c a b l e E m i s s i o n s Limitations/Control Measures</u>
Gel Coat Spray Booth A	OAC rule 3745-31-05(A)(3)	8.0 lbs/hr OC from coatings 40 lbs/day OC from coatings 3.7 TPY OC from coatings 3.27 lbs/day OC from cleanup 0.60 TPY OC from cleanup
	OAC rule 3745-31-05(D)	See term A.2.2.a.
	OAC rule 3745-15-07	See Part I, Term A.7
	OAC rule 3745-21-07(G)	Same as OAC rule 3745-31-05.

2. Additional Terms and Conditions

2.a Hazardous Air Pollutants

The total allowable emissions of Hazardous Air Pollutants (HAPs), as identified in Section 112(b) of Title III of the Clean Air Act, from this facility shall not exceed 9.9 TPY for any single HAP and 24.9 TPY for any combination of HAPs. Compliance with the above limitations shall be based on a rolling, 12-month summation.

The facility has existing records to show compliance for the first year.

- 2.b** Compliance with OAC rule 3745-31-05 shall be demonstrated by the resin usage limits, cleanup material usage limits, OC emission limitations and compliance with the Air Toxics Policy.

B. Operational Restrictions

1. The amount of cleanup material used in emissions unit R001 shall not exceed 0.5 gallons/day and 182.5 gallons/year.
2. The amount of gel coat used in emissions unit R001 shall not exceed 3.1 gallons/hour, 15.49 gallons/day and 3040 gallons/year. The gallons/year limit is based upon a rolling, 12-month summation.
3. The styrene content of the gel coat used in emissions unit R001 shall not exceed 48% by weight.
4. The permittee shall employ nonphotochemically reactive cleanup materials in emissions unit R001.
5. The permittee shall employ cleanup materials in emissions unit R001 which have a maximum density of 6.54 pounds of OC per gallon, as applied.
6. Each emissions unit will be operated and maintained in accordance with manufacturer's recommendations. Spray booth exhaust filters shall be maintained (changed or cleaned) regularly per manufacturer's recommendations in order to maintain the highest effective level of particulate emissions control. Maintenance of exhaust filters (cleaning and/or changing of filter elements) shall be recorded in an operations log maintained at this facility.

C. Monitoring and/or Recordkeeping Requirements

1. The permittee shall collect and record the following information each month for the entire facility:
 - a. The name and identification number of each coating, employed.
 - b. The individual Hazardous Air Pollutant (HAP) content for each HAP of each coating in pounds of individual HAP per gallon of coating, as applied.
 - c. The total combined HAP content of each coating in pounds of combined HAPs per gallon of coating, as applied [sum all the individual HAP contents from (b)].
 - d. The number of gallons of each coating employed.
 - e. The name and identification of each cleanup material employed.
 - f. The individual HAP content for each HAP of each cleanup material in pounds of individual HAP per gallon of cleanup material, as applied.
 - g. The total combined HAP content of each cleanup material in pounds of combined HAPs per gallon of cleanup material, as applied [(sum all the individual HAP contents from (f))].
 - h. The number of gallons of each cleanup material employed.

3. The permittee shall collect and record the following information for each change where the air toxic modeling was required pursuant to the Air Toxic Policy:
 - a. Background data that describes the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc).
 - b. A copy of the resulting computer model runs that show the results of the application of the Air Toxic Policy for the change.

D. Reporting Requirements

1. The permittee shall submit deviation (excursion) reports which include the following information for emissions unit R001:
 - a. An identification of each day during which the average hourly organic compound emissions from the coatings exceeded 8.0 pounds per hour, and the actual average hourly organic compound emissions for each such day.
 - b. An identification of each day during which the organic compound emissions from the coatings exceeded 40 pounds per day, and the actual organic compound emissions for each such day.
2. The permittee shall submit deviation (excursion) reports which identify all exceedances of the usage limitations in T&C B.1 and B.2.
3. The permittee shall submit deviation (excursion) reports which identify all exceedances of the styrene content and/or cleanup material OC content limitation in T&C B.3 and B.5.
4. The permittee shall submit annual reports which specify the total organic compound emissions from emissions unit R001 for the previous calendar year. These reports shall be submitted by January 30 of each year.
5. The permittee shall notify the Hamilton County Department of Environmental Services of any monthly record showing any deviation from the following:
 - a. The total individual HAP emissions limitation for each HAP from all coatings and cleanup materials employed, in pounds or tons per rolling, 12-month period.
 - b. The total combined HAP emissions from all coatings and cleanup materials employed, in pounds or tons per rolling, 12-month period.
6. The deviation reports shall be submitted in accordance with the reporting requirements of the General Terms and Conditions of this permit.

E. Testing Requirements

1. Compliance with the OC emission limitations for emissions unit R001 shall be demonstrated by the following:
 - a. Emission Factor = Base Emission Factor X Controlled Spray Factor.
Base Emission Factor = $[(.01036 \times \% \text{ styrene in neat resin}) - 0.195]$
Controlled Spray Factor = 0.73 if Controlled spray methods are used and 1 if not used.
 - b. #/hr OC emissions = # gel coat/hr X emission factor
 - c. #/day OC emissions = # gel coat/day X emission factor
 - d. Ton/yr OC emissions = Ton gel coat/yr* X emission factor
* Based on a rolling, 12-month summation.

The emission factors are from the Composites Fabricators Association Open Molding Emission Model, Dated 5/98.

2. Compliance with the usage restrictions in T&C B.1 and B.2 shall be demonstrated by the recordkeeping in T&C C.2.
3. Compliance with the HAP emission limitations in T&C A.2.a shall be demonstrated by the recordkeeping in T&C C.1.
4. Compliance with the styrene content limit and OC content for the cleanup materials in T&C B.3 and B.5 shall be demonstrated by the recordkeeping in T&C C.2.

F. Miscellaneous Requirements

1. This permit allows the use of materials (typically coatings and cleanup materials) specified by the permittee in the permit to install application for this emissions unit. The emission limitation(s) specified in this permit was (were) established using the Ohio EPA's "Air Toxic Policy" and is (are) based on both the materials used and the design parameters of the emissions unit's exhaust system, as specified in the application. The Ohio EPA's "Air Toxic Policy" was applied for each pollutant using the SCREEN 3.0 model and comparing the predicted 1-hour maximum ground-level concentration to the Maximum Acceptable Ground-Level Concentration (MAGLC).

The following summarizes the results of the modeling for each pollutant:

Pollutant: Styrene

TLV (ug/m3): 85,000

Maximum Hourly Emission Rate for both emissions units (lbs/hr): 16

Predicted 1 Hour Maximum Ground-Level Concentration at the Fenceline (ug/m3): 1907

Maximum Acceptable Ground-Level Concentration (MAGLC) (ug/m3): 2024

For any change to the emissions unit or its method of operation that either would require an increase in the emission limitation(s) established by this permit or would otherwise be considered a "modification" as defined in OAC rule 3745-31-01, the permittee shall obtain a final permit to install prior to the change.

2. The following terms and conditions are federally enforceable:
A.2.2.a., A.2.2.b., B.1 - 6, C. 1- 2, D. 1 - 6 and E. 1 - 4.

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S) [Continued]

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
Gel Coat Spray Booth B	OAC rule 3745-31-05(A)(3)	8.0 lbs/hr OC from coatings 40 lbs/day OC from coatings 3.7 TPY OC from coatings 3.27 lbs/day OC from cleanup 0.60 TPY OC from cleanup
	OAC rule 3745-31-05(D)	See term A.2.2.a
	OAC rule 3745-15-07	See Part I, Term A.7
	OAC rule 3745-21-07(G)	Same as OAC rule 3745-31-05.

2. Additional Terms and Conditions

2.a Hazardous Air Pollutants

The total allowable emissions of Hazardous Air Pollutants (HAPs), as identified in Section 112(b) of Title III of the Clean Air Act, from this facility shall not exceed 9.9 TPY for any single HAP and 24.9 TPY for any combination of HAPs. Compliance with the above limitations shall be based on a rolling, 12-month summation.

The facility has existing records to show compliance for the first year.

- 2.b** Compliance with OAC rule 3745-31-05 shall be demonstrated by the resin usage limits, cleanup material usage limits, OC emission limitations and compliance with the Air Toxics Policy.

B. Operational Restrictions

1. The amount of cleanup material used in emissions unit R002 shall not exceed 0.5 gallons/day and 182.5 gallons/year.

2. The amount of gel coat used in emissions unit R002 shall not exceed 3.1 gallons/hour, 15.49 gallons/day and 3040 gallons/year. The gallons/year limit is based upon a rolling, 12-month summation.
3. The styrene content of the gel coat used in emissions unit R001 shall not exceed 48% by weight.
4. The permittee shall employ nonphotochemically reactive cleanup materials in emissions unit R002.
5. The permittee shall employ cleanup materials in emissions unit R002 which have a maximum density of 6.54 pounds of OC per gallon, as applied.
6. Each emissions unit will be operated and maintained in accordance with manufacturer's recommendations. Spray booth exhaust filters shall be maintained (changed or cleaned) regularly per manufacturer's recommendations in order to maintain the highest effective level of particulate emissions control. Maintenance of exhaust filters (cleaning and/or changing of filter elements) shall be recorded in an operations log maintained at this facility.

C. Monitoring and/or Recordkeeping Requirements

1. The permittee shall collect and record the following information each month for the entire facility:
 - a. The name and identification number of each coating, as employed.
 - b. The individual Hazardous Air Pollutant (HAP) content for each HAP of each coating in pounds of individual HAP per gallon of coating, as applied.
 - c. The total combined HAP content of each coating in pounds of combined HAPs per gallon of coating, as applied [sum all the individual HAP contents from (b)].
 - d. The number of gallons of each coating employed.
 - e. The name and identification of each cleanup material employed.
 - f. The individual HAP content for each HAP of each cleanup material in pounds of individual HAP per gallon of cleanup material, as applied.
 - g. The total combined HAP content of each cleanup material in pounds of combined HAPs per gallon of cleanup material, as applied [(sum all the individual HAP contents from (f))].
 - h. The number of gallons of each cleanup material employed.
 - i. The total individual HAP emissions for each HAP from all coatings and cleanup materials employed, in pounds or tons per month [for each HAP the sum of (b) times (d) for each coating and the sum of (f) times (h) for each cleanup material].

- j. The total combined HAP emissions from all coatings and cleanup materials employed, in pounds or tons per month [the sum of (c) times (d) for each coating plus the sum of (g) times (h) for each cleanup material].
- k. The updated rolling, 12-month summation for individual HAP emissions for each HAP, in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months.
- l. The updated rolling, 12-month summation for total combined HAP emissions, in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months.

A listing of the HAPs can be found in Section 112(b) of the Clean Air Act or can be obtained by contacting your Hamilton County Department of Environmental Services contact. This information does not have to be kept on a line-by-line basis.

- 2. The permittee shall collect and record the following information for each day for emissions units R002:
 - a. The company identification for each coating (neat resin) and cleanup material employed.
 - b. The number of gallons of each coating material employed.
 - c. The percent styrene of each coating employed in each emissions unit.
 - d. The number of gallons of cleanup material employed.
 - e. The organic compound content of the cleanup material, in pounds per gallon.
 - f. The total organic compound emission rate for all coatings, in pounds per day.
 - g. The cleanup material emission rate in pounds per day.
 - h. The total number of hours the emissions unit was in operation.
 - i. The average hourly organic compound emission rate for all coatings, in pounds per hour (f/h).
 - j. Documentation on whether each cleanup material is a photochemically reactive material.

[Note: The coating information must be for the coatings as employed, including any thinning solvents added at the emissions unit. Also, the definitions of “nonphotochemically reactive” is based upon OAC rule 3745-21-01(C)(5).]

3. The permittee shall collect and record the following information for each change where the air toxic modeling was required pursuant to the Air Toxic Policy:
 - a. Background data that describes the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc).
 - b. A copy of the resulting computer model runs that show the results of the application of the Air Toxic Policy for the change.

D. Reporting Requirements

1. The permittee shall submit deviation (excursion) reports which include the following information for emissions unit R002:
 - a. An identification of each day during which the average hourly organic compound emissions from the coatings exceeded 8.0 pounds per hour, and the actual average hourly organic compound emissions for each such day.
 - b. An identification of each day during which the organic compound emissions from the coatings exceeded 40.0 pounds per day, and the actual organic compound emissions for each such day.
2. The permittee shall submit deviation (excursion) reports which identify all exceedances of the usage limitations in T&C B.1 and B.2.
3. The permittee shall submit deviation (excursion) reports which identify all exceedances of the styrene content and/or cleanup material OC content limitation in T&C B.3 and B.5.
4. The permittee shall submit annual reports which specify the total organic compound emissions from emissions unit R001 for the previous calendar year. These reports shall be submitted by January 30 of each year.
5. The permittee shall notify the Hamilton County Department of Environmental Services of any monthly record showing any deviation from the following:
 - a. The total individual HAP emissions limitation for each HAP from all coatings and cleanup materials employed, in pounds or tons per rolling, 12-month period.
 - b. The total combined HAP emissions from all coatings and cleanup materials employed, in pounds or tons per rolling, 12-month period.
6. The deviation reports shall be submitted in accordance with the reporting requirements of the General Terms and Conditions of this permit.

OAC Chapter 3745-31 requires permittees to apply for and obtain a new or modified permit to install prior to making a "modification" as defined by the OAC rule 3745-31-01.

The permittee is hereby advised that the following changes to the process may be determined to be a "modification":

- a. Changes in the composition of the materials used (typically for coatings or cleanup materials), or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value specified in the above table.
- b. Changes to the emissions unit or its exhaust parameters (e.g., increased emission rate [not including an increase in an "allowable" emission limitation specified in the terms and conditions of this permit], reduced exhaust gas flow rate, and decreased stack height).
- c. Changes in the composition of the materials used, or use of new materials, that would result in the emission of an air contaminant not previously permitted.
- d. Changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant that has a listed TLV.

The Ohio EPA will not consider any of the above-mentioned as a "modification" requiring a permit to install, if the following conditions are met:

- a. The change is not otherwise considered a "modification" under OAC Chapter 3745-31.
- b. The permittee can continue to comply with the allowable emission limitations specified in its permit to install.
- c. Prior to the change, the applicant conducts an evaluation pursuant to the Air Toxic Policy, determines that the changed emissions unit still satisfies the Air Toxic Policy, and the permittee maintains documentation that identifies the change and the results of the application of the Air Toxic Policy for the change.

For any change to the emissions unit or its method of operation that either would require an increase in the emission limitation(s) established by this permit or would otherwise be considered a "modification" as defined in OAC rule 3745-31-01, the permittee shall obtain a final permit to install prior to the change.

Schmitt Marble, Inc.

PTI Application: **14-04749**

Date: February 16, 2000

Facility ID: **1431273332**

Emissions Unit ID: **R002**

2. The following terms and conditions are federally enforceable:
A.2.2.a., A.2.2.b., B.1 - 6, C. 1- 2, D. 1 - 6 and E. 1 - 4.