



State of Ohio Environmental Protection Agency

Street Address:

Lazarus Gov. Center  
122 S. Front Street  
Columbus, OH 43215

TELE: (614) 644-3020 FAX: (614) 644-2329

Mailing Address:

Lazarus Gov. Center  
P.O. Box 1049  
Columbus, OH 43216-1049

**RE: FINAL PERMIT TO INSTALL  
CLERMONT COUNTY  
Application No: 14-04854**

**CERTIFIED MAIL**

Y	TOXIC REVIEW
	PSD
	SYNTHETIC MINOR
	CEMS
	MACT
	NSPS
	NESHAPS
	NETTING
	MAJOR NON-ATTAINMENT
	MODELING SUBMITTED
	GASOLINE DISPENSING FACILITY

**DATE: 2/2/00**

US Precision Lens  
Bryan Schroers  
4000 McMann Road  
Cincinnati, OH 45245

Enclosed please find an Ohio EPA Permit to Install which will allow you to install the described source(s) in a manner indicated in the permit. Because this permit contains several conditions and restrictions, I urge you to read it carefully.

The Ohio EPA is urging companies to investigate pollution prevention and energy conservation. Not only will this reduce pollution and energy consumption, but it can also save you money. If you would like to learn ways you can save money while protecting the environment, please contact our Office of Pollution Prevention at (614) 644-3469.

You are hereby notified that this action by the Director is final and may be appealed to the Ohio Environmental Review Appeals Commission pursuant to Chapter 3745.04 of the Ohio Revised Code. The appeal must be in writing and set forth the action complained of and the grounds upon which the appeal is based. It must be filed within thirty (30) days after the notice of the Directors action. A copy of the appeal must be served on the Director of the Ohio Environmental Protection Agency within three (3) days of filing with the Commission. An appeal may be filed with the Environmental Review Appeals Commission at the following address:

Environmental Review Appeals Commission  
236 East Town Street, Room 300  
Columbus, Ohio 43215

Very truly yours,

Thomas G. Rigo, Manager  
Field Operations and Permit Section  
Division of Air Pollution Control

cc: USEPA  
Janet Rickabaugh, Health Commissioner

HCDES

**FINAL PERMIT TO INSTALL 14-04854**

Application Number: 14-04854

APS Premise Number: 1413000327

Permit Fee: **\$800**

Name of Facility: US Precision Lens

Person to Contact: Bryan Schroers

Address: 4000 McMann Road  
Cincinnati, OH 45245

Location of proposed air contaminant source(s) [emissions unit(s)]:

**4000 McMann Road  
Cincinnati, Ohio**

Description of proposed emissions unit(s):

**4 miscellaneous nonmetal parts paint booths - modification of PTI 14-4349.**

The above named entity is hereby granted a Permit to Install for the above described emissions unit(s) pursuant to Chapter 3745-31 of the Ohio Administrative Code. Issuance of this permit does not constitute expressed or implied approval or agreement that, if constructed or modified in accordance with the plans included in the application, the above described emissions unit(s) of environmental pollutants will operate in compliance with applicable State and Federal laws and regulations, and does not constitute expressed or implied assurance that if constructed or modified in accordance with those plans and specifications, the above described emissions unit(s) of pollutants will be granted the necessary permits to operate (air) or NPDES permits as applicable.

This permit is granted subject to the conditions attached hereto.

Ohio Environmental Protection Agency

  
Director

## Part I - GENERAL TERMS AND CONDITIONS

### A. Permit to Install General Terms and Conditions

#### 1. Compliance Requirements

The emissions unit(s) identified in this Permit to Install shall remain in full compliance with all applicable State laws and regulations and the terms and conditions of this permit.

#### 2. Reporting Requirements Related to Monitoring and Recordkeeping Requirements

The permittee shall submit required reports in the following manner:

- a. Reports of any required monitoring and/or recordkeeping information shall be submitted to the appropriate Ohio EPA District Office or local air agency.
- b. Except as otherwise may be provided in the terms and conditions for a specific emissions unit, quarterly written reports of (a) any deviations (excursions) from emission limitations, operational restrictions, and control device operating parameter limitations that have been detected by the testing, monitoring, and recordkeeping requirements specified in this permit, (b) the probable cause of such deviations, and (c) any corrective actions or preventive measures which have been or will be taken, shall be submitted to the appropriate Ohio EPA District Office or local air agency. If no deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted quarterly, i.e., by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters. (These quarterly reports shall exclude deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06.)

#### 3. Records Retention Requirements

Each record of any monitoring data, testing data, and support information required pursuant to this permit shall be retained for a period of five years from the date the record was created. Support information shall include, but not be limited to, all calibration and maintenance records and all original strip-chart recordings for continuous monitoring instrumentation, and copies of all reports required by this permit. Such records may be maintained in computerized form.

#### 4. Inspections and Information Requests

The Director of the Ohio EPA, or an authorized representative of the Director, may, subject to the safety requirements of the permittee and without undue delay, enter upon the premises of this source at any reasonable time for purposes of making inspections, conducting tests, examining records or reports pertaining to any emission of air contaminants, and determining compliance with any applicable State air pollution laws and regulations and the terms and conditions of this permit. The permittee shall furnish to the Director of the Ohio EPA, or an authorized representative of the Director, upon receipt of a written request and within a reasonable time, any information that may be requested to determine whether cause exists for modifying, reopening or revoking this permit or to determine compliance with this permit. Upon verbal or written request, the permittee shall also furnish to the Director of the Ohio EPA, or an authorized representative of the Director, copies of records required to be kept by this permit.

**5. Scheduled Maintenance/Malfunction Reporting**

Any scheduled maintenance of air pollution control equipment shall be performed in accordance with paragraph (A) of OAC rule 3745-15-06. The malfunction of any emissions units or any associated air pollution control system(s) shall be reported to the appropriate Ohio EPA District Office or local air agency in accordance with paragraph (B) of OAC rule 3745-15-06. Except as provided in that rule, any scheduled maintenance or malfunction necessitating the shutdown or bypassing of any air pollution control system(s) shall be accompanied by the shutdown of the emissions unit(s) that is (are) served by such control system(s).

**6. Permit Transfers**

Any transferee of this permit shall assume the responsibilities of the prior permit holder. The appropriate Ohio EPA District Office or local air agency must be notified in writing of any transfer of this permit.

**7. Air Pollution Nuisance**

The air contaminants emitted by the emissions units covered by this permit shall not cause a public nuisance, in violation of OAC rule 3745-15-07.

**8. Termination of Permit to Install**

This Permit to Install shall terminate within eighteen months of the effective date of the Permit to Install if the owner or operator has not undertaken a continuing program of installation or modification or has not entered into a binding contractual obligation to undertake and complete within a reasonable time a continuing program of installation or modification. This deadline may be extended by up to 12 months if application is made to the Director within a reasonable time before the termination date and the party shows good cause for any such extension.

**9. Construction of New Sources(s)**

The proposed emissions unit(s) shall be constructed in strict accordance with the plans and application submitted for this permit to the Director of the Ohio Environmental Protection Agency. There may be no deviation from the approved plans without the express, written approval of the Agency. Any deviations from the approved plans or the above conditions may lead to such sanctions and penalties as provided under Ohio law. Approval of these plans does not constitute an assurance that the proposed facilities will operate in compliance with all Ohio laws and regulations. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed sources are inadequate or cannot meet applicable standards.

If the construction of the proposed emissions unit(s) has already begun or has been completed prior to the date the Director of the Environmental Protection Agency approves the permit application and plans, the approval does not constitute expressed or implied assurance that the proposed facility has been constructed in accordance with the approved plans. The action of beginning and/or completing construction prior to obtaining the Director's approval constitutes a violation of OAC rule 3745-31-02. Furthermore, issuance of the Permit to Install does not constitute an assurance that the proposed source will operate in compliance with all Ohio laws and regulations. Approval of the plans in any case is not to be construed as an approval of the facility as constructed and/or completed. Moreover, issuance of the Permit to Install is not to be construed as a waiver of any rights that the Ohio Environmental Protection Agency (or other persons) may have against the applicant

for starting construction prior to the effective date of the permit. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed facilities prove to be inadequate or cannot meet applicable standards.

**10. Public Disclosure**

The facility is hereby notified that this permit, and all agency records concerning the operation of this permitted source, are subject to public disclosure in accordance with OAC rule 3745-49-03.

**11. Applicability**

This Permit to Install is applicable only to the emissions unit(s) identified in the Permit to Install. Separate application must be made to the Director for the installation or modification of any other emissions unit(s).

**12. Best Available Technology**

As specified in OAC Rule 3745-31-05, all new sources must employ Best Available Technology (BAT). Compliance with the terms and conditions of this permit will fulfill this requirement.

**13. Source Operation and Operating Permit Requirements After Completion of Construction**

This facility is permitted to operate each source described by this Permit to Install for a period of up to one year from the date the source commenced operation. This permission to operate is granted only if the facility complies with all requirements contained in this permit and all applicable air pollution laws, regulations, and policies. Pursuant to OAC Chapter 3745-35, the permittee shall submit a complete operating permit application within thirty (30) days after commencing operation of the emissions unit(s) covered by this permit.

**14. Construction Compliance Certification**

The applicant shall provide Ohio EPA with a written certification (see enclosed form) that the facility has been constructed in accordance with the Permit to Install application and the terms and conditions of the Permit to Install. The certification shall be provided to Ohio EPA upon completion of construction but prior to startup of the source.

**15. Fees**

The permittee shall pay fees to the Director of the Ohio EPA in accordance with ORC section 3745.11 and OAC Chapter 3745-78. The permittee shall pay all applicable Permit to Install fees within 30 days after the issuance of this Permit to Install.

**B. Permit to Install Summary of Allowable Emissions**

The following information summarizes the total allowable emissions, by pollutant, based on the individual allowable emissions of each air contaminant source identified in this permit.

**SUMMARY (for informational purposes only)  
TOTAL PERMIT TO INSTALL ALLOWABLE EMISSIONS**

<u>Pollutant</u>	<u>Tons Per Year</u>
OC	18.4

---

**PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)**

**A. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
Miscellaneous non-metal parts paint spray booth	OAC rule 3745-31-05(A)(3) OAC rule 3745-15-07 OAC rule 3745-21-07 (G)	111 lbs OC/Day 4.6 TPY OC See Part I Term A.7. Exempt

**2. Additional Terms and Conditions**

- 2.a Compliance with OAC rule 3745-31-05(A)(3) shall be demonstrated by the specified mass emission rates, coating and cleanup material OC content and usage limits and compliance with the Air Toxics Policy.
- 2.b The organic compound (OC) content, as applied of each coating employed in this emissions unit shall not exceed 6.2 pounds of OC per gallon of coating, including water and exempt solvents.
- 2.c The OC content of each cleanup material employed in this emissions unit shall not exceed 6.7 pounds of OC per gallon of cleanup material.
- 2.d The daily emission limitation outlined is based upon the emission unit's Potential to Emit (PTE). Therefore, no daily records are required to demonstrate compliance with these limits.

**B. Operational Restrictions**

1. The maximum annual coating and cleanup material usage for emissions unit R001 shall not exceed 1000 gallons per year for coatings and 450 gallons per year for cleanup materials.
2. The use of photochemically reactive material as defined in OAC rule 3745-21-01(C)(5) is prohibited.

**C. Monitoring and/or Recordkeeping Requirements**

1. The permittee shall collect and record the following information for each month for this emissions unit for the purpose of determining annual OC emissions:
  - a. The company identification for each coating and cleanup material employed.

- b. The number of gallons, of each coating employed per month, including water and exempt solvents.
  - c. The number of gallons, of each cleanup material employed per month.
  - d. The OC content of each coating, in pounds per gallon including water and exempt solvents, as applied.
  - e. The OC content of each cleanup material, in pounds per gallon.
  - f. The total OC emission rate for all the coatings and cleanup materials, in tons per month. The sum of  $[(b * d) + (c * e)]/2000$ .
  - g. A record of each coating and cleanup material employed in this emissions unit, indicating whether or not the coating and/or cleanup material is photochemically reactive as defined in OAC rule 3745-21-01(C)(5).
2. The permittee shall collect and record the following information for each change where the air toxic modeling was required pursuant to the Air Toxic Policy:
- a. Background data that describes the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.).
  - b. A copy of the resulting computer model runs that show the results of the application of the Air Toxic Policy for the change.

**D. Reporting Requirements**

1. The permittee shall notify the Hamilton County Department of Environmental Services in writing (deviation report) of any monthly record showing the following for this emissions unit:
  - a. Any exceedance of the annual coating and/or cleanup material usage limitations.
  - b. Any exceedance of the coating and/or cleanup material OC content limitations.
  - c. Any exceedance of the annual OC emission rate limitation.
  - d. The use of coatings and/or cleanup materials which are photochemically reactive, as defined in OAC rule 3745-21-01 (C)(5).
2. The deviation reports shall be submitted in accordance with the reporting requirements of the General Terms and Conditions of this permit.

**E. Testing Requirements**

1. Formulation data or USEPA method 24 (for coatings) or 24A (for flexographic and rotogravure printing inks and related coatings) shall be used to determine the OC contents of the inks and coatings.
2. Compliance with the annual usage limits cited in term B.1 shall be demonstrated by the record keeping in term C.1.

**F. Miscellaneous Requirements**

1. This permit allows the use of materials (typically coatings and cleanup materials) specified by the permittee in the permit to install application for this emissions unit. To fulfill the best available technology requirements of OAC rule 3745-31-05 and to ensure compliance with OAC rule 3745-15-07 (Air Pollution Nuisances Prohibited), the emission limitation(s) specified in this permit was (were) established using the Ohio EPA's "Air Toxics Policy" and is (are) based on both the materials used and the design parameters of the emissions unit's exhaust system, as specified in the application. The Ohio EPA's "Air Toxics Policy" was applied for each pollutant using the SCREEN 3.0 model and comparing the predicted 1-hour maximum ground-level concentration to the Maximum Acceptable Ground-Level Concentration (MAGLC).

The following summarizes the results of the modeling for each pollutant:

Pollutant: 4-Methyl 2-Pentanone

TLV (ug/m3): 205,000

Maximum Hourly Emission Rate (lbs/hr): 6

Predicted 1 Hour Maximum Ground-Level Concentration (ug/m3): 281

Maximum Acceptable Ground-Level Concentration (MAGLC) (ug/m3): 4881

OAC Chapter 3745-31 requires permittees to apply for and obtain a new or modified permit to install prior to making a "modification" as defined by the OAC rule 3745-31-01. The permittee is hereby advised that the following changes to the process may be determined to be a "modification":

- a. Changes in the composition of the materials used (typically for coatings or cleanup materials), or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value specified in the above table.
- b. Changes to the emissions unit or its exhaust parameters (e.g., increased emission rate [not including an increase in an "allowable" emission limitation specified in the terms and conditions of this permit], reduced exhaust gas flow rate, and decreased stack height).
- c. Changes in the composition of the materials used, or use of new materials, that would result in the emission of an air contaminant not previously permitted.
- d. Changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant that has a listed TLV.

The Ohio EPA will not consider any of the above-mentioned as a "modification" requiring a permit to install, if the following conditions are met:

- a. The change is not otherwise considered a "modification" under OAC Chapter 3745-31.
- b. The permittee can continue to comply with the allowable emission limitations specified in its permit to install.

- c. Prior to the change, the applicant conducts an evaluation pursuant to the Air Toxic Policy, determines that the changed emissions unit still satisfies the Air Toxic Policy, and the permittee maintains documentation that identifies the change and the results of the application of the Air Toxic Policy for the change.

For any change to the emissions unit or its method of operation that either would require an increase in the emission limitation(s) established by this permit or would otherwise be considered a "modification" as defined in OAC rule 3745-31-01, the permittee shall obtain a final permit to install prior to the change.

2. The Additional Special Terms and Conditions of this Permit to Install (PTI) shall supersede the Additional Special Terms and Conditions of PTI 14-4349.

**PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S) [Continued]**

**A. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
Miscellaneous non-metal parts paint spray booth	OAC rule 3745-31-05(A)(3)	111 lbs OC/Day 4.6 TPY OC
	OAC rule 3745-15-07	See Part I Term A.7.
	OAC rule 3745-21-07 (G)	Exempt

2. **Additional Terms and Conditions**

- 2.a Compliance with OAC rule 3745-31-05(A)(3) shall be demonstrated by the specified mass emission rates, coating and cleanup material OC content and usage limits and compliance with the Air Toxics Policy.
- 2.b The organic compound (OC) content, as applied of each coating employed in this emissions unit shall not exceed 6.2 pounds of OC per gallon of coating, including water and exempt solvents.
- 2.c The OC content of each cleanup material employed in this emissions unit shall not exceed 6.7 pounds of OC per gallon of cleanup material.
- 2.d The daily emission limitation outlined is based upon the emission unit's Potential to Emit (PTE). Therefore, no daily records are required to demonstrate compliance with these limits.

**B. Operational Restrictions**

1. The maximum annual coating and cleanup material usage for emissions unit R004 shall not exceed 1000 gallons per year for coatings and 450 gallons per year for cleanup materials.
2. The use of photochemically reactive material as defined in OAC rule 3745-21-01(C)(5) is prohibited.

**C. Monitoring and/or Recordkeeping Requirements**

1. The permittee shall collect and record the following information for each month for this emissions unit for the purpose of determining annual OC emissions:

- a. The company identification for each coating and cleanup material employed.
  - b. The number of gallons, of each coating employed per month, including water and exempt solvents.
  - c. The number of gallons, of each cleanup material employed per month.
  - d. The OC content of each coating, in pounds per gallon including water and exempt solvents, as applied.
  - e. The OC content of each cleanup material, in pounds per gallon.
  - f. The total OC emission rate for all the coatings and cleanup materials, in tons per month. The sum of  $[(b * d) + (c * e)]/2000$ .
  - g. A record of each coating and cleanup material employed in this emissions unit, indicating whether or not the coating and/or cleanup material is photochemically reactive as defined in OAC rule 3745-21-01(C)(5).
2. The permittee shall collect and record the following information for each change where the air toxic modeling was required pursuant to the Air Toxic Policy:
- a. Background data that describes the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.).
  - b. A copy of the resulting computer model runs that show the results of the application of the Air Toxic Policy for the change.

#### **D. Reporting Requirements**

1. The permittee shall notify the Hamilton County Department of Environmental Services in writing (deviation reports) of any monthly record showing the following for this emissions unit:
  - a. Any exceedance of the annual coating and/or cleanup material usage limitations.
  - b. Any exceedance of the coating and/or cleanup material OC content limitations.
  - c. Any exceedance of the annual OC emission rate limitation.
  - d. The use of coatings and/or cleanup materials which are photochemically reactive, as defined in OAC rule 3745-21-01 (C)(5).
2. The deviation reports shall be submitted in accordance with the reporting requirements of the General Terms and Conditions of this permit.

**E. Testing Requirements**

1. Formulation data or USEPA method 24 (for coatings) or 24A (for flexographic and rotogravure printing inks and related coatings) shall be used to determine the OC contents of the inks and coatings.
2. Compliance with the annual usage limits cited in term B.1 shall be demonstrated by the record keeping in term C.1.

**F. Miscellaneous Requirements**

1. This permit allows the use of materials (typically coatings and cleanup materials) specified by the permittee in the permit to install application for this emissions unit. To fulfill the best available technology requirements of OAC rule 3745-31-05 and to ensure compliance with OAC rule 3745-15-07 (Air Pollution Nuisances Prohibited), the emission limitation(s) specified in this permit was (were) established using the Ohio EPA's "Air Toxics Policy" and is (are) based on both the materials used and the design parameters of the emissions unit's exhaust system, as specified in the application. The Ohio EPA's "Air Toxics Policy" was applied for each pollutant using the SCREEN 3.0 model and comparing the predicted 1-hour maximum ground-level concentration to the Maximum Acceptable Ground-Level Concentration (MAGLC).

The following summarizes the results of the modeling for each pollutant:

Pollutant: 4-Methyl 2-Pentanone

TLV (ug/m3): 205,000

Maximum Hourly Emission Rate (lbs/hr): 6

Predicted 1 Hour Maximum Ground-Level Concentration (ug/m3): 281

Maximum Acceptable Ground-Level Concentration (MAGLC) (ug/m3): 4881

OAC Chapter 3745-31 requires permittees to apply for and obtain a new or modified permit to install prior to making a "modification" as defined by the OAC rule 3745-31-01. The permittee is hereby advised that the following changes to the process may be determined to be a "modification":

- a. Changes in the composition of the materials used (typically for coatings or cleanup materials), or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value specified in the above table.
- b. Changes to the emissions unit or its exhaust parameters (e.g., increased emission rate [not including an increase in an "allowable" emission limitation specified in the terms and conditions of this permit], reduced exhaust gas flow rate, and decreased stack height).
- c. Changes in the composition of the materials used, or use of new materials, that would result in the emission of an air contaminant not previously permitted.
- d. Changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant that has a listed TLV.

The Ohio EPA will not consider any of the above-mentioned as a “modification” requiring a permit to install, if the following conditions are met:

- a. The change is not otherwise considered a “modification” under OAC Chapter 3745-31.
- b. The permittee can continue to comply with the allowable emission limitations specified in its permit to install.
- c. Prior to the change, the applicant conducts an evaluation pursuant to the Air Toxic Policy, determines that the changed emissions unit still satisfies the Air Toxic Policy, and the permittee maintains documentation that identifies the change and the results of the application of the Air Toxic Policy for the change.

For any change to the emissions unit or its method of operation that either would require an increase in the emission limitation(s) established by this permit or would otherwise be considered a "modification" as defined in OAC rule 3745-31-01, the permittee shall obtain a final permit to install prior to the change.

2. The Additional Special Terms and Conditions of this Permit to Install (PTI) shall supersede the Additional Special Terms and Conditions of PTI 14-4349.

**PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S) [Continued]**

**A. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions <u>Limitations/Control Measures</u></u>
	OAC rule 3745-31-05(A)(3)	111 lbs OC/Day 4.6 TPY OC
Miscellaneous non-metal parts paint spray booth	OAC rule 3745-15-07 OAC rule 3745-21-07 (G)	See Part I Term A.7. Exempt

2. **Additional Terms and Conditions**

- 2.a Compliance with OAC rule 3745-31-05(A)(3) shall be demonstrated by the specified mass emission rates, coating and cleanup material OC content and usage limits and compliance with the Air Toxics Policy.
- 2.b The organic compound (OC) content, as applied of each coating employed in this emissions unit shall not exceed 6.2 pounds of OC per gallon of coating, including water and exempt solvents.
- 2.c The OC content of each cleanup material employed in this emissions unit shall not exceed 6.7 pounds of OC per gallon of cleanup material.
- 2.d The daily emission limitation outlined is based upon the emission unit's Potential to Emit (PTE). Therefore, no daily records are required to demonstrate compliance with these limits.

**B. Operational Restrictions**

1. The maximum annual coating and cleanup material usage for emissions unit R007 shall not exceed 1000 gallons per year for coatings and 450 gallons per year for cleanup materials.
2. The use of photochemically reactive material as defined in OAC rule 3745-21-01(C)(5) is prohibited.

**C. Monitoring and/or Recordkeeping Requirements**

1. The permittee shall collect and record the following information for each month for this emissions unit for the purpose of determining annual OC emissions:
  - a. The company identification for each coating and cleanup material employed.

- b. The number of gallons, of each coating employed per month, including water and exempt solvents.
  - c. The number of gallons, of each cleanup material employed per month.
  - d. The OC content of each coating, in pounds per gallon including water and exempt solvents, as applied.
  - e. The OC content of each cleanup material, in pounds per gallon.
  - f. The total OC emission rate for all the coatings and cleanup materials, in tons per month. The sum of  $[(b * d) + (c * e)]/2000$ .
  - g. A record of each coating and cleanup material employed in this emissions unit, indicating whether or not the coating and/or cleanup material is photochemically reactive as defined in OAC rule 3745-21-01(C)(5).
2. The permittee shall collect and record the following information for each change where the air toxic modeling was required pursuant to the Air Toxic Policy:
- a. Background data that describes the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.).
  - b. A copy of the resulting computer model runs that show the results of the application of the Air Toxic Policy for the change.

#### **D. Reporting Requirements**

1. The permittee shall notify the Hamilton County Department of Environmental Services in writing (deviation report) of any monthly record showing the following for this emissions unit:
  - a. Any exceedance of the annual coating and/or cleanup material usage limitations.
  - b. Any exceedance of the coating and/or cleanup material OC content limitations.
  - c. Any exceedance of the annual OC emission rate limitation.
  - d. The use of coatings and/or cleanup materials which are photochemically reactive, as defined in OAC rule 3745-21-01 (C)(5).
2. The deviation reports shall be submitted in accordance with the reporting requirements of the General Terms and Conditions of this permit.

#### **E. Testing Requirements**

1. Formulation data or USEPA method 24 (for coatings) or 24A (for flexographic and rotogravure printing inks and related coatings) shall be used to determine the OC contents of the inks and coatings.
2. Compliance with the annual usage limits cited in term B.1 shall be demonstrated by the record keeping in term C.1.

**F. Miscellaneous Requirements**

1. This permit allows the use of materials (typically coatings and cleanup materials) specified by the permittee in the permit to install application for this emissions unit. To fulfill the best available technology requirements of OAC rule 3745-31-05 and to ensure compliance with OAC rule 3745-15-07 (Air Pollution Nuisances Prohibited), the emission limitation(s) specified in this permit was (were) established using the Ohio EPA's "Air Toxics Policy" and is (are) based on both the materials used and the design parameters of the emissions unit's exhaust system, as specified in the application. The Ohio EPA's "Air Toxics Policy" was applied for each pollutant using the SCREEN 3.0 model and comparing the predicted 1-hour maximum ground-level concentration to the Maximum Acceptable Ground-Level Concentration (MAGLC).

The following summarizes the results of the modeling for each pollutant:

Pollutant: 4-Methyl 2-Pentanone

TLV (ug/m3): 205,000

Maximum Hourly Emission Rate (lbs/hr): 6

Predicted 1 Hour Maximum Ground-Level Concentration (ug/m3): 281

Maximum Acceptable Ground-Level Concentration (MAGLC) (ug/m3): 4881

OAC Chapter 3745-31 requires permittees to apply for and obtain a new or modified permit to install prior to making a "modification" as defined by the OAC rule 3745-31-01. The permittee is hereby advised that the following changes to the process may be determined to be a "modification":

- a. Changes in the composition of the materials used (typically for coatings or cleanup materials), or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value specified in the above table.
- b. Changes to the emissions unit or its exhaust parameters (e.g., increased emission rate [not including an increase in an "allowable" emission limitation specified in the terms and conditions of this permit], reduced exhaust gas flow rate, and decreased stack height).
- c. Changes in the composition of the materials used, or use of new materials, that would result in the emission of an air contaminant not previously permitted.
- d. Changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant that has a listed TLV.

The Ohio EPA will not consider any of the above-mentioned as a "modification" requiring a permit to install, if the following conditions are met:

- a. The change is not otherwise considered a "modification" under OAC Chapter 3745-31.
- b. The permittee can continue to comply with the allowable emission limitations specified in its permit to install.

- c. Prior to the change, the applicant conducts an evaluation pursuant to the Air Toxic Policy, determines that the changed emissions unit still satisfies the Air Toxic Policy, and the permittee maintains documentation that identifies the change and the results of the application of the Air Toxic Policy for the change.

For any change to the emissions unit or its method of operation that either would require an increase in the emission limitation(s) established by this permit or would otherwise be considered a "modification" as defined in OAC rule 3745-31-01, the permittee shall obtain a final permit to install prior to the change.

2. The Additional Special Terms and Conditions of this Permit to Install (PTI) shall supersede the Additional Special Terms and Conditions of PTI 14-4349.

**PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S) [Continued]**

**A. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
Miscellaneous non-metal parts paint spray booth	OAC rule 3745-31-05(A)(3)	111 lbs OC/Day 4.6 TPY OC
	OAC rule 3745-15-07	See Part I Term A.7.
	OAC rule 3745-21-07(G)	Exempt

**2. Additional Terms and Conditions**

- 2.a Compliance with OAC rule 3745-31-05(A)(3) shall be demonstrated by the specified mass emission rates, coating and cleanup material OC content limits and compliance with the Air Toxics Policy.
- 2.b The organic compound (OC) content, as applied of each coating employed in this emissions unit shall not exceed 6.2 pounds of OC per gallon of coating, including water and exempt solvents.
- 2.c The OC content of each cleanup material employed in this emissions unit shall not exceed 6.7 pounds of OC per gallon of cleanup material.
- 2.d The daily emission limitation outlined is based upon the emission unit's Potential to Emit (PTE). Therefore, no daily records are required to demonstrate compliance with these limits.

**B. Operational Restrictions**

1. The maximum annual coating and cleanup material usage for emissions unit R008 shall not exceed 1000 gallons per year for coatings and 450 gallons per year for cleanup materials.
2. The use of photochemically reactive material as defined in OAC rule 3745-21-01(C)(5) is prohibited.

**C. Monitoring and/or Recordkeeping Requirements**

1. The permittee shall collect and record the following information for each month for this emissions unit for the purpose of determining annual OC emissions:
  - a. The company identification for each coating and cleanup material employed.

- b. The number of gallons, of each coating employed per month, including water and exempt solvents.
  - c. The number of gallons, of each cleanup material employed per month.
  - d. The OC content of each coating, in pounds per gallon including water and exempt solvents, as applied.
  - e. The OC content of each cleanup material, in pounds per gallon.
  - f. The total OC emission rate for all the coatings and cleanup materials, in tons per month. The sum of  $[(b * d) + (c * e)]/2000$ .
  - g. A record of each coating and cleanup material employed in this emissions unit, indicating whether or not the coating and/or cleanup material is photochemically reactive as defined in OAC rule 3745-21-01(C)(5).
2. The permittee shall collect and record the following information for each change where the air toxic modeling was required pursuant to the Air Toxic Policy:
- a. Background data that describes the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.).
  - b. A copy of the resulting computer model runs that show the results of the application of the Air Toxic Policy for the change.

**D. Reporting Requirements**

1. The permittee shall notify the Hamilton County Department of Environmental Services in writing (deviation report) of any monthly record showing the following for this emissions unit:
  - a. Any exceedance of the annual coating and/or cleanup material usage limitations.
  - b. Any exceedance of the coating and/or cleanup material OC content limitations.
  - c. Any exceedance of the annual OC emission rate limitation.
  - d. The use of coatings and/or cleanup materials which are photochemically reactive, as defined in OAC rule 3745-21-01 (C)(5).
2. The deviation reports shall be submitted in accordance with the reporting requirements of the General Terms and Conditions of this permit.

**E. Testing Requirements**

1. Formulation data or USEPA method 24 (for coatings) or 24A (for flexographic and rotogravure printing inks and related coatings) shall be used to determine the OC contents of the inks and coatings.
2. Compliance with the annual usage limits cited in term B.1 shall be demonstrated by the record keeping in term C.1.

**F. Miscellaneous Requirements**

1. This permit allows the use of materials (typically coatings and cleanup materials) specified by the permittee in the permit to install application for this emissions unit. To fulfill the best available technology requirements of OAC rule 3745-31-05 and to ensure compliance with OAC rule 3745-15-07 (Air Pollution Nuisances Prohibited), the emission limitation(s) specified in this permit was (were) established using the Ohio EPA's "Air Toxics Policy" and is (are) based on both the materials used and the design parameters of the emissions unit's exhaust system, as specified in the application. The Ohio EPA's "Air Toxics Policy" was applied for each pollutant using the SCREEN 3.0 model and comparing the predicted 1-hour maximum ground-level concentration to the Maximum Acceptable Ground-Level Concentration (MAGLC).

The following summarizes the results of the modeling for each pollutant:

Pollutant: 4-Methyl 2-Pentanone

TLV (ug/m3): 205,000

Maximum Hourly Emission Rate (lbs/hr): 6

Predicted 1 Hour Maximum Ground-Level Concentration (ug/m3): 281

Maximum Acceptable Ground-Level Concentration (MAGLC) (ug/m3): 4881

OAC Chapter 3745-31 requires permittees to apply for and obtain a new or modified permit to install prior to making a "modification" as defined by the OAC rule 3745-31-01. The permittee is hereby advised that the following changes to the process may be determined to be a "modification":

- a. Changes in the composition of the materials used (typically for coatings or cleanup materials), or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value specified in the above table.
- b. Changes to the emissions unit or its exhaust parameters (e.g., increased emission rate [not including an increase in an "allowable" emission limitation specified in the terms and conditions of this permit], reduced exhaust gas flow rate, and decreased stack height).
- c. Changes in the composition of the materials used, or use of new materials, that would result in the emission of an air contaminant not previously permitted.
- d. Changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant that has a listed TLV.

The Ohio EPA will not consider any of the above-mentioned as a "modification" requiring a permit to install, if the following conditions are met:

- a. The change is not otherwise considered a "modification" under OAC Chapter 3745-31.
- b. The permittee can continue to comply with the allowable emission limitations specified in its permit to install.

- c. Prior to the change, the applicant conducts an evaluation pursuant to the Air Toxic Policy, determines that the changed emissions unit still satisfies the Air Toxic Policy, and the permittee maintains documentation that identifies the change and the results of the application of the Air Toxic Policy for the change.

For any change to the emissions unit or its method of operation that either would require an increase in the emission limitation(s) established by this permit or would otherwise be considered a "modification" as defined in OAC rule 3745-31-01, the permittee shall obtain a final permit to install prior to the change.

2. The Additional Special Terms and Conditions of this Permit to Install (PTI) shall supersede the Additional Special Terms and Conditions of PTI 14-4349.