



State of Ohio Environmental Protection Agency

Street Address:

Mailing Address:

Lazarus Gov. Center TELE: (614) 644-3020 FAX: (614) 644-2329

Lazarus Gov.  
Center

RE: **FINAL PERMIT TO INSTALL MODIFICATION** CERTIFIED MAIL  
MONTGOMERY COUNTY  
Application No: 08-03840

DATE: 5/3/2001

DMAX Ltd  
Vincent Festa  
PO Box 490158  
West Carrollton, OH 45449

Enclosed Please find a modification to the Ohio EPA Permit To Install referenced above which will modify the terms and conditions.

You are hereby notified that this action by the Director is final and may be appealed to the Ohio Environmental Review Appeals Commission pursuant to Chapter 3745.04 of the Ohio Revised Code. The appeal must be in writing and set forth the action complained of and the grounds upon which the appeal is based. It must be filed within thirty (30) days after the notice of the Directors action. A copy of the appeal must be served on the Director of the Ohio Environmental Protection Agency within three (3) days of filing with the Commission. An appeal may be filed with the Environmental Review Appeals Commission at the following address:

Environmental Review Appeals Commission  
236 East Town Street, Room 300  
Columbus, Ohio 43215

Very truly yours,

Thomas G. Rigo, Manager  
Field Operations and Permit Section  
Division of Air Pollution Control

CC: USEPA

RAPCA



**Permit To Install  
Terms and Conditions**

**Issue Date: 5/3/2001  
Effective Date: 5/3/2001**

FINAL ADMINISTRATIVE MODIFICATION OF PERMIT TO INSTALL 08-03840

Application Number: **08-03840**  
APS Premise Number: **0857103196**  
Permit Fee: **\$1400**  
Name of Facility: **DMAX Ltd**  
Person to Contact: **Vincent Festa**  
Address: **PO Box 490158  
West Carrollton, OH 45449**

Location of proposed air contaminant source(s) [emissions unit(s)]:  
**3100 Dryden Rd  
Moraine, OHIO**

Description of modification:  
**Modification to PTI 08-3840, originally issued 7/15/1998 for hot test stand 1-9; audit test stand 1-4; wet machining; dry machining; fuel injection stand; heat treat.**

The above named entity is hereby granted a modification to the permit to install described above pursuant to Chapter 3745-31 of the Ohio Administrative Code. Issuance of this modification does not constitute expressed or implied approval or agreement that, if constructed or modified in accordance with the plans included in the application, the above described source(s) of environmental pollutants will operate in compliance with applicable State and Federal laws and regulations, and does not constitute expressed or implied assurance that if constructed or modified in accordance with those plans included in the application, the above described source(s) of pollutants will be granted the necessary operating permits.

This permit is granted subject to the conditions attached hereto.

Ohio Environmental Protection Agency

  
Director

**DMAX Ltd**Facility ID: **0857103196****PTI Application: 08-03840****Modification Issued: 5/3/2001****GENERAL PERMIT CONDITIONS****TERMINATION OF PERMIT TO INSTALL**

Substantial construction for installation must take place within 18 months of the effective date of this permit. This deadline may be extended by up to 12 months if application is made to the Director within a reasonable time before the termination date and the party shows good cause for any such extension.

**NOTICE OF INSPECTION**

The Director of the Ohio Environmental Protection Agency, or his authorized representatives, may enter upon the premises of the above-named applicant during construction and operation at any reasonable time for the purpose of making inspections, conducting tests, or to examine records or reports pertaining to the construction, modification or installation of the source(s) of environmental pollutants identified within this permit.

**CONSTRUCTION OF NEW SOURCES**

The proposed emissions unit(s) shall be constructed in strict accordance with the plans and application submitted for this permit to the Director of the Ohio Environmental Protection Agency. There may be no deviation from the approved plans without the express, written approval of the Agency. Any deviations from the approved plans or the above conditions may lead to such sanctions and penalties as provided under Ohio law. Approval of these plans does not constitute an assurance that the proposed facilities will operate in compliance with all Ohio laws and regulations. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed sources cannot meet the requirements of this permit or cannot meet applicable standards.

If the construction of the proposed emissions unit(s) has already begun or has been completed prior to the date the Director of the Environmental Protection Agency approves the permit application and plans, the approval does not constitute expressed or implied assurance that the proposed facility has been constructed in accordance with the approved plans. The action of beginning and/or completing construction prior to obtaining the Director's approval constitutes a violation of OAC rule 3745-31-02. Furthermore, issuance of the Permit to Install does not constitute an assurance that the proposed source will operate in compliance with all Ohio laws and regulations. Approval of the plans in any case is not to be construed as an approval of the facility as constructed and/or completed. Moreover, issuance of the Permit to Install is not to be construed as a waiver of any rights that the Ohio Environmental Protection Agency (or other persons) may have against the applicant for starting construction prior to the effective date of the permit. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed facilities cannot meet the requirements of this permit or cannot meet applicable standards.

**PERMIT TO INSTALL FEE**

In accordance with Ohio Revised Code 3745.11, the specified Permit to Install fee must be remitted within 30 days of the effective date of this permit to install.

**DMAX Ltd**

**PTI Application: 08-03840**

**Modification Issued: 5/3/2001**

Facility ID: **0857103196**

### **PUBLIC DISCLOSURE**

The facility is hereby notified that this permit, and all agency records concerning the operation of this permitted source, are subject to public disclosure in accordance with OAC Rule 3745-49-03.

### **APPLICABILITY**

This Permit to Install is applicable only to the contaminant sources identified. Separate application must be made to the Director for the installation or modification of any other contaminant sources.

### **BEST AVAILABLE TECHNOLOGY**

As specified in OAC Rule 3745-31-05, all new sources must employ Best Available Technology (BAT). Compliance with the terms and conditions of this permit will fulfill this requirement.

### **SOURCE OPERATION AND OPERATING PERMIT REQUIREMENTS AFTER COMPLETION OF CONSTRUCTION**

If the permittee is required to apply for a Title V permit pursuant to OAC Chapter 3745-77, the permittee shall submit a complete Title V permit application or a complete Title V permit modification application within twelve (12) months after commencing operation of the emissions units covered by this permit. However, if the proposed new or modified source(s) would be prohibited by the terms and conditions of an existing Title V permit, a Title V permit modification must be obtained before the operation of such new or modified source(s) pursuant to OAC rule 3745-77-04(D) and OAC rule 3745-77-08(C)(3)(d).

If the permittee is required to apply for permit(s) pursuant to OAC Chapter 3745-35, the source(s) identified in this Permit To Install is (are) permitted to operate for a period of up to one year from the date the source(s) commenced operation. Permission to operate is granted only if the facility complies with all requirements contained in this permit and all applicable air pollution laws, regulations, and policies. Pursuant to OAC Chapter 3745-35, the permittee shall submit a complete operating permit application within thirty (30) days after commencing operation of the source(s) covered by this permit.

5

**DMAX Ltd**

**PTI Application: 08-03840**

**Modification Issued: 5/3/2001**

Facility ID: **0857103196**

**DMAX Ltd**  
**PTI Application: 08-03840**  
**Modification Issued: 5/3/2001**

Facility ID: **0857103196**

<u>Ohio EPA Source Number</u>	<u>Source Identification Number</u>	<u>BAT Determination</u>	<u>Applicable Federal &amp; OAC Rules</u>	<u>Permit Allowable Mass Emissions and/or Control/Usage Requirements</u>
-------------------------------	-------------------------------------	--------------------------	---	--

AIR EMISSION SUMMARY

The air contaminant emissions units listed below comprise the Permit to Install for **DMAX Ltd** located in **Montgomery** County. The emissions units listed below shall not exceed the emission limits/control requirements contained in the table. This condition in no way limits the applicability of any other state or federal regulations. Additionally, this condition does not limit the applicability of additional special terms and conditions of this permit.

Ohio EPA Source Number

P004  
Cont'd

P001

P001  
Cont'd

P002

P003

P004

**DMAX Ltd**  
**PTI Application: 08-03840**  
**Modification Issued: 5/3/2001**

Facility ID: **0857103196**

<u>Ohio EPA Source Number</u>	<u>Source Identification Number</u>	<u>BAT Determination</u>	<u>Applicable Federal &amp; OAC Rules</u>	<u>Permit Allowable Mass Emissions and/or Control/Usage Requirements</u>
			P008	
		P007		
P005	P006			
P005 Cont'd				
	P006 Cont'd			
		P007 Cont'd		
			P008 Cont'd	
				P009 Cont'd
				P010
			P009	

**DMAX Ltd**  
**PTI Application: 08-03840**  
**Modification Issued: 5/3/2001**

Facility ID: **0857103196**

<u>Ohio EPA Source Number</u>	<u>Source Identification Number</u>	<u>BAT Determination</u>	<u>Applicable Federal &amp; OAC Rules</u>	<u>Permit Allowable Mass Emissions and/or Control/Usage Requirements</u>
---	---	------------------------------	---	--

P013  
Cont'd

P014  
Cont'd

P015

P014

P013

P012

P011

P012  
Cont'd

**DMAX Ltd**  
**PTI Application: 08-03840**  
**Modification Issued: 5/3/2001**

Facility ID: **0857103196**

<u>Ohio EPA Source Number</u>	<u>Source Identification Number</u>	<u>BAT Determination</u>	<u>Applicable Federal &amp; OAC Rules</u>	<u>Permit Allowable Mass Emissions and/or Control/Usage Requirements</u>
P016	Source Identification <u>Description</u>			
	Diesel engine hot test stand no. 1	Diesel engine hot test stand no. 2	Diesel engine hot test stand no. 3	Diesel engine hot test stand no. 4

P016  
Cont'd

P017

**DMAX Ltd**

Facility ID: **0857103196**

**PTI Application: 08-03840**

**Modification Issued: 5/3/2001**

<u>Ohio EPA Source Number</u>	<u>Source Identification Number</u>	<u>BAT Determination</u>	<u>Applicable Federal &amp; OAC Rules</u>	<u>Permit Allowable Mass Emissions and/or Control/Usage Requirements</u>
Diesel engine hot test stand no. 5	Diesel engine hot test stand no. 6	Diesel engine hot test stand no. 7	Diesel engine hot test stand no. 8	Diesel engine hot test stand no. 9

DMAX Ltd

Facility ID: 0857103196

PTI Application: 08-03840

Modification Issued: 5/3/2001

<u>Ohio EPA Source Number</u>	<u>Source Identification Number</u>	<u>BAT Determination</u>	<u>Applicable Federal &amp; OAC Rules</u>	<u>Permit Allowable Mass Emissions and/or Control/Usage Requirements</u>
	Diesel engine audit test stand no. 2			
Diesel engine audit test stand no. 1				
				Dry machining operations
			Wet machining operations	
	Diesel engine audit test stand no. 4			
Diesel engine audit test stand no. 3				Electronic fuel injection calibration stand

**DMAX Ltd**

**PTI Application: 08-03840**

**Modification Issued: 5/3/2001**

Facility ID: **0857103196**

<u>Ohio EPA Source Number</u>	<u>Source Identification Number</u>	<u>BAT Determination</u>	<u>Applicable Federal &amp; OAC Rules</u>	<u>Permit Allowable Mass Emissions and/or Control/Usage Requirements</u>
---	---	------------------------------	---	--

BAT  
Determination

Heat treat

\*

\*

\*

\*

**DMAX Ltd**

**PTI Application: 08-03840**

**Modification Issued: 5/3/2001**

Facility ID: **0857103196**

<u>Ohio EPA Source Number</u>	<u>Source Identification Number</u>	<u>BAT Determination</u>	<u>Applicable Federal &amp; OAC Rules</u>	<u>Permit Allowable Mass Emissions and/or Control/Usage Requirements</u>
---	---	------------------------------	---	--

\*

\*

\*

\*

**DMAX Ltd**

Facility ID: **0857103196**

**PTI Application: 08-03840**

**Modification Issued: 5/3/2001**

<u>Ohio EPA Source Number</u>	<u>Source Identification Number</u>	<u>BAT Determination</u>	<u>Applicable Federal &amp; OAC Rules</u>	<u>Permit Allowable Mass Emissions and/or Control/Usage Requirements</u>
---	---	------------------------------	---	--

\*

\*

\*

\*

\*

**DMAX Ltd**

Facility ID: **0857103196**

**PTI Application: 08-03840**

**Modification Issued: 5/3/2001**

<u>Ohio EPA Source Number</u>	<u>Source Identification Number</u>	<u>BAT Determination</u>	<u>Applicable Federal &amp; OAC Rules</u>	<u>Permit Allowable Mass Emissions and/or Control/Usage Requirements</u>
---	---	------------------------------	---	--

\* \*

Applicable Federal & 3745-17-07  
OAC Rules (A)

3745-31-05

3745-31-05

\*

\*

\*

\*

DMAX Ltd

Facility ID: 0857103196

PTI Application: 08-03840

Modification Issued: 5/3/2001

<u>Ohio EPA Source Number</u>	<u>Source Identification Number</u>	<u>BAT Determination</u>	<u>Applicable Federal &amp; OAC Rules</u>	<u>Permit Allowable Mass Emissions and/or Control/Usage Requirements</u>
3745-17-07 7 (A)	3745-17-07 (A)	3745-17-07 (A)	3745-17-07 (A)	3745-17-07 (A)
				3745-31-05
3745-31-05 5	3745-31-05	3745-31-05	3745-31-05	

**DMAX Ltd**

Facility ID: **0857103196**

**PTI Application: 08-03840**

**Modification Issued: 5/3/2001**

<u>Ohio EPA Source Number</u>	<u>Source Identification Number</u>	<u>BAT Determination</u>	<u>Applicable Federal &amp; OAC Rules</u>	<u>Permit Allowable Mass Emissions and/or Control/Usage Requirements</u>
3745-17-07 (A)	3745-31-05	3745-31-05		
3745-31-05 (A)	3745-31-05			
3745-17-07 (A)				3745-17-07 (A)
			3745-17-07 (A)	3745-31-05
		3745-17-07 (A)	3745-31-05	
	3745-17-07 (A)	3745-31-05		
3745-17-07 (A)				

**DMAX Ltd**  
**PTI Application: 08-03840**  
**Modification Issued: 5/3/2001**

Facility ID: **0857103196**

<u>Ohio EPA Source Number</u>	<u>Source Identification Number</u>	<u>BAT Determination</u>	<u>Applicable Federal &amp; OAC Rules</u>	<u>Permit Allowable Mass Emissions and/or Control/Usage Requirements</u> average.
	3745-17-07 (A)		Permit Allowable Mass Emissions and/or Control/Usage Requirements	Less stringent than the opacity limit established above for BAT.
	3745-17-11	3745-21-07 (G)	NO <sub>x</sub> : 0.57 pound/hour, 2.50 TPY	NO <sub>x</sub> : 0.57 pound/hour, 2.50 TPY
		3745-31-05	CO: 0.29 pound/hour 1.27 TPY	CO: 0.29 pound/hour 1.27 TPY
	3745-21-07 (G)		SO <sub>2</sub> : 0.13 pound/hour, 0.57 TPY	SO <sub>2</sub> : 0.13 pound/hour, 0.57 TPY
	3745-31-05		VOC: 0.03 pound/hour, 0.13 TPY	VOC: 0.03 pound/hour, 0.13 TPY
3745-17-07 (A)			PM: 0.14 pound/hour, 0.61 TPY	PM: 0.14 pound/hour, 0.61 TPY
			Annual limits are based upon a rolling 12-month summation.	Annual limits are based upon a rolling 12-month summation.
3745-31-05			The total combined emissions for P001, P002, P003, P004, P005, P006, P007, P008 and P009 are not to exceed 9.55 TPY	The total combined emissions for P001, P002, P003, P004, P005, P006, P007, P008, and P009 are not to exceed 9.55 TPY
	3745-17-07 (A)	3745-17-07 (A)	NO <sub>x</sub> ; 4.78 TPY	NO <sub>x</sub> ; 4.78 TPY
	3745-17-11		CO; 2.22 TPY	CO; 2.22 TPY
		3745-17-11 (A)(2)	S <sub>02</sub> ; 0.48 TPY	S <sub>02</sub> ; 0.48 TPY
			VOC; 2.39 TPY	VOC; 2.39 TPY
			PM; as a rolling 12 month summation.	PM; as a rolling 12 month summation.
	3745-31-05		Visible emissions shall not exceed 10 percent opacity, as a 6 minute	Visible emissions shall not exceed 10 percent opacity, as a 6 minute

**DMAX Ltd**  
**PTI Application: 08-03840**  
**Modification Issued: 5/3/2001**

Facility ID: **0857103196**

<u>Ohio EPA Source Number</u>	<u>Source Identification Number</u>	<u>BAT Determination</u>	<u>Applicable Federal &amp; OAC Rules</u>	<u>Permit Allowable Mass Emissions and/or Control/Usage Requirements</u>
average.	12-month summation.	0.57 TPY VOC: 0.03 pound/hour, 0.13 TPY	Annual limits are based upon a rolling 12-month summation.	Annual limits are based upon a rolling 12-month summation.
Less stringent than the opacity limit established above for BAT.	The total combined emissions for P001, P002, P003, P004, P005, P006, P007, P008, and P009 are not to exceed 9.55 TPY NO <sub>x</sub> ; 4.78 TPY CO; 2.22 TPY SO <sub>2</sub> ; 0.48 TPY VOC; 2.39 TPY PM; as a rolling 12 month summation.  Visible emissions shall not exceed 10 percent opacity, as a 6 minute average.  Less stringent than the opacity limit established above for BAT.	PM: 0.14 pound/hour, 0.61 TPY  Annual limits are based upon a rolling 12-month summation.  The total combined emissions for P001, P002, P003, P004, P005, P006, P007, P008, and P009 are not to exceed 9.55 TPY NO <sub>x</sub> ; 4.78 TPY CO; 2.22 TPY SO <sub>2</sub> ; 0.48 TPY VOC; 2.39 TPY PM; as a rolling 12 month summation.  Visible emissions shall not exceed 10 percent opacity, as a 6 minute average.  Less stringent than the opacity limit established above for BAT.	The total combined emissions for P001, P002, P003, P004, P005, P006, P007, P008, and P009 are not to exceed 9.55 TPY NO <sub>x</sub> ; 4.78 TPY CO; 2.22 TPY SO <sub>2</sub> ; 0.48 TPY VOC; 2.39 TPY PM; as a rolling 12 month summation.  Visible emissions shall not exceed 10 percent opacity, as a 6 minute average.  Less stringent than the opacity limit established above for BAT.	The total combined emissions for P001, P002, P003, P004, P005, P006, P007, P008, and P009 are not to exceed 9.55 TPY NO <sub>x</sub> ; 4.78 TPY CO; 2.22 TPY SO <sub>2</sub> ; 0.48 TPY VOC; 2.39 TPY PM; as a rolling 12 month summation.  Visible emissions shall not exceed 10 percent opacity, as a 6 minute average.  Less stringent than the opacity limit established above for BAT.
NO <sub>x</sub> : 0.57 pound/hour, 2.50 TPY CO: 0.29 pound/hour 1.27 TPY SO <sub>2</sub> : 0.13 pound/hour, 0.57 TPY VOC: 0.03 pound/hour, 0.13 TPY PM: 0.14 pound/hour, 0.61 TPY Annual limits are based upon a rolling	NO <sub>x</sub> : 0.57 pound/hour, 2.50 TPY CO: 0.29 pound/hour, 1.27 TPY SO <sub>2</sub> : 0.13 pound/hour, 0.57 TPY VOC: 0.03 pound/hour, 0.13 TPY PM: 0.14 pound/hour, 0.61 TPY	NO <sub>x</sub> : 0.57 pound/hour, 2.50 TPY CO: 0.29 pound/hour, 1.27 TPY SO <sub>2</sub> : 0.13 pound/hour, 0.57 TPY VOC: 0.03 pound/hour, 0.13 TPY PM: 0.14 pound/hour, 0.61 TPY	NO <sub>x</sub> : 0.57 pound/hour, 2.50 TPY CO: 0.29 pound/hour, 1.27 TPY SO <sub>2</sub> : 0.13 pound/hour, 0.57 TPY VOC: 0.03 pound/hour, 0.13 TPY PM: 0.14 pound/hour, 0.61 TPY	NO <sub>x</sub> : 0.57 pound/hour, 2.50 TPY CO: 0.29 pound/hour, 1.27 TPY SO <sub>2</sub> : 0.13 pound/hour, 0.57 TPY VOC: 0.03 pound/hour, 0.13 TPY PM: 0.14 pound/hour, 0.61 TPY Annual limits are based upon a rolling 12-month

DMAX Ltd

Facility ID: 0857103196

PTI Application: 08-03840

Modification Issued: 5/3/2001

<u>Ohio EPA Source Number</u>	<u>Source Identification Number</u>	<u>BAT Determination</u>	<u>Applicable Federal &amp; OAC Rules</u>	<u>Permit Allowable Mass Emissions and/or Control/Usage Requirements</u>
summation	Less stringent than the opacity limit established above for	Visible emissions shall not exceed 10 percent opacity, as a 6 minute average.		2.94 TPY CO: 0.88 pound/hour 1.47 TPY
The total combined emissions for P001, P002, P003, P004, P005, P006, P007, P008, and P009 are not to exceed 9.55 TPY	BAT. NO <sub>x</sub> : 0.57 pound/hour, 2.50 TPY CO: 0.29 pound/hour 1.27 TPY SO <sub>2</sub> : 0.13 pound/hour, 0.57 TPY VOC: 0.03 pound/hour, 0.13 TPY PM: 0.14 pound/hour, 0.61 TPY Annual limits are based upon a rolling 12-month summation.	Less stringent than the opacity limit established above for BAT. NO <sub>x</sub> : 0.57 pound/hour, 2.50 TPY CO: 0.29 pound/hour 1.27 TPY SO <sub>2</sub> : 0.13 pound/hour, 0.57 TPY VOC: 0.03 pound/hour, 0.13 TPY PM: 0.14 pound/hour, 0.61 TPY Annual limits are based upon a rolling 12-month summation.	NO <sub>x</sub> : 1.76 pounds/hour, 2.94 TPY CO: 0.88 pound/hour 1.47 TPY SO <sub>2</sub> : 0.41 pound/hour, 0.68 TPY VOC: 0.09 pound/hour, 0.15 TPY PM: 0.44 pound/hour, 0.73 TPY Annual limits are based upon a rolling 12-month summation. The total combined emissions for P010, P011, P012, and P013 shall not to exceed 2.94 TPY NO <sub>x</sub> ; 1.47 TPY CO; 0.68 TPY SO <sub>2</sub> ; 0.15 TPY VOC; 0.73 TPY PM; as a rolling 12 month summation.	SO <sub>2</sub> : 0.41 pound/hour, 0.68 TPY VOC: 0.09 pound/hour, 0.15 TPY PM: 0.44 pound/hour, 0.73 TPY Annual limits are based upon a rolling 12-month summation. The total combined emissions for P010, P011, P012, and P013 shall not to exceed 2.94 TPY NO <sub>x</sub> ; 1.47 TPY CO; 0.68 TPY SO <sub>2</sub> ; 0.15 TPY VOC; 0.73 TPY PM; as a rolling 12 month summation. Visible emissions shall not exceed 10 percent opacity, as a 6 minute average.
Visible emissions shall not exceed 10 percent opacity, as a 6 minute average.	NO <sub>x</sub> ; 4.78 TPY CO; 2.22 TPY SO <sub>2</sub> ; 0.48 TPY VOC; 2.39 TPY PM; as a rolling 12 month summation.	Visible emissions shall not exceed 10 percent opacity, as a 6 minute average. Less stringent than the opacity limit established above for BAT.	Less stringent than the opacity limit established above for BAT. NO <sub>x</sub> : 1.76 pounds/hour, 2.94 TPY	NO <sub>x</sub> : 1.76 pounds/hour, 2.94 TPY CO: 0.88 pound/hour 1.47 TPY SO <sub>2</sub> : 0.41 pound/hour, 0.68 TPY

DMAX Ltd

Facility ID: 0857103196

PTI Application: 08-03840

Modification Issued: 5/3/2001

<u>Ohio EPA Source Number</u>	<u>Source Identification Number</u>	<u>BAT Determination</u>	<u>Applicable Federal &amp; OAC Rules</u>	<u>Permit Allowable Mass Emissions and/or Control/Usage Requirements</u>
VOC: 0.09 pound/hour, 0.15 TPY PM: 0.44 pound/hour, 0.73 TPY Annual limits are based upon a rolling 12-month summation	Visible emissions shall not exceed 10 percent opacity, as a 6 minute average. Less stringent than the opacity limit established above for BAT.	P013 shall not exceed 2.94 TPY NO <sub>x</sub> ; 1.47 TPY CO; 0.68 TPY SO <sub>2</sub> ; 0.15 TPY VOC; 0.73 TPY PM; as a rolling 12 month summation. Visible emissions shall not exceed 10 percent opacity, as a 6 minute average. Less stringent than the opacity limit established above for BAT.	Rule limit less stringent than BAT  0.7 pound/hour PM, 2.93 TPY PM, as a rolling, 12-month summation.  Visible emissions shall not exceed 10 percent opacity as a 6 minute average.  Less stringent than the opacity limit established above for BAT.  Less stringent than the mass emissions limit established above for BAT.	1.81 TPY PM; 0.37 pound/hour NH <sub>3</sub> , 1.62 TPY NH <sub>3</sub> ; 0.05 pound/hour NO <sub>x</sub> , 0.23 TPY NO <sub>x</sub> ; 0.01 pound/hour CO, 0.05 TPY CO; as a rolling 12 month summation. Visible emissions shall not exceed 20 percent opacity, as a 6 minute average. Less stringent than the opacity limit established above for BAT. Same as the mass emission limit established above for BAT.
The total combined emissions for P010, P011, P012, and P013 shall not to exceed 2.94 TPY NO <sub>x</sub> ; 1.47 TPY CO; 0.68 TPY SO <sub>2</sub> ; 0.15 TPY VOC; 0.73 TPY PM; as a rolling 12 month summation	N <sub>0x</sub> : 1.76 pounds/hour, 2.94 TPY CO: 0.88 pound/hour 1.47 TPY SO <sub>2</sub> : 0.41 pound/hour, 0.68 TPY VOC: 0.09 pound/hour, 0.15 TPY PM: 0.44 pound/hour, 0.73 TPY Annual limits are based upon a rolling 12-month summation. The total combined emissions for P010, P011, P012 and	PM: 1.13 pounds/hour, 5.52 TPY VOC: 3.9 pounds/hour, 10.32 TPY Annual limits are based upon a rolling, 12 month summation. Visible emissions shall not exceed 10 percent opacity as a 6 minute average. Less stringent than the opacity limit established above for BAT. Less stringent than the mass emission limit established above for BAT.	Less stringent than the opacity limit established above for BAT.  Less stringent than the mass emissions limit established above for BAT.  2.8 pounds VOC/hour 7.30 TPY VOC, as a rolling, 12-month summation.  Rule limit less stringent than BAT	Less stringent than the opacity limit established above for BAT.
			0.41 pound/hour PM,	

**DMAX Ltd**Facility ID: **0857103196****PTI Application: 08-03840****Modification Issued: 5/3/2001**

<u>Ohio EPA Source Number</u>	<u>Source Identification Number</u>	<u>BAT Determination</u>	<u>Applicable Federal &amp; OAC Rules</u>	<u>Permit Allowable Mass Emissions and/or Control/Usage Requirements</u>
---	---	------------------------------	---	--

- \* BAT is compliance with applicable OAC rules and specified emission limitations; recordkeeping and reporting requirements. For emissions unit P120 BAT shall include the use of a fabric filter with an operating control efficiency of at least 90 percent. For emissions unit P119 the use of photochemically reactive materials, as defined in OAC rule 3745-21-01(C)(5), is prohibited per BAT.

**DMAX Ltd****PTI Application: 08-03840****Modification Issued: 5/3/2001**Facility ID: **0857103196**

- \*\* BAT is compliance with applicable OAC rules, specified emission limitations and the Air Toxics Policy; recordkeeping and reporting requirements. In addition, for emissions unit P122 BAT shall include the use of a thermal incinerator with an operating control efficiency of at least 80 percent.

SUMMARY  
TOTAL PERMIT TO INSTALL ALLOWABLE EMISSIONS

<u>Pollutant</u>	<u>Tons/Year</u>
VOC	18.25
NO <sub>x</sub>	12.72
PM	13.38
CO	6.30
SO <sub>2</sub>	2.90
NH <sub>3</sub>	1.62

**PERFORMANCE TEST REQUIREMENTS**

The permittee shall conduct, or have conducted, performance testing on the air contaminant source(s) in accordance with procedures approved by the Agency. Two copies of the written report describing the test procedures followed and the results of such tests shall be submitted and signed by the person responsible for the test. The Director, or an Ohio EPA representative, shall be allowed to witness the test, examine testing equipment, and require the acquisition or submission of data and information necessary to assure that the source operation and testing procedures provide a valid characterization of the emissions from the source and/or the performance of the control equipment.

- A. A completed Intent to Test form shall be submitted to the appropriate Ohio EPA District Office or Local Air Pollution Control Agency where the original permit application was filed. This notice shall be made 30 days in advance and shall specify the source operating parameters, the proposed test procedures, and the time, date, place and person(s) conducting such tests.
- B. Two copies of the test results shall be submitted within 30 days after the completion of the performance

24

**DMAX Ltd**

**PTI Application: 08-03840**

**Modification Issued: 5/3/2001**

Facility ID: **0857103196**

test.

**DMAX Ltd**  
**PTI Application: 08-03840**  
**Modification Issued: 5/3/2001**

Facility ID: **0857103196**

C. Tests shall be performed for the following source(s) and pollutant(s):

<u>Source</u>	<u>Pollutant(s)</u>
P001	CO, N0 <sub>x</sub> , SO <sub>2</sub>
P010	CO, N0 <sub>x</sub> , SO <sub>2</sub>
P014	PM
P015	PM
P017	NH <sub>3</sub> , PM

**REPORTING REQUIREMENTS**

Unless otherwise specified, reports required by the Permit to Install need only be submitted to **Regional Air Pollution Control Agency, 451 West Third Street, Dayton, OH 45422.**

**WASTE DISPOSAL**

The owner/operator shall comply with any applicable state and federal requirements governing the storage, treatment, transport and disposal of any waste material generated by the operation of the sources.

**MAINTENANCE OF EQUIPMENT**

This source and its associated air pollution control system(s) shall be maintained regularly in accordance with good engineering practices and the recommendations of the respective manufacturers in order to minimize air contaminant emissions.

**MALFUNCTION/ABATEMENT**

In accordance with OAC RULE 3745-15-06, any malfunction of the source(s) or associated air pollution control system(s) shall be reported immediately to the **Regional Air Pollution Control Agency, 451 West Third Street, Dayton, OH 45422.**

Except as provided by OAC Rule 3745-15-06(A)(3), scheduled maintenance of air pollution control equipment that requires the shutdown or bypassing of air pollution control system(s) must be accompanied by the shutdown of the associated air pollution sources.

**AIR POLLUTION NUISANCES PROHIBITED**

**DMAX Ltd**

Facility ID: **0857103196**

**PTI Application: 08-03840**

**Modification Issued: 5/3/2001**

The air contaminant source(s) identified in this permit may not cause a public nuisance in violation of OAC Rule 3745-15-07.

DMAX Ltd

PTI Application: 08-03840

Modification Issued: 5/3/2001

Facility ID: 0857103196

**NINETY DAY OPERATING PERIOD**

The facility will be permitted to operate during a 90-day period in accordance with OAC Rule 3745-35-02(C)(4)(b). The purpose of this period of operation is to fulfill the performance tests conditions used in the determination of compliance with the provisions of this Permit to Install or other applicable Ohio EPA rules.

**CONSTRUCTION COMPLIANCE CERTIFICATION**

The applicant shall provide Ohio EPA with a written certification (see enclosed form) that the facility has been constructed in accordance with the Permit to Install application and the terms and conditions of the Permit to Install. The certification shall be provided to Ohio EPA upon completion of construction but prior to startup of the source.

**ADDITIONAL SPECIAL TERMS AND CONDITIONS****A. Operational Restrictions**

1. The maximum annual production rate for this facility shall not exceed 200,000 engines, based upon a rolling, 12-month summation of monthly production records.

To ensure enforceability during the first 12 calendar months of operation following the startup of the engine plant, the permittee shall not exceed the production levels specified in the following table:

<b><u>Month(s)</u></b>	<b><u>Engine Production</u></b>
1 to 3	50,000 engines
1 to 6	100,000 engines
1 to 9	150,000 engines
1 to 12	200,000 engines

After the first 12 calendar months of operation following the startup of this facility, compliance with the annual production limitation shall be based upon a rolling, 12-month summation of the monthly production records.

2. The maximum annual engines tested by the audit test stands, emissions units **P010, P011, P012 and P013**, shall not exceed a combined total of 20,000 engines tested, based upon a rolling, 12-month summation of monthly testing records.

DMAX Ltd

PTI Application: 08-03840

Modification Issued: 5/3/2001

Facility ID: 0857103196

To ensure enforceability during the first 12 calendar months of operation following the startup of emissions units **P010, P011, P012 and P013**, the permittee shall not exceed the engine audit tests specified in the following table:

<u>Month(s)</u>	<u>Engine Audit Tests</u>
1 to 3	5,000 engines
1 to 6	10,000 engines
1 to 9	15,000 engines
1 to 12	20,000 engines

After the first 12 calendar months of operation following the startup of emissions units **P010, P011, P012 and P013**, compliance with the maximum annual engines tested limitation shall be based upon a rolling, 12-month summation of the monthly engines tested.

3. The maximum annual coolant usage employed by emissions unit **P014** shall not exceed 258,000 gallons, based upon a rolling, 12-month summation of monthly production records.

To ensure enforceability during the first 12 calendar months of operation following the startup of emissions unit **P014**, the permittee shall not exceed the coolant usage specified in the following table:

<u>Month(s)</u>	<u>Coolant Usage (gal)</u>
1 to 3	64,500
1 to 6	129,000
1 to 9	193,500
1 to 12	258,000

After the first 12 calendar months of operation following the startup of emissions unit **P014**, compliance with the annual coolant usage limitation shall be based upon a rolling, 12-month summation of the monthly coolant usage.

4. The VOC content of the coolant employed in emissions unit **P014**, Coolant System for Wet Machining, shall not exceed 0.08 pounds per gallon.
5. The use of photochemically reactive materials, as defined by OAC rule 3745-21-01(C)(5), in emissions unit P014 is prohibited.

Prior to employing any photochemically reactive materials, the permittee shall provide written notification to, and obtain approval from, the Regional Air Pollution Control Agency. Such notification shall include information sufficient to determine that the emissions associated with the

DMAX Ltd

PTI Application: 08-03840

Modification Issued: 5/3/2001

Facility ID: 0857103196

proposed change in materials will comply with the emission limits and/or control requirements as defined in OAC rule 3745-21-07(G)(2). This notification, at a minimum, shall include the company identification of the new material to be employed, the solvent composition of the material, and the maximum amount to be used, in pounds per hour.

6. The maximum annual diesel fuel usage for the diagnostic checks performed on the engines by the Fuel Injection Stands, emissions unit **P016**, shall not exceed 2,000 gallons, based upon a rolling, 12-month summation of monthly production records.

To ensure enforceability during the first 12 calendar months of operation following the startup of emissions unit **P016**, the permittee shall not exceed the diesel fuel usage specified in the following table:

<u>Month(s)</u>	<u>Fuel Injection Tests</u>
1 to 3	500 gal
1 to 6	1,000 gal
1 to 9	1,500 gal
1 to 12	2,000 gal

After the first 12 calendar months of operation following the startup of emissions unit **P016**, compliance with the annual diesel fuel usage limitation shall be based upon a rolling, 12-month summation of the monthly diesel fuel usage.

7. The pressure drop across the fabric filter shall be maintained within the range established during the most recent emission test that demonstrated that the emission unit **P015**, Dry Machining Operations, was in compliance or by the manufacturer's recommendation.
8. The average combustion temperature within the thermal incinerator, for any 3-hour block of time when the emissions unit is in operation, shall not be more than 50 degrees Fahrenheit below the average temperature during the most recent emission test that demonstrated that emissions unit **P017**, Heat Treat, was in compliance.

#### **B. Monitoring and/or Recordkeeping Requirements**

1. The permittee shall maintain monthly records of the following information:
  - a. the total number of engines produced; and,
  - b. beginning after the first 12 calendar months of operation following the issuance of this permit, the rolling, 12-month summation of the production rates.

**DMAX Ltd**

**PTI Application: 08-03840**

**Modification Issued: 5/3/2001**

Facility ID: **0857103196**

**DMAX Ltd****PTI Application: 08-03840****Modification Issued: 5/3/2001**Facility ID: **0857103196**

Also, during the first 12 calendar months of operation following the issuance of this permit, the permittee shall record the cumulative production rate of engines produced for each calendar month.

2. The permittee shall maintain monthly records of the following information for emissions units **P010, P011, P012 and P013**, Diesel Engine Audit Test Stands:
  - a. the total number of engines tested by the audit test stands; and,
  - b. beginning after the first 12 calendar months of operation following the issuance of this permit, the rolling, 12-month summation of the total number of engines tested by the audit test stands.

Also, during the first 12 calendar months of operation following the issuance of this permit, the permittee shall record the cumulative total number of engines tested by the audit test stands for each calendar month.

3. The permittee shall maintain monthly records of the following information for emissions unit **P014**, the Coolant System for Wet Machining:
  - a. the total amount, in gallons, of coolant usage;
  - b. the total VOC emissions from the coolant usage, in pounds; and,
  - c. beginning after the first 12 calendar months of operation following the issuance of this permit, the rolling, 12-month summation of the total amount, in gallons, of coolant usage.

Also, during the first 12 calendar months of operation following the issuance of this permit, the permittee shall record the cumulative total amount, in gallons, of coolant usage for each calendar month; and,

- d. the rolling, 12-month summation of the VOC emissions from the coolant usage, in tons.
4. For the dry machining operations, emissions unit **P015**:

The permittee shall properly install, operate, and maintain equipment to monitor the pressure drop across the fabric filter while the emissions unit is in operation. The monitoring equipment shall be installed, calibrated, operated, and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual(s). The permittee shall record the pressure drop across the fabric filter on a once per shift basis.

**DMAX Ltd**Facility ID: **0857103196****PTI Application: 08-03840****Modification Issued: 5/3/2001**

5. The permittee shall maintain monthly records of the following information for emissions unit **P016**, the Fuel Injection Calibration Stand:
  - a. the total amount, in gallons, of diesel fuel usage;
  - b. the total VOC emissions from the diesel fuel usage; and,
  - c. beginning after the first 12 calendar months of operation following the issuance of this permit, the rolling, 12-month summation of the total amount, in gallons, of diesel fuel usage.

Also, during the first 12 calendar months of operation following the issuance of this permit, the permittee shall record the cumulative total amount, in gallons, of diesel fuel usage for each calendar month.

- d. the rolling, 12-month summation of the VOC emissions, in tons.
6. For emissions unit **P017**, the Heat Treat, the permittee shall operate and maintain a continuous temperature monitor and recorder which measures and records the combustion temperature within the thermal incinerator when the emissions unit is in operation. Units shall be in degrees Fahrenheit. The monitoring and recording devices shall be capable of accurately measuring the desired parameter. The temperature monitor and recorder shall be installed, calibrated, operated and maintained in accordance with the manufacturer's recommendations, with any modifications deemed necessary by the permittee.

The permittee shall collect and record the following information for each day:

- a. all 3-hour blocks of time during which the average combustion temperature within the thermal incinerator, when the emissions unit was in operation, was more than 50 degrees Fahrenheit below the average temperature during the most recent emission test that demonstrated the emissions unit was in compliance; and,
  - b. a log of the downtime for the capture (collection) system, control device, and monitoring equipment, when the associated emissions unit was in operation.
7. Each record of any monitoring data, testing data, and support information required pursuant to this permit shall be retained for a period of five years from the date the record was created. Support information shall include, but not be limited to, all calibration and maintenance records and all original strip chart recordings for continuous monitoring instrumentation, and copies of all

**DMAX Ltd****PTI Application: 08-03840****Modification Issued: 5/3/2001**Facility ID: **0857103196**

reports required by this permit. Such records may be maintained in computerized form.

**C. Reporting Requirements**

1. The permittee shall submit quarterly deviation (excursion) reports that identify all periods of time during which the pressure drop across the fabric filter, for emission unit **P015**, did not comply with the allowable range as specified in Additional Special Term and Condition A.7.
2. The permittee shall submit quarterly deviation (excursion) reports which identify all 3-hour blocks of time during which the average combustion temperature within the thermal incinerator, for emissions unit **P017**, does not comply with the temperature limitation specified in Additional Special Term and Condition A.8.
3. The permittee shall submit quarterly deviation (excursion) reports which identify all exceedances of the rolling, 12-month engine production limitation, engines tested by audit test stands limitation, coolant usage limitation, coolant VOC content limitation, diesel fuel usage limitation, and for the first 12 calendar months of operation, all exceedances of the maximum allowable cumulative production levels, engines tested by audit test stand levels, coolant fuel usage levels and diesel fuel usage levels.

The permittee shall submit required quarterly deviation (excursion) reports in the following manner:

- a. reports of any required monitoring and/or record keeping information shall be submitted to the Regional Air Pollution Control Agency; and,
  - b. except as otherwise may be provided in the terms and conditions for a specific emissions unit, quarterly written reports of (a) any deviations (excursions) from emission limitations and operational restrictions that have been detected by the testing, monitoring, and record keeping requirements specified in this permit, (b) the probable cause of such deviations, and (c) any corrective actions or preventive measures which have been or will be taken, shall be submitted to the Regional Air Pollution Control Agency. If no deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted quarterly, i.e., by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters. (These quarterly reports shall exclude deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06.)
4. The permittee shall submit, in writing, an annual report to the Director (the Regional Air Pollution Control Agency) which specifies: the total engine production; hours of operation; engines tested by the audit test stand; coolant usage; diesel fuel usage; the combined emissions for the Diesel Engine Hot Test Stands (emissions units **P001, P002, P003, P004, P005, P006, P007, P008 and P009**); the combined emissions for the Diesel Engine Audit Test Stands (emissions units **P010, P011, P012, P013 and P014**); the particulate and VOC emissions from the Wet Machining Operations (emissions unit **P014**); the particulate emissions from the Dry Machining Operations

**DMAX Ltd**Facility ID: **0857103196****PTI Application: 08-03840****Modification Issued: 5/3/2001**

(emissions unit **P015**); the VOC emissions from the Electronic Fuel Injection Stand (emissions unit **P016**); the PM, NH<sub>3</sub>, NO<sub>x</sub> and CO emissions from the Heat Treat (emissions unit **P017**). These reports shall be submitted by January 31 of each year and shall cover the previous 12 calendar months.

**D. Compliance Method Determination:**

1. Compliance with the emission limitation(s) of these terms and conditions shall be determined in accordance with the following method(s):

**For P001 thru P009**

**DMAX Ltd****PTI Application: 08-03840****Modification Issued: 5/3/2001**Facility ID: **0857103196**a. Emission Limitation

0.57 pound NO<sub>x</sub> per hour (common hourly emission limitation for emissions units: P001, P002, P003, P004, P005, P006, P007, P008 and P009)

Applicable Compliance Method

Compliance for each hot test stand shall be determined by multiplying the company derived emission rate of (A.) 4.0 grams per horsepower-hour by the average horsepower output during the test, 250 horsepower, and dividing 453.6 grams per pound. The result, 2.2 pounds per hour, is then multiplied by a factor of (B.) 0.04333 hour per test, and then multiplied by the maximum number of engines tested per hour, (C.) 6 engines per hour.

b. Emission Limitation

2.50 tons NO<sub>x</sub> per year (common annual emission limitation for emissions units: P001, P002, P003, P004, P005, P006, P007, P008 and P009)

Applicable Compliance Method

Compliance for each hot test stand shall be determined by multiplying the hourly emission rate for NO<sub>x</sub>, (A.) 0.57 lb/hr, by the maximum annual operating hours, (B.) 8,760 hrs/yr.

c. Emission Limitation

9.55 tons NO<sub>x</sub> per year (combined total emissions for emissions units: P001, P002, P003, P004, P005, P006, P007, P008 and P009)

Applicable Compliance Method

Compliance shall be determined by multiplying the company derived emission rate of (A.) 4.0 grams per horsepower-hour by the average horsepower output during the test, 250 horsepower, and dividing by 453.6 grams per pound. The result, 2.2 pounds per hour, is then multiplied by a factor of (B.) 0.04333 hour per test, and then multiplied by the maximum number of engines tested per year, (C.) 200,000 engines per year.

d. Emission Limitation

0.29 pound CO per hour (common hourly emission limitation for emissions units: P001, P002, P003, P004, P005, P006, P007, P008 and P009)

**DMAX Ltd****PTI Application: 08-03840****Modification Issued: 5/3/2001**Facility ID: **0857103196**Applicable Compliance Method

Compliance for each hot test stand shall be determined by multiplying the company derived emission rate of (A.) 2.0 grams per horsepower-hour by the average horsepower output during the test, 250 horsepower, and dividing 453.6 grams per pound. The result, 1.1 pounds per hour, is then multiplied by a factor of (B.) 0.04333 hour per test, and then multiplied by the maximum number of engines tested per hour, (C.) 6 engines per hour.

e. Emission Limitation

1.27 ton CO per year (common annual emission limitation for emissions units: P001, P002, P003, P004, P005, P006, P007, P008 and P009)

Applicable Compliance Method

Compliance for each hot test stand shall be determined by multiplying the hourly emission rate for CO, (A.) 0.29 lb/hr, by the maximum annual operating hours, (B.) 8,760 hrs/yr.

f. Emission Limitation

4.78 tons CO per year (combined total emissions for emissions units: P001, P002, P003, P004, P005, P006, P007, P008 and P009)

Applicable Compliance Method

Compliance shall be determined by multiplying the company derived emission rate of (A.) 2.0 grams per horsepower-hour by the average horsepower output during the test, 250 horsepower, and dividing by 453.6 grams per pound. The result, 1.1 pounds per hour, is then multiplied by a factor of (B.) 0.04333 hour per test, and then multiplied by the maximum number of engines tested per year, (C.) 200,000 engines per year.

g. Emission Limitation

0.13 pound SO<sub>2</sub> per hour (common hourly emission limitation for emissions units: P001, P002, P003, P004, P005, P006, P007, P008 and P009)

Applicable Compliance Method

Compliance for each hot test stand shall be determined by multiplying the AP-42 emission

rate (Table 3.3-3) of (A.) 0.931 gram per horsepower-hour by the average horsepower output during the test, 250 horsepower, and dividing 453.6 grams per pound. The result, 0.51 pound per hour, is then multiplied by a factor of (B.) 0.04333 hour per test, and then multiplied by the maximum number of engines tested per hour, (C.) 6 engines per hour.

h. Emission Limitation

0.57 ton SO<sub>2</sub> per year (common annual emission limitation for emissions units: P001, P002, P003, P004, P005, P006, P007, P008 and P009)

Applicable Compliance Method

Compliance for each hot test stand shall be determined by multiplying the hourly emission rate for SO<sub>2</sub>, (A.) 0.13 lb/hr, by the maximum annual operating hours, (B.) 8,760 hrs/yr.

i. Emission Limitation

2.22 tons SO<sub>2</sub> per year (combined total emissions for emissions units: P001, P002, P003, P004, P005, P006, P007, P008 and P009)

Applicable Compliance Method

Compliance shall be determined by multiplying the AP-42 emission rate (Table 3.3-3) of (A.) 0.931 gram per horsepower-hour by the average horsepower output during the test, 250 horsepower, and dividing by 453.6 grams per pound. The result, 0.51 pound per hour, is then multiplied by a factor of (B.) 0.04333 hour per test, and then multiplied by the maximum number of engines tested per year, (C.) 200,000 engines per year.

j. Emission Limitation

0.03 pound VOC per hour (common hourly emission limitation for emissions units: P001, P002, P003, P004, P005, P006, P007, P008 and P009)

Applicable Compliance Method

Compliance for each hot test stand shall be determined by multiplying the company derived emission rate of (A.) 0.2 gram per horsepower-hour by the average horsepower output during the test, 250 horsepower, and dividing 453.6 grams per pound. The result, 0.11 pound per hour, is then multiplied by a factor of (B.) 0.04333 hour per test, and then multiplied by the maximum number of engines tested per hour, (C.) 6 engines per hour.

k. Emission Limitation

0.13 ton VOC per year (common annual emission limitation for emissions units: P001, P002, P003, P004, P005, P006, P007, P008 and P009)

**DMAX Ltd****PTI Application: 08-03840****Modification Issued: 5/3/2001**Facility ID: **0857103196**Applicable Compliance Method

Compliance for each hot test stand shall be determined by multiplying the hourly emission rate for VOC, (A.) 0.03 lb/hr, by the maximum annual operating hours, (B.) 8,760 hrs/yr.

l. Emission Limitation

0.48 ton VOC per year (combined total emissions for emissions units: P001, P002, P003, P004, P005, P006, P007, P008 and P009)

Applicable Compliance Method

Compliance shall be determined by multiplying the company derived emission rate of (A.) 0.2 gram per horsepower-hour by the average horsepower output during the test, 250 horsepower, and dividing by 453.6 grams per pound. The result, 0.11 pound per hour, is then multiplied by a factor of (B.) 0.04333 hour per test, and then multiplied by the maximum number of engines tested per year, (C.) 200,000 engines per year.

m. Emission Limitation

0.14 pound PM per hour (common hourly emission limitation for emissions units: P001, P002, P003, P004, P005, P006, P007, P008 and P009)

Applicable Compliance Method

Compliance for each hot test stand shall be determined by multiplying the AP-42 emission rate (Table 3.3-2) of (A.) 1.0 gram per horsepower-hour by the average horsepower output during the test, 250 horsepower, and dividing 453.6 grams per pound. The result, 0.55 pound per hour, is then multiplied by a factor of (B.) 0.04333 hour per test, and then multiplied by the maximum number of engines tested per hour, (C.) 6 engines per hour.

n. Emission Limitation

0.61 ton PM per year (common annual emission limitation for emissions units: P001, P002, P003, P004, P005, P006, P007, P008 and P009)

Applicable Compliance Method

Compliance for each hot test stand shall be determined by multiplying the hourly emission

**DMAX Ltd**Facility ID: **0857103196****PTI Application: 08-03840****Modification Issued: 5/3/2001**

rate for PM, (A.) 0.14 lb/hr, by the maximum annual operating hours, (B.) 8,760 hrs/yr.

o. Emission Limitation

2.39 tons PM per year (combined total emissions for emissions units: P001, P002, P003, P004, P005, P006, P007, P008 and P009)

Applicable Compliance Method

Compliance shall be determined by multiplying the AP-42 emission rate (Table 3.3-2) of (A.) 1.0 gram per horsepower-hour by the average horsepower output during the test, 250 horsepower, and dividing by 453.6 grams per pound. The result, 0.55 pound per hour, is then multiplied by a factor of (B.) 0.04333 hour per test, and then multiplied by the maximum number of engines tested per year, (C.) 200,000 engines per year.

**DMAX Ltd****PTI Application: 08-03840****Modification Issued: 5/3/2001**Facility ID: **0857103196**

p. Emission Limitation

Visible emissions shall not exceed 10 percent opacity for a 6-minute average (common visible emission limitation for emissions units: P001, P002, P003, P004, P005, P006, P007, P008 and P009)

Applicable Compliance Method

Compliance shall be determined through visible emission evaluations performed in accordance with OAC rule 3745-17-03(B)(1) using the methods and procedures specified in USEPA Method Reference Method 9.

**For P010 thru P013**

q. Emission Limitation

1.76 pounds NO<sub>x</sub> per hour (common hourly emission limitation for emissions units: P010, P011, P012 and P013)

Applicable Compliance Method

Compliance for each audit test stand shall be determined by multiplying the company derived emission rate of (A.) 4.0 grams per horsepower-hour by the average horsepower output during the test, 250 horsepower, and dividing

453.6 grams per pound. The result, 2.2 pounds per hour, is then multiplied by a factor of (B.) 0.1333 hour per test, and then multiplied by the maximum number of engines tested per hour, (C.) 6 engines per hour.

r. Emission Limitation

2.94 tons NO<sub>x</sub> per year (common and combined total emissions for emissions units: P010, P011, P012, and P013.)

Applicable Compliance Method

Compliance shall be determined by multiplying the company derived emission rate of (A.) 4.0 grams per horsepower-hour by the average horsepower output during the test, 250 horsepower, and dividing by 453.6 grams per pound. The result, 2.2 pounds per hour, is then multiplied by a factor of (B.) 0.1333 hour per test, and then multiplied by the maximum number of engines tested per year, (C.) 20,000 engines per year.

**DMAX Ltd****PTI Application: 08-03840****Modification Issued: 5/3/2001**Facility ID: **0857103196**s. Emission Limitation

0.88 pound CO per hour (common hourly emission limitation for emissions units: P010, P011, P012 and P013)

Applicable Compliance Method

Compliance for each audit test stand shall be determined by multiplying the company derived emission rate of (A.) 2.0 grams per horsepower-hour by the average horsepower output during the test, 250 horsepower, and dividing 453.6 grams per pound. The result, 1.1 pounds per hour, is then multiplied by a factor of (B.) 0.1333 hour per test, and then multiplied by the maximum number of engines tested per hour, (C.) 6 engines per hour.

t. Emission Limitation

1.47 tons CO per year (common and combined total emissions for emissions units: P010, P011, P012 and P013)

Applicable Compliance Method

Compliance shall be determined by multiplying the company derived emission rate of (A.) 2.0 grams per horsepower-hour by the average horsepower output during the test, 250 horsepower, and dividing by 453.6 grams per pound.

The result, 1.1 pounds per hour, is then multiplied by a factor of (B.) 0.1333 hour per test, and then multiplied by the maximum number of engines tested per year, (C.) 20,000 engines per year.

u. Emission Limitation

0.41 pound SO<sub>2</sub> per hour (common hourly emission limitation for emissions units: P010, P011, P012 and P013)

Applicable Compliance Method

Compliance for each audit test stand shall be determined by multiplying the AP-42 emission rate (Table 3.3-3) of (A.) 0.931 gram per horsepower-hour by the average horsepower output during the test, 250 horsepower, and dividing 453.6 grams per pound. The result, 0.51 pound per hour, is then multiplied by a factor of (B.) 0.1333 hour per test, and then multiplied by the maximum number of engines tested per hour, (C.) 6

42

**DMAX Ltd**

**PTI Application: 08-03840**

**Modification Issued: 5/3/2001**

Facility ID: **0857103196**

engines per hour.

**DMAX Ltd****PTI Application: 08-03840****Modification Issued: 5/3/2001**Facility ID: **0857103196**v. Emission Limitation

0.68 ton SO<sub>2</sub> per year (common and combined total

emissions for emissions units: P010, P011, P012 and P013)

Applicable Compliance Method

Compliance shall be determined by multiplying the AP-42 emission rate (Table 3.3-3) of (A.) 0.931 gram per horsepower-hour by the average horsepower output during the test, 250 horsepower, and dividing by 453.6 grams per pound. The result, 0.51 pound per hour, is then multiplied by a factor of (B.) 0.1333 hour per test, and then multiplied by the maximum number of engines tested per year, (C.) 20,000 engines per year.

w. Emission Limitation

0.09 pound VOC per hour (common hourly emission limitation for emissions units: P010, P011, P012 and P013)

Applicable Compliance Method

Compliance for each audit test stand shall be determined by multiplying the company derived emission rate of (A.) 0.2 gram per horsepower-hour by the average horsepower output during the test, 250 horsepower, and dividing

453.6 grams per pound. The result, 0.11 pound per hour, is then multiplied by a factor of (B.) 0.1333 hour per test, and then multiplied by the maximum number of engines tested per hour, (C.) 6 engines per hour.

x. Emission Limitation

0.15 ton VOC per year (common and combined total emissions for emissions units: P010, P011, P012 and P013)

Applicable Compliance Method

Compliance shall be determined by multiplying the company derived emission rate of (A.) 0.2 gram per horsepower-hour by the average horsepower output during the test, 250 horsepower, and dividing by 453.6 grams per pound. The result, 0.11 pound per hour, is then multiplied by a factor of (B.) 0.1333 hour per test, and then multiplied by the

**DMAX Ltd**

**PTI Application: 08-03840**

**Modification Issued: 5/3/2001**

Facility ID: **0857103196**

maximum number of engines tested per year, (C.) 20,000 engines per year.

**DMAX Ltd****PTI Application: 08-03840****Modification Issued: 5/3/2001**Facility ID: **0857103196**y. Emission Limitation

0.44 pound PM per hour (common hourly emission limitation for emissions units: P010, P011, P012 and P013)

Applicable Compliance Method

Compliance for each audit test stand shall be determined by multiplying the AP-42 emission rate (Table 3.3-2) of (A.) 1.0 gram per horsepower-hour by the average horsepower output during the test, 250 horsepower, and dividing 453.6 grams per pound. The result, 0.55 pound per hour, is then multiplied by a factor of (B.) 0.1333 hour per test, and then multiplied by the maximum number of engines tested per hour, (C.) 6 engines per hour.

z. Emission Limitation

0.73 ton PM per year (common and combined total emissions for emissions units: P010, P011, P012 and P013)

Applicable Compliance Method

Compliance shall be determined by multiplying the AP-42 emission rate (Table 3.3-2) of (A.) 1.0 gram per horsepower-hour by the average horsepower output during the test, 250 horsepower, and dividing by 453.6 grams per pound. The result, 0.55 pound per hour, is then multiplied by a factor of (B.) 0.1333 hour per test, and then multiplied by the maximum number of engines tested per year, (C.) 20,000 engines per year.

aa. Emission Limitation

Visible emissions shall not exceed 10 percent opacity for a 6-minute average (common visible emission limitation for emissions units: P010, P011, P012 and P013)

Applicable Compliance Method

Compliance shall be determined through visible emission evaluations performed in accordance with OAC rule 3745-17-03(B)(1) using the methods and procedures specified in USEPA Method Reference Method 9.

**P014**

**DMAX Ltd**

**PTI Application: 08-03840**

**Modification Issued: 5/3/2001**

Facility ID: **0857103196**

ab. Emission Limitation

1.3 pounds PM per hour

**DMAX Ltd**Facility ID: **0857103196****PTI Application: 08-03840****Modification Issued: 5/3/2001**Applicable Compliance Method

Compliance shall be determined by dividing the company derived emission rate of (A.) 0.0007 grain per dry standard cubic foot by 7000 grains per pound, and then multiply the result, 1.0 EE-7 lb/dscf, by the maximum air flow rate, (B.) 12.6 MMft<sup>3</sup>/hr.

ac. Emission Limitation

5.52 tons PM per year

Applicable Compliance Method

Compliance shall be determined by dividing the company derived emission rate of (A.) 0.0007 grain per dry standard cubic foot by 7000 grains per pound, then multiply the result, 1.0 EE-7 lb/dscf, by the maximum air flow rate, (B.) 12.6 MMft<sup>3</sup>/hr, and then multiply the result by the maximum number of hours operated per year (C.) 8,760 hours per year.

ad. Emission Limitation

3.9 pounds of VOC per hour

Applicable Compliance Method

Compliance shall be determined by multiplying the maximum hourly usage rate of coolant, 49.125 gallons per hour, by the maximum VOC content of coolant, 0.08 pounds VOC per gallon.

ae. Emission Limitation

10.32 tons VOC per year

Applicable Compliance Method

Compliance shall be determined by multiplying the maximum annual coolant usage, 258,000 gallons, by the VOC content of the coolant, 0.08 pound per gallon.

af. Emission Limitation

Visible emissions shall not exceed 10 percent opacity as a 6-minute average.

**DMAX Ltd****PTI Application: 08-03840****Modification Issued: 5/3/2001**Facility ID: **0857103196**Applicable Compliance Method

Compliance shall be determined through visible emission evaluations performed in accordance with OAC rule 3745-17-03(B)(1) using the methods and procedures specified in USEPA Method Reference Method 9.

**P015**ag. Emission Limitation

0.7 pound PM per hour

Applicable Compliance Method

Compliance shall be determined by dividing the company derived emission rate of (A.) 0.003 grain per dry standard cubic foot by 7000 grains per pound, and then multiply the result, 4.29 EE-7 lb/dscf, by the maximum hourly air flow rate, (B.) 1.56 MMft<sup>3</sup>/hr.

ah. Emission Limitation

2.93 tons PM per year

Applicable Compliance Method

Compliance shall be determined by dividing the company derived emission rate of (A.) 0.003 grains per dry standard cubic foot by 7000 grains per pound, then multiply the result, 4.29 EE-7 lb/dscf, by the maximum hourly air flow rate, (B.) 1.56 MMft<sup>3</sup>/hr, and then multiply the result by the maximum number of hours operated per year (C.) 8,760 hours per year.

ai. Emission Limitation

Visible emissions shall not exceed 10 percent opacity as a 6-minute average.

Applicable Compliance Method

Compliance shall be determined through visible emission evaluations performed in accordance with OAC rule 3745-17-03(B)(1) using the methods and procedures specified in USEPA Method Reference Method 9.

**For P016**aj. Emission Limitation

**DMAX Ltd**

**PTI Application: 08-03840**

**Modification Issued: 5/3/2001**

Facility ID: **0857103196**

2.8 pounds VOC per hour

Applicable Compliance Method

Compliance shall be determined by multiplying the maximum hourly usage rate of diesel fuel, 0.38 gallon per hour, by the VOC content of diesel fuel, 7.3 pounds VOC per gallon.

**DMAX Ltd**Facility ID: **0857103196****PTI Application: 08-03840****Modification Issued: 5/3/2001**ak. Emission Limitation

7.3 tons VOC per year

Applicable Compliance Method

Compliance shall be determined by multiplying the maximum annual diesel fuel usage, 2,000 gallons, by the VOC content of the diesel fuel, 7.3 pounds per gallon.

**For P017**al. Emission Limitation

0.41 lb PM per hour

Applicable Compliance Method

Compliance shall be determined by multiplying the company derived emission rate, (A.) 1.42 EE-4 lbs PM/lbs of part, by the pounds per part, (B.) 65 lbs/part, and then multiply the result by the maximum number of parts per hour, (C.) 44 parts/hour.

am. Emission Limitation

1.81 tons PM per year

Applicable Compliance Method

Compliance shall be determined by summing the PM emissions from natural gas combustion with the PM emissions from the process. The annual PM emissions from natural gas combustion shall be determined by multiplying the maximum natural gas usage rate, (A.) 519 ft<sup>3</sup>/hr, by the AP-42 PM emission factor (Table 1.4-1), (B.) 0.000012 lb/ft<sup>3</sup>, then multiply the result by the maximum number of operating hours, (C.) 8,760 hours per year. The annual PM emissions from the process shall be determined by multiplying the company derived emission rate, (A.) 1.42 EE-4 pounds PM/pounds of part, by the pounds per part, (B.) 65 pounds/part, then multiplying the result by the maximum number of parts per hour, (C.) 44 parts/hour, and next multiply the result by the maximum number of hours operated per year, (D.) 8,760 hours/year.

an. Emission Limitation

51

**DMAX Ltd**

**PTI Application: 08-03840**

**Modification Issued: 5/3/2001**

Facility ID: **0857103196**

0.37 pound NH<sub>3</sub> per hour

**DMAX Ltd**Facility ID: **0857103196****PTI Application: 08-03840****Modification Issued: 5/3/2001**Applicable Compliance Method

Compliance shall be determined by multiplying the company derived emission rate, (A.) 4.41 EE-7 lbs/ft<sup>3</sup>, by the maximum hourly air flow rate, (B.) 840,000 ft<sup>3</sup>/hr.

ao. Emission Limitation

1.62 tons NH<sub>3</sub> per year

Applicable Compliance Method

Compliance shall be determined by multiplying the company derived emission rate, (A.) 4.41 EE-7 lbs/ft<sup>3</sup>, by the maximum hourly air flow rate, (B.) 840,000 ft<sup>3</sup>/hr, then multiply the results by the maximum number of operating hours, (C.) 8,760 hours per year.

ap. Emission Limitation

0.05 pound NO<sub>x</sub> per hour

Applicable Compliance Method

Compliance shall be determined by multiplying the maximum hourly natural gas usage rate, (A.) 519 ft<sup>3</sup>/hr, by the AP-42 NO<sub>x</sub> emission factor (Table 1.4-1), (B.) 0.0001 lb/ft<sup>3</sup>.

aq. Emission Limitation

0.23 ton NO<sub>x</sub>/yr

Applicable Compliance Method

Compliance shall be determined by multiplying the maximum hourly natural gas usage rate, (A.) 519 ft<sup>3</sup>/hr, by the AP-42 NO<sub>x</sub> emission factor (Table 1.4-1), (B.) 0.0001 lb/ft<sup>3</sup>, then multiply the result by the maximum number of operating hours, (C.) 8,760 hours per year.

ar. Emission Limitation

0.01 pound of CO per hour

Applicable Compliance Method

**DMAX Ltd****PTI Application: 08-03840****Modification Issued: 5/3/2001**Facility ID: **0857103196**

Compliance shall be determined by multiplying the maximum hourly natural gas usage rate, (A.) 519 ft<sup>3</sup>/hr, by the AP-42 CO emission rate (Table 1.4-1), (B.) 0.000021 lb/ft<sup>3</sup>.

DMAX Ltd

PTI Application: 08-03840

Modification Issued: 5/3/2001

Facility ID: 0857103196

as. Emission Limitation

0.5 ton CO per year

Applicable Compliance Method

Compliance shall be determined by multiplying the maximum hourly natural gas usage rate, (A.) 519 ft<sup>3</sup>/hr, by the AP-42 CO emission factor (Table 1.4-1), (B.) 0.00021 lb/ft<sup>3</sup>, then multiply the result by the maximum number of operating hours, (C.) 8,760 hours per year.

at. Emission Limitation

Visible emissions shall not exceed 20 percent opacity for a 6-minute average.

Applicable Compliance Method

Compliance shall be determined through visible emission evaluations performed in accordance with OAC rule 3745-17-03(B)(1) using the methods and procedures specified in USEPA Method 9.

**E. Miscellaneous Requirements**

1. This permit allows the use of ammonia (NH<sub>3</sub>) specified by the permittee in the application for PTI number 08-3840. In conjunction with the best available technology requirements of OAC rule 3745-31-05, the NH<sub>3</sub> emission limitation(s) specified in this permit was established in accordance with the Ohio EPA's "Air Toxics Policy" and is based on both data and the design parameters of the emissions unit's exhaust system, as specified in the application. Compliance with the Ohio EPA's "Air Toxics Policy" was demonstrated for NH<sub>3</sub> based on the Screen3 model and a comparison of the predicted 1 hour maximum ground-level concentration to the MAGLC. The following summarizes the results of the modeling for each pollutant:

**Pollutant: NH<sub>3</sub>****TLV (ug/m<sup>3</sup>): 17,000.0****Maximum Hourly Emission Rate (lbs/hr): 0.37****Predicted 1 Hour Maximum Ground-Level Concentration at the Fenceline (ug/m<sup>3</sup>): 7.5****Maximum Acceptable Ground-Level Concentration (MAGLC) (ug/m<sup>3</sup>): 170.0**

Any of the following changes may be deemed a "modification" to the emissions unit and, as such,

**DMAX Ltd**Facility ID: **0857103196****PTI Application: 08-03840****Modification Issued: 5/3/2001**

prior notification to and approval from the Regional Air Pollution Control Agency are required, including the possible issuance of modifications to PTI number 08-3840 and the operating permit:

- a. any changes in the composition of the nitriding materials, or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as

**DMAX Ltd**Facility ID: **0857103196****PTI Application: 08-03840****Modification Issued: 5/3/2001**

indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value specified in the above table;

- b. any change to the emissions unit or its exhaust parameters (e.g., increased emission rate, reduction of exhaust gas flow rate, and decreased stack height) that would result in an exceedance of any MAGLC specified in the above table;
- c. any change to the emissions unit or its method of operation that would either require an increase in the emission limitation(s) established by this permit or would otherwise be considered a "modification" as defined in OAC rule 3745-31-01; and,
- d. any change in the composition of the materials employed, or use of new materials, that would result in an increase in emissions of any "Hazardous Air Pollutants" (HAPS) as defined in OAC rule 3745-77-01(V).