

Synthetic Minor Determination and/or **Netting Determination**

Permit To Install **08-03785**

A. Source Description

Butler Asphalt emissions unit P901-275 tons/hr portable drum mix hot mix asphalt; rotary dryer controlled with a baghouse is being administratively modified. The facility is proposing to restrict the hourly maximum annual asphalt production tonnage from 325 TPH to 275 TPH and the annual maximum asphalt production from 406,250 tons to 343,750 tons as a rolling 12-month summation, therefore avoiding Title V permitting requirements. Therefore, with this modification the facility will not trigger Title V operating permit requirements.

B. Facility Emissions and Attainment Status

Without federally enforceable restrictions, the potential Carbon Monoxide (CO) emissions are 190.90 tons/yr. The emissions unit is located in Montgomery county which is currently designated as non-attainment for ozone.

C. Source Emissions

With a restriction on the maximum annual asphalt production tonnage of 343,750 as a rolling 12-month summation, CO emissions are 27.2 tons/yr. This is below the major source threshold of 100 tons/yr which would require the facility to obtain a Title V permit.

D. Conclusion

With the federally enforceable asphalt production rate, based on a rolling 12 month basis emission rate of CO, the emissions are below major source thresholds for Title V permitting requirements. Therefore through federally enforceable terms and conditions and record keeping requirements, Butler Asphalt plant will not trigger the Title V permitting requirements.



State of Ohio Environmental Protection Agency

Street Address:

Mailing Address:

Lazarus Gov. Center TELE: (614) 644-3020 FAX: (614) 644-2329

Lazarus Gov.
Center

**RE: DRAFT PERMIT TO INSTALL MODIFICATION
MONTGOMERY COUNTY**

CERTIFIED MAIL

Application No: 08-03785

Fac ID: 0857700172

DATE: 1/27/2005

Butler Asphalt Company
David Poynter
P.O. Box 248 7500 Johnson Station Rd.
Vandalia, OH 453779620

You are hereby notified that the Ohio Environmental Protection Agency has made a draft action recommending that the Director issue a Permit to Install modification for the air contaminant source(s) [emissions unit(s)] shown on the enclosed draft permit modification. This draft action is not an authorization to begin construction or modification of your emissions unit(s). The purpose of this draft is to solicit public comments on the proposed installation. A public notice concerning the draft permit will appear in the Ohio EPA Weekly Review and the newspaper in the county where the facility will be located. Public comments will be accepted by the field office within 30 days of the date of publication in the newspaper. Any comments you have on the draft permit modification should be directed to the appropriate field office within the comment period. A copy of your comments should also be mailed to Robert Hodanbosi, Division of Air Pollution Control, Ohio EPA, P.O. Box 1049, Columbus, OH, 43266-0149.

A Permit to Install modification may be issued in proposed or final form based on the draft action, any written public comments received within 30 days of the public notice, or record of a public meeting if one is held. You will be notified in writing of a scheduled public meeting. Upon issuance of a final Permit to Install modification a fee of **\$ 625** will be due. Please do not submit any payment now.

The Ohio EPA is urging companies to investigate pollution prevention and energy conservation. Not only will this reduce pollution and energy consumption, but it can also save you money. If you would like to learn ways you can save money while protecting the environment, please contact our Office of Pollution Prevention at (614) 644-3469. If you have any questions about this draft permit, please contact the field office where you submitted your application, or Mike Ahern, Field Operations & Permit Section at (614) 644-3631.

Sincerely,

Michael W. Ahern, Manager
Permit Issuance and Data Management Section
Division of Air Pollution Control

CC: USEPA

RAPCA

Miami Valley Regional Planning Commission

KY

IN

MONTGOMERY COUNTY

PUBLIC NOTICE

ISSUANCE OF DRAFT PERMIT TO INSTALL **08-03785** FOR AN AIR CONTAMINANT SOURCE FOR **Butler Asphalt Company**

On 1/27/2005 the Director of the Ohio Environmental Protection Agency issued a draft action of a Permit To Install an air contaminant source for **Butler Asphalt Company**, located at **7500 South Cassel Road, Vandalia, Ohio**.

Installation of the air contaminant source identified below may proceed upon final issuance of Permit To Install 08-03785:

Adm. mod. to derate the plant from 325 TPH to 275 TPH and update emission factors.

Comments concerning this draft action, or a request for a public meeting, must be sent in writing to the address identified below no later than thirty (30) days from the date this notice is published. All inquiries concerning this draft action may be directed to the contact identified below.

John Paul, Regional Air Pollution Control Agency, 117 South Main Street, Dayton, OH 45422-1280
[(937)225-4435]



**Permit To Install
Terms and Conditions**

**Issue Date: To be entered upon final issuance
Effective Date: To be entered upon final issuance**

DRAFT MODIFICATION OF PERMIT TO INSTALL 08-03785

Application Number: 08-03785
Facility ID: 0857700172
Permit Fee: **To be entered upon final issuance**
Name of Facility: Butler Asphalt Company
Person to Contact: David Poynter
Address: P.O. Box 248 7500 Johnson Station Rd.
Vandalia, OH 453779620

Location of proposed air contaminant source(s) [emissions unit(s)]:
**7500 South Cassel Road
Vandalia, Ohio**

Description of proposed emissions unit(s):
Adm. mod. to derate the plant from 325 TPH to 275 TPH and update emission factors.

The above named entity is hereby granted a modification to the permit to install described above pursuant to Chapter 3745-31 of the Ohio Administrative Code. Issuance of this modification does not constitute expressed or implied approval or agreement that, if constructed or modified in accordance with the plans included in the application, the above described source(s) of environmental pollutants will operate in compliance with applicable State and Federal laws and regulations, and does not constitute expressed or implied assurance that if constructed or modified in accordance with those plans included in the application, the above described source(s) of pollutants will be granted the necessary operating permits.

This permit is granted subject to the conditions attached hereto.

Ohio Environmental Protection Agency

Director

Part I - GENERAL TERMS AND CONDITIONS

A. Permit to Install General Terms and Conditions

1. Compliance Requirements

The emissions unit(s) identified in this Permit to Install shall remain in full compliance with all applicable State laws and regulations and the terms and conditions of this permit.

2. Reporting Requirements

The permittee shall submit required reports in the following manner:

- a. Reports of any required monitoring and/or recordkeeping information shall be submitted to the appropriate Ohio EPA District Office or local air agency.
- b. Except as otherwise may be provided in the terms and conditions for a specific emissions unit, quarterly written reports of (a) any deviations (excursions) from emission limitations, operational restrictions, and control device operating parameter limitations that have been detected by the testing, monitoring, and recordkeeping requirements specified in this permit, (b) the probable cause of such deviations, and (c) any corrective actions or preventive measures which have been or will be taken, shall be submitted to the appropriate Ohio EPA District Office or local air agency. If no deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted quarterly, i.e., by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters. (These quarterly reports shall exclude deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06.)

3. Records Retention Requirements

Each record of any monitoring data, testing data, and support information required pursuant to this permit shall be retained for a period of five years from the date the record was created. Support information shall include, but not be limited to, all calibration and maintenance records and all original strip-chart recordings for continuous monitoring instrumentation, and copies of all reports required by this permit. Such records may be maintained in computerized form.

4. Inspections and Information Requests

The Director of the Ohio EPA, or an authorized representative of the Director, may, subject to the safety requirements of the permittee and without undue delay, enter upon the premises of this source at any reasonable time for purposes of making inspections, conducting tests, examining records or reports pertaining to any emission of air contaminants, and determining compliance with any applicable State air pollution laws and regulations and the terms and conditions of this permit. The permittee shall furnish to the Director of the Ohio EPA, or an authorized representative of the Director, upon receipt of a written request and within a reasonable time, any

Issued: To be entered upon final issuance

information that may be requested to determine whether cause exists for modifying, reopening or revoking this permit or to determine compliance with this permit. Upon verbal or written request, the permittee shall also furnish to the Director of the Ohio EPA, or an authorized representative of the Director, copies of records required to be kept by this permit.

5. Scheduled Maintenance/Malfunction Reporting

Any scheduled maintenance of air pollution control equipment shall be performed in accordance with paragraph (A) of OAC rule 3745-15-06. The malfunction of any emissions units or any associated air pollution control system(s) shall be reported to the appropriate Ohio EPA District Office or local air agency in accordance with paragraph (B) of OAC rule 3745-15-06. Except as provided in that rule, any scheduled maintenance or malfunction necessitating the shutdown or bypassing of any air pollution control system(s) shall be accompanied by the shutdown of the emissions unit(s) that is (are) served by such control system(s).

6. Permit Transfers

Any transferee of this permit shall assume the responsibilities of the prior permit holder. The appropriate Ohio EPA District Office or local air agency must be notified in writing of any transfer of this permit.

7. Air Pollution Nuisance

The air contaminants emitted by the emissions units covered by this permit shall not cause a public nuisance, in violation of OAC rule 3745-15-07.

8. Termination of Permit to Install

This Permit to Install shall terminate within eighteen months of the effective date of the Permit to Install if the owner or operator has not undertaken a continuing program of installation or modification or has not entered into a binding contractual obligation to undertake and complete within a reasonable time a continuing program of installation or modification. This deadline may be extended by up to 12 months if application is made to the Director within a reasonable time before the termination date and the party shows good cause for any such extension.

9. Construction of New Sources(s)

The proposed emissions unit(s) shall be constructed in strict accordance with the plans and application submitted for this permit to the Director of the Ohio Environmental Protection Agency. There may be no deviation from the approved plans without the express, written approval of the Agency. Any deviations from the approved plans or the above conditions may lead to such sanctions and penalties as provided under Ohio law. Approval of these plans does not constitute an assurance

that the proposed facilities will operate in compliance with all Ohio laws and regulations. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed sources cannot meet the requirements of this permit or cannot meet applicable standards.

If the construction of the proposed emissions unit(s) has already begun or has been completed prior to the date the Director of the Environmental Protection Agency approves the permit application and plans, the approval does not constitute expressed or implied assurance that the proposed facility has been constructed in accordance with the approved plans. The action of beginning and/or completing construction prior to obtaining the Director's approval constitutes a violation of OAC rule 3745-31-02. Furthermore, issuance of the Permit to Install does not constitute an assurance that the proposed source will operate in compliance with all Ohio laws and regulations. Approval of the plans in any case is not to be construed as an approval of the facility as constructed and/or completed. Moreover, issuance of the Permit to Install is not to be construed as a waiver of any rights that the Ohio Environmental Protection Agency (or other persons) may have against the applicant for starting construction prior to the effective date of the permit. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed facilities cannot meet the requirements of this permit or cannot meet applicable standards.

10. Public Disclosure

The facility is hereby notified that this permit, and all agency records concerning the operation of this permitted source, are subject to public disclosure in accordance with OAC rule 3745-49-03.

11. Applicability

This Permit To Install is applicable only to the emissions unit(s) identified in the Permit To Install. Separate Permit To Install for the installation or modification of any other emissions unit(s) are required for any emissions unit for which a Permit To Install is required.

12. Best Available Technology

As specified in OAC Rule 3745-31-05, all new sources must employ Best Available Technology (BAT). Compliance with the terms and conditions of this permit will fulfill this requirement.

13. Source Operation and Operating Permit Requirements After Completion of Construction

This facility is permitted to operate each source described by this Permit to Install for a period of up to one year from the date the source commenced operation. This permission to operate is

Butler Asphalt Company

Facility ID: 0857700172

PTI Application: 08-03785

Issued: To be entered upon final issuance

granted only if the facility complies with all requirements contained in this permit and all applicable air pollution laws, regulations, and policies. Pursuant to OAC Chapter 3745-35, the permittee shall submit a complete operating permit application within ninety (90) days after commencing operation of the emissions unit(s) covered by this permit.

14. Construction Compliance Certification

The applicant shall provide Ohio EPA with a written certification (see enclosed form) that the facility has been constructed in accordance with the Permit to Install application and the terms and conditions of the Permit to Install. The certification shall be provided to Ohio EPA upon completion of construction but prior to startup of the source.

15. Fees

The permittee shall pay fees to the Director of the Ohio EPA in accordance with ORC section 3745.11 and OAC Chapter 3745-78. The permittee shall pay all applicable Permit to Install fees within 30 days after the issuance of this Permit to Install.

B. Permit to Install Summary of Allowable Emissions

The following information summarizes the total allowable emissions, by pollutant, based on the individual allowable emissions of each air contaminant source identified in this permit.

**SUMMARY (for informational purposes only)
TOTAL PERMIT TO INSTALL ALLOWABLE EMISSIONS**

<u>Pollutant</u>	<u>Tons Per Year</u>
particulate matter	5.16
(fugitive)	(2.94)
volatile organic	
compound	8.05
nitrogen oxide	
sulfur dioxide	6.54
carbon monoxide	1.15
	27.2

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

Operations, Property,
and/or Equipment

P901 - 275 TPH Portable drum mix
asphalt plant with baghouse.

*administrative modification

aggregate storage bins, cold aggregate
elevator, load-out and silo filling
operations

Emissions Unit ID: **P901**

Applicable Rules/Requirements

Applicable Emissions
Limitations/Control Measures

OAC rule 3745-31-05(A)(3)

The requirements of this rule also include compliance with the requirements of NSPS 40 CFR Part 60, Subpart I, and OAC 3745-35-07(B).

OAC rule 3745-17-07(A) and 3745-17-11(B)

The particulate emissions (PE) from this emissions unit when burning #2 fuel oil shall not exceed 5.16 tons/yr.

OAC rule 3745-18-06(E)(2)

The carbon monoxide (CO) emissions from this emissions unit when burning #2 fuel oil shall not exceed 43.6 lbs/hr.

OAC rule 3745-31-05(A)(3)

The volatile organic compound (VOC) emissions from this emissions unit when burning #2 fuel oil shall not exceed 12.9 lbs/hr and 8.05 tons/yr.

The nitrogen oxide (NO_x) emissions from this emissions unit when burning #2 fuel oil shall not exceed 10.5 lbs/hr and 6.54 tons/yr.

OAC rule 3745-17-07(B)

The sulfur dioxide (SO₂) emissions from this emissions unit when burning #2 fuel oil shall not exceed 1.84 lbs/hr and 1.15 tons/yr.

OAC rule 3745-35-07(B)
(Synthetic minor to avoid Title V)

The carbon monoxide CO emissions from this emissions unit when burning #2 oil shall not exceed 27.2 tons/yr.

NSPS 40 CFR Part 60, Subpart I

The ton/yr limitations are based upon a rolling 12-month summation.

OAC rule 3745-17-07(B) and OAC rule 3745-17-08(B)

Butler

PTI A

Emissions Unit ID: **P901**

Issued: To be entered upon final issuance

Particulate emissions from the stack shall not exceed 0.04 grain per dry standard cubic foot of exhaust gases.

Visible particulate emissions shall not exceed 20 percent opacity, as a 6-minute average, from the stack, except as provided by 40 CFR Part 60, Subpart I.

The emission limitations specified in these rules are less stringent than the emission limitations specified in 40 CFR Part 60, Subpart I.

The emission limitation specified by this rule is less stringent than the emission limitation specified in OAC rule 3745-31-05(A)(3).

The fugitive particulate emissions from silo filling and plant load out (hot end) shall not exceed 0.19 ton/yr.

The fugitive VOC emissions from silo filling and plant load out (hot end) shall not exceed 2.75 tons/yr.

Visible particulate emissions from any fugitive source shall not exceed 20 percent opacity, as a 3-minute average.

The drop height of the front end loader bucket shall be minimized to the extent possible in order to minimize or eliminate visible

emissions of fugitive dust from the elevator loading area.

The aggregate loaded into the storage bins shall have a moisture content sufficient to minimize or eliminate the visible emissions of fugitive dust from the elevator and the transfer point to the dryer.

See A.2.c.

Butler

PTI A

Emissions Unit ID: P901

Issued: To be entered upon final issuance

2. Additional Terms and Conditions

- 2.a** The lbs/hr of CO, NO_x, SO₂ and VOC emissions limitations were established for PTI purposes to reflect the potential to emit for this emissions unit. Therefore, it is not necessary to develop record keeping and/or reporting requirements to ensure compliance with these limits.
- 2.b** The particulate emission limitation specified above includes particulate matter (PM₁₀) emissions that are less than 10 microns in diameter.
- 2.c** OAC rules 3745-17-07(B) and 3745-17-08(B) are applicable only when the emissions unit is located in an "Appendix A" area, as specified in OAC rule 3745-17-08.

B. Operational Restrictions

- 1. The maximum annual production rate for this emissions unit shall not exceed 343,750 tons, based upon a rolling 12-month summation. Since this is an existing source it has existing records and therefore does not need to be limited to first year monthly amounts of production.
- 2. The pressure drop across the baghouse shall be maintained within the range of 3-5 inches of water when the emissions unit is in operation.
- 3. All recycled, on-spec used oil burned in this emissions unit shall meet the following specifications:

Contaminant/Property	Allowable Specifications
arsenic	5 ppm, maximum
cadmium	2 ppm, maximum
chromium	10 ppm, maximum
lead	100 ppm, maximum
PCB's	50 ppm, maximum*
total halogens	4000 ppm maximum**
mercury	1 ppm, maximum
flash point	100 degrees Fahrenheit, minimum
heat content	135,000 Btu/gallon, minimum

* If the permittee is burning used oil with any quantifiable level 2ppm < 50 ppm of PCBs, then the permittee is subject to any applicable requirements found under 40 CFR part 279., subparts G and H and 40 CFR 761.20(e).

Emissions Unit ID: **P901**

- ** Used oil containing more than 1000 ppm total halogens is presumed to be a hazardous waste under the rebuttable presumption provided under 40 CFR 279.10(b)(1)(ii) and OAC rule 3745-279-10(B)(1)(b). Therefore, the permittee may receive and burn used oil exceeding 1000 ppm of total halogens (but less than 4000 ppm, maximum) only if the used oil supplier has demonstrated the used oil does not contain any hazardous waste pursuant to OAC rule 3745-279-63.
4. The permittee may substitute reclaimed asphalt pavement (RAP) in the raw material feed mix in amounts not to exceed 50 percent of all aggregate materials.
 5. The permittee shall burn only #2 fuel oil in this emissions unit.

C. Monitoring and/or Recordkeeping Requirements

1. The permittee shall maintain monthly records of the following information:
 - a. The total quantity of asphalt products produced each month;
 - b. The rolling, 12-month summation of the monthly production rates; and
 - c. The maximum percentage RAP used for any mix.
2. The permittee shall properly, operate, and maintain equipment to monitor the pressure drop across the baghouse when the emissions unit is in operation. The monitoring equipment shall be installed, calibrated, operated, and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual(s). The permittee shall record the pressure drop across the baghouse on a daily basis.
3. The permittee shall receive a chemical analysis with each shipment of used oil from the supplier. The analysis shall identify the name and address of the supplier, the supplier's USEPA identification number, and the following information:
 - a. The date of shipment or delivery.
 - b. The quantity of used oil received.
 - c. The Btu value of the used oil, in BTU/gallon.
 - d. The flash point of the used oil in degrees F.
 - e. The arsenic content, in ppm.
 - f. The cadmium content, in ppm.
 - g. The chromium content, in ppm.
 - h. The lead content, in ppm.
 - i. The PCB content, in ppm.

Issued: To be entered upon final issuance

- j. The total halogen content, in ppm.
- k. The mercury content, in ppm.

Each analysis shall be kept in a readily accessible location for at least 5 years and shall be made available to the Director (the appropriate Ohio EPS District Office or local air agency) upon verbal or written request. The Director or any authorized representative of the Director may require or may conduct periodic, detailed chemical analyses through an independent laboratory of any used oil shipment received by this facility, of any used oil stored at this facility, or of any used oil sampled at the dryer.

- 4. The permittee shall perform daily checks, when the emissions unit is in operation and when the weather conditions allow, for any visible particulate emissions from the stack and for any visible fugitive particulate emissions from the rotary dryer, aggregate storage bins and cold aggregate elevator, load out and silo filling operations serving this emissions unit. The presence or absence of any visible emissions shall be noted in an operations log. If visible emissions are observed, the permittee shall also note the following in the operations log:
 - a. The location and color of the emissions;
 - b. Whether the emissions are representative of normal operations;
 - c. If the emissions are not representative of normal operations, the cause of the abnormal emissions;
 - d. The total duration of any visible emission incident; and
 - e. Any corrective actions taken to minimize or eliminate the abnormal visible emissions.

If visible emissions are present, a visible emission incident has occurred. The observer does not have to document the exact start and end times for the visible emission incident under item (d) above or continue the daily check until the incident has ended. The observer may indicate that the visible emission incident was continuous during the observation period (or, if known, continuous during the operation of the emissions unit). With respect to the documentation of corrective actions, the observer may indicate that no corrective actions were taken if the visible emissions were representative of normal operations, or specify the minor corrective actions that were taken to ensure that the emissions unit continued to operate under normal conditions, or specify the corrective actions that were taken to eliminate abnormal visible emissions.

- 5. The permittee may, upon receipt of written approval from the appropriate Ohio EPA District Office or local air agency, modify the above-mentioned frequencies for performing the

Emissions Unit ID: **P901**

visible emissions checks if operating experience indicates that less frequent visible emissions checks would be sufficient to ensure compliance with the above-mentioned applicable requirements.

6. For each day during which the permittee burns a fuel other than #2 fuel oil, the permittee shall maintain a record of the type and quantity of fuel burned in the emissions unit.

D. Reporting Requirements

1. The permittee shall submit quarterly deviation (excursion) reports to the Director (the appropriate District Office or local air agency) which identify all exceedances of the rolling, 12-month production rate limitation.
2. The permittee shall submit pressure drop quarterly deviation (excursion) reports that identify all periods of time during which the pressure drop across the baghouse did not comply with the allowable range specified above.
3. The permittee shall submit quarterly deviation (excursion) reports to the USEPA and the Ohio EPA (appropriate DO or LAA) if any of the used oil exceeds the used oil specifications in this permit. An identification number from USEPA shall be obtained prior to the combustion of any used oil.

Before the permittee accepts the first shipment of any off-specification used oil from a marketer, the permittee must provide the marketer a one-time, written and signed notice certifying that:

- a. The company has notified USEPA of its used oil management activities and that the notice included the location and description of those activities; and
- b. The company will burn the used oil only in an industrial furnace or boiler identified in 40 CFR Part 266.41(b) and OAC rule 3745-279-42.

A copy of each certification notice that the permittee sends to a marketer must be kept on file for a minimum of 5 years from the date it last received off-specification used oil from that marketer.

4. The permittee shall submit annual reports of the production rate and the total PM, OC, NO_x, SO₂ and CO emissions for this emissions units. These reports shall be submitted by April 15th of each year to the Director (District Office or Local Air Agency).
5. The permittee shall submit quarterly deviation (excursion) reports that (a) identify all days during which any abnormal visible particulate emissions were observed from the stack serving this

Issued: To be entered upon final issuance

- emissions unit, (b) identify all days during which any abnormal visible fugitive particulate emissions were observed from the rotary dryer, aggregate storage bins and cold aggregate elevator, load out and silo filling operations serving this emissions unit, and (c) describe any corrective actions taken to minimize the abnormal visible particulate and/or abnormal visible fugitive particulate emissions.
6. The permittee shall submit quarterly deviation (excursion) reports to the Director (the appropriate District Office or local air agency) which identify all exceedances of the RAP limitation specified above.
 7. The permittee shall submit quarterly deviation (excursion) reports to the Director (the appropriate District Office or local air agency) which identify each day when a fuel other than #2 fuel oil was burned in the emissions unit.
 8. The deviation (excursion) reports shall be submitted in accordance with the requirements specified in Part I - General Term and Condition A.2 of this permit.

E. Testing Requirements

1. Compliance Methods
Compliance with the emissions limitation(s) in section A.1 of these terms and conditions shall be determined in accordance with the following method(s):
 - a. Emission Limitation-
PE emissions when burning #2 oil shall not exceed 0.04 gr/dscf; CO emissions when burning #2 fuel oil shall not exceed 43.6 lbs/hr; NO_x emissions when burning #2 fuel oil shall not exceed 10.5 lbs/hr; SO₂ emissions when burning #2 fuel oil shall not exceed 1.84 lbs/hr; VOC emissions when burning #2 fuel oil shall not exceed 12.9 lbs/hr.

Applicable Compliance Method-

If required, compliance shall be based on conducting a stack test for this emissions unit in order to demonstrate compliance with the allowable mass emission rate for PM, CO, NO_x, VOC and SO₂.

The following test method(s) shall be employed to demonstrate compliance with the allowable emission rate(s) for:

PM, USEPA Reference Methods 1-5, of 40 CFR Part 60, Appendix A.

CO, USEPA Reference Methods 1-4 and 10 of 40 CFR Part 60, Appendix A.

NO_x, USEPA Reference Methods 1-4 and 7 or 7 E of 40 CFR Part 60, Appendix A.

VOC, USEPA Reference Methods 1-4 and 18 and/or 25 of 40 CFR Part 60, Appendix A.

SO₂, USEPA Reference Methods 1-4 and 6 or 6C of 40 CFR Part 60, Appendix A.

The test shall be conducted while the emissions unit is operating at or near maximum capacity and burning only #2 oil for PM, CO, NO_x, VOC, and SO₂ and employing RAP to verify VOC emissions, unless otherwise specified or approved by the Ohio EPA District Office or local air agency.

Not later than 30 days prior to the proposed test date(s), the permittee shall submit an "Intent to Test" notification. The "Intent to Test" notification shall describe in detail the proposed

Butler

PTI A

Emissions Unit ID: **P901**

Issued: To be entered upon final issuance

test methods and procedures, the emissions unit operating parameters, the time(s) and dates(s) of the test(s), and the person(s) who will be conducting the test(s). Failure to submit such notification for review and approval prior to the test(s) may result in the field office's refusal to accept the results of the emissions test(s).

Personnel from the Ohio EPA District Office or local air agency shall be permitted to witness the test(s), examine the testing equipment and acquire data and information regarding the emissions unit operating parameters.

A comprehensive written report on the results of the emissions test(s) shall be submitted 30 days following completion of the test(s). The permittee may request additional time for the submittal of the written report, where warranted, with prior approval from the appropriate Ohio EPA District Office or local air agency.

- b. Emission Limitation -
Particulate emissions from the stack shall not exceed 5.16 tons/yr, on a 12-month rolling basis.

Applicable Compliance Method: Compliance with the annual emissions limitation shall be determined by multiplying the observed emission rate from the most recent emissions testing, in pounds of PE per ton of asphalt produced, by the actual rolling 12 month summation of asphalt produced, in tons per rolling 12-month period (as derived from the records required by term and condition C.1 above), and dividing by 2000 lbs/ton.

- c. Emissions Limitation-
CO emissions when burning #2 fuel oil shall not exceed 27.2 tons/yr, on a 12-month rolling basis.

Applicable Compliance Method: Compliance with the annual emissions limitation shall be determined by multiplying the observed emission rate from the most recent emissions testing, in pounds of CO per ton of asphalt produced, by the actual rolling 12 month summation of asphalt produced, in tons per rolling 12-month period (as derived from the records required by term and condition C.1 above), and dividing by 2000 lbs/ton.

- d. Emissions Limitation-
NO_x emissions when burning #2 oil shall not exceed 6.54 tons/yr, on a 12-month rolling basis.

Applicable Compliance Method: Compliance with the annual emissions limitation shall be

Emissions Unit ID: P901

determined by multiplying the observed emission rate from the most recent emissions testing, in pounds of NOx per ton of asphalt produced, by the actual rolling 12 month summation of asphalt produced, in tons per rolling 12-month period (as derived from the records required by term and condition C.1 above), and dividing by 2000 lbs/ton.

- e. SO₂ emissions when burning #2 oil shall not exceed 1.15 tons/yr, on a 12-month rolling basis.

Applicable Compliance Method: Compliance with the annual emissions limitation shall be determined by multiplying the observed emission rate from the most recent emissions testing,

in pounds of SO₂ per ton of asphalt produced, by the actual rolling 12 month summation of asphalt produced, in tons per rolling 12-month period (as derived from the records required by term and condition C.1 above), and dividing by 2000 lbs/ton.

- f. Emission Limitation-
VOC emissions from this emissions unit when burning #2 fuel oil shall not exceed 8.05 tons/yr, on a 12-month rolling basis.

Applicable Compliance Method: Compliance with the annual emissions limitation shall be determined by multiplying the observed emission rate from the most recent emissions testing, in pounds of VOC per ton of asphalt produced, by the actual rolling 12 month summation of asphalt produced, in tons per rolling 12-month period (as derived from the records required by term and condition C.1 above), and dividing by 2000 lbs/ton.

- g. Emission Limitation -
Fugitive particulate emissions shall not exceed 0.19 ton/yr, on a 12-month rolling basis.

Applicable Compliance Method -

Compliance with the annual fugitive particulate emissions shall be assumed based upon the following worst case calculations:

Fugitive particulate emissions from the hot end are calculated as follows

$$\begin{aligned} & \text{Silo filling (343,750 tons/yr of material/yr x 0.00058 lb PM/ton x ton/2000 lbs) +} \\ & \text{Plant Load Out (343,750 tons/yr of asphalt produced/yr x 0.00052 lb PM/ton x ton/2000} \\ & \text{lbs)} \\ & = 0.19 \text{ ton/yr particulate} \end{aligned}$$

The emission factors in the above equations are derived from AP-42, Fifth Edition, Table

Butler

PTI A

Emissions Unit ID: **P901**

Issued: To be entered upon final issuance

11.1-14 (3/04).

- h. Emission Limitation -
Fugitive VOC emissions shall not exceed 2.75 tons/yr, on a 12-month rolling basis.

Applicable Compliance Method -
Compliance with the annual fugitive VOC emissions shall be assumed based upon the following worst case calculations:

Fugitive VOC emissions from the hot end are calculated as follows
Silo filling (343,750 tons/yr of material/yr x 0.012 lb VOC/ton x ton/2000 lbs) +
Plant Load Out (343,750 tons/yr of asphalt produced/yr x 0.004 lb VOC/ton x ton/2000 lbs)
= 2.75 tons VOC

The emission factors in the above equations are derived from AP-42, Fifth Edition, Table 11.1-14 (3/04).

- i. Emissions Limitation-
20 percent opacity as a 6-minute average, from the stack

Applicable Compliance Method-
Compliance shall be demonstrated through visible emissions observations in accordance with OAC rule 3745-17-03(B)(1).

- j. Emission Limitation-
20 percent opacity as a 3-minute average, from fugitives

Applicable Compliance Method-
Compliance shall be demonstrated through visible emissions observations in accordance with OAC rule 3745-17-03(B)(3).

F. Miscellaneous Requirements

1. *This administrative modification is a modification of permit to install (PTI) 08-3785 issued on April 1, 1998 and modified on July 8, 1999 and results in the following emissions changes: for PM emissions, -2.1 TPY, for CO emissions +19.94, for VOC emissions - 5.95 TPY, for NOx emissions -8.69 TPY, for SO2 emissions -10.23 TPY. The terms and conditions of this permit supercede the two previous modifications of PTI 08-3785.

Butler

PTI A

Emissions Unit ID: **P901**

Issued: To be entered upon final issuance

2. The Terms and Conditions of Sections A, B, C, D and E are federally enforceable
3. Pursuant to OAC rule 3745-31-03(A)(1)(p), the permittee of a portable emissions unit may relocate within the State of Ohio without first obtaining a permit to install (PTI) providing certain criteria are met. The portable emissions unit shall meet one of the two following scenarios in order to qualify for this PTI exemption for the new location:
 - a. The following determinations have been documented, pursuant to OAC rule 3745-31-03(A)(1)(p)(i):
 - i. the portable emissions unit is equipped with the best available technology for such portable emissions unit;
 - ii. the portable emissions unit is operating pursuant to a currently effective permit to operate (PTO) or registration status;
 - iii. the applicant has provided proper notice of intent to relocate the portable emissions unit to Regional Air Pollution Control Agency (RAPCA) and the appropriate field office having jurisdiction over the new site within a minimum of 30 days prior to the scheduled relocation; and
 - iv. in Regional Air Pollution Control Agency's (RAPCA) and the appropriate field office's (having jurisdiction over the new site) judgement, the proposed site is acceptable under OAC rule 3745-15-07.
 - b. In the alternative, pursuant to OAC rule 3745-31-03(A)(1)(p)(ii), the permittee of a portable emissions unit may relocate within the State of Ohio without first obtaining a PTI, providing the following criteria of OAC rule 3745-31-05(E) are met:
 - i. the portable emissions unit permittee possesses an Ohio EPA PTI, PTO or registration status;
 - ii. the portable emissions unit is equipped with best available technology;
 - iii. the portable emissions unit owner has identified the proposed site to Ohio EPA;
 - iv. Ohio EPA has determined that the portable emissions unit, at the proposed site, will have an acceptable environmental impact;
 - v. a public notice, consistent with OAC Chapter 3745-47, is published in the county

where the proposed site is located;

- vi. the owner of the proposed site has provided the portable emissions unit owner with approval or equivalent declaration that it is acceptable to the site owner to move the portable emissions unit to this proposed site; and
- vii. the portable emissions unit owner has provided Ohio EPA with 15 days written notice of the relocation.

Any site approvals issued by the Ohio EPA, pursuant to OAC rule 3745-31-03(A)(1)(p)(ii), shall be valid for no longer than 3 years and are subject to renewal.

In order for the Regional Air Pollution Control Agency (RAPCA) and the appropriate field office having jurisdiction over the new site to determine compliance with all of the above criteria, the permittee of the portable emissions unit must file a " Notice of Intent to Relocate", within the specified time frame (30 or 15 days) prior to the relocation of the emissions unit with Regional Air Pollution Control Agency (RAPCA) and the appropriate field office having jurisdiction over the new site. Upon receipt of the notice, Regional Air Pollution Control Agency (RAPCA), and/or appropriate field office having jurisdiction over the new site, will evaluate the request in accordance with the above criteria.