

Facility ID: 0679000287 Issuance type: Final State Permit To Operate

This version of facility specific terms and conditions was converted from a database format to an HTML file during an upgrade of the Ohio EPA, Division of Air Pollution Control's permitting software. Every attempt has been made to convert the terms and conditions to look and substantively conform to the permit issued or being drafted in STARS. However, the format of the terms may vary slightly from the original. In addition, although it is not expected, there is a slight possibility that a term and condition may have been inadvertently "left out" of this reproduction during the conversion process. Therefore, if this version is to be used as a starting point in drafting a new version of a permit, it is imperative that the entire set of terms and conditions be reviewed to ensure they substantively mimic the issued permit. The official version of any permit issued final by Ohio EPA is kept in the Agency's Legal section. The Legal section may be contacted at (614) 644-3037.

In addition to the terms and conditions, hyperlinks have been inserted into the document so you may more readily access the section of the document you wish to review.

Finally, the term language under "Part II" and before "A. Applicable Emissions Limitations..." has been added to aid in document conversion, and was not part of the original issued permit.

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION

Facility ID: 0679000287 Emissions Unit ID: R001 Issuance type: Final State Permit To Operate

[Go to the top of this document](#)

Part II - Special Terms and Conditions

This permit document constitutes a permit-to-install issued in accordance with ORC 3704.03(F) and a permit-to-operate issued in accordance with ORC 3704.03(G).

1. For the purpose of a permit-to-install document, the emissions unit terms and conditions identified below are federally enforceable with the exception of those listed below which are enforceable under state law only.
 - (a) None.
2. For the purpose of a permit-to-operate document, the emissions unit terms and conditions identified below are enforceable under state law only with the exception of those listed below which are federally enforceable.
 - (a) None.

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
Spray Booth for Staining & Finishing	OAC 3745-31-05 (PTI # 06-5688)	On any day in which photochemically reactive materials (PRM) are employed, emissions of organic compounds (OC) shall not exceed 8 pounds per hour (lbs/hr) nor 40 pounds per day (lbs/day). OC emissions from all coatings and cleanup materials shall not exceed 7.3 tons per year (tpy).
	OAC 3745-21-07 (G)(2)	Compliance with the emission limits from OAC rule 3745-21-07(G)(2) shall satisfy the best available technology (BAT) requirement of OAC rule 3745-31-05.

2. **Additional Terms and Conditions**
 - (a) None

B. Operational Restrictions

1. None

C. Monitoring and/or Record Keeping Requirements

1. The permittee shall collect and record the following information for each day [except (k), (l), & (m) which shall be compiled annually] for the coating operation:

The permittee shall collect and record the following information for each day for the coating operation:

- (a) The company identification for each coating and photochemically reactive cleanup material employed.
- (b) The number of gallons of each coating and photochemically reactive cleanup material employed.
- (c) For each day during which a PRM is employed, the number of gallons of each coating and photochemically reactive cleanup material employed each hour of the day.
- (d) The OC content of each coating and photochemically reactive cleanup material, in pounds per gallon (lbs/gal).
- (e) For each day during which a photochemically reactive material is employed, the total OC emission rate for all coatings and photochemically reactive cleanup materials, in lbs/day [i.e. (b)x(d)].
- (f) For each day during which a PRM is employed, the total OC emission rate for all coatings and photochemically reactive cleanup materials, in pounds per hour for each hour of the day [i.e. (c)x(d)].
- (g) The company identification for each nonphotochemically reactive cleanup material employed.
- (h) The number of gallons of each nonphotochemically reactive cleanup material employed.
- (i) The OC content of each nonphotochemically reactive cleanup material employed, in lbs/gal.
- (j) The total OC emission rate for all nonphotochemically reactive cleanup materials employed, in lbs/day [i.e. (h)x(i)].

- (l) The total year-to-date OC emission rate for all coatings and cleanup materials for all days during which PRMs are not employed, in lbs/yr [i.e. sum of (j)], for all operating days in the calendar year].
- (l) The total year-to-date OC emission rate for all coatings and cleanup materials for all days during which PRMs are employed, in lbs/yr [i.e. sum of (e)], for all operating days in the calendar year].
- (m) The total year-to-date OC emission rate for all coatings and cleanup materials for all days during which PRMs and/or non-PRMs are employed, in tpy [i.e. {(k) + (l)}, in lbs/yr, divided by 2000 lbs/ton].

[Note: The coating information must be for the coatings as employed, including any thinning solvents added at the emissions unit. Also, the definitions of "photochemically reactive" and "nonphotochemically reactive" are based upon OAC rule 3745-21-01(C)(5).]

2. The permit to install for this emissions unit (R001) was evaluated based on the actual materials (typically coatings and cleanup materials) and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant(s):

Pollutant: Methyl Ethyl Ketone

TLV (mg/m³): 590,000
 Maximum Hourly Emission Rate (lbs/hr): 2.7
 Predicted 1-Hour MAGLC at Fenceline (ug/m³): 2491
 MAGLC (ug/m³): 14,048

Pollutant: Isobutyl Acetate

TLV (mg/m³): 713,000
 Maximum Hourly Emission Rate (lbs/hr): 1.3
 Predicted 1-Hour MAGLC at Fenceline (ug/m³): 1,205
 MAGLC (ug/m³): 16,976

Pollutant: Xylene

TLV (mg/m³): 434,000
 Maximum Hourly Emission Rate (lbs/hr): 5.2
 Predicted 1-MAGLC at Fenceline (ug/m³): 4,818
 MAGLC (ug/m³): 10,333

Pollutant: 1,2,4 Trimethylbenzene

TLV (mg/m³): 123,000
 Maximum Hourly Emission Rate (lbs/hr): 2.03
 Predicted 1-Hour MAGLC at Fenceline (ug/m³): 1,881
 MAGLC (ug/m³): 2,929

Pollutant: Ethylbenzene

TLV (mg/m³): 434,000
 Maximum Hourly Emission Rate (lbs/hr): 1.4
 Predicted 1-Hour MAGLC at Fenceline (ug/m³): 1,297
 MAGLC (ug/m³): 10,333
 Pollutant: Toluene

TLV (mg/m³): 188,000
 Maximum Hourly Emission Rate (lbs/hr): 1.6
 Predicted 1-Hour MAGLC at Fenceline (ug/m³): 1,482
 MAGLC (ug/m³): 4,476

Pollutant: Butyl Acetate

TLV (mg/m³): 713,000
 Maximum Hourly Emission Rate (lbs/hr): 2.5
 Predicted 1-Hour MAGLC at Fenceline (ug/m³): 2,316
 MAGLC (ug/m³): 16,976

Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be still satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

- a. changes in the composition of the materials used (typically for coatings or cleanup materials), or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value previously modeled;
- b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and
- c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow,

changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01(VV)(1)(a)(ii), and a modification of the existing permit to install will not be required. If the change(s) is (are) defined as a modification under other provisions of the modification definition (other than (VV)(1)(a)(ii)), then the permittee shall obtain a final permit to install prior to the change.

The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy:"

- a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
- b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and
- c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

D. Reporting Requirements

1. The permittee shall submit deviation (excursion) reports which include the following information:
For the days during which a photochemically reactive material was employed, an identification of each day during which the average hourly OC emissions from the coatings and photochemically reactive cleanup materials exceeded 8 lbs/hr, and the actual average hourly OC emissions for each such day.
For the days during which a photochemically reactive material was employed, an identification of each day during which the OC emissions from the coatings and photochemically reactive cleanup materials exceeded 40 lbs/day, and the actual OC emissions for each such day.

These reports shall be submitted within 30 days after the occurrence.
2. The permittee shall also submit annual reports which specify the total OC emissions from this emissions unit for the previous calendar year. These reports shall be submitted to the appropriate Ohio EPA District Office (Southeast District Office) or local air agency by January 31 of each year.

E. Testing Requirements

1. Compliance with the emission limitations of 8 lbs/hr of OC, 40 lbs/day of OC, and 7.3 tpy of OC shall be based upon the record keeping specified in C.1.f, C.1.e, and C.1.m, respectively.

F. Miscellaneous Requirements

1. None