



State of Ohio Environmental Protection Agency

**RE: FINAL PERMIT TO INSTALL
MONTGOMERY COUNTY**

CERTIFIED MAIL

Street Address:

122 S. Front Street

Lazarus Gov. Center **TELE:** (614) 644-3020 **FAX:** (614) 644-2329

Mailing Address:

Lazarus Gov. Center
P.O. Box 1049

Application No: 08-04467

DATE: 6/17/2003

Voss Village Cadillac
Jack Leet
766 Miamisburg-Centerville Rd
Centerville, OH 454596523

Enclosed please find an Ohio EPA Permit to Install which will allow you to install the described source(s) in a manner indicated in the permit. Because this permit contains several conditions and restrictions, I urge you to read it carefully.

The Ohio EPA is urging companies to investigate pollution prevention and energy conservation. Not only will this reduce pollution and energy consumption, but it can also save you money. If you would like to learn ways you can save money while protecting the environment, please contact our Office of Pollution Prevention at (614) 644-3469.

You are hereby notified that this action by the Director is final and may be appealed to the Ohio Environmental Review Appeals Commission pursuant to Chapter 3745.04 of the Ohio Revised Code. The appeal must be in writing and set forth the action complained of and the grounds upon which the appeal is based. It must be filed within thirty (30) days after the notice of the Directors action. A copy of the appeal must be served on the Director of the Ohio Environmental Protection Agency within three (3) days of filing with the Commission. An appeal may be filed with the Environmental Review Appeals Commission at the following address:

Environmental Review Appeals Commission
309 South Fourth Street, Room 222
Columbus, Ohio 43215

Sincerely,

Michael W. Ahern, Supervisor
Field Operations and Permit Section
Division of Air Pollution Control

cc: USEPA

RAPCA



**Permit To Install
Terms and Conditions**

**Issue Date: 6/17/2003
Effective Date: 6/17/2003**

FINAL PERMIT TO INSTALL 08-04467

Application Number: 08-04467
APS Premise Number: 0857813236
Permit Fee: **\$600**
Name of Facility: Voss Village Cadillac
Person to Contact: Jack Leet
Address: 766 Miamisburg-Centerville Rd
Centerville, OH 454596523

Location of proposed air contaminant source(s) [emissions unit(s)]:
**650 Miamisburg-Centerville Rd
Centerville, Ohio**

Description of proposed emissions unit(s):
3 misc metal parts spray booth.

The above named entity is hereby granted a Permit to Install for the above described emissions unit(s) pursuant to Chapter 3745-31 of the Ohio Administrative Code. Issuance of this permit does not constitute expressed or implied approval or agreement that, if constructed or modified in accordance with the plans included in the application, the above described emissions unit(s) of environmental pollutants will operate in compliance with applicable State and Federal laws and regulations, and does not constitute expressed or implied assurance that if constructed or modified in accordance with those plans and specifications, the above described emissions unit(s) of pollutants will be granted the necessary permits to operate (air) or NPDES permits as applicable.

This permit is granted subject to the conditions attached hereto.

Ohio Environmental Protection Agency

Director

Part I - GENERAL TERMS AND CONDITIONS

A. Permit to Install General Terms and Conditions

1. Compliance Requirements

The emissions unit(s) identified in this Permit to Install shall remain in full compliance with all applicable State laws and regulations and the terms and conditions of this permit.

2. Reporting Requirements

The permittee shall submit required reports in the following manner:

- a. Reports of any required monitoring and/or recordkeeping information shall be submitted to the appropriate Ohio EPA District Office or local air agency.
- b. Except as otherwise may be provided in the terms and conditions for a specific emissions unit, quarterly written reports of (a) any deviations (excursions) from emission limitations, operational restrictions, and control device operating parameter limitations that have been detected by the testing, monitoring, and recordkeeping requirements specified in this permit, (b) the probable cause of such deviations, and (c) any corrective actions or preventive measures which have been or will be taken, shall be submitted to the appropriate Ohio EPA District Office or local air agency. If no deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted quarterly, i.e., by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters. (These quarterly reports shall exclude deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06.)

3. Records Retention Requirements

Each record of any monitoring data, testing data, and support information required pursuant to this permit shall be retained for a period of five years from the date the record was created. Support information shall include, but not be limited to, all calibration and maintenance records and all original strip-chart recordings for continuous monitoring instrumentation, and copies of all reports required by this permit. Such records may be maintained in computerized form.

4. Inspections and Information Requests

The Director of the Ohio EPA, or an authorized representative of the Director, may, subject to the safety requirements of the permittee and without undue delay, enter upon the premises of this source at any reasonable time for purposes of making inspections, conducting tests, examining records or reports pertaining to any emission of air contaminants, and determining compliance with any applicable State air pollution laws and regulations and the terms and conditions of this permit. The permittee shall furnish to the Director of the Ohio EPA, or an authorized

representative of the Director, upon receipt of a written request and within a reasonable time, any information that may be requested to determine whether cause exists for modifying, reopening or revoking this permit or to determine compliance with this permit. Upon verbal or written request, the permittee shall also furnish to the Director of the Ohio EPA, or an authorized representative of the Director, copies of records required to be kept by this permit.

5. Scheduled Maintenance/Malfunction Reporting

Any scheduled maintenance of air pollution control equipment shall be performed in accordance with paragraph (A) of OAC rule 3745-15-06. The malfunction of any emissions units or any associated air pollution control system(s) shall be reported to the appropriate Ohio EPA District Office or local air agency in accordance with paragraph (B) of OAC rule 3745-15-06. Except as provided in that rule, any scheduled maintenance or malfunction necessitating the shutdown or bypassing of any air pollution control system(s) shall be accompanied by the shutdown of the emissions unit(s) that is (are) served by such control system(s).

6. Permit Transfers

Any transferee of this permit shall assume the responsibilities of the prior permit holder. The appropriate Ohio EPA District Office or local air agency must be notified in writing of any transfer of this permit.

7. Air Pollution Nuisance

The air contaminants emitted by the emissions units covered by this permit shall not cause a public nuisance, in violation of OAC rule 3745-15-07.

8. Termination of Permit to Install

This Permit to Install shall terminate within eighteen months of the effective date of the Permit to Install if the owner or operator has not undertaken a continuing program of installation or modification or has not entered into a binding contractual obligation to undertake and complete within a reasonable time a continuing program of installation or modification. This deadline may be extended by up to 12 months if application is made to the Director within a reasonable time before the termination date and the party shows good cause for any such extension.

9. Construction of New Sources(s)

The proposed emissions unit(s) shall be constructed in strict accordance with the plans and application submitted for this permit to the Director of the Ohio Environmental Protection Agency. There may be no deviation from the approved plans without the express, written approval of the Agency. Any deviations from the approved plans or the above conditions may lead to such sanctions and penalties as provided under Ohio law. Approval of these plans does not constitute an assurance that the proposed facilities will operate in compliance with all Ohio laws and regulations. Additional facilities shall be installed upon orders of the Ohio

Voss Village Cadillac
PTI Application: 08-04467
Issued: 6/17/2003

Facility ID: 0857813236

Environmental Protection Agency if the proposed sources cannot meet the requirements of this permit or cannot meet applicable standards.

If the construction of the proposed emissions unit(s) has already begun or has been completed prior to the date the Director of the Environmental Protection Agency approves the permit application and plans, the approval does not constitute expressed or implied assurance that the proposed facility has been constructed in accordance with the approved plans. The action of beginning and/or completing construction prior to obtaining the Director's approval constitutes a violation of OAC rule 3745-31-02. Furthermore, issuance of the Permit to Install does not constitute an assurance that the proposed source will operate in compliance with all Ohio laws and regulations. Approval of the plans in any case is not to be construed as an approval of the facility as constructed and/or completed. Moreover, issuance of the Permit to Install is not to be construed as a waiver of any rights that the Ohio Environmental Protection Agency (or other persons) may have against the applicant for starting construction prior to the effective date of the permit. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed facilities cannot meet the requirements of this permit or cannot meet applicable standards.

10. Public Disclosure

The facility is hereby notified that this permit, and all agency records concerning the operation of this permitted source, are subject to public disclosure in accordance with OAC rule 3745-49-03.

11. Applicability

This Permit To Install is applicable only to the emissions unit(s) identified in the Permit To Install. Separate Permit To Install for the installation or modification of any other emissions unit(s) are required for any emissions unit for which a Permit To Install is required.

12. Best Available Technology

As specified in OAC Rule 3745-31-05, all new sources must employ Best Available Technology (BAT). Compliance with the terms and conditions of this permit will fulfill this requirement.

13. Source Operation and Operating Permit Requirements After Completion of Construction

This facility is permitted to operate each source described by this Permit to Install for a period of up to one year from the date the source commenced operation. This permission to operate is granted only if the facility complies with all requirements contained in this permit and all applicable air pollution laws, regulations, and policies. Pursuant to OAC Chapter 3745-35, the permittee shall submit a complete operating permit application within ninety (90) days after commencing operation of the emissions unit(s) covered by this permit.

Voss Village Cadillac
 PTI Application: 08-04467
 Issued: 6/17/2003

Facility ID: 0857813236

14. Construction Compliance Certification

The applicant shall provide Ohio EPA with a written certification (see enclosed form) that the facility has been constructed in accordance with the Permit to Install application and the terms and conditions of the Permit to Install. The certification shall be provided to Ohio EPA upon completion of construction but prior to startup of the source.

15. Fees

The permittee shall pay fees to the Director of the Ohio EPA in accordance with ORC section 3745.11 and OAC Chapter 3745-78. The permittee shall pay all applicable Permit to Install fees within 30 days after the issuance of this Permit to Install.

B. Permit to Install Summary of Allowable Emissions

The following information summarizes the total allowable emissions, by pollutant, based on the individual allowable emissions of each air contaminant source identified in this permit.

**SUMMARY (for informational purposes only)
 TOTAL PERMIT TO INSTALL ALLOWABLE EMISSIONS**

<u>Pollutant</u>	<u>Tons Per Year</u>
VOC	7.84

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

- 1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
K001 - Spray Booth 1 - Automotive and Truck Repair (See Section A.2.bc)	OAC rule 3745-31-05(A)(3)	Volatile Organic Compounds (VOC) emissions shall not exceed the following: 86.7 pounds per hour, excluding cleanup, 40 pounds per day and 5.43 tons per year (TPY), including cleanup.
	OAC rule 3745-21-09(U)(1)	The requirements established pursuant to this rule also includes compliance with the requirements of OAC rule 3745-35-07(B).
	OAC rule 3745-35-07(B) Synthetic Minor to Avoid Title V permitting requirements and the Maximum Achievable Control Technology (MACT) regulation for Miscellaneous Metal Parts Coating under 40 Code of Federal Regulation (CFR) Part 63, Subpart MMMM.	This operation is exempt from the requirements of this rule pursuant to OAC rule 3745-21-09 (U)(2)(c).
		See Section A.2.ab.

2. Additional Terms and Conditions

- 2.a The 6.7 pounds of VOC per hour limitation was established for PTI purposes to reflect the potential to emit for this emissions unit. Therefore, it is not necessary to develop record keeping and/or reporting requirements to ensure compliance with this limitation.

- 2.ab** The emissions of Hazardous Air Pollutants (HAPs), as identified in section 112(b) of Title III of the Clean Air Act, from this facility shall be less than 9.9 TPY for any single HAP and 24.9 TPY for any combination of HAPs, based on rolling, 12-month summations.
- 2.bc** Prior to this permitting action, this emission unit was a 'de minimis' source pursuant to OAC rule 3745-15-05. This permitting action is required because the permittee is requesting emission increases over the 'de minimis' source levels pursuant to OAC rule 3745-15-05, thereby requiring the permittee to apply for and obtain a new air permit to install for the increase in emissions.

B. Operational Restrictions

None

C. Monitoring and/or Recordkeeping Requirements

1. The permittee shall collect and record the following information each daymonth for this emission unit to determine annual VOC emissions:
 - a. The name and identification number of each coating employed.
 - b. The volume, in gallons, of each coating employed.
 - c. The VOC content of each coating, as applied, in pounds per gallon.
 - d. The name and identification of each cleanup material employed.
 - e. The number of gallons of each cleanup material employed.
 - f. The number of gallons of each cleanup material drummed for shipment off-site.
 - g. The VOC content of each cleanup material, in pounds per gallon.
 - h. The total number of hours the emissions unit was in operation.
 - ih. The total VOC emissions from all coatings and cleanup materials employed, in lbs/daypounds or ton, (i.e., the summation of the products of C.1.b X C.1.c for each coating material plus the sum of the products of [(C.1.e - C.1.f) X C.1.g] for each cleanup material).
 - j. The average hourly VOC emission rate for all coatings and cleanup materials, (i.e., (C.1.i)/(C.1.h), in lbs/hr(average)).

2. The permittee shall collect and record the following information each month for emissions units K001, K002 and K003:
 - a. The name and identification of each coating material employed.
 - b. The individual Hazardous Air Pollutant (HAP)* content for each HAP of each coating material, in pounds of individual HAP per gallon, as applied..
 - c. The total combined HAP content of each coating material, in pounds of combined HAPs per gallon, as applied (the sum of all the individual HAP contents from C.2.b).
 - d. The number of gallons of each coating material employed.
 - e. The name and identification of each cleanup material employed.
 - f. The individual HAP content of each cleanup material, in pounds of individual HAP per gallon of cleanup material, as applied.
 - g. The total combined HAP content of each cleanup material, in pounds of combined HAPs per gallon of cleanup material, as applied (the sum of all the individual HAP contents form C.2.f).
 - h. The number of gallons of each cleanup material employed.
 - i. The number of gallons of each cleanup material drummed for shipment off-site.
 - j. The total individual HAP emission rate, in tons per month, for each HAP (i.e., for each HAP, the sum of the products of C.2.b X C.2.d for each coating material plus the sum of the products of [C.2.f X (C.2.h- C.2.i)] for each cleanup material).
 - k. The total combined HAP emission rate, in tons per month, for all HAPs employed (i.e., the sum of the products of C.2.c X C.2.d for each coating material plus the sum of the products of [C.2.g X (C.2.h - C.2.i)] for each cleanup material).
 - l. The cumulative monthly total, in tons/month, for the first twelve months following the issuance of this permit to install and the updated rolling twelve month total thereafter, of the total individual HAPs for all of the HAPs employed at this facility.
 - m. The cumulative monthly total, in tons/month, for the first twelve months following the issuance of this permit to install and the updated rolling twelve month total thereafter, of

Voss Village Cadillac
PTI Application: 08 04467
Issued

Facility ID: 0857813236

Emissions Unit ID: K001

the total combined HAPs for all of the HAPs employed at this facility.

* A listing of the HAPs can be found in Section 112 (b) of the Clean Air Act or can be obtained by contacting Ohio EPA field office or local agency contact. This information does not have to be kept on a line-by-line basis.

3. The permit to install for this emissions unit K001 was evaluated based on the actual materials (typically coatings and cleanup materials) for emissions units K001 through K003 and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approval model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarized the results of the modeling for the "worst-case" pollutant(s).

Pollutant: Heptane

TLV(mg/m³): 60.6

Maximum Hourly Emission Rate (lbs/hr): 12.03

Predicted 1-Hour Maximum Ground-Level
Concentration (ug/m³): 1129.62

MAGLC(ug/m³): 1,444

Physical changes to or changes in the method of operation of the emissions unit after its installation of modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the Permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

- a. changes in the composition of the materials used (typically for coatings or cleanup materials), or the use of the new materials, that would result in the emission of a compound with a lower Threshold Limit Value(TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)", than the lowest TLV value previously modeled;
- b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and
- c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01(VV)(1)(a)(ii), and a modification of the existing permit to install will not be required. If the change(s) is (are) defined as a modification under other provisions of the modification definition (other than (VV)(1)(a)(ii)), then the permittee shall obtain a final permit to install prior to the change.

Emissions Unit ID: **K001**

4. The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy":
 - a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
 - b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and
 - c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

D. Reporting Requirements

1. In accordance with Section A.2. of the General Terms and Conditions of this permit, the permittee shall submit quarterly deviation (excursion) reports that include the following:
 - a. An identification of each day during which the volatile organic compound emissions from the coatings and cleanup materials exceeded 8 pounds per hour, and the actual average volatile organic compound emissions for each such hour.
 - b. An identification of each day during which the volatile organic compound emissions from the coatings and cleanup materials exceeded 40 pounds per day, and the actual volatile organic compound emissions for each such day.
 - ca. An identification of each month during which the rolling, 12-month individual facility HAP emission rate exceeded the 9.9 TPY rolling, 12-month individual facility HAP emission limitation, and the actual rolling, 12-month individual facility HAP emission rate for each such month.
 - db. An identification of each month during which the rolling, 12-month combined facility HAP emission rate exceeded the 24.9 TPY rolling, 12-month combined facility HAP emission limitation, and the actual rolling, 12-month combined facility HAP emission rate for each such month.
2. The permittee shall submit annual reports which specify the total VOC emissions from this emissions unit for the previous calendar year. These reports shall be submitted by January 31 of each year.

E. Testing Requirements

1. Compliance with the specified emission limitations in Section A.1. of this permit shall be demonstrated in accordance with the following methods:

- a. Emission Limitation-
8.06.7 pounds of VOC per hour, excluding cleanup
- Applicable Compliance Method-
Compliance shall be based upon the maximum hourly coating usage rate multiplied by the maximum VOC content. record keeping requirements specified in Section C.1. of this permit.
- b. Emission Limitation-
40 pounds of VOC per day
- Applicable Compliance Method-
Compliance shall be based upon the record keeping requirements specified in Section C.1. of this permit.
- cb. Emission Limitation-
5.43 TPY VOC, including cleanup materials
- Applicable Compliance Method-
Compliance shall be based upon the record keeping requirements specified in Section C.1. and C.3. of this permit and shall be the summation of the 12 monthly VOC emission rates divided by 2000 lbs/ton.
- dc. Emission Limitation-
9.9 TPY of an individual HAP, based on a 12-month rolling summation
- Applicable Compliance Method-
Compliance shall be based upon the record keeping requirements specified in Sections C.2. of this permit.
- ed. Emission Limitation-
24.9 TPY of any combination of HAPs, based on a 12-month rolling summation
- Applicable Compliance Method-
Compliance shall be based upon the record keeping requirements specified in Sections C.2. of this permit.

F. Miscellaneous Requirements

1. The terms and conditions from Section A.2.ab., Section C.1., Section C.2. and Section D.1. are federally enforceable.

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
K002 - Spray Booth 2 - Automotive and Truck Repair (See Section A.2.bc)	OAC rule 3745-31-05(A)(3)	Volatile Organic Compounds (VOC) emissions shall not exceed the following: 86.7 pounds per hour, excluding cleanup, 40 pounds per day, and 1.21 tons per year (TPY).
	OAC rule 3745-21-09(U)(1)	The requirements established pursuant to this rule also include compliance with the requirements of OAC rule 3745-35-07(B).
	OAC rule 3745-35-07(B) Synthetic Minor to Avoid Title V permitting requirements and the Maximum Achievable Control Technology (MACT) regulations for Miscellaneous Metal Parts Coating under 40 Code of Federal Regulation (CFR) Part 63, Subpart Mmmm.	This operation is exempt from the requirements of this rule pursuant to OAC rule 3745-21-09 (U)(2)(c).
		See Section A.2.ab.

2. Additional Terms and Conditions

- 2.a** The 6.7 pounds of VOC per hour limitation was established for PTI purposes to reflect the potential to emit for this emission unit. Therefore, it is not necessary to develop record keeping and/or reporting requirements to ensure compliance with this limitation.

- 2.ab** The emissions of Hazardous Air Pollutants (HAPs), as identified in section 112(b) of Title III of the Clean Air Act, from this facility shall be less than 9.9 TPY for any single HAP and 24.9 TPY for any combination of HAPs, based on rolling, 12-month summations.

- 2.bc** Prior to this permitting action, this emission unit was a 'de minimis' source pursuant to OAC rule 3745-15-05. This permitting action is required because the permittee is requesting emission increases over the 'de minimis' source levels pursuant to OAC rule 3745-15-05, thereby requiring the permittee to apply for and obtain a new air permit to install for the increase in emissions.

B. Operational Restrictions

None

C. Monitoring and/or Recordkeeping Requirements

1. The permittee shall collect and record the following information each daymonth for this emission unit to determine annual VOC emissions:
 - a. The name and identification number of each coating employed.
 - b. The volume, in gallons, of each coating employed.
 - c. The VOC content of each coating, as applied, in pounds per gallon.
 - d. The name and identification of each cleanup material employed.
 - e. The number of gallons of each cleanup material employed.
 - f. The number of gallons of each cleanup material drummed for shipment off-site.
 - g. The VOC content of each cleanup material, in pounds per gallon.
 - h. The total number of hours the emissions unit was in operation.
 - ih. The total VOC emissions from all coatings and cleanup materials employed, in pounds or ton, (i.e., the summation of the products of C.1.b X C.1.c for each coating material plus the sum of the products of [C.1.e - C.1.f] X C.1.g] for each cleanup material).
 - j. The average hourly VOC emission rate for all coatings and cleanup materials, (i.e, (C.1.i)/(C.1.h), in pounds per hour (average)).
2. The permittee shall collect and record the following information each month for emissions units K001, K002 and K003:

- a. The name and identification of each coating material employed.
- b. The individual Hazardous Air Pollutant (HAP)* content for each HAP of each coating material, in pounds of individual HAP per gallon, as applied..
- c. The total combined HAP content of each coating material, in pounds of combined HAPs per gallon, as applied (the sum of all the individual HAP contents from C.2.b).
- d. The number of gallons of each coating material employed.
- e. The name and identification of each cleanup material employed.
- f. The individual HAP content of each cleanup material, in pounds of individual HAP per gallon of cleanup material, as applied.
- g. The total combined HAP content of each cleanup material, in pounds of combined HAPs per gallon of cleanup material, as applied (the sum of all the individual HAP contents form C.2.f).
- h. The number of gallons of each cleanup material employed.
- i. The number of gallons of each cleanup material drummed for shipment off-site.
- j. The total individual HAP emission rate, in tons per month, for each HAP (i.e., for each HAP, the sum of the products of C.2.b X C.2.d for each coating material plus the sum of the products of [C.2.f X (C.2.h - C.2.i)] for each cleanup material).
- k. The total combined HAP emission rate, in tons per month, for all HAPs employed (i.e., the sum of the products of C.2.c X C.2.d for each coating material plus the sum of the products of [C.2.g X (C.2.h - C.2.i)] for each cleanup material).
- l. The cumulative monthly total, in tons/month, for the first twelve months following the issuance of this permit to install and the updated rolling twelve month total thereafter, of the total individual HAPs for all of the HAPs employed at this facility.
- m. The cumulative monthly total, in tons/month, for the first twelve months following the issuance of this permit to install and the updated rolling twelve month total thereafter, of the total combined HAPs for all of the HAPs employed at this facility.

* A listing of the HAPs can be found in Section 112 (b) of the Clean Air Act or can be obtained

Emissions Unit ID: **K002**

by contacting Ohio EPA field office or local agency contact. This information does not have to be kept on a line-by-line basis.

3. The permit to install for this emissions unit K001 was evaluated based on the actual materials (typically coatings and cleanup materials) for emissions units K001 through K003 and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approval model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarized the results of the modeling for the "worst-case" pollutant(s).

Pollutant: Heptane

TLV(mg/m³): 60.6

Maximum Hourly Emission Rate (lbs/hr):12.03

Predicted 1-Hour Maximum Ground-Level
Concentration (ug/m³): 1129.62

MAGLC(ug/m³): 1,444

Physical changes to or changes in the method of operation of the emissions unit after its installation of modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the Permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

- a. changes in the composition of the materials used (typically for coatings or cleanup materials), or the use of the new materials, that would result in the emission of a compound with a lower Threshold Limit Value(TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)", than the lowest TLV value previously modeled;
- b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and

- c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01(VV)(1)(a)(ii), and a modification of the existing permit to install will not be required. If the change(s) is (are) defined as a modification under other provisions of the modification definition (other than (VV)(1)(a)(ii)), then the permittee shall obtain a final permit to install prior to the change.

4. The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy":
 - a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
 - b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and
 - c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

D. Reporting Requirements

1. In accordance with Section A.2. of the General Terms and Conditions of this permit, the permittee shall submit quarterly deviation (excursion) reports that include the following:
 - a. An identification of each day during which the volatile organic compound emissions from the coatings and cleanup materials exceeded 8 pound per hour, and the actual average volatile organic compound emissions for each such hour.
 - b. An identification of each day during which the volatile organic compound emissions from the coatings and cleanup materials exceeded 40 pounds per day, and the actual volatile organic compound emissions for each such day.
 - ca. An identification of each month during which the rolling, 12-month individual facility HAP emission rate exceeded the 9.9 TPY rolling, 12-month individual facility HAP emission limitation, and the actual rolling, 12-month individual facility HAP emission rate for each such month.

- db. An identification of each month during which the rolling, 12-month combined facility HAP emission rate exceeded the 24.9 TPY rolling, 12-month combined facility HAP emission limitation, and the actual rolling, 12-month combined facility HAP emission rate for each such month.
- 2. The permittee shall submit annual reports which specify the total VOC emissions from this emission unit for the previous calendar year. These reports shall be submitted by January 31 of each year.

E. Testing Requirements

- 1. Compliance with the specified emission limitations in Section A.1. of this permit shall be demonstrated in accordance with the following methods:
 - a. Emission Limitation-
86.7 pounds of VOC per hour, excluding cleanup

Applicable Compliance Method-
Compliance shall be based upon the maximum hourly coating usage rate multiplied by the maximum VOC content. record keeping requirements specified in Section C.1. of this permit.
Emission Limitation-
40 pounds of VOC per day

Applicable Compliance Method-
Compliance shall be based upon the record keeping requirements specified in Section C.1. of this permit.
 - cb. Emission Limitation-
1.21 TPY VOC, including cleanup materials

Applicable Compliance Method-
Compliance shall be based upon the record keeping requirements specified in Section C.1. and C.3. of this permit and shall be the summation of the 12 monthly VOC emission rates divided by 2000 lbs/ton.

- dc. Emission Limitation-
9.9 TPY of an individual HAP, based on a 12-month rolling summation

Applicable Compliance Method-
Compliance shall be based upon the record keeping requirements specified in Sections C.2. of this permit.

- ed. Emission Limitation-
24.9 TPY of any combination of HAPs, based on a 12-month rolling summation

Applicable Compliance Method-
Compliance shall be based upon the record keeping requirements specified in Sections C.2. of this permit.

F. Miscellaneous Requirements

- 1. The terms and conditions from Section A.2.ab., Section C.1., Section C.2. and Section D.1. are federally enforceable.

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

- The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
K003 - Spray Booth 3 - Automotive and Truck Repair (See Section A.2.bc)	OAC rule 3745-31-05(A)(3)	Volatile Organic Compounds (VOC) emissions shall not exceed the following: 86.7 pounds per hour, excluding cleanup 40 pounds per day, and 1.21 tons per year (TPY).
	OAC rule 3745-21-09(U)(1)	The requirements established pursuant to this rule also include compliance with the requirements of OAC rule 3745-35-07(B).
	OAC rule 3745-35-07(B) Synthetic Minor to Avoid Title V permitting requirements and the Maximum Achievable Control Technology (MACT) regulation for Miscellaneous Metal Parts Coating under 40 Code of Federal Regulation (CFR) Part 63, Subpart Mmmm.	This operation is exempt from the requirements of this rule pursuant to OAC rule 3745-21-09 (U)(2)(c).
		See Section A.2.ab.

2. Additional Terms and Conditions

- 2.a** The 6.7 pounds of VOC per hour limitation was established for PTI purposes to reflect the potential to emit for this emissions unit. Therefore, it is not necessary to develop record keeping and/or reporting requirements to ensure compliance with this limitation.
- 2.ab** The emissions of Hazardous Air Pollutants (HAPs), as identified in section 112(b) of Title III of the Clean Air Act, from this facility shall be less than 9.9 TPY for any single HAP and 24.9 TPY for any combination of HAPs, based on rolling, 12-month summations.
- 2.bc** Prior to this permitting action, this emission unit was a 'de minimis' source pursuant to OAC rule 3745-15-05. This permitting action is required because the permittee is requesting emission increases over the 'de minimis' source levels pursuant to OAC rule 3745-15-05, thereby requiring the permittee to apply for and obtain a new air permit to install for the increase in emissions.

B. Operational Restrictions

None

C. Monitoring and/or Recordkeeping Requirements

1. The permittee shall collect and record the following information each daymonth for this emission unit to determine annual VOC emissions:
 - a. The name and identification number of each coating employed.
 - b. The volume, in gallons, of each coating employed.
 - c. The VOC content of each coating, as applied, in pounds per gallon.
 - d. The name and identification of each cleanup material employed.
 - e. The number of gallons of each cleanup material employed.
 - f. The number of gallons of each cleanup material drummed for shipment off-site.
 - g. The VOC content of each cleanup material, in pounds per gallon.
 - h. The total number of hours the emissions unit was in operation.
 - ih. The total VOC emissions from all coatings and cleanup materials employed, in pounds or ton, (i.e., the summation of the products of C.1.b X C.1.c for each coating

material plus the sum of the products of [(C.1.e - C.1.f) X C.1.g] for each cleanup material). j. The average hourly VOC emission rate for all coatings and cleanup materials, (i.e., (C.1.i)/(C.1.h), in pounds per hour (average)).

2. The permittee shall collect and record the following information each month for emissions units K001, K002 and K003:
 - a. The name and identification of each coating material employed.
 - b. The individual Hazardous Air Pollutant (HAP)* content for each HAP of each coating material, in pounds of individual HAP per gallon, as applied..
 - c. The total combined HAP content of each coating material, in pounds of combined HAPs per gallon, as applied (the sum of all the individual HAP contents from C.2.b).
 - d. The number of gallons of each coating material employed.

- e. The name and identification of each cleanup material employed.
 - f. The individual HAP content of each cleanup material, in pounds of individual HAP per gallon of cleanup material, as applied.
 - g. The total combined HAP content of each cleanup material, in pounds of combined HAPs per gallon of cleanup material, as applied (the sum of all the individual HAP contents from C.2.f).
 - h. The number of gallons of each cleanup material employed.
 - i. The number of gallons of each cleanup material drummed for shipment off-site.
 - j. The total individual HAP emission rate, in tons per month, for each HAP (i.e., for each HAP, the sum of the products of C.2.bX C.2.d for each coating material plus the sum of the products of [C.2.f X (C.2.h - C.2.i)] for each cleanup material).
 - k. The total combined HAP emission rate, in tons per month, for all HAPs employed (i.e., the sum of the products of C.2.c X C.2.d for each coating material plus the sum of the products of [C.2.g X (C.2.h - C.2.i)] for each cleanup material).
 - l. The cumulative monthly total, in tons/month, for the first twelve months following the issuance of this permit to install and the updated rolling twelve month total thereafter, of the total individual HAPs for all of the HAPs employed at this facility.
 - m. The cumulative monthly total, in tons/month, for the first twelve months following the issuance of this permit to install and the updated rolling twelve month total thereafter, of the total combined HAPs for all of the HAPs employed at this facility.
- * A listing of the HAPs can be found in Section 112 (b) of the Clean Air Act or can be obtained by contacting Ohio EPA field office or local agency contact. This information does not have to be kept on a line-by-line basis.
3. The permit to install for this emissions unit K001 was evaluated based on the actual materials (typically coatings and cleanup materials) for emissions units K001 through K003 and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approval model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0

model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarized the results of the modeling for the "worst-case" pollutant(s).

Pollutant: Heptane

TLV(mg/m³): 60.6

Maximum Hourly Emission Rate (lbs/hr): 12.03

Predicted 1-Hour Maximum Ground-Level
Concentration (ug/m³): 1129.62

MAGLC(ug/m³): 1,444

Physical changes to or changes in the method of operation of the emissions unit after its installation of modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the Permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

- a. changes in the composition of the materials used (typically for coatings or cleanup materials), or the use of the new materials, that would result in the emission of a compound with a lower Threshold Limit Value(TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)", than the lowest TLV value previously modeled;
- b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and
- c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01(VV)(1)(a)(ii), and a modification of the existing permit to install will not be required. If the change(s) is (are) defined as a modification under other provisions of the modification definition (other than (VV)(1)(a)(ii)), then the permittee shall obtain a final permit to install prior to the change.

Emissions Unit ID: **K003**

4. The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy":
 - a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
 - b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and
 - c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

D. Reporting Requirements

1. In accordance with Section A.2. of the General Terms and Conditions of this permit, the permittee shall submit quarterly deviation (excursion) reports that include the following:
 - a. An identification of each day during which the volatile organic compound emissions from the coatings and cleanup materials exceeded 8 pounds per hour, and the actual average volatile organic compound emissions for each such day.
 - b. An identification of each day during which the volatile organic compound emissions from the coatings and cleanup materials exceeded 40 pounds per day, and the actual volatile organic compound emissions for each such day.
 - ca. An identification of each month during which the rolling, 12-month individual facility HAP emission rate exceeded the 9.9 TPY rolling, 12-month individual facility HAP emission limitation, and the actual rolling, 12-month individual facility HAP emission rate for each such month.
 - db. An identification of each month during which the rolling, 12-month combined facility HAP emission rate exceeded the 24.9 TPY rolling, 12-month combined facility HAP emission limitation, and the actual rolling, 12-month combined facility HAP emission rate for each such month.
2. The permittee shall submit annual reports which specify the total VOC emissions from this emission unit for the previous calendar year. These reports shall be submitted by January 31 of each year.

E. Testing Requirements

1. Compliance with the specified emission limitations in Section A.1. of this permit shall be demonstrated in accordance with the following methods:
 - a. Emission Limitation-
86.7 pounds of VOC per hour, excluding cleanup

Applicable Compliance Method-
Compliance shall be based upon the maximum hourly coating usage rate and the maximum VOC content record keeping requirements specified in Section C.1. of this permit.
 - b. Emission Limitation-
40 pounds of VOC per day

Applicable Compliance Method-
Compliance with shall be based upon the record keeping requirements specified in Section C.1. of this permit.
 - cb. Emission Limitation-
1.21 TPY VOC, including cleanup materials

Applicable Compliance Method-
Compliance shall be based upon the record keeping requirements specified in Section C.1. of this permit and shall be the summation of the 12 monthly VOC emission rates divided by 2000 lbs/ton.

- dc. Emission Limitation-
9.9 TPY of an individual HAP, based on a 12-month rolling summation

Applicable Compliance Method-
Compliance shall be based upon the record keeping requirements specified in Sections C.2. of this permit.

- ed. Emission Limitation-
24.9 TPY of any combination of HAPs, based on a 12-month rolling summation

Applicable Compliance Method-
Compliance shall be based upon the record keeping requirements specified in Sections C.2. of this permit.

F. Miscellaneous Requirements

- 1. The terms and conditions from Section A.2.ab., Section C.1., Section C.2. and Section D.1. are federally enforceable.