OhioEPA

State of Ohio Environmental Protection Agency

Street Address:
Lazarus Gov. Center
122 S. Front Street
Columbus, OH 43215

TELE: (614) 644-3020 **FAX:** (614) 644-2329

Mailing Address:
Lazarus Gov. Center
P.O. Box 1049
Columbus, OH 43216-1049

07/27/01

CERTIFIED MAIL

RE: Final Title V Chapter 3745-77 permit

03-26-00-0060
Style-Mark, Inc.
Jenny Bischoff
960 West Barre Road
PO Box 301
Archbold, OH 43502

Dear Jenny Bischoff:

Enclosed is the Title V permit that allows you to operate the facility in the manner indicated in the permit. Because this permit may contain several conditions and restrictions, we urge you to read it carefully.

The Ohio EPA is encouraging companies to investigate pollution prevention and energy conservation. Not only will this reduce pollution and energy consumption, but it can also save you money. If you would like to learn ways you can save money while protecting the environment, please contact our Office of Pollution Prevention at (614) 644-3469.

You are hereby notified that this action of the Director is final and may be appealed to the Environmental Review Appeals Commission pursuant to Section 3745.04 of the Ohio Revised Code. The appeal must be in writing and set forth the action complained of and the grounds upon which the appeal is based. It must be filed with the Environmental Review Appeals Commission within thirty (30) days after notice of the Director's action. A copy of the appeal must be served on the Director of the Ohio Environmental Protection Agency within three (3) days of filing with the Commission. It is also requested by the Director that a copy of the appeal be served upon the Environmental Enforcement Section of the Office of the Attorney General. An appeal may be filed with the Environmental Review Appeals Commission at the following address:

Environmental Review Appeals Commission
236 East Town Street
Room 300
Columbus, Ohio 43215

If you have any questions, please contact Northwest District Office.

Very truly yours,

Thomas G. Rigo

Thomas G. Rigo, Manager
Field Operations and Permit Section
Division of Air Pollution Control

cc: Northwest District Office
File, DAPC PMU

State of Ohio Environmental Protection Agency

FINAL TITLE V PERMIT

Issue Date: **07/27/01**	Effective Date: **07/27/01**	Expiration Date: **07/27/06**

This document constitutes issuance of a Title V permit for Facility ID: 03-26-00-0060 to:

Style-Mark, Inc.
960 West Barre Road
P.O. BOX 301
Archbold, OH 43502-0301

Emissions Unit ID (Company ID)/Emissions Unit Activity Description

P001 (Foam Machine #1&2)
The foam machine is a foam dispensing machine.

P002 (Foam Machine #3)
The foam machine is a foam dispensing machine.

P003 (Foam Machine #4)
The foam machine is a foam dispensing machine.

P004 (Foam Machine #5)
The foam machine is a foam dispensing machine.

P005 (Foam Machine #6)
The foam machine is a foam dispensing machine.

P006 (Foam Machine #7)
The foam machine is a foam dispensing machine.

P901 (Solvent Clean up (plantwide))
various clean up operations

R001 (Specialty Ext Paint Booth)
This process puts a finish coat on polyurethane millwork

R002 (Master/Carrier Booth)
This process coats wood masters and silicone molds

R005 (Exterior 1 Paint Booth)
This process puts a finish coat on polyurethane millwork

R006 (Exterior 2 Paint Booth)
This process puts a finish coat on polyurethane millwork

R008 (Mold Coat #1 Booth)
This process coats silicone molds with mold release paint

R009 (Mold Coat #2 Booth)
This process coats silicone molds with mold release paint

R010 (Mold Coat #3 Booth)
This process coats silicone molds with mold release paint

R011 (Mold Coat #4 Booth)
This process coats silicone molds with mold release paint

R012 (Mold Coat #5 Booth)
This process coats silicone molds with mold release paint

R013 (Mold Coat #6 Booth)
This process coats silicone molds with mold release paint

R014 (Mold Coat #7 Booth)
This process coats silicone molds with mold release paint

R015 (Maintenance Booth)
This process coats silicone molds with mold release paint

R016 (Exterior 3 Paint Booth (Automatic))
This process puts a finish coat on polyurethane millwork

You will be contacted approximately eighteen (18) months prior to the expiration date regarding the renewal of this permit. If you are not contacted, please contact the appropriate Ohio EPA District Office or local air agency listed below. This permit and the authorization to operate the air contaminant sources (emissions units) at this facility shall expire at midnight on the expiration date shown above. If a renewal permit is not issued prior to the expiration date, the permittee may continue to operate pursuant to OAC rule 3745-77-04(A) and in accordance with the terms of this permit beyond the expiration date, provided that a complete renewal application is submitted no earlier than eighteen (18) months and no later than one-hundred eighty (180) days prior to the expiration date.

Described below is the Ohio EPA District Office or local air agency that is responsible for processing and administering your Title V permit:

Northwest District Office
347 North Dunbridge Road
Bowling Green, OH 43402
(419) 352-8461

OHIO ENVIRONMENTAL PROTECTION AGENCY



Christopher Jones
Director

PART I - GENERAL TERMS AND CONDITIONS

A. State and Federally Enforceable Section

1. Monitoring and Related Recordkeeping and Reporting Requirements

a. Except as may otherwise be provided in the terms and conditions for a specific emissions unit, the permittee shall maintain records that include the following, where applicable, for any required monitoring under this permit:

i. The date, place (as defined in the permit), and time of sampling or measurements.
ii. The date(s) analyses were performed.
iii. The company or entity that performed the analyses.
iv. The analytical techniques or methods used.
v. The results of such analyses.
vi. The operating conditions existing at the time of sampling or measurement.

b. Each record of any monitoring data, testing data, and support information required pursuant to this permit shall be retained for a period of five years from the date the record was created. Support information shall include all calibration and maintenance records and all original strip-chart recordings for continuous monitoring instrumentation, and copies of all reports required by this permit. Such records may be maintained in computerized form.

c. Except as may otherwise be provided in the terms and conditions for a specific emissions unit, the permittee shall submit required reports in the following manner:

i. Reports of any required monitoring and/or recordkeeping information shall be submitted to the appropriate Ohio EPA District Office or local air agency.
ii. Quarterly written reports of (i) any deviations from federally enforceable emission limitations, operational restrictions, and control device operating parameter limitations, excluding deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06, that have been detected by the testing, monitoring and recordkeeping requirements specified in this permit, (ii) the probable cause of such deviations, and (iii) any corrective actions or preventive measures taken, shall be promptly made to the appropriate Ohio EPA District Office or local air agency. These quarterly written reports shall satisfy the requirements of OAC rule 3745-77-07(A)(3)(c)(i) and (ii) pertaining to the submission of monitoring reports every six months and OAC rule 3745-77-07(A)(3)(c)(iii) pertaining to the prompt reporting of all deviations except malfunctions, which shall be reported in accordance with OAC rule 3745-15-06. The written reports shall be submitted quarterly, i.e., by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters. (These quarterly reports shall exclude deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06.) See B.8 below if no deviations occurred during the quarter.
iii. Written reports, which identify any deviations from the federally enforceable monitoring, recordkeeping, and reporting requirements contained in this permit shall be submitted to

the appropriate Ohio EPA District Office or local air agency every six months, i.e., by January 31 and July 31 of each year for the previous six calendar months. These semi-annual written reports shall satisfy the requirements of OAC rule 3745-77-07(A)(3)(c)(i) and (ii) pertaining to the reporting of any deviations related to the monitoring, recordkeeping, and reporting requirements. If no deviations occurred during a six-month period, the permittee shall submit a semi-annual report, which states that no deviations occurred during that period.

iv. Each written report shall be signed by a responsible official certifying that, based on information and belief formed after reasonable inquiry, the statements and information in the report are true, accurate, and complete.

2. Scheduled Maintenance/Malfunction Reporting

Any scheduled maintenance of air pollution control equipment shall be performed in accordance with paragraph (A) of OAC rule 3745-15-06. The malfunction, i.e., upset, of any emissions units or any associated air pollution control system(s) shall be reported to the appropriate Ohio EPA District Office or local air agency in accordance with paragraph (B) of OAC rule 3745-15-06. (The definition of an upset condition shall be the same as that used in OAC rule 3745-15-06(B)(1) for a malfunction.) The verbal and written reports submitted pursuant to OAC rule 3745-15-06 shall satisfy the requirements of OAC rule 3745-77-07(A)(3)(c)(iii) pertaining to the prompt reporting of deviations caused by malfunctions or upsets.

Except as provided in that rule, any scheduled maintenance or malfunction necessitating the shutdown or bypassing of any air pollution control system(s) shall be accompanied by the shutdown of the emission unit(s) that is (are) served by such control system(s).

3. Risk Management Plans

If the permittee is required to develop and register a risk management plan pursuant to section 112(r) of the Clean Air Act, as amended, 42 U.S.C. 7401 et seq. ("Act"), the permittee shall comply with the requirement to register such a plan.

4. Title IV Provisions

If the permittee is subject to the requirements of 40 CFR Part 72 concerning acid rain, the permittee shall ensure that any affected emissions unit complies with those requirements. Emissions exceeding any allowances that are lawfully held under Title IV of the Act, or any regulations adopted thereunder, are prohibited.

5. Severability Clause

A determination that any term or condition of this permit is invalid shall not invalidate the force or effect of any other term or condition thereof, except to the extent that any other term or condition depends in whole or in part for its operation or implementation upon the term or condition declared invalid.

6. General Requirements

a. The permittee must comply with all terms and conditions of this permit. Any noncompliance with the federally enforceable terms and conditions of this permit constitutes a violation of the Act, and is grounds for enforcement action or for permit revocation, revocation and reissuance, or modification, or for denial of a permit renewal application.

b. It shall not be a defense for the permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the federally enforceable terms and conditions of this permit.

c. This permit may be modified, reopened, revoked, or revoked and reissued, for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or revocation, or of a notification of planned changes or anticipated noncompliance does not stay any term and condition of this permit.

d. This permit does not convey any property rights of any sort, or any exclusive privilege.

e. The permittee shall furnish to the Director of the Ohio EPA, or an authorized representative of the Director, upon receipt of a written request and within a reasonable time, any information that may be requested to determine whether cause exists for modifying, reopening or revoking this permit or to determine compliance with this permit. Upon request, the permittee shall also furnish to the Director or an authorized representative of the Director, copies of records required to be kept by this permit. For information claimed to be confidential in the submittal to the Director, if the Administrator of the U.S. EPA requests such information, the permittee may furnish such records directly to the Administrator along with a claim of confidentiality.

7. Fees

The permittee shall pay fees to the Director of the Ohio EPA in accordance with ORC section 3745.11 and OAC Chapter 3745-78.

8. Marketable Permit Programs

No revision of this permit is required under any approved economic incentive, marketable permits, emissions trading, and other similar programs or processes for changes that are provided for in this permit.

9. Reasonably Anticipated Operating Scenarios

The permittee is hereby authorized to make changes among operating scenarios authorized in this permit without notice to the Ohio EPA, but, contemporaneous with making a change from one operating scenario to another, the permittee must record in a log at the permitted facility the scenario under which the permittee is operating. The permit shield provided in these general terms and conditions shall apply to all operating scenarios authorized in this permit.

10. Reopening for Cause

This Title V permit will be reopened prior to its expiration date under the following conditions:

a. Additional applicable requirements under the Act become applicable to one or more emissions units covered by this permit, and this permit has a remaining term of three or more years. Such a reopening shall be completed not later than eighteen months after promulgation of the applicable requirement. No such reopening is required if the effective date of the requirement is later than the date on which the permit is due to expire, unless the original permit or any of its terms and conditions has been extended pursuant to paragraph (E)(1) of OAC rule 3745-77-08.

b. This permit is issued to an affected source under the acid rain program and additional requirements (including excess emissions requirements) become applicable. Upon approval by the Administrator, excess emissions offset plans shall be deemed to be incorporated into the permit, and shall not require a reopening of this permit.

c. The Director of the Ohio EPA or the Administrator of the U.S. EPA determines that the federally applicable requirements in this permit are based on a material mistake, or that inaccurate statements were made in establishing the emissions standards or other terms and conditions of this permit related to such federally applicable requirements.

d. The Administrator of the U.S. EPA or the Director of the Ohio EPA determines that this permit must be revised or revoked to assure compliance with the applicable requirements.

11. Federal and State Enforceability

Only those terms and conditions designated in this permit as federally enforceable, that are required under the Act, or any of its applicable requirements, including relevant provisions designed to limit the potential to emit of a source, are enforceable by the Administrator of the U.S. EPA, the State, and citizens under the Act. All other terms and conditions of this permit shall not be federally enforceable and shall be enforceable under State law only.

12. Compliance Requirements

a. Any document (including reports) required to be submitted and required by a federally applicable requirement in this Title V permit shall include a certification by a responsible official that, based on information and belief formed after reasonable inquiry, the statements in the document are true, accurate, and complete.

b. Upon presentation of credentials and other documents as may be required by law, the permittee shall allow the Director of the Ohio EPA or an authorized representative of the Director to:

   i. At reasonable times, enter upon the permittee's premises where a source is located or the emissions-related activity is conducted, or where records must be kept under the conditions of this permit.

ii. Have access to and copy, at reasonable times, any records that must be kept under the conditions of this permit, subject to the protection from disclosure to the public of confidential information consistent with paragraph (E) of OAC rule 3745-77-03.
iii. Inspect at reasonable times any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under this permit.
iv. As authorized by the Act, sample or monitor at reasonable times substances or parameters for the purpose of assuring compliance with the permit and applicable requirements.

c. The permittee shall submit progress reports to the appropriate Ohio EPA District Office or local air agency concerning any schedule of compliance for meeting an applicable requirement. Progress reports shall be submitted semiannually, or more frequently if specified in the applicable requirement or by the Director of the Ohio EPA. Progress reports shall contain the following:

i. Dates for achieving the activities, milestones, or compliance required in any schedule of compliance, and dates when such activities, milestones, or compliance were achieved.
ii. An explanation of why any dates in any schedule of compliance were not or will not be met, and any preventive or corrective measures adopted.

d. Compliance certifications concerning the terms and conditions contained in this permit that are federally enforceable emission limitations, standards, or work practices, shall be submitted to the appropriate Ohio EPA District Office or local air agency in the following manner and with the following content:

i. Compliance certifications shall be submitted annually on a calendar year basis. The annual certification shall be submitted on or before April 30th of each year during the permit term.
ii. Compliance certifications shall include the following:

(a) An identification of each term or condition of this permit that is the basis of the certification.
(b) The permittee's current compliance status.
(c) Whether compliance was continuous or intermittent.
(d) The method(s) used for determining the compliance status of the source currently and over the required reporting period.
(e) Such other facts as the Director of the Ohio EPA may require in the permit to determine the compliance status of the source.

iii. Compliance certifications shall contain such additional requirements as may be specified pursuant to sections 114(a)(3) and 504(b) of the Act.

13. Permit Shield

a. Compliance with the terms and conditions of this permit (including terms and conditions established for alternate operating scenarios, emissions trading, and emissions averaging, but

excluding terms and conditions for which the permit shield is expressly prohibited under OAC rule 3745-77-07) shall be deemed compliance with the applicable requirements identified and addressed in this permit as of the date of permit issuance.

b. This permit shield provision shall apply to any requirement identified in this permit pursuant to OAC rule 3745-77-07(F)(2), as a requirement that does not apply to the source or to one or more emissions units within the source.

14. Operational Flexibility

The permittee is authorized to make the changes identified in OAC rule 3745-77-07(H)(1)(a) to (H)(1)(c) within the permitted stationary source without obtaining a permit revision, if such change is not a modification under any provision of Title I of the Act [as defined in OAC rule 3745-77-01(JJ)], and does not result in an exceedance of the emissions allowed under this permit (whether expressed therein as a rate of emissions or in terms of total emissions), and the permittee provides the Administrator of the U.S. EPA and the appropriate Ohio EPA District Office or local air agency with written notification within a minimum of seven days in advance of the proposed changes, unless the change is associated with, or in response to, emergency conditions. If less than seven days notice is provided because of a need to respond more quickly to such emergency conditions, the permittee shall provide notice to the Administrator of the U.S. EPA and the appropriate District Office of the Ohio EPA or local air agency as soon as possible after learning of the need to make the change. The notification shall contain the items required under OAC rule 3745-77-07(H)(2)(d).

15. Emergencies

The permittee shall have an affirmative defense of emergency to an action brought for noncompliance with technology-based emission limitations if the conditions of OAC rule 3745-77-07(G)(3) are met. This emergency defense provision is in addition to any emergency or upset provision contained in any applicable requirement.

16. Off Permit Changes

The owner or operator of a Title V source may make any change in its operations or emissions at the source that is not specifically addressed or prohibited in the Title V permit, without obtaining an amendment or modification of the permit, provided that the following conditions are met:

a. The change does not result in conditions that violate any applicable requirements or that violate any existing federally enforceable permit term or condition;

b. The permittee provides contemporaneous written notice of the change to the director and the administrator, except that no such notice shall be required for changes that qualify as insignificant emission levels or activities as defined in OAC rule 3745-77-01(U). Such written notice shall describe each such change, the date of such change, any change in emissions or

pollutants emitted, and any federally applicable requirement that would apply as a result of the change;

c. The change shall not qualify for the permit shield under OAC rule 3745-77-07(F);

d. The permittee shall keep a record describing all changes made at the source that result in emissions of a regulated air pollutant subject to an applicable requirement, but not otherwise regulated under the permit, and the emissions resulting from those changes; and

e. The change is not subject to any applicable requirement under Title IV of the Act or is not a modification under any provision of Title I of the Act.

Paragraph (I) of rule 3745-77-07 of the Administrative Code applies only to modification or amendment of the permittee's Title V permit. The change made may require a permit to install under Chapter 3745-31 of the Administrative Code if the change constitutes a modification as defined in that Chapter. Nothing in paragraph (I) of rule 3745-77-07 of the Administrative Code shall affect any applicable obligation under Chapter 3745-31 of the Administrative Code.

(For further clarification, the permittee can refer to Engineering Guide #63 that is available in their STARSHIP software package.)

17. Compliance Method Requirements

Nothing in this permit shall alter or affect the ability of any person to establish compliance with, or a violation of, any applicable requirement through the use of credible evidence to the extent authorized by law. Nothing in this permit shall be construed to waive any defenses otherwise available to the permittee, including but not limited to, any challenge to the Credible Evidence Rule (see 62 Fed. Reg. 8314, Feb. 24, 1997), in the context of any future proceeding.

18. Insignificant Activity

Each insignificant activity that has one or more applicable requirements shall comply with those applicable requirements.

B. State Only Enforceable Section

1. Permit to Install Requirement

Prior to the "installation" or "modification" of any "air contaminant source," as those terms are defined in OAC rule 3745-31-01, a permit to install must be obtained from the Ohio EPA pursuant to OAC Chapter 3745-31.

2. Reporting Requirements Related to Monitoring and Recordkeeping Requirements

The permittee shall submit required reports in the following manner:

a. Reports of any required monitoring and/or recordkeeping information shall be submitted to the appropriate Ohio EPA District Office or local air agency.

b. Except as otherwise may be provided in the terms and conditions for a specific emissions unit, quarterly written reports of (a) any deviations (excursions) from emission limitations, operational restrictions, and control device operating parameter limitations that have been detected by the testing, monitoring, and recordkeeping requirements specified in this permit, (b) the probable cause of such deviations, and (c) any corrective actions or preventive measures which have been or will be taken, shall be submitted to the appropriate Ohio EPA District Office or local air agency. If no deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted quarterly, i.e., by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters. (These quarterly reports shall exclude deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06.)

3. Records Retention Requirements

Each record of any monitoring data, testing data, and support information required pursuant to this permit shall be retained for a period of five years from the date the record was created. Support information shall include, but not be limited to, all calibration and maintenance records and all original strip-chart recordings for continuous monitoring instrumentation, and copies of all reports required by this permit. Such records may be maintained in computerized form.

4. Inspections and Information Requests

The Director of the Ohio EPA, or an authorized representative of the Director, may, subject to the safety requirements of the permittee and without undue delay, enter upon the premises of this source at any reasonable time for purposes of making inspections, conducting tests, examining records or reports pertaining to any emission of air contaminants, and determining compliance with any applicable State air pollution laws and regulations and the terms and conditions of this permit. The permittee shall furnish to the Director of the Ohio EPA, or an authorized representative of the Director, upon receipt of a written request and within a reasonable time, any information that may be requested to determine whether cause exists for modifying, reopening or revoking this permit or to determine compliance with

this permit. Upon verbal or written request, the permittee shall also furnish to the Director of the Ohio EPA, or an authorized representative of the Director, copies of records required to be kept by this permit.

5. Scheduled Maintenance/Malfunction Reporting

Any scheduled maintenance of air pollution control equipment shall be performed in accordance with paragraph (A) of OAC rule 3745-15-06. The malfunction of any emissions units or any associated air pollution control system(s) shall be reported to the appropriate Ohio EPA District Office or local air agency in accordance with paragraph (B) of OAC rule 3745-15-06. Except as provided in that rule, any scheduled maintenance or malfunction necessitating the shutdown or bypassing of any air pollution control system(s) shall be accompanied by the shutdown of the emissions unit(s) that is (are) served by such control system(s).

6. Permit Transfers

Any transferee of this permit shall assume the responsibilities of the prior permit holder. The appropriate Ohio EPA District Office or local air agency must be notified in writing of any transfer of this permit.

7. Air Pollution Nuisance

The air contaminants emitted by the emissions units covered by this permit shall not cause a public nuisance, in violation of OAC rule 3745-15-07.

8. Additional Reporting Requirements When There Are No Deviations of <u>Federally Enforceable</u> Emission Limitations, Operational Restrictions, or Control Device Operating Parameter Limitations (See Section A of This Permit)

If no deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted quarterly, i.e., by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters.

Part II - Specific Facility Terms and Conditions

A. State and Federally Enforcable Section

None

B. State Only Enforceable Section

1. The following insignificant emissions units are located at this facility:

Air Make-Up Unit #1, emissions unit B001;
Air Make-Up Unit #2, emissions unit B002; and
Air Make-Up Unit #3, emissions unit B003.

Each insignificant emissions unit at this facility must comply with all applicable State and federal regulations, as well as any emission limitations and/or control requirements contained within a Permit to Install (PTI) for the emissions unit.

Part III - Terms and Conditions for Emissions Units

Emissions Unit ID: Foam Machine #1&2 (P001)

Activity Description: The foam machine is a foam dispensing machine.

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

Operations, Property, and/or Equipment	Applicable Rules/ Requirements	Applicable Emissions Limitations/Control Measures
foam line machine #1 & #2	OAC rule 3745-31-05 (PTI 03-11125)	See A.I.2.a. 6.5 lbs organic compounds OC/hr, 28.5 tons OC/yr (see A.I.2.b)
	OAC rule 3745-21-07(G)	none (See A.II.1.)

2. Additional Terms and Conditions

2.a The permittee shall emit no more than 45.0 tons of OC (from cleanup materials) per rolling, 12-month period from emissions units P001, P002, P003, P004, P005 and P006, combined.

2.b The 6.5 lbs OC/hr and 28.5 tons OC/yr emission limitations were established for PTI purposes to reflect the potential to emit for this emissions unit. Therefore, it is not necessary to develop record keeping and reporting requirements to ensure compliance with these limitations.

II. Operational Restrictions

1. The permittee shall not employ any material in this emissions unit that is a photochemically reactive material. "Photochemically reactive material" is defined in OAC rule 3745-21-01(C)(5).

III. Monitoring and/or Record Keeping Requirements

1. The permittee shall collect and record the following information each month for emissions units P001, P002, P003, P004, P005 and P006, combined:

1.a the company identification for each flush solvent (cleanup material) employed;

1.b the OC content of each cleanup material employed, in pounds per gallon;

1.c the number of gallons of each cleanup material employed;

1.d the number of gallons of each waste cleanup material sent off site for reclamation/disposal;

1.e the total OC emission rate for all the cleanup materials employed [summation of (b x (c - d)) for all cleanup materials], in pounds; and

1.f the rolling, 12-month summation of the monthly OC emission rates, in tons.

III. Monitoring and/or Record Keeping Requirements (continued)

2. The permittee may also calculate the monthly OC emission rate in accordance with the following formula, for the emission rate required by Section A.III.1.e, if waste cleanup materials are sent off site for reclamation/disposal:

monthly OC emissions from cleanup operations (pounds/month) = summation of [(Ai-Bi) X di] for i = 1 to n

where:

i = 1, 2, 3,...n

n = the total number of different types of cleanup materials employed

Ai = the number of gallons of cleanup material i consumed (gallons/month)

Bi = the number of gallons of cleanup material i sent off site for disposal or reclamation, minus solids content of said material (gallons/month)

di = density of cleanup material i, in pounds/gallon

3. The permittee shall record and maintain the following information each day for this emissions unit:

3.a the company identification for each cleanup material employed; and

3.b documentation on whether or not each cleanup material employed is a photochemically reactive material.

IV. Reporting Requirements

1. The permittee shall submit quarterly deviation (excursion) reports that identify all exceedances of the rolling, 12-month OC emission limitation of 45 tons. All quarterly deviation reports shall be submitted in accordance with paragraph A.1.c of the General Terms and Conditions of this permit.

2. The permittee shall notify the Director (the appropriate Ohio EPA District Office or local air agency) in writing of any daily record showing the use of any noncomplying cleanup material (i.e., photochemically reactive cleanup material) in this emissions unit. The notification shall include a copy of such record and shall be sent to the Director (the appropriate Ohio EPA District Office or local air agency) within 30 days after the exceedance occurs.

3. The permittee shall submit annual reports that specify the total actual OC emissions from emissions units P001, P002, P003, P004, P005 and P006, combined. These reports shall be submitted by January 31 of each year and shall cover the previous calendar year.

V. Testing Requirements

1. Compliance with the emission limitations/usage restrictions of this permit shall be determined in accordance with the following methods:

1.a Emission Limitation: 45.0 tons OC per rolling, 12-month period

Applicable Compliance Method: Compliance shall be based upon the record keeping requirements specified in section A.III.1 of the terms and conditions of this permit.

V. Testing Requirements (continued)

1.b Emission Limitations: 6.5 lbs OC/hr, 28.5 tons OC/yr

Applicable Compliance Method: Compliance with the hourly limitation shall be determined by multiplying the maximum flush solvent usage rate (gallons/hr) by the maximum OC content of all the flush solvents (lbs/gallon), as applied, and then multiplying by 0.3.*

The tons/yr limitation was developed by multiplying the 6.5 lbs/hr limitation by 8760, and then dividing by 2000. Therefore, provided compliance is shown with the hourly limitation, compliance shall also be shown with the annual limitation.

* 70% of the cleanup materials (flush solvents) employed in this emissions unit is sent off site for disposal/reclamation.

2. The permittee shall determine the OC contents of the cleanup materials based upon the formulation data supplied by the manufacturer of the cleanup materials, or from data determined by analysis of each cleanup material, as received, in accordance with 40 CFR, Part 60, Appendix A, Method 24.

VI. Miscellaneous Requirements

None

B. State Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

Operations, Property, and/or Equipment	Applicable Rules/ Requirements	Applicable Emissions Limitations/Control Measures
foam line machine #1 & #2	none	none

2. Additional Terms and Conditions

None

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

1. The permit to install for emissions units R001, R002, R005, R006, R008, R009 thru R016, P001 thru P006 and P901 was evaluated based on the actual materials (coatings and cleanup materials) and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant(s):

Pollutant: Butyl Acetate

TLV (ug/m3): 950,000

Maximum Hourly Emission Rate (lbs/hr): 57.8

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 5,770

MAGLC (ug/m3): 22,620

Pollutant: methyl ethyl ketone

TLV (ug/m3): 590,000

Maximum Hourly Emission Rate (lbs/hr): 70.1

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 7,000

MAGLC (ug/m3): 14,048

Pollutant: isopropyl alcohol

TLV (ug/m3): 983,000

Maximum Hourly Emission Rate (lbs/hr): 20.6

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 2,060

MAGLC (ug/m3): 23,400

Pollutant: xylene

TLV (ug/m3): 434,000

Maximum Hourly Emission Rate (lbs/hr): 4.3

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 430

MAGLC (ug/m3): 10,333

III. Monitoring and/or Record Keeping Requirements (continued)

2. Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be still satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

a. changes in the composition of the materials used (coatings or cleanup materials), or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value previously modeled;

b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and

c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01(VV)(1)(a)(ii), and a modification of the existing permit to install will not be required. If the change(s) is (are) defined as a modification under other provisions of the modification definition (other than (VV)(1)(a)(ii)), then the permittee shall obtain a final permit to install prior to the change.

3. The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy:"

a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);

b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and

c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Part III - Terms and Conditions for Emissions Units

Emissions Unit ID: Foam Machine #3 (P002)

Activity Description: The foam machine is a foam dispensing machine.

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

Operations, Property, and/or Equipment	Applicable Rules/ Requirements	Applicable Emissions Limitations/Control Measures
foam line machine #3	OAC rule 3745-31-05 (PTI 03-11125)	See A.I.2.a. 6.5 lbs organic compounds OC/hr, 28.5 tons OC/yr (see A.I.2.b)
	OAC rule 3745-21-07(G)	none (See A.II.1.)

2. Additional Terms and Conditions

2.a The permittee shall emit no more than 45.0 tons of OC (from cleanup materials) per rolling, 12-month period from emissions units P001, P002, P003, P004, P005 and P006, combined.

2.b The 6.5 lbs OC/hr and 28.5 tons OC/yr emission limitations were established for PTI purposes to reflect the potential to emit for this emissions unit. Therefore, it is not necessary to develop record keeping and reporting requirements to ensure compliance with these limitations.

II. Operational Restrictions

1. The permittee shall not employ any material in this emissions unit that is a photochemically reactive material. "Photochemically reactive material" is defined in OAC rule 3745-21-01(C)(5).

III. Monitoring and/or Record Keeping Requirements

1. The permittee shall collect and record the following information each month for emissions units P001, P002, P003, P004, P005 and P006, combined:

1.a the company identification for each flush solvent (cleanup material) employed;

1.b the OC content of each cleanup material employed, in pounds per gallon;

1.c the number of gallons of each cleanup material employed;

1.d the number of gallons of each waste cleanup material sent off site for reclamation/disposal;

1.e the total OC emission rate for all the cleanup materials employed [summation of (b x (c - d)) for all cleanup materials], in pounds; and

1.f the rolling, 12-month summation of the monthly OC emission rates, in tons.

III. Monitoring and/or Record Keeping Requirements (continued)

2. The permittee may also calculate the monthly OC emission rate in accordance with the following formula, for the emission rate required by Section A.III.1.e, if waste cleanup materials are sent off site for reclamation/disposal:

monthly OC emissions from cleanup operations (pounds/month) = summation of [(Ai-Bi) X di] for i = 1 to n

where:

i = 1, 2, 3,...n

n = the total number of different types of cleanup materials employed

Ai = the number of gallons of cleanup material i consumed (gallons/month)

Bi = the number of gallons of cleanup material i sent off site for disposal or reclamation, minus solids content of said material (gallons/month)

di = density of cleanup material i, in pounds/gallon

3. The permittee shall record and maintain the following information each day for this emissions unit:

3.a the company identification for each cleanup material employed; and

3.b documentation on whether or not each cleanup material employed is a photochemically reactive material.

IV. Reporting Requirements

1. The permittee shall submit quarterly deviation (excursion) reports that identify all exceedances of the rolling, 12-month OC emission limitation of 45 tons. All quarterly deviation reports shall be submitted in accordance with paragraph A.1.c of the General Terms and Conditions of this permit.

2. The permittee shall notify the Director (the appropriate Ohio EPA District Office or local air agency) in writing of any daily record showing the use of any noncomplying cleanup material (i.e., photochemically reactive cleanup material) in this emissions unit. The notification shall include a copy of such record and shall be sent to the Director (the appropriate Ohio EPA District Office or local air agency) within 30 days after the exceedance occurs.

3. The permittee shall submit annual reports that specify the total actual OC emissions from emissions units P001, P002, P003, P004, P005 and P006, combined. These reports shall be submitted by January 31 of each year and shall cover the previous calendar year.

V. Testing Requirements

1. Compliance with the emission limitations/usage restrictions of this permit shall be determined in accordance with the following methods:

1.a Emission Limitation: 45.0 tons OC per rolling, 12-month period

Applicable Compliance Method: Compliance shall be based upon the record keeping requirements specified in section A.III.1 of the terms and conditions of this permit.

V. Testing Requirements (continued)

1.b Emission Limitations: 6.5 lbs OC/hr, 28.5 tons OC/yr

Applicable Compliance Method: Compliance with the hourly limitation shall be determined by multiplying the maximum flush solvent usage rate (gallons/hr) by the maximum OC content of all the flush solvents (lbs/gallon), as applied, and then multiplying by 0.3.*

The tons/yr limitation was developed by multiplying the 6.5 lbs/hr limitation by 8760, and then dividing by 2000. Therefore, provided compliance is shown with the hourly limitation, compliance shall also be shown with the annual limitation.

* 70% of the cleanup materials (flush solvents) employed in this emissions unit is sent off site for disposal/reclamation.

2. The permittee shall determine the OC contents of the cleanup materials based upon the formulation data supplied by the manufacturer of the cleanup materials, or from data determined by analysis of each cleanup material, as received, in accordance with 40 CFR, Part 60, Appendix A, Method 24.

VI. Miscellaneous Requirements

None

B. State Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

Operations, Property, and/or Equipment	Applicable Rules/ Requirements	Applicable Emissions Limitations/Control Measures
foam line machine #3	none	none

2. Additional Terms and Conditions

None

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

1. The permit to install for emissions units R001, R002, R005, R006, R008, R009 thru R016, P001 thru P006 and P901 was evaluated based on the actual materials (coatings and cleanup materials) and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant(s):

Pollutant: Butyl Acetate

TLV (ug/m3): 950,000

Maximum Hourly Emission Rate (lbs/hr): 57.8

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 5,770

MAGLC (ug/m3): 22,620

Pollutant: methyl ethyl ketone

TLV (ug/m3): 590,000

Maximum Hourly Emission Rate (lbs/hr): 70.1

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 7,000

MAGLC (ug/m3): 14,048

Pollutant: isopropyl alcohol

TLV (ug/m3): 983,000

Maximum Hourly Emission Rate (lbs/hr): 20.6

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 2,060

MAGLC (ug/m3): 23,400

Pollutant: xylene

TLV (ug/m3): 434,000

Maximum Hourly Emission Rate (lbs/hr): 4.3

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 430

MAGLC (ug/m3): 10,333

III. Monitoring and/or Record Keeping Requirements (continued)

2. Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be still satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

a. changes in the composition of the materials used (coatings or cleanup materials), or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value previously modeled;

b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and

c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01(VV)(1)(a)(ii), and a modification of the existing permit to install will not be required. If the change(s) is (are) defined as a modification under other provisions of the modification definition (other than (VV)(1)(a)(ii)), then the permittee shall obtain a final permit to install prior to the change.

3. The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy:"

a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);

b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and

c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Part III - Terms and Conditions for Emissions Units

Emissions Unit ID: Foam Machine #4 (P003)

Activity Description: The foam machine is a foam dispensing machine.

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

Operations, Property, and/or Equipment	Applicable Rules/ Requirements	Applicable Emissions Limitations/Control Measures
foam line machine #4	OAC rule 3745-31-05 (PTI 03-11125)	See A.I.2.a. 6.5 lbs organic compounds OC/hr, 28.5 tons OC/yr (see A.I.2.b)
	OAC rule 3745-21-07(G)	none (See A.II.1.)

2. Additional Terms and Conditions

2.a The permittee shall emit no more than 45.0 tons of OC (from cleanup materials) per rolling, 12-month period from emissions units P001, P002, P003, P004, P005 and P006, combined.

2.b The 6.5 lbs OC/hr and 28.5 tons OC/yr emission limitations were established for PTI purposes to reflect the potential to emit for this emissions unit. Therefore, it is not necessary to develop record keeping and reporting requirements to ensure compliance with these limitations.

II. Operational Restrictions

1. The permittee shall not employ any material in this emissions unit that is a photochemically reactive material. "Photochemically reactive material" is defined in OAC rule 3745-21-01(C)(5).

III. Monitoring and/or Record Keeping Requirements

1. The permittee shall collect and record the following information each month for emissions units P001, P002, P003, P004, P005 and P006, combined:

1.a the company identification for each flush solvent (cleanup material) employed;

1.b the OC content of each cleanup material employed, in pounds per gallon;

1.c the number of gallons of each cleanup material employed;

1.d the number of gallons of each waste cleanup material sent off site for reclamation/disposal;

1.e the total OC emission rate for all the cleanup materials employed [summation of (b x (c - d)) for all cleanup materials], in pounds; and

1.f the rolling, 12-month summation of the monthly OC emission rates, in tons.

III. Monitoring and/or Record Keeping Requirements (continued)

2. The permittee may also calculate the monthly OC emission rate in accordance with the following formula, for the emission rate required by Section A.III.1.e, if waste cleanup materials are sent off site for reclamation/disposal:

monthly OC emissions from cleanup operations (pounds/month) = summation of [(Ai-Bi) X di] for i = 1 to n

where:

i = 1, 2, 3,...n

n = the total number of different types of cleanup materials employed

Ai = the number of gallons of cleanup material i consumed (gallons/month)

Bi = the number of gallons of cleanup material i sent off site for disposal or reclamation, minus solids content of said material (gallons/month)

di = density of cleanup material i, in pounds/gallon

3. The permittee shall record and maintain the following information each day for this emissions unit:

3.a the company identification for each cleanup material employed; and

3.b documentation on whether or not each cleanup material employed is a photochemically reactive material.

IV. Reporting Requirements

1. The permittee shall submit quarterly deviation (excursion) reports that identify all exceedances of the rolling, 12-month OC emission limitation of 45 tons. All quarterly deviation reports shall be submitted in accordance with paragraph A.1.c of the General Terms and Conditions of this permit.

2. The permittee shall notify the Director (the appropriate Ohio EPA District Office or local air agency) in writing of any daily record showing the use of any noncomplying cleanup material (i.e., photochemically reactive cleanup material) in this emissions unit. The notification shall include a copy of such record and shall be sent to the Director (the appropriate Ohio EPA District Office or local air agency) within 30 days after the exceedance occurs.

3. The permittee shall submit annual reports that specify the total actual OC emissions from emissions units P001, P002, P003, P004, P005 and P006, combined. These reports shall be submitted by January 31 of each year and shall cover the previous calendar year.

V. Testing Requirements

1. Compliance with the emission limitations/usage restrictions of this permit shall be determined in accordance with the following methods:

1.a Emission Limitation: 45.0 tons OC per rolling, 12-month period

Applicable Compliance Method: Compliance shall be based upon the record keeping requirements specified in section A.III.1 of the terms and conditions of this permit.

V. Testing Requirements (continued)

1.b Emission Limitations: 6.5 lbs OC/hr, 28.5 tons OC/yr

Applicable Compliance Method: Compliance with the hourly limitation shall be determined by multiplying the maximum flush solvent usage rate (gallons/hr) by the maximum OC content of all the flush solvents (lbs/gallon), as applied, and then multiplying by 0.3.*

The tons/yr limitation was developed by multiplying the 6.5 lbs/hr limitation by 8760, and then dividing by 2000. Therefore, provided compliance is shown with the hourly limitation, compliance shall also be shown with the annual limitation.

* 70% of the cleanup materials (flush solvents) employed in this emissions unit is sent off site for disposal/reclamation.

2. The permittee shall determine the OC contents of the cleanup materials based upon the formulation data supplied by the manufacturer of the cleanup materials, or from data determined by analysis of each cleanup material, as received, in accordance with 40 CFR, Part 60, Appendix A, Method 24.

VI. Miscellaneous Requirements

None

B. State Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

Operations, Property, and/or Equipment	Applicable Rules/ Requirements	Applicable Emissions Limitations/Control Measures
foam line machine #4	none	none

2. Additional Terms and Conditions

None

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

1. The permit to install for emissions units R001, R002, R005, R006, R008, R009 thru R016, P001 thru P006 and P901 was evaluated based on the actual materials (coatings and cleanup materials) and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant(s):

Pollutant: Butyl Acetate

TLV (ug/m3): 950,000

Maximum Hourly Emission Rate (lbs/hr): 57.8

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 5,770

MAGLC (ug/m3): 22,620

Pollutant: methyl ethyl ketone

TLV (ug/m3): 590,000

Maximum Hourly Emission Rate (lbs/hr): 70.1

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 7,000

MAGLC (ug/m3): 14,048

Pollutant: isopropyl alcohol

TLV (ug/m3): 983,000

Maximum Hourly Emission Rate (lbs/hr): 20.6

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 2,060

MAGLC (ug/m3): 23,400

Pollutant: xylene

TLV (ug/m3): 434,000

Maximum Hourly Emission Rate (lbs/hr): 4.3

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 430

MAGLC (ug/m3): 10,333

III. Monitoring and/or Record Keeping Requirements (continued)

2. Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be still satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

a. changes in the composition of the materials used (coatings or cleanup materials), or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value previously modeled;

b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and

c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01(VV)(1)(a)(ii), and a modification of the existing permit to install will not be required. If the change(s) is (are) defined as a modification under other provisions of the modification definition (other than (VV)(1)(a)(ii)), then the permittee shall obtain a final permit to install prior to the change.

3. The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy:"

a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);

b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and

c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Part III - Terms and Conditions for Emissions Units

Emissions Unit ID: Foam Machine #5 (P004)

Activity Description: The foam machine is a foam dispensing machine.

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

Operations, Property, and/or Equipment	Applicable Rules/ Requirements	Applicable Emissions Limitations/Control Measures
foam line machine #5	OAC rule 3745-31-05 (PTI 03-11125)	See A.I.2.a. 6.5 lbs organic compounds OC/hr, 28.5 tons OC/yr (see A.I.2.b)
	OAC rule 3745-21-07(G)	none (See A.II.1.)

2. Additional Terms and Conditions

2.a The permittee shall emit no more than 45.0 tons of OC (from cleanup materials) per rolling, 12-month period from emissions units P001, P002, P003, P004, P005 and P006, combined.

2.b The 6.5 lbs OC/hr and 28.5 tons OC/yr emission limitations were established for PTI purposes to reflect the potential to emit for this emissions unit. Therefore, it is not necessary to develop record keeping and reporting requirements to ensure compliance with these limitations.

II. Operational Restrictions

1. The permittee shall not employ any material in this emissions unit that is a photochemically reactive material. "Photochemically reactive material" is defined in OAC rule 3745-21-01(C)(5).

III. Monitoring and/or Record Keeping Requirements

1. The permittee shall collect and record the following information each month for emissions units P001, P002, P003, P004, P005 and P006, combined:

1.a the company identification for each flush solvent (cleanup material) employed;

1.b the OC content of each cleanup material employed, in pounds per gallon;

1.c the number of gallons of each cleanup material employed;

1.d the number of gallons of each waste cleanup material sent off site for reclamation/disposal;

1.e the total OC emission rate for all the cleanup materials employed [summation of (b x (c - d)) for all cleanup materials], in pounds; and

1.f the rolling, 12-month summation of the monthly OC emission rates, in tons.

III. Monitoring and/or Record Keeping Requirements (continued)

2. The permittee may also calculate the monthly OC emission rate in accordance with the following formula, for the emission rate required by Section A.III.1.e, if waste cleanup materials are sent off site for reclamation/disposal:

monthly OC emissions from cleanup operations (pounds/month) = summation of [(Ai-Bi) X di] for i = 1 to n

where:

i = 1, 2, 3,...n

n = the total number of different types of cleanup materials employed

Ai = the number of gallons of cleanup material i consumed (gallons/month)

Bi = the number of gallons of cleanup material i sent off site for disposal or reclamation, minus solids content of said material (gallons/month)

di = density of cleanup material i, in pounds/gallon

3. The permittee shall record and maintain the following information each day for this emissions unit:

3.a the company identification for each cleanup material employed; and

3.b documentation on whether or not each cleanup material employed is a photochemically reactive material.

IV. Reporting Requirements

1. The permittee shall submit quarterly deviation (excursion) reports that identify all exceedances of the rolling, 12-month OC emission limitation of 45 tons. All quarterly deviation reports shall be submitted in accordance with paragraph A.1.c of the General Terms and Conditions of this permit.

2. The permittee shall notify the Director (the appropriate Ohio EPA District Office or local air agency) in writing of any daily record showing the use of any noncomplying cleanup material (i.e., photochemically reactive cleanup material) in this emissions unit. The notification shall include a copy of such record and shall be sent to the Director (the appropriate Ohio EPA District Office or local air agency) within 30 days after the exceedance occurs.

3. The permittee shall submit annual reports that specify the total actual OC emissions from emissions units P001, P002, P003, P004, P005 and P006, combined. These reports shall be submitted by January 31 of each year and shall cover the previous calendar year.

V. Testing Requirements

1. Compliance with the emission limitations/usage restrictions of this permit shall be determined in accordance with the following methods:

1.a Emission Limitation: 45.0 tons OC per rolling, 12-month period

Applicable Compliance Method: Compliance shall be based upon the record keeping requirements specified in section A.III.1 of the terms and conditions of this permit.

V. Testing Requirements (continued)

1.b Emission Limitations: 6.5 lbs OC/hr, 28.5 tons OC/yr

Applicable Compliance Method: Compliance with the hourly limitation shall be determined by multiplying the maximum flush solvent usage rate (gallons/hr) by the maximum OC content of all the flush solvents (lbs/gallon), as applied, and then multiplying by 0.3.*

The tons/yr limitation was developed by multiplying the 6.5 lbs/hr limitation by 8760, and then dividing by 2000. Therefore, provided compliance is shown with the hourly limitation, compliance shall also be shown with the annual limitation.

* 70% of the cleanup materials (flush solvents) employed in this emissions unit is sent off site for disposal/reclamation.

2. The permittee shall determine the OC contents of the cleanup materials based upon the formulation data supplied by the manufacturer of the cleanup materials, or from data determined by analysis of each cleanup material, as received, in accordance with 40 CFR, Part 60, Appendix A, Method 24.

VI. Miscellaneous Requirements

None

B. State Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

Operations, Property, and/or Equipment	Applicable Rules/ Requirements	Applicable Emissions Limitations/Control Measures
foam line machine #5	none	none

2. Additional Terms and Conditions

None

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

1. The permit to install for emissions units R001, R002, R005, R006, R008, R009 thru R016, P001 thru P006 and P901 was evaluated based on the actual materials (coatings and cleanup materials) and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant(s):

Pollutant: Butyl Acetate

TLV (ug/m3): 950,000

Maximum Hourly Emission Rate (lbs/hr): 57.8

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 5,770

MAGLC (ug/m3): 22,620

Pollutant: methyl ethyl ketone

TLV (ug/m3): 590,000

Maximum Hourly Emission Rate (lbs/hr): 70.1

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 7,000

MAGLC (ug/m3): 14,048

Pollutant: isopropyl alcohol

TLV (ug/m3): 983,000

Maximum Hourly Emission Rate (lbs/hr): 20.6

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 2,060

MAGLC (ug/m3): 23,400

Pollutant: xylene

TLV (ug/m3): 434,000

Maximum Hourly Emission Rate (lbs/hr): 4.3

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 430

MAGLC (ug/m3): 10,333

III. Monitoring and/or Record Keeping Requirements (continued)

2. Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be still satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

a. changes in the composition of the materials used (coatings or cleanup materials), or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value previously modeled;

b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and

c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01(VV)(1)(a)(ii), and a modification of the existing permit to install will not be required. If the change(s) is (are) defined as a modification under other provisions of the modification definition (other than (VV)(1)(a)(ii)), then the permittee shall obtain a final permit to install prior to the change.

3. The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy:"

a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);

b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and

c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Part III - Terms and Conditions for Emissions Units

Emissions Unit ID: Foam Machine #6 (P005)

Activity Description: The foam machine is a foam dispensing machine.

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

Operations, Property, and/or Equipment	Applicable Rules/ Requirements	Applicable Emissions Limitations/Control Measures
foam line machine #6	OAC rule 3745-31-05 (PTI 03-11125)	See A.I.2.a. 6.5 lbs organic compounds OC/hr, 28.5 tons OC/yr (see A.I.2.b)
	OAC rule 3745-21-07(G)	none (See A.II.1.)

2. Additional Terms and Conditions

2.a The permittee shall emit no more than 45.0 tons of OC (from cleanup materials) per rolling, 12-month period from emissions units P001, P002, P003, P004, P005 and P006, combined.

2.b The 6.5 lbs OC/hr and 28.5 tons OC/yr emission limitations were established for PTI purposes to reflect the potential to emit for this emissions unit. Therefore, it is not necessary to develop record keeping and reporting requirements to ensure compliance with these limitations.

II. Operational Restrictions

1. The permittee shall not employ any material in this emissions unit that is a photochemically reactive material. "Photochemically reactive material" is defined in OAC rule 3745-21-01(C)(5).

III. Monitoring and/or Record Keeping Requirements

1. The permittee shall collect and record the following information each month for emissions units P001, P002, P003, P004, P005 and P006, combined:

1.a the company identification for each flush solvent (cleanup material) employed;

1.b the OC content of each cleanup material employed, in pounds per gallon;

1.c the number of gallons of each cleanup material employed;

1.d the number of gallons of each waste cleanup material sent off site for reclamation/disposal;

1.e the total OC emission rate for all the cleanup materials employed [summation of (b x (c - d)) for all cleanup materials], in pounds; and

1.f the rolling, 12-month summation of the monthly OC emission rates, in tons.

III. Monitoring and/or Record Keeping Requirements (continued)

2. The permittee may also calculate the monthly OC emission rate in accordance with the following formula, for the emission rate required by Section A.III.1.e, if waste cleanup materials are sent off site for reclamation/disposal:

monthly OC emissions from cleanup operations (pounds/month) = summation of [(Ai-Bi) X di] for i = 1 to n

where:

i = 1, 2, 3,...n

n = the total number of different types of cleanup materials employed

Ai = the number of gallons of cleanup material i consumed (gallons/month)

Bi = the number of gallons of cleanup material i sent off site for disposal or reclamation, minus solids content of said material (gallons/month)

di = density of cleanup material i, in pounds/gallon

3. The permittee shall record and maintain the following information each day for this emissions unit:

3.a the company identification for each cleanup material employed; and

3.b documentation on whether or not each cleanup material employed is a photochemically reactive material.

IV. Reporting Requirements

1. The permittee shall submit quarterly deviation (excursion) reports that identify all exceedances of the rolling, 12-month OC emission limitation of 45 tons. All quarterly deviation reports shall be submitted in accordance with paragraph A.1.c of the General Terms and Conditions of this permit.

2. The permittee shall notify the Director (the appropriate Ohio EPA District Office or local air agency) in writing of any daily record showing the use of any noncomplying cleanup material (i.e., photochemically reactive cleanup material) in this emissions unit. The notification shall include a copy of such record and shall be sent to the Director (the appropriate Ohio EPA District Office or local air agency) within 30 days after the exceedance occurs.

3. The permittee shall submit annual reports that specify the total actual OC emissions from emissions units P001, P002, P003, P004, P005 and P006, combined. These reports shall be submitted by January 31 of each year and shall cover the previous calendar year.

V. Testing Requirements

1. Compliance with the emission limitations/usage restrictions of this permit shall be determined in accordance with the following methods:

1.a Emission Limitation: 45.0 tons OC per rolling, 12-month period

Applicable Compliance Method: Compliance shall be based upon the record keeping requirements specified in section A.III.1 of the terms and conditions of this permit.

V. Testing Requirements (continued)

1.b Emission Limitations: 6.5 lbs OC/hr, 28.5 tons OC/yr

Applicable Compliance Method: Compliance with the hourly limitation shall be determined by multiplying the maximum flush solvent usage rate (gallons/hr) by the maximum OC content of all the flush solvents (lbs/gallon), as applied, and then multiplying by 0.3.*

The tons/yr limitation was developed by multiplying the 6.5 lbs/hr limitation by 8760, and then dividing by 2000. Therefore, provided compliance is shown with the hourly limitation, compliance shall also be shown with the annual limitation.

* 70% of the cleanup materials (flush solvents) employed in this emissions unit is sent off site for disposal/reclamation.

2. The permittee shall determine the OC contents of the cleanup materials based upon the formulation data supplied by the manufacturer of the cleanup materials, or from data determined by analysis of each cleanup material, as received, in accordance with 40 CFR, Part 60, Appendix A, Method 24.

VI. Miscellaneous Requirements

None

B. State Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

Operations, Property, and/or Equipment	Applicable Rules/ Requirements	Applicable Emissions Limitations/Control Measures
foam line machine #6	none	none

2. Additional Terms and Conditions

None

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

1. The permit to install for emissions units R001, R002, R005, R006, R008, R009 thru R016, P001 thru P006 and P901 was evaluated based on the actual materials (coatings and cleanup materials) and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant(s):

Pollutant: Butyl Acetate

TLV (ug/m3): 950,000

Maximum Hourly Emission Rate (lbs/hr): 57.8

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 5,770

MAGLC (ug/m3): 22,620

Pollutant: methyl ethyl ketone

TLV (ug/m3): 590,000

Maximum Hourly Emission Rate (lbs/hr): 70.1

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 7,000

MAGLC (ug/m3): 14,048

Pollutant: isopropyl alcohol

TLV (ug/m3): 983,000

Maximum Hourly Emission Rate (lbs/hr): 20.6

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 2,060

MAGLC (ug/m3): 23,400

Pollutant: xylene

TLV (ug/m3): 434,000

Maximum Hourly Emission Rate (lbs/hr): 4.3

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 430

MAGLC (ug/m3): 10,333

III. Monitoring and/or Record Keeping Requirements (continued)

2. Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be still satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

a. changes in the composition of the materials used (coatings or cleanup materials), or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value previously modeled;

b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and

c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01(VV)(1)(a)(ii), and a modification of the existing permit to install will not be required. If the change(s) is (are) defined as a modification under other provisions of the modification definition (other than (VV)(1)(a)(ii)), then the permittee shall obtain a final permit to install prior to the change.

3. The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy:"

a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);

b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and

c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Part III - Terms and Conditions for Emissions Units

Emissions Unit ID: Foam Machine #7 (P006)

Activity Description: The foam machine is a foam dispensing machine.

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

Operations, Property, and/or Equipment	Applicable Rules/ Requirements	Applicable Emissions Limitations/Control Measures
foam line machine #7	OAC rule 3745-31-05 (PTI 03-11125)	See A.I.2.a. 6.5 lbs organic compounds OC/hr, 28.5 tons OC/yr (see A.I.2.b)
	OAC rule 3745-21-07(G)	none (See A.II.1.)

2. Additional Terms and Conditions

2.a The permittee shall emit no more than 45.0 tons of OC (from cleanup materials) per rolling, 12-month period from emissions units P001, P002, P003, P004, P005 and P006, combined.

2.b The 6.5 lbs OC/hr and 28.5 tons OC/yr emission limitations were established for PTI purposes to reflect the potential to emit for this emissions unit. Therefore, it is not necessary to develop record keeping and reporting requirements to ensure compliance with these limitations.

II. Operational Restrictions

1. The permittee shall not employ any material in this emissions unit that is a photochemically reactive material. "Photochemically reactive material" is defined in OAC rule 3745-21-01(C)(5).

III. Monitoring and/or Record Keeping Requirements

1. The permittee shall collect and record the following information each month for emissions units P001, P002, P003, P004, P005 and P006, combined:

1.a the company identification for each flush solvent (cleanup material) employed;

1.b the OC content of each cleanup material employed, in pounds per gallon;

1.c the number of gallons of each cleanup material employed;

1.d the number of gallons of each waste cleanup material sent off site for reclamation/disposal;

1.e the total OC emission rate for all the cleanup materials employed [summation of (b x (c - d)) for all cleanup materials], in pounds; and

1.f the rolling, 12-month summation of the monthly OC emission rates, in tons.

III. Monitoring and/or Record Keeping Requirements (continued)

2. The permittee may also calculate the monthly OC emission rate in accordance with the following formula, for the emission rate required by Section A.III.1.e, if waste cleanup materials are sent off site for reclamation/disposal:

monthly OC emissions from cleanup operations (pounds/month) = summation of [(Ai-Bi) X di] for i = 1 to n

where:

i = 1, 2, 3,...n

n = the total number of different types of cleanup materials employed

Ai = the number of gallons of cleanup material i consumed (gallons/month)

Bi = the number of gallons of cleanup material i sent off site for disposal or reclamation, minus solids content of said material (gallons/month)

di = density of cleanup material i, in pounds/gallon

3. The permittee shall record and maintain the following information each day for this emissions unit:

3.a the company identification for each cleanup material employed; and

3.b documentation on whether or not each cleanup material employed is a photochemically reactive material.

IV. Reporting Requirements

1. The permittee shall submit quarterly deviation (excursion) reports that identify all exceedances of the rolling, 12-month OC emission limitation of 45 tons. All quarterly deviation reports shall be submitted in accordance with paragraph A.1.c of the General Terms and Conditions of this permit.

2. The permittee shall notify the Director (the appropriate Ohio EPA District Office or local air agency) in writing of any daily record showing the use of any noncomplying cleanup material (i.e., photochemically reactive cleanup material) in this emissions unit. The notification shall include a copy of such record and shall be sent to the Director (the appropriate Ohio EPA District Office or local air agency) within 30 days after the exceedance occurs.

3. The permittee shall submit annual reports that specify the total actual OC emissions from emissions units P001, P002, P003, P004, P005 and P006, combined. These reports shall be submitted by January 31 of each year and shall cover the previous calendar year.

V. Testing Requirements

1. Compliance with the emission limitations/usage restrictions of this permit shall be determined in accordance with the following methods:

1.a Emission Limitation: 45.0 tons OC per rolling, 12-month period

Applicable Compliance Method: Compliance shall be based upon the record keeping requirements specified in section A.III.1 of the terms and conditions of this permit.

V. Testing Requirements (continued)

1.b Emission Limitations: 6.5 lbs OC/hr, 28.5 tons OC/yr

Applicable Compliance Method: Compliance with the hourly limitation shall be determined by multiplying the maximum flush solvent usage rate (gallons/hr) by the maximum OC content of all the flush solvents (lbs/gallon), as applied, and then multiplying by 0.3.*

The tons/yr limitation was developed by multiplying the 6.5 lbs/hr limitation by 8760, and then dividing by 2000. Therefore, provided compliance is shown with the hourly limitation, compliance shall also be shown with the annual limitation.

* 70% of the cleanup materials (flush solvents) employed in this emissions unit is sent off site for disposal/reclamation.

2. The permittee shall determine the OC contents of the cleanup materials based upon the formulation data supplied by the manufacturer of the cleanup materials, or from data determined by analysis of each cleanup material, as received, in accordance with 40 CFR, Part 60, Appendix A, Method 24.

VI. Miscellaneous Requirements

None

B. State Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

Operations, Property, and/or Equipment	Applicable Rules/ Requirements	Applicable Emissions Limitations/Control Measures
foam line machine #7	none	none

2. Additional Terms and Conditions

None

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

1. The permit to install for emissions units R001, R002, R005, R006, R008, R009 thru R016, P001 thru P006 and P901 was evaluated based on the actual materials (coatings and cleanup materials) and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant(s):

Pollutant: Butyl Acetate

TLV (ug/m3): 950,000

Maximum Hourly Emission Rate (lbs/hr): 57.8

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 5,770

MAGLC (ug/m3): 22,620

Pollutant: methyl ethyl ketone

TLV (ug/m3): 590,000

Maximum Hourly Emission Rate (lbs/hr): 70.1

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 7,000

MAGLC (ug/m3): 14,048

Pollutant: isopropyl alcohol

TLV (ug/m3): 983,000

Maximum Hourly Emission Rate (lbs/hr): 20.6

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 2,060

MAGLC (ug/m3): 23,400

Pollutant: xylene

TLV (ug/m3): 434,000

Maximum Hourly Emission Rate (lbs/hr): 4.3

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 430

MAGLC (ug/m3): 10,333

III. Monitoring and/or Record Keeping Requirements (continued)

2. Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be still satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

a. changes in the composition of the materials used (coatings or cleanup materials), or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value previously modeled;

b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and

c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01(VV)(1)(a)(ii), and a modification of the existing permit to install will not be required. If the change(s) is (are) defined as a modification under other provisions of the modification definition (other than (VV)(1)(a)(ii)), then the permittee shall obtain a final permit to install prior to the change.

3. The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy:"

a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);

b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and

c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Part III - Terms and Conditions for Emissions Units

Emissions Unit ID: Solvent Clean up (plantwide) (P901)

Activity Description: various clean up operations

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

Operations, Property, and/or Equipment	Applicable Rules/ Requirements	Applicable Emissions Limitations/Control Measures
facility solvent-cleaning operations	OAC rule 3745-31-05 (PTI 03-11125)	See A.I.2.a. 4.0 tons organic compounds (OC)/month
	OAC rule 3745-21-07(G)	none (See A.II.1.)

2. Additional Terms and Conditions

2.a The permittee shall emit no more than 15.0 tons of OC per rolling, 12-month period from this emissions unit.

II. Operational Restrictions

1. The permittee shall not employ any cleanup material in this emissions unit that is a photochemically reactive material. "Photochemically reactive material" is defined in OAC rule 3745-21-01(C)(5).

III. Monitoring and/or Record Keeping Requirements

1. The permittee shall collect and record the following information each month for this emissions unit:

1.a the company identification for each cleanup material employed;

1.b the OC content of each cleanup material employed, in pounds per gallon;

1.c the number of gallons of each cleanup material employed;

1.d the number of gallons of each waste cleanup material sent off site for reclamation/disposal;

1.e the total OC emission rate for all the cleanup materials employed [summation of (b x (c - d)) for all cleanup materials], in pounds; and

1.f the rolling, 12-month summation of the monthly OC emission rates, in tons.

III. Monitoring and/or Record Keeping Requirements (continued)

2. The permittee may also calculate the monthly OC emission rate in accordance with the following formula, for the emission rate required by Section A.III.1.e, if waste cleanup materials are sent off site for reclamation/disposal:

monthly OC emissions from cleanup operations (pounds/month) = summation of [(Ai-Bi) X di] for i = 1 to n

where:

i = 1, 2, 3,...n

n = the total number of different types of cleanup materials employed

Ai = the number of gallons of cleanup material i consumed (gallons/month)

Bi = the number of gallons of cleanup material i sent off site for disposal or reclamation, minus solids content of said material (gallons/month)

di = density of cleanup material i, in pounds/gallon

3. The permittee shall record and maintain the following information each day for this emissions unit:

3.a the company identification for each cleanup material employed; and

3.b documentation on whether or not each cleanup material employed is a photochemically reactive material.

IV. Reporting Requirements

1. The permittee shall submit deviation (excursion) reports that identify the following information:

a. all exceedances of the rolling, 12-month OC emission limitation of 15 tons; and

b. all exceedance of the monthly OC emission limitation of 4.0 tons.

All quarterly deviation reports shall be submitted in accordance with paragraph A.1.c of the General Terms and Conditions of this permit.

2. The permittee shall notify the Director (the appropriate Ohio EPA District Office or local air agency) in writing of any daily record showing the use of any noncomplying cleanup material (i.e., photochemically reactive cleanup material) in this emissions unit. The notification shall include a copy of such record and shall be sent to the Director (the appropriate Ohio EPA District Office or local air agency) within 30 days after the exceedance occurs.

3. The permittee shall submit annual reports that specify the total actual OC emissions from this emissions unit. These reports shall be submitted by January 31 of each year and shall cover the previous calendar year.

V. Testing Requirements

1. Compliance with the emission limitations/usage restrictions of this permit shall be determined in accordance with the following methods:

1.a Emission Limitation: 15.0 tons OC per rolling, 12-month period

Applicable Compliance Method: Compliance shall be based upon the record keeping requirements specified in section A.III.1 of the terms and conditions of this permit.

1.b Emission Limitation: 4.0 tons OC/month

Applicable Compliance Method: Compliance shall be based upon the record keeping requirements specified in section A.III.1 of the terms and conditions of this permit.

V. Testing Requirements (continued)

2. The permittee shall determine the OC contents of the cleanup materials based upon the formulation data supplied by the manufacturer of the cleanup materials, or from data determined by analysis of each cleanup material, as received, in accordance with 40 CFR, Part 60, Appendix A, Method 24.

VI. Miscellaneous Requirements

None

B. State Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

Operations, Property, and/or Equipment	Applicable Rules/ Requirements	Applicable Emissions Limitations/Control Measures
facility solvent-cleaning operations	none	none

2. Additional Terms and Conditions

None

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

1. The permit to install for emissions units R001, R002, R005, R006, R008, R009 thru R016, P001 thru P006 and P901 was evaluated based on the actual materials (cleanup materials) and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant(s):

Pollutant: butyl Acetate

TLV (ug/m3): 950,000

Maximum Hourly Emission Rate (lbs/hr): 57.8

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 5,770

MAGLC (ug/m3): 22,620

Pollutant: methyl ethyl ketone

TLV (ug/m3): 590,000

Maximum Hourly Emission Rate (lbs/hr): 70.1

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 7,000

MAGLC (ug/m3): 14,048

Pollutant: isopropyl alcohol

TLV (ug/m3): 983,000

Maximum Hourly Emission Rate (lbs/hr): 20.6

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 2,060

MAGLC (ug/m3): 23,400

Pollutant: xylene

TLV (ug/m3): 434,000

Maximum Hourly Emission Rate (lbs/hr): 4.3

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 430

MAGLC (ug/m3): 10,333

III. Monitoring and/or Record Keeping Requirements (continued)

2. Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be still satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

a. changes in the composition of the materials used (cleanup materials), or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value previously modeled;

b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and

c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01(VV)(1)(a)(ii), and a modification of the existing permit to install will not be required. If the change(s) is (are) defined as a modification under other provisions of the modification definition (other than (VV)(1)(a)(ii)), then the permittee shall obtain a final permit to install prior to the change.

3. The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy:"

a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);

b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and

c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Part III - Terms and Conditions for Emissions Units

Emissions Unit ID: Specialty Ext Paint Booth (R001)

Activity Description: This process puts a finish coat on polyurethane millwork

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

Operations, Property, and/or Equipment	Applicable Rules/ Requirements	Applicable Emissions Limitations/Control Measures
specialty paint booth, sample finishing	OAC rule 3745-31-05 (PTI 03-11125)	See A.I.2.a.
		17.5 lbs organic compounds (OC)/hr (see A.I.2.b)
		0.65 lb particulate emissions (PE)/hr (see A.I.2.b), 0.7 ton PE/yr
		0% opacity, as a six-minute average
	OAC rule 3745-21-07(G)	none (See A.II.1.)

2. Additional Terms and Conditions

2.a The permittee shall emit no more than 15.0 tons of OC, from coatings, per rolling, 12-month summation of the monthly OC input rates for this emissions unit.

2.b The 17.5 lbs OC/hr and 0.65 lb PE/hr emission limitations were established for PTI purposes to reflect the potentials to emit for this emissions unit. Therefore, it is not necessary to develop record keeping and reporting requirements to ensure compliance with these limitations.

2.c The uncontrolled mass rate of PE from this emissions unit is less than 10 lbs/hr. Therefore, pursuant to OAC rule 3745-17-11(A)(2)(a)(ii), Figure II of OAC rule 3745-17-11 does not apply. Also, Table I does not apply because the facility is located in Fulton County.

2.d This emissions unit is exempt from the visible emissions limitations specified in OAC rule 3745-17-07(A), pursuant to OAC rule 3745-17-07(A)(3)(h), because OAC rule 3745-17-11 is not applicable.

2.e The OC emissions from the cleanup materials used in this emissions unit are permitted under emissions unit P901. Therefore, no record keeping and reporting requirements are necessary for the cleanup operations associated with this emissions unit.

II. Operational Restrictions

1. The permittee shall not employ any material in this emissions unit that is a photochemically reactive material. "Photochemically reactive material" is defined in OAC rule 3745-21-01(C)(5).

2. The permittee shall operate the dry filtration system whenever this emissions unit is in operation.

III. Monitoring and/or Record Keeping Requirements

1. The permittee shall collect and record the following information each month for this emissions unit:

1.a the company identification of each coating employed;

1.b the OC content of each coating employed, in pounds per gallon, as applied;

1.c the solids content of each coating employed, in pounds per gallon, as applied;

1.d the number of gallons of each coating employed;

1.e the total OC emission rate for all the coatings employed [summation of (b x d) for all coatings], in tons;

1.f the total coating solids usage rate for all the coatings employed [summation of (c x d) for all coatings], in tons; and

1.g the rolling, 12-month summation of the monthly OC emission rates (input rates), in tons.

2. The permittee shall record and maintain the following information each day for this emissions unit:

2.a the company identification for each material employed; and

2.b documentation on whether or not each material employed is a photochemically reactive material.

3. The permittee shall maintain daily records that document any time periods when the dry filtration system was not in service when the emissions unit was in operation.

IV. Reporting Requirements

1. The permittee shall submit quarterly deviation (excursion) reports that identify all exceedances of the rolling, 12-month OC emission limitation of 15 tons. All quarterly deviation reports shall be submitted in accordance with paragraph A.1.c of the General Terms and Conditions of this permit.

2. The permittee shall notify the Director (the appropriate Ohio EPA District Office or local air agency) in writing of any daily record showing the use of any noncomplying material (i.e., photochemically reactive material) in this emissions unit. The notification shall include a copy of such record and shall be sent to the Director (the appropriate Ohio EPA District Office or local air agency) within 30 days after the exceedance occurs.

3. The permittee shall submit annual reports that specify the total actual OC emissions from this emissions unit. These reports shall be submitted by January 31 of each year and shall cover the previous calendar year.

4. The permittee shall notify the Director (the appropriate Ohio EPA District Office or local air agency) in writing of any daily record showing that the dry filtration system was not in service when the emissions unit was in operation. The notification shall include a copy of such record and shall be sent to the Director (the appropriate District Office or local air agency) within 30 days after the event occurs.

V. Testing Requirements

1. Compliance with the emission limitations/usage restrictions of this permit shall be determined in accordance with the following methods:

1.a Emission Limitation: 15.0 tons OC per rolling, 12-month period

Applicable Compliance Method: Compliance shall be based upon the record keeping requirements specified in section A.III.1 of the terms and conditions of this permit.

1.b Emission Limitation: 17.5 lbs OC/hr

Applicable Compliance Method: Compliance shall be determined by multiplying the maximum coating usage rate (gallons/hr) by the maximum OC content of all the coatings (lbs/gallon).

V. Testing Requirements (continued)

1.c Emission Limitation: 0.65 lb PE/hr

Applicable Compliance Method:

To determine the actual worst case particulate emissions rate (E), the following equation shall be used for the paint spraying operations:

E = particulate emissions rate (lbs/hr)

E = (maximum coating solids usage rate, in pounds per hour) X (1-TE) X (1-CE)

where:

TE = transfer efficiency, which is the ratio of the amount of coating solids deposited on the coated part to the amount of coating solids used

CE = control efficiency of the control equipment

If required, the permittee shall demonstrate compliance with the emission limit above pursuant to OAC rule 3745-17-03(B)(10).

1.d Emission Limitation: 0.7 ton PE/yr

Applicable Compliance Method:

The permittee shall determine compliance based upon the following equation:

E = particulate emissions rate (tons/yr)

E = [coating solids usage rate (this is calculated by summing the 12 monthly coating solids usage rates, from section 1.f, for the calendar year), in tons per year] X (1-TE) X (1-CE)

where:

TE = transfer efficiency, which is the ratio of the amount of coating solids deposited on the coated part to the amount of coating solids used)

CE = control efficiency of the control equipment

1.e Emission Limitation: 0% opacity, as a six-minute average

Applicable Compliance Method: If required, compliance with the visible emissions limitation shall be determined in accordance with Method 9 of 40 CFR, Part 60, Appendix A.

2. The permittee shall determine the OC contents of the coatings based upon the formulation data supplied by the manufacturer of the coatings, or from data determined by analysis of each coating, as received, in accordance with 40 CFR, Part 60, Appendix A, Method 24.

VI. Miscellaneous Requirements

None

B. State Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

Operations, Property, and/or Equipment	Applicable Rules/ Requirements	Applicable Emissions Limitations/Control Measures
specialty paint booth, sample finishing	none	none

2. Additional Terms and Conditions

None

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

1. The permit to install for emissions units R001, R002, R005, R006, R008, R009 thru R016, P001 thru P006 and P901 was evaluated based on the actual materials (coatings and cleanup materials) and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant(s):

Pollutant: Butyl Acetate

TLV (ug/m3): 950,000

Maximum Hourly Emission Rate (lbs/hr): 57.8

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 5,770

MAGLC (ug/m3): 22,620

Pollutant: methyl ethyl ketone

TLV (ug/m3): 590,000

Maximum Hourly Emission Rate (lbs/hr): 70.1

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 7,000

MAGLC (ug/m3): 14,048

Pollutant: isopropyl alcohol

TLV (ug/m3): 983,000

Maximum Hourly Emission Rate (lbs/hr): 20.6

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 2,060

MAGLC (ug/m3): 23,400

Pollutant: xylene

TLV (ug/m3): 434,000

Maximum Hourly Emission Rate (lbs/hr): 4.3

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 430

MAGLC (ug/m3): 10,333

III. Monitoring and/or Record Keeping Requirements (continued)

2. Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be still satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

a. changes in the composition of the materials used (coatings or cleanup materials), or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value previously modeled;

b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and

c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01(VV)(1)(a)(ii), and a modification of the existing permit to install will not be required. If the change(s) is (are) defined as a modification under other provisions of the modification definition (other than (VV)(1)(a)(ii)), then the permittee shall obtain a final permit to install prior to the change.

3. The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy:"

a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);

b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and

c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Part III - Terms and Conditions for Emissions Units

Emissions Unit ID: Master/Carrier Booth (R002)

Activity Description: This process coats wood masters and silicone molds

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

Operations, Property, and/or Equipment	Applicable Rules/ Requirements	Applicable Emissions Limitations/Control Measures
mold master paint booth	OAC rule 3745-31-05 (PTI 03-11125)	See A.I.2.a. The requirements of this rule also include compliance with the requirements of OAC rule 3745-21-07(G)(2). 0.65 lb particulate emissions (PE)/hr, 3.25 lbs PE/day, 0.5 ton PE/yr (see A.I.2.b) 0% opacity, as a six-minute average
	OAC rule 3745-21-07(G)(2)	8 lbs organic compounds (OC)/hr, 40 lbs OC/day

2. Additional Terms and Conditions

2.a The permittee shall emit no more than 6.5 tons of OC (from coatings), based upon a rolling, 12-month period from emissions units R002 and R015, combined.

2.b The PE, from emissions units R002 and R015, combined, shall not exceed 0.5 ton/yr.

2.c The uncontrolled mass rate of PE from this emissions unit is less than 10 lbs/hr. Therefore, pursuant to OAC rule 3745-17-11(A)(2)(a)(ii), Figure II of OAC rule 3745-17-11 does not apply. Also, Table I does not apply because the facility is located in Fulton County.

2.d This emissions unit is exempt from the visible emissions limitations specified in OAC rule 3745-17-07(A), pursuant to OAC rule 3745-17-07(A)(3)(h), because OAC rule 3745-17-11 is not applicable.

2.e The OC emissions from the cleanup materials used in this emissions unit are permitted under emissions unit P901. Therefore, no record keeping and reporting requirements are necessary for the cleanup operations associated with this emissions unit.

II. Operational Restrictions

1. The permittee shall operate the dry filtration system whenever this emissions unit is in operation.

2. The permittee shall not employ any cleanup material in this emissions unit that is a photochemically reactive material. "Photochemically reactive material" is defined in OAC rule 3745-21-01(C)(5).

III. Monitoring and/or Record Keeping Requirements

1. The permitee shall collect and record the following information each day for this emissions unit:

1.a the company identification for each coating employed;

1.b the OC content of each coating employed, in pounds per gallon;

1.c the number of gallons of each coating employed;

1.d the total OC emission rate for all the coatings employed [summation of (b x c) for all coatings], in pounds;

1.e the number of hours the emissions unit was in operation; and

1.f the average hourly OC emission rate (d/e), in pounds/hr (average).

2. The permittee shall collect and record the following information each month for emissions units R002 and R015, combined:

2.a the company identification for each coating employed;

2.b the OC content of each coating employed, in pounds per gallon, as applied;

2.c the solids content of each coating employed, in pounds per gallon;

2.d the number of gallons of each coating employed;

2.e the total OC emission rate for all the coatings employed [summation of (b x d) for all coatings], in tons;

2.f the total coating solids usage rate for all the coatings employed [summation of (c x d) for all coatings], in tons; and

2.g the rolling, 12-month summation of the monthly OC emission rates (input rates), in tons.

3. The permittee shall maintain daily records that document any time periods when the dry filtration system was not in service when the emissions unit was in operation.

IV. Reporting Requirements

1. The permittee shall submit quarterly deviation (excursion) reports that include the following information:

1.a an identification of each day during which the average hourly OC emissions from the coatings exceed 8 pounds per hour, and the actual average hourly OC emissions for each such day;

1.b an identification of each day during which the OC emissions from the coatings exceed 40 pounds per day, and the actual organic compound emissions for each such day; and

1.c an identification of all exceedances of the rolling, 12-month OC emission limitation of 6.5 tons.

All quarterly deviation reports shall be submitted in accordance with paragraph A.1.c of the General Terms and Conditions of this permit.

2. The permittee shall submit annual reports that specify the total actual OC emissions from emissions units R002 and R015, combined. These reports shall be submitted by January 31 of each year and shall cover the previous calendar year.

3. The permittee shall notify the Director (the appropriate Ohio EPA District Office or local air agency) in writing of any daily record showing that the dry filtration system was not in service when the emissions unit was in operation. The notification shall include a copy of such record and shall be sent to the Director (the appropriate District Office or local air agency) within 30 days after the event occurs.

V. Testing Requirements

1. Compliance with the emission limitations/usage restrictions of this permit shall be determined in accordance with the following methods:

1.a Emission Limitation: 6.5 tons OC per rolling, 12-month period

Applicable Compliance Method: Compliance shall be based upon the record keeping requirements specified in section A.III.2 of the terms and conditions of this permit.

1.b Emission Limitations: 8 lbs/hr, 40 lbs/day

Applicable Compliance Method: Compliance shall be based upon the record keeping requirements specified in section A.III.1 of the terms and conditions of this permit.

1.c Emission Limitation: 0.65 lb PE/hr

Applicable Compliance Method:

To determine the actual worst case particulate emissions rate (E), the following equation shall be used for the paint spraying operations:

E = particulate emissions rate (lbs/hr)

E = (maximum coating solids usage rate, in pounds per hour) X (1-TE) X (1-CE)

where:

TE = transfer efficiency, which is the ratio of the amount of coating solids deposited on the coated part to the amount of coating solids used

CE = control efficiency of the control equipment

If required, the permittee shall demonstrate compliance with the emission limit abovee pursuant to OAC rule 3745-17-03(B)(10).

1.d Emission Limitation: 3.25 lbs PE/day

Applicable Compliance Method:

To determine the actual worst case particulate emissions rate (E), the following equation shall be used for the paint spraying operations:

E = particulate emissions rate (lbs/day)

E = (maximum coating solids usage rate, in pounds per day) X (1-TE) X (1-CE)

where:

TE = transfer efficiency, which is the ratio of the amount of coating solids deposited on the coated part to the amount of coating solids used

CE = control efficiency of the control equipment

1.e Emission Limitation: 0% opacity, as a six-minute average

Applicable Compliance Method: If required, compliance with the visible emissions limitation shall be determined in accordance with Method 9 of 40 CFR, Part 60, Appendix A.

V. Testing Requirements (continued)

1.f Emission Limitation: 0.5 ton PE/yr (for emissions units R002 and R015, combined)

Applicable Compliance Method:

The permittee shall determine compliance based upon the following equation:

E = particulate emissions rate (tons/yr)

E = [coating solids usage rate (this is calculated by summing the 12 monthly coating solids usage rates, from section 2.f, for the calendar year), in tons per year] X (1-TE) X (1-CE)

where:

TE = transfer efficiency, which is the ratio of the amount of coating solids deposited on the coated part to the amount of coating solids used)

CE = control efficiency of the control equipment

2. The permittee shall determine the OC contents of the coatings based upon the formulation data supplied by the manufacturer of the coatings, or from data determined by analysis of each coating, as received, in accordance with 40 CFR, Part 60, Appendix A, Method 24.

VI. Miscellaneous Requirements

None

B. State Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

Operations, Property, and/or Equipment	Applicable Rules/ Requirements	Applicable Emissions Limitations/Control Measures
mold master paint booth	none	none

2. Additional Terms and Conditions

None

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

1. The permit to install for emissions units R001, R002, R005, R006, R008, R009 thru R016, P001 thru P006, and P901 was evaluated based on the actual materials (coatings and cleanup materials) and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant(s):

Pollutant: Butyl Acetate

TLV (ug/m3): 950,000

Maximum Hourly Emission Rate (lbs/hr): 57.8

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 5,770

MAGLC (ug/m3): 22,620

Pollutant: methyl ethyl ketone

TLV (ug/m3): 590,000

Maximum Hourly Emission Rate (lbs/hr): 70.1

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 7,000

MAGLC (ug/m3): 14,048

Pollutant: isopropyl alcohol

TLV (ug/m3): 983,000

Maximum Hourly Emission Rate (lbs/hr): 20.6

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 2,060

MAGLC (ug/m3): 23,400

Pollutant: xylene

TLV (ug/m3): 434,000

Maximum Hourly Emission Rate (lbs/hr): 4.3

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 430

MAGLC (ug/m3): 10,333

III. Monitoring and/or Record Keeping Requirements (continued)

2. Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be still satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

a. changes in the composition of the materials used (coatings or cleanup materials), or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value previously modeled;

b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and

c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01(VV)(1)(a)(ii), and a modification of the existing permit to install will not be required. If the change(s) is (are) defined as a modification under other provisions of the modification definition (other than (VV)(1)(a)(ii)), then the permittee shall obtain a final permit to install prior to the change.

3. The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy:"

a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);

b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and

c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Part III - Terms and Conditions for Emissions Units

Emissions Unit ID: Exterior 1 Paint Booth (R005)

Activity Description: This process puts a finish coat on polyurethane millwork

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

Operations, Property, and/or Equipment	Applicable Rules/ Requirements	Applicable Emissions Limitations/Control Measures
exterior paint booth #1	OAC rule 3745-31-05 (PTI 03-11125)	See A.I.2.a.
		17.5 lbs organic compounds (OC)/hr, 76.7 tons OC/yr (see A.I.2.b)
		0.65 lb particulate emissions (PE)/hr, 2.8 tons PE/yr (see A.I.2.b)
		3.6 tons PE/yr (see A.I.2.c)
		0% opacity, as a six-minute average
	OAC rule 3745-21-07(G)	none (See A.II.1.)

2. Additional Terms and Conditions

2.a The permittee shall emit no more than 80.0 tons of OC (from coatings), based upon a rolling, 12-month period from emissions units R005, R006 and R016, combined.

2.b The 17.5 lbs OC/hr, 76.7 tons OC/yr, 0.65 lb PE/hr and 2.8 tons PE/yr emission limitations were established for PTI purposes to reflect the potentials to emit for this emissions unit. Therefore, it is not necessary to develop record keeping and reporting requirements to ensure compliance with these limitations.

2.c The PE, from emissions units R005, R006 and R016, combined, shall not exceed 3.6 tons/yr.

2.d The OC emissions from the cleanup materials used in this emissions unit are permitted under emissions unit P901. Therefore, no record keeping and reporting requirements are necessary for the cleanup operations associated with this emissions unit.

2.e The uncontrolled mass rate of PE from this emissions unit is less than 10 lbs/hr. Therefore, pursuant to OAC rule 3745-17-11(A)(2)(a)(ii), Figure II of OAC rule 3745-17-11 does not apply. Also, Table I does not apply because the facility is located in Fulton County.

2.f This emissions unit is exempt from the visible emissions limitations specified in OAC rule 3745-17-07(A), pursuant to OAC rule 3745-17-07(A)(3)(h), because OAC rule 3745-17-11 is not applicable.

II. Operational Restrictions

1. The permittee shall not employ any material in this emissions unit that is a photochemically reactive material. "Photochemically reactive material" is defined in OAC rule 3745-21-01(C)(5).

II. Operational Restrictions (continued)

2. The permittee shall operate the dry filtration system whenever this emissions unit is in operation.

III. Monitoring and/or Record Keeping Requirements

1. The permittee shall collect and record the following information each month for emissions units R005, R006 and R016, combined:

1.a the company identification for each coating employed;

1.b the OC content of each coating employed, in pounds per gallon, as applied;

1.c the solids content of each coating employed, in pounds per gallon;

1.d the number of gallons of each coating employed;

1.e the total OC emission rate for all the coatings employed [summation of (b x d) for all coatings], in tons;

1.f the total coating solids usage rate for all the coatings employed [summation of (c x d) for all coatings], in tons; and

1.g the rolling, 12-month summation of the monthly OC emission rates (input rates), in tons.

2. The permittee shall record and maintain the following information each day for the coatings employed in this emissions unit:

2.a the company identification for each material employed; and

2.b documentation on whether or not each material employed is a photochemically reactive material.

3. The permittee shall maintain daily records that document any time periods when the dry filtration system was not in service when the emissions unit was in operation.

IV. Reporting Requirements

1. The permittee shall submit quarterly deviation (excursion) reports that identify all exceedances of the rolling, 12-month OC emission limitation of 80 tons. All quarterly deviation reports shall be submitted in accordance with paragraph A.1.c of the General Terms and Conditions of this permit.

2. The permittee shall notify the Director (appropriate Ohio EPA District Office or local air agency) in writing of any daily record showing the use of any noncomplying material (i.e., photochemically reactive material) in this emissions unit. The notification shall include a copy of such record and shall be sent to the Director (appropriate Ohio EPA District Office or local air agency) within 30 days after the exceedance occurs.

3. The permittee shall submit annual reports that specify the total actual OC emissions from emissions units R005, R006 and R016, combined. These reports shall be submitted by January 31 of each year and shall cover the previous calendar year.

4. The permittee shall notify the Director (the appropriate Ohio EPA District Office or local air agency) in writing of any daily record showing that the dry filtration system was not in service when the emissions unit was in operation. The notification shall include a copy of such record and shall be sent to the Director (the appropriate Ohio EPA District Office or local air agency) within 30 days after the event occurs.

V. Testing Requirements

1. Compliance with the emission limitations/usage restrictions of this permit shall be determined in accordance with the following methods:

1.a Emission Limitations: 80.0 tons OC per rolling, 12-month period

Applicable Compliance Method: Compliance shall be based upon the record keeping requirements specified in section A.III.1 of the terms and conditions of this permit.

V. Testing Requirements (continued)

1.b Emission Limitations: 17.5 lbs OC/hr, 76.7 tons OC/yr

Applicable Compliance Method: Compliance with the hourly limitation shall be determined by multiplying the maximum coating usage rate (gallons/hr) by the maximum OC content of all the coatings (pounds/gallon), as applied.

If required, compliance with the hourly limitation shall be demonstrated pursuant to Method 25 of 40 CFR, Part 60, Appendix A.

Compliance with the annual limitation shall be assumed as long as compliance with hourly limitation is maintained (the annual limitation was calculated by multiplying the hourly limitation by 8760, and then dividing by 2000).

1.c Emission Limitations: 0.65 lb PE/hr, 2.8 tons PE/yr

Applicable Compliance Method:

To determine the actual worst case particulate emissions rate (E), the following equation shall be used for the paint spraying operations:

E = particulate emissions rate (lbs/hr)

E = (maximum coating solids usage rate, in pounds per hour) X (1-TE) X (1-CE)

where:

TE = transfer efficiency, which is the ratio of the amount of coating solids deposited on the coated part to the amount of coating solids used

CE = control efficiency of the control equipment

If required, the permittee shall demonstrate compliance with the emission limit above pursuant to OAC rule 3745-17-03(B)(10).

The tons/yr limitation was developed by multiplying the 0.65 lb/hr limitation by 8760, and then dividing by 2000. Therefore, provided compliance is shown with the hourly limitation, compliance shall also be shown with the annual limitation.

1.d Emission Limitation: 3.6 tons PE/yr (for emissions units R005, R006 and R016, combined)

Applicable Compliance Method:

The permittee shall determine compliance based upon the following equation:

E = particulate emissions rate (tons/yr)

E = [coating solids usage rate (this is calculated by summing the 12 monthly coating solids usage rates, from section 1.f, for the calendar year), in tons per year] X (1-TE) X (1-CE)

where:

TE = transfer efficiency, which is the ratio of the amount of coating solids deposited on the coated part to the amount of coating solids used)

CE = control efficiency of the control equipment

1.e Emission Limitation: 0% opacity, as a six-minute average

Applicable Compliance Method: If required, compliance with the visible emissions limitation shall be determined in accordance with Method 9 of 40 CFR, Part 60, Appendix A.

V. Testing Requirements (continued)

2. The permittee shall determine the OC contents of the coatings based upon the formulation data supplied by the manufacturer of the coatings, or from data determined by analysis of each coating, as received, in accordance with 40 CFR, Part 60, Appendix A, Method 24.

VI. Miscellaneous Requirements

None

B. State Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

Operations, Property, and/or Equipment	Applicable Rules/ Requirements	Applicable Emissions Limitations/Control Measures
Exterior paint booth #1	none	none

2. Additional Terms and Conditions

None

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

1. The permit to install for emissions units R001, R002, R005, R006, R008, R009 thru R016, P001 thru P006, and P901 was evaluated based on the actual materials (coatings and cleanup materials) and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant(s):

Pollutant: Butyl Acetate

TLV (ug/m3): 950,000

Maximum Hourly Emission Rate (lbs/hr): 57.8

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 5,770

MAGLC (ug/m3): 22,620

Pollutant: methyl ethyl ketone

TLV (ug/m3): 590,000

Maximum Hourly Emission Rate (lbs/hr): 70.1

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 7,000

MAGLC (ug/m3): 14,048

Pollutant: isopropyl alcohol

TLV (ug/m3): 983,000

Maximum Hourly Emission Rate (lbs/hr): 20.6

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 2,060

MAGLC (ug/m3): 23,400

Pollutant: xylene

TLV (ug/m3): 434,000

Maximum Hourly Emission Rate (lbs/hr): 4.3

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 430

MAGLC (ug/m3): 10,333

III. Monitoring and/or Record Keeping Requirements (continued)

2. Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be still satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

a. changes in the composition of the materials used (coatings or cleanup materials), or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value previously modeled;

b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and

c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01(VV)(1)(a)(ii), and a modification of the existing permit to install will not be required. If the change(s) is (are) defined as a modification under other provisions of the modification definition (other than (VV)(1)(a)(ii)), then the permittee shall obtain a final permit to install prior to the change.

3. The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy:"

a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);

b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and

c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Part III - Terms and Conditions for Emissions Units

Emissions Unit ID: Exterior 2 Paint Booth (R006)

Activity Description: This process puts a finish coat on polyurethane millwork

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

Operations, Property, and/or Equipment	Applicable Rules/ Requirements	Applicable Emissions Limitations/Control Measures
exterior paint booth #2	OAC rule 3745-31-05 (PTI 03-11125)	See A.I.2.a.
		17.5 lbs organic compounds (OC)/hr, 76.7 tons OC/yr (see A.I.2.b)
		0.65 lb particulate emissions (PE)/hr, 2.8 tons PE/yr (see A.I.2.b)
		3.6 tons PE/yr (see A.I.2.c)
		0% opacity, as a six-minute average
	OAC rule 3745-21-07(G)	none (See A.II.1.)

2. Additional Terms and Conditions

2.a The permittee shall emit no more than 80.0 tons of OC (from coatings), based upon a rolling, 12-month period from emissions units R005, R006 and R016, combined.

2.b The 17.5 lbs OC/hr, 76.7 tons OC/yr, 0.65 lb PE/hr and 2.8 tons PE/yr emission limitations were established for PTI purposes to reflect the potentials to emit for this emissions unit. Therefore, it is not necessary to develop record keeping and reporting requirements to ensure compliance with these limitations.

2.c The PE, from emissions units R005, R006 and R016, combined, shall not exceed 3.6 tons/yr.

2.d The OC emissions from the cleanup materials used in this emissions unit are permitted under emissions unit P901. Therefore, no record keeping and reporting requirements are necessary for the cleanup operations associated with this emissions unit.

2.e The uncontrolled mass rate of PE from this emissions unit is less than 10 lbs/hr. Therefore, pursuant to OAC rule 3745-17-11(A)(2)(a)(ii), Figure II of OAC rule 3745-17-11 does not apply. Also, Table I does not apply because the facility is located in Fulton County.

2.f This emissions unit is exempt from the visible emissions limitations specified in OAC rule 3745-17-07(A), pursuant to OAC rule 3745-17-07(A)(3)(h), because OAC rule 3745-17-11 is not applicable.

II. Operational Restrictions

1. The permittee shall not employ any material in this emissions unit that is a photochemically reactive material. "Photochemically reactive material" is defined in OAC rule 3745-21-01(C)(5).

II. Operational Restrictions (continued)

2. The permittee shall operate the dry filtration system whenever this emissions unit is in operation.

III. Monitoring and/or Record Keeping Requirements

1. The permittee shall collect and record the following information each month for emissions units R005, R006 and R016, combined:

1.a the company identification for each coating employed;

1.b the OC content of each coating employed, in pounds per gallon, as applied;

1.c the solids content of each coating employed, in pounds per gallon;

1.d the number of gallons of each coating employed;

1.e the total OC emission rate for all the coatings employed [summation of (b x d) for all coatings], in tons;

1.f the total coating solids usage rate for all the coatings employed [summation of (c x d) for all coatings], in tons; and

1.g the rolling, 12-month summation of the monthly OC emission rates (input rates), in tons.

2. The permittee shall record and maintain the following information each day for the coatings employed in this emissions unit:

2.a the company identification for each material employed; and

2.b documentation on whether or not each material employed is a photochemically reactive material.

3. The permittee shall maintain daily records that document any time periods when the dry filtration system was not in service when the emissions unit was in operation.

IV. Reporting Requirements

1. The permittee shall submit quarterly deviation (excursion) reports that identify all exceedances of the rolling, 12-month OC emission limitation of 80 tons. All quarterly deviation reports shall be submitted in accordance with paragraph A.1.c of the General Terms and Conditions of this permit.

2. The permittee shall notify the Director (appropriate Ohio EPA District Office or local air agency) in writing of any daily record showing the use of any noncomplying material (i.e., photochemically reactive material) in this emissions unit. The notification shall include a copy of such record and shall be sent to the Director (appropriate Ohio EPA District Office or local air agency) within 30 days after the exceedance occurs.

3. The permittee shall submit annual reports that specify the total actual OC emissions from emissions units R005, R006 and R016, combined. These reports shall be submitted by January 31 of each year and shall cover the previous calendar year.

4. The permittee shall notify the Director (the appropriate Ohio EPA District Office or local air agency) in writing of any daily record showing that the dry filtration system was not in service when the emissions unit was in operation. The notification shall include a copy of such record and shall be sent to the Director (the appropriate Ohio EPA District Office or local air agency) within 30 days after the event occurs.

V. Testing Requirements

1. Compliance with the emission limitations/usage restrictions of this permit shall be determined in accordance with the following methods:

1.a Emission Limitations: 80.0 tons OC per rolling, 12-month period

Applicable Compliance Method: Compliance shall be based upon the record keeping requirements specified in section A.III.1 of the terms and conditions of this permit.

V. Testing Requirements (continued)

1.b Emission Limitations: 17.5 lbs OC/hr, 76.7 tons OC/yr

Applicable Compliance Method: Compliance with the hourly limitation shall be determined by multiplying the maximum coating usage rate (gallons/hr) by the maximum OC content of all the coatings (pounds/gallon), as applied.

If required, compliance with the hourly limitation shall be demonstrated pursuant to Method 25 of 40 CFR, Part 60, Appendix A.

Compliance with the annual limitation shall be assumed as long as compliance with hourly limitation is maintained (the annual limitation was calculated by multiplying the hourly limitation by 8760, and then dividing by 2000).

1.c Emission Limitations: 0.65 lb PE/hr, 2.8 tons PE/yr

Applicable Compliance Method:

To determine the actual worst case particulate emissions rate (E), the following equation shall be used for the paint spraying operations:

E = particulate emissions rate (lbs/hr)

E = (maximum coating solids usage rate, in pounds per hour) X (1-TE) X (1-CE)

where:

TE = transfer efficiency, which is the ratio of the amount of coating solids deposited on the coated part to the amount of coating solids used

CE = control efficiency of the control equipment

If required, the permittee shall demonstrate compliance with the emission limit above pursuant to OAC rule 3745-17-03(B)(10).

The tons/yr limitation was developed by multiplying the 0.65 lb/hr limitation by 8760, and then dividing by 2000. Therefore, provided compliance is shown with the hourly limitation, compliance shall also be shown with the annual limitation.

1.d Emission Limitation: 3.6 tons PE/yr (for emissions units R005, R006 and R016, combined)

Applicable Compliance Method:

The permittee shall determine compliance based upon the following equation:

E = particulate emissions rate (tons/yr)

E = [coating solids usage rate (this is calculated by summing the 12 monthly coating solids usage rates, from section 1.f, for the calendar year), in tons per year] X (1-TE) X (1-CE)

where:

TE = transfer efficiency, which is the ratio of the amount of coating solids deposited on the coated part to the amount of coating solids used)

CE = control efficiency of the control equipment

1.e Emission Limitation: 0% opacity, as a six-minute average

Applicable Compliance Method: If required, compliance with the visible emissions limitation shall be determined in accordance with Method 9 of 40 CFR, Part 60, Appendix A.

V. Testing Requirements (continued)

2. The permittee shall determine the OC contents of the coatings based upon the formulation data supplied by the manufacturer of the coatings, or from data determined by analysis of each coating, as received, in accordance with 40 CFR, Part 60, Appendix A, Method 24.

VI. Miscellaneous Requirements

None

B. State Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

Operations, Property, and/or Equipment	Applicable Rules/ Requirements	Applicable Emissions Limitations/Control Measures
exterior paint booth #2	none	none

2. Additional Terms and Conditions

None

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

1. The permit to install for emissions units R001, R002, R005, R006, R008, R009 thru R016, P001 thru P006, and P901 was evaluated based on the actual materials (coatings and cleanup materials) and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant(s):

Pollutant: Butyl Acetate

TLV (ug/m3): 950,000

Maximum Hourly Emission Rate (lbs/hr): 57.8

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 5,770

MAGLC (ug/m3): 22,620

Pollutant: methyl ethyl ketone

TLV (ug/m3): 590,000

Maximum Hourly Emission Rate (lbs/hr): 70.1

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 7,000

MAGLC (ug/m3): 14,048

Pollutant: isopropyl alcohol

TLV (ug/m3): 983,000

Maximum Hourly Emission Rate (lbs/hr): 20.6

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 2,060

MAGLC (ug/m3): 23,400

Pollutant: xylene

TLV (ug/m3): 434,000

Maximum Hourly Emission Rate (lbs/hr): 4.3

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 430

MAGLC (ug/m3): 10,333

III. Monitoring and/or Record Keeping Requirements (continued)

2. Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be still satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

a. changes in the composition of the materials used (coatings or cleanup materials), or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value previously modeled;

b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and

c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01(VV)(1)(a)(ii), and a modification of the existing permit to install will not be required. If the change(s) is (are) defined as a modification under other provisions of the modification definition (other than (VV)(1)(a)(ii)), then the permittee shall obtain a final permit to install prior to the change.

3. The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy:"

a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);

b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and

c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Part III - Terms and Conditions for Emissions Units

Emissions Unit ID: Mold Coat #1 Booth (R008)

Activity Description: This process coats silicone molds with mold release paint

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

Operations, Property, and/or Equipment	Applicable Rules/ Requirements	Applicable Emissions Limitations/Control Measures
mold coating booth # 1	OAC rule 3745-31-05 (PTI 03-11125)	See A.I.2.a.
		15.0 lbs organic compounds (OC)/hr, 65.7 tons OC/yr (see A.I.2.b)
		0.29 lb particulate emissions (PE)/hr, 1.3 tons PE/yr (see A.I.2.b)
		1.5 tons PE/yr (see A.I.2.c)
		0% opacity, as a six-minute average
	OAC rule 3745-21-07(G)	none (See A.II.1.)

2. Additional Terms and Conditions

2.a The permittee shall emit no more than 75.0 tons of OC (from coatings), based upon a rolling, 12-month period from emissions units R008, R009, R010, R011, R012, R013 and R014, combined.

2.b The 15.0 lbs OC/hr, 65.7 tons OC/yr, 0.29 lb PE/hr and 1.3 tons PE/yr emission limitations were established for PTI purposes to reflect the potentials to emit for this emissions unit. Therefore, it is not necessary to develop record keeping and reporting requirements to ensure compliance with these limitations.

2.c The PE, from emissions units R008, R009, R010, R011, R012, R013 and R014, combined, shall not exceed 1.5 tons/yr.

2.d The OC emissions from the cleanup materials used in this emissions unit are permitted under emissions unit P901. Therefore, no record keeping and reporting requirements are necessary for the cleanup operations associated with this emissions unit.

2.e The uncontrolled mass rate of PE from this emissions unit is less than 10 lbs/hr. Therefore, pursuant to OAC rule 3745-17-11(A)(2)(a)(ii), Figure II of OAC rule 3745-17-11 does not apply. Also, Table I does not apply because the facility is located in Fulton County.

2.f This emissions unit is exempt from the visible emissions limitations specified in OAC rule 3745-17-07(A), pursuant to OAC rule 3745-17-07(A)(3)(h), because OAC rule 3745-17-11 is not applicable.

II. Operational Restrictions

1. The permittee shall not employ any material in this emissions unit that is a photochemically reactive material. "Photochemically reactive material" is defined in OAC rule 3745-21-01(C)(5).

2. The permittee shall operate the dry filtration system whenever this emissions unit is in operation.

III. Monitoring and/or Record Keeping Requirements

1. The permittee shall collect and record the following information each month for emissions units R008, R009, R010, R011, R012, R013 and R014, combined:

1.a the company identification for each coating employed;

1.b the OC content of each coating employed, in pounds per gallon, as applied;

1.c the solids content of each coating employed, in pounds per gallon;

1.d the number of gallons of each coating employed;

1.e the total OC emission rate for all the coatings employed [summation of (b x d) for all coatings], in tons;

1.f the total coating solids usage rate for all the coatings employed [summation of (c x d) for all coatings], in tons; and

1.g the rolling, 12-month summation of the monthly OC emission rates (input rates), in tons.

2. The permittee shall record and maintain the following information each day for the coatings employed in this emissions unit:

2.a the company identification for each material employed; and

2.b documentation on whether or not each material employed is a photochemically reactive material.

3. The permittee shall maintain daily records that document any time periods when the dry filtration system was not in service when the emissions unit was in operation.

IV. Reporting Requirements

1. The permittee shall submit quarterly deviation (excursion) reports that identify all exceedances of the rolling, 12-month OC emission limitation of 75 tons. All quarterly deviation reports shall be submitted in accordance with paragraph A.1.c of the General Terms and Conditions of this permit.

2. The permittee shall notify the Director (appropriate Ohio EPA District Office or local air agency) in writing of any daily record showing the use of any noncomplying material (i.e., photochemically reactive material) in this emissions unit. The notification shall include a copy of such record and shall be sent to the Director (appropriate Ohio EPA District Office or local air agency) within 30 days after the exceedance occurs.

3. The permittee shall submit annual reports that specify the total actual OC emissions from emissions units R008, R009, R010, R011, R012, R013 and R014, combined. These reports shall be submitted by January 31 of each year and shall cover the previous calendar year.

4. The permittee shall notify the Director (the appropriate Ohio EPA District Office or local air agency) in writing of any daily record showing that the dry filtration system was not in service when the emissions unit was in operation. The notification shall include a copy of such record and shall be sent to the Director (the appropriate Ohio EPA District Office or local air agency) within 30 days after the event occurs.

V. Testing Requirements

1. Compliance with the emission limitations/usage restrictions of this permit shall be determined in accordance with the following methods:

V. Testing Requirements (continued)

1.a Emission Limitation: 75.0 tons OC per rolling, 12-month period

Applicable Compliance Method: Compliance shall be based upon the record keeping requirements specified in section A.III.1 of the terms and conditions of this permit.

1.b Emission Limitations: 15.0 lbs OC/hr, 65.7 tons OC/yr

Applicable Compliance Method: Compliance with the hourly limitation shall be determined by multiplying the maximum coating usage rate (gallons/hr) by the maximum OC content of all the coatings (pounds/gallon), as applied.

If required, compliance with the hourly limitation shall be demonstrated pursuant to Method 25 of 40 CFR, Part 60, Appendix A.

Compliance with the annual limitation shall be assumed as long as compliance with hourly limitation is maintained (the annual limitation was calculated by multiplying the hourly limitation by 8760, and then dividing by 2000).

1.c Emission Limitations: 0.29 lb PE/hr, 1.3 tons PE/yr

Applicable Compliance Method:

To determine the actual worst case particulate emissions rate (E), the following equation shall be used for the paint spraying operations:

E = particulate emissions rate (lbs/hr)

E = (maximum coating solids usage rate, in pounds per hour) X (1-TE) X (1-CE)

where:

TE = transfer efficiency, which is the ratio of the amount of coating solids deposited on the coated part to the amount of coating solids used

CE = control efficiency of the control equipment

If required, the permittee shall demonstrate compliance with the emission limit above pursuant to OAC rule 3745-17-03(B)(10).

The tons/yr limitation was developed by multiplying the 0.65 lb/hr limitation by 8760, and then dividing by 2000. Therefore, provided compliance is shown with the hourly limitation, compliance shall also be shown with the annual limitation.

V. Testing Requirements (continued)

1.d Emission Limitation: 1.5 tons PE/yr (for emissions units R008, R009, R010, R011, R012, R013 and R014, combined)

Applicable Compliance Method:

The permittee shall determine compliance based upon the following equation:

E = particulate emissions rate (tons/yr)

E = [coating solids usage rate (this is calculated by summing the 12 monthly coating solids usage rates, from section 1.f, for the calendar year), in tons per year] X (1-TE) X (1-CE)

where:

TE = transfer efficiency, which is the ratio of the amount of coating solids deposited on the coated part to the amount of coating solids used)

CE = control efficiency of the control equipment

1.e Emission Limitation: 0% opacity, as a six-minute average

Applicable Compliance Method: If required, compliance with the visible emissions limitation shall be determined in accordance with Method 9 of 40 CFR, Part 60, Appendix A.

2. The permittee shall determine the OC contents of the coatings based upon the formulation data supplied by the manufacturer of the coatings, or from data determined by analysis of each coating, as received, in accordance with 40 CFR, Part 60, Appendix A, Method 24.

VI. Miscellaneous Requirements

None

B. State Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

Operations, Property, and/or Equipment	Applicable Rules/ Requirements	Applicable Emissions Limitations/Control Measures
mold coating booth # 1	none	none

2. Additional Terms and Conditions

None

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

1. The permit to install for emissions units R001, R002, R005, R006, R008, R009 thru R016, P001 thru P006, and P901 was evaluated based on the actual materials (coatings and cleanup materials) and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant(s):

Pollutant: Butyl Acetate

TLV (ug/m3): 950,000

Maximum Hourly Emission Rate (lbs/hr): 57.8

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 5,770

MAGLC (ug/m3): 22,620

Pollutant: methyl ethyl ketone

TLV (ug/m3): 590,000

Maximum Hourly Emission Rate (lbs/hr): 70.1

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 7,000

MAGLC (ug/m3): 14,048

Pollutant: isopropyl alcohol

TLV (ug/m3): 983,000

Maximum Hourly Emission Rate (lbs/hr): 20.6

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 2,060

MAGLC (ug/m3): 23,400

Pollutant: xylene

TLV (ug/m3): 434,000

Maximum Hourly Emission Rate (lbs/hr): 4.3

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 430

MAGLC (ug/m3): 10,333

III. Monitoring and/or Record Keeping Requirements (continued)

2. Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be still satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

a. changes in the composition of the materials used (coatings or cleanup materials), or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value previously modeled;

b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and

c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01(VV)(1)(a)(ii), and a modification of the existing permit to install will not be required. If the change(s) is (are) defined as a modification under other provisions of the modification definition (other than (VV)(1)(a)(ii)), then the permittee shall obtain a final permit to install prior to the change.

3. The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy:"

a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);

b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and

c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Part III - Terms and Conditions for Emissions Units

Emissions Unit ID: Mold Coat #2 Booth (R009)

Activity Description: This process coats silicone molds with mold release paint

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

Operations, Property, and/or Equipment	Applicable Rules/ Requirements	Applicable Emissions Limitations/Control Measures
mold coating booth # 2	OAC rule 3745-31-05 (PTI 03-11125)	See A.I.2.a.
		15.0 lbs organic compounds (OC)/hr, 65.7 tons OC/yr (see A.I.2.b)
		0.29 lb particulate emissions (PE)/hr, 1.3 tons PE/yr (see A.I.2.b)
		1.5 tons PE/yr (see A.I.2.c)
		0% opacity, as a six-minute average
	OAC rule 3745-21-07(G)	none (See A.II.1.)

2. Additional Terms and Conditions

2.a The permittee shall emit no more than 75.0 tons of OC (from coatings), based upon a rolling, 12-month period from emissions units R008, R009, R010, R011, R012, R013 and R014, combined.

2.b The 15.0 lbs OC/hr, 65.7 tons OC/yr, 0.29 lb PE/hr and 1.3 tons PE/yr emission limitations were established for PTI purposes to reflect the potentials to emit for this emissions unit. Therefore, it is not necessary to develop record keeping and reporting requirements to ensure compliance with these limitations.

2.c The PE, from emissions units R008, R009, R010, R011, R012, R013 and R014, combined, shall not exceed 1.5 tons/yr.

2.d The OC emissions from the cleanup materials used in this emissions unit are permitted under emissions unit P901. Therefore, no record keeping and reporting requirements are necessary for the cleanup operations associated with this emissions unit.

2.e The uncontrolled mass rate of PE from this emissions unit is less than 10 lbs/hr. Therefore, pursuant to OAC rule 3745-17-11(A)(2)(a)(ii), Figure II of OAC rule 3745-17-11 does not apply. Also, Table I does not apply because the facility is located in Fulton County.

2.f This emissions unit is exempt from the visible emissions limitations specified in OAC rule 3745-17-07(A), pursuant to OAC rule 3745-17-07(A)(3)(h), because OAC rule 3745-17-11 is not applicable.

II. Operational Restrictions

1. The permittee shall not employ any material in this emissions unit that is a photochemically reactive material. "Photochemically reactive material" is defined in OAC rule 3745-21-01(C)(5).

2. The permittee shall operate the dry filtration system whenever this emissions unit is in operation.

III. Monitoring and/or Record Keeping Requirements

1. The permittee shall collect and record the following information each month for emissions units R008, R009, R010, R011, R012, R013 and R014, combined:

1.a the company identification for each coating employed;

1.b the OC content of each coating employed, in pounds per gallon, as applied;

1.c the solids content of each coating employed, in pounds per gallon;

1.d the number of gallons of each coating employed;

1.e the total OC emission rate for all the coatings employed [summation of (b x d) for all coatings], in tons;

1.f the total coating solids usage rate for all the coatings employed [summation of (c x d) for all coatings], in tons; and

1.g the rolling, 12-month summation of the monthly OC emission rates (input rates), in tons.

2. The permittee shall record and maintain the following information each day for the coatings employed in this emissions unit:

2.a the company identification for each material employed; and

2.b documentation on whether or not each material employed is a photochemically reactive material.

3. The permittee shall maintain daily records that document any time periods when the dry filtration system was not in service when the emissions unit was in operation.

IV. Reporting Requirements

1. The permittee shall submit quarterly deviation (excursion) reports that identify all exceedances of the rolling, 12-month OC emission limitation of 75 tons. All quarterly deviation reports shall be submitted in accordance with paragraph A.1.c of the General Terms and Conditions of this permit.

2. The permittee shall notify the Director (appropriate Ohio EPA District Office or local air agency) in writing of any daily record showing the use of any noncomplying material (i.e., photochemically reactive material) in this emissions unit. The notification shall include a copy of such record and shall be sent to the Director (appropriate Ohio EPA District Office or local air agency) within 30 days after the exceedance occurs.

3. The permittee shall submit annual reports that specify the total actual OC emissions from emissions units R008, R009, R010, R011, R012, R013 and R014, combined. These reports shall be submitted by January 31 of each year and shall cover the previous calendar year.

4. The permittee shall notify the Director (the appropriate Ohio EPA District Office or local air agency) in writing of any daily record showing that the dry filtration system was not in service when the emissions unit was in operation. The notification shall include a copy of such record and shall be sent to the Director (the appropriate Ohio EPA District Office or local air agency) within 30 days after the event occurs.

V. Testing Requirements

1. Compliance with the emission limitations/usage restrictions of this permit shall be determined in accordance with the following methods:

V. Testing Requirements (continued)

1.a Emission Limitation: 75.0 tons OC per rolling, 12-month period

Applicable Compliance Method: Compliance shall be based upon the record keeping requirements specified in section A.III.1 of the terms and conditions of this permit.

1.b Emission Limitations: 15.0 lbs OC/hr, 65.7 tons OC/yr

Applicable Compliance Method: Compliance with the hourly limitation shall be determined by multiplying the maximum coating usage rate (gallons/hr) by the maximum OC content of all the coatings (pounds/gallon), as applied.

If required, compliance with the hourly limitation shall be demonstrated pursuant to Method 25 of 40 CFR, Part 60, Appendix A.

Compliance with the annual limitation shall be assumed as long as compliance with hourly limitation is maintained (the annual limitation was calculated by multiplying the hourly limitation by 8760, and then dividing by 2000).

1.c Emission Limitations: 0.29 lb PE/hr, 1.3 tons PE/yr

Applicable Compliance Method:

To determine the actual worst case particulate emissions rate (E), the following equation shall be used for the paint spraying operations:

E = particulate emissions rate (lbs/hr)

E = (maximum coating solids usage rate, in pounds per hour) X (1-TE) X (1-CE)

where:

TE = transfer efficiency, which is the ratio of the amount of coating solids deposited on the coated part to the amount of coating solids used

CE = control efficiency of the control equipment

If required, the permittee shall demonstrate compliance with the emission limit above pursuant to OAC rule 3745-17-03(B)(10).

The tons/yr limitation was developed by multiplying the 0.65 lb/hr limitation by 8760, and then dividing by 2000. Therefore, provided compliance is shown with the hourly limitation, compliance shall also be shown with the annual limitation.

V. Testing Requirements (continued)

1.d Emission Limitation: 1.5 tons PE/yr (for emissions units R008, R009, R010, R011, R012, R013 and R014, combined)

Applicable Compliance Method:

The permittee shall determine compliance based upon the following equation:

E = particulate emissions rate (tons/yr)

E = [coating solids usage rate (this is calculated by summing the 12 monthly coating solids usage rates, from section 1.f, for the calendar year), in tons per year] X (1-TE) X (1-CE)

where:

TE = transfer efficiency, which is the ratio of the amount of coating solids deposited on the coated part to the amount of coating solids used)

CE = control efficiency of the control equipment

1.e Emission Limitation: 0% opacity, as a six-minute average

Applicable Compliance Method: If required, compliance with the visible emissions limitation shall be determined in accordance with Method 9 of 40 CFR, Part 60, Appendix A.

2. The permittee shall determine the OC contents of the coatings based upon the formulation data supplied by the manufacturer of the coatings, or from data determined by analysis of each coating, as received, in accordance with 40 CFR, Part 60, Appendix A, Method 24.

VI. Miscellaneous Requirements

None

B. State Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

Operations, Property, and/or Equipment	Applicable Rules/ Requirements	Applicable Emissions Limitations/Control Measures
mold coating booth # 2	none	none

2. Additional Terms and Conditions

None

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

1. The permit to install for emissions units R001, R002, R005, R006, R008, R009 thru R016, P001 thru P006, and P901 was evaluated based on the actual materials (coatings and cleanup materials) and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant(s):

Pollutant: Butyl Acetate

TLV (ug/m3): 950,000

Maximum Hourly Emission Rate (lbs/hr): 57.8

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 5,770

MAGLC (ug/m3): 22,620

Pollutant: methyl ethyl ketone

TLV (ug/m3): 590,000

Maximum Hourly Emission Rate (lbs/hr): 70.1

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 7,000

MAGLC (ug/m3): 14,048

Pollutant: isopropyl alcohol

TLV (ug/m3): 983,000

Maximum Hourly Emission Rate (lbs/hr): 20.6

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 2,060

MAGLC (ug/m3): 23,400

Pollutant: xylene

TLV (ug/m3): 434,000

Maximum Hourly Emission Rate (lbs/hr): 4.3

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 430

MAGLC (ug/m3): 10,333

III. Monitoring and/or Record Keeping Requirements (continued)

2. Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be still satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

a. changes in the composition of the materials used (coatings or cleanup materials), or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value previously modeled;

b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and

c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01(VV)(1)(a)(ii), and a modification of the existing permit to install will not be required. If the change(s) is (are) defined as a modification under other provisions of the modification definition (other than (VV)(1)(a)(ii)), then the permittee shall obtain a final permit to install prior to the change.

3. The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy:"

a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);

b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and

c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Part III - Terms and Conditions for Emissions Units

Emissions Unit ID: Mold Coat #3 Booth (R010)

Activity Description: This process coats silicone molds with mold release paint

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

Operations, Property, and/or Equipment	Applicable Rules/ Requirements	Applicable Emissions Limitations/Control Measures
mold coating booth # 3	OAC rule 3745-31-05 (PTI 03-11125)	See A.I.2.a.
		15.0 lbs organic compounds (OC)/hr, 65.7 tons OC/yr (see A.I.2.b)
		0.29 lb particulate emissions (PE)/hr, 1.3 tons PE/yr (see A.I.2.b)
		1.5 tons PE/yr (see A.I.2.c)
		0% opacity, as a six-minute average
	OAC rule 3745-21-07(G)	none (See A.II.1.)

2. Additional Terms and Conditions

2.a The permittee shall emit no more than 75.0 tons of OC (from coatings), based upon a rolling, 12-month period from emissions units R008, R009, R010, R011, R012, R013 and R014, combined.

2.b The 15.0 lbs OC/hr, 65.7 tons OC/yr, 0.29 lb PE/hr and 1.3 tons PE/yr emission limitations were established for PTI purposes to reflect the potentials to emit for this emissions unit. Therefore, it is not necessary to develop record keeping and reporting requirements to ensure compliance with these limitations.

2.c The PE, from emissions units R008, R009, R010, R011, R012, R013 and R014, combined, shall not exceed 1.5 tons/yr.

2.d The OC emissions from the cleanup materials used in this emissions unit are permitted under emissions unit P901. Therefore, no record keeping and reporting requirements are necessary for the cleanup operations associated with this emissions unit.

2.e The uncontrolled mass rate of PE from this emissions unit is less than 10 lbs/hr. Therefore, pursuant to OAC rule 3745-17-11(A)(2)(a)(ii), Figure II of OAC rule 3745-17-11 does not apply. Also, Table I does not apply because the facility is located in Fulton County.

2.f This emissions unit is exempt from the visible emissions limitations specified in OAC rule 3745-17-07(A), pursuant to OAC rule 3745-17-07(A)(3)(h), because OAC rule 3745-17-11 is not applicable.

II. Operational Restrictions

1. The permittee shall not employ any material in this emissions unit that is a photochemically reactive material. "Photochemically reactive material" is defined in OAC rule 3745-21-01(C)(5).

2. The permittee shall operate the dry filtration system whenever this emissions unit is in operation.

III. Monitoring and/or Record Keeping Requirements

1. The permittee shall collect and record the following information each month for emissions units R008, R009, R010, R011, R012, R013 and R014, combined:

1.a the company identification for each coating employed;

1.b the OC content of each coating employed, in pounds per gallon, as applied;

1.c the solids content of each coating employed, in pounds per gallon;

1.d the number of gallons of each coating employed;

1.e the total OC emission rate for all the coatings employed [summation of (b x d) for all coatings], in tons;

1.f the total coating solids usage rate for all the coatings employed [summation of (c x d) for all coatings], in tons; and

1.g the rolling, 12-month summation of the monthly OC emission rates (input rates), in tons.

2. The permittee shall record and maintain the following information each day for the coatings employed in this emissions unit:

2.a the company identification for each material employed; and

2.b documentation on whether or not each material employed is a photochemically reactive material.

3. The permittee shall maintain daily records that document any time periods when the dry filtration system was not in service when the emissions unit was in operation.

IV. Reporting Requirements

1. The permittee shall submit quarterly deviation (excursion) reports that identify all exceedances of the rolling, 12-month OC emission limitation of 75 tons. All quarterly deviation reports shall be submitted in accordance with paragraph A.1.c of the General Terms and Conditions of this permit.

2. The permittee shall notify the Director (appropriate Ohio EPA District Office or local air agency) in writing of any daily record showing the use of any noncomplying material (i.e., photochemically reactive material) in this emissions unit. The notification shall include a copy of such record and shall be sent to the Director (appropriate Ohio EPA District Office or local air agency) within 30 days after the exceedance occurs.

3. The permittee shall submit annual reports that specify the total actual OC emissions from emissions units R008, R009, R010, R011, R012, R013 and R014, combined. These reports shall be submitted by January 31 of each year and shall cover the previous calendar year.

4. The permittee shall notify the Director (the appropriate Ohio EPA District Office or local air agency) in writing of any daily record showing that the dry filtration system was not in service when the emissions unit was in operation. The notification shall include a copy of such record and shall be sent to the Director (the appropriate Ohio EPA District Office or local air agency) within 30 days after the event occurs.

V. Testing Requirements

1. Compliance with the emission limitations/usage restrictions of this permit shall be determined in accordance with the following methods:

V. Testing Requirements (continued)

1.a Emission Limitation: 75.0 tons OC per rolling, 12-month period

Applicable Compliance Method: Compliance shall be based upon the record keeping requirements specified in section A.III.1 of the terms and conditions of this permit.

1.b Emission Limitations: 15.0 lbs OC/hr, 65.7 tons OC/yr

Applicable Compliance Method: Compliance with the hourly limitation shall be determined by multiplying the maximum coating usage rate (gallons/hr) by the maximum OC content of all the coatings (pounds/gallon), as applied.

If required, compliance with the hourly limitation shall be demonstrated pursuant to Method 25 of 40 CFR, Part 60, Appendix A.

Compliance with the annual limitation shall be assumed as long as compliance with hourly limitation is maintained (the annual limitation was calculated by multiplying the hourly limitation by 8760, and then dividing by 2000).

1.c Emission Limitations: 0.29 lb PE/hr, 1.3 tons PE/yr

Applicable Compliance Method:

To determine the actual worst case particulate emissions rate (E), the following equation shall be used for the paint spraying operations:

E = particulate emissions rate (lbs/hr)

E = (maximum coating solids usage rate, in pounds per hour) X (1-TE) X (1-CE)

where:

TE = transfer efficiency, which is the ratio of the amount of coating solids deposited on the coated part to the amount of coating solids used

CE = control efficiency of the control equipment

If required, the permittee shall demonstrate compliance with the emission limit above pursuant to OAC rule 3745-17-03(B)(10).

The tons/yr limitation was developed by multiplying the 0.65 lb/hr limitation by 8760, and then dividing by 2000. Therefore, provided compliance is shown with the hourly limitation, compliance shall also be shown with the annual limitation.

V. Testing Requirements (continued)

1.d Emission Limitation: 1.5 tons PE/yr (for emissions units R008, R009, R010, R011, R012, R013 and R014, combined)

Applicable Compliance Method:

The permittee shall determine compliance based upon the following equation:

E = particulate emissions rate (tons/yr)

E = [coating solids usage rate (this is calculated by summing the 12 monthly coating solids usage rates, from section 1.f, for the calendar year), in tons per year] X (1-TE) X (1-CE)

where:

TE = transfer efficiency, which is the ratio of the amount of coating solids deposited on the coated part to the amount of coating solids used)

CE = control efficiency of the control equipment

1.e Emission Limitation: 0% opacity, as a six-minute average

Applicable Compliance Method: If required, compliance with the visible emissions limitation shall be determined in accordance with Method 9 of 40 CFR, Part 60, Appendix A.

2. The permittee shall determine the OC contents of the coatings based upon the formulation data supplied by the manufacturer of the coatings, or from data determined by analysis of each coating, as received, in accordance with 40 CFR, Part 60, Appendix A, Method 24.

VI. Miscellaneous Requirements

None

B. State Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

Operations, Property, and/or Equipment	Applicable Rules/ Requirements	Applicable Emissions Limitations/Control Measures
mold coating booth # 3	none	none

2. Additional Terms and Conditions

None

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

1. The permit to install for emissions units R001, R002, R005, R006, R008, R009 thru R016, P001 thru P006, and P901 was evaluated based on the actual materials (coatings and cleanup materials) and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant(s):

Pollutant: Butyl Acetate

TLV (ug/m3): 950,000

Maximum Hourly Emission Rate (lbs/hr): 57.8

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 5,770

MAGLC (ug/m3): 22,620

Pollutant: methyl ethyl ketone

TLV (ug/m3): 590,000

Maximum Hourly Emission Rate (lbs/hr): 70.1

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 7,000

MAGLC (ug/m3): 14,048

Pollutant: isopropyl alcohol

TLV (ug/m3): 983,000

Maximum Hourly Emission Rate (lbs/hr): 20.6

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 2,060

MAGLC (ug/m3): 23,400

Pollutant: xylene

TLV (ug/m3): 434,000

Maximum Hourly Emission Rate (lbs/hr): 4.3

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 430

MAGLC (ug/m3): 10,333

III. Monitoring and/or Record Keeping Requirements (continued)

2. Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be still satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

a. changes in the composition of the materials used (coatings or cleanup materials), or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value previously modeled;

b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and

c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01(VV)(1)(a)(ii), and a modification of the existing permit to install will not be required. If the change(s) is (are) defined as a modification under other provisions of the modification definition (other than (VV)(1)(a)(ii)), then the permittee shall obtain a final permit to install prior to the change.

3. The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy:"

a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);

b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and

c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Part III - Terms and Conditions for Emissions Units

Emissions Unit ID: Mold Coat #4 Booth (R011)

Activity Description: This process coats silicone molds with mold release paint

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

Operations, Property, and/or Equipment	Applicable Rules/ Requirements	Applicable Emissions Limitations/Control Measures
mold coating booth # 4	OAC rule 3745-31-05 (PTI 03-11125)	See A.I.2.a.
		15.0 lbs organic compounds (OC)/hr, 65.7 tons OC/yr (see A.I.2.b)
		0.29 lb particulate emissions (PE)/hr, 1.3 tons PE/yr (see A.I.2.b)
		1.5 tons PE/yr (see A.I.2.c)
		0% opacity, as a six-minute average
	OAC rule 3745-21-07(G)	none (See A.II.1.)

2. Additional Terms and Conditions

2.a The permittee shall emit no more than 75.0 tons of OC (from coatings), based upon a rolling, 12-month period from emissions units R008, R009, R010, R011, R012, R013 and R014, combined.

2.b The 15.0 lbs OC/hr, 65.7 tons OC/yr, 0.29 lb PE/hr and 1.3 tons PE/yr emission limitations were established for PTI purposes to reflect the potentials to emit for this emissions unit. Therefore, it is not necessary to develop record keeping and reporting requirements to ensure compliance with these limitations.

2.c The PE, from emissions units R008, R009, R010, R011, R012, R013 and R014, combined, shall not exceed 1.5 tons/yr.

2.d The OC emissions from the cleanup materials used in this emissions unit are permitted under emissions unit P901. Therefore, no record keeping and reporting requirements are necessary for the cleanup operations associated with this emissions unit.

2.e The uncontrolled mass rate of PE from this emissions unit is less than 10 lbs/hr. Therefore, pursuant to OAC rule 3745-17-11(A)(2)(a)(ii), Figure II of OAC rule 3745-17-11 does not apply. Also, Table I does not apply because the facility is located in Fulton County.

2.f This emissions unit is exempt from the visible emissions limitations specified in OAC rule 3745-17-07(A), pursuant to OAC rule 3745-17-07(A)(3)(h), because OAC rule 3745-17-11 is not applicable.

II. Operational Restrictions

1. The permittee shall not employ any material in this emissions unit that is a photochemically reactive material. "Photochemically reactive material" is defined in OAC rule 3745-21-01(C)(5).

2. The permittee shall operate the dry filtration system whenever this emissions unit is in operation.

III. Monitoring and/or Record Keeping Requirements

1. The permittee shall collect and record the following information each month for emissions units R008, R009, R010, R011, R012, R013 and R014, combined:

1.a the company identification for each coating employed;

1.b the OC content of each coating employed, in pounds per gallon, as applied;

1.c the solids content of each coating employed, in pounds per gallon;

1.d the number of gallons of each coating employed;

1.e the total OC emission rate for all the coatings employed [summation of (b x d) for all coatings], in tons;

1.f the total coating solids usage rate for all the coatings employed [summation of (c x d) for all coatings], in tons; and

1.g the rolling, 12-month summation of the monthly OC emission rates (input rates), in tons.

2. The permittee shall record and maintain the following information each day for the coatings employed in this emissions unit:

2.a the company identification for each material employed; and

2.b documentation on whether or not each material employed is a photochemically reactive material.

3. The permittee shall maintain daily records that document any time periods when the dry filtration system was not in service when the emissions unit was in operation.

IV. Reporting Requirements

1. The permittee shall submit quarterly deviation (excursion) reports that identify all exceedances of the rolling, 12-month OC emission limitation of 75 tons. All quarterly deviation reports shall be submitted in accordance with paragraph A.1.c of the General Terms and Conditions of this permit.

2. The permittee shall notify the Director (appropriate Ohio EPA District Office or local air agency) in writing of any daily record showing the use of any noncomplying material (i.e., photochemically reactive material) in this emissions unit. The notification shall include a copy of such record and shall be sent to the Director (appropriate Ohio EPA District Office or local air agency) within 30 days after the exceedance occurs.

3. The permittee shall submit annual reports that specify the total actual OC emissions from emissions units R008, R009, R010, R011, R012, R013 and R014, combined. These reports shall be submitted by January 31 of each year and shall cover the previous calendar year.

4. The permittee shall notify the Director (the appropriate Ohio EPA District Office or local air agency) in writing of any daily record showing that the dry filtration system was not in service when the emissions unit was in operation. The notification shall include a copy of such record and shall be sent to the Director (the appropriate Ohio EPA District Office or local air agency) within 30 days after the event occurs.

V. Testing Requirements

1. Compliance with the emission limitations/usage restrictions of this permit shall be determined in accordance with the following methods:

V. Testing Requirements (continued)

1.a Emission Limitation: 75.0 tons OC per rolling, 12-month period

Applicable Compliance Method: Compliance shall be based upon the record keeping requirements specified in section A.III.1 of the terms and conditions of this permit.

1.b Emission Limitations: 15.0 lbs OC/hr, 65.7 tons OC/yr

Applicable Compliance Method: Compliance with the hourly limitation shall be determined by multiplying the maximum coating usage rate (gallons/hr) by the maximum OC content of all the coatings (pounds/gallon), as applied.

If required, compliance with the hourly limitation shall be demonstrated pursuant to Method 25 of 40 CFR, Part 60, Appendix A.

Compliance with the annual limitation shall be assumed as long as compliance with hourly limitation is maintained (the annual limitation was calculated by multiplying the hourly limitation by 8760, and then dividing by 2000).

1.c Emission Limitations: 0.29 lb PE/hr, 1.3 tons PE/yr

Applicable Compliance Method:

To determine the actual worst case particulate emissions rate (E), the following equation shall be used for the paint spraying operations:

E = particulate emissions rate (lbs/hr)

E = (maximum coating solids usage rate, in pounds per hour) X (1-TE) X (1-CE)

where:

TE = transfer efficiency, which is the ratio of the amount of coating solids deposited on the coated part to the amount of coating solids used

CE = control efficiency of the control equipment

If required, the permittee shall demonstrate compliance with the emission limit above pursuant to OAC rule 3745-17-03(B)(10).

The tons/yr limitation was developed by multiplying the 0.65 lb/hr limitation by 8760, and then dividing by 2000. Therefore, provided compliance is shown with the hourly limitation, compliance shall also be shown with the annual limitation.

V. Testing Requirements (continued)

1.d Emission Limitation: 1.5 tons PE/yr (for emissions units R008, R009, R010, R011, R012, R013 and R014, combined)

Applicable Compliance Method:

The permittee shall determine compliance based upon the following equation:

E = particulate emissions rate (tons/yr)

E = [coating solids usage rate (this is calculated by summing the 12 monthly coating solids usage rates, from section 1.f, for the calendar year), in tons per year] X (1-TE) X (1-CE)

where:

TE = transfer efficiency, which is the ratio of the amount of coating solids deposited on the coated part to the amount of coating solids used)

CE = control efficiency of the control equipment

1.e Emission Limitation: 0% opacity, as a six-minute average

Applicable Compliance Method: If required, compliance with the visible emissions limitation shall be determined in accordance with Method 9 of 40 CFR, Part 60, Appendix A.

2. The permittee shall determine the OC contents of the coatings based upon the formulation data supplied by the manufacturer of the coatings, or from data determined by analysis of each coating, as received, in accordance with 40 CFR, Part 60, Appendix A, Method 24.

VI. Miscellaneous Requirements

None

B. State Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

Operations, Property, and/or Equipment	Applicable Rules/ Requirements	Applicable Emissions Limitations/Control Measures
mold coating booth # 4	none	none

2. Additional Terms and Conditions

None

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

1. The permit to install for emissions units R001, R002, R005, R006, R008, R009 thru R016, P001 thru P006, and P901 was evaluated based on the actual materials (coatings and cleanup materials) and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant(s):

Pollutant: Butyl Acetate

TLV (ug/m3): 950,000

Maximum Hourly Emission Rate (lbs/hr): 57.8

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 5,770

MAGLC (ug/m3): 22,620

Pollutant: methyl ethyl ketone

TLV (ug/m3): 590,000

Maximum Hourly Emission Rate (lbs/hr): 70.1

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 7,000

MAGLC (ug/m3): 14,048

Pollutant: isopropyl alcohol

TLV (ug/m3): 983,000

Maximum Hourly Emission Rate (lbs/hr): 20.6

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 2,060

MAGLC (ug/m3): 23,400

Pollutant: xylene

TLV (ug/m3): 434,000

Maximum Hourly Emission Rate (lbs/hr): 4.3

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 430

MAGLC (ug/m3): 10,333

III. Monitoring and/or Record Keeping Requirements (continued)

2. Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be still satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

a. changes in the composition of the materials used (coatings or cleanup materials), or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value previously modeled;

b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and

c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01(VV)(1)(a)(ii), and a modification of the existing permit to install will not be required. If the change(s) is (are) defined as a modification under other provisions of the modification definition (other than (VV)(1)(a)(ii)), then the permittee shall obtain a final permit to install prior to the change.

3. The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy:"

a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);

b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and

c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Part III - Terms and Conditions for Emissions Units

Emissions Unit ID: Mold Coat #5 Booth (R012)

Activity Description: This process coats silicone molds with mold release paint

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

Operations, Property, and/or Equipment	Applicable Rules/ Requirements	Applicable Emissions Limitations/Control Measures
mold coating booth # 5	OAC rule 3745-31-05 (PTI 03-11125)	See A.I.2.a.
		15.0 lbs organic compounds (OC)/hr, 65.7 tons OC/yr (see A.I.2.b)
		0.29 lb particulate emissions (PE)/hr, 1.3 tons PE/yr (see A.I.2.b)
		1.5 tons PE/yr (see A.I.2.c)
		0% opacity, as a six-minute average
	OAC rule 3745-21-07(G)	none (See A.II.1.)

2. Additional Terms and Conditions

2.a The permittee shall emit no more than 75.0 tons of OC (from coatings), based upon a rolling, 12-month period from emissions units R008, R009, R010, R011, R012, R013 and R014, combined.

2.b The 15.0 lbs OC/hr, 65.7 tons OC/yr, 0.29 lb PE/hr and 1.3 tons PE/yr emission limitations were established for PTI purposes to reflect the potentials to emit for this emissions unit. Therefore, it is not necessary to develop record keeping and reporting requirements to ensure compliance with these limitations.

2.c The PE, from emissions units R008, R009, R010, R011, R012, R013 and R014, combined, shall not exceed 1.5 tons/yr.

2.d The OC emissions from the cleanup materials used in this emissions unit are permitted under emissions unit P901. Therefore, no record keeping and reporting requirements are necessary for the cleanup operations associated with this emissions unit.

2.e The uncontrolled mass rate of PE from this emissions unit is less than 10 lbs/hr. Therefore, pursuant to OAC rule 3745-17-11(A)(2)(a)(ii), Figure II of OAC rule 3745-17-11 does not apply. Also, Table I does not apply because the facility is located in Fulton County.

2.f This emissions unit is exempt from the visible emissions limitations specified in OAC rule 3745-17-07(A), pursuant to OAC rule 3745-17-07(A)(3)(h), because OAC rule 3745-17-11 is not applicable.

II. Operational Restrictions

1. The permittee shall not employ any material in this emissions unit that is a photochemically reactive material. "Photochemically reactive material" is defined in OAC rule 3745-21-01(C)(5).

2. The permittee shall operate the dry filtration system whenever this emissions unit is in operation.

III. Monitoring and/or Record Keeping Requirements

1. The permittee shall collect and record the following information each month for emissions units R008, R009, R010, R011, R012, R013 and R014, combined:

1.a the company identification for each coating employed;

1.b the OC content of each coating employed, in pounds per gallon, as applied;

1.c the solids content of each coating employed, in pounds per gallon;

1.d the number of gallons of each coating employed;

1.e the total OC emission rate for all the coatings employed [summation of (b x d) for all coatings], in tons;

1.f the total coating solids usage rate for all the coatings employed [summation of (c x d) for all coatings], in tons; and

1.g the rolling, 12-month summation of the monthly OC emission rates (input rates), in tons.

2. The permittee shall record and maintain the following information each day for the coatings employed in this emissions unit:

2.a the company identification for each material employed; and

2.b documentation on whether or not each material employed is a photochemically reactive material.

3. The permittee shall maintain daily records that document any time periods when the dry filtration system was not in service when the emissions unit was in operation.

IV. Reporting Requirements

1. The permittee shall submit quarterly deviation (excursion) reports that identify all exceedances of the rolling, 12-month OC emission limitation of 75 tons. All quarterly deviation reports shall be submitted in accordance with paragraph A.1.c of the General Terms and Conditions of this permit.

2. The permittee shall notify the Director (appropriate Ohio EPA District Office or local air agency) in writing of any daily record showing the use of any noncomplying material (i.e., photochemically reactive material) in this emissions unit. The notification shall include a copy of such record and shall be sent to the Director (appropriate Ohio EPA District Office or local air agency) within 30 days after the exceedance occurs.

3. The permittee shall submit annual reports that specify the total actual OC emissions from emissions units R008, R009, R010, R011, R012, R013 and R014, combined. These reports shall be submitted by January 31 of each year and shall cover the previous calendar year.

4. The permittee shall notify the Director (the appropriate Ohio EPA District Office or local air agency) in writing of any daily record showing that the dry filtration system was not in service when the emissions unit was in operation. The notification shall include a copy of such record and shall be sent to the Director (the appropriate Ohio EPA District Office or local air agency) within 30 days after the event occurs.

V. Testing Requirements

1. Compliance with the emission limitations/usage restrictions of this permit shall be determined in accordance with the following methods:

V. Testing Requirements (continued)

1.a Emission Limitation: 75.0 tons OC per rolling, 12-month period

Applicable Compliance Method: Compliance shall be based upon the record keeping requirements specified in section A.III.1 of the terms and conditions of this permit.

1.b Emission Limitations: 15.0 lbs OC/hr, 65.7 tons OC/yr

Applicable Compliance Method: Compliance with the hourly limitation shall be determined by multiplying the maximum coating usage rate (gallons/hr) by the maximum OC content of all the coatings (pounds/gallon), as applied.

If required, compliance with the hourly limitation shall be demonstrated pursuant to Method 25 of 40 CFR, Part 60, Appendix A.

Compliance with the annual limitation shall be assumed as long as compliance with hourly limitation is maintained (the annual limitation was calculated by multiplying the hourly limitation by 8760, and then dividing by 2000).

1.c Emission Limitations: 0.29 lb PE/hr, 1.3 tons PE/yr

Applicable Compliance Method:

To determine the actual worst case particulate emissions rate (E), the following equation shall be used for the paint spraying operations:

E = particulate emissions rate (lbs/hr)

E = (maximum coating solids usage rate, in pounds per hour) X (1-TE) X (1-CE)

where:

TE = transfer efficiency, which is the ratio of the amount of coating solids deposited on the coated part to the amount of coating solids used

CE = control efficiency of the control equipment

If required, the permittee shall demonstrate compliance with the emission limit above pursuant to OAC rule 3745-17-03(B)(10).

The tons/yr limitation was developed by multiplying the 0.65 lb/hr limitation by 8760, and then dividing by 2000. Therefore, provided compliance is shown with the hourly limitation, compliance shall also be shown with the annual limitation.

V. Testing Requirements (continued)

1.d Emission Limitation: 1.5 tons PE/yr (for emissions units R008, R009, R010, R011, R012, R013 and R014, combined)

Applicable Compliance Method:

The permittee shall determine compliance based upon the following equation:

E = particulate emissions rate (tons/yr)

E = [coating solids usage rate (this is calculated by summing the 12 monthly coating solids usage rates, from section 1.f, for the calendar year), in tons per year] X (1-TE) X (1-CE)

where:

TE = transfer efficiency, which is the ratio of the amount of coating solids deposited on the coated part to the amount of coating solids used)

CE = control efficiency of the control equipment

1.e Emission Limitation: 0% opacity, as a six-minute average

Applicable Compliance Method: If required, compliance with the visible emissions limitation shall be determined in accordance with Method 9 of 40 CFR, Part 60, Appendix A.

2. The permittee shall determine the OC contents of the coatings based upon the formulation data supplied by the manufacturer of the coatings, or from data determined by analysis of each coating, as received, in accordance with 40 CFR, Part 60, Appendix A, Method 24.

VI. Miscellaneous Requirements

None

B. State Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

Operations, Property, and/or Equipment	Applicable Rules/ Requirements	Applicable Emissions Limitations/Control Measures
mold coating booth # 5	none	none

2. Additional Terms and Conditions

None

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

1. The permit to install for emissions units R001, R002, R005, R006, R008, R009 thru R016, P001 thru P006, and P901 was evaluated based on the actual materials (coatings and cleanup materials) and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant(s):

Pollutant: Butyl Acetate

TLV (ug/m3): 950,000

Maximum Hourly Emission Rate (lbs/hr): 57.8

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 5,770

MAGLC (ug/m3): 22,620

Pollutant: methyl ethyl ketone

TLV (ug/m3): 590,000

Maximum Hourly Emission Rate (lbs/hr): 70.1

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 7,000

MAGLC (ug/m3): 14,048

Pollutant: isopropyl alcohol

TLV (ug/m3): 983,000

Maximum Hourly Emission Rate (lbs/hr): 20.6

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 2,060

MAGLC (ug/m3): 23,400

Pollutant: xylene

TLV (ug/m3): 434,000

Maximum Hourly Emission Rate (lbs/hr): 4.3

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 430

MAGLC (ug/m3): 10,333

III. Monitoring and/or Record Keeping Requirements (continued)

2. Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be still satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

a. changes in the composition of the materials used (coatings or cleanup materials), or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value previously modeled;

b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and

c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01(VV)(1)(a)(ii), and a modification of the existing permit to install will not be required. If the change(s) is (are) defined as a modification under other provisions of the modification definition (other than (VV)(1)(a)(ii)), then the permittee shall obtain a final permit to install prior to the change.

3. The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy:"

a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);

b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and

c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Part III - Terms and Conditions for Emissions Units

Emissions Unit ID: Mold Coat #6 Booth (R013)

Activity Description: This process coats silicone molds with mold release paint

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

Operations, Property, and/or Equipment	Applicable Rules/ Requirements	Applicable Emissions Limitations/Control Measures
mold coating booth # 6	OAC rule 3745-31-05 (PTI 03-11125)	See A.I.2.a.
		15.0 lbs organic compounds (OC)/hr, 65.7 tons OC/yr (see A.I.2.b)
		0.29 lb particulate emissions (PE)/hr, 1.3 tons PE/yr (see A.I.2.b)
		1.5 tons PE/yr (see A.I.2.c)
		0% opacity, as a six-minute average
	OAC rule 3745-21-07(G)	none (See A.II.1.)

2. Additional Terms and Conditions

2.a The permittee shall emit no more than 75.0 tons of OC (from coatings), based upon a rolling, 12-month period from emissions units R008, R009, R010, R011, R012, R013 and R014, combined.

2.b The 15.0 lbs OC/hr, 65.7 tons OC/yr, 0.29 lb PE/hr and 1.3 tons PE/yr emission limitations were established for PTI purposes to reflect the potentials to emit for this emissions unit. Therefore, it is not necessary to develop record keeping and reporting requirements to ensure compliance with these limitations.

2.c The PE, from emissions units R008, R009, R010, R011, R012, R013 and R014, combined, shall not exceed 1.5 tons/yr.

2.d The OC emissions from the cleanup materials used in this emissions unit are permitted under emissions unit P901. Therefore, no record keeping and reporting requirements are necessary for the cleanup operations associated with this emissions unit.

2.e The uncontrolled mass rate of PE from this emissions unit is less than 10 lbs/hr. Therefore, pursuant to OAC rule 3745-17-11(A)(2)(a)(ii), Figure II of OAC rule 3745-17-11 does not apply. Also, Table I does not apply because the facility is located in Fulton County.

2.f This emissions unit is exempt from the visible emissions limitations specified in OAC rule 3745-17-07(A), pursuant to OAC rule 3745-17-07(A)(3)(h), because OAC rule 3745-17-11 is not applicable.

II. Operational Restrictions

1. The permittee shall not employ any material in this emissions unit that is a photochemically reactive material. "Photochemically reactive material" is defined in OAC rule 3745-21-01(C)(5).

2. The permittee shall operate the dry filtration system whenever this emissions unit is in operation.

III. Monitoring and/or Record Keeping Requirements

1. The permittee shall collect and record the following information each month for emissions units R008, R009, R010, R011, R012, R013 and R014, combined:

1.a the company identification for each coating employed;

1.b the OC content of each coating employed, in pounds per gallon, as applied;

1.c the solids content of each coating employed, in pounds per gallon;

1.d the number of gallons of each coating employed;

1.e the total OC emission rate for all the coatings employed [summation of (b x d) for all coatings], in tons;

1.f the total coating solids usage rate for all the coatings employed [summation of (c x d) for all coatings], in tons; and

1.g the rolling, 12-month summation of the monthly OC emission rates (input rates), in tons.

2. The permittee shall record and maintain the following information each day for the coatings employed in this emissions unit:

2.a the company identification for each material employed; and

2.b documentation on whether or not each material employed is a photochemically reactive material.

3. The permittee shall maintain daily records that document any time periods when the dry filtration system was not in service when the emissions unit was in operation.

IV. Reporting Requirements

1. The permittee shall submit quarterly deviation (excursion) reports that identify all exceedances of the rolling, 12-month OC emission limitation of 75 tons. All quarterly deviation reports shall be submitted in accordance with paragraph A.1.c of the General Terms and Conditions of this permit.

2. The permittee shall notify the Director (appropriate Ohio EPA District Office or local air agency) in writing of any daily record showing the use of any noncomplying material (i.e., photochemically reactive material) in this emissions unit. The notification shall include a copy of such record and shall be sent to the Director (appropriate Ohio EPA District Office or local air agency) within 30 days after the exceedance occurs.

3. The permittee shall submit annual reports that specify the total actual OC emissions from emissions units R008, R009, R010, R011, R012, R013 and R014, combined. These reports shall be submitted by January 31 of each year and shall cover the previous calendar year.

4. The permittee shall notify the Director (the appropriate Ohio EPA District Office or local air agency) in writing of any daily record showing that the dry filtration system was not in service when the emissions unit was in operation. The notification shall include a copy of such record and shall be sent to the Director (the appropriate Ohio EPA District Office or local air agency) within 30 days after the event occurs.

V. Testing Requirements

1. Compliance with the emission limitations/usage restrictions of this permit shall be determined in accordance with the following methods:

V. Testing Requirements (continued)

1.a Emission Limitation: 75.0 tons OC per rolling, 12-month period

Applicable Compliance Method: Compliance shall be based upon the record keeping requirements specified in section A.III.1 of the terms and conditions of this permit.

1.b Emission Limitations: 15.0 lbs OC/hr, 65.7 tons OC/yr

Applicable Compliance Method: Compliance with the hourly limitation shall be determined by multiplying the maximum coating usage rate (gallons/hr) by the maximum OC content of all the coatings (pounds/gallon), as applied.

If required, compliance with the hourly limitation shall be demonstrated pursuant to Method 25 of 40 CFR, Part 60, Appendix A.

Compliance with the annual limitation shall be assumed as long as compliance with hourly limitation is maintained (the annual limitation was calculated by multiplying the hourly limitation by 8760, and then dividing by 2000).

1.c Emission Limitations: 0.29 lb PE/hr, 1.3 tons PE/yr

Applicable Compliance Method:

To determine the actual worst case particulate emissions rate (E), the following equation shall be used for the paint spraying operations:

E = particulate emissions rate (lbs/hr)

E = (maximum coating solids usage rate, in pounds per hour) X (1-TE) X (1-CE)

where:

TE = transfer efficiency, which is the ratio of the amount of coating solids deposited on the coated part to the amount of coating solids used

CE = control efficiency of the control equipment

If required, the permittee shall demonstrate compliance with the emission limit above pursuant to OAC rule 3745-17-03(B)(10).

The tons/yr limitation was developed by multiplying the 0.65 lb/hr limitation by 8760, and then dividing by 2000. Therefore, provided compliance is shown with the hourly limitation, compliance shall also be shown with the annual limitation.

V. Testing Requirements (continued)

1.d Emission Limitation: 1.5 tons PE/yr (for emissions units R008, R009, R010, R011, R012, R013 and R014, combined)

Applicable Compliance Method:

The permittee shall determine compliance based upon the following equation:

E = particulate emissions rate (tons/yr)

E = [coating solids usage rate (this is calculated by summing the 12 monthly coating solids usage rates, from section 1.f, for the calendar year), in tons per year] X (1-TE) X (1-CE)

where:

TE = transfer efficiency, which is the ratio of the amount of coating solids deposited on the coated part to the amount of coating solids used)

CE = control efficiency of the control equipment

1.e Emission Limitation: 0% opacity, as a six-minute average

Applicable Compliance Method: If required, compliance with the visible emissions limitation shall be determined in accordance with Method 9 of 40 CFR, Part 60, Appendix A.

2. The permittee shall determine the OC contents of the coatings based upon the formulation data supplied by the manufacturer of the coatings, or from data determined by analysis of each coating, as received, in accordance with 40 CFR, Part 60, Appendix A, Method 24.

VI. Miscellaneous Requirements

None

B. State Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

Operations, Property, and/or Equipment	Applicable Rules/ Requirements	Applicable Emissions Limitations/Control Measures
mold coating booth # 6	none	none

2. Additional Terms and Conditions

None

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

1. The permit to install for emissions units R001, R002, R005, R006, R008, R009 thru R016, P001 thru P006, and P901 was evaluated based on the actual materials (coatings and cleanup materials) and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant(s):

Pollutant: Butyl Acetate

TLV (ug/m3): 950,000

Maximum Hourly Emission Rate (lbs/hr): 57.8

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 5,770

MAGLC (ug/m3): 22,620

Pollutant: methyl ethyl ketone

TLV (ug/m3): 590,000

Maximum Hourly Emission Rate (lbs/hr): 70.1

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 7,000

MAGLC (ug/m3): 14,048

Pollutant: isopropyl alcohol

TLV (ug/m3): 983,000

Maximum Hourly Emission Rate (lbs/hr): 20.6

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 2,060

MAGLC (ug/m3): 23,400

Pollutant: xylene

TLV (ug/m3): 434,000

Maximum Hourly Emission Rate (lbs/hr): 4.3

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 430

MAGLC (ug/m3): 10,333

III. Monitoring and/or Record Keeping Requirements (continued)

2. Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be still satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

a. changes in the composition of the materials used (coatings or cleanup materials), or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value previously modeled;

b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and

c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01(VV)(1)(a)(ii), and a modification of the existing permit to install will not be required. If the change(s) is (are) defined as a modification under other provisions of the modification definition (other than (VV)(1)(a)(ii)), then the permittee shall obtain a final permit to install prior to the change.

3. The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy:"

a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);

b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and

c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Part III - Terms and Conditions for Emissions Units

Emissions Unit ID: Mold Coat #7 Booth (R014)

Activity Description: This process coats silicone molds with mold release paint

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

Operations, Property, and/or Equipment	Applicable Rules/ Requirements	Applicable Emissions Limitations/Control Measures
mold coating booth # 7	OAC rule 3745-31-05 (PTI 03-11125)	See A.I.2.a.
		15.0 lbs organic compounds (OC)/hr, 65.7 tons OC/yr (see A.I.2.b)
		0.29 lb particulate emissions (PE)/hr, 1.3 tons PE/yr (see A.I.2.b)
		1.5 tons PE/yr (see A.I.2.c)
		0% opacity, as a six-minute average
	OAC rule 3745-21-07(G)	none (See A.II.1.)

2. Additional Terms and Conditions

2.a The permittee shall emit no more than 75.0 tons of OC (from coatings), based upon a rolling, 12-month period from emissions units R008, R009, R010, R011, R012, R013 and R014, combined.

2.b The 15.0 lbs OC/hr, 65.7 tons OC/yr, 0.29 lb PE/hr and 1.3 tons PE/yr emission limitations were established for PTI purposes to reflect the potentials to emit for this emissions unit. Therefore, it is not necessary to develop record keeping and reporting requirements to ensure compliance with these limitations.

2.c The PE, from emissions units R008, R009, R010, R011, R012, R013 and R014, combined, shall not exceed 1.5 tons/yr.

2.d The OC emissions from the cleanup materials used in this emissions unit are permitted under emissions unit P901. Therefore, no record keeping and reporting requirements are necessary for the cleanup operations associated with this emissions unit.

2.e The uncontrolled mass rate of PE from this emissions unit is less than 10 lbs/hr. Therefore, pursuant to OAC rule 3745-17-11(A)(2)(a)(ii), Figure II of OAC rule 3745-17-11 does not apply. Also, Table I does not apply because the facility is located in Fulton County.

2.f This emissions unit is exempt from the visible emissions limitations specified in OAC rule 3745-17-07(A), pursuant to OAC rule 3745-17-07(A)(3)(h), because OAC rule 3745-17-11 is not applicable.

II. Operational Restrictions

1. The permittee shall not employ any material in this emissions unit that is a photochemically reactive material. "Photochemically reactive material" is defined in OAC rule 3745-21-01(C)(5).

2. The permittee shall operate the dry filtration system whenever this emissions unit is in operation.

III. Monitoring and/or Record Keeping Requirements

1. The permittee shall collect and record the following information each month for emissions units R008, R009, R010, R011, R012, R013 and R014, combined:

1.a the company identification for each coating employed;

1.b the OC content of each coating employed, in pounds per gallon, as applied;

1.c the solids content of each coating employed, in pounds per gallon;

1.d the number of gallons of each coating employed;

1.e the total OC emission rate for all the coatings employed [summation of (b x d) for all coatings], in tons;

1.f the total coating solids usage rate for all the coatings employed [summation of (c x d) for all coatings], in tons; and

1.g the rolling, 12-month summation of the monthly OC emission rates (input rates), in tons.

2. The permittee shall record and maintain the following information each day for the coatings employed in this emissions unit:

2.a the company identification for each material employed; and

2.b documentation on whether or not each material employed is a photochemically reactive material.

3. The permittee shall maintain daily records that document any time periods when the dry filtration system was not in service when the emissions unit was in operation.

IV. Reporting Requirements

1. The permittee shall submit quarterly deviation (excursion) reports that identify all exceedances of the rolling, 12-month OC emission limitation of 75 tons. All quarterly deviation reports shall be submitted in accordance with paragraph A.1.c of the General Terms and Conditions of this permit.

2. The permittee shall notify the Director (appropriate Ohio EPA District Office or local air agency) in writing of any daily record showing the use of any noncomplying material (i.e., photochemically reactive material) in this emissions unit. The notification shall include a copy of such record and shall be sent to the Director (appropriate Ohio EPA District Office or local air agency) within 30 days after the exceedance occurs.

3. The permittee shall submit annual reports that specify the total actual OC emissions from emissions units R008, R009, R010, R011, R012, R013 and R014, combined. These reports shall be submitted by January 31 of each year and shall cover the previous calendar year.

4. The permittee shall notify the Director (the appropriate Ohio EPA District Office or local air agency) in writing of any daily record showing that the dry filtration system was not in service when the emissions unit was in operation. The notification shall include a copy of such record and shall be sent to the Director (the appropriate Ohio EPA District Office or local air agency) within 30 days after the event occurs.

V. Testing Requirements

1. Compliance with the emission limitations/usage restrictions of this permit shall be determined in accordance with the following methods:

V. Testing Requirements (continued)

1.a Emission Limitation: 75.0 tons OC per rolling, 12-month period

Applicable Compliance Method: Compliance shall be based upon the record keeping requirements specified in section A.III.1 of the terms and conditions of this permit.

1.b Emission Limitations: 15.0 lbs OC/hr, 65.7 tons OC/yr

Applicable Compliance Method: Compliance with the hourly limitation shall be determined by multiplying the maximum coating usage rate (gallons/hr) by the maximum OC content of all the coatings (pounds/gallon), as applied.

If required, compliance with the hourly limitation shall be demonstrated pursuant to Method 25 of 40 CFR, Part 60, Appendix A.

Compliance with the annual limitation shall be assumed as long as compliance with hourly limitation is maintained (the annual limitation was calculated by multiplying the hourly limitation by 8760, and then dividing by 2000).

1.c Emission Limitations: 0.29 lb PE/hr, 1.3 tons PE/yr

Applicable Compliance Method:

To determine the actual worst case particulate emissions rate (E), the following equation shall be used for the paint spraying operations:

E = particulate emissions rate (lbs/hr)

E = (maximum coating solids usage rate, in pounds per hour) X (1-TE) X (1-CE)

where:

TE = transfer efficiency, which is the ratio of the amount of coating solids deposited on the coated part to the amount of coating solids used

CE = control efficiency of the control equipment

If required, the permittee shall demonstrate compliance with the emission limit above pursuant to OAC rule 3745-17-03(B)(10).

The tons/yr limitation was developed by multiplying the 0.65 lb/hr limitation by 8760, and then dividing by 2000. Therefore, provided compliance is shown with the hourly limitation, compliance shall also be shown with the annual limitation.

V. Testing Requirements (continued)

1.d Emission Limitation: 1.5 tons PE/yr (for emissions units R008, R009, R010, R011, R012, R013 and R014, combined)

Applicable Compliance Method:

The permittee shall determine compliance based upon the following equation:

E = particulate emissions rate (tons/yr)

E = [coating solids usage rate (this is calculated by summing the 12 monthly coating solids usage rates, from section 1.f, for the calendar year), in tons per year] X (1-TE) X (1-CE)

where:

TE = transfer efficiency, which is the ratio of the amount of coating solids deposited on the coated part to the amount of coating solids used)

CE = control efficiency of the control equipment

1.e Emission Limitation: 0% opacity, as a six-minute average

Applicable Compliance Method: If required, compliance with the visible emissions limitation shall be determined in accordance with Method 9 of 40 CFR, Part 60, Appendix A.

2. The permittee shall determine the OC contents of the coatings based upon the formulation data supplied by the manufacturer of the coatings, or from data determined by analysis of each coating, as received, in accordance with 40 CFR, Part 60, Appendix A, Method 24.

VI. Miscellaneous Requirements

None

B. State Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

Operations, Property, and/or Equipment	Applicable Rules/ Requirements	Applicable Emissions Limitations/Control Measures
mold coating booth # 7	none	none

2. Additional Terms and Conditions

None

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

1. The permit to install for emissions units R001, R002, R005, R006, R008, R009 thru R016, P001 thru P006, and P901 was evaluated based on the actual materials (coatings and cleanup materials) and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant(s):

Pollutant: Butyl Acetate

TLV (ug/m3): 950,000

Maximum Hourly Emission Rate (lbs/hr): 57.8

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 5,770

MAGLC (ug/m3): 22,620

Pollutant: methyl ethyl ketone

TLV (ug/m3): 590,000

Maximum Hourly Emission Rate (lbs/hr): 70.1

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 7,000

MAGLC (ug/m3): 14,048

Pollutant: isopropyl alcohol

TLV (ug/m3): 983,000

Maximum Hourly Emission Rate (lbs/hr): 20.6

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 2,060

MAGLC (ug/m3): 23,400

Pollutant: xylene

TLV (ug/m3): 434,000

Maximum Hourly Emission Rate (lbs/hr): 4.3

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 430

MAGLC (ug/m3): 10,333

III. Monitoring and/or Record Keeping Requirements (continued)

2. Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be still satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

a. changes in the composition of the materials used (coatings or cleanup materials), or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value previously modeled;

b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and

c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01(VV)(1)(a)(ii), and a modification of the existing permit to install will not be required. If the change(s) is (are) defined as a modification under other provisions of the modification definition (other than (VV)(1)(a)(ii)), then the permittee shall obtain a final permit to install prior to the change.

3. The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy:"

a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);

b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and

c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Part III - Terms and Conditions for Emissions Units

Emissions Unit ID: Maintenance Booth (R015)

Activity Description: This process coats silicone molds with mold release paint

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

Operations, Property, and/or Equipment	Applicable Rules/ Requirements	Applicable Emissions Limitations/Control Measures
maintenance booth	OAC rule 3745-31-05 (PTI 03-11125)	See A.I.2.a. 15 lbs organic compounds (OC)/hr (see A.I.2.b) 0.93 lb particulate emissions (PE)/hr, 3.98 lbs PE/day, 0.5 ton PE/yr (see A.I.2.c) 0% opacity, as a six-minute average The requirements of this rule also include compliance with the requirements of OAC rule 3745-21-09(U)(2)(e).
	OAC rule 3745-21-07(G)	none (See A.II.1.)
	OAC rule 3745-21-09(U)(2)(e)	Coatings usage shall not exceed 10 gallons/day (for the coatings used for metal parts).

2. Additional Terms and Conditions

2.a The permittee shall emit no more than 6.5 tons of OC (from coatings), based upon a rolling, 12-month period from emissions units R002 and R015, combined.

2.b The 15.0 lbs OC/hr emission limitation was established for PTI purposes to reflect the potential to emit for this emissions unit. Therefore, it is not necessary to develop record keeping and reporting requirements to ensure compliance with this limitation.

2.c The PE, from emissions units R002 and R015, combined, shall not exceed 0.5 ton/yr.

2.d The uncontrolled mass rate of PE from this emissions unit is less than 10 lbs/hr. Therefore, pursuant to OAC rule 3745-17-11(A)(2)(a)(ii), Figure II of OAC rule 3745-17-11 does not apply. Also, Table I does not apply because the facility is located in Fulton County.

2.e This emissions unit is exempt from the visible emissions limitations specified in OAC rule 3745-17-07(A), pursuant to OAC rule 3745-17-07(A)(3)(h), because OAC rule 3745-17-11 is not applicable.

2. Additional Terms and Conditions (continued)

2.f The OC emissions from the cleanup materials used in this emissions unit are permitted under emissions unit P901. Therefore, no record keeping and reporting requirements are necessary for the cleanup operations associated with this emissions unit.

II. Operational Restrictions

1. The permittee shall not employ any material in this emissions unit that is a photochemically reactive material. "Photochemically reactive material" is defined in OAC rule 3745-21-01(C)(5).

2. The permittee shall operate the dry filtration system whenever this emissions unit is in operation.

III. Monitoring and/or Record Keeping Requirements

1. The permittee shall collect and record the following information each month for emissions units R002 and R015, combined:

1.a the company identification for each coating employed;

1.b the OC content of each coating employed, in pounds per gallon, as applied;

1.c the solids content of each coating employed, in pounds per gallon, as applied;

1.d the number of gallons of each coating employed;

1.e the total OC emission rate for all the coatings employed [summation of (b x d) for all coatings], in tons;

1.f the total coaitng solids usage rate for all the coatings employed [summation of (c x d) for all coatings], in tons; and

1.g the rolling, 12-month summation of the monthly OC emission rates (input rates), in tons.

2. When coating metal parts, the permittee shall collect and record the following information each day for this emissions unit for the coatings used for the metal parts:

2.a the volume, in gallons, of each coating employed; and

2.b the total volume, in gallons, of all the coatings employed.

3. When coating non-metal parts, the permittee shall collect and record the following information each day for this emissions unit for the coatings used for the non-metal parts:

a. the name and identification number for each material employed; and

b. documentation on whether or not each material employed is a photochemically reactive material.

4. The permittee shall maintain daily records that document any time periods when the dry filtration system was not in service when the emissions unit was in operation.

IV. Reporting Requirements

1. The permittee shall submit quarterly deviation (excursion) reports that identify all exceedances of the rolling, 12-month OC emission limitation of 6.5 tons. All quarterly deviation reports shall be submitted in accordance with paragraph A.1.c of the General Terms and Conditions of this permit.

2. The permittee shall notify the Director (the appropriate Ohio EPA District Office or local air agency) in writing of any daily record showing the use of any noncomplying material (i.e., photochemically reactive material) in this emissions unit. The notification shall include a copy of such record and shall be sent to the Director (the appropriate Ohio EPA District Office or local air agency) within 30 days after the exceedance occurs.

3. The permittee shall submit annual reports that specify the total actual OC emissions from emissions units R002 and R015, combined. These reports shall be submitted by January 31 of each year and shall cover the previous calendar year.

IV. Reporting Requirements (continued)

4. The permittee shall notify the Director (the appropriate District Office or local air agency) in writing of any daily record showing that the dry filtration system was not in service when the emissions unit was in operation. The notification shall include a copy of such record and shall be sent to the Director (the appropriate District Office or local air agency) within 30 days after the event occurs.

5. The permittee shall notify the Director (the appropriate Ohio EPA District Office or local air agency) of any daily record showing that this emissions unit employed more than the applicable maximum daily coating usage restriction of 10 gallons. A copy of such record shall be sent to the Director (the appropriate Ohio EPA District Office or local air agency) within 45 days after the exceedance occurs.

V. Testing Requirements

1. Compliance with the emission limitations/usage restrictions of this permit shall be determined in accordance with the following methods:

1.a Emission Limitation: 6.5 tons OC/yr (for emissions units R002 and R015, combined)

Applicable Compliance Method: Compliance shall be based upon the record keeping requirements specified in section A.III.1 of the terms and conditions of this permit.

1.b Emission Limitation: 15.0 lbs OC/hr

Applicable Compliance Method: Compliance shall be determined by multiplying the maximum hourly coating usage rate (gallons/hr) by the maximum OC content of all the coatings (lbs/gallons).

1.c Emission Limitation: 0.93 lb PE/hr

To determine the actual worst case particulate emissions rate (E), the following equation shall be used for the paint spraying operations:

E = particulate emissions rate (lbs/hr)

E = (maximum coating solids usage rate, in pounds per hour) X (1-TE) X (1-CE)

where:

TE = transfer efficiency, which is the ratio of the amount of coating solids deposited on the coated part to the amount of coating solids used

CE = control efficiency of the control equipment

If required, the permittee shall demonstrate compliance with the emission limit above pursuant to OAC rule 3745-17-03(B)(10).

1.d Emission Limitation: 3.98 lbs PE/day

To determine the actual worst case particulate emissions rate (E), the following equation shall be used for the paint spraying operations:

E = particulate emissions rate (lbs/day)

E = (maximum coating solids usage rate, in pounds per day) X (1-TE) X (1-CE)

where:

TE = transfer efficiency, which is the ratio of the amount of coating solids deposited on the coated part to the amount of coating solids used

CE = control efficiency of the control equipment

V. Testing Requirements (continued)

1.e Emission Limitation: 0.5 ton PE/yr, for emissions units R002 and R015, combined

The permittee shall determine compliance based upon the following equation:

E = particulate emissions rate (tons/yr)

E = [coating solids usage rate (this is calculated by summing the 12 monthly coating solids usage rates, from section 1.f, for the calendar year), in tons per year] X (1-TE) X (1-CE)

where:

TE = transfer efficiency, which is the ratio of the amount of coating solids deposited on the coated part to the amount of coating solids used)

CE = control efficiency of the control equipment

1.f Emission Limitation: 0% opacity, as a six-minute average

Applicable Compliance Method: If required, compliance with the visible emissions limitation shall be determined in accordance with Method 9 of 40 CFR, Part 60, Appendix A.

1.g Usage Restriction: 10 gallons/day of coatings usage (for the coatings used for metal parts)

Applicable Compliance Method: Compliance shall be based upon the record keeping requirements specified in section A.III.2 of the terms and conditions of this permit.

2. The permittee shall determine the OC contents of the coatings based upon the formulation data supplied by the manufacturer of the coatings, or from data determined by analysis of each coating, as received, in accordance with 40 CFR, Part 60, Appendix A, Method 24.

VI. Miscellaneous Requirements

None

B. State Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

Operations, Property, and/or Equipment	Applicable Rules/ Requirements	Applicable Emissions Limitations/Control Measures
maintenance booth	none	none

2. Additional Terms and Conditions

None

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

1. The permit to install for emissions units R001, R002, R005, R006, R008, R009 thru R016, P001 thru P006, and P901 was evaluated based on the actual materials (coatings and cleanup materials) and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant(s):

Pollutant: Butyl Acetate

TLV (ug/m3): 950,000

Maximum Hourly Emission Rate (lbs/hr): 57.8

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 5,770

MAGLC (ug/m3): 22,620

Pollutant: methyl ethyl ketone

TLV (ug/m3): 590,000

Maximum Hourly Emission Rate (lbs/hr): 70.1

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 7,000

MAGLC (ug/m3): 14,048

Pollutant: isopropyl alcohol

TLV (ug/m3): 983,000

Maximum Hourly Emission Rate (lbs/hr): 20.6

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 2,060

MAGLC (ug/m3): 23,400

Pollutant: xylene

TLV (ug/m3): 434,000

Maximum Hourly Emission Rate (lbs/hr): 4.3

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 430

MAGLC (ug/m3): 10,333

III. Monitoring and/or Record Keeping Requirements (continued)

2. Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be still satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

a. changes in the composition of the materials used (coatings or cleanup materials), or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value previously modeled;

b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and

c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01(VV)(1)(a)(ii), and a modification of the existing permit to install will not be required. If the change(s) is (are) defined as a modification under other provisions of the modification definition (other than (VV)(1)(a)(ii)), then the permittee shall obtain a final permit to install prior to the change.

3. The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy:"

a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);

b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and

c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Part III - Terms and Conditions for Emissions Units

Emissions Unit ID: Exterior 3 Paint Booth (Automatic) (R016)

Activity Description: This process puts a finish coat on polyurethane millwork

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

Operations, Property, and/or Equipment	Applicable Rules/ Requirements	Applicable Emissions Limitations/Control Measures
exterior paint booth #3	OAC rule 3745-31-05 (PTI 03-11125)	See A.I.2.a. 48.0 lbs organic compounds (OC)/hr (see A.I.2.b) 1.78 lbs particulate emissions (PE)/hr (see A.I.2.b) 3.6 tons PE/yr (see A.I.2.c) 0% opacity, as a six-minute average
	OAC rule 3745-21-07(G)	none (See A.II.1.)

2. Additional Terms and Conditions

2.a The permittee shall emit no more than 80.0 tons of OC (from coatings), based upon a rolling, 12-month period from emissions units R005, R006 and R016, combined.

2.b The 48.0 lbs OC/hr and 1.78 lbs PE/hr emission limitations were established for PTI purposes to reflect the potentials to emit for this emissions unit. Therefore, it is not necessary to develop record keeping and reporting requirements to ensure compliance with these limitations.

2.c The PE, from emissions units R005, R006 and R016, combined, shall not exceed 3.6 tons/yr.

2.d The OC emissions from the cleanup materials used in this emissions unit are permitted under emissions unit P901. Therefore, no record keeping and reporting requirements are necessary for the cleanup operations associated with this emissions unit.

2.e The uncontrolled mass rate of PE from this emissions unit is less than 10 lbs/hr. Therefore, pursuant to OAC rule 3745-17-11(A)(2)(a)(ii), Figure II of OAC rule 3745-17-11 does not apply. Also, Table I does not apply because the facility is located in Fulton County.

2.f This emissions unit is exempt from the visible emissions limitations specified in OAC rule 3745-17-07(A), pursuant to OAC rule 3745-17-07(A)(3)(h), because OAC rule 3745-17-11 is not applicable.

II. Operational Restrictions

1. The permittee shall not employ any material in this emissions unit that is a photochemically reactive material. "Photochemically reactive material" is defined in OAC rule 3745-21-01(C)(5).

II. Operational Restrictions (continued)

2. The permittee shall operate the dry filtration system whenever this emissions unit is in operation.

III. Monitoring and/or Record Keeping Requirements

1. The permittee shall collect and record the following information each month for emissions units R005, R006 and R016, combined:

1.a the company identification for each coating employed;

1.b the OC content of each coating employed, in pounds per gallon, as applied;

1.c the solids content of each coating employed, in pounds per gallon;

1.d the number of gallons of each coating employed;

1.e the total OC emission rate for all the coatings employed [summation of (b x d) for all coatings], in tons;

1.f the total coating solids usage rate for all the coatings employed [summation of (c x d) for all coatings], in tons; and

1.g the rolling, 12-month summation of the monthly OC emission rates (input rates), in tons.

2. The permittee shall record and maintain the following information each day for the coatings employed in this emissions unit:

2.a the company identification for each material employed; and

2.b documentation on whether or not each material employed is a photochemically reactive material.

3. The permittee shall maintain daily records that document any time periods when the dry filtration system was not in service when the emissions unit was in operation.

IV. Reporting Requirements

1. The permittee shall submit quarterly deviation (excursion) reports that identify all exceedances of the rolling, 12-month OC emission limitation of 80 tons. All quarterly deviation reports shall be submitted in accordance with paragraph A.1.c of the General Terms and Conditions of this permit.

2. The permittee shall notify the Director (appropriate Ohio EPA District Office or local air agency) in writing of any daily record showing the use of any noncomplying material (i.e., photochemically reactive material) in this emissions unit. The notification shall include a copy of such record and shall be sent to the Director (appropriate Ohio EPA District Office or local air agency) within 30 days after the exceedance occurs.

3. The permittee shall submit annual reports that specify the total actual OC emissions from emissions units R005, R006 and R016, combined. These reports shall be submitted by January 31 of each year and shall cover the previous calendar year.

4. The permittee shall notify the Director (the appropriate Ohio EPA District Office or local air agency) in writing of any daily record showing that the dry filtration system was not in service when the emissions unit was in operation. The notification shall include a copy of such record and shall be sent to the Director (the appropriate Ohio EPA District Office or local air agency) within 30 days after the event occurs.

V. Testing Requirements

1. Compliance with the emission limitations/usage restrictions of this permit shall be determined in accordance with the following methods:

1.a Emission Limitation: 80.0 tons OC per rolling, 12-month period

Applicable Compliance Method: Compliance shall be based upon the record keeping requirements specified in section A.III.1 of the terms and conditions of this permit.

V. Testing Requirements (continued)

1.b Emission Limitation: 48.0 lbs OC/hr

Applicable Compliance Method: Compliance with the hourly limitation shall be determined by multiplying the maximum coating usage rate (gallons/hr) by the maximum OC content of all the coatings (pounds/gallon), as applied.

If required, compliance with the hourly limitation shall be demonstrated pursuant to Method 25 of 40 CFR, Part 60, Appendix A.

1.c Emission Limitations: 1.78 lbs PE/hr

Applicable Compliance Method:

To determine the actual worst case particulate emissions rate (E), the following equation shall be used for the paint spraying operations:

E = particulate emissions rate (lbs/hr)

E = (maximum coating solids usage rate, in pounds per hour) X (1-TE) X (1-CE)

where:

TE = transfer efficiency, which is the ratio of the amount of coating solids deposited on the coated part to the amount of coating solids used

CE = control efficiency of the control equipment

If required, the permittee shall demonstrate compliance with the emission limit above pursuant to OAC rule 3745-17-03(B)(10).

1.d Emission Limitation: 3.6 tons PE/yr (for emissions units R005, R006 and R016, combined)

Applicable Compliance Method:

The permittee shall determine compliance based upon the following equation:

E = particulate emissions rate (tons/yr)

E = [coating solids usage rate (this is calculated by summing the 12 monthly coating solids usage rates, from section 1.f, for the calendar year), in tons per year] X (1-TE) X (1-CE)

where:

TE = transfer efficiency, which is the ratio of the amount of coating solids deposited on the coated part to the amount of coating solids used)

CE = control efficiency of the control equipment

1.e Emission Limitation: 0% opacity, as a six-minute average

Applicable Compliance Method: If required, compliance with the visible emissions limitation shall be determined in accordance with Method 9 of 40 CFR Part 60, Appendix A.

2. The permittee shall determine the OC contents of the coatings based upon the formulation data supplied by the manufacturer of the coatings, or from data determined by analysis of each coating, as received, in accordance with 40 CFR, Part 60, Appendix A, Method 24.

VI. Miscellaneous Requirements

None

B. State Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

Operations, Property, and/or Equipment	Applicable Rules/ Requirements	Applicable Emissions Limitations/Control Measures
Exterior paint booth #3	none	none

2. Additional Terms and Conditions

None

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

1. The permit to install for emissions units R001, R002, R005, R006, R008, R009 thru R016, P001 thru P006, and P901 was evaluated based on the actual materials (coatings and cleanup materials) and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant(s):

Pollutant: Butyl Acetate

TLV (ug/m3): 950,000

Maximum Hourly Emission Rate (lbs/hr): 57.8

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 5,770

MAGLC (ug/m3): 22,620

Pollutant: methyl ethyl ketone

TLV (ug/m3): 590,000

Maximum Hourly Emission Rate (lbs/hr): 70.1

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 7,000

MAGLC (ug/m3): 14,048

Pollutant: isopropyl alcohol

TLV (ug/m3): 983,000

Maximum Hourly Emission Rate (lbs/hr): 20.6

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 2,060

MAGLC (ug/m3): 23,400

Pollutant: xylene

TLV (ug/m3): 434,000

Maximum Hourly Emission Rate (lbs/hr): 4.3

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 430

MAGLC (ug/m3): 10,333

III. Monitoring and/or Record Keeping Requirements (continued)

2. Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be still satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

a. changes in the composition of the materials used (coatings or cleanup materials), or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value previously modeled;

b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and

c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01(VV)(1)(a)(ii), and a modification of the existing permit to install will not be required. If the change(s) is (are) defined as a modification under other provisions of the modification definition (other than (VV)(1)(a)(ii)), then the permittee shall obtain a final permit to install prior to the change.

3. The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy:"

a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);

b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and

c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

****

THIS IS THE LAST PAGE OF THE PERMIT

****