



State of Ohio Environmental Protection Agency

Street Address:

Lazarus Gov. Center
122 S. Front Street
Columbus, OH 43215

TELE: (614) 644-3020 FAX: (614) 644-2329

Mailing Address:

Lazarus Gov. Center
P.O. Box 1049
Columbus, OH 43216-1049

12/20/05

CERTIFIED MAIL

RE: Final Title V Significant Permit Modification Chapter 3745-77 permit

06-71-01-0121
Kenworth Truck Company
Kenneth G Legner
65 Kenworth Drive
Chillicothe, OH 45601

Dear Kenneth G Legner:

Enclosed is the Title V permit that allows you to operate the facility in the manner indicated in the permit. Because this permit may contain several conditions and restrictions, we urge you to read it carefully.

The Ohio EPA is encouraging companies to investigate pollution prevention and energy conservation. Not only will this reduce pollution and energy consumption, but it can also save you money. If you would like to learn ways you can save money while protecting the environment, please contact our Office of Pollution Prevention at (614) 644-3469.

You are hereby notified that this action of the Director is final and may be appealed to the Environmental Review Appeals Commission pursuant to Section 3745.04 of the Ohio Revised Code. The appeal must be in writing and set forth the action complained of and the grounds upon which the appeal is based. It must be filed with the Environmental Review Appeals Commission within thirty (30) days after notice of the Director's action. A copy of the appeal must be served on the Director of the Ohio Environmental Protection Agency within three (3) days of filing with the Commission. It is also requested by the Director that a copy of the appeal be served upon the Environmental Enforcement Section of the Office of the Attorney General. An appeal may be filed with the Environmental Review Appeals Commission at the following address:

Environmental Review Appeals Commission
309 South Fourth Street, Room 222
Columbus, Ohio 43215

If you have any questions, please contact Southeast District Office.

Sincerely,


Michael W. Ahern, Supervisor
Field Operations and Permit Section
Division of Air Pollution Control

cc: Southeast District Office
File, DAPC PMU



State of Ohio Environmental Protection Agency

FINAL TITLE V SIGNIFICANT PERMIT MODIFICATION

Original Effective Date: 05/29/02

Expiration Date: 05/29/07

Modification Effective Date:
12/20/05

This document constitutes issuance of a Title V significant permit modification for Facility ID: 06-71-01-0121 to:

Kenworth Truck Company
65 Kenworth Drive
Chillicothe, OH 45601

Emissions Unit ID (Company ID)/Emissions Unit Activity Description

F001 (Plant Roadways and Parking) Fugitive emissions from plant roads and parking areas	Paint truck cabs	K018 (Touch Up Booth #4) Touch Up paint on trucks//to be installed/ESTIMATED DATES
K001 (Frame Assembly) Paint chassis for trucks	K006 (Cab Booth #2) Paint truck cabs	K019 (Cab Touch Up TKS) Touch up paint for cabs
K002 (R&D Booth) Test paints, paint some small parts	K007 (Cab Booth #3) Paint truck cabs	K020 (Fiberglass) Touch up paint for cabs
K003 (Touch Up Booth #1) Touch up paint on trucks	K016 (Cab Booth #4) Paint truck cabs	R010 (Undercoating Booth) Solvent wiping of cabs
K004 (Touch Up Booth #2) Touch up paint on trucks	K017 (Touch Up Booth #3) Touch Up paint on trucks//to be installed/ESTIMATED DATES	
K005 (Cab Booth #1)		

You will be contacted approximately eighteen (18) months prior to the expiration date regarding the renewal of this permit. If you are not contacted, please contact the appropriate Ohio EPA District Office or local air agency listed below. This permit and the authorization to operate the air contaminant sources (emissions units) at this facility shall expire at midnight on the expiration date shown above. If a renewal permit is not issued prior to the expiration date, the permittee may continue to operate pursuant to OAC rule 3745-77-08(E) and in accordance with the terms of this permit beyond the expiration date, provided that a complete renewal application is submitted no earlier than eighteen (18) months and no later than one-hundred eighty (180) days prior to the expiration date.

Described below is the current Ohio EPA District Office or local air agency that is responsible for processing and administering your Title V permit:

Southeast District Office
2195 Front Street
Logan, OH 43138
(740) 385-8501

Ohio Environmental Protection Agency

Joseph P. Koncelik
Director

PART I - GENERAL TERMS AND CONDITIONS

A. State and Federally Enforceable Section

1. Monitoring and Related Record Keeping and Reporting Requirements

- a. Except as may otherwise be provided in the terms and conditions for a specific emissions unit, i.e., in Section A.III of Part III of this Title V permit, the permittee shall maintain records that include the following, where applicable, for any required monitoring under this permit:
- i. The date, place (as defined in the permit), and time of sampling or measurements.
 - ii. The date(s) analyses were performed.
 - iii. The company or entity that performed the analyses.
 - iv. The analytical techniques or methods used.
 - v. The results of such analyses.
 - vi. The operating conditions existing at the time of sampling or measurement.
(Authority for term: OAC rule 3745-77-07(A)(3)(b)(i))
- b. Each record of any monitoring data, testing data, and support information required pursuant to this permit shall be retained for a period of five years from the date the record was created. Support information shall include all calibration and maintenance records and all original strip-chart recordings for continuous monitoring instrumentation, and copies of all reports required by this permit. Such records may be maintained in computerized form.
(Authority for term: OAC rule 3745-77-07(A)(3)(b)(ii))
- c. The permittee shall submit required reports in the following manner:

i. **All reporting required in accordance with OAC rule 3745-77-07(A)(3)(c) for deviations caused by malfunctions shall be submitted in the following manner:**

Any malfunction, as defined in OAC rule 3745-15-06(B)(1), shall be promptly reported to the Ohio EPA in accordance with OAC rule 3745-15-06. In addition, to fulfill the OAC rule 3745-77-07(A)(3)(c) deviation reporting requirements for malfunctions, written reports that identify each malfunction that occurred during each calendar quarter (including each malfunction reported only verbally in accordance with OAC rule 3745-15-06) shall be submitted (i.e., postmarked) by January 31, April 30, July 31, and October 31 of each year in accordance with General Term and Condition A.1.c.ii below; and each report shall cover the previous calendar quarter.

In accordance with OAC rule 3745-15-06, a malfunction reportable under OAC rule 3745-15-06(B) constitutes a violation of an emission limitation (or control requirement) and, therefore, is a deviation of the federally enforceable permit requirements. Even though verbal notifications and written reports are required for malfunctions pursuant to OAC rule 3745-15-06, the written reports required pursuant to this term must be submitted quarterly to satisfy the prompt reporting provision of OAC rule 3745-77-07(A)(3)(c).

In identifying each deviation caused by a malfunction, the permittee shall specify the emission limitation(s) (or control requirement(s)) for which the deviation occurred, describe each deviation, and provide the magnitude and duration of each deviation. For a specific malfunction, if this information has been provided in a written report that was submitted in accordance with OAC rule 3745-15-06, the permittee may simply reference that written report to identify the deviation. Nevertheless, all malfunctions, including those reported only verbally in accordance with OAC rule 3745-15-06, must be reported in writing on a quarterly basis.

Any scheduled maintenance, as referenced in OAC rule 3745-15-06(A)(1), that results in a deviation from a

federally enforceable emission limitation (or control requirement) shall be reported in the same manner as described above for malfunctions.

(Authority for term: OAC rule 3745-77-07(A)(3)(c))

- ii. **Except as may otherwise be provided in the terms and conditions for a specific emissions unit, i.e., in Section A.IV of Part III of this Title V permit or, in some cases, in Part II of this Title V permit, all reporting required in accordance with OAC rule 3745-77-07(A)(3)(c) for deviations of the emission limitations, operational restrictions, and control device operating parameter limitations shall be submitted in the following manner:**

Written reports of (a) any deviations from federally enforceable emission limitations, operational restrictions, and control device operating parameter limitations, (b) the probable cause of such deviations, and (c) any corrective actions or preventive measures taken, shall be promptly made to the appropriate Ohio EPA District Office or local air agency. Except as provided below, the written reports shall be submitted (i.e., postmarked) by January 31, April 30, July 31, and October 31 of each year; and each report shall cover the previous calendar quarter.

In identifying each deviation, the permittee shall specify the emission limitation(s), operational restriction(s), and/or control device operating parameter limitation(s) for which the deviation occurred, describe each deviation, and provide the estimated magnitude and duration of each deviation.

These written deviation reports shall satisfy the requirements of OAC rule 3745-77-07(A)(3)(c) pertaining to the submission of monitoring reports every six months and to the prompt reporting of all deviations. Full compliance with OAC rule 3745-77-07(A)(3)(c) requires reporting of all other deviations of the federally enforceable requirements specified in the permit as required by such rule.

If an emissions unit has a deviation reporting requirement for a specific emission limitation, operational restriction, or control device operating parameter limitation that is not on a quarterly basis (e.g., within 30 days following the end of the calendar month, or within 30 or 45 days after the exceedance occurs), that deviation reporting requirement satisfies the reporting requirements specified in this General Term and Condition for that specific emission limitation, operational restriction, or control device parameter limitation. Following the provisions of that non-quarterly deviation reporting requirement will also satisfy (for the deviations so reported) the requirements of OAC rule 3745-77-07(A)(3)(c) pertaining to the submission of monitoring reports every six months and to the prompt reporting of all deviations, and additional quarterly deviation reports for that specific emission limitation, operational restriction, or control device parameter limitation are not required pursuant to this General Term and Condition.

See B.6 below if no deviations occurred during the quarter.

(Authority for term: OAC rule 3745-77-07(A)(3)(c))

- iii. **All reporting required in accordance with the OAC rule 3745-77-07(A)(3)(c) for other deviations of the federally enforceable permit requirements which are not reported in accordance with General Term and Condition A.1.c.ii above shall be submitted in the following manner:**

Unless otherwise specified by rule, written reports that identify deviations of the following federally enforceable requirements contained in this permit; General Terms and Conditions: A.2, A.3, A.4, A.6.e, A.7, A.12, A.14, A.18, A.19, A.20, and A.22 of Part I of this Title V permit, as well as any deviations from the requirements in Section A.V or A.VI of Part III of this Title V permit, and any monitoring, record keeping, and reporting requirements, which are not reported in accordance with General Term and Condition A.1.c.ii above shall be submitted (i.e., postmarked) to the appropriate Ohio EPA District Office or local air agency by January 31 and July 31 of each year; and each report shall cover the previous six calendar months. Unless otherwise specified by rule, all other deviations from federally enforceable requirements identified in this permit shall be submitted annually as part of the annual compliance certification, including deviations of federally enforceable requirements not specifically addressed by permit or rule for the insignificant activities or emissions levels (IEU) identified in Part II.A of this Title V permit. Annual reporting of deviations is

deemed adequate to meet the deviation reporting requirements for IEUs unless otherwise specified by permit or rule.

In identifying each deviation, the permittee shall specify the federally enforceable requirement for which the deviation occurred, describe each deviation, and provide the magnitude and duration of each deviation.

These semi-annual and annual written reports shall satisfy the reporting requirements of OAC rule 3745-77-07(A)(3)(c) for any deviations from the federally enforceable requirements contained in this permit that are not reported in accordance with General Term and Condition A.1.c.ii above.

If no such deviations occurred during a six-month period, the permittee shall submit a semi-annual report which states that no such deviations occurred during that period.

(Authority for term: OAC rules 3745-77-07(A)(3)(c)(i) and (ii) and OAC rule 3745-77-07(A)(13)(b))

- iv. Each written report shall be signed by a responsible official certifying that, "based on information and belief formed after reasonable inquiry, the statements and information in the report (including any written malfunction reports required by OAC rule 3745-15-06 that are referenced in the deviation reports) are true, accurate, and complete."
(Authority for term: OAC rule 3745-77-07(A)(3)(c)(iv))
- v. Reports of any required monitoring and/or record keeping information shall be submitted to the appropriate Ohio EPA District Office or local air agency.
(Authority for term: OAC rule 3745-77-07(A)(3)(c))

2. Scheduled Maintenance

Any scheduled maintenance of air pollution control equipment shall be performed in accordance with paragraph (A) of OAC rule 3745-15-06. Except as provided in OAC rule 3745-15-06(A)(3), any scheduled maintenance necessitating the shutdown or bypassing of any air pollution control system(s) shall be accompanied by the shutdown of the emissions unit(s) that is (are) served by such control system(s). Any scheduled maintenance, as defined in OAC rule 3745-15-06(A)(1), that results in a deviation from a federally enforceable emission limitation (or control requirement) shall be reported in the same manner as described for malfunctions in General Term and Condition A.1.c.i above.

(Authority for term: OAC rule 3745-77-07(A)(3)(c))

3. Risk Management Plans

If applicable, the permittee shall develop and register a risk management plan pursuant to section 112(r) of the Clean Air Act, as amended, 42 U.S.C. § 7401 et seq. ("Act"); and, pursuant to 40 C.F.R. 68.215(a), the permittee shall submit either of the following:

- a. a compliance plan for meeting the requirements of 40 C.F.R. Part 68 by the date specified in 40 C.F.R. 68.10(a) and OAC 3745-104-05(A); or
- b. as part of the compliance certification submitted under 40 C.F.R. 70.6(c)(5), a certification statement that the source is in compliance with all requirements of 40 C.F.R. Part 68 and OAC Chapter 3745-104, including the registration and submission of the risk management plan.

(Authority for term: OAC rule 3745-77-07(A)(4))

4. Title IV Provisions

If the permittee is subject to the requirements of 40 CFR Part 72 concerning acid rain, the permittee shall ensure that any affected emissions unit complies with those requirements. Emissions exceeding any allowances that are lawfully held under Title IV of the Act, or any regulations adopted thereunder, are prohibited.

(Authority for term: OAC rule 3745-77-07(A)(5))

5. Severability Clause

A determination that any term or condition of this permit is invalid shall not invalidate the force or effect of any other term or condition thereof, except to the extent that any other term or condition depends in whole or in part for its operation or implementation upon the term or condition declared invalid.

(Authority for term: OAC rule 3745-77-07(A)(6))

6. General Requirements

- a. The permittee must comply with all terms and conditions of this permit. Any noncompliance with the federally enforceable terms and conditions of this permit constitutes a violation of the Act, and is grounds for enforcement action or for permit revocation, revocation and reissuance, or modification, or for denial of a permit renewal application.
- b. It shall not be a defense for the permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the federally enforceable terms and conditions of this permit.
- c. This permit may be modified, reopened, revoked, or revoked and reissued, for cause, in accordance with A.10 below. The filing of a request by the permittee for a permit modification, revocation and reissuance, or revocation, or of a notification of planned changes or anticipated noncompliance does not stay any term and condition of this permit.
- d. This permit does not convey any property rights of any sort, or any exclusive privilege.
- e. The permittee shall furnish to the Director of the Ohio EPA, or an authorized representative of the Director, upon receipt of a written request and within a reasonable time, any information that may be requested to determine whether cause exists for modifying, reopening or revoking this permit or to determine compliance with this permit. Upon request, the permittee shall also furnish to the Director or an authorized representative of the Director, copies of records required to be kept by this permit. For information claimed to be confidential in the submittal to the Director, if the Administrator of the U.S. EPA requests such information, the permittee may furnish such records directly to the Administrator along with a claim of confidentiality.
- f. Except as otherwise indicated below, this Title V permit, or permit modification, is effective for five years from the original effective date specified in the permit. In the event that this facility becomes eligible for non-title V permits, this permit shall cease to be enforceable upon final issuance of all applicable OAC Chapter 3745-35 operating permits and/or registrations for all subject emissions units located at the facility and:
 - i. the permittee submits an approved facility-wide potential to emit analysis supporting a claim that the facility no longer meets the definition of a “major source” as defined in OAC rule 3745-77-01(W) based on the permanent shutdown and removal of one or more emissions units identified in this permit; or
 - ii. the permittee no longer meets the definition of a “major source” as defined in OAC rule 3745-77-01(W) based on obtaining restrictions on the facility-wide potential(s) to emit that are federally enforceable or legally and practically enforceable ; or
 - iii. a combination of i. and ii. above.

The permittee shall comply with any residual requirements, such as quarterly deviation reports, semi-annual deviation reports, and annual compliance certifications covering the period during which this Title V permit was enforceable. All records relating to this permit must be maintained in accordance with law.

(Authority for term: OAC rule 3745-77-01(W), OAC rule 3745-77-07(A)(3)(b)(ii), OAC rule 3745-77(A)(7))

7. Fees

The permittee shall pay fees to the Director of the Ohio EPA in accordance with ORC section 3745.11 and OAC Chapter 3745-78.

(Authority for term: OAC rule 3745-77-07(A)(8))

8. Marketable Permit Programs

No revision of this permit is required under any approved economic incentive, marketable permits, emissions trading, and other similar programs or processes for changes that are provided for in this permit.

(Authority for term: OAC rule 3745-77-07(A)(9))

9. Reasonably Anticipated Operating Scenarios

The permittee is hereby authorized to make changes among operating scenarios authorized in this permit without notice to the Ohio EPA, but, contemporaneous with making a change from one operating scenario to another, the permittee must record in a log at the permitted facility the scenario under which the permittee is operating. The permit shield provided in these general terms and conditions shall apply to all operating scenarios authorized in this permit.

(Authority for term: OAC rule 3745-77-07(A)(10))

10. Reopening for Cause

This Title V permit will be reopened prior to its expiration date under the following conditions:

- a. Additional applicable requirements under the Act become applicable to one or more emissions units covered by this permit, and this permit has a remaining term of three or more years. Such a reopening shall be completed not later than eighteen (18) months after promulgation of the applicable requirement. No such reopening is required if the effective date of the requirement is later than the date on which the permit is due to expire, unless the original permit or any of its terms and conditions has been extended pursuant to paragraph (E)(1) of OAC rule 3745-77-08.
- b. This permit is issued to an affected source under the acid rain program and additional requirements (including excess emissions requirements) become applicable. Upon approval by the Administrator, excess emissions offset plans shall be deemed to be incorporated into the permit, and shall not require a reopening of this permit.
- c. The Director of the Ohio EPA or the Administrator of the U.S. EPA determines that the federally applicable requirements in this permit are based on a material mistake, or that inaccurate statements were made in establishing the emissions standards or other terms and conditions of this permit related to such federally applicable requirements.
- d. The Administrator of the U.S. EPA or the Director of the Ohio EPA determines that this permit must be revised or revoked to assure compliance with the applicable requirements.

(Authority for term: OAC rules 3745-77-07(A)(12) and 3745-77-08(D))

11. Federal and State Enforceability

Only those terms and conditions designated in this permit as federally enforceable, that are required under the Act, or any of its applicable requirements, including relevant provisions designed to limit the potential to emit of a source, are enforceable by the Administrator of the U.S. EPA, the State, and citizens under the Act. All other terms and conditions of this permit shall not be federally enforceable and shall be enforceable under State law only.

(Authority for term: OAC rule 3745-77-07(B))

12. Compliance Requirements

- a. Any document (including reports) required to be submitted and required by a federally applicable requirement in this Title V permit shall include a certification by a responsible official that, based on information and belief formed after reasonable inquiry, the statements in the document are true, accurate, and complete.
- b. Upon presentation of credentials and other documents as may be required by law, the permittee shall allow the Director of the Ohio EPA or an authorized representative of the Director to:
 - i. At reasonable times, enter upon the permittee's premises where a source is located or the emissions-related activity is conducted, or where records must be kept under the conditions of this permit.
 - ii. Have access to and copy, at reasonable times, any records that must be kept under the conditions of this permit, subject to the protection from disclosure to the public of confidential information consistent with paragraph (E) of OAC rule 3745-77-03.
 - iii. Inspect at reasonable times any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under this permit.
 - iv. As authorized by the Act, sample or monitor at reasonable times substances or parameters for the purpose of assuring compliance with the permit and applicable requirements.

- c. The permittee shall submit progress reports to the appropriate Ohio EPA District Office or local air agency concerning any schedule of compliance for meeting an applicable requirement. Progress reports shall be submitted semiannually, or more frequently if specified in the applicable requirement or by the Director of the Ohio EPA. Progress reports shall contain the following:
- i. Dates for achieving the activities, milestones, or compliance required in any schedule of compliance, and dates when such activities, milestones, or compliance were achieved.
 - ii. An explanation of why any dates in any schedule of compliance were not or will not be met, and any preventive or corrective measures adopted.
- d. Compliance certifications concerning the terms and conditions contained in this permit that are federally enforceable emission limitations, standards, or work practices, shall be submitted to the Director (the appropriate Ohio EPA District Office or local air agency) and the Administrator of the U.S. EPA in the following manner and with the following content:
- i. Compliance certifications shall be submitted annually on a calendar year basis. The annual certification shall be submitted (i.e., postmarked) on or before April 30th of each year during the permit term.
 - ii. Compliance certifications shall include the following:
 - (a) An identification of each term or condition of this permit that is the basis of the certification.
 - (b) The permittee's current compliance status.
 - (c) Whether compliance was continuous or intermittent.
 - (d) The method(s) used for determining the compliance status of the source currently and over the required reporting period.
 - (e) Such other facts as the Director of the Ohio EPA may require in the permit to determine the compliance status of the source.
 - iii. Compliance certifications shall contain such additional requirements as may be specified pursuant to sections 114(a)(3) and 504(b) of the Act.

(Authority for term: OAC rules 3745-77-07(C)(1),(2),(4) and (5) and ORC section 3704.03(L))

13. Permit Shield

- a. Compliance with the terms and conditions of this permit (including terms and conditions established for alternate operating scenarios, emissions trading, and emissions averaging, but excluding terms and conditions for which the permit shield is expressly prohibited under OAC rule 3745-77-07) shall be deemed compliance with the applicable requirements identified and addressed in this permit as of the date of permit issuance.
- b. This permit shield provision shall apply to any requirement identified in this permit pursuant to OAC rule 3745-77-07(F)(2), as a requirement that does not apply to the source or to one or more emissions units within the source.

(Authority for term: OAC rule 3745-77-07(F))

14. Operational Flexibility

The permittee is authorized to make the changes identified in OAC rule 3745-77-07(H)(1)(a) to (H)(1)(c) within the permitted stationary source without obtaining a permit revision, if such change is not a modification under any provision of Title I of the Act [as defined in OAC rule 3745-77-01(JJ)], and does not result in an exceedance of the emissions allowed under this permit (whether expressed therein as a rate of emissions or in terms of total emissions), and the permittee provides the Administrator of the U.S. EPA and the appropriate Ohio EPA District Office or local air agency with written notification within a minimum of seven days in advance of the proposed changes, unless the change is associated with, or in response to, emergency conditions. If less than seven days notice is provided because of a need to respond more quickly to such emergency conditions, the permittee shall provide notice to the Administrator of the U.S. EPA and the appropriate District Office of the Ohio EPA or local air agency as soon as possible after learning of the need to make the change. The

notification shall contain the items required under OAC rule 3745-77-07(H)(2)(d).
(Authority for term: OAC rules 3745-77-07(H)(1) and (2))

15. Emergencies

The permittee shall have an affirmative defense of emergency to an action brought for noncompliance with technology-based emission limitations if the conditions of OAC rule 3745-77-07(G)(3) are met. This emergency defense provision is in addition to any emergency or upset provision contained in any applicable requirement.
(Authority for term: OAC rule 3745-77-07(G))

16. Off-Permit Changes

The owner or operator of a Title V source may make any change in its operations or emissions at the source that is not specifically addressed or prohibited in the Title V permit, without obtaining an amendment or modification of the permit, provided that the following conditions are met:

- a. The change does not result in conditions that violate any applicable requirements or that violate any existing federally enforceable permit term or condition.
- b. The permittee provides contemporaneous written notice of the change to the Director and the Administrator of the U.S. EPA, except that no such notice shall be required for changes that qualify as insignificant emissions levels or activities as defined in OAC rule 3745-77-01(U). Such written notice shall describe each such change, the date of such change, any change in emissions or pollutants emitted, and any federally applicable requirement that would apply as a result of the change.
- c. The change shall not qualify for the permit shield under OAC rule 3745-77-07(F).
- d. The permittee shall keep a record describing all changes made at the source that result in emissions of a regulated air pollutant subject to an applicable requirement, but not otherwise regulated under the permit, and the emissions resulting from those changes.
- e. The change is not subject to any applicable requirement under Title IV of the Act or is not a modification under any provision of Title I of the Act.

Paragraph (I) of rule 3745-77-07 of the Administrative Code applies only to modification or amendment of the permittee's Title V permit. The change made may require a permit to install under Chapter 3745-31 of the Administrative Code if the change constitutes a modification as defined in that Chapter. Nothing in paragraph (I) of rule 3745-77-07 of the Administrative Code shall affect any applicable obligation under Chapter 3745-31 of the Administrative Code.
(Authority for term: OAC rule 3745-77-07(I))

17. Compliance Method Requirements

Nothing in this permit shall alter or affect the ability of any person to establish compliance with, or a violation of, any applicable requirement through the use of credible evidence to the extent authorized by law. Nothing in this permit shall be construed to waive any defenses otherwise available to the permittee, including but not limited to, any challenge to the Credible Evidence Rule (see 62 Fed. Reg. 8314, Feb. 24, 1997), in the context of any future proceeding.
(This term is provided for informational purposes only.)

18. Insignificant Activities or Emissions Levels

Each IEU that has one or more applicable requirements shall comply with those applicable requirements.
(Authority for term: OAC rule 3745-77-07(A)(1))

19. Permit to Install Requirement

Prior to the "installation" or "modification" of any "air contaminant source," as those terms are defined in OAC rule 3745-31-01, a permit to install must be obtained from the Ohio EPA pursuant to OAC Chapter 3745-31.
(Authority for term: OAC rule 3745-77-07(A)(1))

20. Air Pollution Nuisance

The air contaminants emitted by the emissions units covered by this permit shall not cause a public nuisance, in violation of OAC rule 3745-15-07.

(Authority for term: OAC rule 3745-77-07(A)(1))

21. Permanent Shutdown of an Emissions Unit

The permittee may notify Ohio EPA of any emissions unit that is permanently shut down by submitting a certification from the responsible official that identifies the date on which the emissions unit was permanently shut down. Authorization to operate the affected emissions unit shall cease upon the date certified by the responsible official that the emissions unit was permanently shut down.

After the date on which an emissions unit is permanently shut down (i.e., that has been physically removed from service or has been altered in such a way that it can no longer operate without a subsequent “modification” or “installation” as defined in OAC Chapter 3745-31 and therefore ceases to meet the definition of an “emissions unit” as defined in OAC rule 3745-77-01(O)), rendering existing permit terms and conditions irrelevant, the permittee shall not be required, after the date of the certification and submission to Ohio EPA, to meet any Title V permit requirements applicable to that emissions unit, except for any residual requirements, such as the quarterly deviation reports, semi-annual deviation reports and annual compliance certification covering the period during which the emissions unit last operated. All records relating to the shutdown emissions unit, generated while the emissions unit was in operation, must be maintained in accordance with law.

No emissions unit certified by the responsible official as being permanently shut down may resume operation without first applying for and obtaining a permit to install pursuant to OAC Chapter 3745-31.

(Authority for term: OAC rule 3745-77-01)

22. Title VI Provisions

If applicable, the permittee shall comply with the standards for recycling and reducing emissions of ozone depleting substances pursuant to 40 CFR Part 82, Subpart F, except as provided for motor vehicle air conditioners in Subpart B of 40 CFR Part 82:

- a. Persons opening appliances for maintenance, service, repair, or disposal must comply with the required practices specified in 40 CFR 82.156.
- b. Equipment used during the maintenance, service, repair, or disposal of appliances must comply with the standards for recycling and recovery equipment specified in 40 CFR 82.158.
- c. Persons performing maintenance, service, repair, or disposal of appliances must be certified by an approved technician certification program pursuant to 40 CFR 82.161.

(Authority for term: OAC rule 3745-77-01(H)(11))

B. State Only Enforceable Section

1. Reporting Requirements Related to Monitoring and Record Keeping Requirements

The permittee shall submit required reports in the following manner:

- a. Reports of any required monitoring and/or record keeping information shall be submitted to the appropriate Ohio EPA District Office or local air agency.
- b. Except as otherwise may be provided in the terms and conditions for a specific emissions unit, quarterly written reports of (i) any deviations (excursions) from emission limitations, operational restrictions, and control device operating parameter limitations that have been detected by the testing, monitoring, and record keeping requirements specified in this permit, (ii) the probable cause of such deviations, and (iii) any corrective actions or preventive measures which have been or will be taken, shall be submitted to the appropriate Ohio EPA District Office or local air agency. In identifying each deviation, the permittee shall specify the applicable requirement for which the deviation occurred, describe each deviation, and provide the magnitude and duration of each deviation. If no deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted (i.e., postmarked) quarterly, by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters. (These quarterly reports shall exclude deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06.)

2. Records Retention Requirements

Each record of any monitoring data, testing data, and support information required pursuant to this permit shall be retained for a period of five years from the date the record was created. Support information shall include, but not be limited to, all calibration and maintenance records and all original strip-chart recordings for continuous monitoring instrumentation, and copies of all reports required by this permit. Such records may be maintained in computerized form.

3. Inspections and Information Requests

The Director of the Ohio EPA, or an authorized representative of the Director, may, subject to the safety requirements of the permittee and without undue delay, enter upon the premises of this source at any reasonable time for purposes of making inspections, conducting tests, examining records or reports pertaining to any emission of air contaminants, and determining compliance with any applicable State air pollution laws and regulations and the terms and conditions of this permit. The permittee shall furnish to the Director of the Ohio EPA, or an authorized representative of the Director, upon receipt of a written request and within a reasonable time, any information that may be requested to determine whether cause exists for modifying, reopening or revoking this permit or to determine compliance with this permit. Upon verbal or written request, the permittee shall also furnish to the Director of the Ohio EPA, or an authorized representative of the Director, copies of records required to be kept by this permit.

4. Scheduled Maintenance/Malfunction Reporting

Any scheduled maintenance of air pollution control equipment shall be performed in accordance with paragraph (A) of OAC rule 3745-15-06. The malfunction of any emissions units or any associated air pollution control system(s) shall be reported to the appropriate Ohio EPA District Office or local air agency in accordance with paragraph (B) of OAC rule 3745-15-06. Except as provided in that rule, any scheduled maintenance or malfunction necessitating the shutdown or bypassing of any air pollution control system(s) shall be accompanied by the shutdown of the emissions unit(s) that is (are) served by such control system(s).

5. Permit Transfers

Any transferee of this permit shall assume the responsibilities of the prior permit holder. The appropriate Ohio EPA District Office or local air agency must be notified in writing of any transfer of this permit.

6. Additional Reporting Requirements When There Are No Deviations of Federally Enforceable Emission Limitations, Operational Restrictions, or Control Device Operating Parameter Limitations (See Section A of This Permit)

If no emission limitation (or control requirement), operational restriction and/or control device parameter limitation deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted (i.e., postmarked) by January 31, April 30, July 31, and October 31 of each year; and each report shall cover the previous calendar quarter.

The permittee is not required to submit a quarterly report which states that no deviations occurred during that quarter for the following situations:

- a. where an emissions unit has deviation reporting requirements for a specific emission limitation, operational restriction, or control device parameter limitation that override the deviation reporting requirements specified in General Term and Condition A.1.c.ii; or
- b. where an uncontrolled emissions unit has no monitoring, record keeping, or reporting requirements and the emissions unit's applicable emission limitations are established at the potentials to emit; or
- c. where the company's responsible official has certified that an emissions unit has been permanently shut down.

Part II - Specific Facility Terms and Conditions

A. State and Federally Enforceable Section

1. Facility Emission Limitation.

Pursuant to OAC rule 3745-31-05(D) in Permit to Install 06-4949, the coating and cleanup material usages shall be limited such that the maximum annual VOC usage for this facility (i.e., emissions units K001, K002, K003, K004, K005, K006, K007, K016, K017, K018, K019, K020, and R010) shall not exceed 335.0 tons, based upon a rolling, 12-month summation of the VOC usage for all coatings and cleanup materials (solvent-based gun cleaner, water-based gun cleaner, and wipe solvent). For the purpose of this usage limitation, VOC usage is equivalent to VOC emissions.

2. Facility Monitoring and/or Record Keeping Requirements.

The permittee shall maintain a master file that includes the name, identification number, VOC content, and VOC content (excluding water and exempt solvents) of each coating used and/or offered by the facility. The master file shall also include the name, identification number, and VOC content of each cleanup material (solvent-based gun cleaner, water-based gun cleaner, and wipe solvent) used at the facility. This master file shall be updated as new coatings and cleanup materials become available.

The permittee shall collect and record the following information each month:

- a. the number of gallons of each wipe solvent and water-based gun cleaner employed;
- b. the total VOC emissions from all wipe solvents and water-based gun cleaner employed, in pounds and tons;
- c. the total VOC emissions from all coatings and cleanup materials (solvent-based gun cleaner, water-based gun cleaner, and wipe solvent) employed in emissions units K001 through K007, K016 through K020, and R010, in tons; and
- d. the rolling, 12-month summation of the VOC emissions from all coatings and cleanup materials (solvent-based gun cleaner, water-based gun cleaner, and wipe solvent) employed in emissions units K001 through K007, K016 through K020, and R010, in tons.

3. Facility Reporting Requirements.

The permittee shall submit quarterly deviation (excursion) reports that include an identification of each month during which the VOC emissions from the coatings and cleanup materials (solvent-based gun cleaner, water-based gun cleaner, and wipe solvent) employed in emissions units K001 through K007, K016 through K020, and R010 exceeded 335.0 tpy, as a rolling, 12-month summation, and the actual VOC emissions for each such month.

The deviation reports shall be submitted in accordance with the requirements specified in Part I - General Term and Condition A.1.c.ii.

4. Facility Testing Requirements.

Emission Limitation:

335.0 tpy of VOC, based upon a rolling, 12-month summation of the VOC usage for all coatings and cleanup materials (solvent-based gun cleaner, water-based gun cleaner, and wipe solvent) employed in emissions units K001 through K007, K016 through K020, and R010.

Applicable Compliance Method:

Compliance shall be demonstrated based upon the record keeping requirements specified in Part II section A.2 and Part III section A.III for each emissions unit.

A. State and Federally Enforceable Section (continued)

5. The facility-wide individual HAP and the facility-wide total HAP, combined, emission rates shall not exceed 9.9 and 24.9 tons per year, respectively, based upon a rolling, 12-month summation of the emission rates. To ensure enforceability during the first 12 calendar months of operation following the issuance of this permit, the permittee shall not exceed the usage levels specified in the following table:

Month(s)	Total HAP Emissions (Tons)	Individual HAP Emissions (Tons)
1	2.1	0.9
1-2	4.2	1.7
1-3	6.3	2.6
1-4	8.4	3.4
1-5	10.5	4.3
1-6	12.6	5.1
1-7	14.7	6.0
1-8	16.8	6.8
1-9	18.9	7.7
1-10	20.9	8.5
1-11	22.9	9.4
1-12	24.9	9.9

After the first 12 calendar months of operation following issuance of this permit, compliance with the facility-wide individual HAP and the facility-wide total HAP, combined, emission limitations shall be based upon a rolling, 12-month summation of the monthly usage/emissions figures.

6. The following insignificant emissions units are located at this facility:

K021 - paint mix room (PTI 06-4949);
 Z002 - west generator;
 Z003 - east generator;
 Z012 - diesel fuel back-up generator;
 Z013 - back-up pump;
 Z019 - natural gas heater less than 10 mmBtu/hr;
 Z020 - natural gas heater less than 10 mmBtu/hr;
 Z021 - natural gas heater less than 10 mmBtu/hr;
 Z022 - natural gas heater less than 10 mmBtu/hr;
 Z023 - natural gas heater less than 10 mmBtu/hr;
 Z024 - natural gas heater less than 10 mmBtu/hr;
 Z025 - natural gas heater less than 10 mmBtu/hr;
 Z026 - natural gas heater less than 10 mmBtu/hr;
 Z027 - natural gas heater less than 10 mmBtu/hr;
 Z028 - natural gas heater less than 10 mmBtu/hr;
 Z029 - vehicle testing department;
 Z030 - dynamometer #1; and
 Z031 - dynamometer #2.

Each insignificant emissions unit at this facility must comply with all applicable State and federal regulations, as well as any emission limitations and/or control requirements contained within a permit to install for the emissions unit. Insignificant emissions units listed above that are not subject to specific permit to install requirements are subject to one or more applicable requirements contained in the SIP-approved versions of OAC Chapters 3745-17, 3745-18, and 3745-21.

B. State Only Enforceable Section

1. The following insignificant emissions units located at this facility are exempt from permit requirements because they are not subject to any applicable requirements or because they meet the "de minimus" criteria established in OAC rule 3745-15-05:

Z004 - solvent reclamation system;
Z005 - cab washer;
Z006 - maintenance parts washer;
Z007 - maintenance welding/cutting;
Z008 - paint mixing in Dupont room;
Z009 - maintenance welder;
Z010 - tool crib welding station;
Z011 - tool crib parts washer;
Z014 - mobile cutting torch;
Z015 - cutting torches (2 frame rail stationary torches);
Z016 - axle weld;
Z017 - cardboard bailers around plant;
Z018 - trash compactor;
Z032 - facility wide maintenance painting; and
Z033 - frame rail enclosed cutting area torch.

Part III - Terms and Conditions for Emissions Units

Emissions Unit ID: Plant Roadways and Parking (F001)
Activity Description: Fugitive emissions from plant roads and parking areas

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
Plant roadways and parking areas	OAC rule 3745-31-05(A)(3) (PTI 06-07156)	<p>Total particulate emissions (PE) shall not exceed 6.47 tons per year.</p> <p>No visible particulate emissions except for one minute during any 60-minute period.</p> <p>Best available control measures that are sufficient to minimize or eliminate visible emissions of fugitive dust (see sections A.I.2.b through A.I.2.f).</p>

2. Additional Terms and Conditions

- 2.a The paved roadways and parking areas that are covered by this permit and subject to the above-mentioned requirements are listed below:
 - paved roadways:
 - All
 - paved parking areas:
 - All
- 2.b The permittee shall employ best available control measures on all paved roadways and parking areas for the purpose of ensuring compliance with the above-mentioned applicable requirements. In accordance with the permittee's permit application, the permittee has committed to sweep the paved roadways and parking areas at sufficient frequencies to ensure compliance. Nothing in this paragraph shall prohibit the permittee from employing other control measures to ensure compliance.
- 2.c The needed frequencies of implementation of the control measures shall be determined by the permittee's inspections pursuant to the monitoring section of this permit. Implementation of the control measures shall not be necessary for a paved roadway or parking area that is covered with snow and/or ice or if precipitation has occurred that is sufficient for that day to ensure compliance with the above-mentioned applicable requirements. Implementation of any control measure may be suspended if unsafe or hazardous driving conditions would be created by its use.

2. Additional Terms and Conditions (continued)

- 2.d** The permittee shall promptly remove, in such a manner as to minimize or prevent resuspension, earth and/or other material from paved streets onto which such material has been deposited by trucking or earth moving equipment or erosion by water or other means.
- 2.e** Open-bodied vehicles transporting materials likely to become airborne shall have such materials covered at all times if the control measure is necessary for the materials being transported.
- 2.f** Implementation of the above-mentioned control measures in accordance with the terms and conditions of this permit is appropriate and sufficient to satisfy the best available technology requirements of OAC rule 3745-31-05.

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

- 1.** Except as otherwise provided in this section, the permittee shall perform inspections of the paved roadways and parking areas in accordance with the following frequencies:

paved roadways	minimum inspection frequency
All	Weekly
paved parking areas	minimum inspection frequency
All	Weekly
- 2.** The purpose of the inspections is to determine the need for implementing the above-mentioned control measures. The inspections shall be performed during representative, normal traffic conditions. No inspection shall be necessary for a roadway or parking area that is covered with snow and/or ice or if precipitation has occurred that is sufficient for that day to ensure compliance with the above-mentioned applicable requirements. Any required inspection that is not performed due to any of the above-identified events shall be performed as soon as such event(s) has (have) ended, except if the next required inspection is within one week.
- 3.** The permittee shall maintain records of the following information:
 - a. The date and reason any required inspection was not performed, including those inspections that were not performed due to snow and/or ice cover or precipitation;
 - b. The date of each inspection where it was determined by the permittee that it was necessary to implement the control measures;
 - c. The dates the control measures were implemented; and
 - d. On a calendar quarter basis, the total number of days the control measures were implemented and the total number of days where snow and/or ice cover or precipitation were sufficient to not require the control measures.

The information required in section A.III.3.d shall be updated on a calendar quarter basis within 30 days after the end of each calendar quarter.

IV. Reporting Requirements

1. The permittee shall submit deviation reports that identify any of the following occurrences:
 - a. Each day during which an inspection was not performed by the required frequency, excluding an inspection which was not performed due to an exemption for snow and/or ice cover or precipitation; and
 - b. Each instance when a control measure, that was to be implemented as a result of an inspection, was not implemented.

The deviation reports shall be submitted in accordance with the reporting requirements of the General Terms and Conditions of this permit.

V. Testing Requirements

1. Emission Limitation:

No visible particulate emissions except for one minute during any 60-minute period.

Applicable Compliance Method:

If required, compliance with the emission limitation for the paved roadways and parking areas identified above shall be determined in accordance with Test Method 22 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources," as such Appendix existed on July 1, 1996, and the modifications listed in paragraphs (B)(4)(a) through (B)(4)(d) of OAC rule 3745-17-03.

2. Emission Limitation:

Total particulate emissions (PE) shall not exceed 6.47 tons per year.

Applicable Compliance Method:

The emission factor calculation for paved roadways and parking areas in AP-42 section 13.2.1-5 (September, 1998) shall be utilized to determine compliance. Initial compliance has been determined using inputs representing Potential To Emit (PTE) conditions as follows:

$$E = K \times (SL/2)^{0.65} \times (W/3)^{1.5} \times (1 - P/4N)$$

where:

E = size-specific emission factor (lb/VMT);

K = particle size multiplier = 0.082;

SL = silt content of road surface material (g/m²) = 0.4g/m²;

W = mean vehicle weight (tons) = 4.2;

P = number of "wet" days with at least 0.01 inch of precipitation during period = 136; and

N = number of days in averaging period = 365.

Using the values in the above equation, the PE factors were used to calculate emissions as follows:

$$E = 0.082 \times (0.4/2)^{0.65} \times (4.2/3)^{1.5} \times [1 - (136/4 \times 365)]$$

$$E = 0.043 \text{ lb/VMT}$$

To calculate the actual emissions, multiply the emission factor by VMT/yr to obtain the annual PE rates:

$$\text{Annual: PE (TPY)} = (0.043 \text{ lb/VMT}) \times (299,083 \text{ VMT/yr}) / (2000 \text{ lbs/ton}) = 6.466 \text{ tpy}$$

VI. Miscellaneous Requirements

None

B. State Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
---	---	--

2. Additional Terms and Conditions

None

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Part III - Terms and Conditions for Emissions Units

Emissions Unit ID: Frame Assembly (K001)
Activity Description: Paint chassis for trucks

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

- The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
frame assembly controlled with a water wash system	OAC rule 3745-31-05(A)(3) (PTI 06-4949)	<p>Volatile organic compound (VOC) emissions shall not exceed 200.0 lbs/hr and 174.0 tpy of VOC, based upon a rolling, 12-month summation of the VOC emissions from all coatings and cleanup materials (solvent-based gun cleaner).</p> <p>Particulate emissions shall not exceed 11.3 tpy.</p> <p>The requirements of this rule also include compliance with the requirements of OAC rules 3745-17-07(A), 3745-17-11(B), and 3745-21-09(U)(1)(c).</p>
	OAC rule 3745-17-07(A)	Visible particulate emissions shall not exceed 20% opacity as a 6-minute average, except as provided by the rule.
	OAC rule 3745-17-11(B)	Particulate emissions shall not exceed 2.58 lbs/hr.
	OAC rule 3745-21-07(G)(2)	See A.II.2 below.
	OAC rule 3745-21-09(U)(1)(c)	<p>The VOC contents of the coatings employed shall not exceed the following:</p> <p>3.5 pounds of VOC per gallon of coating, excluding water and exempt solvents, for an extreme performance coating (daily volume-weighted average)</p>

2. Additional Terms and Conditions

- 2.a** Total facility-wide Hazardous Air Pollutant (HAP) emissions, combined, shall not exceed 24.9 tons per rolling, 12-month period.

Individual facility-wide HAP emissions shall not exceed 9.9 tons per rolling, 12-month period.

- 2.b** For the requirements of this emissions unit, "cleanup materials" shall refer only to solvent-based gun cleaner. Requirements for cleanup materials other than solvent-based gun cleaner (i.e., water-based gun cleaner, wipe solvent) are addressed in Part II.

II. Operational Restrictions

1. The permittee shall operate the water wash system for the control of particulate emissions when this emissions unit is in operation.
2. The permittee shall not employ any photochemically reactive materials, as defined in OAC rule 3745-21-01(C)(5), in this emissions unit.

III. Monitoring and/or Record Keeping Requirements

1. The permittee shall collect and record the following information each day for this emissions unit:
 - a. the name and identification number of each coating and cleanup material employed;
 - b. the VOC content of each coating (excluding water and exempt solvents), and cleanup material, in pounds per gallon;
 - c. the number of gallons of each coating, and cleanup material (solvent based gun cleaner) employed;
 - d. the daily volume-weighted average VOC content of all coatings, as applied, calculated in accordance with the equation specified in paragraph (B)(9) of OAC rule 3745-21-10 for CVOC,2.
 - e. the hours of operation; and
 - f. the total VOC emissions from all coatings and cleanup materials (solvent based gun cleaner) employed $[(b \times c) / e]$, in lbs/hr.
2. The permittee shall collect and record the following information each month for the line:
 - a. the name and identification number of each coating, and cleanup material employed;
 - b. the VOC content of each coating (excluding water and exempt solvents), and cleanup material, in pounds per gallon;
 - c. the total HAP content of each coating, and cleanup material, in pounds per gallon;
 - d. the individual HAP content of each coating, and cleanup material, in pounds per gallon;
 - e. the number of gallons of each coating, and cleanup material (solvent based gun cleaner) employed;
 - f. the total VOC emissions (VOC applied) from all coatings, and cleanup materials (solvent based gun cleaner) employed [the sum of ((2.b times 2.e) divided by 2000 lb/ton) for all coatings and cleanup materials], in tons;
 - g. the rolling, 12-month summation of the VOC emissions, in tons; and
 - h. beginning after the first 12 calendar months of operation following issuance of this permit, the rolling 12-month summation of the gallons of each coating and clean-up material (solvent based gun cleaner) employed. Also, during the first 12 calendar months of operation following issuance of this permit, the permittee shall record the cumulative coating usage for each calendar month.

III. Monitoring and/or Record Keeping Requirements (continued)

3. The permittee shall maintain daily records that document any time periods when the water wash system was not in service when the emissions unit was in operation.
4. For each day a photochemically reactive coating and/or cleanup material is employed, the permittee shall maintain a record of the type and quantity of photochemically reactive materials employed in this emissions unit.

IV. Reporting Requirements

1. The permittee shall notify the Ohio EPA Southeast District Office in writing of any daily record showing that the daily volume-weighted average VOC content exceeds the applicable limitation. The notification shall include a copy of such record and shall be sent to the Ohio EPA Southeast District Office within 45 days after the exceedance occurs.
2. The permittee shall submit quarterly deviation (excursion) reports that include the following information:
 - a. an identification of each day during which the VOC emissions from all the coatings and cleanup materials (solvent-based gun cleaner) exceeded 200.0 lbs/hr, and the actual hourly average VOC emissions for each such day; and
 - b. an identification of each month during which the VOC emissions from the coatings and cleanup materials (solvent-based gun cleaner) employed in this emissions unit exceeded 174.0 tpy, as a rolling, 12-month summation, and the actual VOC emissions for each such month.
3. The permittee shall submit quarterly deviation (excursion) reports that identify all days when this emissions unit was in operation and the water wash system was not in service.
4. The permittee shall submit deviation reports that identify the days during which photochemically reactive materials were employed in this emissions unit. Each report shall identify the cause for the use of the photochemically reactive material(s), and the estimated total quantity of material(s) emitted during each such day, in pounds. Each report shall be submitted to the Ohio EPA Southeast District Office within 30 days of the deviation.
5. The permittee shall submit deviation (excursion) reports that identify all exceedances of the rolling, 12-month facility-wide total HAP emission limitation and, for the first 12 calendar months of operation, all exceedances of the maximum allowable cumulative total HAP emission limitation set forth in Part II, section A.5 of this permit.
6. The permittee shall submit deviation (excursion) reports that identify all exceedances of the rolling, 12-month facility-wide individual HAP emission limitation and, for the first 12 calendar months of operation, all exceedances of the maximum allowable cumulative individual HAP emission limitation set forth in Part II, section A.5 of this permit.
7. The quarterly deviation reports shall be submitted in accordance with the requirements specified in Part I - General Term and Condition A.1.c.ii.

V. Testing Requirements

1. Compliance with the emission limitations in section A.I.1 of these terms and conditions shall be determined in accordance with the following methods:
 - 1.a Emission Limitation:

3.5 pounds of VOC per gallon of coating, excluding water and exempt solvents (daily volume-weighted average), for an extreme performance coating

Applicable Compliance Method:

Compliance shall be demonstrated based upon the record keeping requirements specified in section A.III.1.

V. Testing Requirements (continued)

1.b Emission Limitation:

200.0 lbs/hr of VOC

Applicable Compliance Method:

Compliance may be demonstrated based upon the record keeping requirements specified in sections A.III.1 and A.III.2. If required, compliance shall be demonstrated based upon emission tests performed in accordance with the requirements specified in 40 CFR Part 60, Appendix A, Methods 1 through 4 and 25.

1.c Emission Limitation:

174.0 tpy of VOC, based on a rolling, 12-month summation

Applicable Compliance Method:

Compliance shall be demonstrated based upon the record keeping requirements specified in sections A.III.1 and A.III.2.

1.d Emission Limitation:

2.58 lbs/hr of particulate emissions

Applicable Compliance Method:

Compliance may be demonstrated by multiplying the particulate emission factor of 244.4 lbs/hr of solids by the control efficiency of (1 - 0.99). This emission factor was established from company data to determine an emission rate for particulates from spray booths at this facility. If required, the permittee shall demonstrate compliance with this emission limitation in accordance with the methods and procedures specified in OAC rule 3745-17-03(B)(10).

1.e Emission Limitation:

11.3 tpy of particulate emissions

Applicable Compliance Method:

Compliance shall be demonstrated by multiplying the allowable emission limitation for particulate emissions by the actual hours of operation per year, and then dividing by 2000 lbs/ton.

1.f Emission Limitation:

20% opacity as a 6-minute average

Applicable Compliance Method:

Compliance shall be demonstrated based upon visible particulate emission observations performed in accordance with the methods and procedures specified in 40 CFR Part 60, Appendix A, Method 9 and OAC rule 3745-17-03(B)(1).

1.g Emission Limitation:

Total facility-wide HAP emissions, combined, shall not exceed 24.9 tons per rolling, 12-month period.

Applicable Compliance Method:

Compliance shall be based on the record keeping requirements specified in section A.III.2.

V. Testing Requirements (continued)

1.h Emission Limitation:

Individual facility-wide HAP emissions shall not exceed 9.9 tons per rolling, 12-month period.

Applicable Compliance Method:

Compliance shall be based on the record keeping requirements specified in section A.III.2.

2. Formulation data shall be used to determine the VOC contents of the cleanup materials.

USEPA Method 24 shall be used to determine the VOC contents for coatings. If any such coating has not been analyzed using Method 24 since January 1, 1991, the permittee shall either conduct a Method 24 analysis of the coating or obtain a Method 24 analysis of the coating from the coating supplier within one year of the issuance of the Permit to Operate. If the permittee determines that Method 24 cannot be used for a particular coating, the permittee shall so notify the Administrator of the USEPA and shall use formulation data for that coating to demonstrate compliance until the USEPA provides alternative analytical procedures or alternative precision statements for Method 24.

VI. Miscellaneous Requirements

None

B. State Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
---	---	--

2. Additional Terms and Conditions

None

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Part III - Terms and Conditions for Emissions Units

Emissions Unit ID: R&D Booth (K002)
Activity Description: Test paints, paint some small parts

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

- The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
R&D booth controlled with an exhaust filter	OAC rule 3745-31-05(A)(3) (PTI 06-4949)	Volatile organic compound (VOC) emissions shall not exceed 50.0 lbs/hr and 20.0 tpy of VOC, based upon a rolling, 12-month summation of the VOC emissions from all coatings and cleanup materials (solvent-based gun cleaner). Particulate emissions shall not exceed 2.41 tpy. The requirements of this rule also include compliance with the requirements of OAC rules 3745-17-07(A), 3745-17-11(B), and 3745-21-09(U)(2)(e)(iii).
	OAC rule 3745-17-07(A)	Visible particulate emissions shall not exceed 20% opacity as a 6-minute average, except as provided by the rule.
	OAC rule 3745-17-11(B)	Particulate emissions shall not exceed 0.551 lb/hr.
	OAC rule 3745-21-07(G)(2)	See A.II.2 below.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
	OAC rule 3745-21-09(U)(2)(e)(iii)	<p>This emissions unit shall not employ more than 10.0 gallons of coatings on metal parts in any given day.</p> <p>If this emissions unit ever employs more than 10.0 gallons of coatings on metal parts in any given day, thereafter, the VOC content of all metal parts coatings employed shall not exceed 3.5 pounds of VOC per gallon of coating, excluding water and exempt solvents, as a daily, volume-weighted average, pursuant to OAC rule 3745-21-09(U)(1)(c), and the 10.0 gallons per day limitation shall no longer be applicable.</p>

2. Additional Terms and Conditions

- 2.a** Total facility-wide Hazardous Air Pollutant (HAP) emissions, combined, shall not exceed 24.9 tons per rolling, 12-month period.

Individual facility-wide HAP emissions shall not exceed 9.9 tons per rolling, 12-month period.

- 2.b** For the requirements of this emissions unit, "cleanup materials" shall refer only to solvent-based gun cleaner. Requirements for cleanup materials other than solvent-based gun cleaner (i.e., water-based gun cleaner, wipe solvent) are addressed in Part II.

II. Operational Restrictions

1. The permittee shall employ the exhaust filter system for the control of particulate emissions when this emissions unit is in operation.
2. The permittee shall not employ any photochemically reactive materials, as defined in OAC rule 3745-21-01(C)(5), in this emissions unit.

III. Monitoring and/or Record Keeping Requirements

1. The permittee shall collect and record the following information each day for this emissions unit:
 - a. the name and identification number of each coating and cleanup material employed;
 - b. the VOC content of each coating (excluding water and exempt solvents), and cleanup material, in pounds per gallon;
 - c. the number of gallons of each coating, and cleanup material (solvent based gun cleaner) employed;
 - d. the daily volume-weighted average VOC content of all coatings, as applied, calculated in accordance with the equation specified in paragraph (B)(9) of OAC rule 3745-21-10 for CVOC,2.
 - e. the hours of operation; and
 - f. the total VOC emissions from all coatings and cleanup materials (solvent based gun cleaner) employed [(b X c) / e], in lbs/hr.

III. Monitoring and/or Record Keeping Requirements (continued)

2. The permittee shall collect and record the following information each month for the line:
 - a. the name and identification number of each coating, and cleanup material employed;
 - b. the VOC content of each coating (excluding water and exempt solvents), and cleanup material, in pounds per gallon;
 - c. the total HAP content of each coating, and cleanup material, in pounds per gallon;
 - d. the individual HAP content of each coating, and cleanup material, in pounds per gallon;
 - e. the number of gallons of each coating, and cleanup material (solvent based gun cleaner) employed;
 - f. the total VOC emissions (VOC applied) from all coatings, and cleanup materials (solvent based gun cleaner) employed [the sum of ((2.b times 2.e) divided by 2000 lb/ton) for all coatings and cleanup materials], in tons;
 - g. the rolling, 12-month summation of the VOC emissions, in tons; and
 - h. beginning after the first 12 calendar months of operation following issuance of this permit, the rolling 12-month summation of the gallons of each coating and clean-up material (solvent based gun cleaner) employed. Also, during the first 12 calendar months of operation following issuance of this permit, the permittee shall record the cumulative coating usage for each calendar month.
3. The permittee shall maintain daily records that document any time periods when the exhaust filter system was not in service when the emissions unit was in operation.
4. For each day a photochemically reactive coating and/or cleanup material is employed, the permittee shall maintain a record of the type and quantity of photochemically reactive materials employed in this emissions unit.

IV. Reporting Requirements

1. The permittee shall notify the Ohio EPA Southeast District Office in writing of any daily record showing that the coating line employs more than the applicable maximum daily coating usage limit. The notification shall include a copy of such record and shall be sent to the Ohio EPA Southeast District Office within 45 days after the exceedance occurs.
2. If this emissions unit ever employs more than 10.0 gallons of coatings on metal parts in any given day, thereafter, the permittee shall notify the Ohio EPA Southeast District Office in writing of any daily record showing that the daily volume-weighted average VOC content exceeds the applicable limitation. The notification shall include a copy of such record and shall be sent to the Ohio EPA Southeast District Office within 45 days after the exceedance occurs.
3. The permittee shall submit quarterly deviation (excursion) reports that include the following information:
 - a. an identification of each day during which the VOC emissions from all the coatings and cleanup materials (solvent-based gun cleaner) exceeded 50.0 lbs/hr, and the actual hourly average VOC emissions for each such day; and
 - b. an identification of each month during which the VOC emissions from the coatings and cleanup materials (solvent-based gun cleaner) employed in this emissions unit exceeded 20.0 tpy, as a rolling, 12-month summation, and the actual VOC emissions for each such month.
4. The permittee shall submit quarterly deviation (excursion) reports that identify all days when this emissions unit was in operation and the filter exhaust system was not in service.

IV. Reporting Requirements (continued)

5. The permittee shall submit deviation reports which identify the days during which photochemically reactive materials were employed in this emissions unit. Each report shall identify the cause for the use of the photochemically reactive material(s), and the estimated total quantity of material(s) emitted during each such day, in pounds. Each report shall be submitted to the Ohio EPA Southeast District Office within 30 days of the deviation.
6. The permittee shall submit deviation (excursion) reports that identify all exceedances of the rolling, 12-month facility-wide total HAP emission limitation and, for the first 12 calendar months of operation, all exceedances of the maximum allowable cumulative total HAP emission limitation set forth in Part II, section A.5 of this permit.
7. The permittee shall submit deviation (excursion) reports that identify all exceedances of the rolling, 12-month facility-wide individual HAP emission limitation and, for the first 12 calendar months of operation, all exceedances of the maximum allowable cumulative individual HAP emission limitation set forth in Part II, section A.5 of this permit.
8. The quarterly deviation reports shall be submitted in accordance with the requirements specified in Part I - General Term and Condition A.1.c.ii.

V. Testing Requirements

1. Compliance with the emission limitations in section A.I.1 of these terms and conditions shall be determined in accordance with the following methods:

- 1.a Emission Limitation:

This emissions unit shall not employ more than 10.0 gallons of coating on metal parts in any given day. If this emissions unit ever employs more than 10.0 gallons of coating on metal parts in any given day, thereafter, the VOC content of all metal parts coatings employed shall not exceed 3.5 pounds of VOC per gallon of coating, excluding water and exempt solvents, as a daily, volume-weighted average, pursuant to OAC rule 3745-21-09(U)(1)(c), and the 10.0 gallons per day limitation shall no longer be applicable.

Applicable Compliance Method:

Compliance shall be demonstrated based upon the record keeping requirements specified in section A.III.1.

- 1.b Emission Limitation:

50.0 lbs/hr of VOC

Applicable Compliance Method:

Compliance may be demonstrated based upon the record keeping requirements specified in sections A.III.1 and A.III.2. If required, compliance shall also be demonstrated based upon emission tests performed in accordance with the requirements specified in 40 CFR Part 60, Appendix A, Methods 1 through 4 and 25.

- 1.c Emission Limitation:

20.0 tpy of VOC, based on a rolling, 12-month summation

Applicable Compliance Method:

Compliance shall be demonstrated based upon the record keeping requirements specified in sections A.III.1 and A.III.2.

V. Testing Requirements (continued)

1.d Emission Limitation:

Particulate emissions shall not exceed 0.551 lb/hr.

Applicable Compliance Method:

To determine the actual worst case particulate emission rate, the following equation may be used:

$$E = (M) * (1-TE) * (1-CE)$$

where:

E = particulate matter emission rate (lbs/hr),

M = maximum coating solids usage rate (lbs/hr),

TE = transfer efficiency of coating equipment (ratio of the amount of coating solids deposited on the coated part to the amount of coating solids used),

CE = control efficiency of the control equipment. If more than one piece of control equipment is used in series, the equation should be multiplied by additional (1-CE) terms for each additional piece of equipment.

If required, the permittee shall demonstrate compliance with this emission limitation in accordance with the methods and procedures specified in OAC rule 3745-17-03(B)(10).

1.e Emission Limitation:

2.41 tpy of particulate emissions

Applicable Compliance Method:

Compliance shall be demonstrated by multiplying the allowable emission limitation for particulate emissions by the actual hours of operation per year, and then dividing by 2000 lbs/ton.

1.f Emission Limitation:

20% opacity as a 6-minute average

Applicable Compliance Method:

Compliance shall be demonstrated based upon visible particulate emission observations performed in accordance with the methods and procedures specified in 40 CFR Part 60, Appendix A, Method 9 and OAC rule 3745-17-03(B)(1).

1.g Emission Limitation:

Total facility-wide HAP emissions, combined, shall not exceed 24.9 tons per rolling, 12-month period.

Applicable Compliance Method:

Compliance shall be based on the record keeping requirements specified in section A.III.2.

1.h Emission Limitation:

Individual facility-wide HAP emissions shall not exceed 9.9 tons per rolling, 12-month period.

Applicable Compliance Method:

Compliance shall be based on the record keeping requirements specified in section A.III.2.

V. Testing Requirements (continued)

2. Formulation data shall be used to determine the VOC contents of the cleanup materials.

USEPA Method 24 shall be used to determine the VOC contents for coatings. If any such coating has not been analyzed using Method 24 since January 1, 1991, the permittee shall either conduct a Method 24 analysis of the coating or obtain a Method 24 analysis of the coating from the coating supplier within one year of the issuance of the Permit to Operate. If the permittee determines that Method 24 cannot be used for a particular coating, the permittee shall so notify the Administrator of the USEPA and shall use formulation data for that coating to demonstrate compliance until the USEPA provides alternative analytical procedures or alternative precision statements for Method 24.

VI. Miscellaneous Requirements

None

B. State Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
---	---	--

2. Additional Terms and Conditions

None

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Part III - Terms and Conditions for Emissions Units

Emissions Unit ID: Touch Up Booth #1 (K003)
Activity Description: Touch up paint on trucks

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

- The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
touch up booth #1 controlled with an exhaust filter	OAC rule 3745-31-05(A)(3) (PTI 06-4949)	Volatile organic compound (VOC) emissions shall not exceed 50.0 lbs/hr and 20.0 tpy of VOC, based upon a rolling, 12-month summation of the VOC emissions from all coatings and cleanup materials (solvent-based gun cleaner).
		Particulate emissions shall not exceed 2.41 tpy.
		The requirements of this rule also include compliance with the requirements of OAC rules 3745-17-07(A), 3745-17-11(B), and 3745-21-09(U)(2)(e)(iii).
	OAC rule 3745-17-07(A)	Visible particulate emissions shall not exceed 20% opacity as a 6-minute average, except as provided by the rule.
	OAC rule 3745-17-11(B)	Particulate emissions shall not exceed 0.551 lb/hr.
	OAC rule 3745-21-07(G)(2)	See A.II.2 below.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
	OAC rule 3745-21-09(U)(2)(e)(iii)	<p>This emissions unit shall not employ more than 10.0 gallons of coatings on metal parts in any given day.</p> <p>If this emissions unit ever employs more than 10.0 gallons of coatings on metal parts in any given day, thereafter, the VOC content of all metal parts coatings employed shall not exceed 3.5 pounds of VOC per gallon of coating, excluding water and exempt solvents, as a daily, volume-weighted average, pursuant to OAC rule 3745-21-09(U)(1)(c), and the 10.0 gallons per day limitation shall no longer be applicable.</p>

2. Additional Terms and Conditions

- 2.a** Total facility-wide Hazardous Air Pollutant (HAP) emissions, combined, shall not exceed 24.9 tons per rolling, 12-month period.

Individual facility-wide HAP emissions shall not exceed 9.9 tons per rolling, 12-month period.

- 2.b** For the requirements of this emissions unit, "cleanup materials" shall refer only to solvent-based gun cleaner. Requirements for cleanup materials other than solvent-based gun cleaner (i.e., water-based gun cleaner, wipe solvent) are addressed in Part II.

II. Operational Restrictions

1. The permittee shall employ the exhaust filter system for the control of particulate emissions when this emissions unit is in operation.
2. The permittee shall not employ any photochemically reactive materials, as defined in OAC rule 3745-21-01(C)(5), in this emissions unit.

III. Monitoring and/or Record Keeping Requirements

1. The permittee shall collect and record the following information each day for this emissions unit:
 - a. the name and identification number of each coating and cleanup material employed;
 - b. the VOC content of each coating (excluding water and exempt solvents), and cleanup material, in pounds per gallon;
 - c. the number of gallons of each coating, and cleanup material (solvent based gun cleaner) employed;
 - d. the daily volume-weighted average VOC content of all coatings, as applied, calculated in accordance with the equation specified in paragraph (B)(9) of OAC rule 3745-21-10 for CVOC,2.
 - e. the hours of operation; and
 - f. the total VOC emissions from all coatings and cleanup materials (solvent based gun cleaner) employed [(b X c) / e], in lbs/hr.

III. Monitoring and/or Record Keeping Requirements (continued)

2. The permittee shall collect and record the following information each month for the line:
 - a. the name and identification number of each coating, and cleanup material employed;
 - b. the VOC content of each coating (excluding water and exempt solvents), and cleanup material, in pounds per gallon;
 - c. the total HAP content of each coating, and cleanup material, in pounds per gallon;
 - d. the individual HAP content of each coating, and cleanup material, in pounds per gallon;
 - e. the number of gallons of each coating, and cleanup material (solvent based gun cleaner) employed;
 - f. the total VOC emissions (VOC applied) from all coatings, and cleanup materials (solvent based gun cleaner) employed [the sum of ((2.b times 2.e) divided by 2000 lb/ton) for all coatings and cleanup materials], in tons;
 - g. the rolling, 12-month summation of the VOC emissions, in tons; and
 - h. beginning after the first 12 calendar months of operation following issuance of this permit, the rolling 12-month summation of the gallons of each coating and clean-up material (solvent based gun cleaner) employed. Also, during the first 12 calendar months of operation following issuance of this permit, the permittee shall record the cumulative coating usage for each calendar month.
3. The permittee shall maintain daily records that document any time periods when the exhaust filter system was not in service when the emissions unit was in operation.
4. For each day a photochemically reactive coating and/or cleanup material is employed, the permittee shall maintain a record of the type and quantity of photochemically reactive materials employed in this emissions unit.

IV. Reporting Requirements

1. The permittee shall notify the Ohio EPA Southeast District Office in writing of any daily record showing that the coating line employs more than the applicable maximum daily coating usage limit. The notification shall include a copy of such record and shall be sent to the Ohio EPA Southeast District Office within 45 days after the exceedance occurs.
2. If this emissions unit ever employs more than 10.0 gallons of coatings on metal parts in any given day, thereafter, the permittee shall notify the Ohio EPA Southeast District Office in writing of any daily record showing that the daily volume-weighted average VOC content exceeds the applicable limitation. The notification shall include a copy of such record and shall be sent to the Ohio EPA Southeast District Office within 45 days after the exceedance occurs.
3. The permittee shall submit quarterly deviation (excursion) reports that include the following information:
 - a. an identification of each day during which the VOC emissions from all the coatings and cleanup materials (solvent-based gun cleaner) exceeded 50.0 lbs/hr, and the actual hourly average VOC emissions for each such day; and
 - b. an identification of each month during which the VOC emissions from the coatings and cleanup materials (solvent-based gun cleaner) employed in this emissions unit exceeded 20.0 tpy, as a rolling, 12-month summation, and the actual VOC emissions for each such month.
4. The permittee shall submit quarterly deviation (excursion) reports that identify all days when this emissions unit was in operation and the filter exhaust system was not in service.

IV. Reporting Requirements (continued)

5. The permittee shall submit deviation reports which identify the days during which photochemically reactive materials were employed in this emissions unit. Each report shall identify the cause for the use of the photochemically reactive material(s), and the estimated total quantity of material(s) emitted during each such day, in pounds. Each report shall be submitted to the Ohio EPA Southeast District Office within 30 days of the deviation.
6. The permittee shall submit deviation (excursion) reports that identify all exceedances of the rolling, 12-month facility-wide total HAP emission limitation and, for the first 12 calendar months of operation, all exceedances of the maximum allowable cumulative total HAP emission limitation set forth in Part II, section A.5 of this permit.
7. The permittee shall submit deviation (excursion) reports that identify all exceedances of the rolling, 12-month facility-wide individual HAP emission limitation and, for the first 12 calendar months of operation, all exceedances of the maximum allowable cumulative individual HAP emission limitation set forth in Part II, section A.5 of this permit.
8. The quarterly deviation reports shall be submitted in accordance with the requirements specified in Part I - General Term and Condition A.1.c.ii.

V. Testing Requirements

1. Compliance with the emission limitations in section A.I.1 of these terms and conditions shall be determined in accordance with the following methods:

1.a Emission Limitation:

This emissions unit shall not employ more than 10.0 gallons of coating on metal parts in any given day. If this emissions unit ever employs more than 10.0 gallons of coating on metal parts in any given day, thereafter, the VOC content of all metal parts coatings employed shall not exceed 3.5 pounds of VOC per gallon of coating, excluding water and exempt solvents, as a daily, volume-weighted average, pursuant to OAC rule 3745-21-09(U)(1)(c), and the 10.0 gallons per day limitation shall no longer be applicable.

Applicable Compliance Method:

Compliance shall be demonstrated based upon the record keeping requirements specified in section A.III.1.

1.b Emission Limitation:

50.0 lbs/hr of VOC

Applicable Compliance Method:

Compliance may be demonstrated based upon the record keeping requirements specified in sections A.III.1 and A.III.2. If required, compliance shall also be demonstrated based upon emission tests performed in accordance with the requirements specified in 40 CFR Part 60, Appendix A, Methods 1 through 4 and 25.

1.c Emission Limitation:

20.0 tpy of VOC, based on a rolling, 12-month summation

Applicable Compliance Method:

Compliance shall be demonstrated based upon the record keeping requirements specified in sections A.III.1 and A.III.2.

V. Testing Requirements (continued)

1.d Emission Limitation:

Particulate emissions shall not exceed 0.551 lb/hr.

Applicable Compliance Method:

To determine the actual worst case particulate emission rate, the following equation may be used:

$$E = (M) * (1-TE) * (1-CE)$$

where:

E = particulate matter emission rate (lbs/hr),

M = maximum coating solids usage rate (lbs/hr),

TE = transfer efficiency of coating equipment (ratio of the amount of coating solids deposited on the coated part to the amount of coating solids used),

CE = control efficiency of the control equipment. If more than one piece of control equipment is used in series, the equation should be multiplied by additional (1-CE) terms for each additional piece of equipment.

If required, the permittee shall demonstrate compliance with this emission limitation in accordance with the methods and procedures specified in OAC rule 3745-17-03(B)(10).

1.e Emission Limitation:

2.41 tpy of particulate emissions

Applicable Compliance Method:

Compliance shall be demonstrated by multiplying the allowable emission limitation for particulate emissions by the actual hours of operation per year, and then dividing by 2000 lbs/ton.

1.f Emission Limitation:

20% opacity as a 6-minute average

Applicable Compliance Method:

Compliance shall be demonstrated based upon visible particulate emission observations performed in accordance with the methods and procedures specified in 40 CFR Part 60, Appendix A, Method 9 and OAC rule 3745-17-03(B)(1).

1.g Emission Limitation:

Total facility-wide HAP emissions, combined, shall not exceed 24.9 tons per rolling, 12-month period.

Applicable Compliance Method:

Compliance shall be based on the record keeping requirements specified in section A.III.2.

1.h Emission Limitation:

Individual facility-wide HAP emissions shall not exceed 9.9 tons per rolling, 12-month period.

Applicable Compliance Method:

Compliance shall be based on the record keeping requirements specified in section A.III.2.

V. Testing Requirements (continued)

2. Formulation data shall be used to determine the VOC contents of the cleanup materials.

USEPA Method 24 shall be used to determine the VOC contents for coatings. If any such coating has not been analyzed using Method 24 since January 1, 1991, the permittee shall either conduct a Method 24 analysis of the coating or obtain a Method 24 analysis of the coating from the coating supplier within one year of the issuance of the Permit to Operate. If the permittee determines that Method 24 cannot be used for a particular coating, the permittee shall so notify the Administrator of the USEPA and shall use formulation data for that coating to demonstrate compliance until the USEPA provides alternative analytical procedures or alternative precision statements for Method 24.

VI. Miscellaneous Requirements

None

B. State Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
---	---	--

2. Additional Terms and Conditions

None

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Part III - Terms and Conditions for Emissions Units

Emissions Unit ID: Touch Up Booth #2 (K004)
Activity Description: Touch up paint on trucks

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

- The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
touch up booth #2 controlled with an exhaust filter	OAC rule 3745-31-05(A)(3) (PTI 06-4949)	Volatile organic compound (VOC) emissions shall not exceed 50.0 lbs/hr and 20.0 tpy of VOC, based upon a rolling, 12-month summation of the VOC emissions from all coatings and cleanup materials (solvent-based gun cleaner).
		Particulate emissions shall not exceed 2.41 tpy.
		The requirements of this rule also include compliance with the requirements of OAC rules 3745-17-07(A), 3745-17-11(B), and 3745-21-09(U)(2)(e)(iii).
	OAC rule 3745-17-07(A)	Visible particulate emissions shall not exceed 20% opacity as a 6-minute average, except as provided by the rule.
	OAC rule 3745-17-11(B)	Particulate emissions shall not exceed 0.551 lb/hr.
	OAC rule 3745-21-07(G)(2)	See A.II.2 below.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
	OAC rule 3745-21-09(U)(2)(e)(iii)	<p>This emissions unit shall not employ more than 10.0 gallons of coatings on metal parts in any given day.</p> <p>If this emissions unit ever employs more than 10.0 gallons of coatings on metal parts in any given day, thereafter, the VOC content of all metal parts coatings employed shall not exceed 3.5 pounds of VOC per gallon of coating, excluding water and exempt solvents, as a daily, volume-weighted average, pursuant to OAC rule 3745-21-09(U)(1)(c), and the 10.0 gallons per day limitation shall no longer be applicable.</p>

2. Additional Terms and Conditions

- 2.a** Total facility-wide Hazardous Air Pollutant (HAP) emissions, combined, shall not exceed 24.9 tons per rolling, 12-month period.

Individual facility-wide HAP emissions shall not exceed 9.9 tons per rolling, 12-month period.

- 2.b** For the requirements of this emissions unit, "cleanup materials" shall refer only to solvent-based gun cleaner. Requirements for cleanup materials other than solvent-based gun cleaner (i.e., water-based gun cleaner, wipe solvent) are addressed in Part II.

II. Operational Restrictions

1. The permittee shall employ the exhaust filter system for the control of particulate emissions when this emissions unit is in operation.
2. The permittee shall not employ any photochemically reactive materials, as defined in OAC rule 3745-21-01(C)(5), in this emissions unit.

III. Monitoring and/or Record Keeping Requirements

1. The permittee shall collect and record the following information each day for this emissions unit:
 - a. the name and identification number of each coating and cleanup material employed;
 - b. the VOC content of each coating (excluding water and exempt solvents), and cleanup material, in pounds per gallon;
 - c. the number of gallons of each coating, and cleanup material (solvent based gun cleaner) employed;
 - d. the daily volume-weighted average VOC content of all coatings, as applied, calculated in accordance with the equation specified in paragraph (B)(9) of OAC rule 3745-21-10 for CVOC,2.
 - e. the hours of operation; and
 - f. the total VOC emissions from all coatings and cleanup materials (solvent based gun cleaner) employed [(b X c) / e], in lbs/hr.

III. Monitoring and/or Record Keeping Requirements (continued)

2. The permittee shall collect and record the following information each month for the line:
 - a. the name and identification number of each coating, and cleanup material employed;
 - b. the VOC content of each coating (excluding water and exempt solvents), and cleanup material, in pounds per gallon;
 - c. the total HAP content of each coating, and cleanup material, in pounds per gallon;
 - d. the individual HAP content of each coating, and cleanup material, in pounds per gallon;
 - e. the number of gallons of each coating, and cleanup material (solvent based gun cleaner) employed;
 - f. the total VOC emissions (VOC applied) from all coatings, and cleanup materials (solvent based gun cleaner) employed [the sum of ((2.b times 2.e) divided by 2000 lb/ton) for all coatings and cleanup materials], in tons;
 - g. the rolling, 12-month summation of the VOC emissions, in tons; and
 - h. beginning after the first 12 calendar months of operation following issuance of this permit, the rolling 12-month summation of the gallons of each coating and clean-up material (solvent based gun cleaner) employed. Also, during the first 12 calendar months of operation following issuance of this permit, the permittee shall record the cumulative coating usage for each calendar month.
3. The permittee shall maintain daily records that document any time periods when the exhaust filter system was not in service when the emissions unit was in operation.
4. For each day a photochemically reactive coating and/or cleanup material is employed, the permittee shall maintain a record of the type and quantity of photochemically reactive materials employed in this emissions unit.

IV. Reporting Requirements

1. The permittee shall notify the Ohio EPA Southeast District Office in writing of any daily record showing that the coating line employs more than the applicable maximum daily coating usage limit. The notification shall include a copy of such record and shall be sent to the Ohio EPA Southeast District Office within 45 days after the exceedance occurs.
2. If this emissions unit ever employs more than 10.0 gallons of coatings on metal parts in any given day, thereafter, the permittee shall notify the Ohio EPA Southeast District Office in writing of any daily record showing that the daily volume-weighted average VOC content exceeds the applicable limitation. The notification shall include a copy of such record and shall be sent to the Ohio EPA Southeast District Office within 45 days after the exceedance occurs.
3. The permittee shall submit quarterly deviation (excursion) reports that include the following information:
 - a. an identification of each day during which the VOC emissions from all the coatings and cleanup materials (solvent-based gun cleaner) exceeded 50.0 lbs/hr, and the actual hourly average VOC emissions for each such day; and
 - b. an identification of each month during which the VOC emissions from the coatings and cleanup materials (solvent-based gun cleaner) employed in this emissions unit exceeded 20.0 tpy, as a rolling, 12-month summation, and the actual VOC emissions for each such month.
4. The permittee shall submit quarterly deviation (excursion) reports that identify all days when this emissions unit was in operation and the filter exhaust system was not in service.

IV. Reporting Requirements (continued)

5. The permittee shall submit deviation reports which identify the days during which photochemically reactive materials were employed in this emissions unit. Each report shall identify the cause for the use of the photochemically reactive material(s), and the estimated total quantity of material(s) emitted during each such day, in pounds. Each report shall be submitted to the Ohio EPA Southeast District Office within 30 days of the deviation.
6. The permittee shall submit deviation (excursion) reports that identify all exceedances of the rolling, 12-month facility-wide total HAP emission limitation and, for the first 12 calendar months of operation, all exceedances of the maximum allowable cumulative total HAP emission limitation set forth in Part II, section A.5 of this permit.
7. The permittee shall submit deviation (excursion) reports that identify all exceedances of the rolling, 12-month facility-wide individual HAP emission limitation and, for the first 12 calendar months of operation, all exceedances of the maximum allowable cumulative individual HAP emission limitation set forth in Part II, section A.5 of this permit.
8. The quarterly deviation reports shall be submitted in accordance with the requirements specified in Part I - General Term and Condition A.1.c.ii.

V. Testing Requirements

1. Compliance with the emission limitations in section A.I.1 of these terms and conditions shall be determined in accordance with the following methods:

1.a Emission Limitation:

This emissions unit shall not employ more than 10.0 gallons of coating on metal parts in any given day. If this emissions unit ever employs more than 10.0 gallons of coating on metal parts in any given day, thereafter, the VOC content of all metal parts coatings employed shall not exceed 3.5 pounds of VOC per gallon of coating, excluding water and exempt solvents, as a daily, volume-weighted average, pursuant to OAC rule 3745-21-09(U)(1)(c), and the 10.0 gallons per day limitation shall no longer be applicable.

Applicable Compliance Method:

Compliance shall be demonstrated based upon the record keeping requirements specified in section A.III.1.

1.b Emission Limitation:

50.0 lbs/hr of VOC

Applicable Compliance Method:

Compliance may be demonstrated based upon the record keeping requirements specified in sections A.III.1 and A.III.2. If required, compliance shall also be demonstrated based upon emission tests performed in accordance with the requirements specified in 40 CFR Part 60, Appendix A, Methods 1 through 4 and 25.

1.c Emission Limitation:

20.0 tpy of VOC, based on a rolling, 12-month summation

Applicable Compliance Method:

Compliance shall be demonstrated based upon the record keeping requirements specified in sections A.III.1 and A.III.2.

V. Testing Requirements (continued)

1.d Emission Limitation:

Particulate emissions shall not exceed 0.551 lb/hr.

Applicable Compliance Method:

To determine the actual worst case particulate emission rate, the following equation may be used:

$$E = (M) * (1-TE) * (1-CE)$$

where:

E = particulate matter emission rate (lbs/hr),

M = maximum coating solids usage rate (lbs/hr),

TE = transfer efficiency of coating equipment (ratio of the amount of coating solids deposited on the coated part to the amount of coating solids used),

CE = control efficiency of the control equipment. If more than one piece of control equipment is used in series, the equation should be multiplied by additional (1-CE) terms for each additional piece of equipment.

If required, the permittee shall demonstrate compliance with this emission limitation in accordance with the methods and procedures specified in OAC rule 3745-17-03(B)(10).

1.e Emission Limitation:

2.41 tpy of particulate emissions

Applicable Compliance Method:

Compliance shall be demonstrated by multiplying the allowable emission limitation for particulate emissions by the actual hours of operation per year, and then dividing by 2000 lbs/ton.

1.f Emission Limitation:

20% opacity as a 6-minute average

Applicable Compliance Method:

Compliance shall be demonstrated based upon visible particulate emission observations performed in accordance with the methods and procedures specified in 40 CFR Part 60, Appendix A, Method 9 and OAC rule 3745-17-03(B)(1).

1.g Emission Limitation:

Total facility-wide HAP emissions, combined, shall not exceed 24.9 tons per rolling, 12-month period.

Applicable Compliance Method:

Compliance shall be based on the record keeping requirements specified in section A.III.2.

1.h Emission Limitation:

Individual facility-wide HAP emissions shall not exceed 9.9 tons per rolling, 12-month period.

Applicable Compliance Method:

Compliance shall be based on the record keeping requirements specified in section A.III.2.

V. Testing Requirements (continued)

2. Formulation data shall be used to determine the VOC contents of the cleanup materials.

USEPA Method 24 shall be used to determine the VOC contents for coatings. If any such coating has not been analyzed using Method 24 since January 1, 1991, the permittee shall either conduct a Method 24 analysis of the coating or obtain a Method 24 analysis of the coating from the coating supplier within one year of the issuance of the Permit to Operate. If the permittee determines that Method 24 cannot be used for a particular coating, the permittee shall so notify the Administrator of the USEPA and shall use formulation data for that coating to demonstrate compliance until the USEPA provides alternative analytical procedures or alternative precision statements for Method 24.

VI. Miscellaneous Requirements

None

B. State Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
---	---	--

2. Additional Terms and Conditions

None

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Part III - Terms and Conditions for Emissions Units

Emissions Unit ID: Cab Booth #1 (K005)
Activity Description: Paint truck cabs

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

- The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
cab booth #1 controlled with a water wash system	OAC rule 3745-31-05(A)(3) (PTI 06-4949)	Volatile organic compound (VOC) emissions shall not exceed 200.0 lbs/hr and 80.0 tpy of VOC, based upon a rolling, 12-month summation of the VOC emissions from all coatings and cleanup materials (solvent-based gun cleaner).
		Particulate emissions shall not exceed 11.3 tpy.
		The requirements of this rule also include compliance with the requirements of OAC rules 3745-17-07(A), 3745-17-11(B), and 3745-21-09(U)(1)(c).
	OAC rule 3745-17-07(A)	Visible particulate emissions shall not exceed 20% opacity as a 6-minute average, except as provided by the rule.
	OAC rule 3745-17-11(B)	Particulate emissions shall not exceed 2.58 lbs/hr.
	OAC rule 3745-21-07(G)(2)	See A.II.2 below.
	OAC rule 3745-21-09(U)(1)(c)	The VOC contents of the coatings employed shall not exceed the following:
		3.5 pounds of VOC per gallon of coating, excluding water and exempt solvents, for an extreme performance coating (daily volume-weighted average)

2. Additional Terms and Conditions

2.a Total facility-wide Hazardous Air Pollutant (HAP) emissions, combined, shall not exceed 24.9 tons per rolling, 12-month period.

Individual facility-wide HAP emissions shall not exceed 9.9 tons per rolling, 12-month period.

2.b For the requirements of this emissions unit, "cleanup materials" shall refer only to solvent-based gun cleaner. Requirements for cleanup materials other than solvent-based gun cleaner (i.e., water-based gun cleaner, wipe solvent) are addressed in Part II.

II. Operational Restrictions

1. The permittee shall operate the water wash system for the control of particulate emissions when this emissions unit is in operation.
2. The permittee shall not employ any photochemically reactive materials, as defined in OAC rule 3745-21-01(C)(5), in this emissions unit.

III. Monitoring and/or Record Keeping Requirements

1. The permittee shall collect and record the following information each day for this emissions unit:
 - a. the name and identification number of each coating and cleanup material employed;
 - b. the VOC content of each coating (excluding water and exempt solvents), and cleanup material, in pounds per gallon;
 - c. the number of gallons of each coating, and cleanup material (solvent based gun cleaner) employed;
 - d. the daily volume-weighted average VOC content of all coatings, as applied, calculated in accordance with the equation specified in paragraph (B)(9) of OAC rule 3745-21-10 for CVOC,2.
 - e. the hours of operation; and
 - f. the total VOC emissions from all coatings and cleanup materials (solvent based gun cleaner) employed $[(b \times c) / e]$, in lbs/hr.
2. The permittee shall collect and record the following information each month for the line:
 - a. the name and identification number of each coating, and cleanup material employed;
 - b. the VOC content of each coating (excluding water and exempt solvents), and cleanup material, in pounds per gallon;
 - c. the total HAP content of each coating, and cleanup material, in pounds per gallon;
 - d. the individual HAP content of each coating, and cleanup material, in pounds per gallon;
 - e. the number of gallons of each coating, and cleanup material (solvent based gun cleaner) employed;
 - f. the total VOC emissions (VOC applied) from all coatings, and cleanup materials (solvent based gun cleaner) employed [the sum of ((2.b times 2.e) divided by 2000 lb/ton) for all coatings and cleanup materials], in tons;
 - g. the rolling, 12-month summation of the VOC emissions, in tons; and
 - h. beginning after the first 12 calendar months of operation following issuance of this permit, the rolling 12-month summation of the gallons of each coating and clean-up material (solvent based gun cleaner) employed. Also, during the first 12 calendar months of operation following issuance of this permit, the permittee shall record the cumulative coating usage for each calendar month.

III. Monitoring and/or Record Keeping Requirements (continued)

3. The permittee shall maintain daily records that document any time periods when the water wash system was not in service when the emissions unit was in operation.
4. For each day a photochemically reactive coating and/or cleanup material is employed, the permittee shall maintain a record of the type and quantity of photochemically reactive materials employed in this emissions unit.

IV. Reporting Requirements

1. The permittee shall notify the Ohio EPA Southeast District Office in writing of any daily record showing that the daily volume-weighted average VOC content exceeds the applicable limitation. The notification shall include a copy of such record and shall be sent to the Ohio EPA Southeast District Office within 45 days after the exceedance occurs.
2. The permittee shall submit quarterly deviation (excursion) reports that include the following information:
 - a. an identification of each day during which the VOC emissions from all the coatings and cleanup materials (solvent-based gun cleaner) exceeded 200.0 lbs/hr, and the actual hourly average VOC emissions for each such day; and
 - b. an identification of each month during which the VOC emissions from the coatings and cleanup materials (solvent-based gun cleaner) employed in this emissions unit exceeded 80.0 tpy, as a rolling, 12-month summation, and the actual VOC emissions for each such month.
3. The permittee shall submit quarterly deviation (excursion) reports that identify all days when this emissions unit was in operation and the water wash system was not in service.
4. The permittee shall submit deviation reports which identify the days during which photochemically reactive materials were employed in this emissions unit. Each report shall identify the cause for the use of the photochemically reactive material(s), and the estimated total quantity of material(s) emitted during each such day, in pounds. Each report shall be submitted to the Ohio EPA Southeast District Office within 30 days of the deviation.
5. The permittee shall submit deviation (excursion) reports that identify all exceedances of the rolling, 12-month facility-wide total HAP emission limitation and, for the first 12 calendar months of operation, all exceedances of the maximum allowable cumulative total HAP emission limitation set forth in Part II, section A.5 of this permit.
6. The permittee shall submit deviation (excursion) reports that identify all exceedances of the rolling, 12-month facility-wide individual HAP emission limitation and, for the first 12 calendar months of operation, all exceedances of the maximum allowable cumulative individual HAP emission limitation set forth in Part II, section A.5 of this permit.
7. The quarterly deviation reports shall be submitted in accordance with the requirements specified in Part I - General Term and Condition A.1.c.ii.

V. Testing Requirements

1. Compliance with the emission limitations in section A.I.1 of these terms and conditions shall be determined in accordance with the following methods:
 - 1.a Emission Limitation:

3.5 pounds of VOC per gallon of coating, excluding water and exempt solvents (daily volume-weighted average), for an extreme performance coating

Applicable Compliance Method:

Compliance shall be demonstrated based upon the record keeping requirements specified in section A.III.1.

V. Testing Requirements (continued)

1.b Emission Limitation:

200.0 lbs/hr of VOC

Applicable Compliance Method:

Compliance may be demonstrated based upon the record keeping requirements specified in sections A.III.1 and A.III.2. If required, compliance shall also be demonstrated based upon emission tests performed in accordance with the requirements specified in 40 CFR Part 60, Appendix A, Methods 1 through 4 and 25.

1.c Emission Limitation:

80.0 tpy of VOC, based on a rolling, 12-month summation

Applicable Compliance Method:

Compliance shall be demonstrated based upon the record keeping requirements specified in sections A.III.1 and A.III.2.

1.d Emission Limitation:

2.58 lbs/hr of particulate emissions

Applicable Compliance Method:

Compliance may be demonstrated by multiplying the particulate emission factor of 244.4 lbs/hr of solids by the control efficiency of (1 - 0.99). This emission factor was established from company data to determine an emission rate for particulates from spray booths at this facility. If required, the permittee shall demonstrate compliance with this emission limitation in accordance with the methods and procedures specified in OAC rule 3745-17-03(B)(10).

1.e Emission Limitation:

11.3 tpy of particulate emissions

Applicable Compliance Method:

Compliance shall be demonstrated by multiplying the allowable emission limitation for particulate emissions by the actual hours of operation per year, and then dividing by 2000 lbs/ton.

1.f Emission Limitation:

20% opacity as a 6-minute average

Applicable Compliance Method:

Compliance shall be demonstrated based upon visible particulate emission observations performed in accordance with the methods and procedures specified in 40 CFR Part 60, Appendix A, Method 9 and OAC rule 3745-17-03(B)(1).

1.g Emission Limitation:

Total facility-wide HAP emissions, combined, shall not exceed 24.9 tons per rolling, 12-month period.

Applicable Compliance Method:

Compliance shall be based on the record keeping requirements specified in section A.III.2.

V. Testing Requirements (continued)

1.h Emission Limitation:

Individual facility-wide HAP emissions shall not exceed 9.9 tons per rolling, 12-month period.

Applicable Compliance Method:

Compliance shall be based on the record keeping requirements specified in section A.III.2.

2. Formulation data shall be used to determine the VOC contents of the cleanup materials.

USEPA Method 24 shall be used to determine the VOC contents for coatings. If any such coating has not been analyzed using Method 24 since January 1, 1991, the permittee shall either conduct a Method 24 analysis of the coating or obtain a Method 24 analysis of the coating from the coating supplier within one year of the issuance of the Permit to Operate. If the permittee determines that Method 24 cannot be used for a particular coating, the permittee shall so notify the Administrator of the USEPA and shall use formulation data for that coating to demonstrate compliance until the USEPA provides alternative analytical procedures or alternative precision statements for Method 24.

VI. Miscellaneous Requirements

None

B. State Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
---	---	--

2. Additional Terms and Conditions

None

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Part III - Terms and Conditions for Emissions Units

Emissions Unit ID: Cab Booth #2 (K006)
Activity Description: Paint truck cabs

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

- The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
cab booth #2 controlled with a water wash system	OAC rule 3745-31-05(A)(3) (PTI 06-4949)	<p>Volatile organic compound (VOC) emissions shall not exceed 200.0 lbs/hr and 80.0 tpy of VOC, based upon a rolling, 12-month summation of the VOC emissions from all coatings and cleanup materials (solvent-based gun cleaner).</p> <p>Particulate emissions shall not exceed 11.3 tpy.</p> <p>The requirements of this rule also include compliance with the requirements of OAC rules 3745-17-07(A), 3745-17-11(B), and 3745-21-09(U)(1)(c).</p>
	OAC rule 3745-17-07(A)	Visible particulate emissions shall not exceed 20% opacity as a 6-minute average, except as provided by the rule.
	OAC rule 3745-17-11(B)	Particulate emissions shall not exceed 2.58 lbs/hr.
	OAC rule 3745-21-07(G)(2)	See A.II.2 below.
	OAC rule 3745-21-09(U)(1)(c)	<p>The VOC contents of the coatings employed shall not exceed the following:</p> <p>3.5 pounds of VOC per gallon of coating, excluding water and exempt solvents, for an extreme performance coating (daily volume-weighted average)</p>

2. Additional Terms and Conditions

- 2.a** Total facility-wide Hazardous Air Pollutant (HAP) emissions, combined, shall not exceed 24.9 tons per rolling, 12-month period.

Individual facility-wide HAP emissions shall not exceed 9.9 tons per rolling, 12-month period.

- 2.b** For the requirements of this emissions unit, "cleanup materials" shall refer only to solvent-based gun cleaner. Requirements for cleanup materials other than solvent-based gun cleaner (i.e., water-based gun cleaner, wipe solvent) are addressed in Part II.

II. Operational Restrictions

1. The permittee shall operate the water wash system for the control of particulate emissions when this emissions unit is in operation.
2. The permittee shall not employ any photochemically reactive materials, as defined in OAC rule 3745-21-01(C)(5), in this emissions unit.

III. Monitoring and/or Record Keeping Requirements

1. The permittee shall collect and record the following information each day for this emissions unit:
 - a. the name and identification number of each coating and cleanup material employed;
 - b. the VOC content of each coating (excluding water and exempt solvents), and cleanup material, in pounds per gallon;
 - c. the number of gallons of each coating, and cleanup material (solvent based gun cleaner) employed;
 - d. the daily volume-weighted average VOC content of all coatings, as applied, calculated in accordance with the equation specified in paragraph (B)(9) of OAC rule 3745-21-10 for CVOC,2.
 - e. the hours of operation; and
 - f. the total VOC emissions from all coatings and cleanup materials (solvent based gun cleaner) employed $[(b \times c) / e]$, in lbs/hr.
2. The permittee shall collect and record the following information each month for the line:
 - a. the name and identification number of each coating, and cleanup material employed;
 - b. the VOC content of each coating (excluding water and exempt solvents), and cleanup material, in pounds per gallon;
 - c. the total HAP content of each coating, and cleanup material, in pounds per gallon;
 - d. the individual HAP content of each coating, and cleanup material, in pounds per gallon;
 - e. the number of gallons of each coating, and cleanup material (solvent based gun cleaner) employed;
 - f. the total VOC emissions (VOC applied) from all coatings, and cleanup materials (solvent based gun cleaner) employed [the sum of ((2.b times 2.e) divided by 2000 lb/ton) for all coatings and cleanup materials], in tons;
 - g. the rolling, 12-month summation of the VOC emissions, in tons; and
 - h. beginning after the first 12 calendar months of operation following issuance of this permit, the rolling 12-month summation of the gallons of each coating and clean-up material (solvent based gun cleaner) employed. Also, during the first 12 calendar months of operation following issuance of this permit, the permittee shall record the cumulative coating usage for each calendar month.

III. Monitoring and/or Record Keeping Requirements (continued)

3. The permittee shall maintain daily records that document any time periods when the water wash system was not in service when the emissions unit was in operation.
4. For each day a photochemically reactive coating and/or cleanup material is employed, the permittee shall maintain a record of the type and quantity of photochemically reactive materials employed in this emissions unit.

IV. Reporting Requirements

1. The permittee shall notify the Ohio EPA Southeast District Office in writing of any daily record showing that the daily volume-weighted average VOC content exceeds the applicable limitation. The notification shall include a copy of such record and shall be sent to the Ohio EPA Southeast District Office within 45 days after the exceedance occurs.
2. The permittee shall submit quarterly deviation (excursion) reports that include the following information:
 - a. an identification of each day during which the VOC emissions from all the coatings and cleanup materials (solvent-based gun cleaner) exceeded 200.0 lbs/hr, and the actual hourly average VOC emissions for each such day; and
 - b. an identification of each month during which the VOC emissions from the coatings and cleanup materials (solvent-based gun cleaner) employed in this emissions unit exceeded 80.0 tpy, as a rolling, 12-month summation, and the actual VOC emissions for each such month.
3. The permittee shall submit quarterly deviation (excursion) reports that identify all days when this emissions unit was in operation and the water wash system was not in service.
4. The permittee shall submit deviation reports which identify the days during which photochemically reactive materials were employed in this emissions unit. Each report shall identify the cause for the use of the photochemically reactive material(s), and the estimated total quantity of material(s) emitted during each such day, in pounds. Each report shall be submitted to the Ohio EPA Southeast District Office within 30 days of the deviation.
5. The permittee shall submit deviation (excursion) reports that identify all exceedances of the rolling, 12-month facility-wide total HAP emission limitation and, for the first 12 calendar months of operation, all exceedances of the maximum allowable cumulative total HAP emission limitation set forth in Part II, section A.5 of this permit.
6. The permittee shall submit deviation (excursion) reports that identify all exceedances of the rolling, 12-month facility-wide individual HAP emission limitation and, for the first 12 calendar months of operation, all exceedances of the maximum allowable cumulative individual HAP emission limitation set forth in Part II, section A.5 of this permit.
7. The quarterly deviation reports shall be submitted in accordance with the requirements specified in Part I - General Term and Condition A.1.c.ii.

V. Testing Requirements

1. Compliance with the emission limitations in section A.I.1 of these terms and conditions shall be determined in accordance with the following methods:

1.a Emission Limitation:

3.5 pounds of VOC per gallon of coating, excluding water and exempt solvents (daily volume-weighted average), for an extreme performance coating

Applicable Compliance Method:

Compliance shall be demonstrated based upon the record keeping requirements specified in section A.III.1.

V. Testing Requirements (continued)

1.b Emission Limitation:

200.0 lbs/hr of VOC

Applicable Compliance Method:

Compliance may be demonstrated based upon the record keeping requirements specified in sections A.III.1 and A.III.2. If required, compliance shall also be demonstrated based upon emission tests performed in accordance with the requirements specified in 40 CFR Part 60, Appendix A, Methods 1 through 4 and 25.

1.c Emission Limitation:

80.0 tpy of VOC, based on a rolling, 12-month summation

Applicable Compliance Method:

Compliance shall be demonstrated based upon the record keeping requirements specified in sections A.III.1 and A.III.2.

1.d Emission Limitation:

2.58 lbs/hr of particulate emissions

Applicable Compliance Method:

Compliance may be demonstrated by multiplying the particulate emission factor of 244.4 lbs/hr of solids by the control efficiency of (1 - 0.99). This emission factor was established from company data to determine an emission rate for particulates from spray booths at this facility. If required, the permittee shall demonstrate compliance with this emission limitation in accordance with the methods and procedures specified in OAC rule 3745-17-03(B)(10).

1.e Emission Limitation:

11.3 tpy of particulate emissions

Applicable Compliance Method:

Compliance shall be demonstrated by multiplying the allowable emission limitation for particulate emissions by the actual hours of operation per year, and then dividing by 2000 lbs/ton.

1.f Emission Limitation:

20% opacity as a 6-minute average

Applicable Compliance Method:

Compliance shall be demonstrated based upon visible particulate emission observations performed in accordance with the methods and procedures specified in 40 CFR Part 60, Appendix A, Method 9 and OAC rule 3745-17-03(B)(1).

1.g Emission Limitation:

Total facility-wide HAP emissions, combined, shall not exceed 24.9 tons per rolling, 12-month period.

Applicable Compliance Method:

Compliance shall be based on the record keeping requirements specified in section A.III.2.

V. Testing Requirements (continued)

1.h Emission Limitation:

Individual facility-wide HAP emissions shall not exceed 9.9 tons per rolling, 12-month period.

Applicable Compliance Method:

Compliance shall be based on the record keeping requirements specified in section A.III.2.

2. Formulation data shall be used to determine the VOC contents of the cleanup materials.

USEPA Method 24 shall be used to determine the VOC contents for coatings. If any such coating has not been analyzed using Method 24 since January 1, 1991, the permittee shall either conduct a Method 24 analysis of the coating or obtain a Method 24 analysis of the coating from the coating supplier within one year of the issuance of the Permit to Operate. If the permittee determines that Method 24 cannot be used for a particular coating, the permittee shall so notify the Administrator of the USEPA and shall use formulation data for that coating to demonstrate compliance until the USEPA provides alternative analytical procedures or alternative precision statements for Method 24.

VI. Miscellaneous Requirements

None

B. State Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
---	---	--

2. Additional Terms and Conditions

None

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Part III - Terms and Conditions for Emissions Units

Emissions Unit ID: Cab Booth #3 (K007)
Activity Description: Paint truck cabs

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

- The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
cab booth #3 controlled with a water wash system	OAC rule 3745-31-05(A)(3) (PTI 06-4949)	Volatile organic compound (VOC) emissions shall not exceed 200.0 lbs/hr and 80.0 tpy of VOC, based upon a rolling, 12-month summation of the VOC emissions from all coatings and cleanup materials (solvent-based gun cleaner).
		Particulate emissions shall not exceed 11.3 tpy.
		The requirements of this rule also include compliance with the requirements of OAC rules 3745-17-07(A), 3745-17-11(B), and 3745-21-09(U)(1)(c).
	OAC rule 3745-17-07(A)	Visible particulate emissions shall not exceed 20% opacity as a 6-minute average, except as provided by the rule.
	OAC rule 3745-17-11(B)	Particulate emissions shall not exceed 2.58 lbs/hr.
	OAC rule 3745-21-07(G)(2)	See A.II.2 below.
	OAC rule 3745-21-09(U)(1)(c)	The VOC contents of the coatings employed shall not exceed the following:
		3.5 pounds of VOC per gallon of coating, excluding water and exempt solvents, for an extreme performance coating (daily volume-weighted average)

2. Additional Terms and Conditions

- 2.a** Total facility-wide Hazardous Air Pollutant (HAP) emissions, combined, shall not exceed 24.9 tons per rolling, 12-month period.

Individual facility-wide HAP emissions shall not exceed 9.9 tons per rolling, 12-month period.

- 2.b** For the requirements of this emissions unit, "cleanup materials" shall refer only to solvent-based gun cleaner. Requirements for cleanup materials other than solvent-based gun cleaner (i.e., water-based gun cleaner, wipe solvent) are addressed in Part II.

II. Operational Restrictions

1. The permittee shall operate the water wash system for the control of particulate emissions when this emissions unit is in operation.
2. The permittee shall not employ any photochemically reactive materials, as defined in OAC rule 3745-21-01(C)(5), in this emissions unit.

III. Monitoring and/or Record Keeping Requirements

1. The permittee shall collect and record the following information each day for this emissions unit:
 - a. the name and identification number of each coating and cleanup material employed;
 - b. the VOC content of each coating (excluding water and exempt solvents), and cleanup material, in pounds per gallon;
 - c. the number of gallons of each coating, and cleanup material (solvent based gun cleaner) employed;
 - d. the daily volume-weighted average VOC content of all coatings, as applied, calculated in accordance with the equation specified in paragraph (B)(9) of OAC rule 3745-21-10 for CVOC,2.
 - e. the hours of operation; and
 - f. the total VOC emissions from all coatings and cleanup materials (solvent based gun cleaner) employed $[(b \times c) / e]$, in lbs/hr.
2. The permittee shall collect and record the following information each month for the line:
 - a. the name and identification number of each coating, and cleanup material employed;
 - b. the VOC content of each coating (excluding water and exempt solvents), and cleanup material, in pounds per gallon;
 - c. the total HAP content of each coating, and cleanup material, in pounds per gallon;
 - d. the individual HAP content of each coating, and cleanup material, in pounds per gallon;
 - e. the number of gallons of each coating, and cleanup material (solvent based gun cleaner) employed;
 - f. the total VOC emissions (VOC applied) from all coatings, and cleanup materials (solvent based gun cleaner) employed [the sum of ((2.b times 2.e) divided by 2000 lb/ton) for all coatings and cleanup materials], in tons;
 - g. the rolling, 12-month summation of the VOC emissions, in tons; and
 - h. beginning after the first 12 calendar months of operation following issuance of this permit, the rolling 12-month summation of the gallons of each coating and clean-up material (solvent based gun cleaner) employed. Also, during the first 12 calendar months of operation following issuance of this permit, the permittee shall record the cumulative coating usage for each calendar month.

III. Monitoring and/or Record Keeping Requirements (continued)

3. The permittee shall maintain daily records that document any time periods when the water wash system was not in service when the emissions unit was in operation.
4. For each day a photochemically reactive coating and/or cleanup material is employed, the permittee shall maintain a record of the type and quantity of photochemically reactive materials employed in this emissions unit.

IV. Reporting Requirements

1. The permittee shall notify the Ohio EPA Southeast District Office in writing of any daily record showing that the daily volume-weighted average VOC content exceeds the applicable limitation. The notification shall include a copy of such record and shall be sent to the Ohio EPA Southeast District Office within 45 days after the exceedance occurs.
2. The permittee shall submit quarterly deviation (excursion) reports that include the following information:
 - a. an identification of each day during which the VOC emissions from all the coatings and cleanup materials (solvent-based gun cleaner) exceeded 200.0 lbs/hr, and the actual hourly average VOC emissions for each such day; and
 - b. an identification of each month during which the VOC emissions from the coatings and cleanup materials (solvent-based gun cleaner) employed in this emissions unit exceeded 80.0 tpy, as a rolling, 12-month summation, and the actual VOC emissions for each such month.
3. The permittee shall submit quarterly deviation (excursion) reports that identify all days when this emissions unit was in operation and the water wash system was not in service.
4. The permittee shall submit deviation reports which identify the days during which photochemically reactive materials were employed in this emissions unit. Each report shall identify the cause for the use of the photochemically reactive material(s), and the estimated total quantity of material(s) emitted during each such day, in pounds. Each report shall be submitted to the Ohio EPA Southeast District Office within 30 days of the deviation.
5. The permittee shall submit deviation (excursion) reports that identify all exceedances of the rolling, 12-month facility-wide total HAP emission limitation and, for the first 12 calendar months of operation, all exceedances of the maximum allowable cumulative total HAP emission limitation set forth in Part II, section A.5 of this permit.
6. The permittee shall submit deviation (excursion) reports that identify all exceedances of the rolling, 12-month facility-wide individual HAP emission limitation and, for the first 12 calendar months of operation, all exceedances of the maximum allowable cumulative individual HAP emission limitation set forth in Part II, section A.5 of this permit.
7. The quarterly deviation reports shall be submitted in accordance with the requirements specified in Part I - General Term and Condition A.1.c.ii.

V. Testing Requirements

1. Compliance with the emission limitations in section A.I.1 of these terms and conditions shall be determined in accordance with the following methods:
 - 1.a Emission Limitation:

3.5 pounds of VOC per gallon of coating, excluding water and exempt solvents (daily volume-weighted average), for an extreme performance coating

Applicable Compliance Method:

Compliance shall be demonstrated based upon the record keeping requirements specified in section A.III.1.

V. Testing Requirements (continued)

1.b Emission Limitation:

200.0 lbs/hr of VOC

Applicable Compliance Method:

Compliance may be demonstrated based upon the record keeping requirements specified in sections A.III.1 and A.III.2. If required, compliance shall also be demonstrated based upon emission tests performed in accordance with the requirements specified in 40 CFR Part 60, Appendix A, Methods 1 through 4 and 25.

1.c Emission Limitation:

80.0 tpy of VOC, based on a rolling, 12-month summation

Applicable Compliance Method:

Compliance shall be demonstrated based upon the record keeping requirements specified in sections A.III.1 and A.III.2.

1.d Emission Limitation:

2.58 lbs/hr of particulate emissions

Applicable Compliance Method:

Compliance may be demonstrated by multiplying the particulate emission factor of 244.4 lbs/hr of solids by the control efficiency of (1 - 0.99). This emission factor was established from company data to determine an emission rate for particulates from spray booths at this facility. If required, the permittee shall demonstrate compliance with this emission limitation in accordance with the methods and procedures specified in OAC rule 3745-17-03(B)(10).

1.e Emission Limitation:

11.3 tpy of particulate emissions

Applicable Compliance Method:

Compliance shall be demonstrated by multiplying the allowable emission limitation for particulate emissions by the actual hours of operation per year, and then dividing by 2000 lbs/ton.

1.f Emission Limitation:

20% opacity as a 6-minute average

Applicable Compliance Method:

Compliance shall be demonstrated based upon visible particulate emission observations performed in accordance with the methods and procedures specified in 40 CFR Part 60, Appendix A, Method 9 and OAC rule 3745-17-03(B)(1).

1.g Emission Limitation:

Total facility-wide HAP emissions, combined, shall not exceed 24.9 tons per rolling, 12-month period.

Applicable Compliance Method:

Compliance shall be based on the record keeping requirements specified in section A.III.2.

V. Testing Requirements (continued)

1.h Emission Limitation:

Individual facility-wide HAP emissions shall not exceed 9.9 tons per rolling, 12-month period.

Applicable Compliance Method:

Compliance shall be based on the record keeping requirements specified in section A.III.2.

2. Formulation data shall be used to determine the VOC contents of the cleanup materials.

USEPA Method 24 shall be used to determine the VOC contents for coatings. If any such coating has not been analyzed using Method 24 since January 1, 1991, the permittee shall either conduct a Method 24 analysis of the coating or obtain a Method 24 analysis of the coating from the coating supplier within one year of the issuance of the Permit to Operate. If the permittee determines that Method 24 cannot be used for a particular coating, the permittee shall so notify the Administrator of the USEPA and shall use formulation data for that coating to demonstrate compliance until the USEPA provides alternative analytical procedures or alternative precision statements for Method 24.

VI. Miscellaneous Requirements

None

B. State Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
---	---	--

2. Additional Terms and Conditions

None

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Part III - Terms and Conditions for Emissions Units

Emissions Unit ID: Cab Booth #4 (K016)
Activity Description: Paint truck cabs

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

- The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
cab booth #4 controlled with a water wash system	OAC rule 3745-31-05(A)(3) (PTI 06-4949)	<p>Volatile organic compound (VOC) emissions shall not exceed 200.0 lbs/hr and 80.0 tpy of VOC, based upon a rolling, 12-month summation of the VOC emissions from all coatings and cleanup materials (solvent-based gun cleaner).</p> <p>Particulate emissions shall not exceed 11.3 tpy.</p> <p>The requirements of this rule also include compliance with the requirements of OAC rules 3745-17-07(A), 3745-17-11(B), and 3745-21-09(U)(1)(c).</p>
	OAC rule 3745-17-07(A)	Visible particulate emissions shall not exceed 20% opacity as a 6-minute average, except as provided by the rule.
	OAC rule 3745-17-11(B)	Particulate emissions shall not exceed 2.58 lbs/hr.
	OAC rule 3745-21-07(G)(2)	See A.II.2 below.
	OAC rule 3745-21-09(U)(1)(c)	<p>The VOC contents of the coatings employed shall not exceed the following:</p> <p>3.5 pounds of VOC per gallon of coating, excluding water and exempt solvents, for an extreme performance coating (daily volume-weighted average)</p>

2. Additional Terms and Conditions

- 2.a** Total facility-wide Hazardous Air Pollutant (HAP) emissions, combined, shall not exceed 24.9 tons per rolling, 12-month period.

Individual facility-wide HAP emissions shall not exceed 9.9 tons per rolling, 12-month period.

- 2.b** For the requirements of this emissions unit, "cleanup materials" shall refer only to solvent-based gun cleaner. Requirements for cleanup materials other than solvent-based gun cleaner (i.e., water-based gun cleaner, wipe solvent) are addressed in Part II.

II. Operational Restrictions

1. The permittee shall operate the water wash system for the control of particulate emissions when this emissions unit is in operation.
2. The permittee shall not employ any photochemically reactive materials, as defined in OAC rule 3745-21-01(C)(5), in this emissions unit.

III. Monitoring and/or Record Keeping Requirements

1. The permittee shall collect and record the following information each day for this emissions unit:
 - a. the name and identification number of each coating and cleanup material employed;
 - b. the VOC content of each coating (excluding water and exempt solvents), and cleanup material, in pounds per gallon;
 - c. the number of gallons of each coating, and cleanup material (solvent based gun cleaner) employed;
 - d. the daily volume-weighted average VOC content of all coatings, as applied, calculated in accordance with the equation specified in paragraph (B)(9) of OAC rule 3745-21-10 for CVOC,2.
 - e. the hours of operation; and
 - f. the total VOC emissions from all coatings and cleanup materials (solvent based gun cleaner) employed $[(b \times c) / e]$, in lbs/hr.
2. The permittee shall collect and record the following information each month for the line:
 - a. the name and identification number of each coating, and cleanup material employed;
 - b. the VOC content of each coating (excluding water and exempt solvents), and cleanup material, in pounds per gallon;
 - c. the total HAP content of each coating, and cleanup material, in pounds per gallon;
 - d. the individual HAP content of each coating, and cleanup material, in pounds per gallon;
 - e. the number of gallons of each coating, and cleanup material (solvent based gun cleaner) employed;
 - f. the total VOC emissions (VOC applied) from all coatings, and cleanup materials (solvent based gun cleaner) employed [the sum of ((2.b times 2.e) divided by 2000 lb/ton) for all coatings and cleanup materials], in tons;
 - g. the rolling, 12-month summation of the VOC emissions, in tons; and
 - h. beginning after the first 12 calendar months of operation following issuance of this permit, the rolling 12-month summation of the gallons of each coating and clean-up material (solvent based gun cleaner) employed. Also, during the first 12 calendar months of operation following issuance of this permit, the permittee shall record the cumulative coating usage for each calendar month.

III. Monitoring and/or Record Keeping Requirements (continued)

3. The permittee shall maintain daily records that document any time periods when the water wash system was not in service when the emissions unit was in operation.
4. For each day a photochemically reactive coating and/or cleanup material is employed, the permittee shall maintain a record of the type and quantity of photochemically reactive materials employed in this emissions unit.

IV. Reporting Requirements

1. The permittee shall notify the Ohio EPA Southeast District Office in writing of any daily record showing that the daily volume-weighted average VOC content exceeds the applicable limitation. The notification shall include a copy of such record and shall be sent to the Ohio EPA Southeast District Office within 45 days after the exceedance occurs.
2. The permittee shall submit quarterly deviation (excursion) reports that include the following information:
 - a. an identification of each day during which the VOC emissions from all the coatings and cleanup materials (solvent-based gun cleaner) exceeded 200.0 lbs/hr, and the actual hourly average VOC emissions for each such day; and
 - b. an identification of each month during which the VOC emissions from the coatings and cleanup materials (solvent-based gun cleaner) employed in this emissions unit exceeded 80.0 tpy, as a rolling, 12-month summation, and the actual VOC emissions for each such month.
3. The permittee shall submit quarterly deviation (excursion) reports that identify all days when this emissions unit was in operation and the water wash system was not in service.
4. The permittee shall submit deviation reports which identify the days during which photochemically reactive materials were employed in this emissions unit. Each report shall identify the cause for the use of the photochemically reactive material(s), and the estimated total quantity of material(s) emitted during each such day, in pounds. Each report shall be submitted to the Ohio EPA Southeast District Office within 30 days of the deviation.
5. The permittee shall submit deviation (excursion) reports that identify all exceedances of the rolling, 12-month facility-wide total HAP emission limitation and, for the first 12 calendar months of operation, all exceedances of the maximum allowable cumulative total HAP emission limitation set forth in Part II, section A.5 of this permit.
6. The permittee shall submit deviation (excursion) reports that identify all exceedances of the rolling, 12-month facility-wide individual HAP emission limitation and, for the first 12 calendar months of operation, all exceedances of the maximum allowable cumulative individual HAP emission limitation set forth in Part II, section A.5 of this permit.
7. The quarterly deviation reports shall be submitted in accordance with the requirements specified in Part I - General Term and Condition A.1.c.ii.

V. Testing Requirements

1. Compliance with the emission limitations in section A.I.1 of these terms and conditions shall be determined in accordance with the following methods:
 - 1.a Emission Limitation:

3.5 pounds of VOC per gallon of coating, excluding water and exempt solvents (daily volume-weighted average), for an extreme performance coating

Applicable Compliance Method:

Compliance shall be demonstrated based upon the record keeping requirements specified in section A.III.1.

V. Testing Requirements (continued)

1.b Emission Limitation:

200.0 lbs/hr of VOC

Applicable Compliance Method:

Compliance may be demonstrated based upon the record keeping requirements specified in sections A.III.1 and A.III.2. If required, compliance shall also be demonstrated based upon emission tests performed in accordance with the requirements specified in 40 CFR Part 60, Appendix A, Methods 1 through 4 and 25.

1.c Emission Limitation:

80.0 tpy of VOC, based on a rolling, 12-month summation

Applicable Compliance Method:

Compliance shall be demonstrated based upon the record keeping requirements specified in sections A.III.1 and A.III.2.

1.d Emission Limitation:

2.58 lbs/hr of particulate emissions

Applicable Compliance Method:

Compliance may be demonstrated by multiplying the particulate emission factor of 244.4 lbs/hr of solids by the control efficiency of (1 - 0.99). This emission factor was established from company data to determine an emission rate for particulates from spray booths at this facility. If required, the permittee shall demonstrate compliance with this emission limitation in accordance with the methods and procedures specified in OAC rule 3745-17-03(B)(10).

1.e Emission Limitation:

11.3 tpy of particulate emissions

Applicable Compliance Method:

Compliance shall be demonstrated by multiplying the allowable emission limitation for particulate emissions by the actual hours of operation per year, and then dividing by 2000 lbs/ton.

1.f Emission Limitation:

20% opacity as a 6-minute average

Applicable Compliance Method:

Compliance shall be demonstrated based upon visible particulate emission observations performed in accordance with the methods and procedures specified in 40 CFR Part 60, Appendix A, Method 9 and OAC rule 3745-17-03(B)(1).

1.g Emission Limitation:

Total facility-wide HAP emissions, combined, shall not exceed 24.9 tons per rolling, 12-month period.

Applicable Compliance Method:

Compliance shall be based on the record keeping requirements specified in section A.III.2.

V. Testing Requirements (continued)

1.h Emission Limitation:

Individual facility-wide HAP emissions shall not exceed 9.9 tons per rolling, 12-month period.

Applicable Compliance Method:

Compliance shall be based on the record keeping requirements specified in section A.III.2.

2. Formulation data shall be used to determine the VOC contents of the cleanup materials.

USEPA Method 24 shall be used to determine the VOC contents for coatings. If any such coating has not been analyzed using Method 24 since January 1, 1991, the permittee shall either conduct a Method 24 analysis of the coating or obtain a Method 24 analysis of the coating from the coating supplier within one year of the issuance of the Permit to Operate. If the permittee determines that Method 24 cannot be used for a particular coating, the permittee shall so notify the Administrator of the USEPA and shall use formulation data for that coating to demonstrate compliance until the USEPA provides alternative analytical procedures or alternative precision statements for Method 24.

VI. Miscellaneous Requirements

None

B. State Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
---	---	--

2. Additional Terms and Conditions

None

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Part III - Terms and Conditions for Emissions Units

Emissions Unit ID: Touch Up Booth #3 (K017)

Activity Description: Touch Up paint on trucks//to be installed/ESTIMATED DATES

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

- The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
touch up booth #3 controlled with an exhaust filter	OAC rule 3745-31-05(A)(3) (PTI 06-4949)	Volatile organic compound (VOC) emissions shall not exceed 50.0 lbs/hr and 20.0 tpy of VOC, based upon a rolling, 12-month summation of the VOC emissions from all coatings and cleanup materials (solvent-based gun cleaner).
		Particulate emissions shall not exceed 2.41 tpy.
		The requirements of this rule also include compliance with the requirements of OAC rules 3745-17-07(A), 3745-17-11(B), and 3745-21-09(U)(2)(e)(iii).
	OAC rule 3745-17-07(A)	Visible particulate emissions shall not exceed 20% opacity as a 6-minute average, except as provided by the rule.
	OAC rule 3745-17-11(B)	Particulate emissions shall not exceed 0.551 lb/hr.
	OAC rule 3745-21-07(G)(2)	See A.II.2 below.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
	OAC rule 3745-21-09(U)(2)(e)(iii)	<p>This emissions unit shall not employ more than 10.0 gallons of coatings on metal parts in any given day.</p> <p>If this emissions unit ever employs more than 10.0 gallons of coatings on metal parts in any given day, thereafter, the VOC content of all metal parts coatings employed shall not exceed 3.5 pounds of VOC per gallon of coating, excluding water and exempt solvents, as a daily, volume-weighted average, pursuant to OAC rule 3745-21-09(U)(1)(c), and the 10.0 gallons per day limitation shall no longer be applicable.</p>

2. Additional Terms and Conditions

- 2.a** Total facility-wide Hazardous Air Pollutant (HAP) emissions, combined, shall not exceed 24.9 tons per rolling, 12-month period.

Individual facility-wide HAP emissions shall not exceed 9.9 tons per rolling, 12-month period.

- 2.b** For the requirements of this emissions unit, "cleanup materials" shall refer only to solvent-based gun cleaner. Requirements for cleanup materials other than solvent-based gun cleaner (i.e., water-based gun cleaner, wipe solvent) are addressed in Part II.

II. Operational Restrictions

1. The permittee shall employ the exhaust filter system for the control of particulate emissions when this emissions unit is in operation.
2. The permittee shall not employ any photochemically reactive materials, as defined in OAC rule 3745-21-01(C)(5), in this emissions unit.

III. Monitoring and/or Record Keeping Requirements

1. The permittee shall collect and record the following information each day for this emissions unit:
 - a. the name and identification number of each coating and cleanup material employed;
 - b. the VOC content of each coating (excluding water and exempt solvents), and cleanup material, in pounds per gallon;
 - c. the number of gallons of each coating, and cleanup material (solvent based gun cleaner) employed;
 - d. the daily volume-weighted average VOC content of all coatings, as applied, calculated in accordance with the equation specified in paragraph (B)(9) of OAC rule 3745-21-10 for CVOC,2.
 - e. the hours of operation; and
 - f. the total VOC emissions from all coatings and cleanup materials (solvent based gun cleaner) employed [(b X c) / e], in lbs/hr.

III. Monitoring and/or Record Keeping Requirements (continued)

2. The permittee shall collect and record the following information each month for the line:
 - a. the name and identification number of each coating, and cleanup material employed;
 - b. the VOC content of each coating (excluding water and exempt solvents), and cleanup material, in pounds per gallon;
 - c. the total HAP content of each coating, and cleanup material, in pounds per gallon;
 - d. the individual HAP content of each coating, and cleanup material, in pounds per gallon;
 - e. the number of gallons of each coating, and cleanup material (solvent based gun cleaner) employed;
 - f. the total VOC emissions (VOC applied) from all coatings, and cleanup materials (solvent based gun cleaner) employed [the sum of ((2.b times 2.e) divided by 2000 lb/ton) for all coatings and cleanup materials], in tons;
 - g. the rolling, 12-month summation of the VOC emissions, in tons; and
 - h. beginning after the first 12 calendar months of operation following issuance of this permit, the rolling 12-month summation of the gallons of each coating and clean-up material (solvent based gun cleaner) employed. Also, during the first 12 calendar months of operation following issuance of this permit, the permittee shall record the cumulative coating usage for each calendar month.
3. The permittee shall maintain daily records that document any time periods when the exhaust filter system was not in service when the emissions unit was in operation.
4. For each day a photochemically reactive coating and/or cleanup material is employed, the permittee shall maintain a record of the type and quantity of photochemically reactive materials employed in this emissions unit.

IV. Reporting Requirements

1. The permittee shall notify the Ohio EPA Southeast District Office in writing of any daily record showing that the coating line employs more than the applicable maximum daily coating usage limit. The notification shall include a copy of such record and shall be sent to the Ohio EPA Southeast District Office within 45 days after the exceedance occurs.
2. If this emissions unit ever employs more than 10.0 gallons of coatings on metal parts in any given day, thereafter, the permittee shall notify the Ohio EPA Southeast District Office in writing of any daily record showing that the daily volume-weighted average VOC content exceeds the applicable limitation. The notification shall include a copy of such record and shall be sent to the Ohio EPA Southeast District Office within 45 days after the exceedance occurs.
3. The permittee shall submit quarterly deviation (excursion) reports that include the following information:
 - a. an identification of each day during which the VOC emissions from all the coatings and cleanup materials (solvent-based gun cleaner) exceeded 50.0 lbs/hr, and the actual hourly average VOC emissions for each such day; and
 - b. an identification of each month during which the VOC emissions from the coatings and cleanup materials (solvent-based gun cleaner) employed in this emissions unit exceeded 20.0 tpy, as a rolling, 12-month summation, and the actual VOC emissions for each such month.
4. The permittee shall submit quarterly deviation (excursion) reports that identify all days when this emissions unit was in operation and the filter exhaust system was not in service.

IV. Reporting Requirements (continued)

5. The permittee shall submit deviation reports which identify the days during which photochemically reactive materials were employed in this emissions unit. Each report shall identify the cause for the use of the photochemically reactive material(s), and the estimated total quantity of material(s) emitted during each such day, in pounds. Each report shall be submitted to the Ohio EPA Southeast District Office within 30 days of the deviation.
6. The permittee shall submit deviation (excursion) reports that identify all exceedances of the rolling, 12-month facility-wide total HAP emission limitation and, for the first 12 calendar months of operation, all exceedances of the maximum allowable cumulative total HAP emission limitation set forth in Part II, section A.5 of this permit.
7. The permittee shall submit deviation (excursion) reports that identify all exceedances of the rolling, 12-month facility-wide individual HAP emission limitation and, for the first 12 calendar months of operation, all exceedances of the maximum allowable cumulative individual HAP emission limitation set forth in Part II, section A.5 of this permit.
8. The quarterly deviation reports shall be submitted in accordance with the requirements specified in Part I - General Term and Condition A.1.c.ii.

V. Testing Requirements

1. Compliance with the emission limitations in section A.I.1 of these terms and conditions shall be determined in accordance with the following methods:

1.a Emission Limitation:

This emissions unit shall not employ more than 10.0 gallons of coating on metal parts in any given day. If this emissions unit ever employs more than 10.0 gallons of coating on metal parts in any given day, thereafter, the VOC content of all metal parts coatings employed shall not exceed 3.5 pounds of VOC per gallon of coating, excluding water and exempt solvents, as a daily, volume-weighted average, pursuant to OAC rule 3745-21-09(U)(1)(c), and the 10.0 gallons per day limitation shall no longer be applicable.

Applicable Compliance Method:

Compliance shall be demonstrated based upon the record keeping requirements specified in section A.III.1.

1.b Emission Limitation:

50.0 lbs/hr of VOC

Applicable Compliance Method:

Compliance may be demonstrated based upon the record keeping requirements specified in sections A.III.1 and A.III.2. If required, compliance shall also be demonstrated based upon emission tests performed in accordance with the requirements specified in 40 CFR Part 60, Appendix A, Methods 1 through 4 and 25.

1.c Emission Limitation:

20.0 tpy of VOC, based on a rolling, 12-month summation

Applicable Compliance Method:

Compliance shall be demonstrated based upon the record keeping requirements specified in sections A.III.1 and A.III.2.

V. Testing Requirements (continued)

1.d Emission Limitation:

Particulate emissions shall not exceed 0.551 lb/hr.

Applicable Compliance Method:

To determine the actual worst case particulate emission rate, the following equation may be used:

$$E = (M) * (1-TE) * (1-CE)$$

where:

E = particulate matter emission rate (lbs/hr),

M = maximum coating solids usage rate (lbs/hr),

TE = transfer efficiency of coating equipment (ratio of the amount of coating solids deposited on the coated part to the amount of coating solids used),

CE = control efficiency of the control equipment. If more than one piece of control equipment is used in series, the equation should be multiplied by additional (1-CE) terms for each additional piece of equipment.

If required, the permittee shall demonstrate compliance with this emission limitation in accordance with the methods and procedures specified in OAC rule 3745-17-03(B)(10).

1.e Emission Limitation:

2.41 tpy of particulate emissions

Applicable Compliance Method:

Compliance shall be demonstrated by multiplying the allowable emission limitation for particulate emissions by the actual hours of operation per year, and then dividing by 2000 lbs/ton.

1.f Emission Limitation:

20% opacity as a 6-minute average

Applicable Compliance Method:

Compliance shall be demonstrated based upon visible particulate emission observations performed in accordance with the methods and procedures specified in 40 CFR Part 60, Appendix A, Method 9 and OAC rule 3745-17-03(B)(1).

1.g Emission Limitation:

Total facility-wide HAP emissions, combined, shall not exceed 24.9 tons per rolling, 12-month period.

Applicable Compliance Method:

Compliance shall be based on the record keeping requirements specified in section A.III.2.

1.h Emission Limitation:

Individual facility-wide HAP emissions shall not exceed 9.9 tons per rolling, 12-month period.

Applicable Compliance Method:

Compliance shall be based on the record keeping requirements specified in section A.III.2.

V. Testing Requirements (continued)

2. Formulation data shall be used to determine the VOC contents of the cleanup materials.

USEPA Method 24 shall be used to determine the VOC contents for coatings. If any such coating has not been analyzed using Method 24 since January 1, 1991, the permittee shall either conduct a Method 24 analysis of the coating or obtain a Method 24 analysis of the coating from the coating supplier within one year of the issuance of the Permit to Operate. If the permittee determines that Method 24 cannot be used for a particular coating, the permittee shall so notify the Administrator of the USEPA and shall use formulation data for that coating to demonstrate compliance until the USEPA provides alternative analytical procedures or alternative precision statements for Method 24.

VI. Miscellaneous Requirements

None

B. State Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
---	---	--

2. Additional Terms and Conditions

None

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Part III - Terms and Conditions for Emissions Units

Emissions Unit ID: Touch Up Booth #4 (K018)

Activity Description: Touch Up paint on trucks//to be installed/ESTIMATED DATES

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
touch up booth #4 controlled with an exhaust filter	OAC rule 3745-31-05(A)(3) (PTI 06-4949)	Volatile organic compound (VOC) emissions shall not exceed 50.0 lbs/hr and 20.0 tpy of VOC, based upon a rolling, 12-month summation of the VOC emissions from all coatings and cleanup materials (solvent-based gun cleaner).
		Particulate emissions shall not exceed 2.41 tpy.
		The requirements of this rule also include compliance with the requirements of OAC rules 3745-17-07(A), 3745-17-11(B), and 3745-21-09(U)(2)(e)(iii).
	OAC rule 3745-17-07(A)	Visible particulate emissions shall not exceed 20% opacity as a 6-minute average, except as provided by the rule.
	OAC rule 3745-17-11(B)	Particulate emissions shall not exceed 0.551 lb/hr.
	OAC rule 3745-21-07(G)(2)	See A.II.2 below.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
	OAC rule 3745-21-09(U)(2)(e)(iii)	<p>This emissions unit shall not employ more than 10.0 gallons of coatings on metal parts in any given day.</p> <p>If this emissions unit ever employs more than 10.0 gallons of coatings on metal parts in any given day, thereafter, the VOC content of all metal parts coatings employed shall not exceed 3.5 pounds of VOC per gallon of coating, excluding water and exempt solvents, as a daily, volume-weighted average, pursuant to OAC rule 3745-21-09(U)(1)(c), and the 10.0 gallons per day limitation shall no longer be applicable.</p>

2. Additional Terms and Conditions

- 2.a** Total facility-wide Hazardous Air Pollutant (HAP) emissions, combined, shall not exceed 24.9 tons per rolling, 12-month period.

Individual facility-wide HAP emissions shall not exceed 9.9 tons per rolling, 12-month period.

- 2.b** For the requirements of this emissions unit, "cleanup materials" shall refer only to solvent-based gun cleaner. Requirements for cleanup materials other than solvent-based gun cleaner (i.e., water-based gun cleaner, wipe solvent) are addressed in Part II.

II. Operational Restrictions

1. The permittee shall employ the exhaust filter system for the control of particulate emissions when this emissions unit is in operation.
2. The permittee shall not employ any photochemically reactive materials, as defined in OAC rule 3745-21-01(C)(5), in this emissions unit.

III. Monitoring and/or Record Keeping Requirements

1. The permittee shall collect and record the following information each day for this emissions unit:
 - a. the name and identification number of each coating and cleanup material employed;
 - b. the VOC content of each coating (excluding water and exempt solvents), and cleanup material, in pounds per gallon;
 - c. the number of gallons of each coating, and cleanup material (solvent based gun cleaner) employed;
 - d. the daily volume-weighted average VOC content of all coatings, as applied, calculated in accordance with the equation specified in paragraph (B)(9) of OAC rule 3745-21-10 for CVOC,2.
 - e. the hours of operation; and
 - f. the total VOC emissions from all coatings and cleanup materials (solvent based gun cleaner) employed [(b X c) / e], in lbs/hr.

III. Monitoring and/or Record Keeping Requirements (continued)

2. The permittee shall collect and record the following information each month for the line:
 - a. the name and identification number of each coating, and cleanup material employed;
 - b. the VOC content of each coating (excluding water and exempt solvents), and cleanup material, in pounds per gallon;
 - c. the total HAP content of each coating, and cleanup material, in pounds per gallon;
 - d. the individual HAP content of each coating, and cleanup material, in pounds per gallon;
 - e. the number of gallons of each coating, and cleanup material (solvent based gun cleaner) employed;
 - f. the total VOC emissions (VOC applied) from all coatings, and cleanup materials (solvent based gun cleaner) employed [the sum of ((2.b times 2.e) divided by 2000 lb/ton) for all coatings and cleanup materials], in tons;
 - g. the rolling, 12-month summation of the VOC emissions, in tons; and
 - h. beginning after the first 12 calendar months of operation following issuance of this permit, the rolling 12-month summation of the gallons of each coating and clean-up material (solvent based gun cleaner) employed. Also, during the first 12 calendar months of operation following issuance of this permit, the permittee shall record the cumulative coating usage for each calendar month.
3. The permittee shall maintain daily records that document any time periods when the exhaust filter system was not in service when the emissions unit was in operation.
4. For each day a photochemically reactive coating and/or cleanup material is employed, the permittee shall maintain a record of the type and quantity of photochemically reactive materials employed in this emissions unit.

IV. Reporting Requirements

1. The permittee shall notify the Ohio EPA Southeast District Office in writing of any daily record showing that the coating line employs more than the applicable maximum daily coating usage limit. The notification shall include a copy of such record and shall be sent to the Ohio EPA Southeast District Office within 45 days after the exceedance occurs.
2. If this emissions unit ever employs more than 10.0 gallons of coatings on metal parts in any given day, thereafter, the permittee shall notify the Ohio EPA Southeast District Office in writing of any daily record showing that the daily volume-weighted average VOC content exceeds the applicable limitation. The notification shall include a copy of such record and shall be sent to the Ohio EPA Southeast District Office within 45 days after the exceedance occurs.
3. The permittee shall submit quarterly deviation (excursion) reports that include the following information:
 - a. an identification of each day during which the VOC emissions from all the coatings and cleanup materials (solvent-based gun cleaner) exceeded 50.0 lbs/hr, and the actual hourly average VOC emissions for each such day; and
 - b. an identification of each month during which the VOC emissions from the coatings and cleanup materials (solvent-based gun cleaner) employed in this emissions unit exceeded 20.0 tpy, as a rolling, 12-month summation, and the actual VOC emissions for each such month.
4. The permittee shall submit quarterly deviation (excursion) reports that identify all days when this emissions unit was in operation and the filter exhaust system was not in service.

IV. Reporting Requirements (continued)

5. The permittee shall submit deviation reports which identify the days during which photochemically reactive materials were employed in this emissions unit. Each report shall identify the cause for the use of the photochemically reactive material(s), and the estimated total quantity of material(s) emitted during each such day, in pounds. Each report shall be submitted to the Ohio EPA Southeast District Office within 30 days of the deviation.
6. The permittee shall submit deviation (excursion) reports that identify all exceedances of the rolling, 12-month facility-wide total HAP emission limitation and, for the first 12 calendar months of operation, all exceedances of the maximum allowable cumulative total HAP emission limitation set forth in Part II, section A.5 of this permit.
7. The permittee shall submit deviation (excursion) reports that identify all exceedances of the rolling, 12-month facility-wide individual HAP emission limitation and, for the first 12 calendar months of operation, all exceedances of the maximum allowable cumulative individual HAP emission limitation set forth in Part II, section A.5 of this permit.
8. The quarterly deviation reports shall be submitted in accordance with the requirements specified in Part I - General Term and Condition A.1.c.ii.

V. Testing Requirements

1. Compliance with the emission limitations in section A.I.1 of these terms and conditions shall be determined in accordance with the following methods:

1.a Emission Limitation:

This emissions unit shall not employ more than 10.0 gallons of coating on metal parts in any given day. If this emissions unit ever employs more than 10.0 gallons of coating on metal parts in any given day, thereafter, the VOC content of all metal parts coatings employed shall not exceed 3.5 pounds of VOC per gallon of coating, excluding water and exempt solvents, as a daily, volume-weighted average, pursuant to OAC rule 3745-21-09(U)(1)(c), and the 10.0 gallons per day limitation shall no longer be applicable.

Applicable Compliance Method:

Compliance shall be demonstrated based upon the record keeping requirements specified in section A.III.1.

1.b Emission Limitation:

50.0 lbs/hr of VOC

Applicable Compliance Method:

Compliance may be demonstrated based upon the record keeping requirements specified in sections A.III.1 and A.III.2. If required, compliance shall also be demonstrated based upon emission tests performed in accordance with the requirements specified in 40 CFR Part 60, Appendix A, Methods 1 through 4 and 25.

1.c Emission Limitation:

20.0 tpy of VOC, based on a rolling, 12-month summation

Applicable Compliance Method:

Compliance shall be demonstrated based upon the record keeping requirements specified in sections A.III.1 and A.III.2.

V. Testing Requirements (continued)

1.d Emission Limitation:

Particulate emissions shall not exceed 0.551 lb/hr.

Applicable Compliance Method:

To determine the actual worst case particulate emission rate, the following equation may be used:

$$E = (M) * (1-TE) * (1-CE)$$

where:

E = particulate matter emission rate (lbs/hr),

M = maximum coating solids usage rate (lbs/hr),

TE = transfer efficiency of coating equipment (ratio of the amount of coating solids deposited on the coated part to the amount of coating solids used),

CE = control efficiency of the control equipment. If more than one piece of control equipment is used in series, the equation should be multiplied by additional (1-CE) terms for each additional piece of equipment.

If required, the permittee shall demonstrate compliance with this emission limitation in accordance with the methods and procedures specified in OAC rule 3745-17-03(B)(10).

1.e Emission Limitation:

2.41 tpy of particulate emissions

Applicable Compliance Method:

Compliance shall be demonstrated by multiplying the allowable emission limitation for particulate emissions by the actual hours of operation per year, and then dividing by 2000 lbs/ton.

1.f Emission Limitation:

20% opacity as a 6-minute average

Applicable Compliance Method:

Compliance shall be demonstrated based upon visible particulate emission observations performed in accordance with the methods and procedures specified in 40 CFR Part 60, Appendix A, Method 9 and OAC rule 3745-17-03(B)(1).

1.g Emission Limitation:

Total facility-wide HAP emissions, combined, shall not exceed 24.9 tons per rolling, 12-month period.

Applicable Compliance Method:

Compliance shall be based on the record keeping requirements specified in section A.III.2.

1.h Emission Limitation:

Individual facility-wide HAP emissions shall not exceed 9.9 tons per rolling, 12-month period.

Applicable Compliance Method:

Compliance shall be based on the record keeping requirements specified in section A.III.2.

V. Testing Requirements (continued)

2. Formulation data shall be used to determine the VOC contents of the cleanup materials.

USEPA Method 24 shall be used to determine the VOC contents for coatings. If any such coating has not been analyzed using Method 24 since January 1, 1991, the permittee shall either conduct a Method 24 analysis of the coating or obtain a Method 24 analysis of the coating from the coating supplier within one year of the issuance of the Permit to Operate. If the permittee determines that Method 24 cannot be used for a particular coating, the permittee shall so notify the Administrator of the USEPA and shall use formulation data for that coating to demonstrate compliance until the USEPA provides alternative analytical procedures or alternative precision statements for Method 24.

VI. Miscellaneous Requirements

None

B. State Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
---	---	--

2. Additional Terms and Conditions

None

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Part III - Terms and Conditions for Emissions Units

Emissions Unit ID: Cab Touch Up TKS (K019)

Activity Description: Touch up paint for cabs

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

- The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
cab touch up TKS controlled with an exhaust filter	OAC rule 3745-31-05(A)(3) (PTI 06-4949)	<p>Volatile organic compound (VOC) emissions shall not exceed 50.0 lbs/hr and 20.0 tpy of VOC, based upon a rolling, 12-month summation of the VOC emissions from all coatings and cleanup materials (solvent-based gun cleaner).</p> <p>Particulate emissions shall not exceed 2.41 tpy.</p> <p>The requirements of this rule also include compliance with the requirements of OAC rules 3745-17-07(A), 3745-17-11(B), and 3745-21-09(U)(2)(e)(iii).</p>
	OAC rule 3745-17-07(A)	Visible particulate emissions shall not exceed 20% opacity as a 6-minute average, except as provided by the rule.
	OAC rule 3745-17-11(B)	Particulate emissions shall not exceed 0.551 lb/hr.
	OAC rule 3745-21-07(G)(2)	See A.II.2 below.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
	OAC rule 3745-21-09(U)(2)(e)(iii)	<p>This emissions unit shall not employ more than 10.0 gallons of coatings on metal parts in any given day.</p> <p>If this emissions unit ever employs more than 10.0 gallons of coatings on metal parts in any given day, thereafter, the VOC content of all metal parts coatings employed shall not exceed 3.5 pounds of VOC per gallon of coating, excluding water and exempt solvents, as a daily, volume-weighted average, pursuant to OAC rule 3745-21-09(U)(1)(c), and the 10.0 gallons per day limitation shall no longer be applicable.</p>

2. Additional Terms and Conditions

- 2.a** Total facility-wide Hazardous Air Pollutant (HAP) emissions, combined, shall not exceed 24.9 tons per rolling, 12-month period.

Individual facility-wide HAP emissions shall not exceed 9.9 tons per rolling, 12-month period.

- 2.b** For the requirements of this emissions unit, "cleanup materials" shall refer only to solvent-based gun cleaner. Requirements for cleanup materials other than solvent-based gun cleaner (i.e., water-based gun cleaner, wipe solvent) are addressed in Part II.

II. Operational Restrictions

1. The permittee shall employ the exhaust filter system for the control of particulate emissions when this emissions unit is in operation.
2. The permittee shall not employ any photochemically reactive materials, as defined in OAC rule 3745-21-01(C)(5), in this emissions unit.

III. Monitoring and/or Record Keeping Requirements

1. The permittee shall collect and record the following information each day for this emissions unit:
 - a. the name and identification number of each coating and cleanup material employed;
 - b. the VOC content of each coating (excluding water and exempt solvents), and cleanup material, in pounds per gallon;
 - c. the number of gallons of each coating, and cleanup material (solvent based gun cleaner) employed;
 - d. the daily volume-weighted average VOC content of all coatings, as applied, calculated in accordance with the equation specified in paragraph (B)(9) of OAC rule 3745-21-10 for CVOC,2.
 - e. the hours of operation; and
 - f. the total VOC emissions from all coatings and cleanup materials (solvent based gun cleaner) employed [(b X c) / e], in lbs/hr.

III. Monitoring and/or Record Keeping Requirements (continued)

2. The permittee shall collect and record the following information each month for the line:
 - a. the name and identification number of each coating, and cleanup material employed;
 - b. the VOC content of each coating (excluding water and exempt solvents), and cleanup material, in pounds per gallon;
 - c. the total HAP content of each coating, and cleanup material, in pounds per gallon;
 - d. the individual HAP content of each coating, and cleanup material, in pounds per gallon;
 - e. the number of gallons of each coating, and cleanup material (solvent based gun cleaner) employed;
 - f. the total VOC emissions (VOC applied) from all coatings, and cleanup materials (solvent based gun cleaner) employed [the sum of ((2.b times 2.e) divided by 2000 lb/ton) for all coatings and cleanup materials], in tons;
 - g. the rolling, 12-month summation of the VOC emissions, in tons; and
 - h. beginning after the first 12 calendar months of operation following issuance of this permit, the rolling 12-month summation of the gallons of each coating and clean-up material (solvent based gun cleaner) employed. Also, during the first 12 calendar months of operation following issuance of this permit, the permittee shall record the cumulative coating usage for each calendar month.
3. The permittee shall maintain daily records that document any time periods when the exhaust filter system was not in service when the emissions unit was in operation.
4. For each day a photochemically reactive coating and/or cleanup material is employed, the permittee shall maintain a record of the type and quantity of photochemically reactive materials employed in this emissions unit.

IV. Reporting Requirements

1. The permittee shall notify the Ohio EPA Southeast District Office in writing of any daily record showing that the coating line employs more than the applicable maximum daily coating usage limit. The notification shall include a copy of such record and shall be sent to the Ohio EPA Southeast District Office within 45 days after the exceedance occurs.
2. If this emissions unit ever employs more than 10.0 gallons of coatings on metal parts in any given day, thereafter, the permittee shall notify the Ohio EPA Southeast District Office in writing of any daily record showing that the daily volume-weighted average VOC content exceeds the applicable limitation. The notification shall include a copy of such record and shall be sent to the Ohio EPA Southeast District Office within 45 days after the exceedance occurs.
3. The permittee shall submit quarterly deviation (excursion) reports that include the following information:
 - a. an identification of each day during which the VOC emissions from all the coatings and cleanup materials (solvent-based gun cleaner) exceeded 50.0 lbs/hr, and the actual hourly average VOC emissions for each such day; and
 - b. an identification of each month during which the VOC emissions from the coatings and cleanup materials (solvent-based gun cleaner) employed in this emissions unit exceeded 20.0 tpy, as a rolling, 12-month summation, and the actual VOC emissions for each such month.
4. The permittee shall submit quarterly deviation (excursion) reports that identify all days when this emissions unit was in operation and the filter exhaust system was not in service.

IV. Reporting Requirements (continued)

5. The permittee shall submit deviation reports which identify the days during which photochemically reactive materials were employed in this emissions unit. Each report shall identify the cause for the use of the photochemically reactive material(s), and the estimated total quantity of material(s) emitted during each such day, in pounds. Each report shall be submitted to the Ohio EPA Southeast District Office within 30 days of the deviation.
6. The permittee shall submit deviation (excursion) reports that identify all exceedances of the rolling, 12-month facility-wide total HAP emission limitation and, for the first 12 calendar months of operation, all exceedances of the maximum allowable cumulative total HAP emission limitation set forth in Part II, section A.5 of this permit.
7. The permittee shall submit deviation (excursion) reports that identify all exceedances of the rolling, 12-month facility-wide individual HAP emission limitation and, for the first 12 calendar months of operation, all exceedances of the maximum allowable cumulative individual HAP emission limitation set forth in Part II, section A.5 of this permit.
8. The quarterly deviation reports shall be submitted in accordance with the requirements specified in Part I - General Term and Condition A.1.c.ii.

V. Testing Requirements

1. Compliance with the emission limitations in section A.I.1 of these terms and conditions shall be determined in accordance with the following methods:

- 1.a Emission Limitation:

This emissions unit shall not employ more than 10.0 gallons of coating on metal parts in any given day. If this emissions unit ever employs more than 10.0 gallons of coating on metal parts in any given day, thereafter, the VOC content of all metal parts coatings employed shall not exceed 3.5 pounds of VOC per gallon of coating, excluding water and exempt solvents, as a daily, volume-weighted average, pursuant to OAC rule 3745-21-09(U)(1)(c), and the 10.0 gallons per day limitation shall no longer be applicable.

Applicable Compliance Method:

Compliance shall be demonstrated based upon the record keeping requirements specified in section A.III.1.

- 1.b Emission Limitation:

50.0 lbs/hr of VOC

Applicable Compliance Method:

Compliance may be demonstrated based upon the record keeping requirements specified in sections A.III.1 and A.III.2. If required, compliance shall also be demonstrated based upon emission tests performed in accordance with the requirements specified in 40 CFR Part 60, Appendix A, Methods 1 through 4 and 25.

- 1.c Emission Limitation:

20.0 tpy of VOC, based on a rolling, 12-month summation

Applicable Compliance Method:

Compliance shall be demonstrated based upon the record keeping requirements specified in sections A.III.1 and A.III.2.

V. Testing Requirements (continued)

1.d Emission Limitation:

Particulate emissions shall not exceed 0.551 lb/hr.

Applicable Compliance Method:

To determine the actual worst case particulate emission rate, the following equation may be used:

$$E = (M) * (1-TE) * (1-CE)$$

where:

E = particulate matter emission rate (lbs/hr),

M = maximum coating solids usage rate (lbs/hr),

TE = transfer efficiency of coating equipment (ratio of the amount of coating solids deposited on the coated part to the amount of coating solids used),

CE = control efficiency of the control equipment. If more than one piece of control equipment is used in series, the equation should be multiplied by additional (1-CE) terms for each additional piece of equipment.

If required, the permittee shall demonstrate compliance with this emission limitation in accordance with the methods and procedures specified in OAC rule 3745-17-03(B)(10).

1.e Emission Limitation:

2.41 tpy of particulate emissions

Applicable Compliance Method:

Compliance shall be demonstrated by multiplying the allowable emission limitation for particulate emissions by the actual hours of operation per year, and then dividing by 2000 lbs/ton.

1.f Emission Limitation:

20% opacity as a 6-minute average

Applicable Compliance Method:

Compliance shall be demonstrated based upon visible particulate emission observations performed in accordance with the methods and procedures specified in 40 CFR Part 60, Appendix A, Method 9 and OAC rule 3745-17-03(B)(1).

1.g Emission Limitation:

Total facility-wide HAP emissions, combined, shall not exceed 24.9 tons per rolling, 12-month period.

Applicable Compliance Method:

Compliance shall be based on the record keeping requirements specified in section A.III.2.

1.h Emission Limitation:

Individual facility-wide HAP emissions shall not exceed 9.9 tons per rolling, 12-month period.

Applicable Compliance Method:

Compliance shall be based on the record keeping requirements specified in section A.III.2.

V. Testing Requirements (continued)

2. Formulation data shall be used to determine the VOC contents of the cleanup materials.

USEPA Method 24 shall be used to determine the VOC contents for coatings. If any such coating has not been analyzed using Method 24 since January 1, 1991, the permittee shall either conduct a Method 24 analysis of the coating or obtain a Method 24 analysis of the coating from the coating supplier within one year of the issuance of the Permit to Operate. If the permittee determines that Method 24 cannot be used for a particular coating, the permittee shall so notify the Administrator of the USEPA and shall use formulation data for that coating to demonstrate compliance until the USEPA provides alternative analytical procedures or alternative precision statements for Method 24.

VI. Miscellaneous Requirements

None

B. State Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
---	---	--

2. Additional Terms and Conditions

None

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Part III - Terms and Conditions for Emissions Units

Emissions Unit ID: Fiberglass (K020)
Activity Description: Touch up paint for cabs

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

- The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
fiberglass touch up controlled with an exhaust filter	OAC rule 3745-31-05(A)(3) (PTI 06-4949)	Volatile organic compound (VOC) emissions shall not exceed 50.0 lbs/hr and 20.0 tpy of VOC, based upon a rolling, 12-month summation of the VOC emissions from all coatings and cleanup materials (solvent-based gun cleaner).
		Particulate emissions shall not exceed 2.41 tpy.
		The requirements of this rule also include compliance with the requirements of OAC rules 3745-17-07(A), 3745-17-11(B), and 3745-21-09(U)(2)(e)(iii).
	OAC rule 3745-17-07(A)	Visible particulate emissions shall not exceed 20% opacity as a 6-minute average, except as provided by the rule.
	OAC rule 3745-17-11(B)	Particulate emissions shall not exceed 0.551 lb/hr.
	OAC rule 3745-21-07(G)(2)	See A.II.2 below.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
	OAC rule 3745-21-09(U)(2)(e)(iii)	<p>This emissions unit shall not employ more than 10.0 gallons of coatings on metal parts in any given day.</p> <p>If this emissions unit ever employs more than 10.0 gallons of coatings on metal parts in any given day, thereafter, the VOC content of all metal parts coatings employed shall not exceed 3.5 pounds of VOC per gallon of coating, excluding water and exempt solvents, as a daily, volume-weighted average, pursuant to OAC rule 3745-21-09(U)(1)(c), and the 10.0 gallons per day limitation shall no longer be applicable.</p>

2. Additional Terms and Conditions

- 2.a** Total facility-wide Hazardous Air Pollutant (HAP) emissions, combined, shall not exceed 24.9 tons per rolling, 12-month period.

Individual facility-wide HAP emissions shall not exceed 9.9 tons per rolling, 12-month period.

- 2.b** For the requirements of this emissions unit, "cleanup materials" shall refer only to solvent-based gun cleaner. Requirements for cleanup materials other than solvent-based gun cleaner (i.e., water-based gun cleaner, wipe solvent) are addressed in Part II.

II. Operational Restrictions

1. The permittee shall employ the exhaust filter system for the control of particulate emissions when this emissions unit is in operation.
2. The permittee shall not employ any photochemically reactive materials, as defined in OAC rule 3745-21-01(C)(5), in this emissions unit.

III. Monitoring and/or Record Keeping Requirements

1. The permittee shall collect and record the following information each day for this emissions unit:
 - a. the name and identification number of each coating and cleanup material employed;
 - b. the VOC content of each coating (excluding water and exempt solvents), and cleanup material, in pounds per gallon;
 - c. the number of gallons of each coating, and cleanup material (solvent based gun cleaner) employed;
 - d. the daily volume-weighted average VOC content of all coatings, as applied, calculated in accordance with the equation specified in paragraph (B)(9) of OAC rule 3745-21-10 for CVOC,2.
 - e. the hours of operation; and
 - f. the total VOC emissions from all coatings and cleanup materials (solvent based gun cleaner) employed [(b X c) / e], in lbs/hr.

III. Monitoring and/or Record Keeping Requirements (continued)

2. The permittee shall collect and record the following information each month for the line:
 - a. the name and identification number of each coating, and cleanup material employed;
 - b. the VOC content of each coating (excluding water and exempt solvents), and cleanup material, in pounds per gallon;
 - c. the total HAP content of each coating, and cleanup material, in pounds per gallon;
 - d. the individual HAP content of each coating, and cleanup material, in pounds per gallon;
 - e. the number of gallons of each coating, and cleanup material (solvent based gun cleaner) employed;
 - f. the total VOC emissions (VOC applied) from all coatings, and cleanup materials (solvent based gun cleaner) employed [the sum of ((2.b times 2.e) divided by 2000 lb/ton) for all coatings and cleanup materials], in tons;
 - g. the rolling, 12-month summation of the VOC emissions, in tons; and
 - h. beginning after the first 12 calendar months of operation following issuance of this permit, the rolling 12-month summation of the gallons of each coating and clean-up material (solvent based gun cleaner) employed. Also, during the first 12 calendar months of operation following issuance of this permit, the permittee shall record the cumulative coating usage for each calendar month.
3. The permittee shall maintain daily records that document any time periods when the exhaust filter system was not in service when the emissions unit was in operation.
4. For each day a photochemically reactive coating and/or cleanup material is employed, the permittee shall maintain a record of the type and quantity of photochemically reactive materials employed in this emissions unit.

IV. Reporting Requirements

1. The permittee shall notify the Ohio EPA Southeast District Office in writing of any daily record showing that the coating line employs more than the applicable maximum daily coating usage limit. The notification shall include a copy of such record and shall be sent to the Ohio EPA Southeast District Office within 45 days after the exceedance occurs.
2. If this emissions unit ever employs more than 10.0 gallons of coatings on metal parts in any given day, thereafter, the permittee shall notify the Ohio EPA Southeast District Office in writing of any daily record showing that the daily volume-weighted average VOC content exceeds the applicable limitation. The notification shall include a copy of such record and shall be sent to the Ohio EPA Southeast District Office within 45 days after the exceedance occurs.
3. The permittee shall submit quarterly deviation (excursion) reports that include the following information:
 - a. an identification of each day during which the VOC emissions from all the coatings and cleanup materials (solvent-based gun cleaner) exceeded 50.0 lbs/hr, and the actual hourly average VOC emissions for each such day; and
 - b. an identification of each month during which the VOC emissions from the coatings and cleanup materials (solvent-based gun cleaner) employed in this emissions unit exceeded 20.0 tpy, as a rolling, 12-month summation, and the actual VOC emissions for each such month.
4. The permittee shall submit quarterly deviation (excursion) reports that identify all days when this emissions unit was in operation and the filter exhaust system was not in service.

IV. Reporting Requirements (continued)

5. The permittee shall submit deviation reports which identify the days during which photochemically reactive materials were employed in this emissions unit. Each report shall identify the cause for the use of the photochemically reactive material(s), and the estimated total quantity of material(s) emitted during each such day, in pounds. Each report shall be submitted to the Ohio EPA Southeast District Office within 30 days of the deviation.
6. The permittee shall submit deviation (excursion) reports that identify all exceedances of the rolling, 12-month facility-wide total HAP emission limitation and, for the first 12 calendar months of operation, all exceedances of the maximum allowable cumulative total HAP emission limitation set forth in Part II, section A.5 of this permit.
7. The permittee shall submit deviation (excursion) reports that identify all exceedances of the rolling, 12-month facility-wide individual HAP emission limitation and, for the first 12 calendar months of operation, all exceedances of the maximum allowable cumulative individual HAP emission limitation set forth in Part II, section A.5 of this permit.
8. The quarterly deviation reports shall be submitted in accordance with the requirements specified in Part I - General Term and Condition A.1.c.ii.

V. Testing Requirements

1. Compliance with the emission limitations in section A.I.1 of these terms and conditions shall be determined in accordance with the following methods:

- 1.a Emission Limitation:

This emissions unit shall not employ more than 10.0 gallons of coating on metal parts in any given day. If this emissions unit ever employs more than 10.0 gallons of coating on metal parts in any given day, thereafter, the VOC content of all metal parts coatings employed shall not exceed 3.5 pounds of VOC per gallon of coating, excluding water and exempt solvents, as a daily, volume-weighted average, pursuant to OAC rule 3745-21-09(U)(1)(c), and the 10.0 gallons per day limitation shall no longer be applicable.

Applicable Compliance Method:

Compliance shall be demonstrated based upon the record keeping requirements specified in section A.III.1.

- 1.b Emission Limitation:

50.0 lbs/hr of VOC

Applicable Compliance Method:

Compliance may be demonstrated based upon the record keeping requirements specified in sections A.III.1 and A.III.2. If required, compliance shall also be demonstrated based upon emission tests performed in accordance with the requirements specified in 40 CFR Part 60, Appendix A, Methods 1 through 4 and 25.

- 1.c Emission Limitation:

20.0 tpy of VOC, based on a rolling, 12-month summation

Applicable Compliance Method:

Compliance shall be demonstrated based upon the record keeping requirements specified in sections A.III.1 and A.III.2.

V. Testing Requirements (continued)

1.d Emission Limitation:

Particulate emissions shall not exceed 0.551 lb/hr.

Applicable Compliance Method:

To determine the actual worst case particulate emission rate, the following equation may be used:

$$E = (M) * (1-TE) * (1-CE)$$

where:

E = particulate matter emission rate (lbs/hr),

M = maximum coating solids usage rate (lbs/hr),

TE = transfer efficiency of coating equipment (ratio of the amount of coating solids deposited on the coated part to the amount of coating solids used),

CE = control efficiency of the control equipment. If more than one piece of control equipment is used in series, the equation should be multiplied by additional (1-CE) terms for each additional piece of equipment.

If required, the permittee shall demonstrate compliance with this emission limitation in accordance with the methods and procedures specified in OAC rule 3745-17-03(B)(10).

1.e Emission Limitation:

2.41 tpy of particulate emissions

Applicable Compliance Method:

Compliance shall be demonstrated by multiplying the allowable emission limitation for particulate emissions by the actual hours of operation per year, and then dividing by 2000 lbs/ton.

1.f Emission Limitation:

20% opacity as a 6-minute average

Applicable Compliance Method:

Compliance shall be demonstrated based upon visible particulate emission observations performed in accordance with the methods and procedures specified in 40 CFR Part 60, Appendix A, Method 9 and OAC rule 3745-17-03(B)(1).

1.g Emission Limitation:

Total facility-wide HAP emissions, combined, shall not exceed 24.9 tons per rolling, 12-month period.

Applicable Compliance Method:

Compliance shall be based on the record keeping requirements specified in section A.III.2.

1.h Emission Limitation:

Individual facility-wide HAP emissions shall not exceed 9.9 tons per rolling, 12-month period.

Applicable Compliance Method:

Compliance shall be based on the record keeping requirements specified in section A.III.2.

V. Testing Requirements (continued)

2. Formulation data shall be used to determine the VOC contents of the cleanup materials.

USEPA Method 24 shall be used to determine the VOC contents for coatings. If any such coating has not been analyzed using Method 24 since January 1, 1991, the permittee shall either conduct a Method 24 analysis of the coating or obtain a Method 24 analysis of the coating from the coating supplier within one year of the issuance of the Permit to Operate. If the permittee determines that Method 24 cannot be used for a particular coating, the permittee shall so notify the Administrator of the USEPA and shall use formulation data for that coating to demonstrate compliance until the USEPA provides alternative analytical procedures or alternative precision statements for Method 24.

VI. Miscellaneous Requirements

None

B. State Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
---	---	--

2. Additional Terms and Conditions

None

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

Part III - Terms and Conditions for Emissions Units

Emissions Unit ID: Undercoating Booth (R010)
Activity Description: Solvent wiping of cabs

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

- The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
undercoating booth controlled with a dry filtration system	OAC rule 3745-31-05(A)(3) (PTI 06-4949)	<p>Volatile organic compound (VOC) emissions shall not exceed 50.0 lbs/hr and 20.0 tpy of VOC, based upon a rolling, 12-month summation of the VOC emissions from all coatings and cleanup materials (solvent-based gun cleaner).</p> <p>Particulate emissions shall not exceed 2.41 tpy.</p> <p>The requirements of this rule also include compliance with the requirements of OAC rules 3745-17-07(A), 3745-17-11(B), and 3745-21-09(U)(2)(e)(iii).</p>
	OAC rule 3745-17-07(A)	Visible particulate emissions shall not exceed 20% opacity as a 6-minute average, except as provided by the rule.
	OAC rule 3745-17-11(B)	Particulate emissions shall not exceed 0.551 lb/hr.
	OAC rule 3745-21-07(G)(2)	See A.II.2 below.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
	OAC rule 3745-21-09(U)(2)(e)(iii)	<p>This emissions unit shall not employ more than 10.0 gallons of coatings on metal parts in any given day.</p> <p>If this emissions unit ever employs more than 10.0 gallons of coatings on metal parts in any given day, thereafter, the VOC content of all metal parts coatings employed shall not exceed 3.5 pounds of VOC per gallon of coating, excluding water and exempt solvents, as a daily, volume-weighted average, pursuant to OAC rule 3745-21-09(U)(1)(c), and the 10.0 gallons per day limitation shall no longer be applicable.</p>

2. Additional Terms and Conditions

- 2.a** Total facility-wide Hazardous Air Pollutant (HAP) emissions, combined, shall not exceed 24.9 tons per rolling, 12-month period.

Individual facility-wide HAP emissions shall not exceed 9.9 tons per rolling, 12-month period.

- 2.b** For the requirements of this emissions unit, "cleanup materials" shall refer only to solvent-based gun cleaner. Requirements for cleanup materials other than solvent-based gun cleaner (i.e., water-based gun cleaner, wipe solvent) are addressed in Part II.

II. Operational Restrictions

1. The permittee shall operate the dry filtration system for the control of particulate emissions when this emissions unit is in operation.
2. The permittee shall not employ any photochemically reactive materials, as defined in OAC rule 3745-21-01(C)(5), in this emissions unit.

III. Monitoring and/or Record Keeping Requirements

1. The permittee shall collect and record the following information each day for this emissions unit:
 - a. the name and identification number of each coating and cleanup material employed;
 - b. the VOC content of each coating (excluding water and exempt solvents), and cleanup material, in pounds per gallon;
 - c. the number of gallons of each coating, and cleanup material (solvent based gun cleaner) employed;
 - d. the daily volume-weighted average VOC content of all coatings, as applied, calculated in accordance with the equation specified in paragraph (B)(9) of OAC rule 3745-21-10 for CVOC,2.
 - e. the hours of operation; and
 - f. the total VOC emissions from all coatings and cleanup materials (solvent based gun cleaner) employed [(b X c) / e], in lbs/hr.

III. Monitoring and/or Record Keeping Requirements (continued)

2. The permittee shall collect and record the following information each month for the line:
 - a. the name and identification number of each coating, and cleanup material employed;
 - b. the VOC content of each coating (excluding water and exempt solvents), and cleanup material, in pounds per gallon;
 - c. the total HAP content of each coating, and cleanup material, in pounds per gallon;
 - d. the individual HAP content of each coating, and cleanup material, in pounds per gallon;
 - e. the number of gallons of each coating, and cleanup material (solvent based gun cleaner) employed;
 - f. the total VOC emissions (VOC applied) from all coatings, and cleanup materials (solvent based gun cleaner) employed [the sum of ((2.b times 2.e) divided by 2000 lb/ton) for all coatings and cleanup materials], in tons;
 - g. the rolling, 12-month summation of the VOC emissions, in tons; and
 - h. beginning after the first 12 calendar months of operation following issuance of this permit, the rolling 12-month summation of the gallons of each coating and clean-up material (solvent based gun cleaner) employed. Also, during the first 12 calendar months of operation following issuance of this permit, the permittee shall record the cumulative coating usage for each calendar month.
3. The permittee shall maintain daily records that document any time periods when the dry filtration system was not in service when the emissions unit was in operation.
4. For each day a photochemically reactive coating and/or cleanup material is employed, the permittee shall maintain a record of the type and quantity of photochemically reactive materials employed in this emissions unit.

IV. Reporting Requirements

1. The permittee shall notify the Ohio EPA Southeast District Office in writing of any daily record showing that the coating line employs more than the applicable maximum daily coating usage limit. The notification shall include a copy of such record and shall be sent to the Ohio EPA Southeast District Office within 45 days after the exceedance occurs.
2. If this emissions unit ever employs more than 10.0 gallons of coatings on metal parts in any given day, thereafter, the permittee shall notify the Ohio EPA Southeast District Office in writing of any daily record showing that the daily volume-weighted average VOC content exceeds the applicable limitation. The notification shall include a copy of such record and shall be sent to the Ohio EPA Southeast District Office within 45 days after the exceedance occurs.
3. The permittee shall submit quarterly deviation (excursion) reports that include the following information:
 - a. an identification of each day during which the VOC emissions from all the coatings and cleanup materials (solvent-based gun cleaner) exceeded 50.0 lbs/hr, and the actual hourly average VOC emissions for each such day; and
 - b. an identification of each month during which the VOC emissions from the coatings and cleanup materials (solvent-based gun cleaner) employed in this emissions unit exceeded 20.0 tpy, as a rolling, 12-month summation, and the actual VOC emissions for each such month.
4. The permittee shall submit quarterly deviation (excursion) reports that identify all days when this emissions unit was in operation and the dry filtration system was not in service.

IV. Reporting Requirements (continued)

5. The permittee shall submit deviation reports which identify the days during which photochemically reactive materials were employed in this emissions unit. Each report shall identify the cause for the use of the photochemically reactive material(s), and the estimated total quantity of material(s) emitted during each such day, in pounds. Each report shall be submitted to the Ohio EPA Southeast District Office within 30 days of the deviation.
6. The permittee shall submit deviation (excursion) reports that identify all exceedances of the rolling, 12-month facility-wide total HAP emission limitation and, for the first 12 calendar months of operation, all exceedances of the maximum allowable cumulative total HAP emission limitation set forth in Part II, section A.5 of this permit.
7. The permittee shall submit deviation (excursion) reports that identify all exceedances of the rolling, 12-month facility-wide individual HAP emission limitation and, for the first 12 calendar months of operation, all exceedances of the maximum allowable cumulative individual HAP emission limitation set forth in Part II, section A.5 of this permit.
8. The quarterly deviation reports shall be submitted in accordance with the requirements specified in Part I - General Term and Condition A.1.c.ii.

V. Testing Requirements

1. Compliance with the emission limitations in section A.I.1 of these terms and conditions shall be determined in accordance with the following methods:

- 1.a Emission Limitation:

This emissions unit shall not employ more than 10.0 gallons of coating on metal parts in any given day. If this emissions unit ever employs more than 10.0 gallons of coating on metal parts in any given day, thereafter, the VOC content of all metal parts coatings employed shall not exceed 3.5 pounds of VOC per gallon of coating, excluding water and exempt solvents, as a daily, volume-weighted average, pursuant to OAC rule 3745-21-09(U)(1)(c), and the 10.0 gallons per day limitation shall no longer be applicable.

Applicable Compliance Method:

Compliance shall be demonstrated based upon the record keeping requirements specified in section A.III.1.

- 1.b Emission Limitation:

50.0 lbs/hr of VOC

Applicable Compliance Method:

Compliance may be demonstrated based upon the record keeping requirements specified in sections A.III.1 and A.III.2. If required, compliance shall also be demonstrated based upon emission tests performed in accordance with the requirements specified in 40 CFR Part 60, Appendix A, Methods 1 through 4 and 25.

- 1.c Emission Limitation:

20.0 tpy of VOC, based on a rolling, 12-month summation

Applicable Compliance Method:

Compliance shall be demonstrated based upon the record keeping requirements specified in sections A.III.1 and A.III.2.

V. Testing Requirements (continued)

1.d Emission Limitation:

Particulate emissions shall not exceed 0.551 lb/hr.

Applicable Compliance Method:

To determine the actual worst case particulate emission rate, the following equation may be used:

$$E = (M) * (1-TE) * (1-CE)$$

where:

E = particulate matter emission rate (lbs/hr),

M = maximum coating solids usage rate (lbs/hr),

TE = transfer efficiency of coating equipment (ratio of the amount of coating solids deposited on the coated part to the amount of coating solids used),

CE = control efficiency of the control equipment. If more than one piece of control equipment is used in series, the equation should be multiplied by additional (1-CE) terms for each additional piece of equipment.

If required, the permittee shall demonstrate compliance with this emission limitation in accordance with the methods and procedures specified in OAC rule 3745-17-03(B)(10).

1.e Emission Limitation:

2.41 tpy of particulate emissions

Applicable Compliance Method:

Compliance shall be demonstrated by multiplying the allowable emission limitation for particulate emissions by the actual hours of operation per year, and then dividing by 2000 lbs/ton.

1.f Emission Limitation:

20% opacity as a 6-minute average

Applicable Compliance Method:

Compliance shall be demonstrated based upon visible particulate emission observations performed in accordance with the methods and procedures specified in 40 CFR Part 60, Appendix A, Method 9 and OAC rule 3745-17-03(B)(1).

1.g Emission Limitation:

Total facility-wide HAP emissions, combined, shall not exceed 24.9 tons per rolling, 12-month period.

Applicable Compliance Method:

Compliance shall be based on the record keeping requirements specified in section A.III.2.

1.h Emission Limitation:

Individual facility-wide HAP emissions shall not exceed 9.9 tons per rolling, 12-month period.

Applicable Compliance Method:

Compliance shall be based on the record keeping requirements specified in section A.III.2.

V. Testing Requirements (continued)

2. Formulation data shall be used to determine the VOC contents of the cleanup materials.

USEPA Method 24 shall be used to determine the VOC contents for coatings. If any such coating has not been analyzed using Method 24 since January 1, 1991, the permittee shall either conduct a Method 24 analysis of the coating or obtain a Method 24 analysis of the coating from the coating supplier within one year of the issuance of the Permit to Operate. If the permittee determines that Method 24 cannot be used for a particular coating, the permittee shall so notify the Administrator of the USEPA and shall use formulation data for that coating to demonstrate compliance until the USEPA provides alternative analytical procedures or alternative precision statements for Method 24.

VI. Miscellaneous Requirements

None

B. State Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
---	---	--

2. Additional Terms and Conditions

None

II. Operational Restrictions

None

III. Monitoring and/or Record Keeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

None

THIS IS THE LAST PAGE OF THE PERMIT
