



State of Ohio Environmental Protection Agency

**RE: FINAL PERMIT TO INSTALL MODIFICATION  
CUYAHOGA COUNTY**

**CERTIFIED MAIL**

Street Address:

122 S. Front Street

Lazarus Gov. Center TELE: (614) 644-3020 FAX: (614) 644-2329

Mailing Address:  
Lazarus Gov. Center  
P.O. Box 1049

**Application No: 13-04412**

**Fac ID: 1318000404**

**DATE: 12/26/2006**

CMC - Kilroy Steel  
Glenn Shealy  
Post Office Box 71 301 New State Road  
Cayce, SC 29601

Enclosed Please find a modification to the Ohio EPA Permit To Install referenced above which will modify the terms and conditions.

You are hereby notified that this action of the Director is final and may be appealed to the Environmental Review Appeals Commission pursuant to Section 3745.04 of the Ohio Revised Code. The appeal must be in writing and set forth the action complained of and the grounds upon which the appeal is based. The appeal must be filed with the Commission within thirty (30) days after notice of the Director's action. The appeal must be accompanied by a filing fee of \$70.00 which the Commission, in its discretion, may reduce if by affidavit you demonstrate that payment of the full amount of the fee would cause extreme hardship. Notice of the filing of the appeal shall be filed with the Director within three (3) days of filing with the Commission. Ohio EPA requests that a copy of the appeal be served upon the Ohio Attorney General's Office, Environmental Enforcement Section. An appeal may be filed with the Environmental Review Appeals Commission at the following address:

Environmental Review Appeals Commission  
309 South Fourth Street, Room 222  
Columbus, OH 43215

Sincerely,

Michael W. Ahern, Manager  
Permit Issuance and Data Management Section  
Division of Air Pollution Control

CC: USEPA

CLAA



Permit To Install  
Terms and Conditions

Issue Date: 12/26/2006  
Effective Date: 12/26/2006

**FINAL ADMINISTRATIVE MODIFICATION OF PERMIT TO INSTALL 13-04412**

Application Number: 13-04412  
Facility ID: 1318000404  
Permit Fee: **\$300**  
Name of Facility: CMC - Kilroy Steel  
Person to Contact: Glenn Shealy  
Address: Post Office Box 71 301 New State Road  
Cayce, SC 29601

Location of proposed air contaminant source(s) [emissions unit(s)]:  
**8500 Union Avenue  
Cleveland, Ohio**

Description of proposed emissions unit(s):  
**Administrative modification for three airless spray guns to account for additional coatings overlooked in original PTI application submittal --K001, K002, and K003.**

The above named entity is hereby granted a modification to the permit to install described above pursuant to Chapter 3745-31 of the Ohio Administrative Code. Issuance of this modification does not constitute expressed or implied approval or agreement that, if constructed or modified in accordance with the plans included in the application, the above described source(s) of environmental pollutants will operate in compliance with applicable State and Federal laws and regulations, and does not constitute expressed or implied assurance that if constructed or modified in accordance with those plans included in the application, the above described source(s) of pollutants will be granted the necessary operating permits.

This permit is granted subject to the conditions attached hereto.

Ohio Environmental Protection Agency

Director

## Part I - GENERAL TERMS AND CONDITIONS

### A. Permit to Install General Terms and Conditions

#### 1. Compliance Requirements

The emissions unit(s) identified in this Permit to Install shall remain in full compliance with all applicable State laws and regulations and the terms and conditions of this permit.

#### 2. Reporting Requirements

The permittee shall submit required reports in the following manner:

- a. Reports of any required monitoring and/or recordkeeping information shall be submitted to the appropriate Ohio EPA District Office or local air agency.
- b. Except as otherwise may be provided in the terms and conditions for a specific emissions unit, quarterly written reports of (a) any deviations (excursions) from emission limitations, operational restrictions, and control device operating parameter limitations that have been detected by the testing, monitoring, and recordkeeping requirements specified in this permit, (b) the probable cause of such deviations, and (c) any corrective actions or preventive measures which have been or will be taken, shall be submitted to the appropriate Ohio EPA District Office or local air agency. If no deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted (i.e., postmarked) quarterly by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters. (These quarterly reports shall exclude deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06.)

#### 3. Records Retention Requirements

Each record of any monitoring data, testing data, and support information required pursuant to this permit shall be retained for a period of five years from the date the record was created. Support information shall include, but not be limited to, all calibration and maintenance records and all original strip-chart recordings for continuous monitoring instrumentation, and copies of all reports required by this permit. Such records may be maintained in computerized form.

#### 4. Inspections and Information Requests

The Director of the Ohio EPA, or an authorized representative of the Director, may, subject to the safety requirements of the permittee and without undue delay, enter upon

**CMC - Kilroy Steel**  
**PTI Application: 13-04412**  
**Modification Issued: 12/26/2006**

**Facility ID: 131800040**

the premises of this source at any reasonable time for purposes of making inspections, conducting tests, examining records or reports pertaining to any emission of air contaminants, and determining compliance with any applicable State air pollution laws and regulations and the terms and conditions of this permit. The permittee shall furnish to the Director of the Ohio EPA, or an authorized representative of the Director, upon receipt of a written request and within a reasonable time, any information that may be requested to determine whether cause exists for modifying, reopening or revoking this permit or to determine compliance with this permit. Upon verbal or written request, the permittee shall also furnish to the Director of the Ohio EPA, or an authorized representative of the Director, copies of records required to be kept by this permit.

**5. Scheduled Maintenance/Malfunction Reporting**

Any scheduled maintenance of air pollution control equipment shall be performed in accordance with paragraph (A) of OAC rule 3745-15-06. The malfunction of any emissions units or any associated air pollution control system(s) shall be reported to the appropriate Ohio EPA District Office or local air agency in accordance with paragraph (B) of OAC rule 3745-15-06. Except as provided in that rule, any scheduled maintenance or malfunction necessitating the shutdown or bypassing of any air pollution control system(s) shall be accompanied by the shutdown of the emissions unit(s) that is (are) served by such control system(s).

**6. Permit Transfers**

Any transferee of this permit shall assume the responsibilities of the prior permit holder. The appropriate Ohio EPA District Office or local air agency must be notified in writing of any transfer of this permit.

**7. Air Pollution Nuisance**

The air contaminants emitted by the emissions units covered by this permit shall not cause a public nuisance, in violation of OAC rule 3745-15-07.

**8. Termination of Permit to Install**

This Permit to Install shall terminate within eighteen months of the effective date of the Permit to Install if the owner or operator has not undertaken a continuing program of installation or modification or has not entered into a binding contractual obligation to undertake and complete within a reasonable time a continuing program of installation or modification. This deadline may be extended by up to 12 months if application is made to the Director within a reasonable time before the termination date and the party shows good cause for any such extension.

**9. Construction of New Sources(s)**

**CMC - Kilroy Steel**  
**PTI Application: 13-04412**  
**Modification Issued: 12/26/2006**

**Facility ID: 131800040**

The proposed emissions unit(s) shall be constructed in strict accordance with the plans and application submitted for this permit to the Director of the Ohio Environmental Protection Agency. There may be no deviation from the approved plans without the express, written approval of the Agency. Any deviations from the approved plans or the above conditions may lead to such sanctions and penalties as provided under Ohio law. Approval of these plans does not constitute an assurance that the proposed facilities will operate in compliance with all Ohio laws and regulations. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed sources cannot meet the requirements of this permit or cannot meet applicable standards.

If the construction of the proposed emissions unit(s) has already begun or has been completed prior to the date the Director of the Environmental Protection Agency approves the permit application and plans, the approval does not constitute expressed or implied assurance that the proposed facility has been constructed in accordance with the approved plans. The action of beginning and/or completing construction prior to obtaining the Director's approval constitutes a violation of OAC rule 3745-31-02. Furthermore, issuance of the Permit to Install does not constitute an assurance that the proposed source will operate in compliance with all Ohio laws and regulations. Approval of the plans in any case is not to be construed as an approval of the facility as constructed and/or completed. Moreover, issuance of the Permit to Install is not to be construed as a waiver of any rights that the Ohio Environmental Protection Agency (or other persons) may have against the applicant for starting construction prior to the effective date of the permit. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed facilities cannot meet the requirements of this permit or cannot meet applicable standards.

#### **10. Public Disclosure**

The facility is hereby notified that this permit, and all agency records concerning the operation of this permitted source, are subject to public disclosure in accordance with OAC rule 3745-49-03.

#### **11. Applicability**

This Permit To Install is applicable only to the emissions unit(s) identified in the Permit To Install. Separate Permit To Install for the installation or modification of any other emissions unit(s) are required for any emissions unit for which a Permit To Install is required.

#### **12. Best Available Technology**

As specified in OAC Rule 3745-31-05, all new sources must employ Best Available Technology (BAT). Compliance with the terms and conditions of this permit will fulfill this requirement.

CMC - Kilroy Steel  
 PTI Application: 13-04412  
 Modification Issued: 12/26/2006

Facility ID: 131800040

**13. Source Operation and Operating Permit Requirements After Completion of Construction**

This facility is permitted to operate each source described by this Permit to Install for a period of up to one year from the date the source commenced operation. This permission to operate is granted only if the facility complies with all requirements contained in this permit and all applicable air pollution laws, regulations, and policies. Pursuant to OAC Chapter 3745-35, the permittee shall submit a complete operating permit application within ninety (90) days after commencing operation of the emissions unit(s) covered by this permit.

**14. Construction Compliance Certification**

The applicant shall provide Ohio EPA with a written certification (see enclosed form) that the facility has been constructed in accordance with the Permit to Install application and the terms and conditions of the Permit to Install. The certification shall be provided to Ohio EPA upon completion of construction but prior to startup of the source.

**15. Fees**

The permittee shall pay fees to the Director of the Ohio EPA in accordance with ORC section 3745.11 and OAC Chapter 3745-78. The permittee shall pay all applicable Permit to Install fees within 30 days after the issuance of this Permit to Install.

**B. Permit to Install Summary of Allowable Emissions**

The following information summarizes the total allowable emissions, by pollutant, based on the individual allowable emissions of each air contaminant source identified in this permit.

SUMMARY (for informational purposes only)  
 TOTAL PERMIT TO INSTALL ALLOWABLE EMISSIONS

<u>Pollutant</u>	<u>Tons Per Year</u>
VOC (coating and cleanup)	95.85



Modification Issued: 12/26/2006

95.85 TPY based upon a rolling, 12-month summation of emissions.

- 2.b The total allowable emissions of Hazardous Air Pollutants (HAPs), as identified in Section 112(b) of Title III of the Clean Air Act, from emissions units K001, K002, and K003 shall not exceed 9.9 tons/year for any individual HAP or 24.9 tons/year for a combination of HAPs. Compliance with the above limitations shall be based upon a rolling, 12-month summation of emissions for this emissions unit plus the annual HAP contribution from all other emissions units at this facility (K001, K002, and K003).

**B. Operational Restrictions**

- 1. The maximum annual operating hours for emission units K001, K002, and K003 shall not exceed 18,000 collectively, based on a 12-month rolling summation of the operating hours.

To ensure enforceability during the first 12 calendar months of operation or the first 12 calendar months following the issuance of this permit, the permittee shall not exceed the operating hours levels specified in the following table:

<u>Month(s)</u>	<u>Maximum Allowable Cumulative Operating Hours for K001, K002, and K003 combined</u>
1	3,000
1-2	4,500
1-3	6,000
1-4	7,500
1-5	9,000
1-6	10,500
1-7	12,000
1-8	13,500
1-9	15,000
1-10	16,500
1-11	18,000
1-12	18,000

After the first 12 calendar months of operation or the first 12 calendar months following the issuance of this permit, compliance with the annual operating hours limitation shall be based upon a rolling, 12-month summation of the operating hours.

2. The permittee shall keep all doors closed, in this emission unit's coating area, while conducting painting activities.

### C. Monitoring and/or Recordkeeping Requirements

1. The permittee shall maintain daily records that document any time periods when doors were not closed in this emission unit's coating area, while painting activities were conducted.
2. The permittee shall collect and record the following information each day for this emissions unit:
  - a. the name and identification number of each coating employed and cleanup material dispensed;
  - b. the amount, in gallons, of each coating employed;
  - c. the amount, in gallons, of each cleanup material dispensed;
  - d. the VOC content of each coating and cleanup material, in pounds per gallon, as applied;
  - e. the total VOC emission rate for all coatings, in pounds and tons [summation of (b x d) for all coatings];
  - f. hours of operation;
  - g. average hourly emission rate, in pounds per hour (e/f);
  - h. the amount, in gallons, of cleanup material that is contained for disposal;
  - i. the total emission rate for cleanup material [d(c-h)], in pounds and tons; and
  - j. the VOC content of each coating, in pounds per gallon less water and exempt solvents, as applied.
3. The permittee shall collect and record the total VOC emissions from all coatings and cleanup materials employed for this emissions unit, for the purpose of determining annual VOC emissions (summation of daily emissions from C.2 above divided by 2000

lbs/ton).

4. The permittee shall collect and record from emissions units K001, K002, and K003 on a monthly basis, the rolling, 12-month summation of VOC emissions, in tons per year, for all coatings and cleanup materials. This shall include information for the current month and the preceding eleven calendar months. For the first twelve months following the issuance of the permit, this shall be a cumulative total for all months since the issuance of the PTI.
5. The permittee shall maintain monthly records of the following information for the facility (K001, K002, and K003):
  - a. the name and identification number of each HAP containing material employed;
  - b. the individual HAP content for each HAP, in pounds of individual HAP per gallon of material;
  - c. the total combined HAP content, in pounds of combined HAPs per gallon of material [sum all the individual HAP contents from (b)];
  - d. the number of gallons, of each HAP containing material employed;
  - e. the total individual HAP usage for each HAP from all HAP containing materials, in pounds or tons per month [for each HAP the sum of (b) times (c) for each material];
  - f. the total combined HAP usage from all HAP containing materials, in pounds or tons per month [the sum of (c) times (d) for each material];
  - g. the updated rolling, 12-month summation of usage and emissions for each individual HAP, in tons. This shall include the information for the current month and the preceding eleven calendar months. For the first twelve months following the issuance of the permit, this shall be a cumulative total for all months since the issuance of the PTI;
  - h. the updated rolling, 12-month summation of usage and emissions for the total combined HAPs, in tons. This shall include the information for the current month and the preceding eleven calendar months. For the first twelve months following the issuance of this permit, this shall be a cumulative total for all months since the issuance of the PTI;

**Modification Issued: 12/26/2006**

- i. the operating hours for each month; and
- g. beginning after the first 12 calendar months of operation or the first 12 calendar months following the issuance of this permit, the rolling, 12 month summation of the operating hours.

Also, during the first 12 calendar months of operation or the first 12 calendar months following the issuance of this permit, the permittee shall record the cumulative operating hours for each calendar month.

\* A listing of the HAPs can be found in Section 112(b) of the Clean Air Act or can be obtained by contacting your Cleveland Division of Air Quality (Cleveland DAQ) contact. This information does not have to be kept on an individual emission unit basis.

6. The permit to install for this emissions unit (K001) was evaluated based on the actual materials (typically coatings) and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant:

Pollutant: Xylene  
 TLV (mg/m<sup>3</sup>): 434.4  
 Maximum Hourly Emission Rate (lbs/hr): 24.9 lbs/hr (Total for K001, K002, and K003 combined)  
 Predicted 1-Hour Maximum Ground-Level Concentration at the property line (µg/m<sup>3</sup>): 6,054  
 MAGLC (µg/m<sup>3</sup>): 10,342

Pollutant: MIBK  
 TLV (mg/m<sup>3</sup>): 204.9  
 Maximum Hourly Emission Rate (lbs/hr): 15.78 lbs/hr (Total for K001, K002, and K003 combined)  
 Predicted 1-Hour Maximum Ground-Level Concentration at the property line (µg/m<sup>3</sup>): 3,837  
 MAGLC (µg/m<sup>3</sup>): 4,879

CMC - Kilroy Steel  
PTI Application: 13-04412  
Modif

Facility ID: 131800040

Emissions Unit ID: K001

Pollutant: Ethyl benzene

TLV (mg/m<sup>3</sup>): 434.4

Maximum Hourly Emission Rate (lbs/hr): 14.43 lbs/hr (Total for K001, K002, and K003 combined)

Predicted 1-Hour Maximum Ground-Level

Concentration at the property line (µg/m<sup>3</sup>): 3,509

MAGLC (µg/m<sup>3</sup>): 10,342

Pollutant: Toluene

TLV (mg/m<sup>3</sup>): 188.4

Maximum Hourly Emission Rate (lbs/hr): 3.21 lbs/hr (Total for K001, K002, and K003 combined)

Predicted 1-Hour Maximum Ground-Level

Concentration at the property line (µg/m<sup>3</sup>): 780

MAGLC (µg/m<sup>3</sup>): 4,486

Pollutant: Cumene

TLV (mg/m<sup>3</sup>): 245.8

Maximum Hourly Emission Rate (lbs/hr): 15.78 lbs/hr (Total for K001, K002, and K003 combined)

Predicted 1-Hour Maximum Ground-Level

Concentration at the property line (µg/m<sup>3</sup>): 299

MAGLC (µg/m<sup>3</sup>): 4,879

7. Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:
- a. changes in the composition of the materials used (typically for coatings or cleanup materials), or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value previously modeled;
  - b. changes in the composition of the materials, or use of new materials, that would

**Modification Issued: 12/26/2006**

result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and

- c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01 solely due to the emissions of any type of toxic air contaminant not previously emitted, and a modification of the existing permit to install will not be required, even if the toxic air contaminant emissions are greater than the de minimis level in OAC rule 3745-15-05. If the change(s) is (are) defined as a modification under other provisions of the modification definition, then the permittee shall obtain a final permit to install prior to the change.

8. The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy:"
  - a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
  - b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and
  - c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

**D. Reporting Requirements**

1. The permittee shall notify the Cleveland DAQ in writing of any daily record showing that the doors were not closed in this emission unit's coating area, while conducting painting activities. The notification shall include a copy of the record and shall be sent within 30 days after the event occurs.
2. The permittee shall notify the Cleveland DAQ in writing of any daily record showing the use of noncomplying coatings. The notification shall include a copy of such record and shall be sent to the Cleveland DAQ within 30 days following the end of the calendar month.
3. The permittee shall submit quarterly deviation (excursion) reports to the Cleveland DAQ that identify each day during which the average hourly VOC emissions from the coating operation exceeded 10.50 lbs/hr. Each report shall be submitted in accordance with the general terms and conditions within this permit.
4. The permittee shall submit to the Cleveland DAQ, by January 31 of each year, an annual emissions report that specifies the total VOC emissions for this emissions unit.
5. The permittee shall submit deviation (excursion) reports for the entire facility (includes emissions units K001, K002, and K003) which include the following information:
  - a. an identification of each month during which the rolling, 12-month individual HAP emissions exceed 9.9 tpy (and combined HAPs emissions exceed 24.9 tpy) based on a rolling, 12-month summation and the actual rolling, 12-month individual (and combined) HAP emissions for each such month; and
  - b. an identification of all exceedances of the rolling, 12-month limitation of the hours of operation; and for the first 12 calendar months of operation or the first 12 calendar months following the issuance of this permit, all exceedances of the maximum allowable cumulative hours of operation.

These reports shall be submitted in accordance with the reporting requirements specified in Part 1 - General Terms and Conditions, Section A of this permit.

6. The permittee shall submit quarterly deviation (excursion) reports which identify all exceedances of the rolling, 12-month emission limitation for VOC from emissions units K001, K002, and K003. This written report shall be submitted to the Cleveland DAQ within 30 days of the occurrence of the deviation.

## E. Testing Requirements

1. Compliance with the emission limitation(s) in Section A.1 of these terms and conditions shall be determined in accordance with the following method(s):

- a. Emission Limitation:  
VOC emissions shall not exceed 10.50 lbs/hr from coatings.

Applicable Compliance Method:  
Compliance with the above daily emission limitation shall be determined by the record keeping as specified in Section C.2.

- b. Emission Limitation:  
VOC emissions shall not exceed 45.99 tons per year from coatings.

Applicable Compliance Method:  
Compliance with yearly emission limitation shall be determined by summing the daily emission rates and dividing by 2000 lbs/ton for each calendar year, as specified in Section C.3.

- c. Emission Limitation:

The VOC content of the coatings shall not exceed 3.50 pounds of VOC per gallon of coating, excluding water and exempt solvents.

Applicable Compliance Method:  
Compliance with the VOC limitation above shall be determined from the record keeping as specified in Section C.2.

Compliance may also be determined by calculating the VOC content in accordance with the equation specified in OAC Rule 3745-21-10(B)(9) for CVOC,2 for the daily volume-weighted average VOC content.

U.S. EPA Method 24 shall be used to determine the VOC contents of the coatings employed. The permittee may obtain the Method 24 analysis for each coating from the supplier.

- d. Emission Limitation:  
VOC emissions from cleanup materials shall not exceed 0.45 tons per year.

**Modification Issued: 12/26/2006**

Applicable Compliance Method:

Compliance with the VOC limitation above shall be determined from the record keeping as specified in Section C.3.

Formulation data shall be used to determine VOC content of the cleanup material.

e. Emission Limitation:

VOC emissions from emissions units K001, K002, and K003 shall not exceed 95.85 TPY based upon a rolling, 12-month summation of emissions.

Applicable Compliance Method:

Compliance shall be determined based upon the record keeping specified in section C.4.

f. Emission Limitation:

HAPs from emissions units K001, K002, and K003 shall not exceed 9.9 tons/year for any individual HAP.

Applicable Compliance Method:

Compliance shall be determined based upon the record keeping specified in section C.5.

g. Emission Limitation:

HAPs from emissions units K001, K002, and K003 shall not exceed 24.9 tons/year for a combination of HAPs.

Applicable Compliance Method:

Compliance shall be determined based upon the record keeping specified in section C.5.

**F. Miscellaneous Requirements**

None.

17

**CMC - Kilroy Steel**

**PTI Application: 13 04112**

**Modif**

**Facility ID: 131800040**

**Emissions Unit ID: K001**

**PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)**

**A. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
K002 - Steel coating operation using an airless spray gun  MODIFIED	OAC rule 3745-31-05(A)(3)	Volatile Organic Compound (VOC) emissions from coatings shall not exceed 10.50 pounds per hour and 45.99 tons per year.
		VOC emissions from cleanup materials shall not exceed 0.45 tons per year.
		The requirements of this rule also include compliance with the requirements of OAC rule 3745-21-09(U)(1)(d).
	OAC rule 3745-21-09(U)(1)(d)	The VOC content of the coatings shall not exceed 3.50 pounds of VOC per gallon of coating, excluding water and exempt solvents.
	OAC rule 3745-31-05(C) Synthetic Minor to avoid Title V, Nonattainment NSR, and MACT Subpart M	See Additional Terms and Conditions A.2.a and A.2.b below.

**2. Additional Terms and Conditions**

**Modification Issued: 12/26/2006**

- 2.a** VOC emissions from emissions units K001, K002, and K003 shall not exceed 95.85 TPY based upon a rolling, 12-month summation of emissions.
- 2.b** The total allowable emissions of Hazardous Air Pollutants (HAPs), as identified in Section 112(b) of Title III of the Clean Air Act, from emissions units K001, K002, and K003 shall not exceed 9.9 tons/year for any individual HAP or 24.9 tons/year for a combination of HAPs. Compliance with the above limitations shall be based upon a rolling, 12-month summation of emissions for this emissions unit plus the annual HAP contribution from all other emissions units at this facility (K001, K002, and K003).

**B. Operational Restrictions**

1. The maximum annual operating hours for emission units K001, K002, and K003 shall not exceed 18,000 collectively, based on a 12-month rolling summation of the operating hours.

To ensure enforceability during the first 12 calendar months of operation or the first 12 calendar months following the issuance of this permit, the permittee shall not exceed the operating hours levels specified in the following table:

<u>Month(s)</u>	<u>Maximum Allowable Cumulative Operating Hours for K001, K002, and K003 combined</u>
1	3,000
1-2	4,500
1-3	6,000
1-4	7,500
1-5	9,000
1-6	10,500
1-7	12,000
1-8	13,500
1-9	15,000
1-10	16,500
1-11	18,000
1-12	18,000

After the first 12 calendar months of operation or the first 12 calendar months following the issuance of this permit, compliance with the annual operating hours limitation shall

**Modification Issued: 12/26/2006**

be based upon a rolling, 12-month summation of the operating hours.

2. The permittee shall keep all doors closed, in this emission unit's coating area, while conducting painting activities.

**C. Monitoring and/or Recordkeeping Requirements**

1. The permittee shall maintain daily records that document any time periods when doors were not closed in this emission unit's coating area, while painting activities were conducted.
2. The permittee shall collect and record the following information each day for this emissions unit:
  - a. the name and identification number of each coating employed and cleanup material dispensed;
  - b. the amount, in gallons, of each coating employed;
  - c. the amount, in gallons, of each cleanup material dispensed;
  - d. the VOC content of each coating and cleanup material, in pounds per gallon, as applied;
  - e. the total VOC emission rate for all coatings, in pounds and tons [summation of (b x d) for all coatings];
  - f. hours of operation;
  - g. average hourly emission rate, in pounds per hour (e/f);
  - h. the amount, in gallons, of cleanup material that is contained for disposal;
  - i. the total emission rate for cleanup material [d(c-h)], in pounds and tons; and
  - j. the VOC content of each coating, in pounds per gallon less water and exempt solvents, as applied.
3. The permittee shall collect and record the total VOC emissions from all coatings and cleanup materials employed for this emissions unit, for the purpose of determining

**Emissions Unit ID: K002**

annual VOC emissions (summation of daily emissions from C.2 above divided by 2000 lbs/ton).

4. The permittee shall collect and record from emissions units K001, K002, and K003 on a monthly basis, the rolling, 12-month summation of VOC emissions, in tons per year, for all coatings and cleanup materials. This shall include information for the current month and the preceding eleven calendar months. For the first twelve months following the issuance of the permit, this shall be a cumulative total for all months since the issuance of the PTI.
5. The permittee shall maintain monthly records of the following information for the facility (K001, K002, and K003):
  - a. the name and identification number of each HAP containing material employed;
  - b. the individual HAP content for each HAP, in pounds of individual HAP per gallon of material;
  - c. the total combined HAP content, in pounds of combined HAPs per gallon of material [sum all the individual HAP contents from (b)];
  - d. the number of gallons, of each HAP containing material employed;
  - e. the total individual HAP usage for each HAP from all HAP containing materials, in pounds or tons per month [for each HAP the sum of (b) times (c) for each material];
  - f. the total combined HAP usage from all HAP containing materials, in pounds or tons per month [the sum of (c) times (d) for each material];
  - g. the updated rolling, 12-month summation of usage and emissions for each individual HAP, in tons. This shall include the information for the current month and the preceding eleven calendar months. For the first twelve months following the issuance of the permit, this shall be a cumulative total for all months since the issuance of the PTI;
  - h. the updated rolling, 12-month summation of usage and emissions for the total combined HAPs, in tons. This shall include the information for the current month and the preceding eleven calendar months. For the first twelve months following the issuance of this permit, this shall be a cumulative total for all months since the issuance of the PTI;

**Modification Issued: 12/26/2006**

- i. the operating hours for each month; and
- j. beginning after the first 12 calendar months of operation or the first 12 calendar months following the issuance of this permit, the rolling, 12 month summation of the operating hours.

Also, during the first 12 calendar months of operation or the first 12 calendar months following the issuance of this permit, the permittee shall record the cumulative operating hours for each calendar month.

\* A listing of the HAPs can be found in Section 112(b) of the Clean Air Act or can be obtained by contacting your Cleveland Division of Air Quality (Cleveland DAQ) contact. This information does not have to be kept on an individual emission unit basis.

6. The permit to install for this emissions unit (K002) was evaluated based on the actual materials (typically coatings) and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant:

Pollutant: Xylene

TLV (mg/m<sup>3</sup>): 434.4

Maximum Hourly Emission Rate (lbs/hr): 24.9 lbs/hr (Total for K001, K002, and K003 combined)

Predicted 1-Hour Maximum Ground-Level

Concentration at the property line (µg/m<sup>3</sup>): 6,054

MAGLC (µg/m<sup>3</sup>): 10,342

Pollutant: MIBK

TLV (mg/m<sup>3</sup>): 204.9

Maximum Hourly Emission Rate (lbs/hr): 15.78 lbs/hr (Total for K001, K002, and K003 combined)

Predicted 1-Hour Maximum Ground-Level

Concentration at the property line (µg/m<sup>3</sup>): 3,837

MAGLC (µg/m<sup>3</sup>): 4,879

CMC - Kilroy Steel  
PTI Application: 13-04412  
Modif

Facility ID: 131800040

Emissions Unit ID: K002

Pollutant: Ethyl benzene

TLV (mg/m3): 434.4

Maximum Hourly Emission Rate (lbs/hr): 14.43 lbs/hr (Total for K001, K002, and K003 combined)

Predicted 1-Hour Maximum Ground-Level

Concentration at the property line ( $\mu\text{g}/\text{m}^3$ ): 3,509

MAGLC ( $\mu\text{g}/\text{m}^3$ ): 10,342

Pollutant: Toluene

TLV (mg/m3): 188.4

Maximum Hourly Emission Rate (lbs/hr): 3.21 lbs/hr (Total for K001, K002, and K003 combined)

Predicted 1-Hour Maximum Ground-Level

Concentration at the property line ( $\mu\text{g}/\text{m}^3$ ): 780

MAGLC ( $\mu\text{g}/\text{m}^3$ ): 4,486

Pollutant: Cumene

TLV (mg/m3): 245.8

Maximum Hourly Emission Rate (lbs/hr): 15.78 lbs/hr (Total for K001, K002, and K003 combined)

Predicted 1-Hour Maximum Ground-Level

Concentration at the property line ( $\mu\text{g}/\text{m}^3$ ): 299

MAGLC ( $\mu\text{g}/\text{m}^3$ ): 4,879

7. Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:
  - a. changes in the composition of the materials used (typically for coatings or cleanup materials), or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value previously modeled;
  - b. changes in the composition of the materials, or use of new materials, that would

**Modification Issued: 12/26/2006**

result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and

- c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01 solely due to the emissions of any type of toxic air contaminant not previously emitted, and a modification of the existing permit to install will not be required, even if the toxic air contaminant emissions are greater than the de minimis level in OAC rule 3745-15-05. If the change(s) is (are) defined as a modification under other provisions of the modification definition, then the permittee shall obtain a final permit to install prior to the change.

8. The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy:"
  - a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
  - b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and
  - c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

**D. Reporting Requirements**

1. The permittee shall notify the Cleveland DAQ in writing of any daily record showing that the doors were not closed in this emission unit's coating area, while conducting painting activities. The notification shall include a copy of the record and shall be sent within 30 days after the event occurs.
2. The permittee shall notify the Cleveland DAQ in writing of any daily record showing the use of noncomplying coatings. The notification shall include a copy of such record and shall be sent to the Cleveland DAQ within 30 days following the end of the calendar month.
3. The permittee shall submit quarterly deviation (excursion) reports to the Cleveland DAQ that identify each day during which the average hourly VOC emissions from the coating operation exceeded 10.50 lbs/hr. Each report shall be submitted in accordance with the general terms and conditions within this permit.
4. The permittee shall submit to the Cleveland DAQ, by January 31 of each year, an annual emissions report that specifies the total VOC emissions for this emissions unit.
5. The permittee shall submit deviation (excursion) reports for the entire facility (includes emissions units K001, K002, and K003) which include the following information:
  - a. an identification of each month during which the rolling, 12-month individual HAP emissions exceed 9.9 tpy (and combined HAPs emissions exceed 24.9 tpy) based on a rolling, 12-month summation and the actual rolling, 12-month individual (and combined) HAP emissions for each such month; and
  - b. an identification of all exceedances of the rolling, 12-month limitation of the hours of operation; and for the first 12 calendar months of operation or the first 12 calendar months following the issuance of this permit, all exceedances of the maximum allowable cumulative hours of operation.

These reports shall be submitted in accordance with the reporting requirements specified in Part 1 - General Terms and Conditions, Section A of this permit.

6. The permittee shall submit quarterly deviation (excursion) reports which identify all exceedances of the rolling, 12-month emission limitation for VOC from emissions units K001, K002, and K003. This written report shall be submitted to the Cleveland DAQ within 30 days of the occurrence of the deviation.

## E. Testing Requirements

1. Compliance with the emission limitation(s) in Section A.1 of these terms and conditions shall be determined in accordance with the following method(s):

- a. Emission Limitation:  
VOC emissions shall not exceed 10.50 lbs/hr from coatings.

Applicable Compliance Method:  
Compliance with the above daily emission limitation shall be determined by the record keeping as specified in Section C.2.

- b. Emission Limitation:  
VOC emissions shall not exceed 45.99 tons per year from coatings.

Applicable Compliance Method:  
Compliance with yearly emission limitation shall be determined by summing the daily emission rates and dividing by 2000 lbs/ton for each calendar year, as specified in Section C.3.

- c. Emission Limitation:

The VOC content of the coatings shall not exceed 3.50 pounds of VOC per gallon of coating, excluding water and exempt solvents.

Applicable Compliance Method:  
Compliance with the VOC limitation above shall be determined from the record keeping as specified in Section C.2.

Compliance may also be determined by calculating the VOC content in accordance with the equation specified in OAC Rule 3745-21-10(B)(9) for CVOC,2 for the daily volume-weighted average VOC content.

U.S. EPA Method 24 shall be used to determine the VOC contents of the coatings employed. The permittee may obtain the Method 24 analysis for each coating from the supplier.

- d. Emission Limitation:  
VOC emissions from cleanup materials shall not exceed 0.45 tons per year.

**Modification Issued: 12/26/2006**

Applicable Compliance Method:

Compliance with the VOC limitation above shall be determined from the record keeping as specified in Section C.3.

Formulation data shall be used to determine VOC content of the cleanup material.

e. Emission Limitation:

VOC emissions from emissions units K001, K002, and K003 shall not exceed 95.85 TPY based upon a rolling, 12-month summation of emissions.

Applicable Compliance Method:

Compliance shall be determined based upon the record keeping specified in section C.4.

f. Emission Limitation:

HAPs from emissions units K001, K002, and K003 shall not exceed 9.9 tons/year for any individual HAP.

Applicable Compliance Method:

Compliance shall be determined based upon the record keeping specified in section C.5.

g. Emission Limitation:

HAPs from emissions units K001, K002, and K003 shall not exceed 24.9 tons/year for a combination of HAPs.

Applicable Compliance Method:

Compliance shall be determined based upon the record keeping specified in section C.5.

**F. Miscellaneous Requirements**

None.

**PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)**

**A. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
K003 - Steel coating operation using an airless spray gun	OAC rule 3745-31-05(A)(3)	Volatile Organic Compound (VOC) emissions from coatings shall not exceed 10.50 pounds per hour and 45.99 tons per year.
MODIFIED	OAC rule 3745-21-09(U)(1)(d)	VOC emissions from cleanup materials shall not exceed 0.45 tons per year.  The requirements of this rule also include compliance with the requirements of OAC rule 3745-21-09(U)(1)(d).
	OAC rule 3745-31-05(C) Synthetic Minor to avoid Title V, Nonattainment NSR, and MACT Subpart M	The VOC content of the coatings shall not exceed 3.50 pounds of VOC per gallon of coating, excluding water and exempt solvents.  See Additional Terms and Conditions A.2.a and A.2.b below.

**2. Additional Terms and Conditions**

**CMC  
PTI A**

Emissions Unit ID: **K003**

**Modification Issued: 12/26/2006**

- 2.a** VOC emissions from emissions units K001, K002, and K003 shall not exceed 95.85 TPY based upon a rolling, 12-month summation of emissions.
- 2.b** The total allowable emissions of Hazardous Air Pollutants (HAPs), as identified in Section 112(b) of Title III of the Clean Air Act, from emissions units K001, K002, and K003 shall not exceed 9.9 tons/year for any individual HAP or 24.9 tons/year for a combination of HAPs. Compliance with the above limitations shall be based upon a rolling, 12-month summation of emissions for this emissions unit plus the annual HAP contribution from all other emissions units at this facility (K001, K002, and K003).

**B. Operational Restrictions**

1. The maximum annual operating hours for emission units K001, K002, and K003 shall not exceed 18,000 collectively, based on a 12-month rolling summation of the operating hours.

To ensure enforceability during the first 12 calendar months of operation or the first 12 calendar months following the issuance of this permit, the permittee shall not exceed the operating hours levels specified in the following table:

<u>Month(s)</u>	<u>Maximum Allowable Cumulative Operating Hours for K001, K002, and K003 combined</u>
1	3,000
1-2	4,500
1-3	6,000
1-4	7,500
1-5	9,000
1-6	10,500
1-7	12,000
1-8	13,500
1-9	15,000
1-10	16,500
1-11	18,000
1-12	18,000

After the first 12 calendar months of operation or the first 12 calendar months following the issuance of this permit, compliance with the annual operating hours limitation shall

be based upon a rolling, 12-month summation of the operating hours.

2. The permittee shall keep all doors closed, in this emission unit's coating area, while conducting painting activities.

**C. Monitoring and/or Recordkeeping Requirements**

1. The permittee shall maintain daily records that document any time periods when doors were not closed in this emission unit's coating area, while painting activities were conducted.
2. The permittee shall collect and record the following information each day for this emissions unit:
  - a. the name and identification number of each coating employed and cleanup material dispensed;
  - b. the amount, in gallons, of each coating employed;
  - c. the amount, in gallons, of each cleanup material dispensed;
  - d. the VOC content of each coating and cleanup material, in pounds per gallon, as applied;
  - e. the total VOC emission rate for all coatings, in pounds and tons [summation of (b x d) for all coatings];
  - f. hours of operation;
  - g. average hourly emission rate, in pounds per hour (e/f);
  - h. the amount, in gallons, of cleanup material that is contained for disposal;
  - i. the total emission rate for cleanup material [d(c-h)], in pounds and tons; and
  - j. the VOC content of each coating, in pounds per gallon less water and exempt solvents, as applied.
3. The permittee shall collect and record the total VOC emissions from all coatings and cleanup materials employed for this emissions unit, for the purpose of determining annual VOC emissions (summation of daily emissions from C.2 above divided by 2000 lbs/ton).
4. The permittee shall collect and record from emissions units K001, K002, and K003 on a monthly basis, the rolling, 12-month summation of VOC emissions, in tons per year, for

Emissions Unit ID: **K003**

all coatings and cleanup materials. This shall include information for the current month and the preceding eleven calendar months. For the first twelve months following the issuance of the permit, this shall be a cumulative total for all months since the issuance of the PTI.

5. The permittee shall maintain monthly records of the following information for the facility (K001, K002, and K003):
  - a. the name and identification number of each HAP containing material employed;
  - b. the individual HAP content for each HAP, in pounds of individual HAP per gallon of material;
  - c. the total combined HAP content, in pounds of combined HAPs per gallon of material [sum all the individual HAP contents from (b)];
  - d. the number of gallons, of each HAP containing material employed;
  - e. the total individual HAP usage for each HAP from all HAP containing materials, in pounds or tons per month [for each HAP the sum of (b) times (c) for each material];
  - f. the total combined HAP usage from all HAP containing materials, in pounds or tons per month [the sum of (c) times (d) for each material];
  - g. the updated rolling, 12-month summation of usage and emissions for each individual HAP, in tons. This shall include the information for the current month and the preceding eleven calendar months. For the first twelve months following the issuance of the permit, this shall be a cumulative total for all months since the issuance of the PTI;
  - h. the updated rolling, 12-month summation of usage and emissions for the total combined HAPs, in tons. This shall include the information for the current month and the preceding eleven calendar months. For the first twelve months following the issuance of this permit, this shall be a cumulative total for all months since the issuance of the PTI;
  - i. the operating hours for each month; and
  - j. beginning after the first 12 calendar months of operation or the first 12 calendar months following the issuance of this permit, the rolling, 12 month summation of the operating hours.

**Modification Issued: 12/26/2006**

Also, during the first 12 calendar months of operation or the first 12 calendar months following the issuance of this permit, the permittee shall record the cumulative operating hours for each calendar month.

\* A listing of the HAPs can be found in Section 112(b) of the Clean Air Act or can be obtained by contacting your Cleveland Division of Air Quality (Cleveland DAQ) contact. This information does not have to be kept on an individual emission unit basis.

6. The permit to install for this emissions unit (K003) was evaluated based on the actual materials (typically coatings) and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant:

Pollutant: Xylene

TLV (mg/m<sup>3</sup>): 434.4

Maximum Hourly Emission Rate (lbs/hr): 24.9 lbs/hr (Total for K001, K002, and K003 combined)

Predicted 1-Hour Maximum Ground-Level

Concentration at the property line (µg/m<sup>3</sup>): 6,054

MAGLC (µg/m<sup>3</sup>): 10,342

Pollutant: MIBK

TLV (mg/m<sup>3</sup>): 204.9

Maximum Hourly Emission Rate (lbs/hr): 15.78 lbs/hr (Total for K001, K002, and K003 combined)

Predicted 1-Hour Maximum Ground-Level

Concentration at the property line (µg/m<sup>3</sup>): 3,837

MAGLC (µg/m<sup>3</sup>): 4,879

Pollutant: Ethyl benzene

TLV (mg/m<sup>3</sup>): 434.4

Maximum Hourly Emission Rate (lbs/hr): 14.43 lbs/hr (Total for K001, K002, and K003 combined)

Predicted 1-Hour Maximum Ground-Level

CMC - Kilroy Steel  
PTI Application: 12-04412  
Modif

Facility ID: 131800040

Emissions Unit ID: K003

Concentration at the property line ( $\mu\text{g}/\text{m}^3$ ): 3,509  
MAGLC ( $\mu\text{g}/\text{m}^3$ ): 10,342

Pollutant: Toluene  
TLV ( $\text{mg}/\text{m}^3$ ): 188.4  
Maximum Hourly Emission Rate ( $\text{lbs}/\text{hr}$ ): 3.21  $\text{lbs}/\text{hr}$  (Total for K001, K002, and K003 combined)  
Predicted 1-Hour Maximum Ground-Level  
Concentration at the property line ( $\mu\text{g}/\text{m}^3$ ): 780  
MAGLC ( $\mu\text{g}/\text{m}^3$ ): 4,486

Pollutant: Cumene  
TLV ( $\text{mg}/\text{m}^3$ ): 245.8  
Maximum Hourly Emission Rate ( $\text{lbs}/\text{hr}$ ): 15.78  $\text{lbs}/\text{hr}$  (Total for K001, K002, and K003 combined)  
Predicted 1-Hour Maximum Ground-Level  
Concentration at the property line ( $\mu\text{g}/\text{m}^3$ ): 299  
MAGLC ( $\mu\text{g}/\text{m}^3$ ): 4,879

7. Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:
- a. changes in the composition of the materials used (typically for coatings or cleanup materials), or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value previously modeled;
  - b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and
  - c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

**Modification Issued: 12/26/2006**

If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01 solely due to the emissions of any type of toxic air contaminant not previously emitted, and a modification of the existing permit to install will not be required, even if the toxic air contaminant emissions are greater than the de minimis level in OAC rule 3745-15-05. If the change(s) is (are) defined as a modification under other provisions of the modification definition, then the permittee shall obtain a final permit to install prior to the change.

8. The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy:"
  - a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
  - b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and
  - c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

#### **D. Reporting Requirements**

1. The permittee shall notify the Cleveland DAQ in writing of any daily record showing that the doors were not closed in this emission unit's coating area, while conducting painting activities. The notification shall include a copy of the record and shall be sent within 30 days after the event occurs.
2. The permittee shall notify the Cleveland DAQ in writing of any daily record showing the use of noncomplying coatings. The notification shall include a copy of such record and shall be sent to the Cleveland DAQ within 30 days following the end of the calendar month.
3. The permittee shall submit quarterly deviation (excursion) reports to the Cleveland DAQ that identify each day during which the average hourly VOC emissions from the coating operation exceeded 10.50 lbs/hr. Each report shall be submitted in accordance with the general terms and conditions within this permit.

**CMC - Kilroy Steel**  
**PTI Application: 13-04412**  
**Modif**

**Facility ID: 131800040**

**Emissions Unit ID: K003**

4. The permittee shall submit to the Cleveland DAQ, by January 31 of each year, an annual emissions report that specifies the total VOC emissions for this emissions unit.
5. The permittee shall submit deviation (excursion) reports for the entire facility (includes emissions units K001, K002, and K003) which include the following information:
  - a. an identification of each month during which the rolling, 12-month individual HAP emissions exceed 9.9 tpy (and combined HAPs emissions exceed 24.9 tpy) based on a rolling, 12-month summation and the actual rolling, 12-month individual (and combined) HAP emissions for each such month; and
  - b. an identification of all exceedances of the rolling, 12-month limitation of the hours of operation; and for the first 12 calendar months of operation or the first 12 calendar months following the issuance of this permit, all exceedances of the maximum allowable cumulative hours of operation.

These reports shall be submitted in accordance with the reporting requirements specified in Part 1 - General Terms and Conditions, Section A of this permit.

6. The permittee shall submit quarterly deviation (excursion) reports which identify all exceedances of the rolling, 12-month emission limitation for VOC from emissions units K001, K002, and K003. This written report shall be submitted to the Cleveland DAQ within 30 days of the occurrence of the deviation.

## **E. Testing Requirements**

1. Compliance with the emission limitation(s) in Section A.1 of these terms and conditions shall be determined in accordance with the following method(s):
  - a. Emission Limitation:  
VOC emissions shall not exceed 10.50 lbs/hr from coatings.  
  
Applicable Compliance Method:  
Compliance with the above daily emission limitation shall be determined by the record keeping as specified in Section C.2.
  - b. Emission Limitation:  
VOC emissions shall not exceed 45.99 tons per year from coatings.  
  
Applicable Compliance Method:

**Modification Issued: 12/26/2006**

Compliance with yearly emission limitation shall be determined by summing the daily emission rates and dividing by 2000 lbs/ton for each calendar year, as specified in Section C.3.

c. Emission Limitation:

The VOC content of the coatings shall not exceed 3.50 pounds of VOC per gallon of coating, excluding water and exempt solvents.

Applicable Compliance Method:

Compliance with the VOC limitation above shall be determined from the record keeping as specified in Section C.2.

Compliance may also be determined by calculating the VOC content in accordance with the equation specified in OAC Rule 3745-21-10(B)(9) for CVOC,2 for the daily volume-weighted average VOC content.

U.S. EPA Method 24 shall be used to determine the VOC contents of the coatings employed. The permittee may obtain the Method 24 analysis for each coating from the supplier.

d. Emission Limitation:

VOC emissions from cleanup materials shall not exceed 0.45 tons per year.

**Modification Issued: 12/26/2006**

Applicable Compliance Method:

Compliance with the VOC limitation above shall be determined from the record keeping as specified in Section C.3.

Formulation data shall be used to determine VOC content of the cleanup material.

- e. Emission Limitation:  
VOC emissions from emissions units K001, K002, and K003 shall not exceed 95.85 TPY based upon a rolling, 12-month summation of emissions.

Applicable Compliance Method:

Compliance shall be determined based upon the record keeping specified in section C.4.

- f. Emission Limitation:  
HAPs from emissions units K001, K002, and K003 shall not exceed 9.9 tons/year for any individual HAP.

Applicable Compliance Method:

Compliance shall be determined based upon the record keeping specified in section C.5.

- g. Emission Limitation:  
HAPs from emissions units K001, K002, and K003 shall not exceed 24.9 tons/year for a combination of HAPs.

Applicable Compliance Method:

Compliance shall be determined based upon the record keeping specified in section C.5.

## **F. Miscellaneous Requirements**

None.