



State of Ohio Environmental Protection Agency

STREET ADDRESS:

1800 WaterMark Drive
Columbus, OH 43215-1099

TELE: (614) 644-3020 FAX: (614) 644-2329

MAILING ADDRESS:

P.O. Box 1049
Columbus, OH 43216-1049

Re: Permit to Install
Wood County
Application No: 03-0137
NSPS
PSD
TOXIC REVIEW

CERTIFIED MAIL

RECEIVED

January 3, 1997

JAN 13 1997

DECOMA INTERNATIONAL OF AMERICA, INC.
RANDY SMALLBONE
26200 LAHSER ROAD, SUITE 300
SOUTHFIELD, MI 48034

OHIO E.P.A.
N.W.D.O.

Enclosed please find an Ohio EPA Permit to Install which will allow you to install the described source(s) in a manner indicated in the permit. Because this permit contains several conditions and restrictions I urge you to read it carefully.

The Ohio EPA is urging companies to investigate pollution prevention and energy conservation. Not only will this reduce pollution and energy consumption, but it can also save you money. If you would like to learn ways you can save money while protecting the environment, please contact our Office of Pollution Prevention at (614) 644-3469.

You are hereby notified that this action by the Director is final and may be appealed to the Ohio Environmental Board of Review pursuant to Chapter 3745.04 of the Ohio Revised Code. The appeal must be in writing and set forth the action complained of and the grounds upon which the appeal is based. It must be filed with the Environmental Board of Review within thirty (30) days after notice of the Director's action. A copy of the appeal must be served on the Director of the Ohio Environmental Protection Agency within three (3) days of filing with the Board. An appeal may be filed with the Environmental Board of Review at the following address:

Environmental Board of Review
236 East Town Street, Room 300
Columbus, Ohio 43215

Very truly yours,

Thomas G. Rigo, Manager
Field Operations & Permit Section
Division of Air Pollution Control

cc: US EPA
NORTHWEST DISTRICT OFFICE, DAPC

George V. Volnovich, Governor
Nancy P. Hollister, Lt. Governor
Donald R. Schrage, Director



Permit to Install Terms and Conditions

Application No. 03-0137
APS Premise No. 0387000362
Permit Fee: \$12800.00

Name of Facility: DECOMA INTERNATIONAL OF AMERICA, INC.

Person to Contact: RANDY SMALLBONE

Address: 26200 LAHSER ROAD, SUITE 300
SOUTHFIELD, MI 48034

Location of proposed source(s): 7825 CAPLE BLVD.
NORTHWOOD, OHIO

Description of proposed source(s):
13.5 MMBTU/HR NATURAL GAS BOILER, AUTO PLASTIC PARTS PAINT L
INE, 60 PAINT KETTLES AND MISCELLANEOUS CLEANUP OPERATIONS.


Date of Issuance: January 3, 1997

Effective Date: January 3, 1997

The above named entity is hereby granted a permit to install for the above described source(s) pursuant to Chapter 3745-31 of the Ohio Administrative Code. Issuance of this permit does not constitute expressed or implied approval or agreement that, if constructed or modified in accordance with the plans included in the application, the above described source(s) of environmental pollutants will operate in compliance with applicable State and Federal laws and regulations, and does not constitute expressed or implied assurance that if constructed or modified in accordance with those plans and specifications, the above described source(s) of pollutants will be granted the necessary permits to operate (air) or NPDES permits as applicable.

This permit is granted subject to the conditions attached hereto.

Ohio Environmental Protection Agency



Director

TERMINATION OF PERMIT TO INSTALL

Substantial construction for installation must take place within 18 months of the effective date of this permit. This deadline may be extended by up to 12 months if application is made to the Director within a reasonable time before the termination date and the party shows good cause for any such extension.

NOTICE OF INSPECTION

The Director of the Ohio Environmental Protection Agency, or his authorized representatives, may enter upon the premises of the above-named applicant during construction and operation at any reasonable time for the purpose of making inspections, conducting tests, or to examine records or reports pertaining to the construction, modification or installation of the source(s) of environmental pollutants identified within this permit.

CONSTRUCTION OF NEW SOURCES

The proposed source(s) shall be constructed in strict accordance with the plans and application submitted for this permit to the Director of the Ohio Environmental Protection Agency. There may be no deviation from the approved plans without the express, written approval of the Agency. Any deviations from the approved plans or the above conditions may lead to such sanctions and penalties as provided under Ohio law. Approval of these plans does not constitute an assurance that the proposed facilities will operate in compliance with all Ohio laws and regulations. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed sources are inadequate or cannot meet applicable standards.

If the construction of the proposed source(s) has already begun or has been completed prior to the date the Director of the Environmental Protection Agency approves the permit application and plans, the approval does not constitute expressed or implied assurance that the proposed facility has been constructed in accordance with the approved plans. The action of beginning and/or completing construction prior to obtaining the Director's approval constitutes a violation of Ohio Administrative Code (OAC) Rule 3745-31-02. Furthermore, issuance of the Permit to Install does not constitute an assurance that the proposed source will operate in compliance with all Ohio laws and regulations. Approval of the plans in any case is not to be construed as an approval of the facility as constructed and/or completed. Moreover, issuance of the Permit to Install is not to be construed as a waiver of any rights that the Ohio Environmental Protection Agency (or other persons)

DECOMA INTERNATIONAL OF AMERICA, INC.
Application No. 03-0137
Page 3 of 30
January 3, 1997

may have against the applicant for starting construction prior to the effective date of the permit. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed facilities prove to be inadequate or cannot meet applicable standards.

PERMIT TO INSTALL FEE

In accordance with Ohio Revised Code 3745.11, the specified Permit to Install fee must be remitted within 30 days of the effective date of this permit to install.

PUBLIC DISCLOSURE

The facility is hereby notified that this permit, and all agency records concerning the operation of this permitted source, are subject to public disclosure in accordance with OAC Rule 3745-49-03.

APPLICABILITY

This Permit to Install is applicable only to the contaminant sources identified. Separate application must be made to the Director for the installation or modification of any other contaminant sources.

BEST AVAILABLE TECHNOLOGY

As specified in OAC Rule 3745-31-05, all new sources must employ Best Available Technology (BAT). Compliance with the terms and conditions of this permit will fulfill this requirement.

PERMIT TO OPERATE APPLICATION

A Permit to Operate application must be submitted to the appropriate field office for each air contaminant source in this Permit to Install. In accordance with OAC Rule 3745-35-02, the application shall be filed no later than thirty days after commencement of operation.

SOURCE OPERATION AFTER COMPLETION OF CONSTRUCTION

This facility is permitted to operate each source described by this permit to install for a period of up to one year from the date the source commenced operation. This permission to operate is granted only if the facility complies with all requirements contained in this permit and all applicable air pollution laws, regulations, and policies.

AIR EMISSION SUMMARY

The air contaminant sources listed below comprise the Permit to Install for DECOMA INTERNATIONAL OF AMERICA, INC. located in Wood County. The sources listed below shall not exceed the emission limits/control requirements contained in the table. This condition in no way limits the applicability of any other state or federal regulations. Additionally, this condition does not limit the applicability of additional special terms and conditions of this permit.

<u>Ohio EPA Source Number</u>	<u>Source Identification Description</u>	<u>BAT Determination</u>	<u>Applicable Federal & OAC Rules</u>	<u>Permit Allowable Mass Emissions and/or Control/Usage Requirements</u>
B001	13.5 MMBTU/hr natural gas boiler	Compliance with the terms and conditions of this permit	3745-31-05 3745-17-07 3745-17-10 3745-23-06 40 CFR Part 60, Subpart Dc	0.18 lb PM ₁₀ /hr 0.81 ton PM ₁₀ /yr 0.020 lb PM/MMBTU 1.89 lbs NO _x /hr 8.28 tons NO _x /yr 0.14 lb NO _x /MMBTU 0.5 lb CO/hr 2.06 tons CO/yr 0.035 lb CO/MMBTU 0.008 lb SO ₂ /hr 0.04 ton SO ₂ /yr 0.0006 lb SO ₂ /MMBTU Opacity restrictions See Additional Special Terms and Conditions
R001	Paint Line	Compliance with emission limits and use of RTO and PTE. (See Additional Special Terms and Conditions.	3745-31-05 3745-21-07 (G) (2) 3745-17-11 3745-17-07	47.2 lbs OC/hr (stack) 18.8 tons OC/month (stack and fugitive from paint sludge) 398.8 tons OC/yr (stack and fugitive from paint sludge) 1.9 lbs PM ₁₀ /hr (incinerator stack) 8.5 tons PM ₁₀ /yr

<u>Ohio EPA Source Number</u>	<u>Source Identification Description</u>	<u>BAT Determination</u>	<u>Applicable Federal & OAC Rules</u>	<u>Permit Allowable Mass Emissions and/or Control/Usage Requirements</u>
				3.1 lbs NO _x /hr (incinerator stack) 18.99 tons NO _x /yr** 1.3 lbs CO/hr (incinerator stack) 5.7 tons CO/yr Opacity restrictions See Additional Special Terms and Conditions
P001	Miscellaneous cleanup operations	Compliance with emission limits and additional special terms and conditions and employing work practice techniques to minimize emissions	3745-31-05	85 tons OC/year
P002	Paint Kettle	Compliance with emission limits of this permit	3745-31-05 3745-21-07 (G) (2)	8 lbs OC/hr 40 lbs OC/day; 43.22 tons OC/yr* See Additional Special Terms and Conditions (C) (3) for calculation
P003	Paint Kettle	Compliance with emission limits of this permit	3745-31-05 3745-21-07 (G) (2)	8 lbs OC/hr 40 lbs OC/day; 43.22 tons OC/yr* See Additional Special Terms and Conditions (C) (3) for calculation

<u>Ohio EPA Source Number</u>	<u>Source Identification Description</u>	<u>BAT Determination</u>	<u>Applicable Federal & OAC Rules</u>	<u>Permit Allowable Mass Emissions and/or Control/Usage Requirements</u>
P004	Paint Kettle	Compliance with emission limits of this permit	3745-31-05 3745-21-07 (G) (2)	8 lbs OC/hr 40 lbs OC/day; 43.22 tons OC/yr* See Additional Special Terms and Conditions (C) (3) for calculation
P005	Paint Kettle	Compliance with emission limits of this permit	3745-31-05 3745-21-07 (G) (2)	8 lbs OC/hr 40 lbs OC/day; 43.22 tons OC/yr* See Additional Special Terms and Conditions (C) (3) for calculation
P006	Paint Kettle	Compliance with emission limits of this permit	3745-31-05 3745-21-07 (G) (2)	8 lbs OC/hr 40 lbs OC/day; 43.22 tons OC/yr* See Additional Special Terms and Conditions (C) (3) for calculation
P007	Paint Kettle	Compliance with emission limits of this permit	3745-31-05 3745-21-07 (G) (2)	8 lbs OC/hr 40 lbs OC/day; 43.22 tons OC/yr* See Additional Special Terms and Conditions (C) (3) for calculation
P008	Paint Kettle	Compliance with emission limits of this permit	3745-31-05 3745-21-07 (G) (2)	8 lbs OC/hr 40 lbs OC/day; 43.22 tons OC/yr* See Additional Special Terms and Conditions (C) (3) for calculation

<u>Ohio EPA Source Number</u>	<u>Source Identification Description</u>	<u>BAT Determination</u>	<u>Applicable Federal & OAC Rules</u>	<u>Permit Allowable Mass Emissions and/or Control/Usage Requirements</u>
P009	Paint Kettle	Compliance with emission limits of this permit	3745-31-05 3745-21-07 (G) (2)	8 lbs OC/hr 40 lbs OC/day; 43.22 tons OC/yr* See Additional Special Terms and Conditions (C) (3) for calculation
P010	Paint Kettle	Compliance with emission limits of this permit	3745-31-05 3745-21-07 (G) (2)	8 lbs OC/hr 40 lbs OC/day; 43.22 tons OC/yr* See Additional Special Terms and Conditions (C) (3) for calculation
P011	Paint Kettle	Compliance with emission limits of this permit	3745-31-05 3745-21-07 (G) (2)	8 lbs OC/hr 40 lbs OC/day; 43.22 tons OC/yr* See Additional Special Terms and Conditions (C) (3) for calculation
P012	Paint Kettle	Compliance with emission limits of this permit	3745-31-05 3745-21-07 (G) (2)	8 lbs OC/hr 40 lbs OC/day; 43.22 tons OC/yr* See Additional Special Terms and Conditions (C) (3) for calculation
P013	Paint Kettle	Compliance with emission limits of this permit	3745-31-05 3745-21-07 (G) (2)	8 lbs OC/hr 40 lbs OC/day; 43.22 tons OC/yr* See Additional Special Terms and Conditions (C) (3) for calculation

<u>Ohio EPA Source Number</u>	<u>Source Identification Description</u>	<u>BAT Determination</u>	<u>Applicable Federal & OAC Rules</u>	<u>Permit Allowable Mass Emissions and/or Control/Usage Requirements</u>
P014	Paint Kettle	Compliance with emission limits of this permit	3745-31-05 3745-21-07 (G) (2)	8 lbs OC/hr 40 lbs OC/day; 43.22 tons OC/yr* See Additional Special Terms and Conditions (C) (3) for calculation
P015	Paint Kettle	Compliance with emission limits of this permit	3745-31-05 3745-21-07 (G) (2)	8 lbs OC/hr 40 lbs OC/day; 43.22 tons OC/yr* See Additional Special Terms and Conditions (C) (3) for calculation
P016	Paint Kettle	Compliance with emission limits of this permit	3745-31-05 3745-21-07 (G) (2)	8 lbs OC/hr 40 lbs OC/day; 43.22 tons OC/yr* See Additional Special Terms and Conditions (C) (3) for calculation
P017	Paint Kettle	Compliance with emission limits of this permit	3745-31-05 3745-21-07 (G) (2)	8 lbs OC/hr 40 lbs OC/day; 43.22 tons OC/yr* See Additional Special Terms and Conditions (C) (3) for calculation
P018	Paint Kettle	Compliance with emission limits of this permit	3745-31-05 3745-21-07 (G) (2)	8 lbs OC/hr 40 lbs OC/day; 43.22 tons OC/yr* See Additional Special Terms and Conditions (C) (3) for calculation

<u>Ohio EPA Source Number</u>	<u>Source Identification Description</u>	<u>BAT Determination</u>	<u>Applicable Federal & OAC Rules</u>	<u>Permit Allowable Mass Emissions and/or Control/Usage Requirements</u>
P019	Paint Kettle	Compliance with emission limits of this permit	3745-31-05 3745-21-07 (G) (2)	8 lbs OC/hr 40 lbs OC/day; 43.22 tons OC/yr* See Additional Special Terms and Conditions (C) (3) for calculation
P020	Paint Kettle	Compliance with emission limits of this permit	3745-31-05 3745-21-07 (G) (2)	8 lbs OC/hr 40 lbs OC/day; 43.22 tons OC/yr* See Additional Special Terms and Conditions (C) (3) for calculation
P021	Paint Kettle	Compliance with emission limits of this permit	3745-31-05 3745-21-07 (G) (2)	8 lbs OC/hr 40 lbs OC/day; 43.22 tons OC/yr* See Additional Special Terms and Conditions (C) (3) for calculation
P022	Paint Kettle	Compliance with emission limits of this permit	3745-31-05 3745-21-07 (G) (2)	8 lbs OC/hr 40 lbs OC/day; 43.22 tons OC/yr* See Additional Special Terms and Conditions (C) (3) for calculation
P023	Paint Kettle	Compliance with emission limits of this permit	3745-31-05 3745-21-07 (G) (2)	8 lbs OC/hr 40 lbs OC/day; 43.22 tons OC/yr* See Additional Special Terms and Conditions (C) (3) for calculation

<u>Ohio EPA Source Number</u>	<u>Source Identification Description</u>	<u>BAT Determination</u>	<u>Applicable Federal & OAC Rules</u>	<u>Permit Allowable Mass Emissions and/or Control/Usage Requirements</u>
P024	Paint Kettle	Compliance with emission limits of this permit	3745-31-05 3745-21-07 (G) (2)	8 lbs OC/hr 40 lbs OC/day; 43.22 tons OC/yr* See Additional Special Terms and Conditions (C) (3) for calculation
P025	Paint Kettle	Compliance with emission limits of this permit	3745-31-05 3745-21-07 (G) (2)	8 lbs OC/hr 40 lbs OC/day; 43.22 tons OC/yr* See Additional Special Terms and Conditions (C) (3) for calculation
P026	Paint Kettle	Compliance with emission limits of this permit	3745-31-05 3745-21-07 (G) (2)	8 lbs OC/hr 40 lbs OC/day; 43.22 tons OC/yr* See Additional Special Terms and Conditions (C) (3) for calculation
P027	Paint Kettle	Compliance with emission limits of this permit	3745-31-05 3745-21-07 (G) (2)	8 lbs OC/hr 40 lbs OC/day; 43.22 tons OC/yr* See Additional Special Terms and Conditions (C) (3) for calculation
P028	Paint Kettle	Compliance with emission limits of this permit	3745-31-05 3745-21-07 (G) (2)	8 lbs OC/hr 40 lbs OC/day; 43.22 tons OC/yr* See Additional Special Terms and Conditions (C) (3) for calculation

<u>Ohio EPA Source Number</u>	<u>Source Identification Description</u>	<u>BAT Determination</u>	<u>Applicable Federal & OAC Rules</u>	<u>Permit Allowable Mass Emissions and/or Control/Usage Requirements</u>
P029	Paint Kettle	Compliance with emission limits of this permit	3745-31-05 3745-21-07 (G) (2)	8 lbs OC/hr 40 lbs OC/day; 43.22 tons OC/yr* See Additional Special Terms and Conditions (C) (3) for calculation
P030	Paint Kettle	Compliance with emission limits of this permit	3745-31-05 3745-21-07 (G) (2)	8 lbs OC/hr 40 lbs OC/day; 43.22 tons OC/yr* See Additional Special Terms and Conditions (C) (3) for calculation
P031	Paint Kettle	Compliance with emission limits of this permit	3745-31-05 3745-21-07 (G) (2)	8 lbs OC/hr 40 lbs OC/day; 43.22 tons OC/yr* See Additional Special Terms and Conditions (C) (3) for calculation
P032	Paint Kettle	Compliance with emission limits of this permit	3745-31-05 3745-21-07 (G) (2)	8 lbs OC/hr 40 lbs OC/day; 43.22 tons OC/yr* See Additional Special Terms and Conditions (C) (3) for calculation
P033	Paint Kettle	Compliance with emission limits of this permit	3745-31-05 3745-21-07 (G) (2)	8 lbs OC/hr 40 lbs OC/day; 43.22 tons OC/yr* See Additional Special Terms and Conditions (C) (3) for calculation

<u>Ohio EPA Source Number</u>	<u>Source Identification Description</u>	<u>BAT Determination</u>	<u>Applicable Federal & OAC Rules</u>	<u>Permit Allowable Mass Emissions and/or Control/Usage Requirements</u>
P034	Paint Kettle	Compliance with emission limits of this permit	3745-31-05 3745-21-07 (G) (2)	8 lbs OC/hr 40 lbs OC/day; 43.22 tons OC/yr* See Additional Special Terms and Conditions (C) (3) for calculation
P035	Paint Kettle	Compliance with emission limits of this permit	3745-31-05 3745-21-07 (G) (2)	8 lbs OC/hr 40 lbs OC/day; 43.22 tons OC/yr* See Additional Special Terms and Conditions (C) (3) for calculation
P036	Paint Kettle	Compliance with emission limits of this permit	3745-31-05 3745-21-07 (G) (2)	8 lbs OC/hr 40 lbs OC/day; 43.22 tons OC/yr* See Additional Special Terms and Conditions (C) (3) for calculation
P037	Paint Kettle	Compliance with emission limits of this permit	3745-31-05 3745-21-07 (G) (2)	8 lbs OC/hr 40 lbs OC/day; 43.22 tons OC/yr* See Additional Special Terms and Conditions (C) (3) for calculation
P038	Paint Kettle	Compliance with emission limits of this permit	3745-31-05 3745-21-07 (G) (2)	8 lbs OC/hr 40 lbs OC/day; 43.22 tons OC/yr* See Additional Special Terms and Conditions (C) (3) for calculation

<u>Ohio EPA Source Number</u>	<u>Source Identification Description</u>	<u>BAT Determination</u>	<u>Applicable Federal & OAC Rules</u>	<u>Permit Allowable Mass Emissions and/or Control/Usage Requirements</u>
P039	Paint Kettle	Compliance with emission limits of this permit	3745-31-05 3745-21-07 (G) (2)	8 lbs OC/hr 40 lbs OC/day; 43.22 tons OC/yr* See Additional Special Terms and Conditions (C) (3) for calculation
P040	Paint Kettle	Compliance with emission limits of this permit	3745-31-05 3745-21-07 (G) (2)	8 lbs OC/hr 40 lbs OC/day; 43.22 tons OC/yr* See Additional Special Terms and Conditions (C) (3) for calculation
P041	Paint Kettle	Compliance with emission limits of this permit	3745-31-05 3745-21-07 (G) (2)	8 lbs OC/hr 40 lbs OC/day; 43.22 tons OC/yr* See Additional Special Terms and Conditions (C) (3) for calculation
P042	Paint Kettle	Compliance with emission limits of this permit	3745-31-05 3745-21-07 (G) (2)	8 lbs OC/hr 40 lbs OC/day; 43.22 tons OC/yr* See Additional Special Terms and Conditions (C) (3) for calculation
P043	Paint Kettle	Compliance with emission limits of this permit	3745-31-05 3745-21-07 (G) (2)	8 lbs OC/hr 40 lbs OC/day; 43.22 tons OC/yr* See Additional Special Terms and Conditions (C) (3) for calculation

<u>Ohio EPA Source Number</u>	<u>Source Identification Description</u>	<u>BAT Determination</u>	<u>Applicable Federal & OAC Rules</u>	<u>Permit Allowable Mass Emissions and/or Control/Usage Requirements</u>
P044	Paint Kettle	Compliance with emission limits of this permit	3745-31-05 3745-21-07 (G) (2)	8 lbs OC/hr 40 lbs OC/day; 43.22 tons OC/yr* See Additional Special Terms and Conditions (C) (3) for calculation
P045	Paint Kettle	Compliance with emission limits of this permit	3745-31-05 3745-21-07 (G) (2)	8 lbs OC/hr 40 lbs OC/day; 43.22 tons OC/yr* See Additional Special Terms and Conditions (C) (3) for calculation
P046	Paint Kettle	Compliance with emission limits of this permit	3745-31-05 3745-21-07 (G) (2)	8 lbs OC/hr 40 lbs OC/day; 43.22 tons OC/yr* See Additional Special Terms and Conditions (C) (3) for calculation
P047	Paint Kettle	Compliance with emission limits of this permit	3745-31-05 3745-21-07 (G) (2)	8 lbs OC/hr 40 lbs OC/day; 43.22 tons OC/yr* See Additional Special Terms and Conditions (C) (3) for calculation
P048	Paint Kettle	Compliance with emission limits of this permit	3745-31-05 3745-21-07 (G) (2)	8 lbs OC/hr 40 lbs OC/day; 43.22 tons OC/yr* See Additional Special Terms and Conditions (C) (3) for calculation

<u>Ohio EPA Source Number</u>	<u>Source Identification Description</u>	<u>BAT Determination</u>	<u>Applicable Federal & OAC Rules</u>	<u>Permit Allowable Mass Emissions and/or Control/Usage Requirements</u>
P049	Paint Kettle	Compliance with emission limits of this permit	3745-31-05 3745-21-07 (G) (2)	8 lbs OC/hr 40 lbs OC/day; 43.22 tons OC/yr* See Additional Special Terms and Conditions (C) (3) for calculation
P050	Paint Kettle	Compliance with emission limits of this permit	3745-31-05 3745-21-07 (G) (2)	8 lbs OC/hr 40 lbs OC/day; 43.22 tons OC/yr* See Additional Special Terms and Conditions (C) (3) for calculation
P051	Paint Kettle	Compliance with emission limits of this permit	3745-31-05 3745-21-07 (G) (2)	8 lbs OC/hr 40 lbs OC/day; 43.22 tons OC/yr* See Additional Special Terms and Conditions (C) (3) for calculation
P052	Paint Kettle	Compliance with emission limits of this permit	3745-31-05 3745-21-07 (G) (2)	8 lbs OC/hr 40 lbs OC/day; 43.22 tons OC/yr* See Additional Special Terms and Conditions (C) (3) for calculation
P053	Paint Kettle	Compliance with emission limits of this permit	3745-31-05 3745-21-07 (G) (2)	8 lbs OC/hr 40 lbs OC/day; 43.22 tons OC/yr* See Additional Special Terms and Conditions (C) (3) for calculation

<u>Ohio EPA Source Number</u>	<u>Source Identification Description</u>	<u>BAT Determination</u>	<u>Applicable Federal & OAC Rules</u>	<u>Permit Allowable Mass Emissions and/or Control/Usage Requirements</u>
P054	Paint Kettle	Compliance with emission limits of this permit	3745-31-05 3745-21-07 (G) (2)	8 lbs OC/hr 40 lbs OC/day; 43.22 tons OC/yr* See Additional Special Terms and Conditions (C) (3) for calculation
P055	Paint Kettle	Compliance with emission limits of this permit	3745-31-05 3745-21-07 (G) (2)	8 lbs OC/hr 40 lbs OC/day; 43.22 tons OC/yr* See Additional Special Terms and Conditions (C) (3) for calculation
P056	Paint Kettle	Compliance with emission limits of this permit	3745-31-05 3745-21-07 (G) (2)	8 lbs OC/hr 40 lbs OC/day; 43.22 tons OC/yr* See Additional Special Terms and Conditions (C) (3) for calculation
P057	Paint Kettle	Compliance with emission limits of this permit	3745-31-05 3745-21-07 (G) (2)	8 lbs OC/hr 40 lbs OC/day; 43.22 tons OC/yr* See Additional Special Terms and Conditions (C) (3) for calculation
P058	Paint Kettle	Compliance with emission limits of this permit	3745-31-05 3745-21-07 (G) (2)	8 lbs OC/hr 40 lbs OC/day; 43.22 tons OC/yr* See Additional Special Terms and Conditions (C) (3) for calculation

<u>Ohio EPA Source Number</u>	<u>Source Identification Description</u>	<u>BAT Determination</u>	<u>Applicable Federal & OAC Rules</u>	<u>Permit Allowable Mass Emissions and/or Control/Usage Requirements</u>
P059	Paint Kettle	Compliance with emission limits of this permit	3745-31-05 3745-21-07 (G) (2)	8 lbs OC/hr 40 lbs OC/day; 43.22 tons OC/yr* See Additional Special Terms and Conditions (C) (3) for calculation
P060	Paint Kettle	Compliance with emission limits of this permit	3745-31-05 3745-21-07 (G) (2)	8 lbs OC/hr 40 lbs OC/day; 43.22 tons OC/yr* See Additional Special Terms and Conditions (C) (3) for calculation
P061	Paint Kettle	Compliance with emission limits of this permit	3745-31-05 3745-21-07 (G) (2)	8 lbs OC/hr 40 lbs OC/day; 43.22 tons OC/yr* See Additional Special Terms and Conditions (C) (3) for calculation

0.72 TPA OC each

* Combined OC emissions from all Kettles.

** Combined NOx from all combustion units associated with R001.

SUMMARY

TOTAL PERMIT TO INSTALL ALLOWABLE EMISSIONS

<u>Pollutant</u>	<u>Tons/Year</u>
Particulate matter (Less 10 micron)	9.31
Sulfur Dioxide	0.04
Nitrogen Oxide	27.27
Organic Compounds	527.02
Carbon Monoxide	7.76

NSPS REQUIREMENTS

The following sources are subject to the applicable provisions of the New Source Performance Standards (NSPS) as promulgated by the United States Environmental Protection Agency, 40 CFR Part 60.

<u>Source No.</u>	<u>Source Description</u>	<u>NSPS Regulation (Subpart)</u>
B001	13.5 MMBTU/hr natural gas fired boiler	Dc

The application and enforcement of these standards are delegated to the Ohio EPA. The requirements of 40 CFR Part 60 are also federally enforceable.

Pursuant to the NSPS, the source owner/operator is hereby advised of the requirement to report the following at the appropriate times:

- a. construction date (no later than 30 days after such date);
- b. anticipated start-up date (not more than 60 days or less than 30 days prior to such date);
- c. actual start-up date (within 15 days after such date); and
- d. date of performance testing (If required, at least 30 days prior to testing).

Reports are to be sent to:

Ohio Environmental Protection Agency
DAPC - Permit Management Unit
P.O. Box 163669
Columbus, OH 43216-3669

and OEPA Northwest District Office - DAPC
347 North Dunbridge Road
Bowling Green, Ohio 43402

PSD REQUIREMENTS

The source described in this Permit to Install is subject to the applicable provisions of the Prevention of Significant Deterioration (PSD) regulations as promulgated by the United States Environmental Protection Agency 40 CFR 52.21. The authority to apply and enforce the PSD regulations has been delegated to the Ohio Environmental Protection Agency. The terms and conditions of this permit and the requirements of the PSD regulations are also enforceable by the United States Environmental Protection Agency.

In accordance with 40 CFR 124.15, 124.19 and 124.20, the following shall apply: (1) the effective date of this permit shall be 30 days after the service of notice to any public commentors of the final decision to issue, modify, or revoke and re-issue the permit, unless the service of notice is by mail, in which case the effective date of the permit shall be 33 days after the service of

DECOMA INTERNATIONAL OF AMERICA, INC.
Application No. 03-0137
Page 19 of 30
January 3, 1997

notice; and (2) if an appeal is made to the Administrator of the United States Environmental Protection Agency, the effective date of the permit is suspended until such time as the appeal is resolved or denied.

RECORD(S) RETENTION AND AVAILABILITY

All records required by this Permit to Install shall be retained on file for a period of not less than three years unless otherwise indicated by Ohio Environmental Protection Agency. All records shall be made available to the Director, or any representative of the Director, for review during normal business hours.

REPORTING REQUIREMENTS

Unless otherwise specified, reports required by the Permit to Install need only be submitted to OEPA Northwest District Office - DAPC, 347 North Dunbridge Road, Bowling Green, Ohio 43402.

WASTE DISPOSAL

The owner/operator shall comply with any applicable state and federal requirements governing the storage, treatment, transport and disposal of any waste material generated by the operation of the sources.

MAINTENANCE OF EQUIPMENT

This source and its associated air pollution control system(s) shall be maintained regularly in accordance with good engineering practices and the recommendations of the respective manufacturers in order to minimize air contaminant emissions.

MALFUNCTION/ABATEMENT

In accordance with OAC RULE 3745-15-06, any malfunction of the source(s) or associated air pollution control system(s) shall be reported immediately to the OEPA Northwest District Office - DAPC, 347 North Dunbridge Road, Bowling Green, Ohio 43402.

Except as provided by OAC Rule 3745-15-06(A)(3), scheduled maintenance of air pollution control equipment that requires the shutdown or bypassing of air pollution control system(s) must be accompanied by the shutdown of the associated air pollution sources.

AIR POLLUTION NUISANCES PROHIBITED

The air contaminant source(s) identified in this permit may not cause a public nuisance in violation of OAC Rule 3745-15-07.

CONSTRUCTION COMPLIANCE CERTIFICATION

The applicant shall provide Ohio EPA with a written certification (see enclosed form) that the facility has been constructed in accordance with the Permit to Install application and the terms and conditions of the Permit to Install. The certification shall be provided to Ohio EPA upon completion of construction but prior to startup of the source.

ADDITIONAL SPECIAL TERMS AND CONDITIONS

A. Introduction

1. This permit to install (PTI) will allow Decoma International of America, Inc. to install a 13.5 MMBTU/HR natural gas fired boiler (Ohio EPA emissions unit B001), Miscellaneous Cleanup Operations (Ohio EPA emissions unit P001), Paint Mixing Kettles (Ohio EPA emissions units P002, P003, P004, P005, P006, P007, P008, P009, P010, P011, P012, P013, P014, P015, P016, P017, P018, P019, P020, P021, P022, P023, P024, P025, P026, P027, P028, P029, P030, P031, P032, P033, P034, P035, P036, P037, P038, P039, P040, P041, P042, P043, P044, P045, P046, P047, P048, P049, P050, P051, P052, P053, P054, P055, P056, P057, P058, P059, P060, P061), and a Bumper Paint Line (Ohio EPA emissions unit R001).

The Bumper Paint Line (R001) will consists of the following equipment beginning with parts entering a dual line: five stage washer (dual pass), blow off, dry off oven and tack off booth. The parts are then conveyed to either the Topcoat Line or the Prime Line.

The Topcoat Line consists of an adhesion promotor booth (water wash spray booth), flash off, cool down, 3 base coat booths (water wash), flash off, cool down, two clear coat booths (water wash), flash off and five bake oven zones and cool down.

The Prime Line consists of an adhesion promotor booth (water wash spray booth), flash off, one prime coat booth (water wash), flash off and five bake oven zones and cool down.

The emissions from operation of emissions unit R001 are controlled through use of a permanent total enclosure (PTE) which vents to a regenerative thermal oxidizer.

B. Applicable Emission Limitations and/or Control Requirements

1. All natural gas combusting emissions units at the facility were evaluated for emissions of Nitrogen Dioxide (NOx). In order to maintain the facilities NOx emissions below the PSD modeling trigger level of 40 tons the following emissions units, many of which are exempt from permitting per OAC 3745-31-03 (A)(1)(a) or (b) or (c), will employ low NOx burners and emit 0.081 lb. NOx/MMBTU.

<u>Unit Description</u>	<u>Total Heat Input (MMBTU)</u>	<u>Tons NOx/year</u>
Prime Dry off - Zone 1	1.6	0.57
Color Dry off - Zone 1	2.5	0.89
Color Dry off - Zone 2	1.6	0.57
Prime Bake Oven - Zone 1	1.3	0.46
Prime Bake Oven - Zone 2	0.8	0.28
Prime Bake Oven - Zone 3	1.5	0.53
Prime Bake Oven - Zone 4	1.5	0.53
Color Bake Oven - Zone 1	2.6	0.92
Color Bake Oven - Zone 2	2.6	0.92
Color Bake Oven - Zone 3	2.1	0.75
Color Bake Oven - Zone 4	3.5	1.24
Color Bake Oven - Zone 5	3.5	1.24
Thermal Incinerator	12.0	4.26
Bldg. Plant Air Makeup Units	25.0	8.87
Paint Kitchen Air Makeup Units	7.0	2.48
Office Air Handlers	3.0	1.06

The following two natural gas combusting emissions units will not employ Low NOx burners.

<u>Unit Description</u>	<u>Total Heat Input (MMBTU)</u>	<u>Tons NOx/Year</u>
Hot Water Heater (B001)	13.5	8.28
Process Air Makeup -	9.5	5.83
Fresh Air Supply House		
. Total NOx		39.68

2. Particulate matter emissions at the facility were evaluated to ensure emissions of Particulate Matter 10 microns and smaller (PM₁₀) did not exceed the PSD trigger level of 15 tons. All PM emissions will be assumed to be that of PM₁₀. Potential PM₁₀ emissions from the Paint Line were calculated based on the following formula:

$$\begin{aligned}
 \text{PM}_{10} &= \frac{60,000 \text{ dscf}}{\text{min}} \times \frac{60 \text{ min}}{\text{hr}} \times \frac{0.003 \text{ grain}}{\text{dscf}} \times \frac{1 \text{ lb}}{7000 \text{ grains}} \\
 &= 1.54 \text{ lbs/hr and } 6.8 \text{ tpy @ } 8760 \text{ hrs/yr}
 \end{aligned}$$

The other sources of PM₁₀ emissions at the facility are from combustion of natural gas. Based on the AP-42 emission factor for PM₁₀ and a plantwide heat input rate of 95 MM Btu/hr, the potential plantwide emissions of PM₁₀ will be 11.91 tpy.

3. Best Available Technology (BAT) for Ohio EPA emissions unit R001 is use of a permanent total enclosure (PTE) capturing exhaust gases from all paint booths, flash-off areas and bake ovens and exhausting to a regenerative thermal oxidizer (RTO) in combination with an exhaust recirculation system. The RTO shall provide that ninety five percent of the carbon in the organic material being incinerated is oxidized to carbon dioxide. BAT for paint application has been determined to be an automatic or robotic paint spray system using electrostatic applicators or equivalent technology.

The paint spray system will achieve transfer efficiencies of 35-50% with water wash particulate filtering.

C. Operational Restrictions

1. Boiler

The permittee shall combust only natural gas as fuel in the 13.5 MMBTU/hr boiler, Ohio EPA emissions unit B001.

2. Paint Line

The uncontrolled VOC content in the coatings used in the paint line, Ohio EPA emissions unit R001, shall not exceed the limits below based upon a monthly volume weighted average.

<u>Coating</u>	<u>lbs VOC/gal - water</u>
Adhesion Promoter	6.5
Primer	4.1
Basecoat	4.8
Clearcoat	4.0

At the time of permit issuance specific coatings to be employed were not determined thus VOC data supplied for the coatings had not been determined in accordance with USEPA methods. The permittee proposed coatings believed to contain maximum VOC contents. Prior to initial operation of the paint line the permittee shall submit in writing verification that the coatings being employed on the line have had the VOC contents determined in accordance with USEPA approved methods published in 40 CFR, Part 60, Appendix A. Currently the approved methods are EPA Method 24 - Surface Coatings or Method 24A - Printing Inks and related coatings.

3. Paint Kettles

The company shall calculate the uncontrolled OC emission rate (tons/month) from the paint kettles in accordance with the following:

$$E = \frac{\text{(Total gallons processed per month)} \times \text{(OC content (lbs/gal))} \times \text{(1.0\% OC Loss)}}{\text{(2000 lbs/ton)}}$$

where: E = OC emissions, tons/month

4. Miscellaneous Cleanup Operations

Cleanup solvent will be used throughout plant for many different applications, some of which are:

Main floor areas	Maintenance shop (cleaning tools)
Paint kitchen & storage, spills, etc.	Sludge area (major cleanup job)
Air supply hoses	Service of filter banks, repairs, etc.
General warehousing (minor cleanup)	Oven clean zone radiant
Cleaning recirculating fans	Tools - hand & production
Handrails, floors, walls	Doors & hardware
Spray guns, fittings, fans, pumps	Paint kettles & system

Due to the wide variety of cleaning taking place additional BAT review with regards to cleanup emissions is not necessary. The permittee does not currently plan to employ cleaning activities which would be subject to the requirements of Ohio Administrative Code 3745-21-09. The permittee has committed to actively pursue prevention and reduction of cleanup related emissions. The permittee has agreed to contact the office of Pollution Prevention for technical assistance with regards to reduction of these emissions.

The permittee shall submit an annual progress report by February 15 of each year which shall cover the progress achieved with regards to reducing miscellaneous cleanup emissions during the previous calendar year.

5. Toxics Policy

This permit allows for the use of the coatings and cleanup materials specified by the permittee in PTI number 03-0137. In conjunction with the best available technology requirements of OAC rule 3745-31-05, the n-butyl acetate, ethyl acetate, n-butyl alcohol, ethyl alcohol, ethylene glycol monobutyl ether acetate, heptane, isobutyl acetate, isobutyl alcohol, isopropyl alcohol, methyl alcohol, methyl ethyl ketone, methyl isobutyl ketone, n-propyl alcohol, toluene, and xylenes emission limitations specified in this permit were established in accordance with Ohio EPA's "Air Toxics Policy" and are based on both the coating and

cleanup material formulation data and the design parameters of the emissions unit's exhaust system, as specified in the application. Compliance with Ohio EPA's "Air Toxics Policy" was demonstrated for each pollutant based on the Trinity Consultants ISCST3, Version 1.12 model and a comparison of the predicted 1 hour maximum ground level concentration to the MAGLC. All toxic constituents were assumed to be emitted at the highest rate of any of the constituents (xylenes, 32.63 g/s). This resulted in a peak one-hour predicted concentration of 2,075.96 ug/M³, which was less than the MAGLC for each of the toxic constituents with the exception of ethylene glycol monobutyl ether acetate. This constituent was specifically ran at its calculated emission rate to determine a peak impact. The peak predicted concentration of this toxic was 58.66 ug/M³ (MAGLC = 571 ug/M³). The following table summarizes the results of the modeling for each pollutant:

<u>Pollutant</u>	<u>TLV (ug/m³)</u>	<u>Maximum Hourly Emission Rate (lbs/hr)</u>	<u>Predicted 1 Hour Maximum Ground-Level Concentration at the Fenceline (ug/m³)</u>	<u>Maximum Acceptable Ground-Level Concentration (MAGLC) (ug/m³)</u>
n-butyl acetate	710000	5.13	2075.96	16905
ethyl acetate	1440000	1.84	2075.96	34286
n-butyl alcohol	152000	3.24	2075.96	3619
ethyl alcohol	1880000	11.94	2075.96	44762
ethylene glycol monobutyl ether acetate	24000	0.76	58.66	571
heptane	1600000	0.60	2075.96	38095
isobutyl acetate	700000	0.60	2075.96	16667
isobutyl alcohol	150000	1.10	2075.96	3571
isopropyl alcohol	980000	14.60	2075.96	23333
methyl alcohol	260000	10.80	2075.96	6190
methyl ethyl ketone	590000	14.85	2075.96	14048
methyl isobutyl ketone	205000	1.60	2075.96	4881
n-propyl alcohol	500000	12.40	2075.96	11905
toluene	375000	9.20	2075.96	8929
xylenes	435000	32.63	2075.96	10357

Any of the following changes may be deemed a "modification" to the emissions unit and, as such, prior notification to and approval from the Ohio EPA Northwest District Office are required:

- a. any change in the composition of the coatings or cleanup materials, or the use of new coatings or cleanup materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled American Conference of Governmental Industrial Hygienists (ACGIH), than the lowest TLV value specified in the above table;

- b. any change to the emissions unit or its exhaust parameters (e.g., increased emission rate, reduction of exhaust gas flow rate, or decreased stack height) that would result in an exceedance of any MAGLC specified in the above table;
- c. a reduction in the TLV by the ACGIH for any of the coatings and cleanup materials that, at the maximum hourly emission rate specified in the above table, would result in an exceedance of the MAGLC; and
- d. any change to the emissions unit or its method of operation that would either require an increase in the emission limitation(s) established by this permit or would otherwise be considered a "modification" as defined in OAC rule 3745-31-01.

6. Thermal Incinerator Operational Restriction

The average temperature of the exhaust gases from the thermal incinerator, for any 3-hour block of time, shall not be more than 50 degrees Fahrenheit below the average temperature during the most recent emission test that demonstrated the emissions unit was in compliance.

7. Permanent Total Enclosure Operational Restriction

The permanent total enclosure shall be maintained under negative pressure, at a minimum pressure differential that is not less than the minimum pressure differential (inches of water) established during the most recent emission test that demonstrated the emissions unit was in compliance, whenever the emissions unit is in operation.

D. Monitoring and/or Record Keeping Requirements

1. Boiler, emissions unit B001

In accordance with NSPS subpart Dc, the permittee shall maintain daily records which show the amount of natural gas combusted for emissions unit B001.

2. Paint Line, emissions unit R001

The permittee shall collect and record the following information each day for the coating operation:

- a. the company identification for each coating and cleanup material employed;
- b. documentation on whether or not each coating and cleanup material is a photochemically reactive material;
- c. the number of gallons of each coating and cleanup material employed;

- d. the organic compound content of each coating and cleanup material, in pounds per gallon;
- e. the uncontrolled organic compound emission rate for each coating and cleanup material, in pounds per day;
- f. the total number of hours the emissions unit was in operation;
- g. the monthly organic emissions; and
- h. the organic emissions on a rolling, 12-month summation.

[Note: The coating information must be for the coatings as employed, including any thinning solvents added at the emissions unit. Also, the definitions of "photochemically reactive" and "nonphotochemically reactive" are based upon OAC rule 3745-21-01(C)(5).]

3. Paint Kettles, Emissions units P002 thru P061

The permittee shall collect and record the following information on a monthly basis for each coating:

- a. the company identification for each coating and cleanup material processed;
- b. the number of gallons of each coating processed;
- c. the organic compound content of each coating and cleanup material, in pounds per gallon;
- d. the organic emissions on a monthly basis, based on the formula provided in C(3); and
- e. the organic emissions on a rolling, 12-month summation.

4. Miscellaneous Cleanup Operations, Emission unit P001

The permittee shall collect and record the following information on a monthly basis:

- a. the number of gallons of each cleanup material employed;
- b. the organic compound content of cleanup material, in pounds per gallon;
- c. the monthly organic emissions; and
- d. the organic emissions on a rolling, 12-month summation.

5. Thermal Incinerator Temperature Monitoring and Recordkeeping Requirements

The permittee shall operate and maintain a continuous temperature monitor and recorder which measures and records the temperature of the exhaust gases from the thermal incinerator when the emissions unit is in operation. Units shall be in degrees Fahrenheit. The accuracy for each thermocouple, monitor, and recorder shall be guaranteed by the manufacturer to be within ± 1 percent of the temperature being measured or ± 5 degrees Fahrenheit, whichever is greater. The temperature monitor and recorder shall be installed, calibrated, operated and maintained in accordance with the manufacturer's recommendations, instructions and operating manuals.

The permittee shall collect and record the following information each day:

- a. the average temperature of the exhaust gases from the thermal incinerator during each of the 8 3-hour blocks of time during the day; and
- b. a log or record of operating time for the capture (collection) system, control device, monitoring equipment, and the associated emissions unit.

6. Permanent Total Enclosure Monitoring and Recordkeeping Requirements

The permittee shall install, maintain and operate monitoring devices and a recorder which simultaneously measure and record the pressure inside and outside the permanent total enclosure. The monitoring and recording devices shall be installed, calibrated, operated and maintained in accordance with the manufacturer's recommendations, instructions and operating manuals.

The permittee shall record and maintain the following information on a daily basis:

- a. the difference in pressure between the permanent total enclosure and the surrounding area(s); and
- b. a log or record of operating time for the capture (collection) system, control device, monitoring equipment, and the associated emissions unit.

E. Reporting Requirements

1. Thermal Incinerator Temperature Reporting Requirements

The permittee shall submit temperature deviation (exceedance) reports that identify all 3-hour blocks of

time during which the average temperature of the exhaust gases from the thermal incinerator does not comply with the temperature limitation specified above.

2. Permanent Total Enclosure Reporting Requirements

The permittee shall submit pressure differential deviation (exceedance) reports that identify all periods of time during which the permanent total enclosure was not maintained at the required differential pressure specified above.

3. Paint Line, Emissions unit R001, Reporting Requirements

The permittee shall submit deviation (exceedance) reports which include the following information:

- a. an identification of each day during which the average hourly controlled organic compound emission rate (from coatings and cleanup materials) exceeded 47.2 pounds per hour, and the actual average hourly controlled organic compound emission rate for each such day.

4. Paint Kettles, Emissions units P002 thru P061

The permittee shall submit deviation (exceedance) reports which include the following information:

- a. an identification of each day during which the average hourly organic compound emission rate (from coatings and cleanup materials) for each paint kettle (emissions unit) exceeded 8 pounds per hour, and the actual average hourly organic compound emission rate for each such day; and
- b. an identification of each day during which the organic compound emission rate (from coatings and cleanup materials) for each paint kettle (emissions unit) exceeded 40 pounds per day, and the actual organic compound emission rate for each such day.

5. Miscellaneous Cleanup Operations, Emissions unit P001

The permittee shall submit deviation (exceedance) reports which identify all exceedances of the annual emission limitation for P001.

F. Testing Requirements

The permittee shall conduct, or have conducted, emission testing for emissions unit R001 in accordance with the following requirements:

1. the emission testing shall be conducted to demonstrate compliance with the allowable mass emission rate(s) for OC and the capture efficiency and control efficiency limitations for OC;
2. the following test method(s) shall be employed to demonstrate compliance with the allowable mass emission rate(s): for OC, Method 25 of 40 CFR Part 60, Appendix A; and;
3. the test(s) shall be conducted while the emissions unit is operating at or near its maximum capacity, unless otherwise specified or approved by the Ohio EPA Northwest District Office.

The capture efficiency shall be determined using Methods 204 through 204F, as specified in 40 CFR Part 51, Appendix M, or the permittee may request to use an alternative method or procedure for the determination of capture efficiency in accordance with the USEPA's "Guidelines for Determining Capture Efficiency," dated January 9, 1995. (The Ohio EPA will consider the request, including an evaluation of the applicability, necessity, and validity of the alternative, and may approve the use of the alternative if such approval does not contravene any other applicable requirement.)

The control efficiency (i.e., the percent reduction in mass emissions between the inlet and outlet of the control system) shall be determined in accordance with the test methods and procedures specified in OAC rule 3745-21-10. The test methods and procedures selected shall be based on a consideration of the diversity of the organic species present and their total concentration, and on a consideration of the potential presence of interfering gases.

Not later than 30 days prior to the proposed test date(s), the permittee shall submit an "Intent to Test" notification to the Ohio EPA Northwest District Office. The "Intent to Test" notification shall describe in detail the proposed test methods and procedures, the emissions unit operating parameters, the time(s) and date(s) of the test(s), and the person(s) who will be conducting the test(s). Failure to submit such notification for review and approval prior to the test(s) may result in the Ohio EPA Northwest District Office's refusal to accept the results of the emission test(s).

Personnel from the Ohio EPA Northwest District Office shall be permitted to witness the test(s), examine the testing equipment, and acquire data and information necessary to ensure that the operation of the emissions unit and the testing procedures provide a valid characterization of the emissions from the emissions unit and/or the performance of the control equipment.

A comprehensive written report on the results of the emissions test(s) shall be signed by the person or persons responsible for the tests and submitted to the Ohio EPA Northwest District Office within 30 days following completion of the test(s).

The permittee shall conduct, or have conducted with methods approved by the Ohio EPA, emission testing for verification of the emissions estimates supplied by the permittee for emissions units R001 and P001 through P061.

4. Paint Kettles (P001 - P061)

The annual emissions estimate for these units was based on a percentage OC loss of the total OC in the coatings and cleanup materials processed. This testing is to verify the assumed OC emission loss of 1%. This factor was used to calculate the annual emission limit of 43.22 tons OC/year from all paint kettles combined.

5. Paint Line (R001)

The annual emissions attributed to paint booth sludge was based on a percentage of the total OC in the coatings and cleanup material processed. This testing is to verify 4.5% OC emission loss attributed to sludge. 1/2% of the 4.5% sludge emissions are assumed to be emitted on site. The total 4.5% OC sludge emissions result in 194.5 tons OC/year.

G. Miscellaneous Requirements

All records, as well as any supporting analysis, shall be retained in the company's files for a period of not less than five years and shall be made available to the Director or any authorized representative of the Director for review during the normal business hours. All reports are to be submitted to the Ohio EPA, Northwest District Office, Division of Air Pollution Control, 347 North Dunbridge Road, Bowling Green, Ohio 43402.