

John R. Kasich, Governor
Mary Taylor, Lt. Governor
Craig W. Butler, Interim Director

2/11/2014

Certified Mail

Daniel Crago
Valley Asphalt Corp. Plant 6
11641 MOSTELLER RD.
CINCINNATI, OH 45241

No	TOXIC REVIEW
No	SYNTHETIC MINOR TO AVOID MAJOR NSR
No	CEMS
No	MACT/GACT
Yes	NSPS
No	NESHAPS
No	NETTING
No	MODELING SUBMITTED
Yes	SYNTHETIC MINOR TO AVOID TITLE V
Yes	FEDERALLY ENFORCABLE PTIO (FEPTIO)
No	SYNTHETIC MINOR TO AVOID MAJOR GHG

RE: FINALAIR POLLUTION PERMIT-TO-INSTALL AND OPERATE

Facility ID: 0857101899
Permit Number: P0110404
Permit Type: Renewal
County: Montgomery

Dear Permit Holder:

Enclosed please find a final Ohio Environmental Protection Agency (EPA) Air Pollution Permit-to-Install and Operate (PTIO) which will allow you to install, modify, and/or operate the described emissions unit(s) in the manner indicated in the permit. Because this permit contains conditions and restrictions, please read it very carefully. In this letter you will find the information on the following topics:

- **How to appeal this permit**
- **How to save money, reduce pollution and reduce energy consumption**
- **How to give us feedback on your permitting experience**
- **How to get an electronic copy of your permit**

How to appeal this permit

The issuance of this PTIO is a final action of the Director and may be appealed to the Environmental Review Appeals Commission pursuant to Section 3745.04 of the Ohio Revised Code. The appeal must be in writing and set forth the action complained of and the grounds upon which the appeal is based. The appeal must be filed with the Commission within thirty (30) days after notice of the Director's action. The appeal must be accompanied by a filing fee of \$70.00, made payable to "Ohio Treasurer Josh Mandel," which the Commission, in its discretion, may reduce if by affidavit you demonstrate that payment of the full amount of the fee would cause extreme hardship. Notice of the filing of the appeal shall be filed with the Director within three (3) days of filing with the Commission. Ohio EPA requests that a copy of the appeal be served upon the Ohio Attorney General's Office, Environmental Enforcement Section. An appeal may be filed with the Environmental Review Appeals Commission at the following address:

Environmental Review Appeals Commission
77 South High Street, 17th Floor
Columbus, OH 43215

How to save money, reduce pollution and reduce energy consumption

The Ohio EPA is encouraging companies to investigate pollution prevention and energy conservation. Not only will this reduce pollution and energy consumption, but it can also save you money. If you would like to learn ways you can save money while protecting the environment, please contact our Office of Compliance Assistance and Pollution Prevention at (614) 644-3469. Additionally, all or a portion of the capital expenditures related to installing air pollution control equipment under this permit may be eligible for financing and State tax exemptions through the Ohio Air Quality Development Authority (OAQDA) under Ohio Revised Code Section 3706. For more information, see the OAQDA website: www.ohioairquality.org/clean_air

How to give us feedback on your permitting experience

Please complete a survey at www.epa.ohio.gov/survey.aspx and give us feedback on your permitting experience. We value your opinion.

How to get an electronic copy of your permit

This permit can be accessed electronically via the eBusiness Center: Air Services in Microsoft Word format or in Adobe PDF on the Division of Air Pollution Control (DAPC) Web page, www.epa.ohio.gov/dapc by clicking the "Search for Permits" link under the Permitting topic on the Programs tab.

If you have any questions, please contact Regional Air Pollution Control Agency at (937)225-4435 or the Office of Compliance Assistance and Pollution Prevention at (614) 644-3469.

Sincerely,



Michael W. Ahern, Manager

Permit Issuance and Data Management Section, DAPC

Cc: RAPCA



FINAL

**Division of Air Pollution Control
Permit-to-Install and Operate
for
Valley Asphalt Corp. Plant 6**

Facility ID:	0857101899
Permit Number:	P0110404
Permit Type:	Renewal
Issued:	2/11/2014
Effective:	2/11/2014
Expiration:	2/11/2019



Division of Air Pollution Control
Permit-to-Install and Operate
for
Valley Asphalt Corp. Plant 6

Table of Contents

Authorization	1
A. Standard Terms and Conditions	3
1. What does this permit-to-install and operate ("PTIO") allow me to do?.....	4
2. Who is responsible for complying with this permit?	4
3. What records must I keep under this permit?	4
4. What are my permit fees and when do I pay them?.....	4
5. When does my PTIO expire, and when do I need to submit my renewal application?	4
6. What happens to this permit if my project is delayed or I do not install or modify my source?	5
7. What reports must I submit under this permit?	5
8. If I am required to obtain a Title V operating permit in the future, what happens to the operating provisions and PER obligations under this permit?	5
9. What are my obligations when I perform scheduled maintenance on air pollution control equipment? ...	5
10. Do I have to report malfunctions of emissions units or air pollution control equipment? If so, how must I report?	6
11. Can Ohio EPA or my local air agency inspect the facility where the emission unit(s) is/are located?	6
12. What happens if one or more emissions units operated under this permit is/are shut down permanently?	6
13. Can I transfer this permit to a new owner or operator?.....	7
14. Does compliance with this permit constitute compliance with OAC rule 3745-15-07, "air pollution nuisance"?	7
15. What happens if a portion of this permit is determined to be invalid?	7
B. Facility-Wide Terms and Conditions.....	8
C. Emissions Unit Terms and Conditions	10
1. P001, Asphaltic Concrete Batch Plant - Plant #6.....	11



Final Permit-to-Install and Operate
Valley Asphalt Corp. Plant 6
Permit Number: P0110404
Facility ID: 0857101899
Effective Date: 2/11/2014

Authorization

Facility ID: 0857101899
Application Number(s): A0045048, A0045119
Permit Number: P0110404
Permit Description: Renewal FEPTIO for portable asphalt batch mix plant.
Permit Type: Renewal
Permit Fee: \$0.00
Issue Date: 2/11/2014
Effective Date: 2/11/2014
Expiration Date: 2/11/2019
Permit Evaluation Report (PER) Annual Date: Jan 1 - Dec 31, Due Feb 15

This document constitutes issuance to:

Valley Asphalt Corp. Plant 6
1901 DRYDEN RD.
Dayton, OH 45439

of a Permit-to-Install and Operate for the emissions unit(s) identified on the following page.


Ohio Environmental Protection Agency (EPA) District Office or local air agency responsible for processing and administering your permit:

Regional Air Pollution Control Agency
117 South Main Street
Dayton, OH 45422-1280
(937)225-4435

The above named entity is hereby granted this Permit-to-Install and Operate for the air contaminant source(s) (emissions unit(s)) listed in this section pursuant to Chapter 3745-31 of the Ohio Administrative Code. Issuance of this permit does not constitute expressed or implied approval or agreement that, if constructed or modified in accordance with the plans included in the application, the described emissions unit(s) will operate in compliance with applicable State and federal laws and regulations.

This permit is granted subject to the conditions attached hereto.

Ohio Environmental Protection Agency


Craig W. Butler
Interim Director



Final Permit-to-Install and Operate
Valley Asphalt Corp. Plant 6
Permit Number: P0110404
Facility ID: 0857101899
Effective Date: 2/11/2014

Authorization (continued)

Permit Number: P0110404

Permit Description: Renewal FEPTIO for portable asphalt batch mix plant.

Permits for the following Emissions Unit(s) or groups of Emissions Units are in this document as indicated below:

Emissions Unit ID:	P001
Company Equipment ID:	Asphaltic Concrete Batch Plant - Plant #6
Superseded Permit Number:	08-03262
General Permit Category and Type:	Not Applicable



Final Permit-to-Install and Operate
Valley Asphalt Corp. Plant 6
Permit Number: P0110404
Facility ID: 0857101899
Effective Date: 2/11/2014

A. Standard Terms and Conditions



1. What does this permit-to-install and operate ("PTIO") allow me to do?

This permit allows you to install and operate the emissions unit(s) identified in this PTIO. You must install and operate the unit(s) in accordance with the application you submitted and all the terms and conditions contained in this PTIO, including emission limits and those terms that ensure compliance with the emission limits (for example, operating, recordkeeping and monitoring requirements).

2. Who is responsible for complying with this permit?

The person identified on the "Authorization" page, above, is responsible for complying with this permit until the permit is revoked, terminated, or transferred. "Person" means a person, firm, corporation, association, or partnership. The words "you," "your," or "permittee" refer to the "person" identified on the "Authorization" page above.

The permit applies only to the emissions unit(s) identified in the permit. If you install or modify any other equipment that requires an air permit, you must apply for an additional PTIO(s) for these sources.

3. What records must I keep under this permit?

You must keep all records required by this permit, including monitoring data, test results, strip-chart recordings, calibration data, maintenance records, and any other record required by this permit for five years from the date the record was created. You can keep these records electronically, provided they can be made available to Ohio EPA during an inspection at the facility. Failure to make requested records available to Ohio EPA upon request is a violation of this permit requirement.

4. What are my permit fees and when do I pay them?

There are two fees associated with permitted air contaminant sources in Ohio:

PTIO fee. This one-time fee is based on a fee schedule in accordance with Ohio Revised Code (ORC) section 3745.11, or based on a time and materials charge for permit application review and permit processing if required by the Director.

You will be sent an invoice for this fee after you receive this PTIO and payment is due within 30 days of the invoice date. You are required to pay the fee for this PTIO even if you do not install or modify your operations as authorized by this permit.

Annual emissions fee. Ohio EPA will assess a separate fee based on the total annual emissions from your facility. You self-report your emissions in accordance with Ohio Administrative Code (OAC) Chapter 3745-78. This fee assessed is based on a fee schedule in ORC section 3745.11 and funds Ohio EPA's permit compliance oversight activities. For facilities that are permitted as synthetic minor sources, the fee schedule is adjusted annually for inflation. Ohio EPA will notify you when it is time to report your emissions and to pay your annual emission fees.

5. When does my PTIO expire, and when do I need to submit my renewal application?

This permit expires on the date identified at the beginning of this permit document (see "Authorization" page above) and you must submit a renewal application to renew the permit. Ohio EPA will send a renewal notice to you approximately six months prior to the expiration date of this permit. However, it is



very important that you submit a complete renewal permit application (postmarked prior to expiration of this permit) even if you do not receive the renewal notice.

If a complete renewal application is submitted before the expiration date, Ohio EPA considers this a timely application for purposes of ORC section 119.06, and you are authorized to continue operating the emissions unit(s) covered by this permit beyond the expiration date of this permit until final action is taken by Ohio EPA on the renewal application.

6. What happens to this permit if my project is delayed or I do not install or modify my source?

This PTIO expires 18 months after the issue date identified on the "Authorization" page above unless otherwise specified if you have not (1) started constructing the new or modified emission sources identified in this permit, or (2) entered into a binding contract to undertake such construction. This deadline can be extended by up to 12 months, provided you apply to Ohio EPA for this extension within a reasonable time before the 18-month period has ended and you can show good cause for any such extension.

7. What reports must I submit under this permit?

An annual permit evaluation report (PER) is required in addition to any malfunction reporting required by OAC rule 3745-15-06 or other specific rule-based reporting requirement identified in this permit. Your PER due date is identified in the Authorization section of this permit.

8. If I am required to obtain a Title V operating permit in the future, what happens to the operating provisions and PER obligations under this permit?

If you are required to obtain a Title V permit under OAC Chapter 3745-77 in the future, the permit-to-operate portion of this permit will be superseded by the issued Title V permit. From the effective date of the Title V permit forward, this PTIO will effectively become a PTI (permit-to-install) in accordance with OAC rule 3745-31-02(B). The following terms and conditions of this permit will no longer be applicable after issuance of the Title V permit: Section B, Term 1.b) and Section C, for each emissions unit, Term a)(2).

The PER requirements in this permit remain effective until the date the Title V permit is issued and is effective, and cease to apply after the effective date of the Title V permit. The final PER obligation will cover operations up to the effective date of the Title V permit and must be submitted on or before the submission deadline identified in this permit on the last day prior to the effective date of the Title V permit.

9. What are my obligations when I perform scheduled maintenance on air pollution control equipment?

You must perform scheduled maintenance of air pollution control equipment in accordance with OAC rule 3745-15-06(A). If scheduled maintenance requires shutting down or bypassing any air pollution control equipment, you must also shut down the emissions unit(s) served by the air pollution control equipment during maintenance, unless the conditions of OAC rule 3745-15-06(A)(3) are met. Any emissions that exceed permitted amount(s) under this permit (unless specifically exempted by rule) must be reported as deviations in the annual permit evaluation report (PER), including nonexempt excess emissions that occur during approved scheduled maintenance.



10. Do I have to report malfunctions of emissions units or air pollution control equipment? If so, how must I report?

If you have a reportable malfunction of any emissions unit(s) or any associated air pollution control system, you must report this to the [DO/LAA] in accordance with OAC rule 3745-15-06(B). Malfunctions that must be reported are those that result in emissions that exceed permitted emission levels. It is your responsibility to evaluate control equipment breakdowns and operational upsets to determine if a reportable malfunction has occurred.

If you have a malfunction, but determine that it is not a reportable malfunction under OAC rule 3745-15-06(B), it is recommended that you maintain records associated with control equipment breakdown or process upsets. Although it is not a requirement of this permit, Ohio EPA recommends that you maintain records for non-reportable malfunctions.

11. Can Ohio EPA or my local air agency inspect the facility where the emission unit(s) is/are located?

Yes. Under Ohio law, the Director or his authorized representative may inspect the facility, conduct tests, examine records or reports to determine compliance with air pollution laws and regulations and the terms and conditions of this permit. You must provide, within a reasonable time, any information Ohio EPA requests either verbally or in writing.

12. What happens if one or more emissions units operated under this permit is/are shut down permanently?

Ohio EPA can terminate the permit terms associated with any permanently shut down emissions unit. "Shut down" means the emissions unit has been physically removed from service or has been altered in such a way that it can no longer operate without a subsequent "modification" or "installation" as defined in OAC Chapter 3745-31.

You should notify Ohio EPA of any emissions unit that is permanently shut down by submitting a certification that identifies the date on which the emissions unit was permanently shut down. The certification must be submitted by an authorized official from the facility. You cannot continue to operate an emission unit once the certification has been submitted to Ohio EPA by the authorized official.

You must comply with all recordkeeping and reporting for any permanently shut down emissions unit in accordance with the provisions of the permit, regulations or laws that were enforceable during the period of operation, such as the requirement to submit a PER, air fee emission report, or malfunction report. You must also keep all records relating to any permanently shutdown emissions unit, generated while the emissions unit was in operation, for at least five years from the date the record was generated.

Again, you cannot resume operation of any emissions unit certified by the authorized official as being permanently shut down without first applying for and obtaining a permit pursuant to OAC Chapter 3745-31.



13. Can I transfer this permit to a new owner or operator?

You can transfer this permit to a new owner or operator. If you transfer the permit, you must follow the procedures in OAC Chapter 3745-31, including notifying Ohio EPA or the local air agency of the change in ownership or operator. Any transferee of this permit must assume the responsibilities of the transferor permit holder.

14. Does compliance with this permit constitute compliance with OAC rule 3745-15-07, "air pollution nuisance"?

This permit and OAC rule 3745-15-07 prohibit operation of the air contaminant source(s) regulated under this permit in a manner that causes a nuisance. Ohio EPA can require additional controls or modification of the requirements of this permit through enforcement orders or judicial enforcement action if, upon investigation, Ohio EPA determines existing operations are causing a nuisance.

15. What happens if a portion of this permit is determined to be invalid?

If a portion of this permit is determined to be invalid, the remainder of the terms and conditions remain valid and enforceable. The exception is where the enforceability of terms and conditions are dependent on the term or condition that was declared invalid.



Final Permit-to-Install and Operate
Valley Asphalt Corp. Plant 6
Permit Number: P0110404
Facility ID: 0857101899
Effective Date: 2/11/2014

B. Facility-Wide Terms and Conditions



Final Permit-to-Install and Operate

Valley Asphalt Corp. Plant 6

Permit Number: P0110404

Facility ID: 0857101899

Effective Date: 2/11/2014

1. This permit document constitutes a permit-to-install issued in accordance with ORC 3704.03(F) and a permit-to-operate issued in accordance with ORC 3704.03(G).
 - a) For the purpose of a permit-to-install document, the facility-wide terms and conditions identified below are federally enforceable with the exception of those listed below which are enforceable under state law only.
 - (1) None.
 - b) For the purpose of a permit-to-operate document, the facility-wide terms and conditions identified below are enforceable under state law only with the exception of those listed below which are federally enforceable.
 - (1) None.



Final Permit-to-Install and Operate
Valley Asphalt Corp. Plant 6
Permit Number: P0110404
Facility ID: 0857101899
Effective Date: 2/11/2014

C. Emissions Unit Terms and Conditions



1. P001, Asphaltic Concrete Batch Plant - Plant #6

Operations, Property and/or Equipment Description:

300 tons/hr, Hot Mix Asphalt Batch Plant; rotary dryer, hot aggregate elevator, vibrating screens, and weigh hopper, controlled with baghouse

a) This permit document constitutes a permit-to-install issued in accordance with ORC 3704.03(F) and a permit-to-operate issued in accordance with ORC 3704.03(G).

(1) For the purpose of a permit-to-install document, the emissions unit terms and conditions identified below are federally enforceable with the exception of those listed below which are enforceable under state law only.

a. None.

(2) For the purpose of a permit-to-operate document, the emissions unit terms and conditions identified below are enforceable under state law only with the exception of those listed below which are federally enforceable.

a. None.

b) **Applicable Emissions Limitations and/or Control Requirements**

(1) The specific operation(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures are identified below. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC rule 3754-31-05(A)(3) PTI 08-03262 issued 08/23/2007	Stack Emissions Particulate emissions (PE) while burning any approved fuel shall not exceed 2.88 tons/yr based on a rolling, 12-month summation of the monthly emissions. Sulfur dioxide (SO ₂) emissions while burning natural gas shall not exceed 0.0046 pound per ton of asphalt produced and 1.04 tons/yr based on a rolling, 12-month summation of the monthly emissions. SO ₂ emissions while burning No. 2 fuel oil or on-spec used oil shall not exceed 0.088 pound per ton of asphalt produced.



	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
		<p>Nitrogen Oxide (NOx) emissions while burning natural gas shall not exceed 0.025 pound per ton of asphalt produced and 5.63 tons/yr based on a rolling, 12-month summation of the monthly emissions.</p> <p>NOx emissions while burning No. 2 fuel oil or on-spec used oil shall not exceed 0.12 pound per ton of asphalt produced.</p> <p>Carbon monoxide emissions while burning any approved fuel shall not exceed 0.40 pound per ton of asphalt produced.</p> <p>Organic Compound (OC) emissions while burning natural gas or #2 fuel oil shall not exceed 0.015 pound per ton of asphalt produced and 3.38 tons/yr based on a rolling, 12-month summation of the monthly emissions.</p> <p>OC emissions while burning on-spec used oil shall not exceed 0.043 pound per ton of asphalt produced and 9.68 tons/yr based on a rolling, 12-month summation of the monthly emissions.</p> <p>The requirements established pursuant to this rule also include compliance with the requirements of NSPS 40 CFR Part 60 Subpart I and OAC rule 3745-31-05(D).</p> <p>See b)(2)e. and b)(2)f.</p>
b.	OAC rule 38745-17-07(A)	Visible emissions of fugitive dust from the enclosures for the hot aggregate elevator, vibrating screens, and weigh hopper shall not exceed 20 percent opacity, as a 3-minute average.
c.	OAC rule 3745-17-08(B)	The installation and use of adequate enclosures and sufficient draft to minimize or eliminate visible emissions of fugitive dust from the hot aggregate elevator, vibrating screens, and weigh hopper.



	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
d.	NSPS 40 CFR Part 60, Subpart I	<p>PE while burning any approved fuel from the stack shall not exceed 0.04 grains per dry standard cubic foot of exhaust gases.</p> <p>Visible PE from the stack shall not exceed 20 percent opacity, as a 6-minute average, from the stack, except as provided by 40 CFR Part 60.11.</p>
e.	OAC rule 3754-31-05(D) (Synthetic minor to avoid Title V)	<p>Sulfur dioxide (SO₂) emissions while burning No. 2 fuel oil or on-spec used oil shall not exceed 19.8 tons/yr. based on a rolling, 12-month summation of the monthly emissions.</p> <p>Nitrogen Oxide (NO_x) emissions while burning No. 2 fuel oil or on-spec used oil shall not exceed 27.0 tons/yr. based on a rolling, 12-month summation of the monthly emissions.</p> <p>Carbon monoxide (CO) emissions while burning any approved fuel shall not exceed 90.0 tons/yr. based on a rolling, 12-month summation of the monthly emissions.</p>
f.	OAC rule 3745-17-07(A), OAC rule 3745-18-06(E) and OAC rule 3745-17-11(B).	The emission limitations specified in these rules are less stringent than the emission limitation specified in 40 CFR Part 60, Subpart I and OAC rule 3754-31-05(A)(3).
Aggregate Storage Bins, Cold Aggregate Elevators, Plant Silo and Load-out		
g.	OAC rule 3745-31-05(A)(3)	<p>The drop height of the front end loader bucket shall be minimized to the extent possible in order to minimize or eliminate visible emissions of fugitive dust from the aggregate storage bins.</p> <p>The aggregate loaded into the cold aggregate bins shall have moisture content sufficient to minimize or eliminate visible emissions of fugitive dust from conveyors and all transfer points to the dryer.</p>



(2) Additional Terms and Conditions

- a. The maximum annual asphalt production rate for this emissions unit shall not exceed 450,000 tons per year based upon a rolling, 12-month summation of the production rates.
- b. The PE limitation specified above includes particulate matter (PM-10) emissions that are less than 10 microns in diameter.
- c. This emissions unit has been approved for the use of recycled asphalt pavement (RAP) and asphalt shingles.
- d. The emissions from this emissions unit shall be vented to the baghouse at all times the emissions unit is in operation.
- e. Each shipment of oil burned in this emissions unit shall be “on-specification” (on-spec) oil and shall meet the used oil specifications contained in OAC rule 3745-279-11. The permittee shall determine that the used fuel oil meets these specifications by performing analyses or obtaining copies of analyses or other information from the supplier documenting that the used fuel oil does not exceed (except for flash point which shall not fall below) the following limitations:

Contaminant/Property	Allowable Specifications
arsenic	5 ppm, maximum
cadmium	2 ppm, maximum
chromium	10 ppm, maximum
total halogens	less than 1,000 ppm; or 4,000 ppm maximum if the presumption that the used oil contains hazardous waste is rebutted, as described below
lead	100 ppm, maximum
flash point	100°F, minimum

and shall also not exceed the following maximum PCB and mercury limitations nor fall below the following heating value:

heat content	135,000 Btu/gallon, minimum
PCB's	less than 2 ppm
mercury	1 ppm, maximum



Used oil containing 1,000 ppm or greater total halogens is presumed to be a hazardous waste under the rebuttable presumption provided under paragraph (B)(1) of rule 3745-279-10 of the Administrative Code. The permittee may receive and burn used oil equaling or exceeding 1,000 ppm total halogens, but less than 4,000 ppm, only if the permittee has successfully demonstrated, pursuant to OAC rule 3745-279-63, that the used oil does not contain a listed hazardous waste, by either acquiring and maintaining source process information which demonstrates that the used oil was contaminated by halogenated constituents that would not be listed hazardous waste or by demonstrating that the used oil does not contain significant concentrations of halogens by acquiring and maintaining representative analytical data. Acceptable analytical test protocols that can be used to analyze used oil for halogenated hazardous constituents include SW-846 Test Methods 9075, 9076, and 9077.*

If analytical results demonstrate that used oil containing 1,000 ppm or more total halogens, but less than 4,000 total halogens, does not contain greater than 100 ppm of any individual halogenated hazardous constituent found in the listings in OAC rule 3745-51-31 and there is no information suggesting that any other halogenated hazardous constituent (e.g., chlorinated pesticides) has come in contact with the oil, then the presumption that the oil contains hazardous waste has been successfully rebutted.** The rebuttable presumption does not apply to either metal working oils/fluids containing chlorinated paraffins, if processed through a tolling arrangement as described in OAC rule 3745-279-24(C), or used oils contaminated with chlorofluorocarbons removed from refrigeration units.

The burning of used oil not meeting the above limitations is prohibited in this emissions unit and the fuel oil analyses shall document compliance with each limitation before it is burned. The management and burning of used oil is subject to the Standards for the Management of Used Oil, OAC Chapter 3745-279, and the permittee shall document and assure that used oils burned in this emissions unit meet all of the applicable requirements of this Chapter. If the used oil analyses shows total halogens of 1,000 ppm or greater, the permittee shall obtain and maintain all the necessary records to successfully rebut the presumption that the used oil contains or has been mixed with a listed hazardous waste in accordance with this permit.

*EPA publication SW-846, 3rd (or most current) edition, is available from the Government Printing Office, P.O. Box 371954, Pittsburgh, PA 15250-7954; 202/512-1800, document number 955-001-00000-1.

**Division of Materials and Waste Management policy documented in "Used Oil Burners - New Guidance for Rebuttable Presumption", published April 2008 or most current policy.

- f. All No. 2 fuel oil and on-spec used oil burned in this emission unit shall have a sulfur content equal to or less than 0.5 per cent, by weight.



c) Operational Restrictions

- (1) The permittee may not receive or burn any used oil which does not meet the specifications listed in OAC rule 3745-279-11 without first obtaining a permit-to-install and operate that authorizes the burning of off-specification used oil. The burning of off-specification used oil, subject to OAC rule 3745-279-60 through 67, is prohibited as a fuel in this emissions unit.
- (2) The permittee may substitute reclaimed asphalt pavement (RAP) and/or asphalt shingles in amounts not to exceed 50 percent of all aggregate materials in the raw material feed mix.
- (3) The permittee shall only use virgin aggregate, asphalt shingles and reclaimed asphalt pavement (RAP) in the raw material feed mix. For the purposes of this permit, virgin aggregate shall be clean, uncontaminated, quarried material.
- (4) Asphalt shingles removed from buildings (tear-off material) may be used but only if it has been determined that they do not contain asbestos. No asbestos containing asphalt shingles may be used as part of the feed mix. Verification that the shingles do not contain asbestos can either be done by actual testing of a representative sample of the shingles, or by verification from the shingle manufacturer that the shingles do not contain asbestos. Records shall be kept documenting the asbestos verification of any shingles used in the feed mix. These records shall be maintained in accordance with Section A.3. of the Standard Terms and Conditions.
- (5) The permittee shall only burn natural gas, No.2 fuel oil or on-spec used oil in this emissions unit.
- (6) The permittee shall operate and maintain the fuel burner in accordance with the manufacturer's recommendations to ensure efficient combustion of the fuel(s) and to ensure compliance with the applicable emission limitations for CO and NOx.

d) Monitoring and/or Recordkeeping Requirements

- (1) The permittee shall maintain monthly records of the following information:
 - a. the production rate for each month;
 - b. the total asphalt produced for each fuel type for each month;
 - c. the rolling, 12-month summation of the production rates;
 - d. the monthly PE, SO₂, NO_x, CO and OC emissions;
 - e. the rolling, 12-month summation of the PE, SO₂, NO_x, CO and OC emissions; and
 - f. The maximum percentage of RAP or asphalt shingles used for any mix type.



- (2) The permittee shall receive and maintain the chemical analyses from the supplier/marketer for each shipment of used oil burned in this emissions unit (or if the oil is generated on site, the permittee shall conduct the chemical analyses), which shall contain the following information:
- a. the date the used oil was received at the facility and the amount received;
 - b. the name, address, and U.S. EPA identification number (if applicable) of the generator, transporter, processor/refiner, supplier, and/or marketer;
 - c. the results of the following chemical analyses, demonstrating that the used oil meets the standards in OAC rule 3745-279-11 and does not contain quantifiable levels of PCBs:
 - i. arsenic content, in ppm;
 - ii. the cadmium content, in ppm;
 - iii. the chromium content, in ppm;
 - iv. the lead content, in ppm;
 - v. total halogens, in ppm;
 - vi. the flash point; and
 - vii. the PCB content, in ppm
 - d. where the chemical analysis shows a total halogen content between 1,000 ppm, and below 4,000 ppm, the successful demonstration for the rebuttal of the presumption that the used oil contains or has been mixed with a listed hazardous waste, as described in OAC rule 3745-279-63(C); and
 - e. the results of the analyses demonstrating that the used oil meets the heating value and the mercury and PCB limitations contained in this permit.

Each analysis shall be kept in a readily accessible location for a period of not less than 5 years* following the receipt of each shipment of used oil and shall be made available to the Ohio EPA Division of Materials and Waste Management and/or the Division of Air Pollution Control (the appropriate Ohio EPA District Office or local air agency) upon verbal or written request. Any authorized representative of the Ohio EPA may sample or require sampling of any used oil shipments received, stored, or burned by/at this facility for periodic detailed chemical analyses through an independent laboratory.

*The Division of Air Pollution Control requires these records to be maintained for 5 years.

- (3) For each shipment of No. 2 fuel oil and on-spec used oil received for burning in this emissions unit, the permittee shall maintain records of the total quantity of oil received and the permittee's or oil supplier's analyses for sulfur content and heat content.



- (4) In order to maintain compliance with the applicable emission limitation(s) contained in this permit, the acceptable range established for the pressure drop across the baghouse is between 2 to 6 inches of water.
- (5) The permittee shall properly install, operate, and maintain equipment to continuously monitor the pressure drop, in inches of water, across the baghouse when the controlled emissions unit is in operation, including periods of startup and shutdown. The permittee shall record the pressure drop across the baghouse on a daily basis. The monitoring equipment shall be installed, calibrated, operated, and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual(s).

Whenever the monitored value for the pressure drop deviates from the limit or range established in accordance with this permit, the permittee shall promptly investigate the cause of the deviation. The permittee shall maintain records of the following information for each investigation:

- a. the date and time the deviation began;
- b. the magnitude of the deviation at that time;
- c. the date the investigation was conducted;
- d. the name(s) of the personnel who conducted the investigation; and
- e. the findings and recommendations.

In response to each required investigation to determine the cause of a deviation, the permittee shall take prompt corrective action to bring the operation of the control equipment within the acceptable range specified in this permit, unless the permittee determines that corrective action is not necessary and documents the reasons for that determination and the date and time the deviation ended. The permittee shall maintain records of the following information for each corrective action taken:

- f. a description of the corrective action;
- g. the date corrective action was completed;
- h. the date and time the deviation ended;
- i. the total period of time (in minutes) during which there was a deviation;
- j. the pressure drop readings immediately after the corrective action was implemented; and
- k. the name(s) of the personnel who performed the work.

Investigation and records required by this paragraph do not eliminate the need to comply with the requirements of OAC rule 3745-15-06 if it is determined that a malfunction has occurred.



This range or limit on the pressure drop across the baghouse is effective for the duration of this permit, unless revisions are requested by the permittee and approved in writing by the appropriate Ohio EPA District Office or local air agency. The permittee may request revisions to the permitted limit or range for the pressure drop based upon information obtained during future testing that demonstrate compliance with the allowable particulate emission rate for the controlled emissions unit. In addition, approved revisions to the range or limit will not constitute a relaxation of the monitoring requirements of this permit and may be incorporated into this permit by means of an administrative modification.

- (6) The permittee shall perform burner tuning in accordance with term f)(2). While performing each burner tuning, the permittee shall record the results of the burner tuning using the *Burner Tuning Reporting Form for Asphalt Concrete Plants* form (as found in term g)(1) below). An alternative form may be used upon approval of the appropriate Ohio EPA District Office or local air agency.
- (7) Each record of burner tuning shall be kept in a readily accessible location and shall be made available to the Ohio EPA Division of Air Pollution Control (the appropriate Ohio EPA District Office or local air agency) upon verbal or written request.
- (8) The permittee shall perform daily checks, when the emissions unit is in operation and when the weather conditions allow, for any visible particulate emissions from the stack and for any visible emissions of fugitive dust from the rotary drum, hot mix asphalt elevator other areas serving this emissions unit. The presence or absence of any visible emissions shall be noted in an operations log. If visible emissions are observed, the permittee shall also note the following in the operations log:
 - a. the location and color of the emissions;
 - b. whether the emissions are representative of normal operations;
 - c. if the emissions are not representative of normal operations, the cause of the abnormal emissions;
 - d. the total duration of any visible emissions incident; and
 - e. any corrective actions taken to minimize or eliminate the visible emissions.

If visible emissions are present, a visible emissions incident has occurred. The observer does not have to document the exact start and end times for the visible emissions incident under item (d) above or continue the daily check until the incident has ended. The observer may indicate that the visible emissions incident was continuous during the observation period (or, if known, continuous during the operation of the emissions unit). With respect to the documentation of corrective actions, the observer may indicate that no corrective actions were taken if the visible emissions were representative of normal operations, or specify the minor corrective actions that were taken to ensure that the emissions unit continued to operate under normal conditions, or specify the corrective actions that were taken to eliminate abnormal visible emissions.



- (9) The permittee may, upon receipt of written approval from the appropriate Ohio EPA District Office or local air agency, modify the above-mentioned frequencies for performing the visible emissions checks if operating experience indicates that less frequent visible emissions checks would be sufficient to ensure compliance with the above-mentioned applicable requirements.

e) Reporting Requirements

- (1) All applications, notifications or reports required by terms and conditions in this permit to be submitted or "reported in writing" are to be submitted to Ohio EPA through the Ohio EPA's eBusiness Center: Air Services web service ("Air Services"). Ohio EPA will accept hard copy submittals on an as-needed basis if the permittee cannot submit the required documents through the Ohio EPA eBusiness Center. In the event of an alternative hard copy submission in lieu of the eBusiness Center, the post-marked date or the date the document is delivered in person will be recognized as the date submitted. Electronic submission of applications, notifications, or reports required to be submitted to Ohio EPA fulfills the requirement to submit the required information to the Director, the District Office or Local Air Agency, and/or any other individual or organization specifically identified as an additional recipient identified in this permit unless otherwise specified. Consistent with OAC rule 3745-15-03, the required application, notification or report is considered to be "submitted" on the date the submission is successful using a valid electronic signature. Signature by the signatory authority may be represented as provided through procedures established in Air Services.
- (2) The permittee shall notify the U.S. EPA and the Ohio EPA Division of Hazardous Waste Management and the RAPCA, in writing and within 30 days, of burning any used oil exceeding the limitations found in OAC rule 3745-279-11 and/or any incident or occurrence of non-compliance with any other applicable requirement of OAC Chapter 3745-279 and/or 40 CFR part 761 (as specified in term b)(2)e; and shall also notify the appropriate Ohio EPA District Office or local air agency, within the same amount of time, if any oil is/was burned which exceeds the mercury limitation of 1 ppm and/or is documented as having a heating value of less than 135,000 Btu/gallon.
- (3) The permittee shall submit quarterly deviation (excursion) reports that identify:
 - a. all deviations (excursions) of the following emission limitations, operational restrictions and/or control device operating parameter limitations that restrict the Potential to Emit (PTE) of any regulated air pollutant and have been detected by the monitoring, record keeping and/or testing requirements in this permit:
 - i. all exceedances of the rolling, 12-month asphalt production limitation;
 - ii. all exceedances of the rolling 12-month total PE, SO₂, NO_x, OC and CO emission limitations;
 - iii. any exceedances of the used oil standards in OAC rule 3745-279-11;



- iv. any occasion where used oil containing 1,000 ppm or more total halogens was burned prior to receiving information demonstrating a successful rebuttal of the presumption that the used oil contains or has been mixed with a listed hazardous waste;
 - v. any exceedance of the limitations for mercury and/or PCB; and
 - vi. any deviation from the minimum heat content of 135,000 Btu/gallon;
- b. any corrective actions that were taken to remedy the deviations (excursions) or prevent future deviations (excursions); and
 - c. the magnitude and duration of each deviation (excursion).

If no deviations (excursions) occurred during a calendar quarter, the permittee shall submit a report that states that no deviations (excursions) occurred during the quarter.

The quarterly reports shall be submitted each year by January 31 (covering October to December), April 30 (covering January to March), July 31 (covering April to June), and October 31 (covering July to September), unless an alternative schedule has been established and approved by the Director (the appropriate District Office or local air agency).

- (4) Where the analytical results for any shipment of used oil burned in this emissions unit establish that the used oil contains total halogens greater than 1,000 ppm, but less than 4,000 ppm, the results of the analysis for total halogens (from the appropriate test Method 9075, 9076, or 9077) and the information obtained to rebut the presumption that the used oil contains or has been mixed with a listed hazardous waste shall be submitted to the appropriate District Office or local air agency. Each rebuttal demonstration shall include:
 - a. the date the used oil was received;
 - b. the facility location or identification number where the oil was or will be burned;
 - c. the amount of oil in the shipment; and
 - d. all information, including all the analytical results, relied upon by the permittee to rebut the presumption that the used oil contains or has been mixed with a listed hazardous waste.

The rebuttal demonstrations for used oil received from October to December shall be submitted by January 31; used oil received from January to March, by April 30; used oil received from April to June, by July 31; and used oil received from July to September, by October 31.

- (5) The permittee shall identify in the annual permit evaluation report the following information concerning the operations of the baghouse during the 12-month reporting period for this emissions unit:



- a. each period of time (start time and date, and end time and date) when the pressure drop across the bag house was outside of the acceptable range;
 - b. any period of time (start time and date, and end time and date) when the emissions unit(s) was/were in operation and the process emissions were not vented to the bag house;
 - c. each incident of deviation described in e)(5)a. where a prompt investigation was not conducted;
 - d. each incident of deviation described in e)(5)a. where prompt corrective action, that would bring the pressure drop into compliance with the acceptable range, was determined to be necessary and was not taken; and
 - e. each incident of deviation described in e)(5)a. where proper records were not maintained for the investigation and/or the corrective action(s), as identified in the monitoring and record keeping requirements of this permit.
 - f. all days during which any visible particulate emissions were observed from the stack serving this emissions unit;
 - g. all days during which any visible emissions of fugitive dust were observed from the rotary drum, hot mix asphalt elevator other areas serving this emissions unit; and
 - h. any corrective actions taken to minimize or eliminate the visible particulate emissions from the stack and/or visible emissions of fugitive dust.
- (6) The permittee shall submit an annual Permit Evaluation Report (PER) to the Ohio EPA. The PER must be submitted by the due date identified in the Authorization section of this permit. The permit evaluation report shall cover a reporting period of no more than twelve months for each air contaminant source identified in this permit.
- f) **Testing Requirements**
- (1) Compliance with the Emissions Limitations and/or Control Requirements specified in section b)(1) of these terms and conditions shall be determined in accordance with the following methods:
- a. Emission Limitation-
 - PE while burning any approved fuel from the stack shall not exceed 0.04 grains per dry standard cubic foot of exhaust gases;
 - SO₂ emissions while burning natural gas shall not exceed 0.0046 pound per ton of asphalt produced;
 - SO₂ emissions while burning No. 2 fuel oil or on-spec used oil shall not exceed 0.088 pound per ton of asphalt produced;



NO_x emissions while burning natural gas shall not exceed 0.025 pound per ton of asphalt produced;

NO_x emissions while burning No. 2 fuel oil or on-spec used oil shall not exceed 0.12 pound per ton of asphalt produced;

CO emissions while burning any approved fuel shall not exceed 0.40 pound per ton of asphalt produced;

OC emissions while burning natural gas or No. 2 fuel oil shall not exceed 0.015 pound per ton of asphalt produced

OC emissions while burning on-spec used oil shall not exceed 0.043 pound per ton of asphalt produced.

Applicable Compliance Method-

Emissions testing shall be conducted to demonstrate compliance with the allowable mass emissions rate for PE, OC, CO, NO_x and SO₂ for the primary fuel in the appropriate averaging period(s). When requested, testing shall be conducted to demonstrated compliance for other approved fuels, also.

An emissions test shall be conducted within 60 days after startup for the 2014 asphalt production year. An emissions test shall be conducted the during the asphalt production year prior to expiration of this permit. Following tests shall be conducted on a 60 month schedule.

The following test methods shall be employed to demonstrate compliance with the allowable mass emission rates:

PE: Reference Test Methods 1-5

NO_x: Reference Test Methods 1-4 and 7 or 7E

SO₂: Reference Test Methods 1-4 and 6 or 6C

CO: Reference Test Methods 1-4 and 10

OC: Reference Test Methods 1-4, 25, 25A and/or 18

VE: Reference Test Method 9

Alternative U.S. EPA approved test methods may be used with prior approval from the Ohio EPA or Appropriate Ohio EPA District or local air agency.

The test(s) shall be conducted while the emissions unit is operating at or near its maximum capacity and burning natural gas, No. 2 fuel or on-spec used oil for PE, OC, CO, NO_x and SO₂ and employing RAP, unless otherwise specified or approved by the Appropriate Ohio EPA District or local air agency.



Not later than 60 days prior to the proposed test date(s), the permittee shall submit an "Intent to Test" notification to the appropriate Ohio EPA District Office or local air agency. The "Intent to Test" notification shall describe in detail the proposed test methods and procedures, the emissions unit operating parameters, the time(s) and date(s) of the test(s), and the person(s) who will be conducting the test(s). Failure to submit such notification for review and approval prior to the test(s) may result in the Appropriate Ohio EPA District or local air agency's refusal to accept the results of the emission test(s).

Personnel from the appropriate Ohio EPA District Office or local air agency shall be permitted to witness the test(s), examine the testing equipment, and acquire data and information necessary to ensure that the operation of the emissions unit and the testing procedures provide a valid characterization of the emissions from the emissions unit and/or the performance of the control equipment.

A comprehensive written report on the results of the emissions test(s) shall be signed by the person or persons responsible for the tests and submitted to the appropriate Ohio EPA District Office or local air agency within 30 days following completion of the test(s). The permittee may request additional time for the submittal of the written report, where warranted, with prior approval from the appropriate Ohio EPA District Office or local air agency.

b. Emissions Limitation:

The PE from this emissions unit shall not exceed 2.88 tons/year based on a rolling, 12-month summation of the monthly emissions.

Applicable Compliance Method:

This limitation was determined by multiplying the 12-month production summation by the facility based emission factor of 0.0128 lb PM/ton of asphalt production determined from compliance emissions testing conducted on 4/27/99 and dividing by 2,000 lbs/ton.

Compliance shall be determined by multiplying the observed emission rate from the most recent emissions testing, in pounds of PE per ton of asphalt produced for each fuel by the actual rolling 12 month summation of asphalt produced for each fuel, in tons per rolling 12-month period as derived from the records required by d)(1) and dividing by 2000 lbs/ton.

c. Emissions Limitation:

SO₂ emissions from this emission unit while burning natural gas shall not 1.04 tons/yr based on a rolling, 12-month summation of the monthly emissions.

This limitation was determined by multiplying the 12-month production summation by the emission factor of 0.0046 lb SO₂/ton of asphalt production while burning natural gas (AP-42 Section 11.1: Hot Mix Asphalt Plants, Table 11.1-5, 03/04) and dividing by 2,000 lbs/ton.



Compliance shall be determined by multiplying the observed emission rate from the most recent emissions testing, in pounds of SO₂ per ton of asphalt produced, by the actual rolling 12 month summation of asphalt produced for each fuel, in tons per rolling 12-month period, as derived from the records required by d)(1) and dividing by 2000 lbs/ton.

d. Emissions Limitation:

The SO₂ emissions from this emission unit while burning No. 2 fuel oil or used oil shall not exceed 19.8 tons/year based on a rolling, 12-month summation.

Applicable Compliance Method:

This limitation was determined by multiplying the 12-month production summation by the emission factor of 0.088 lb SO₂/ton of asphalt production while burning No. 2 fuel oil or on-spec used oil (AP-42 Section 11.1: Hot Mix Asphalt Plants, Table 11.1-5, 03/04) and dividing by 2,000 lbs/ton.

Compliance shall be determined by multiplying the observed emission rate from the most recent emissions testing, in pounds of SO₂ per ton of asphalt produced by the actual rolling 12 month summation of asphalt produced, in tons per rolling 12-month period, as derived from the records required by d)(1) and dividing by 2000 lbs/ton.

e. Emissions Limitation:

The NO_x emissions while burning natural gas shall not exceed 5.63 tons/yr based on a rolling, 12-month summation of the monthly emissions.

Applicable Compliance Method:

This limitation was determined by multiplying the 12-month production summation by the emission factor of 0.025 lbNO_x/ton of asphalt production while burning natural gas (AP-42 Section 11.1: Hot Mix Asphalt Plants, Table 11.1-5, 03/04), and dividing by 2,000 lbs/ton.

Compliance shall be determined by multiplying the observed emission rate from the most recent emissions testing, in pounds of NO_x per ton of asphalt produced, by the actual rolling 12 month summation of asphalt produced, in tons per rolling 12-month period, as derived from the records required by d)(1) and dividing by 2000 lbs/ton.

f. Emissions Limitation:

The NO_x emissions from this emission unit while burning No. 2 fuel oil or used oil shall not exceed 27.0 tons/year based on a rolling, 12-month summation of the monthly emissions.



Applicable Compliance Method:

This limitation was determined by multiplying the 12-month production summation by the emission factor of 0.12 lbNO_x/ton of asphalt production while burning No. 2 fuel oil or used oil (AP-42 Section 11.1: Hot Mix Asphalt Plants, Table 11.1-5, 03/04), and dividing by 2,000 lbs/ton.

Compliance shall be determined by multiplying the observed emission rate from the most recent emissions testing, in pounds of NO_x per ton of asphalt produced by the actual rolling 12 month summation of asphalt produced, in tons per rolling 12-month period, as derived from the records required by d)(1) and dividing by 2000 lbs/ton.

g. Emissions Limitation:

The CO emissions from this emissions unit while burning any approved fuel shall not exceed 90.0 tons based on a rolling, 12-month summation of the monthly emissions.

Applicable Compliance Method:

This limitation was determined by multiplying the 12-month production summation by the emission factor of 0.40 lb CO/ton of asphalt production while burning natural gas, No. 2 fuel oil, or used oil (AP-42 Section 11.1: Hot Mix Asphalt Plants, Table 11.1-5, 03/04), and dividing by 2,000 lbs/ton.

Compliance shall be determined by multiplying the observed emission rate from the most recent emissions testing, in pounds of CO per ton of asphalt produced, by the actual rolling 12 month summation of asphalt produced, in tons per rolling 12-month period, as derived from the records required by d)(1) and dividing by 2000 lbs/ton.

h. Emission Limitation:

The OC emissions from this emissions unit when burning natural gas or No. 2 fuel oil shall not exceed 3.38 tons/yr based on a rolling, 12-month summation of the monthly emissions.

Applicable Compliance Method:

This limitation was determined by multiplying the 12-month production summation by the emission factor of 0.015 lb OC/ton of asphalt production while burning natural gas and No.2 fuel oil (AP-42 Section 11.1: Hot Mix Asphalt Plants, Table 11.1-6, 03/04), and dividing by 2,000 lbs/ton.

Compliance shall be determined by multiplying the observed emission rate from the most recent emissions testing, in pounds of OC per ton of asphalt produced, by the actual rolling 12 month summation of asphalt produced, in tons per rolling 12-month period, as derived from the records required by d)(1) and dividing by 2000 lbs/ton.



i. Emission Limitation:

The OC emissions from this emissions unit when burning used oil shall not exceed 9.68 tons/year based on a rolling, 12-month summation of the monthly emissions.

Applicable Compliance Method:

This limitation was determined by multiplying the 12-month production summation by the emission factor of 0.043 lb OC/ton of asphalt production for No. 6 fuel while burning on-spec used oil (AP-42 Section 11.1: Hot Mix Asphalt Plants, Table 11.1-6, 03/04), and dividing by 2,000 lbs/ton.

Compliance shall be determined by multiplying the observed emission rate from the most recent emissions testing, in pounds of OC per ton of asphalt produced, by the actual rolling 12 month summation of asphalt produced, in tons per rolling 12-month period, as derived from the records required by d)(1) and dividing by 2000 lbs/ton.

j. Emission Limitation-

20% opacity visible emissions as a 6-minute average (for stack emissions)

Applicable Compliance Method-

When requested compliance shall be determined through visible emission evaluations performed using the methods and procedures specified in Reference Method 9 of 40 CFR Part 60, Appendix A.

k. Emission Limitation-

20% opacity visible emissions as a 3-minute average (for fugitive emissions)

Applicable Compliance Method-

When requested compliance shall be determined through visible emission evaluations performed using the methods and procedures specified in Reference Method 9 of 40 CFR Part 60, Appendix A.

- (2) The concentrations of contaminants (arsenic, cadmium, chromium, lead, mercury, PCBs, and total halogens) in the used oil shall be analyzed using a "total constituent analysis" method, as specified in U.S. EPA publication SW-846, "Test Methods for Evaluating Solid Waste, Physical/Chemical Methods." The applicable test methods that should be used are as follows:

Arsenic, cadmium, chromium, and lead: SW-846, Method 3031 or 3051 (digestion procedures) followed by analysis using Method 6010B or 6020;
Mercury: SW-846, Method 7471A;

PCBs: SW-846, Method 8270C or 8082; and



Total halogens: SW-846, Method 9075, 9076, or 9077.

The permittee shall submit a written request and receive approval from Ohio EPA Division of Materials and Waste Management and/or the Division of Air Pollution Control, of Central Office, before an alternative test method, not listed above, can be used for the total constituent analysis of the above-mentioned used oil contaminants.

(3) Burner Tuning:

a. Introduction:

The permittee is required to conduct periodic tuning of the asphalt plant burner. The purpose of this tuning is to ensure that the burner is adjusted properly so that air pollution emissions remain in compliance with allowable emissions rates and are minimized.

b. Qualifications for Burner Tuning:

Technicians who conduct the burner tuning must be qualified to perform the expected tasks. The permittee is required to provide training to the technicians who perform the burner tuning procedure. Technicians who are qualified shall, at a minimum, have passed manufacturer's training concerning burner tuning, or have been trained by someone who has completed the manufacturer's training concerning burner tuning.

c. Portable Monitor Requirements:

The permittee shall properly operate and maintain portable device(s) to monitor the concentration of CO, NO_x, and O₂ in the stack exhaust gases from this emissions unit. The monitor(s) shall be capable of measuring the expected concentrations of the measured gases. The monitoring equipment shall be calibrated, operated and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual(s). The permittee shall maintain records of each portable monitoring devices calibration.

d. Burner Tuning Procedure:

The first steps concerning burner tuning involve setting the pollutant baseline levels (concentrations) utilizing the portable monitor. These baselines shall be set during the initial U.S. EPA approved emissions testing that demonstrated the emissions unit was in compliance with all applicable emissions limitations. The baselines shall be determined for CO and NO_x. Sampling should measure the exhaust gas values exiting the dryer or the baghouse. The duration of each sample shall follow the portable monitor manufacture's recommendations. Record these values on the *Burner Tuning Reporting Form for Asphalt Concrete Plants* form (as found in Section g)(1) in the "Recent Stack Test Pollutant Baseline Levels" column.



Once the pollutant baseline levels are set, the burner shall be next tuned based on the frequency described in f)(3)e. The general procedure for tuning the burner involves the following steps:

- i. Review the plant operations to ensure the plant is operating normally.
- ii. Confirm that the portable monitor is calibrated per the manufacturer's specifications.
- iii. Using the calibrated monitor and the monitor manufacturer's recommended sampling duration, measure the stack exhaust gas values for CO, NO_x and O₂. These measurements shall be taken at the same location as the location where the baseline samples were taken. Record the values in the "Pre Tuning" results column on the *Burner Tuning Reporting Form for Asphalt Concrete Plants* form.
- iv. Compare the measured stack exhaust gas values with the pollutant baseline values. If all of the measured stack exhaust gas values are equal to or less than 115 per cent of the pollutant baseline values, then it is not necessary to tune the burner and go on to f)(3)d.v. below.

The permittee shall have the burners tuned within two calendar weeks of any measured stack exhaust values greater than 115 per cent of the baseline values. Make any necessary adjustments and repairs. Repeat f)(2)d.iii. and iv. until the measured stack exhaust gas values are equal to or less than 115 per cent of the pollutant baseline values.

- v. Once all of the measured stack exhaust gas values are within the 115 per cent of the pollutant baseline values, record the measured stack exhaust gas values in the "Post Tuning" results column on the *Burner Tuning Reporting Form for Asphalt Concrete Plants* form.
- vi. By January 31 of each year, submit a copy of all *Burner Tuning Reporting Form for Asphalt Concrete Plants* forms produced during the past calendar year to the appropriate Ohio EPA District Office or local air agency responsible for the permitting of the facility.

e. Burner Tuning Frequency

The permittee shall conduct the burner tuning procedure within 20 production days after commencement of the production season in the State of Ohio. The permittee shall conduct another burner tuning procedure within 10 production days before or after June 1st of each year and within 10 production days before or after September 1st of each year. For purposes of this permit, the production season is defined as the time period between the date the first ton of asphalt is produced and the date that the last ton of asphalt is produced during the same calendar year. A burner tuning is not required if the production season ends prior to the associated tuning due date. If the baseline level testing or the initial season tuning is done within 30 days prior to June 1 or September 1, the tuning associated with that due date is not required.



Final Permit-to-Install and Operate

Valley Asphalt Corp. Plant 6

Permit Number: P0110404

Facility ID: 0857101899

Effective Date: 2/11/2014

- (4) In addition to the burner tuning procedure required above, the permittee shall conduct the burner tuning procedure within 20 production days from the date the facility switches to a fuel that is different than the fuel burned during the initial emissions tests that establish the pollutant baseline levels or the fuel burned during the most recent burner tuning procedure, whichever is later.

- g) Miscellaneous Requirements
 - (1) Burner tuning Reporting Form for Asphalt Concrete Plants (see next page).



BURNER TUNING REPORTING FORM FOR ASPHALT CONCRETE PLANTS	
Facility ID:	Tuning Date:
Legal Name:	Other Company Name (if different than legal name):
Mailing Address:	Other Company Site Address: (if different than mailing address):
City, State, Zip Code:	Other Company City, County, Zip Code:
Site Contact Person:	Site Contact Telephone Number:
Site Contact Title:	Site Contact Fax Number:
Name of company performing tuning:	Name of company performing emission monitoring:
Type of plant (ie: batch, drum mix, etc.):	Calibration date for analyzers:

Reason for Tuning: Season Initial Tuning June Tuning September Tuning Fuel Switch Other (describe)

Fuel employed during tuning: Natural Gas Propane # 2 Fuel Oil # 4 Fuel Oil Used Oil Other (describe)

Tuning Results:

Parameter	Recent Stack Test Pollutant Baseline Levels ¹	Results	
		Pre Tuning	Post Tuning ³
Fuel flow to the burner (gallon/hr) (for fuel oil and on-spec used oil)			
Fuel pressure (psi)			
For burners that require compressed air for proper operation, pressure at the burner (psi)			
Carbon Monoxide (CO) concentrations			
NOx concentrations (ppm) ²			
Oxygen concentrations (per cent) ²			
Asphalt Production (tons/hr)			

¹These values are based on the results of the most recent Ohio EPA approved emissions test.

² Specify whether on a dry or wet basis.

³ If the burner did not require adjusting, please record N/A in the post tuning column.



Final Permit-to-Install and Operate

Valley Asphalt Corp. Plant 6

Permit Number: P0110404

Facility ID: 0857101899

Effective Date: 2/11/2014

Describe in detail a list of adjustments and/or repairs made to bring the operating parameters into conformance with the manufacturers specifications. Use additional paper if necessary.

Name

Date

Authorized Signature: This signature shall constitute personal affirmation that all statements or assertions of fact made in this form are true and complete, comply fully with applicable state requirements, and shall subject the signatory to liability under applicable state laws forbidding false or misleading statements.