



State of Ohio Environmental Protection Agency

**RE: FINAL PERMIT TO INSTALL
CUYAHOGA COUNTY**

CERTIFIED MAIL

Street Address:

122 S. Front Street

Lazarus Gov. Center TELE: (614) 644-3020 FAX: (614) 644-2329

Mailing Address:

Lazarus Gov. Center
P.O. Box 1049

Application No: 13-04617

Fac ID: 1318007764

DATE: 4/25/2006

Orlando Baking Company Cleveland Plant
Richard Burke
7777 Grand Avenue
Cleveland, OH 44104

Enclosed please find an Ohio EPA Permit to Install which will allow you to install the described source(s) in a manner indicated in the permit. Because this permit contains several conditions and restrictions, I urge you to read it carefully.

The Ohio EPA is urging companies to investigate pollution prevention and energy conservation. Not only will this reduce pollution and energy consumption, but it can also save you money. If you would like to learn ways you can save money while protecting the environment, please contact our Office of Pollution Prevention at (614) 644-3469.

You are hereby notified that this action by the Director is final and may be appealed to the Ohio Environmental Review Appeals Commission pursuant to Chapter 3745.04 of the Ohio Revised Code. The appeal must be in writing and set forth the action complained of and the grounds upon which the appeal is based. It must be filed within thirty (30) days after the notice of the Directors action. A copy of the appeal must be served on the Director of the Ohio Environmental Protection Agency within three (3) days of filing with the Commission. An appeal may be filed with the Environmental Review Appeals Commission at the following address:

Environmental Review Appeals Commission
309 South Fourth Street, Room 222
Columbus, Ohio 43215

Sincerely,

Michael W. Ahern

Michael W. Ahern, Manager
Permit Issuance and Data Management Section
Division of Air Pollution Control

CC: USEPA

CLAA



**Permit To Install
Terms and Conditions**

**Issue Date: 4/25/2006
Effective Date: 4/25/2006**

FINAL PERMIT TO INSTALL 13-04617

Application Number: 13-04617
Facility ID: 1318007764
Permit Fee: **\$1000**
Name of Facility: Orlando Baking Company Cleveland Plant
Person to Contact: Richard Burke
Address: 7777 Grand Avenue
Cleveland, OH 44104

Location of proposed air contaminant source(s) [emissions unit(s)]:
**7777 Grand Avenue
Cleveland, Ohio**

Description of proposed emissions unit(s):
Baking Ovens and boilers -- P001, P002, B001, and B002.

The above named entity is hereby granted a Permit to Install for the above described emissions unit(s) pursuant to Chapter 3745-31 of the Ohio Administrative Code. Issuance of this permit does not constitute expressed or implied approval or agreement that, if constructed or modified in accordance with the plans included in the application, the above described emissions unit(s) of environmental pollutants will operate in compliance with applicable State and Federal laws and regulations, and does not constitute expressed or implied assurance that if constructed or modified in accordance with those plans and specifications, the above described emissions unit(s) of pollutants will be granted the necessary permits to operate (air) or NPDES permits as applicable.

This permit is granted subject to the conditions attached hereto.

Ohio Environmental Protection Agency

Director

Part I - GENERAL TERMS AND CONDITIONS

A. Permit to Install General Terms and Conditions

1. Compliance Requirements

The emissions unit(s) identified in this Permit to Install shall remain in full compliance with all applicable State laws and regulations and the terms and conditions of this permit.

2. Reporting Requirements

The permittee shall submit required reports in the following manner:

- a. Reports of any required monitoring and/or recordkeeping information shall be submitted to the appropriate Ohio EPA District Office or local air agency.
- b. Except as otherwise may be provided in the terms and conditions for a specific emissions unit, quarterly written reports of (a) any deviations (excursions) from emission limitations, operational restrictions, and control device operating parameter limitations that have been detected by the testing, monitoring, and recordkeeping requirements specified in this permit, (b) the probable cause of such deviations, and (c) any corrective actions or preventive measures which have been or will be taken, shall be submitted to the appropriate Ohio EPA District Office or local air agency. If no deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted quarterly, i.e., by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters. (These quarterly reports shall exclude deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06.)

3. Records Retention Requirements

Each record of any monitoring data, testing data, and support information required pursuant to this permit shall be retained for a period of five years from the date the record was created. Support information shall include, but not be limited to, all calibration and maintenance records and all original strip-chart recordings for continuous monitoring instrumentation, and copies of all reports required by this permit. Such records may be maintained in computerized form.

4. Inspections and Information Requests

The Director of the Ohio EPA, or an authorized representative of the Director, may, subject to the safety requirements of the permittee and without undue delay, enter upon

Orlando Baking Company Cleveland Plant
PTI Application: 13-04617
Issued: 4/25/2006

Facility ID: 1318007764

the premises of this source at any reasonable time for purposes of making inspections, conducting tests, examining records or reports pertaining to any emission of air contaminants, and determining compliance with any applicable State air pollution laws and regulations and the terms and conditions of this permit. The permittee shall furnish to the Director of the Ohio EPA, or an authorized representative of the Director, upon receipt of a written request and within a reasonable time, any information that may be requested to determine whether cause exists for modifying, reopening or revoking this permit or to determine compliance with this permit. Upon verbal or written request, the permittee shall also furnish to the Director of the Ohio EPA, or an authorized representative of the Director, copies of records required to be kept by this permit.

5. Scheduled Maintenance/Malfunction Reporting

Any scheduled maintenance of air pollution control equipment shall be performed in accordance with paragraph (A) of OAC rule 3745-15-06. The malfunction of any emissions units or any associated air pollution control system(s) shall be reported to the appropriate Ohio EPA District Office or local air agency in accordance with paragraph (B) of OAC rule 3745-15-06. Except as provided in that rule, any scheduled maintenance or malfunction necessitating the shutdown or bypassing of any air pollution control system(s) shall be accompanied by the shutdown of the emissions unit(s) that is (are) served by such control system(s).

6. Permit Transfers

Any transferee of this permit shall assume the responsibilities of the prior permit holder. The appropriate Ohio EPA District Office or local air agency must be notified in writing of any transfer of this permit.

7. Air Pollution Nuisance

The air contaminants emitted by the emissions units covered by this permit shall not cause a public nuisance, in violation of OAC rule 3745-15-07.

8. Termination of Permit to Install

This Permit to Install shall terminate within eighteen months of the effective date of the Permit to Install if the owner or operator has not undertaken a continuing program of installation or modification or has not entered into a binding contractual obligation to undertake and complete within a reasonable time a continuing program of installation or modification. This deadline may be extended by up to 12 months if application is made to the Director within a reasonable time before the termination date and the party shows good cause for any such extension.

9. Construction of New Sources(s)

Orlando Baking Company Cleveland Plant
PTI Application: 13-04617
Issued: 4/25/2006

Facility ID: 1318007764

The proposed emissions unit(s) shall be constructed in strict accordance with the plans and application submitted for this permit to the Director of the Ohio Environmental Protection Agency. There may be no deviation from the approved plans without the express, written approval of the Agency. Any deviations from the approved plans or the above conditions may lead to such sanctions and penalties as provided under Ohio law. Approval of these plans does not constitute an assurance that the proposed facilities will operate in compliance with all Ohio laws and regulations. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed sources cannot meet the requirements of this permit or cannot meet applicable standards.

If the construction of the proposed emissions unit(s) has already begun or has been completed prior to the date the Director of the Environmental Protection Agency approves the permit application and plans, the approval does not constitute expressed or implied assurance that the proposed facility has been constructed in accordance with the approved plans. The action of beginning and/or completing construction prior to obtaining the Director's approval constitutes a violation of OAC rule 3745-31-02. Furthermore, issuance of the Permit to Install does not constitute an assurance that the proposed source will operate in compliance with all Ohio laws and regulations. Approval of the plans in any case is not to be construed as an approval of the facility as constructed and/or completed. Moreover, issuance of the Permit to Install is not to be construed as a waiver of any rights that the Ohio Environmental Protection Agency (or other persons) may have against the applicant for starting construction prior to the effective date of the permit. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed facilities cannot meet the requirements of this permit or cannot meet applicable standards.

10. Public Disclosure

The facility is hereby notified that this permit, and all agency records concerning the operation of this permitted source, are subject to public disclosure in accordance with OAC rule 3745-49-03.

11. Applicability

This Permit To Install is applicable only to the emissions unit(s) identified in the Permit To Install. Separate Permit To Install for the installation or modification of any other emissions unit(s) are required for any emissions unit for which a Permit To Install is required.

12. Best Available Technology

As specified in OAC Rule 3745-31-05, all new sources must employ Best Available Technology (BAT). Compliance with the terms and conditions of this permit will fulfill this requirement.

Orlando Baking Company Cleveland Plant
 PTI Application: 13-04617
 Issued: 4/25/2006

Facility ID: 1318007764

13. Source Operation and Operating Permit Requirements After Completion of Construction

This facility is permitted to operate each source described by this Permit to Install for a period of up to one year from the date the source commenced operation. This permission to operate is granted only if the facility complies with all requirements contained in this permit and all applicable air pollution laws, regulations, and policies. Pursuant to OAC Chapter 3745-35, the permittee shall submit a complete operating permit application within ninety (90) days after commencing operation of the emissions unit(s) covered by this permit.

14. Construction Compliance Certification

The applicant shall provide Ohio EPA with a written certification (see enclosed form) that the facility has been constructed in accordance with the Permit to Install application and the terms and conditions of the Permit to Install. The certification shall be provided to Ohio EPA upon completion of construction but prior to startup of the source.

15. Fees

The permittee shall pay fees to the Director of the Ohio EPA in accordance with ORC section 3745.11 and OAC Chapter 3745-78. The permittee shall pay all applicable Permit to Install fees within 30 days after the issuance of this Permit to Install.

B. Permit to Install Summary of Allowable Emissions

The following information summarizes the total allowable emissions, by pollutant, based on the individual allowable emissions of each air contaminant source identified in this permit.

SUMMARY (for informational purposes only)
 TOTAL PERMIT TO INSTALL ALLOWABLE EMISSIONS

<u>Pollutant</u>	<u>Tons Per Year</u>
VOC	83.3
NOx	5.21
CO	4.41

7

Orlando Baking Company Cleveland Plant
PTI Application: 13-04617
Issued: 4/25/2006

Facility ID: 1318007764

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

- The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P001 - 3.36 mmBTU/hour direct natural gas-fired tunnel Baking Oven No. 1	OAC rule 3745-31-05 (A)(3)	6.18 lbs VOC/hour and 27.1 tons/year of VOC
		Visible particulate emissions from the stack(s) serving this emissions unit shall not exceed 5% opacity, as a six-minute average.
		0.33 lb NOx/hour and 1.45 tons/year of NOx from the combustion of natural gas.
		0.28 lb CO/hour and 1.23 tons/year of CO from the combustion of natural gas.
	OAC rule 3745-17-07 (A)	See A.2.a below. The visible emission limitation specified by this rule is less stringent than the requirements of OAC rule 3745-31-05 (A)(3).
	OAC rule 3745-17-11	The emission limitation specified by this rule is less stringent than the requirements of OAC rule 3745-31-05 (A)(3).
	OAC rule 3745-18-06 (A)	Exempt (See B.1 below).

| OAC rule 3745-21-07 (G) | See A.2.b below.

2. Additional Terms and Conditions

- 2.a** The hourly and annual emission limits for this emissions unit have been established at the unit's potential to emit. Therefore, monitoring, record keeping, and reporting are not needed for these limits.
- 2.b** No liquid organic materials are employed in this emissions unit. Therefore, OAC rule 3745-21-07(G) does not apply.

B. Operational Restrictions

1. The permittee shall burn only natural gas in this emissions unit.

C. Monitoring and/or Recordkeeping Requirements

1. For each day during which the permittee burns a fuel other than natural gas, the permittee shall maintain a record of the type and quantity of fuel burned in this emissions unit.
2. The permit to install for this emissions unit, P001, was evaluated based on the actual materials and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied to this emissions unit for each toxic pollutant, using data from the permit to install application, and modeling was performed for the toxic pollutant(s) emitted at over a ton per year using the SCREEN 3.0 model or other Ohio EPA approved model. The predicted 1-hour maximum ground-level concentration result(s) from the use of the SCREEN 3.0 (or other approved) model, was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC), calculated as required in Engineering Guide #70. The following summarizes the results of the modeling for the "worst case" pollutant(s):

Pollutant: ethanol

TLV (mg/m³): 1,000

Maximum Hourly Emission Rate (lbs/hr): 20.85 (total for P001 - P004 and exempt oven #8)

Predicted 1-Hour Maximum Ground-Level Concentration (µg/m³): 14,970

MAGLC ($\mu\text{g}/\text{m}^3$): 23,810

3. Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:
 - a. changes in the composition of the materials used or the use of new materials, that would result in the emission of a compound or chemical with a lower Threshold Limit Value (TLV) than the lowest TLV previously modeled, as documented in the most current version of the American Conference of Governmental Industrial Hygienists' (ACGIH's) handbook entitled "TLVs and BEIs" ("Threshold Limit Values for Chemical Substances and Physical Agents, Biological Exposure Indices");
 - b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and
 - c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).
4. If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01 solely due to the emissions of any type of toxic air contaminant not previously emitted, and a modification of the existing permit to install will not be required, even if the toxic air contaminant emissions are greater than the de minimis level in OAC rule 3745-15-05. If the change(s) meet(s) the definition of a "modification" under other provisions of the rule, then the permittee shall obtain a final permit to install prior to the change.

The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy":

Orlando Baking Company Cleveland Plant

PTI Application: 12-04617

Issue:

Facility ID: 1318007764

Emissions Unit ID: P001

- a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
- b. documentation of the evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and
- c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

D. Reporting Requirements

1. The permittee shall submit deviation (excursion) reports that identify each day when a fuel other than natural gas is burned in this emissions unit. Each report shall be submitted to the Cleveland Division of Air Quality (Cleveland DAQ) within 30 days after the deviation occurs.

E. Testing Requirements

1. Compliance with the emission limitation(s) in Section A.1 of these terms and conditions shall be determined in accordance with the following method(s):

- a. Emission Limitation:
6.18 lbs/hour of VOC

Applicable Compliance Method:

Compliance with the pound per hour limitation shall be determined by multiplying the emission factor established by the equation for VOC emissions from bread baking operations was taken from AP-42, Volume 1, Fifth Edition (January 1995), section 9.9.6, "Bread Baking" by the amount of bread produced, in tons. This is shown below in a one time calculation of Potential-to-Emit for the worst case recipe at the maximum production rate:

$$\text{VOC EF} = 0.95Y_i + 0.195t_i - 0.51S - 0.86t_s + 1.90$$

Where

VOC EF = pounds of VOC per ton of baked bread

Y_i = initial baker's percentage of yeast

t_i = total yeast action time in hours

S = final (spike) baker's percentage of yeast

t_s = spiking time in hours

$$\begin{aligned} \text{VOC EF} &= 0.95(5.0\%) + 0.195(1.33) - 0.51(0\%) - 0.86(0\%) + 1.90 \\ &= 6.91 \text{ pounds VOC/ton of baked bread} \end{aligned}$$

$$\begin{aligned} &(6.91 \text{ pounds VOC/ton of baked bread}) \times (0.895 \text{ ton of baked bread/hour}) \\ &= 6.18 \text{ pounds VOC/hour} \end{aligned}$$

- b. Emission Limitation:
27.1 TPY of VOC

Applicable Compliance Method:

The annual emission limitation was established by multiplying the hourly emission rate by 8,760 hours of operation per year and dividing by 2,000 pounds per ton. Therefore, compliance with the annual emission limitation shall be assumed provided compliance is maintained with the pounds per hour limitation.

- c. Emission Limitation:
5% opacity as a 6-minute average
- Applicable Compliance Method:
Compliance shall be demonstrated based upon the requirements specified in OAC rule 3745-17-03 (B)(1) and the methods and procedures required in 40 CFR Part 60, Appendix A, Method 9.
- d. Emission Limitation:
0.33 lb/hr of NO_x from the 3.36 mmBTU/hour natural gas-fired burner
- Applicable Compliance Method:
Compliance with the pound per hour limitation shall be determined by multiplying the emission factor from Section 1.4 ("Natural Gas Consumption") of AP-42, Fifth Edition, Volume 1, Chapter 1 by the mmBTU/hour rating of the natural gas-fired burner. Since the emissions factors are given in a volume format, they were converted to an energy basis by dividing the given factor by 1,020 mmBTU/10⁶ scf.
- e. Emission Limitation:
1.45 TPY of NO_x from the 3.36 mmBTU/hour natural gas-fired burner
- Applicable Compliance Method:
The annual emission limitation was established by multiplying the hourly emission rate by 8,760 hours of operation per year and dividing by 2,000 pounds per ton. Therefore, compliance with the annual emission limitation shall be assumed provided compliance is maintained with the pounds per hour limitation.
- f. Emission Limitation:
0.28 lb/hr of CO from the 3.36 mmBTU/hour natural gas-fired burner
- Applicable Compliance Method:
Compliance with the pound per hour limitation shall be determined by multiplying the emission factor from Section 1.4 ("Natural Gas Consumption") of AP-42, Fifth Edition, Volume 1, Chapter 1 by the mmBTU/hour rating of the natural gas-fired burner. Since the emissions factors are given in a volume format, they were converted to an energy basis by dividing the given factor by

Orlando Baking Company Cleveland Plant
PTI Application: 12-04617
Issue

Facility ID: 1318007764

Emissions Unit ID: P001

1,020 mmBTU/10⁶ scf.

- g. Emission Limitation:
1.23 TPY of CO from the 3.36 mmBTU/hour natural gas-fired burner

Applicable Compliance Method:

The annual emission limitation was established by multiplying the hourly emission rate by

8,760 hours of operation per year and dividing by 2,000 pounds per ton.

Therefore, compliance with the annual emission limitation shall be assumed provided compliance is maintained with the pounds per hour limitation.

F. Miscellaneous Requirements

1. Potential to Emit (PTE) was determined using the recipe and values listed in the permit.

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P002 - 3.36 mmBTU/hour direct natural gas-fired tunnel Baking Oven No. 3	OAC rule 3745-31-05 (A)(3)	3.87 lbs VOC/hour and 17.0 tons/year of VOC
		Visible particulate emissions from the stack(s) serving this emissions unit shall not exceed 5% opacity, as a six-minute average.
		0.33 lb NOx/hour and 1.45 tons/year of NOx from the combustion of natural gas.
		0.28 lb CO/hour and 1.23 tons/year of CO from the combustion of natural gas.
	OAC rule 3745-17-07 (A)	See A.2.a below. The visible emission limitation specified by this rule is less stringent than the requirements of OAC rule 3745-31-05 (A)(3).
	OAC rule 3745-17-11	The emission limitation specified by this rule is less stringent than the requirements of OAC rule 3745-31-05 (A)(3).
	OAC rule 3745-18-06 (A)	Exempt (See B.1 below).

| OAC rule 3745-21-07 (G) | See A.2.b below.

2. Additional Terms and Conditions

- 2.a** The hourly and annual emission limits for this emissions unit have been established at the unit's potential to emit. Therefore, monitoring, record keeping, and reporting are not needed for these limits.
- 2.b** No liquid organic materials are employed in this emissions unit. Therefore, OAC rule 3745-21-07 (G) does not apply.

B. Operational Restrictions

1. The permittee shall burn only natural gas in this emissions unit.

C. Monitoring and/or Recordkeeping Requirements

1. For each day during which the permittee burns a fuel other than natural gas, the permittee shall maintain a record of the type and quantity of fuel burned in this emissions unit.
2. The permit to install for this emissions unit, P002, was evaluated based on the actual materials and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied to this emissions unit for each toxic pollutant, using data from the permit to install application, and modeling was performed for the toxic pollutant(s) emitted at over a ton per year using the SCREEN 3.0 model or other Ohio EPA approved model. The predicted 1-hour maximum ground-level concentration result(s) from the use of the SCREEN 3.0 (or other approved) model, was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC), calculated as required in Engineering Guide #70. The following summarizes the results of the modeling for the "worst case" pollutant(s):

Pollutant: ethanol

TLV (mg/m³): 1,000

Maximum Hourly Emission Rate (lbs/hr): 20.85 (total for P001 - P004 and exempt oven #8)

Predicted 1-Hour Maximum Ground-Level Concentration (µg/m³): 14,970

Emissions Unit ID: P002

MAGLC ($\mu\text{g}/\text{m}^3$): 23,810

3. Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:
 - a. changes in the composition of the materials used or the use of new materials, that would result in the emission of a compound or chemical with a lower Threshold Limit Value (TLV) than the lowest TLV previously modeled, as documented in the most current version of the American Conference of Governmental Industrial Hygienists' (ACGIH's) handbook entitled "TLVs and BEIs" ("Threshold Limit Values for Chemical Substances and Physical Agents, Biological Exposure Indices");
 - b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and
 - c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).
4. If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01 solely due to the emissions of any type of toxic air contaminant not previously emitted, and a modification of the existing permit to install will not be required, even if the toxic air contaminant emissions are greater than the de minimis level in OAC rule 3745-15-05. If the change(s) meet(s) the definition of a "modification" under other provisions of the rule, then the permittee shall obtain a final permit to install prior to the change.

The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy":

- a. a description of the parameters changed (composition of materials, new

pollutants emitted, change in stack/exhaust parameters, etc.);

- b. documentation of the evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and
- c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

D. Reporting Requirements

1. The permittee shall submit deviation (excursion) reports that identify each day when a fuel other than natural gas is burned in this emissions unit. Each report shall be submitted to the Cleveland Division of Air Quality (Cleveland DAQ) within 30 days after the deviation occurs.

E. Testing Requirements

1. Compliance with the emission limitation(s) in Section A.1 of these terms and conditions shall be determined in accordance with the following method(s):

- a. Emission Limitation:
3.87 lbs/hour of VOC

Applicable Compliance Method:

Compliance with the pound per hour limitation shall be determined by multiplying the emission factor established by the equation for VOC emissions from bread baking operations was taken from AP-42, Volume 1, Fifth Edition (January 1995), section 9.9.6, "Bread Baking" by the amount of bread produced, in tons. This is shown below in a one time calculation of Potential-to-Emit for the worst case recipe at the maximum production rate:

$$\text{VOC EF} = 0.95Y_i + 0.195t_i - 0.51S - 0.86t_s + 1.90$$

Where

VOC EF = pounds of VOC per ton of baked bread

Y_i = initial baker's percentage of yeast

t_i = total yeast action time in hours

S = final (spike) baker's percentage of yeast

t_s = spiking time in hours

$$\begin{aligned} \text{VOC EF} &= 0.95(2.75\%) + 0.195(1.33) - 0.51(0\%) - 0.86(0\%) + 1.90 \\ &= 4.77 \text{ pounds VOC/ton of baked bread} \end{aligned}$$

$$\begin{aligned} &(4.77 \text{ pounds VOC/ton of baked bread}) \times (0.812 \text{ ton of baked bread/hour}) \\ &= 3.87 \text{ pounds VOC/hour} \end{aligned}$$

- b. Emission Limitation:
17.0 TPY of VOC

Applicable Compliance Method:

The annual emission limitation was established by multiplying the hourly emission rate by 8,760 hours of operation per year and dividing by 2,000 pounds per ton. Therefore, compliance with the annual emission limitation shall be assumed provided compliance is maintained with the pounds per hour limitation.

- c. Emission Limitation:
5% opacity as a 6-minute average

Applicable Compliance Method:

Compliance shall be demonstrated based upon the requirements specified in OAC rule 3745-17-03 (B)(1) and the methods and procedures required in 40 CFR Part 60, Appendix A, Method 9.

- d. Emission Limitation:
0.33 lb/hr of NO_x from the 3.36 mmBTU/hour natural gas-fired burner

Applicable Compliance Method:

Compliance with the pound per hour limitation shall be determined by multiplying the emission factor from Section 1.4 ("Natural Gas Consumption") of AP-42, Fifth Edition, Volume 1, Chapter 1 by the mmBTU/hour rating of the natural gas-fired burner. Since the emissions factors are given in a volume format, they were converted to an energy basis by dividing the given factor by 1,020 mmBTU/10⁶ scf.

- e. Emission Limitation:
1.45 TPY of NO_x from the 3.36 mmBTU/hour natural gas-fired burner

Applicable Compliance Method:

The annual emission limitation was established by multiplying the hourly emission rate by 8,760 hours of operation per year and dividing by 2,000 pounds per ton. Therefore, compliance with the annual emission limitation shall be assumed provided compliance is maintained with the pounds per hour limitation.

- f. Emission Limitation:
0.28 lb/hr of CO from the 3.36 mmBTU/hour natural gas-fired burner

Applicable Compliance Method:

Compliance with the pound per hour limitation shall be determined by multiplying the emission factor from Section 1.4 ("Natural Gas Consumption") of AP-42, Fifth Edition, Volume 1, Chapter 1 by the mmBTU/hour rating of the natural gas-fired burner. Since the emissions factors are given in a volume format, they were converted to an energy basis by dividing the given factor by 1,020 mmBTU/10⁶ scf.

- g. Emission Limitation:
1.23 TPY of CO from the 3.36 mmBTU/hour natural gas-fired burner

Applicable Compliance Method:

The annual emission limitation was established by multiplying the hourly emission rate by

8,760 hours of operation per year and dividing by 2,000 pounds per ton. Therefore, compliance with the annual emission limitation shall be assumed provided compliance is maintained with the pounds per hour limitation.

Orlan

PTI A

Issued: 4/25/2006

Emissions Unit ID: **P002**

F. Miscellaneous Requirements

1. Potential to Emit (PTE) was determined using the recipe and values listed in the permit.

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

- The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P003 - 3.36 mmBTU/hour direct natural gas-fired tunnel Baking Oven No. 4	OAC rule 3745-31-05 (A)(3)	3.65 lbs VOC/hour and 16.0 tons/year of VOC
		Visible particulate emissions from the stack(s) serving this emissions unit shall not exceed 5% opacity, as a six-minute average.
		0.33 lb NOx/hour and 1.45 tons/year of NOx from the combustion of natural gas.
		0.28 lb CO/hour and 1.23 tons/year of CO from the combustion of natural gas.
	OAC rule 3745-17-07 (A)	See A.2.a below. The visible emission limitation specified by this rule is less stringent than the requirements of OAC rule 3745-31-05 (A)(3).
	OAC rule 3745-17-11	The emission limitation specified by this rule is less stringent than the requirements of OAC rule 3745-31-05 (A)(3).
	OAC rule 3745-18-06 (A)	Exempt (See B.1 below).
	OAC rule 3745-21-07 (G)	See A.2.b below.

2. Additional Terms and Conditions

- 2.a** The hourly and annual emission limits for this emissions unit have been established at the unit's potential to emit. Therefore, monitoring, record keeping, and reporting are not needed for these limits.
- 2.b** No liquid organic materials are employed in this emissions unit. Therefore, OAC rule 3745-21-07(G) does not apply.

B. Operational Restrictions

1. The permittee shall burn only natural gas in this emissions unit.

C. Monitoring and/or Recordkeeping Requirements

1. For each day during which the permittee burns a fuel other than natural gas, the permittee shall maintain a record of the type and quantity of fuel burned in this emissions unit.
2. The permit to install for this emissions unit, P003, was evaluated based on the actual materials and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied to this emissions unit for each toxic pollutant, using data from the permit to install application, and modeling was performed for the toxic pollutant(s) emitted at over a ton per year using the SCREEN 3.0 model or other Ohio EPA approved model. The predicted 1-hour maximum ground-level concentration result(s) from the use of the SCREEN 3.0 (or other approved) model, was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC), calculated as required in Engineering Guide #70. The following summarizes the results of the modeling for the "worst case" pollutant(s):

Pollutant: ethanol

TLV (mg/m³): 1,000

Maximum Hourly Emission Rate (lbs/hr): 20.85 (total for P001 - P004 and exempt oven #8)

Predicted 1-Hour Maximum Ground-Level Concentration (µg/m³): 14,970

MAGLC (µg/m³): 23,810

3. Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:
 - a. changes in the composition of the materials used or the use of new materials, that would result in the emission of a compound or chemical with a lower Threshold Limit Value (TLV) than the lowest TLV previously modeled, as documented in the most current version of the American Conference of Governmental Industrial Hygienists' (ACGIH's) handbook entitled "TLVs and BEIs" ("Threshold Limit Values for Chemical Substances and Physical Agents, Biological Exposure Indices");
 - b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and
 - c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).
4. If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01 solely due to the emissions of any type of toxic air contaminant not previously emitted, and a modification of the existing permit to install will not be required, even if the toxic air contaminant emissions are greater than the de minimis level in OAC rule 3745-15-05. If the change(s) meet(s) the definition of a "modification" under other provisions of the rule, then the permittee shall obtain a final permit to install prior to the change.

The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy":

- a. a description of the parameters changed (composition of materials, new

Orlando Baking Company Cleveland Plant

PTI Application: 12-04617

Issue:

Facility ID: 1318007764

Emissions Unit ID: P003

pollutants emitted, change in stack/exhaust parameters, etc.);

- b. documentation of the evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and
- c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

D. Reporting Requirements

1. The permittee shall submit deviation (excursion) reports that identify each day when a fuel other than natural gas is burned in this emissions unit. Each report shall be submitted to the Cleveland Division of Air Quality (Cleveland DAQ) within 30 days after the deviation occurs.

E. Testing Requirements

1. Compliance with the emission limitation(s) in Section A.1 of these terms and conditions shall be determined in accordance with the following method(s):

- a. Emission Limitation:
3.65 lbs/hour of VOC

Applicable Compliance Method:

Compliance with the pound per hour limitation shall be determined by multiplying the emission factor established by the equation for VOC emissions from bread baking operations was taken from AP-42, Volume 1, Fifth Edition (January 1995), section 9.9.6, "Bread Baking" by the amount of bread produced, in tons. This is shown below in a one time calculation of Potential-to-Emit for the worst case recipe at the maximum production rate:

$$\text{VOC EF} = 0.95Y_i + 0.195t_i - 0.51S - 0.86t_s + 1.90$$

Where

VOC EF = pounds of VOC per ton of baked bread

Y_i = initial baker's percentage of yeast

t_i = total yeast action time in hours

S = final (spike) baker's percentage of yeast

t_s = spiking time in hours

$$\begin{aligned} \text{VOC EF} &= 0.95(2.75\%) + 0.195(1.33) - 0.51(0\%) - 0.86(0\%) + 1.90 \\ &= 4.77 \text{ pounds VOC/ton of baked bread} \end{aligned}$$

$$\begin{aligned} &(4.77 \text{ pounds VOC/ton of baked bread}) \times (0.765 \text{ tons of baked bread/hour}) \\ &= 3.65 \text{ pounds VOC/hour} \end{aligned}$$

- b. Emission Limitation:
16.0 TPY of VOC

Applicable Compliance Method:

The annual emission limitation was established by multiplying the hourly emission rate by 8,760 hours of operation per year and dividing by 2,000 pounds per ton. Therefore, compliance with the annual emission limitation shall be assumed provided compliance is maintained with the pounds per hour limitation.

- c. Emission Limitation:
5% opacity as a 6-minute average

Applicable Compliance Method:

Compliance shall be demonstrated based upon the requirements specified in OAC rule

3745-17-03 (B)(1) and the methods and procedures required in 40 CFR Part 60, Appendix A, Method 9.

- d. Emission Limitation:
0.33 lb/hr of NO_x from the 3.36 mmBTU/hour natural gas-fired burner

Applicable Compliance Method:

Compliance with the pound per hour limitation shall be determined by multiplying the emission factor from Section 1.4 ("Natural Gas Consumption") of AP-42, Fifth Edition, Volume 1, Chapter 1 by the mmBTU/hour rating of the natural gas-fired burner. Since the emissions factors are given in a volume format, they were converted to an energy basis by dividing the given factor by 1,020 mmBTU/10⁶ scf.

- e. Emission Limitation:
1.45 TPY of NO_x from the 3.36 mmBTU/hour natural gas-fired burner

Applicable Compliance Method:

The annual emission limitation was established by multiplying the hourly emission rate by

8,760 hours of operation per year and dividing by 2,000 pounds per ton. Therefore, compliance with the annual emission limitation shall be assumed provided compliance is maintained with the pounds per hour limitation.

- f. Emission Limitation:
0.28 lb/hr of CO from the 3.36 mmBTU/hour natural gas-fired burner

Applicable Compliance Method:

Compliance with the pound per hour limitation shall be determined by multiplying the emission factor from Section 1.4 ("Natural Gas Consumption") of AP-42, Fifth Edition, Volume 1, Chapter 1 by the mmBTU/hour rating of the natural gas-fired burner. Since the emissions factors are given in a volume format, they were converted to an energy basis by dividing the given factor by

Orlando Baking Company Cleveland Plant
PTI Application: 12-04617
Issue

Facility ID: 1318007764

Emissions Unit ID: P003

1,020 mmBTU/10⁶ scf.

- g. Emission Limitation:
1.23 TPY of CO from the 3.36 mmBTU/hour natural gas-fired burner

Applicable Compliance Method:

The annual emission limitation was established by multiplying the hourly emission rate by 8,760 hours of operation per year and dividing by 2,000 pounds per ton. Therefore, compliance with the annual emission limitation shall be assumed provided compliance is maintained with the pounds per hour limitation.

F. Miscellaneous Requirements

1. Potential to Emit (PTE) was determined using the recipe and values listed in the permit.

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)**A. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P004 - 2.00 mmBTU/hour direct natural gas-fired tunnel Baking Oven No. 7	OAC rule 3745-31-05 (A)(3)	<p>5.3 lbs VOC/hour and 23.2 tons/year of VOC</p> <p>Visible particulate emissions from the stack(s) serving this emissions unit shall not exceed 5% opacity, as a six-minute average.</p> <p>0.2 lb NO_x/hour and 0.86 ton/year of NO_x from the combustion of natural gas.</p> <p>0.16 lb CO/hour and 0.72 ton/year of CO from the combustion of natural gas.</p>
	OAC rule 3745-17-07 (A)	<p>See A.2.a below.</p> <p>The visible emission limitation specified by this rule is less stringent than the requirements of OAC rule 3745-31-05 (A)(3).</p>
	OAC rule 3745-17-11	<p>The emission limitation specified by this rule is less stringent than the requirements of OAC rule 3745-31-05 (A)(3).</p>
	OAC rule 3745-18-06 (A)	Exempt (See B.1 below).

| OAC rule 3745-21-07 (G) | See A.2.b below.

2. Additional Terms and Conditions

- 2.a** The hourly and annual emission limits for this emissions unit have been established at the unit's potential to emit. Therefore, monitoring, record keeping, and reporting are not needed for these limits.
- 2.b** No liquid organic materials are employed in this emissions unit. Therefore, OAC rule 3745-21-07(G) does not apply.

B. Operational Restrictions

1. The permittee shall burn only natural gas in this emissions unit.

C. Monitoring and/or Recordkeeping Requirements

1. For each day during which the permittee burns a fuel other than natural gas, the permittee shall maintain a record of the type and quantity of fuel burned in this emissions unit.
2. The permit to install for this emissions unit, P004, was evaluated based on the actual materials and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied to this emissions unit for each toxic pollutant, using data from the permit to install application, and modeling was performed for the toxic pollutant(s) emitted at over a ton per year using the SCREEN 3.0 model or other Ohio EPA approved model. The predicted 1-hour maximum ground-level concentration result(s) from the use of the SCREEN 3.0 (or other approved) model, was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC), calculated as required in Engineering Guide #70. The following summarizes the results of the modeling for the "worst case" pollutant(s):

Pollutant: ethanol

TLV (mg/m³): 1,000

Maximum Hourly Emission Rate (lbs/hr): 20.85 (total for P001 - P004 and exempt oven #8)

Predicted 1-Hour Maximum Ground-Level Concentration (µg/m³): 14,970

MAGLC ($\mu\text{g}/\text{m}^3$): 23,810

3. Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:
 - a. changes in the composition of the materials used or the use of new materials, that would result in the emission of a compound or chemical with a lower Threshold Limit Value (TLV) than the lowest TLV previously modeled, as documented in the most current version of the American Conference of Governmental Industrial Hygienists' (ACGIH's) handbook entitled "TLVs and BEIs" ("Threshold Limit Values for Chemical Substances and Physical Agents, Biological Exposure Indices");
 - b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and
 - c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).
4. If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01 solely due to the emissions of any type of toxic air contaminant not previously emitted, and a modification of the existing permit to install will not be required, even if the toxic air contaminant emissions are greater than the de minimis level in OAC rule 3745-15-05. If the change(s) meet(s) the definition of a "modification" under other provisions of the rule, then the permittee shall obtain a final permit to install prior to the change.

The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy":

- a. a description of the parameters changed (composition of materials, new

pollutants emitted, change in stack/exhaust parameters, etc.);

- b. documentation of the evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and
- c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

D. Reporting Requirements

1. The permittee shall submit deviation (excursion) reports that identify each day when a fuel other than natural gas is burned in this emissions unit. Each report shall be submitted to the Cleveland Division of Air Quality (Cleveland DAQ) within 30 days after the deviation occurs.

E. Testing Requirements

1. Compliance with the emission limitation(s) in Section A.1 of these terms and conditions shall be determined in accordance with the following method(s):

- a. Emission Limitation:
5.3 lbs/hour of VOC

Applicable Compliance Method:

Compliance with the pound per hour limitation shall be determined by multiplying the emission factor established by the equation for VOC emissions from bread baking operations was taken from AP-42, Volume 1, Fifth Edition (January 1995), section 9.9.6, "Bread Baking" by the amount of bread produced, in tons. This is shown below in a one time calculation of Potential-to-Emit for the worst case recipe at the maximum production rate:

$$\text{VOC EF} = 0.95Y_i + 0.195t_i - 0.51S - 0.86t_s + 1.90$$

Where

VOC EF = pounds of VOC per ton of baked bread

Y_i = initial baker's percentage of yeast

t_i = total yeast action time in hours

S = final (spike) baker's percentage of yeast

t_s = spiking time in hours

$$\begin{aligned} \text{VOC EF} &= 0.95(5.0\%) + 0.195(1.33) - 0.51(0\%) - 0.86(0\%) + 1.90 \\ &= 6.91 \text{ pounds VOC/ton of baked bread} \end{aligned}$$

$$\begin{aligned} &(6.91 \text{ pounds VOC/ton of baked bread}) \times (0.768 \text{ ton of baked bread/hour}) \\ &= 5.3 \text{ pounds VOC/hour} \end{aligned}$$

- b. Emission Limitation:
23.2 TPY of VOC

Applicable Compliance Method:

The annual emission limitation was established by multiplying the hourly emission rate by 8,760 hours of operation per year and dividing by 2,000 pounds per ton. Therefore, compliance with the annual emission limitation shall be assumed provided compliance is maintained with the pounds per hour limitation.

- c. Emission Limitation:
5% opacity as a 6-minute average

Applicable Compliance Method:

Compliance shall be demonstrated based upon the requirements specified in OAC rule 3745-17-03 (B)(1) and the methods and procedures required in 40 CFR Part 60, Appendix A, Method 9.

- d. Emission Limitation:
0.2 lb/hr of NO_x from the 2.00 mmBTU/hour natural gas-fired burner

Applicable Compliance Method:

Compliance with the pound per hour limitation shall be determined by multiplying the emission factor from Section 1.4 ("Natural Gas Consumption") of AP-42, Fifth Edition, Volume 1, Chapter 1 by the mmBTU/hour rating of the natural gas-fired burner. Since the emissions factors are given in a volume format, they were converted to an energy basis by dividing the given factor by 1,020 mmBTU/10⁶ scf.

- e. Emission Limitation:
0.86 TPY of NO_x from the 2.00 mmBTU/hour natural gas-fired burner

Applicable Compliance Method:

The annual emission limitation was established by multiplying the hourly emission rate by 8,760 hours of operation per year and dividing by 2,000 pounds per ton. Therefore, compliance with the annual emission limitation shall be assumed provided compliance is maintained with the pounds per hour limitation.

- f. Emission Limitation:
0.16 lb/hr of CO from the 2.00 mmBTU/hour natural gas-fired burner

Applicable Compliance Method:

Compliance with the pound per hour limitation shall be determined by multiplying the emission factor from Section 1.4 ("Natural Gas Consumption") of AP-42, Fifth Edition, Volume 1, Chapter 1 by the mmBTU/hour rating of the natural gas-fired burner. Since the emissions factors are given in a volume format, they were converted to an energy basis by dividing the given factor by 1,020 mmBTU/10⁶ scf.

- g. Emission Limitation:
0.72 TPY of CO from the 2.00 mmBTU/hour natural gas-fired burner

Applicable Compliance Method:

The annual emission limitation was established by multiplying the hourly emission rate by

8,760 hours of operation per year and dividing by 2,000 pounds per ton. Therefore, compliance with the annual emission limitation shall be assumed provided compliance is maintained with the pounds per hour limitation.

Orlan

PTI A

Issued: 4/25/2006

Emissions Unit ID: **P004**

F. Miscellaneous Requirements

1. Potential to Emit (PTE) was determined using the recipe and values listed in the permit.