

Facility ID: 0812100276 Issuance type: Final State Permit To Operate

This version of facility specific terms and conditions was converted from a database format to an HTML file during an upgrade of the Ohio EPA, Division of Air Pollution Control's permitting software. Every attempt has been made to convert the terms and conditions to look and substantively conform to the permit issued or being drafted in STARS. However, the format of the terms may vary slightly from the original. In addition, although it is not expected, there is a slight possibility that a term and condition may have been inadvertently "left out" of this reproduction during the conversion process. Therefore, if this version is to be used as a starting point in drafting a new version of a permit, it is imperative that the entire set of terms and conditions be reviewed to ensure they substantively mimic the issued permit. The official version of any permit issued final by Ohio EPA is kept in the Agency's Legal section. The Legal section may be contacted at (614) 644-3037.

In addition to the terms and conditions, hyperlinks have been inserted into the document so you may more readily access the section of the document you wish to review.

Finally, the term language under "Part II" and before "A. Applicable Emissions Limitations..." has been added to aid in document conversion, and was not part of the original issued permit.

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION

Facility ID: 0812100276 Emissions Unit ID: P902 Issuance type: Final State Permit To Operate

[Go to the top of this document](#)

Part II - Special Terms and Conditions

This permit document constitutes a permit-to-install issued in accordance with ORC 3704.03(F) and a permit-to-operate issued in accordance with ORC 3704.03(G).

1. For the purpose of a permit-to-install document, the emissions unit terms and conditions identified below are federally enforceable with the exception of those listed below which are enforceable under state law only.
 - (a) None.
2. For the purpose of a permit-to-operate document, the emissions unit terms and conditions identified below are enforceable under state law only with the exception of those listed below which are federally enforceable.
 - (a) None.

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P902 - No Bake Sand Reclamation System with baghouse	OAC rule 3745-31-05(A)(3) PTI 08-04462	Particulate emissions (PE) from this emissions unit shall not exceed 0.98 lbs/hr. Visible PE shall not exceed 5% opacity, as a 6-minute average. Fugitive visible PE shall not exceed 5% opacity, as a 3-minute average, as observed from general ventilation egress points.
	OAC rule 3745-35-07(B) (Synthetic Minor to avoid Title V permitting)	The requirements of this rule also include compliance with the requirements of OAC rules 3745-17-07(A), 3745-17-07(B), 3745-17-11(B) and 3745-35-07(B). PE shall not exceed 4.26 tons per rolling 365-day period.
	OAC rule 3745-17-07(A)(1)	See A.2.b. and B.1. The opacity limitation specified by this rule is less stringent than that established by OAC rule 3745-31-05(A)(3).
	OAC rule 3745-17-07(B)(1)	The opacity limitation specified by this rule is less stringent than that established by OAC rule 3745-31-05(A)(3).
	OAC rule 3745-17-11(B)(1)	The emission limitation specified by this rule is less stringent than that established by OAC rule 3745-31-05(A)(3).

2. Additional Terms and Conditions

- (a) The 0.98 lbs/hr limitation was established to reflect the potential to emit for the emission unit. Therefore, it is not necessary to develop record keeping and/or reporting requirements to ensure compliance with this limit.
With the issuance of the FESOPs for emissions units F001, F002, F006, F015, F016, F018, K002, P011, P905 and P906 and the issuance of Synthetic Minor PTI 08-04462 (issued 8/14/2003) for emissions units F010, F011, F012, F013, F014, P901, P902, and P903, the total allowable particulate (PE) from these emissions units shall not exceed 77 tons per rolling, 365-day period.

B. Operational Restrictions

1. The annual amount of sand handled shall not exceed 292,000 tons, based upon a rolling, 365-day summation.
2. The pressure drop across baghouse shall be maintained within the range of 0.5 to 7.0 inches of water while the emissions unit is in operation.

C. Monitoring and/or Record Keeping Requirements

1. The permittee shall properly operate and maintain equipment to monitor the pressure drop across each baghouse while the emissions unit is in operation. The monitoring equipment shall be calibrated, operated, and maintained

in accordance with the manufacturer's recommendations, instructions, and operating manual(s).

2. The permittee shall record the pressure drop across the baghouse on a daily basis.
3. The permittee shall maintain daily records of the following information for this emissions unit:
 - a. The amount of sand handled, in tons.
 - b. The rolling, 365-day summation of the amount of sand handled, in tons.
 - c. The calculated PE and rolling 365-day summation of PE, in tons.

D. Reporting Requirements

1. The permittee shall submit quarterly deviation (excursion) reports that identify all exceedances of the following:
 - a. The rolling, 365-day limitation on sand handled, in tons, as specified in section B.1 of this permit.
 - a. All periods of time during which the pressure drop across the baghouse did not comply with the allowable range specified in section B.2 of this permit.

The permittee shall submit quarterly deviation (excursion) reports in accordance with the General Terms and Conditions.
2. The permittee shall submit annual reports, for this emissions unit, which specify the following:
 - a. The total PE, in tons based upon a rolling 365-day summation.
 - b. The amount of sand handled, in tons based upon a rolling 365-day summation.

These reports shall be submitted by January 31 of each year and shall cover the previous calendar year.

E. Testing Requirements

1. Compliance with the emission limitation(s) of these terms and conditions shall be determined in accordance with the following method(s):
 - a. Emission Limitation -
0.98 lbs PE/hr
 - Applicable Compliance Method -
Compliance shall be determined by summing the following products:
 - i. Sand dump:

The maximum hourly process rate of 5.0 tons sand/hour is multiplied by the emissions factor, 0.0415 lb PE/ton, (AP-42, Section 13.2.4, Equation 1 (10/01)), resulting in an emission rate of 0.208 lb/hr.
 - ii. Attrition Mill:

The maximum hourly process rate of 5.0 tons sand/hour is multiplied by the emission factor, 0.015 lb PE/ton (AP-42, Chapter 11, Table 11.19.2-2 (01/95)). The results are then multiplied by a control factor of 97%, i.e., (1 - 0.97), resulting in a controlled emission rate of 0.002 lb/hour.
 - iii. Bucket elevator to vibrating screen:

The maximum hourly process rate of 5.0 tons/hour is multiplied by the emission factor, 0.24 lb PE/ton (AP-42, Chapter 11, Table 11.12-2 (01/95)). The results are then multiplied by a control factor of 97%, i.e., (1 - 0.97), resulting in a controlled emission rate of 0.036 lb/hr.
 - iv. Vibrating screener:

The maximum hourly process rate of 5.0 tons sand/hour is multiplied by the emissions factor, 0.071 lb PE/ton, (AP-42, Chapter 11, Table 11.19-2-2 (01/95)), resulting in an emission rate of 0.355 lb/hr.
 - v. Classifier:

The maximum hourly process rate of 5.0 tons/hour is multiplied by the emission factor, 2.00 lb PE/ton (AP-42, Chapter 11, Table 11.19.1-1 (01/95)). The results are then multiplied by a control factor of 97%, i.e., (1 - 0.97), resulting in a controlled emission rate of 0.30 lb/hr.
 - vi. Bucket elevator to surge hopper:

The maximum hourly process rate of 5.0 tons sand/hour is multiplied by the emissions factor, 0.24 lb PE/ton, (AP-42, Chapter 11, Table 11.12-2 (01/95)). The results are then multiplied by a control factor of 94%, i.e., (1 - 0.94), resulting in a controlled emission rate of 0.071 lb/hr.
 - b. Emission Limitation-
4.26 TPY PE, as a rolling 365-day summation
 - Applicable Compliance Method-
Compliance shall be determined by summing the daily emission calculations for the 365-day period and dividing by 2000 lbs/ton.
 - c. Emission Limitation-
5% opacity as a 3 minute average, as observed from general ventilation egress points.
 - Applicable Compliance Method-
Compliance shall be determined by visible emission evaluations performed in accordance with OAC rule 3745-17-03(B)(3) using the methods and procedures specified in U.S. EPA Reference Method 9 of 40 CFR Part 60,

Appendix A.

d. Emission Limitation-
5% opacity as a 6 minute average.

Applicable Compliance Method-
Compliance shall be determined by visible emission evaluations performed in accordance with OAC rule 3745-17-03(B)(1) using the methods and procedures specified in U.S. EPA Reference Method 9 of 40 CFR Part 60, Appendix A.

F. **Miscellaneous Requirements**

1. None