

Facility ID: 0812100525 Issuance type: Final State Permit To Operate

This version of facility specific terms and conditions was converted from a database format to an HTML file during an upgrade of the Ohio EPA, Division of Air Pollution Control's permitting software. Every attempt has been made to convert the terms and conditions to look and substantively conform to the permit issued or being drafted in STARS. However, the format of the terms may vary slightly from the original. In addition, although it is not expected, there is a slight possibility that a term and condition may have been inadvertently "left out" of this reproduction during the conversion process. Therefore, if this version is to be used as a starting point in drafting a new version of a permit, it is imperative that the entire set of terms and conditions be reviewed to ensure they substantively mimic the issued permit. The official version of any permit issued final by Ohio EPA is kept in the Agency's Legal section. The Legal section may be contacted at (614) 644-3037.

In addition to the terms and conditions, hyperlinks have been inserted into the document so you may more readily access the section of the document you wish to review.

Finally, the term language under "Part II" and before "A. Applicable Emissions Limitations..." has been added to aid in document conversion, and was not part of the original issued permit.

[Go to Part II for Emissions Unit K001](#)

[Go to Part II for Emissions Unit K002](#)

[Go to Part II for Emissions Unit K003](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION

Facility ID: 0812100525 Emissions Unit ID: K001 Issuance type: Final State Permit To Operate

[Go to the top of this document](#)

Part II - Special Terms and Conditions

This permit document constitutes a permit-to-install issued in accordance with ORC 3704.03(F) and a permit-to-operate issued in accordance with ORC 3704.03(G).

1. For the purpose of a permit-to-install document, the emissions unit terms and conditions identified below are federally enforceable with the exception of those listed below which are enforceable under state law only.
 - (a) None.
2. For the purpose of a permit-to-operate document, the emissions unit terms and conditions identified below are enforceable under state law only with the exception of those listed below which are federally enforceable.
 - (a) None.

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
K001 - Spray Table No. 1	OAC rule 3745-31-05(A)(3) PTI 08-04668	Organic compound (OC) emissions shall not exceed 8.0 lbs/hr and 40.0 lbs/day, including cleanup.
	OAC rule 3745-31-05(C) PTI 08-04668 (Synthetic Minor to avoid non attainment provisions)	OC emissions from this emissions unit shall not exceed 7.3 tons/per rolling, 365-day period, including cleanup.
	OAC rule 3745-35-07(B) (Synthetic Minor to avoid Title V permitting)	Individual hazardous air pollutant (HAP) emissions from emissions units K001 thru K003, combined, shall not exceed 9.9 tons per rolling, 365-day period.
	OAC rule 3745-21-07(G)	Combined HAP emissions from emissions units K001 thru K003, combined, shall not exceed 24.9 tons per rolling, 365-day period. See A.2.a.

2. Additional Terms and Conditions

- (a) The hourly and daily OC emission limitations specified by this rule are equivalent* to or less stringent** than the hourly and daily OC emission limitations established pursuant to OAC rule 3745-31-05(A)(3).
 - * when the emissions unit is employing any photochemically reactive material (PRM)
 - ** when the emissions unit is employing only non-PRMs.

B. Operational Restrictions

1. The OC content of the coatings and cleanup materials employed in this emissions unit shall not exceed 6.7 pounds per gallon.
2. The annual coatings and cleanup materials usage, for this emissions unit, combined, shall not exceed 2,179 gallons, based on a rolling, 365-day period.

C. Monitoring and/or Record Keeping Requirements

1. The permittee shall collect and record the following information each day for this emissions unit:
 - a. The company identification for each coating and cleanup material employed.
 - b. The number of gallons of each coating and cleanup material employed.
 - c. The OC content for each coating and cleanup material employed, in pounds per gallon.
 - d. The total OC emission rate for all the coatings and cleanup materials employed, in pounds [summation of (b x c) for all coatings and cleanup materials].
 - e. The total number of hours this emissions unit was in operation.

- f. The average hourly OC emission rate for all the coatings and cleanup materials employed, i.e., (d)/(e), in pounds per hour (average).
- g. The rolling, 365-day coatings and cleanup materials usage rate, in gallons, calculated by adding the current day's coatings and cleanup materials usage, from section C.1.b, to the coatings and cleanup materials usage for the preceding 364 calendar days.
- h. The rolling, 365-day OC emission rate, in tons, calculated by adding the current day's OC emissions, from section C.1.d, to the daily OC emissions for the preceding 364 calendar days, and then dividing by 2000 lbs/ton.
- [Note: The coating information must be for the coatings as employed, including any thinning solvents added at the emissions unit.]
2. The permittee shall collect and record the following information each day for emissions units K001 thru K003, combined:
- a. The name and identification number of each coating, as applied.
- b. The individual HAP* content for each HAP of each coating, in pounds of individual HAP per gallon of coating, as applied.
- c. The total combined HAP content of each coating, in pounds of combined HAPs per gallon of coating, as applied (sum all the individual HAP contents from b).
- d. The number of gallons of each coating employed.
- e. The name and identification number for each cleanup material employed.
- f. The individual HAP content for each HAP of each cleanup material, in pounds of individual HAP per gallon of cleanup material employed.
- g. The total combined HAP content of each cleanup material, in pounds of combined HAPs per gallon of cleanup material employed (sum all the individual HAP contents from f).
- h. The number of gallons of each cleanup material employed.
- i. The total individual HAP emissions for each HAP from all the coatings and cleanup materials employed, in tons [(for each HAP, the summation of (b x d) for each coating + the summation of (f x h) for each cleanup material], divided by 2000 lbs/ton].
- j. The total combined HAP emissions from all the coatings and cleanup materials employed, in tons [(the summation of x d) for each coating + the summation of (g x h) for each cleanup material], divided by 2000 lbs/ton].
- k. The rolling, 365-day individual HAP emission rate, in tons.
- l. The rolling, 365-day combined HAPs emission rate, in tons.
- * A listing of the HAPs can be found in Section 112(b) of the Clean Air Act or can be obtained by contacting your Ohio EPA District Office or local air agency contact. Material Safety Data Sheets typically include a listing of the solvents contained in the coatings or cleanup materials.

D. Reporting Requirements

1. The permittee shall submit quarterly deviation (excursion) reports that identify the following information:
- a. Each day during which the average hourly OC emission rate from the coatings and cleanup materials exceeded 8 pounds per hour, and the actual average hourly OC emission rate for each such day (for this emissions unit).
- b. Each day during which the OC emission rate from the coatings and cleanup materials exceeded 40 pounds per day, and the actual OC emission rate for each such day (for this emissions unit).
- c. All exceedances of the rolling, 365-day OC emission limitation of 7.3 tons (for this emissions unit).
- d. All exceedances of the rolling, 365-day individual HAP emission limitation of 9.9 tons (for emissions units K001 thru K003, combined).
- e. All exceedances of the rolling, 365-day combined HAP emission limitation of 24.9 tons (for emissions units K001 thru K003, combined).
- f. All exceedances of the OC content (for the coatings and cleanup materials) limitation of 6.7 pounds per gallon (for this emissions unit).
- g. All exceedances of the rolling, 365-day combined coating and cleanup material usage restriction of 2,179 gallons per year (for this emissions unit).
- The permittee shall submit the quarterly deviation (excursion) reports in accordance with the General Terms and Conditions of this permit.
2. The permittee shall submit annual reports that summarize the following information:
- a. The total OC emissions from this emissions unit, in tons .
- b. The total individual HAP emissions from emissions units K001 thru K003, combined, in tons.
- c. The total combined HAP emissions from emissions units K001 thru K003, combined, in tons.

d. The actual annual coatings and cleanup materials usage for this emissions unit.

These reports shall be submitted by January 31 of each year and shall cover the previous calendar year.

E. Testing Requirements

1. Compliance with the allowable emission limitations in Section A.1 of these terms and conditions shall be determined in accordance with the following methods:
 - a. Emission Limitation:
8.0 lbs/hr OC

Applicable Compliance Method:
Compliance shall be demonstrated in accordance with the record keeping requirements specified in Section C.1 of this permit.

If required, the permittee shall demonstrate compliance based on results of emission testing conducted in accordance with Methods 18, 25, or 25A, as appropriate, of 40 CFR Part 60, Appendix A.
 - b. Emission Limitation:
40.0 lbs/day OC

Applicable Compliance Method:
Compliance shall be demonstrated in accordance with the record keeping requirements specified in Section C.1 of this permit.
 - c. Emission Limitation:
7.3 tons OC per rolling, 365-day period

Applicable Compliance Method -
Compliance shall be demonstrated in accordance with the record keeping requirements specified in Section C.1 of this permit.
 - d. Emission Limitation:
9.9 tons individual HAP per rolling, 365-day period

Applicable Compliance Method -
Compliance shall be demonstrated in accordance with the record keeping requirements specified in Section C.2 of this permit.
 - e. Emission Limitation:
24.9 tons combined HAP per rolling, 365-day period

Applicable Compliance Method -
Compliance shall be demonstrated in accordance with the record keeping requirements specified in Section C.2 of this permit.
2. Formulation data or USEPA Method 24 shall be used to determine the OC content of each coating and cleanup material.

F. Miscellaneous Requirements

1. None

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION

Facility ID: 0812100525 Emissions Unit ID: K002 Issuance type: Final State Permit To Operate

[Go to the top of this document](#)

Part II - Special Terms and Conditions

This permit document constitutes a permit-to-install issued in accordance with ORC 3704.03(F) and a permit-to-operate issued in accordance with ORC 3704.03(G).

1. For the purpose of a permit-to-install document, the emissions unit terms and conditions identified below are federally enforceable with the exception of those listed below which are enforceable under state law only.
 - (a) None.
2. For the purpose of a permit-to-operate document, the emissions unit terms and conditions identified below are enforceable under state law only with the exception of those listed below which are federally enforceable.
 - (a) None.

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
---	--------------------------------------	--

K001 - Spray Table No. 2	OAC rule 3745-31-05(A)(3) PTI 08-04668 OAC rule 3745-31-05(C) PTI 08-04668 (Synthetic Minor to avoid non attainment provisions) OAC rule 3745-35-07(B) (Synthetic Minor to avoid Title V permitting) OAC rule 3745-21-07(G)	Organic compound (OC) emissions shall not exceed 8.0 lbs/hr and 40.0 lbs/day, including cleanup. OC emissions from this emissions unit shall not exceed 7.3 tons/per rolling, 365-day period, including cleanup. Individual hazardous air pollutant (HAP) emissions from emissions units K001 thru K003, combined, shall not exceed 9.9 tons per rolling, 365-day period. Combined HAP emissions from emissions units K001 thru K003, combined, shall not exceed 24.9 tons per rolling, 365-day period. See A.2.a.
--------------------------	--	--

2. **Additional Terms and Conditions**

- (a) The hourly and daily OC emission limitations specified by this rule are equivalent* to or less stringent** than the hourly and daily OC emission limitations established pursuant to OAC rule 3745-31-05(A)(3).

* when the emissions unit is employing any photochemically reactive material (PRM)

** when the emissions unit is employing only non-PRMs.

B. **Operational Restrictions**

- 1. The OC content of the coatings and cleanup materials employed in this emissions unit shall not exceed 6.7 pounds per gallon.
- 2. The annual coatings and cleanup materials usage, for this emissions unit, combined, shall not exceed 2,179 gallons, based on a rolling, 365-day period.

C. **Monitoring and/or Record Keeping Requirements**

- 1. The permittee shall collect and record the following information each day for this emissions unit:
 - a. The company identification for each coating and cleanup material employed.
 - b. The number of gallons of each coating and cleanup material employed.
 - c. The OC content for each coating and cleanup material employed, in pounds per gallon.
 - d. The total OC emission rate for all the coatings and cleanup materials employed, in pounds [summation of (b x c) for all coatings and cleanup materials].
 - e. The total number of hours this emissions unit was in operation.
 - f. The average hourly OC emission rate for all the coatings and cleanup materials employed, i.e., (d)/(e), in pounds per hour (average).
 - g. The rolling, 365-day coatings and cleanup materials usage rate, in gallons, calculated by adding the current day's coatings and cleanup materials usage, from section C.1.b, to the coatings and cleanup materials usage for the preceding 364 calendar days.
 - h. The rolling, 365-day OC emission rate, in tons, calculated by adding the current day's OC emissions, from section C.1.d, to the daily OC emissions for the preceding 364 calendar days, and then dividing by 2000 lbs/ton.

[Note: The coating information must be for the coatings as employed, including any thinning solvents added at the emissions unit.]

- 2. The permittee shall collect and record the following information each day for emissions units K001 thru K003, combined:
 - a. The name and identification number of each coating, as applied.
 - b. The individual HAP* content for each HAP of each coating, in pounds of individual HAP per gallon of coating, as applied.
 - c. The total combined HAP content of each coating, in pounds of combined HAPs per gallon of coating, as applied (sum all the individual HAP contents from b).
 - d. The number of gallons of each coating employed.
 - e. The name and identification number for each cleanup material employed.
 - f. The individual HAP content for each HAP of each cleanup material, in pounds of individual HAP per gallon of cleanup material employed.
 - g. The total combined HAP content of each cleanup material, in pounds of combined HAPs per gallon of cleanup material employed (sum all the individual HAP contents from f).
 - h. The number of gallons of each cleanup material employed.
 - i. The total individual HAP emissions for each HAP from all the coatings and cleanup materials employed, in tons [(for each HAP, the summation of (b x d) for each coating + the summation of (f x h) for each cleanup material), divided by 2000 lbs/ton].
 - j. The total combined HAP emissions from all the coatings and cleanup materials employed, in tons [(the summation of x d) for each coating + the summation of (g x h) for each cleanup material], divided by 2000

lbs/ton].

k. The rolling, 365-day individual HAP emission rate, in tons.

l. The rolling, 365-day combined HAPs emission rate, in tons.

* A listing of the HAPs can be found in Section 112(b) of the Clean Air Act or can be obtained by contacting your Ohio EPA District Office or local air agency contact. Material Safety Data Sheets typically include a listing of the solvents contained in the coatings or cleanup materials.

D. Reporting Requirements

1. The permittee shall submit quarterly deviation (excursion) reports that identify the following information:
 - a. Each day during which the average hourly OC emission rate from the coatings and cleanup materials exceeded 8 pounds per hour, and the actual average hourly OC emission rate for each such day (for this emissions unit).
 - b. Each day during which the OC emission rate from the coatings and cleanup materials exceeded 40 pounds per day, and the actual OC emission rate for each such day (for this emissions unit).
 - c. All exceedances of the rolling, 365-day OC emission limitation of 7.3 tons (for this emissions unit).
 - d. All exceedances of the rolling, 365-day individual HAP emission limitation of 9.9 tons (for emissions units K001 thru K003, combined).
 - e. All exceedances of the rolling, 365-day combined HAP emission limitation of 24.9 tons (for emissions units K001 thru K003, combined).
 - f. All exceedances of the OC content (for the coatings and cleanup materials) limitation of 6.7 pounds per gallon (for this emissions unit).
 - g. All exceedances of the rolling, 365-day combined coating and cleanup material usage restriction of 2,179 gallons per year (for this emissions unit).

The permittee shall submit the quarterly deviation (excursion) reports in accordance with the General Terms and Conditions of this permit.
2. The permittee shall submit annual reports that summarize the following information:
 - a. The total OC emissions from this emissions unit, in tons .
 - b. The total individual HAP emissions from emissions units K001 thru K003, combined, in tons.
 - c. The total combined HAP emissions from emissions units K001 thru K003, combined, in tons.
 - d. The actual annual coatings and cleanup materials usage for this emissions unit.

These reports shall be submitted by January 31 of each year and shall cover the previous calendar year.

E. Testing Requirements

1. Compliance with the allowable emission limitations in Section A.1 of these terms and conditions shall be determined in accordance with the following methods:
 - a. Emission Limitation:
8.0 lbs/hr OC

Applicable Compliance Method:
Compliance shall be demonstrated in accordance with the record keeping requirements specified in Section C.1 of this permit.

If required, the permittee shall demonstrate compliance based on results of emission testing conducted in accordance with Methods 18, 25, or 25A, as appropriate, of 40 CFR Part 60, Appendix A.
 - b. Emission Limitation:
40.0 lbs/day OC

Applicable Compliance Method:
Compliance shall be demonstrated in accordance with the record keeping requirements specified in Section C.1 of this permit.
 - c. Emission Limitation:
7.3 tons OC per rolling, 365-day period

Applicable Compliance Method -
Compliance shall be demonstrated in accordance with the record keeping requirements specified in Section C.1 of this permit.
 - d. Emission Limitation:
9.9 tons individual HAP per rolling, 365-day period

Applicable Compliance Method -
Compliance shall be demonstrated in accordance with the record keeping requirements specified in Section C.2 of this permit.
 - e. Emission Limitation:
24.9 tons combined HAP per rolling, 365-day period

Applicable Compliance Method -
Compliance shall be demonstrated in accordance with the record keeping requirements specified in Section C.2 of this permit.

2. Formulation data or USEPA Method 24 shall be used to determine the OC content of each coating and cleanup material.

F. Miscellaneous Requirements

1. None

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION

Facility ID: 0812100525 Emissions Unit ID: K003 Issuance type: Final State Permit To Operate

[Go to the top of this document](#)

Part II - Special Terms and Conditions

This permit document constitutes a permit-to-install issued in accordance with ORC 3704.03(F) and a permit-to-operate issued in accordance with ORC 3704.03(G).

1. For the purpose of a permit-to-install document, the emissions unit terms and conditions identified below are federally enforceable with the exception of those listed below which are enforceable under state law only.
 - (a) None.
2. For the purpose of a permit-to-operate document, the emissions unit terms and conditions identified below are enforceable under state law only with the exception of those listed below which are federally enforceable.
 - (a) None.

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
K001 - Spray Table No. 3	OAC rule 3745-31-05(A)(3) PTI 08-04668	Organic compound (OC) emissions shall not exceed 8.0 lbs/hr and 40.0 lbs/day, including cleanup.
	OAC rule 3745-31-05(C) PTI 08-04668 (Synthetic Minor to avoid non attainment provisions)	OC emissions from this emissions unit shall not exceed 7.3 tons/per rolling, 365-day period, including cleanup.
	OAC rule 3745-35-07(B) (Synthetic Minor to avoid Title V permitting)	Individual hazardous air pollutant (HAP) emissions from emissions units K001 thru K003, combined, shall not exceed 9.9 tons per rolling, 365-day period.
	OAC rule 3745-21-07(G)	Combined HAP emissions from emissions units K001 thru K003, combined, shall not exceed 24.9 tons per rolling, 365-day period. See A.2.a.

2. **Additional Terms and Conditions**
 - (a) The hourly and daily OC emission limitations specified by this rule are equivalent* to or less stringent** than the hourly and daily OC emission limitations established pursuant to OAC rule 3745-31-05(A)(3).
 - * when the emissions unit is employing any photochemically reactive material (PRM)
 - ** when the emissions unit is employing only non-PRMs.

B. Operational Restrictions

1. The OC content of the coatings and cleanup materials employed in this emissions unit shall not exceed 6.7 pounds per gallon.
2. The annual coatings and cleanup materials usage, for this emissions unit, combined, shall not exceed 2,179 gallons, based on a rolling, 365-day period.

C. Monitoring and/or Record Keeping Requirements

1. The permittee shall collect and record the following information each day for this emissions unit:
 - a. The company identification for each coating and cleanup material employed.
 - b. The number of gallons of each coating and cleanup material employed.
 - c. The OC content for each coating and cleanup material employed, in pounds per gallon.

- d. The total OC emission rate for all the coatings and cleanup materials employed, in pounds [summation of (b x c) for all coatings and cleanup materials].
- e. The total number of hours this emissions unit was in operation.
- f. The average hourly OC emission rate for all the coatings and cleanup materials employed, i.e., (d)/(e), in pounds per hour (average).
- g. The rolling, 365-day coatings and cleanup materials usage rate, in gallons, calculated by adding the current day's coatings and cleanup materials usage, from section C.1.b, to the coatings and cleanup materials usage for the preceding 364 calendar days.
- h. The rolling, 365-day OC emission rate, in tons, calculated by adding the current day's OC emissions, from section C.1.d, to the daily OC emissions for the preceding 364 calendar days, and then dividing by 2000 lbs/ton.
- [Note: The coating information must be for the coatings as employed, including any thinning solvents added at the emissions unit.]
2. The permittee shall collect and record the following information each day for emissions units K001 thru K003, combined:
- a. The name and identification number of each coating, as applied.
- b. The individual HAP* content for each HAP of each coating, in pounds of individual HAP per gallon of coating, as applied.
- c. The total combined HAP content of each coating, in pounds of combined HAPs per gallon of coating, as applied (sum all the individual HAP contents from b).
- d. The number of gallons of each coating employed.
- e. The name and identification number for each cleanup material employed.
- f. The individual HAP content for each HAP of each cleanup material, in pounds of individual HAP per gallon of cleanup material employed.
- g. The total combined HAP content of each cleanup material, in pounds of combined HAPs per gallon of cleanup material employed (sum all the individual HAP contents from f).
- h. The number of gallons of each cleanup material employed.
- i. The total individual HAP emissions from all the coatings and cleanup materials employed, in tons [(for each HAP, the summation of (b x d) for each coating + the summation of (f x h) for each cleanup material], divided by 2000 lbs/ton].
- j. The total combined HAP emissions from all the coatings and cleanup materials employed, in tons [(the summation of x d) for each coating + the summation of (g x h) for each cleanup material], divided by 2000 lbs/ton].
- k. The rolling, 365-day individual HAP emission rate, in tons.
- l. The rolling, 365-day combined HAPs emission rate, in tons.

* A listing of the HAPs can be found in Section 112(b) of the Clean Air Act or can be obtained by contacting your Ohio EPA District Office or local air agency contact. Material Safety Data Sheets typically include a listing of the solvents contained in the coatings or cleanup materials.

D. Reporting Requirements

1. The permittee shall submit quarterly deviation (excursion) reports that identify the following information:
- a. Each day during which the average hourly OC emission rate from the coatings and cleanup materials exceeded 8 pounds per hour, and the actual average hourly OC emission rate for each such day (for this emissions unit).
- b. Each day during which the OC emission rate from the coatings and cleanup materials exceeded 40 pounds per day, and the actual OC emission rate for each such day (for this emissions unit).
- c. All exceedances of the rolling, 365-day OC emission limitation of 7.3 tons (for this emissions unit).
- d. All exceedances of the rolling, 365-day individual HAP emission limitation of 9.9 tons (for emissions units K001 thru K003, combined).
- e. All exceedances of the rolling, 365-day combined HAP emission limitation of 24.9 tons (for emissions units K001 thru K003, combined).
- f. All exceedances of the OC content (for the coatings and cleanup materials) limitation of 6.7 pounds per gallon (for this emissions unit).
- g. All exceedances of the rolling, 365-day combined coating and cleanup material usage restriction of 2,179 gallons per year (for this emissions unit).
- The permittee shall submit the quarterly deviation (excursion) reports in accordance with the General Terms and Conditions of this permit.
2. The permittee shall submit annual reports that summarize the following information:
- a. The total OC emissions from this emissions unit, in tons .

b. The total individual HAP emissions from emissions units K001 thru K003, combined, in tons.

c. The total combined HAP emissions from emissions units K001 thru K003, combined, in tons.

d. The actual annual coatings and cleanup materials usage for this emissions unit.

These reports shall be submitted by January 31 of each year and shall cover the previous calendar year.

E. Testing Requirements

1. Compliance with the allowable emission limitations in Section A.1 of these terms and conditions shall be determined in accordance with the following methods:

a. Emission Limitation:
8.0 lbs/hr OC

Applicable Compliance Method:
Compliance shall be demonstrated in accordance with the record keeping requirements specified in Section C.1 of this permit.

If required, the permittee shall demonstrate compliance based on results of emission testing conducted in accordance with Methods 18, 25, or 25A, as appropriate, of 40 CFR Part 60, Appendix A.

b. Emission Limitation:
40.0 lbs/day OC

Applicable Compliance Method:
Compliance shall be demonstrated in accordance with the record keeping requirements specified in Section C.1 of this permit.

c. Emission Limitation:
7.3 tons OC per rolling, 365-day period

Applicable Compliance Method -
Compliance shall be demonstrated in accordance with the record keeping requirements specified in Section C.1 of this permit.

d. Emission Limitation:
9.9 tons individual HAP per rolling, 365-day period

Applicable Compliance Method -
Compliance shall be demonstrated in accordance with the record keeping requirements specified in Section C.2 of this permit.

e. Emission Limitation:
24.9 tons combined HAP per rolling, 365-day period

Applicable Compliance Method -
Compliance shall be demonstrated in accordance with the record keeping requirements specified in Section C.2 of this permit.

2. Formulation data or USEPA Method 24 shall be used to determine the OC content of each coating and cleanup material.

F. Miscellaneous Requirements

1. None