**John R. Kasich**, Governor
**Mary Taylor**, Lt. Governor
**Craig W. Butler**, Director

6/9/2014

Certified Mail

| | |
|---|---|
| No | TOXIC REVIEW |
| No | PSD |
| No | SYNTHETIC MINOR TO AVOID MAJOR NSR |
| No | CEMS |
| Yes | MACT/GACT |
| No | NSPS |
| No | NESHAPS |
| No | NETTING |
| No | MAJOR NON-ATTAINMENT |
| No | MODELING SUBMITTED |
| No | MAJOR GHG |
| No | SYNTHETIC MINOR TO AVOID MAJOR GHG |

Gale Bradley
Americas Styrenics
925 County Road 1A
Ironton, OH 45638

RE: DRAFT AIR POLLUTION PERMIT-TO-INSTALL
Facility ID: 0744000173
Permit Number: P0116861
Permit Type: Administrative Modification
County: Lawrence

Dear Permit Holder:

A draft of the Ohio Administrative Code (OAC) Chapter 3745-31 Air Pollution Permit-to-Install for the referenced facility has been issued for the emissions unit(s) listed in the Authorization section of the enclosed draft permit. This draft action is not an authorization to begin construction or modification of your emissions unit(s). The purpose of this draft is to solicit public comments on the permit. A public notice will appear in the Ohio Environmental Protection Agency (EPA) Weekly Review and the local newspaper, The Ironton Tribune. A copy of the public notice and the draft permit are enclosed. This permit can be accessed electronically on the Division of Air Pollution Control (DAPC) Web page, www.epa.ohio.gov/dapc by clicking the "Search for Permits" link under the Permitting topic on the Programs tab. Comments will be accepted as a marked-up copy of the draft permit or in narrative format. Any comments must be sent to the following:

Andrew Hall
Permit Review/Development Section
Ohio EPA, DAPC
50 West Town Street, Suite 700
P.O. Box 1049
Columbus, Ohio 43216-1049

and

Portsmouth City Health Dept., Air Pollution Unit
605 Washington Street
3rd Floor
Portsmouth, OH 45662

Comments and/or a request for a public hearing will be accepted within 30 days of the date the notice is published in the newspaper. You will be notified in writing if a public hearing is scheduled. A decision on issuing a final permit-to-install will be made after consideration of comments received and oral testimony if a public hearing is conducted. Any permit fee that will be due upon issuance of a final Permit-to-Install is indicated in the Authorization section. Please do not submit any payment now. If you have any questions, please contact Portsmouth City Health Dept., Air Pollution Unit at (740)353-5156.

Sincerely,

Michael W. Ahern

Michael W. Ahern, Manager
Permit Issuance and Data Management Section, DAPC

Cc: U.S. EPA Region 5 -*Via E-Mail Notification*
Portsmouth; Kentucky; West Virginia

Lawrence County

PUBLIC NOTICE
Issuance of Draft Air Pollution Permit-To-Install
Americas Styrenics

| | |
|---|---|
| Issue Date: | 6/9/2014 |
| Permit Number: | P0116861 |
| Permit Type: | Administrative Modification |
| Permit Description: | Administrative permit modification for two 9.0 MMBtu/hr Dowtherm boilers (B010 and B020) to increase the amount of byproduct fuel burned without increasing emissions.. |
| Facility ID: | 0744000173 |
| Facility Location: | Americas Styrenics<br>925 County Road, 1A<br>Ironton, OH 45638 |
| Facility Description: | Plastics Material and Resin Manufacturing |

The Director of the Ohio Environmental Protection Agency issued the draft permit above. The permit and complete instructions for requesting information or submitting comments may be obtained at: http://epa.ohio.gov/dapc/permitsonline.aspx by entering the permit # or: Anne Chamberlin, Portsmouth City Health Dept., Air Pollution Unit, 605 Washington Street 3rd Floor, Portsmouth, OH 45662. Ph: (740)353-5156

# DRAFT

# Division of Air Pollution Control
# Permit-to-Install
for
Americas Styrenics

| | |
|---|---|
| Facility ID: | 0744000173 |
| Permit Number: | P0116861 |
| Permit Type: | Administrative Modification |
| Issued: | 6/9/2014 |
| Effective: | To be entered upon final issuance |

**Division of Air Pollution Control**
**Permit-to-Install**
for
Americas Styrenics

**Table of Contents**


Authorization ..... 1
A. Standard Terms and Conditions ..... 3
1. Federally Enforceable Standard Terms and Conditions ..... 4
2. Severability Clause ..... 4
3. General Requirements ..... 4
4. Monitoring and Related Record Keeping and Reporting Requirements ..... 5
5. Scheduled Maintenance/Malfunction Reporting ..... 6
6. Compliance Requirements ..... 6
7. Best Available Technology ..... 7
8. Air Pollution Nuisance ..... 8
9. Reporting Requirements ..... 8
10. Applicability ..... 8
11. Construction of New Sources(s) and Authorization to Install ..... 8
12. Permit-To-Operate Application ..... 9
13. Construction Compliance Certification ..... 10
14. Public Disclosure ..... 10
15. Additional Reporting Requirements When There Are No Deviations of Federally Enforceable Emission Limitations, Operational Restrictions, or Control Device Operating Parameter Limitations ..... 10
16. Fees ..... 10
17. Permit Transfers ..... 10
18. Risk Management Plans ..... 10
19. Title IV Provisions ..... 10
B. Facility-Wide Terms and Conditions ..... 11
C. Emissions Unit Terms and Conditions ..... 13
1. B010, Dowtherm Boiler R-1 ..... 14
2. B020, Dowtherm Boiler R-3 ..... 21

# Authorization

| | |
|---|---|
| Facility ID: | 0744000173 |
| Facility Description: | |
| Application Number(s): | M0002782 |
| Permit Number: | P0116861 |
| Permit Description: | Administrative permit modification for two 9.0 MMBtu/hr Dowtherm boilers (B010 and B020) to increase the amount of byproduct fuel burned without increasing emissions.. |
| Permit Type: | Administrative Modification |
| Permit Fee: | $200.00*DO NOT send payment at this time, subject to change before final issuance* |
| Issue Date: | 6/9/2014 |
| Effective Date: | To be entered upon final issuance |

This document constitutes issuance to:

Americas Styrenics
925 County Road
1A
Ironton, OH 45638

of a Permit-to-Install for the emissions unit(s) identified on the following page.

Ohio Environmental Protection Agency (EPA) District Office or local air agency responsible for processing and administering your permit:

Portsmouth City Health Dept., Air Pollution Unit
605 Washington Street
3rd Floor
Portsmouth, OH 45662
(740)353-5156

The above named entity is hereby granted a Permit-to-Install for the emissions unit(s) listed in this section pursuant to Chapter 3745-31 of the Ohio Administrative Code. Issuance of this permit does not constitute expressed or implied approval or agreement that, if constructed or modified in accordance with the plans included in the application, the emissions unit(s) of environmental pollutants will operate in compliance with applicable State and Federal laws and regulations, and does not constitute expressed or implied assurance that if constructed or modified in accordance with those plans and specifications, the above described emissions unit(s) of pollutants will be granted the necessary permits to operate (air) or NPDES permits as applicable.

This permit is granted subject to the conditions attached hereto.

Ohio Environmental Protection Agency

Craig W. Butler
Director

# Authorization (continued)

Permit Number: P0116861
Permit Description: Administrative permit modification for two 9.0 MMBtu/hr Dowtherm boilers (B010 and B020) to increase the amount of byproduct fuel burned without increasing emissions..

Permits for the following Emissions Unit(s) or groups of Emissions Units are in this document as indicated below:

| | |
|---|---|
| **Emissions Unit ID:** | **B010** |
| Company Equipment ID: | Dowtherm Boiler R-1 |
| Superseded Permit Number: | P0107189 |
| General Permit Category and Type: | Not Applicable |
| **Emissions Unit ID:** | **B020** |
| Company Equipment ID: | Dowtherm Boiler R-3 |
| Superseded Permit Number: | P0107189 |
| General Permit Category and Type: | Not Applicable |

# A. Standard Terms and Conditions

**1. Federally Enforceable Standard Terms and Conditions**

a) All Standard Terms and Conditions are federally enforceable, with the exception of those listed below which are enforceable under State law only:

(1) Standard Term and Condition A.2.a), Severability Clause

(2) Standard Term and Condition A.3.c) through A. 3.e)General Requirements

(3) Standard Term and Condition A.6.c) and A. 6.d), Compliance Requirements

(4) Standard Term and Condition A.9., Reporting Requirements

(5) Standard Term and Condition A.10., Applicability

(6) Standard Term and Condition A.11.b) through A.11.e), Construction of New Source(s) and Authorization to Install

(7) Standard Term and Condition A.14., Public Disclosure

(8) Standard Term and Condition A.15., Additional Reporting Requirements When There Are No Deviations of Federally Enforceable Emission Limitations, Operational Restrictions, or Control Device Operating Parameter Limitations

(9) Standard Term and Condition A.16., Fees

(10) Standard Term and Condition A.17., Permit Transfers

**2. Severability Clause**

a) A determination that any term or condition of this permit is invalid shall not invalidate the force or effect of any other term or condition thereof, except to the extent that any other term or condition depends in whole or in part for its operation or implementation upon the term or condition declared invalid.

b) All terms and conditions designated in parts B and C of this permit are federally enforceable as a practical matter, if they are required under the Act, or any of its applicable requirements, including relevant provisions designed to limit the potential to emit of a source, are enforceable by the Administrator of the U.S. EPA and the State and by citizens (to the extent allowed by section 304 of the Act) under the Act. Terms and conditions in parts B and C of this permit shall not be federally enforceable and shall be enforceable under State law only, only if specifically identified in this permit as such.

**3. General Requirements**

a) Any noncompliance with the federally enforceable terms and conditions of this permit constitutes a violation of the Act, and is grounds for enforcement action or for permit revocation, revocation and re-issuance, or modification.

b) It shall not be a defense for the permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the federally enforceable terms and conditions of this permit.

c) This permit may be modified, revoked, or revoked and reissued, for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or revocation, or of a notification of planned changes or anticipated noncompliance does not stay any term and condition of this permit.

d) This permit does not convey any property rights of any sort, or any exclusive privilege.

e) The permittee shall furnish to the Director of the Ohio EPA, or an authorized representative of the Director, upon receipt of a written request and within a reasonable time, any information that may be requested to determine whether cause exists for modifying or revoking this permit or to determine compliance with this permit. Upon request, the permittee shall also furnish to the Director or an authorized representative of the Director, copies of records required to be kept by this permit. For information claimed to be confidential in the submittal to the Director, if the Administrator of the U.S. EPA requests such information, the permittee may furnish such records directly to the Administrator along with a claim of confidentiality.

**4. Monitoring and Related Record Keeping and Reporting Requirements**

a) Except as may otherwise be provided in the terms and conditions for a specific emissions unit, the permittee shall maintain records that include the following, where applicable, for any required monitoring under this permit:

(1) The date, place (as defined in the permit), and time of sampling or measurements.

(2) The date(s) analyses were performed.

(3) The company or entity that performed the analyses.

(4) The analytical techniques or methods used.

(5) The results of such analyses.

(6) The operating conditions existing at the time of sampling or measurement.

b) Each record of any monitoring data, testing data, and support information required pursuant to this permit shall be retained for a period of five years from the date the record was created. Support information shall include, but not be limited to all calibration and maintenance records and all original strip-chart recordings for continuous monitoring instrumentation, and copies of all reports required by this permit. Such records may be maintained in computerized form.

c) Except as may otherwise be provided in the terms and conditions for a specific emissions unit, the permittee shall submit required reports in the following manner:

(1) Reports of any required monitoring and/or recordkeeping of federally enforceable information shall be submitted to the Portsmouth City Health Dept., Air Pollution Unit.

(2) Quarterly written reports of (i) any deviations from federally enforceable emissionlimitations, operationalrestrictions, andcontroldeviceoperatingparameterlimitations, excluding deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06, that have been detected by the testing, monitoring and recordkeeping requirements specified in this permit, (ii) the probable cause of such deviations, and (iii) any corrective actions or preventive measures taken, shall be made to the Portsmouth City Health Dept., Air Pollution Unit. The written reports shall be submitted quarterly, by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters. See A.15. below if no deviations occurred during the quarter.

(3) Written reports, which identify any deviations from the federally enforceable monitoring, recordkeeping, andreportingrequirements contained in this permit shall be submitted to the Portsmouth City Health Dept., Air Pollution Unit every six months, by January 31 and July 31 of each year for the previous six calendar months. If no deviations occurred during a six-month period, the permittee shall submit a semi-annual report, which states that no deviations occurred during that period.

(4) This permit is for an emissions unit located at a Title V facility. Each written report shall be signed by a responsible official certifying that, based on information and belief formed after reasonable inquiry, the statements and information in the report are true, accurate, and complete.

d) The permittee shall report actual emissions pursuant to OAC Chapter 3745-78 for the purpose of collecting Air Pollution Control Fees.

**5. Scheduled Maintenance/Malfunction Reporting**

Any scheduled maintenance of air pollution control equipment shall be performed in accordance with paragraph (A) of OAC rule 3745-15-06. The malfunction, i.e., upset, of any emissions units or any associated air pollution control system(s) shall be reported to thePortsmouth City Health Dept., Air Pollution Unitin accordance with paragraph (B) of OAC rule 3745-15-06. (The definition of an upset condition shall be the same as that used in OAC rule 3745-15-06(B)(1) for a malfunction.) The verbal and written reports shall be submitted pursuant to OAC rule 3745-15-06.

Except as provided in that rule, any scheduled maintenance or malfunction necessitating the shutdown or bypassing of any air pollution control system(s) shall be accompanied by the shutdown of the emission unit(s) that is (are) served by such control system(s).

**6. Compliance Requirements**

a) All applications, notifications or reports required by terms and conditions in this permit to be submitted or "reported in writing" are to be submitted to Ohio EPA through the Ohio EPA's eBusiness Center: Air Services web service ("Air Services"). Ohio EPA will accept hard copy submittals on an as-needed basis if the permittee cannot submit the required documents through the Ohio EPA eBusiness Center. In the event of an alternative hard copy submission in lieu of the eBusiness Center, the post-marked date or the date the document is delivered in person will be recognized as the date submitted. Electronic submission of applications, notifications or reports required to be submitted to Ohio EPA fulfills the requirement to submit the required information to the Director, the appropriate Ohio EPA District Office or contracted

local air agency, and/or any other individual or organization specifically identified as an additional recipient identified in this permit unless otherwise specified. Consistent with OAC rule 3745-15-03, the electronic signature date shall constitute the date that the required application, notification or report is considered to be "submitted". Any document requiring signature may be represented by entry of the personal identification number (PIN) by responsible official as part of the electronic submission process or by the scanned attestation document signed by the Authorized Representative that is attached to the electronically submitted written report.

Any document (including reports) required to be submitted and required by a federally applicable requirement in this permit shall include a certification by a Responsible Official that, based on information and belief formed after reasonable inquiry, the statements in the document are true, accurate, and complete

b) Upon presentation of credentials and other documents as may be required by law, the permittee shall allow the Director of the Ohio EPA or an authorized representative of the Director to:

(1) At reasonable times, enter upon the permittee's premises where a source is located or the emissions-related activity is conducted, or where records must be kept under the conditions of this permit.

(2) Have access to and copy, at reasonable times, any records that must be kept under the conditions of this permit, subject to the protection from disclosure to the public of confidential information consistent with ORC section 3704.08.

(3) Inspect at reasonable times any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under this permit.

(4) As authorized by the Act, sample or monitor at reasonable times substances or parameters for the purpose of assuring compliance with the permit and applicable requirements.

c) The permittee shall submit progress reports to the Portsmouth City Health Dept., Air Pollution Unit concerning any schedule of compliance for meeting an applicable requirement. Progress reports shall be submitted semiannually or more frequently if specified in the applicable requirement or by the Director of the Ohio EPA. Progress reports shall contain the following:

(1) Dates for achieving the activities, milestones, or compliance required in any schedule of compliance, and dates when such activities, milestones, or compliance were achieved.

(2) An explanation of why any dates in any schedule of compliance were not or will not be met, and any preventive or corrective measures adopted.

## 7. Best Available Technology

As specified in OAC Rule 3745-31-05, new sources that must employ Best Available Technology (BAT) shall comply with the Applicable Emission Limitations/Control Measures identified as BAT for each subject emissions unit.

**8. Air Pollution Nuisance**

The air contaminants emitted by the emissions units covered by this permit shall not cause a public nuisance, in violation of OAC rule 3745-15-07.

**9. Reporting Requirements**

The permittee shall submit required reports in the following manner:

a) Reports of any required monitoring and/or recordkeeping of state-only enforceable information shall be submitted to the Portsmouth City Health Dept., Air Pollution Unit.

b) Except as otherwise may be provided in the terms and conditions for a specific emissions unit, quarterly written reports of (a) any deviations (excursions) from state-only required emission limitations, operational restrictions, and control device operating parameter limitations that have been detected by the testing, monitoring, and recordkeeping requirements specified in this permit, (b) the probable cause of such deviations, and (c) any corrective actions or preventive measures which have been or will be taken, shall be submitted to thePortsmouth City Health Dept., Air Pollution Unit. If no deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted quarterly, by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters. (These quarterly reports shall exclude deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06.)

**10. Applicability**

This Permit-to-Install is applicable only to the emissions unit(s) identified in the Permit-to-Install. Separate application must be made to the Director for the installation or modification of any other emissions unit(s)not exempt from the requirement to obtain a Permit-to-Install.

**11. Construction of New Sources(s) and Authorization to Install**

a) This permit does not constitute an assurance that the proposed source will operate in compliance with all Ohio laws and regulations. This permit does not constitute expressed or implied assurance that the proposed facility has been constructed in accordance with the application and terms and conditions of this permit. The action of beginning and/or completing construction prior to obtaining the Director's approval constitutes a violation of OAC rule 3745-31-02. Furthermore, issuance of this permit does not constitute an assurance that the proposed source will operate in compliance with all Ohio laws and regulations. Issuance of this permit is not to be construed as a waiver of any rights that the Ohio Environmental Protection Agency (or other persons) may have against the applicant for starting construction prior to the effective date of the permit. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed facilities cannot meet the requirements of this permit or cannot meet applicable standards.

b) If applicable, authorization to install any new emissions unit included in this permit shall terminate within eighteen months of the effective date of the permit if the owner or operator has not undertaken a continuing program of installation or has not entered into a binding contractual

obligation to undertake and complete within a reasonable time a continuing program of installation. This deadline may be extended by up to 12 months if application is made to the Director within a reasonable time before the termination date and the permittee shows good cause for any such extension.

c) The permittee may notify Ohio EPA of any emissions unit that is permanently shut down (i.e., the emissions unit has been physically removed from service or has been altered in such a way that it can no longer operate without a subsequent "modification" or "installation" as defined in OAC Chapter 3745-31) by submitting a certification from the authorized official that identifies the date on which the emissions unit was permanently shut down. Authorization to operate the affected emissions unit shall cease upon the date certified by the authorized official that the emissions unit was permanently shut down. At a minimum, notification of permanent shut down shall be made or confirmed by marking the affected emissions unit(s) as “permanently shut down” in “Air Services” along with the date the emissions unit(s) was permanently removed and/or disabled. Submitting the facility profile update electronically will constitute notifying the Director of the permanent shutdown of the affected emissions unit(s).

d) The provisions of this permit shall cease to be enforceable for each affected emissions unit after the date on which an emissions unit is permanently shut down (i.e., emissions unit has been physically removed from service or has been altered in such a way that it can no longer operate without a subsequent "modification" or "installation" as defined in OAC Chapter 3745-31). All records relating to any permanently shutdown emissions unit, generated while the emissions unit was in operation, must be maintained in accordance with law. All reports required by this permit must be submitted for any period an affected emissions unit operated prior to permanent shut down. At a minimum, the permit requirements must be evaluated as part of the reporting requirements identified in this permit covering the last period the emissions unit operated.

Unless otherwise exempted,no emissions unit certified by the responsible official as being permanently shut down may resume operation without first applying for and obtaining a permit pursuant to OAC Chapter 3745-31 and OAC Chapter 3745-77 if the restarted operation is subject to one or more applicable requirements.

e) The permittee shall comply with any residual requirements related to this permit, such as the requirement to submit a deviation report, air fee emission report, or other any reporting required by this permit for the period the operating provisions of this permit were enforceable, or as required by regulation or law. All reports shall be submitted in a form and manner prescribed by the Director. All records relating to this permit must be maintained in accordance with law.

**12. Permit-To-Operate Application**

The permittee is required to apply for a Title V permit pursuant to OAC Chapter 3745-77. The permittee shall submit a complete Title V permit application or a complete Title V permit modification application within twelve (12) months after commencing operation of the emissions units covered by this permit. However, if operation of the proposed new or modified source(s) as authorized by this permit would be prohibited by the terms and conditions of an existing Title V permit, a Title V permit modification of such new or modified source(s) pursuant to OAC rule 3745-77-04(D) and OAC rule 3745-77-08(C)(3)(d)must be <u>obtained before</u>operating the source in a manner that would violate the existing Title V permit requirements.

**13. Construction Compliance Certification**

The applicant shall identify the following dates in the "Air Services" facility profile for each new emissions unit identified in this permit.

a) Completion of initial installation date shall be enteredupon completion of construction and prior to start-up.

b) Commence operation after installation or latest modification date shall be entered within 90 days after commencing operation of the applicable emissions unit.

**14. Public Disclosure**

The facility is hereby notified that this permit, and all agency records concerning the operation of this permitted source, are subject to public disclosure in accordance with OAC rule 3745-49-03.

**15. Additional Reporting Requirements When There Are No Deviations of Federally Enforceable Emission Limitations, Operational Restrictions, or Control Device Operating Parameter Limitations**

If no deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted quarterly by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters.

**16. Fees**

The permittee shall pay fees to the Director of the Ohio EPA in accordance with ORC section 3745.11 and OAC Chapter 3745-78. The permittee shall pay all applicable permit-to-install fees within 30 days after the issuance of any permit-to-install. The permittee shall pay all applicable permit-to-operate fees within thirty days of the issuance of the invoice.

**17. Permit Transfers**

Any transferee of this permit shall assume the responsibilities of the prior permit holder. The new owner must update and submit the ownership information via the "Owner/Contact Change" functionality in "Air Services" once the transfer is legally completed.The change must be submitted through "Air Services" within thirty days of the ownership transfer date.

**18. Risk Management Plans**

If the permittee is required to develop and register a risk management plan pursuant to section 112(r) of the Clean Air Act, as amended, 42 U.S.C. 7401 et seq. ("Act"), the permittee shall comply with the requirement to register such a plan.

**19. Title IV Provisions**

If the permittee is subject to the requirements of 40 CFR Part 72 concerning acid rain, the permittee shall ensure that any affected emissions unit complies with those requirements. Emissions exceeding any allowances that are lawfully held under Title IV of the Act, or any regulations adopted thereunder, are prohibited.

# B. Facility-Wide Terms and Conditions

1. All the following facility-wide terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only:

   a) None.

2. The following emissions units contained in this permit are subject to 40 CFR Part 63, Subpart JJJ: B010 and B020. The complete MACT requirements, including the MACT General Provisions may be accessed via the internet from the Electronic Code of Federal Regulations (e-CFR) website http://ecfr.gpoaccess.gov or by contacting the appropriate Ohio EPA District office or local air agency.

# C. Emissions Unit Terms and Conditions

**1. B010, Dowtherm Boiler R-1**

**Operations, Property and/or Equipment Description:**

9.0 MMBtu/hr natural gas, no. 2 fuel oil and byproduct fuel fired boiler – Administrative modification to increase the amount of byproduct fuel burned without increasing emissions.

a) The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

(1) None.

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operation(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures are identified below. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

| | Applicable Rules/Requirements | Applicable Emissions Limitations/Control Measures |
|---|---|---|
| a. | OAC rule 3745-31-05(A)(3) | Particulate emissions (PE) shall not exceed 0.18 pound per hour and 0.79 ton per year.<br><br>Nitrogen oxides ($NO_x$) emissions shall not exceed 2.73 pounds per hour and 11.96 tons per year.<br><br>Sulfur dioxide ($SO_2$) emissions shall not exceed 3.66 pounds per hour and 16.03 tons per year.<br><br>Volatile organic compounds (VOC) emissions shall not exceed 0.047 pound per hour and 0.21 ton per year.<br><br>Carbon monoxide (CO) emissions shall not exceed 0.9 pound per hour and 3.94 tons per year.<br><br>The requirements of this rule also include compliance with the requirements of OAC rules3745-17-07, 3745-17-10, 3745-18-06 and 40 CFR Part 63,Subpart JJJ.<br><br>See b)(2)a through b)(2)e. |
| b. | OAC rule 3745-17-07(A)(1) | Visible particulate emissions from any stack shall not exceed twenty percent |

| | Applicable Rules/Requirements | Applicable Emissions Limitations/Control Measures |
|---|---|---|
| | | opacity as a six minute average, except as provided by rule. |
| c. | OAC rule 3745-17-10(B)(1) | Particulate emissions shall not exceed 0.020 lb/mmBtu of actual heat input |
| d. | OAC rule 3745-18-06(B) | See b)(2)b. |
| e. | 40 CFR Part 63, Subpart JJJ (40 CFR Part 63.1313 - 63.1335) | See b)(2)c. and b)(2)d. |

(2) Additional Terms and Conditions

a. Compliance with the terms and conditions of this PTI will satisfy the Best Available Technology requirements for this source.

b. Fuel burning equipment which have heat input capacities equal to or less than 10mmBtu/hr rated capacity are exempt from OAC rule 3745-18-06(D), (F), and (G).

c. This emissions unit is used as a control device for emissions units P002 (Polystyrene Polymerization Process - Train #1) and P010 (Polystyrene Polymerization Process Train #2). Emissions units P002 and P010 are subject to the requirements of 40 CFR Part 63, Subpart JJJ. Because this emissions unit is used as a control device, it is also subject to the requirements of 40 CFR Part 63, Subpart JJJ. (see B.2)

d. The permittee shall reduce emissions from emissions units P002 and P010 processvents, as defined in 40 CFR 63.1312, by 98 weight percent or to a concentration of20 parts per million by volume (ppmv) on a dry basis, whichever is less stringent. Ifthe permittee elects to comply with the 20 ppmv standard, the concentration shallinclude a correction to 3 percent oxygen only when supplemental combustion air isused to combust the emissions. Compliance shall be based on either organic HAP orTOC.

e. The company has demonstrated that sulfur content is negligible in byproduct fuel.Therefore, it is not necessary to develop monitoring, recordkeeping and/or reportingrequirements to ensure compliance.

c) Operational Restrictions

(1) No. 2 fuel oil shall be burned for emergency backup only when natural gas is unavailable.

(2) No. 2 fuel oil shall have a sulfur content of less than or equal to 0.4 percent, by weight.

(3) The amount of fuel burned in this emissions unit shall not exceed 69% byproduct fuel/ 31% natural gas (or no. 2 fuel oil as emergency backup) mix. This 69% byproduct fuel equates to 286 pounds per hour of byproduct waste fuel.

(4) The no. 2 fuel oil shall have a sulfur content and heat content that meets the allowable SO2 emission limitation of 3.66 pounds per hour.

(5) If a boiler or heater is used to comply with the percent reduction requirement orconcentration limit specified in b)(2)d. above, then the vent stream shall be introduced intothe flame zone of such a device.

d) Monitoring and/or Recordkeeping Requirements

(1) The permittee shall maintain daily records of the quantity of each fuel burned in thisemissions unit, including the ratio of the mix of byproduct waste fuel to natural gas (or no. 2 fuel oil as emergency backup).

(2) The permittee shall maintain records of the oil burned in this emissions unit in accordance with either Alternative 1 or Alternative 2 described below:

a. Alternative 1:

For each shipment of oil received for burning in this emissions unit, the permittee shall collect or require the oil supplier to collect a representative grab sample of oil and maintain records of the total quantity of oil received, the permittee's or oil supplier's analyses for sulfur content and heat content, and the calculated sulfur dioxide emission rate (in lbs/MMBtu). The sulfur dioxide emission rate shall be calculated in accordance with the formula specified in OAC rule 3745-18-04(F). A shipment may be comprised of multiple tank truck loads from the same supplier's batch, or may be represented by single or multiple pipeline deliveries from the same supplier's batch, and the quality of the oil for those loads or pipeline deliveries may be represented by a single batch analysis from the supplier.

b. Alternative 2:

The permittee shall collect a representative grab sample of oil that is burned in this emissions unit for each day when the emissions unit is in operation. If additional fuel oil is added to the tank serving this emissions unit on a day when the emissions unit is in operation, the permittee shall collect a sufficient number of grab samples to develop a composite sample representative of the fuel oil burned in this emissions unit. A representative grab sample of oil does not need to be collected on days when this emissions unit is only operated for the purpose of "test-firing." The permittee shall maintain records of the total quantity of oil burned each day, except for the purpose of test-firing, the permittee's analyses for sulfur content and heat content, and the calculated sulfur dioxide emission rate (in lbs/MMBtu). The sulfur dioxide emission rate shall be calculated in accordance with the formula specified in OAC rule 3745-18-04(F).

The permittee shall perform or require the supplier to perform the analyses for sulfur content and heat content in accordance with 40 CFR Part 60, Appendix A, Method 19, or the appropriate ASTM methods, such as ASTM methods D240 <u>Standard Test Method for Heat of Combustion of Liquid Hydrocarbon Fuels by Bomb Calorimeter</u> and D4294, <u>Standard Test Method for Sulfur in Petroleum and</u>

Petroleum Products by Energy- Dispersive X-Ray Fluorescence Spectrometry, or equivalent methods as approved by the Director.

(3) The permittee shall perform weekly checks, when the emissions unit is in operation andwhen the weather conditions allow, for any visible particulate emissions from the stackserving this emission unit. The presence or absence of any visible emissions shall be notedin an operations log. If visible emissions are observed, the permittee shall also note thefollowing in the operations log:

a. the color of the emissions;

b. whether the emissions are representative of normal operations;

c. if the emissions are not representative of normal operations, the cause of the abnormal emissions;

d. the total duration of any visible emissions incident; and

e. any corrective actions taken to minimize or eliminate the visible emissions.

If visible emissions are present, a visible emissions incident has occurred. The observer does not have to document the exact start and end times for the visible emissions incident under item (d) above or continue the daily check until the incident has ended. The observer may indicate that the visible emissions incident was continuous during the observation period (or, if known, continuous during the operation of the emissions unit). With respect to the documentation of corrective actions, the observer may indicate that no corrective actions were taken if the visible emissions were representative of normal operations, or specify the minor corrective actions that were taken to ensure that the emissions unit continued to operate under normal conditions, or specify the corrective actions that were taken to eliminate abnormal visible emissions.

If the weekly checks show emissions that are representative of normal operation for 1operating quarter, the required frequency of visible emission checks may be reduced to biweekly(once every two weeks, when the emissions unit is in operation). If a subsequentcheck by the permittee or an Ohio EPA inspector indicates emissions that are notrepresentative of normal operation, the frequency of emission checks shall revert back toweekly until such time as there is 1 operating quarter of normal visible emissions.

(4) See 40 CFR Part 63, Subpart JJJ (40 CFR Part 63.1313 - 63.1335).

e) Reporting Requirements

(1) The permittee shall submit quarterly deviation (excursion) reports that identify all exceedances of the byproduct waste fuel usage limitation described in c)(3).

(2) The permittee shall submit quarterly deviation (excursion) reports that identify all times when a shipment of oil is received which exceeds the 0.4 percent, by weight, sulfur content limitation.

(3) The permittee shall submit quarterly deviation (excursion) reports that identify all exceedances of the 3.66 pounds per hour SO2 emission limitation based on the calculations required in d)(2) for no. 2 fuel oil.

(4) The permittee shall submit semiannual written reports that identify:

a. all days during which any visible particulate emissions were observed from the stack serving this emissions unit; and

b. any corrective actions taken to minimize or eliminate the visible particulate emissions.

These reports shall be submitted to the Portsmouth Local Air Agency by January 31 and July 31 of each year and shall cover the previous 6-month period.

(5) See 40 CFR Part 63, Subpart JJJ (40 CFR Part 63.1313 - 63.1335).

f) Testing Requirements

(1) Compliance with the Emissions Limitations and/or Control Requirements specified in section b) of these terms and conditions shall be determined in accordance with the following methods:

a. <u>Emission Limitation</u>:

Visible particulate emissions from any stack shall not exceed 20% opacity as a 6-minute average, except as provided by rule.

<u>Applicable Compliance Method</u>:

If required, compliance shall be demonstrated in accordance with the requirements specified in 40 CFR Part 60, Appendix A, Method 9 and the methods and procedures required in OAC rule 3745-17-03(B)(1).

b. <u>Emission Limitation</u>:

VOC emissions shall not exceed 0.047 pound per hour and 0.21 ton per year.

<u>Applicable Compliance Method</u>:

Compliance may be demonstrated by multiplying the VOC emission factor in lb/mmscf offuel fired, by the maximum quantity of fuel burned per hour, in mmscf. The VOC emissionfactor shall be calculated from the results of the most recent stack test which demonstratedcompliance.

If required, compliance shall be demonstrated based upon the procedures specified in 40CFR Part 60, Appendix A, Methods 18.

The annual limitation was derived by multiplying the allowable hourly emission limitation by8,760 hours per year, and then dividing by 2,000 pounds/ton.

Therefore, providedcompliance is shown with the hourly emission limitation, compliance will be shown withthe annual limitation.

c. Emission Limitation:

NOx emissions shall not exceed 2.73 pounds per hour and 11.96 tons per year.

Applicable Compliance Method:

Compliance may be demonstrated by multiplying the NOx emission factor in lb/mmscf offuel fired, by the maximum quantity of fuel burned per hour, in mmscf. The NOx emissionfactor shall be calculated from the results of the most recent stack test which demonstratedcompliance.

If required, compliance shall be demonstrated based upon the procedures specified in 40CFR Part 60, Appendix A, Methods 1 through 4 and Method 7.

The annual limitation was derived by multiplying the allowable hourly emission limitation by8,760 hours per year, and then dividing by 2,000 pounds/ton. Therefore, providedcompliance is shown with the hourly emission limitation, compliance will be shown withthe annual limitation.

d. Emission Limitation:

PE shall not exceed 0.18 pound per hour and 0.79 ton per year.

Applicable Compliance Method:

Compliance may be demonstrated by multiplying the particulate emission factor inlb/mmscf of fuel fired, by the maximum quantity of fuel burned per hour, in mmscf. The PE factor shall be calculated from the results of the most recent stack testwhich demonstrated compliance.

If required, compliance shall be demonstrated based upon the procedures specified in 40CFR Part 60, Appendix A, Methods 1 through 5.

The annual limitation was derived by multiplying the allowable hourly emission limitation by8,760 hours per year, and then dividing by 2,000 pounds/ton. Therefore, providedcompliance is shown with the hourly emission limitation, compliance will be shown withthe annual limitation.

e. Emission Limitation:

CO emissions shall not exceed 0.9 pound per hour and 3.94 tons per year.

Applicable Compliance Method:

Compliance may be demonstrated by multiplying the CO emission factor in lb/mmscf offuel fired, by the maximum quantity of fuel burned per hour, in mmscf. The CO emissionfactor shall be calculated from the results of the most recent stack test which demonstratedcompliance.

If required, compliance shall be demonstrated based upon the procedures specified in 40CFR Part 60, Appendix A, Methods 1 through 4 and Method 10.

The annual limitation was derived by multiplying the allowable hourly emission limitation by8,760 hours per year, and then dividing by 2,000 pounds/ton. Therefore, providedcompliance is shown with the hourly emission limitation, compliance will be shown withthe annual limitation.

f. Emission Limitation:

$SO_2$ emissions shall not exceed 3.66 pounds per hour and 16.03 tons per year.

Applicable Compliance Method:

Compliance may be demonstrated based on the records required section d) above and by multiplying the $SO_2$ emission factor in lb/1000 gal of fuel fired,by the maximum quantity of fuel burned per hour, in gallons. The SO2 emission factor shallbe obtained from AP-42, Volume 1, 5th Edition, Chapter 1, Section 1.3, Table 1.3-1, dated September, 1998 and the sulfur content of the fuel.

If required, compliance shall be demonstrated based upon the procedures specified in 40CFR Part 60, Appendix A, Methods 1 through 4 and Method 6.

The annual limitation was derived by multiplying the allowable hourly emission limitation by8,760 hours per year, and then dividing by 2,000 pounds/ton. Therefore, providedcompliance is shown with the hourly emission limitation, compliance will be shown withthe annual limitation.

g. Emission Limitation:

Reduce emissions from process vents by 98 weight percent or to a concentration of 20 parts per million byvolume (ppmv) on a dry basis, whichever is less stringent.

Applicable Compliance Method:

Compliance shall be demonstrated based upon compliance with 40 CFR Part 63, Subpart JJJ.

g) Miscellaneous Requirements

(1) None.

**2. B020, Dowtherm Boiler R-3**

**Operations, Property and/or Equipment Description:**

9.0 MMBtu/hr natural gas, no. 2 fuel oil and byproduct fuel fired boiler – Administrative modification to increase the amount of byproduct fuel burned without increasing emissions.

a) The following emissions unit terms and conditions are federally enforceable with the exception of those listed below which are enforceable under state law only.

(1) None.

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operation(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures are identified below. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

| | Applicable Rules/Requirements | Applicable Emissions Limitations/Control Measures |
|---|---|---|
| a. | OAC rule 3745-31-05(A)(3) | Particulate emissions (PE) shall not exceed 0.18 pound per hour and 0.79 ton per year.<br><br>Nitrogen oxides ($NO_x$) emissions shall not exceed 2.73 pounds per hour and 11.96 tons per year.<br><br>Sulfur dioxide ($SO_2$) emissions shall not exceed 3.66 pounds per hour and 16.03 tons per year.<br><br>Volatile organic compounds (VOC) emissions shall not exceed 0.047 pound per hour and 0.21 ton per year.<br><br>Carbon monoxide (CO) emissions shall not exceed 0.9 pound per hour and 3.94 tons per year.<br><br>The requirements of this rule also include compliance with the requirements of OAC rules3745-17-07, 3745-17-10, 3745-18-06 and 40 CFR Part 63,Subpart JJJ.<br><br>See b)(2)a through b)(2)e. |
| b. | OAC rule 3745-17-07(A)(1) | Visible particulate emissions from any stack shall not exceed twenty percent |

| | Applicable Rules/Requirements | Applicable Emissions Limitations/Control Measures |
|---|---|---|
| | | opacity as a six minute average, except as provided by rule. |
| c. | OAC rule 3745-17-10(B)(1) | Particulate emissions shall not exceed 0.020 lb/mmBtu of actual heat input. |
| d. | OAC rule 3745-18-06(B) | See b)(2)b. |
| e. | 40 CFR Part 63, Subpart JJJ (40 CFR Part 63.1313 - 63.1335) | See b)(2)c. and b)(2)d. |

(2) Additional Terms and Conditions

a. Compliance with the terms and conditions of this PTI will satisfy the Best Available Technology requirements for this source.

b. Fuel burning equipment which have heat input capacities equal to or less than 10mmBtu/hr rated capacity are exempt from OAC rule 3745-18-06(D), (F), and (G).

c. This emissions unit is used as a control device for emissions units P002 (Polystyrene Polymerization Process - Train #1) and P010 (Polystyrene Polymerization Process Train #2). Emissions units P002 and P010 are subject to the requirements of 40 CFR Part 63, Subpart JJJ. Because this emissions unit is used as a control device, it is also subject to the requirements of 40 CFR Part 63, Subpart JJJ. (see B.2)

d. The permittee shall reduce emissions from emissions units P002 and P010 processvents, as defined in 40 CFR 63.1312, by 98 weight percent or to a concentration of20 parts per million by volume (ppmv) on a dry basis, whichever is less stringent. Ifthe permittee elects to comply with the 20 ppmv standard, the concentration shallinclude a correction to 3 percent oxygen only when supplemental combustion air isused to combust the emissions. Compliance shall be based on either organic HAP orTOC.

e. The company has demonstrated that sulfur content is negligible in byproduct fuel.Therefore, it is not necessary to develop monitoring, recordkeeping and/or reportingrequirements to ensure compliance.

c) Operational Restrictions

(1) No. 2 fuel oil shall be burned for emergency backup only when natural gas is unavailable.

(2) No. 2 fuel oil shall have a sulfur content of less than or equal to 0.4 percent, by weight.

(3) The amount of fuel burned in this emissions unit shall not exceed 69% byproduct fuel/ 31% natural gas (or no. 2 fuel oil as emergency backup) mix. This 69% byproduct fuel equates to 286 pounds per hour of byproduct waste fuel.

(4) The no. 2 fuel oil shall have a sulfur content and heat content that meets the allowable SO2 emission limitation of 3.66 pounds per hour.

(5) If a boiler or heater is used to comply with the percent reduction requirement orconcentration limit specified in b)(2)d. above, then the vent stream shall be introduced intothe flame zone of such a device.

d) Monitoring and/or Recordkeeping Requirements

(1) The permittee shall maintain daily records of the quantity of each fuel burned in thisemissions unit, including the ratio of the mix of byproduct waste fuel to natural gas (or no. 2 fuel oil as emergency backup).

(2) The permittee shall maintain records of the oil burned in this emissions unit in accordance with either Alternative 1 or Alternative 2 described below:

a. Alternative 1:

For each shipment of oil received for burning in this emissions unit, the permittee shall collect or require the oil supplier to collect a representative grab sample of oil and maintain records of the total quantity of oil received, the permittee's or oil supplier's analyses for sulfur content and heat content, and the calculated sulfur dioxide emission rate (in lbs/MMBtu). The sulfur dioxide emission rate shall be calculated in accordance with the formula specified in OAC rule 3745-18-04(F). A shipment may be comprised of multiple tank truck loads from the same supplier's batch, or may be represented by single or multiple pipeline deliveries from the same supplier's batch, and the quality of the oil for those loads or pipeline deliveries may be represented by a single batch analysis from the supplier.

b. Alternative 2:

The permittee shall collect a representative grab sample of oil that is burned in this emissions unit for each day when the emissions unit is in operation. If additional fuel oil is added to the tank serving this emissions unit on a day when the emissions unit is in operation, the permittee shall collect a sufficient number of grab samples to develop a composite sample representative of the fuel oil burned in this emissions unit. A representative grab sample of oil does not need to be collected on days when this emissions unit is only operated for the purpose of "test-firing." The permittee shall maintain records of the total quantity of oil burned each day, except for the purpose of test-firing, the permittee's analyses for sulfur content and heat content, and the calculated sulfur dioxide emission rate (in lbs/MMBtu). The sulfur dioxide emission rate shall be calculated in accordance with the formula specified in OAC rule 3745-18-04(F).

The permittee shall perform or require the supplier to perform the analyses for sulfur content and heat content in accordance with 40 CFR Part 60, Appendix A, Method 19, or the appropriate ASTM methods, such as ASTM methods D240 <u>Standard Test Method for Heat of Combustion of Liquid Hydrocarbon Fuels by Bomb Calorimeter</u> and D4294, <u>Standard Test Method for Sulfur in Petroleum and</u>

Petroleum Products by Energy- Dispersive X-Ray Fluorescence Spectrometry, or equivalent methods as approved by the Director.

(3) The permittee shall perform weekly checks, when the emissions unit is in operation andwhen the weather conditions allow, for any visible particulate emissions from the stackserving this emission unit. The presence or absence of any visible emissions shall be notedin an operations log. If visible emissions are observed, the permittee shall also note thefollowing in the operations log:

a. the color of the emissions;

b. whether the emissions are representative of normal operations;

c. if the emissions are not representative of normal operations, the cause of the abnormal emissions;

d. the total duration of any visible emissions incident; and

e. any corrective actions taken to minimize or eliminate the visible emissions.

If visible emissions are present, a visible emissions incident has occurred. The observer does not have to document the exact start and end times for the visible emissions incident under item (d) above or continue the daily check until the incident has ended. The observer may indicate that the visible emissions incident was continuous during the observation period (or, if known, continuous during the operation of the emissions unit). With respect to the documentation of corrective actions, the observer may indicate that no corrective actions were taken if the visible emissions were representative of normal operations, or specify the minor corrective actions that were taken to ensure that the emissions unit continued to operate under normal conditions, or specify the corrective actions that were taken to eliminate abnormal visible emissions.

If the weekly checks show emissions that are representative of normal operation for 1operating quarter, the required frequency of visible emission checks may be reduced to biweekly(once every two weeks, when the emissions unit is in operation). If a subsequentcheck by the permittee or an Ohio EPA inspector indicates emissions that are notrepresentative of normal operation, the frequency of emission checks shall revert back toweekly until such time as there is 1 operating quarter of normal visible emissions.

(4) See 40 CFR Part 63, Subpart JJJ (40 CFR Part 63.1313 - 63.1335).

e) Reporting Requirements

(1) The permittee shall submit quarterly deviation (excursion) reports that identify all exceedances of the byproduct waste fuel usage limitation described in c)(3).

(2) The permittee shall submit quarterly deviation (excursion) reports that identify all times when a shipment of oil is received which exceeds the 0.4 percent, by weight, sulfur content limitation.

(3) The permittee shall submit quarterly deviation (excursion) reports that identify all exceedances of the 3.66 pounds per hour SO2 emission limitation based on the calculations required in d)(2) for no. 2 fuel oil.

(4) The permittee shall submit semiannual written reports that identify:

a. all days during which any visible particulate emissions were observed from the stack serving this emissions unit; and

b. any corrective actions taken to minimize or eliminate the visible particulate emissions.

These reports shall be submitted to the Portsmouth Local Air Agency by January 31 and July 31 of each year and shall cover the previous 6-month period.

(5) See 40 CFR Part 63, Subpart JJJ (40 CFR Part 63.1313 - 63.1335).

f) Testing Requirements

(1) Compliance with the Emissions Limitations and/or Control Requirements specified in section b) of these terms and conditions shall be determined in accordance with the following methods:

(2) Compliance with the emission limitations in b)(1) of these terms and conditionsshall be determined in accordance with the following methods:

a. <u>Emission Limitation</u>:

Visible particulate emissions from any stack shall not exceed 20% opacity as a 6-minute average, except as provided by rule.

<u>Applicable Compliance Method</u>:

If required, compliance shall be demonstrated in accordance with the requirements specified in 40 CFR Part 60, Appendix A, Method 9 and the methods and procedures required in OAC rule 3745-17-03(B)(1).

b. <u>Emission Limitation</u>:

VOC emissions shall not exceed 0.047 pound per hour and 0.21 ton per year.

<u>Applicable Compliance Method</u>:

Compliance may be demonstrated by multiplying the VOC emission factor in lb/mmscf offuel fired, by the maximum quantity of fuel burned per hour, in mmscf. The VOC emissionfactor shall be calculated from the results of the most recent stack test which demonstratedcompliance.

If required, compliance shall be demonstrated based upon the procedures specified in 40CFR Part 60, Appendix A, Methods 18.

The annual limitation was derived by multiplying the allowable hourly emission limitation by8,760 hours per year, and then dividing by 2,000 pounds/ton. Therefore, providedcompliance is shown with the hourly emission limitation, compliance will be shown withthe annual limitation.

c. Emission Limitation:

NOx emissions shall not exceed 2.73 pounds per hour and 11.96 tons per year.

Applicable Compliance Method:

Compliance may be demonstrated by multiplying the NOx emission factor in lb/mmscf offuel fired, by the maximum quantity of fuel burned per hour, in mmscf. The NOx emissionfactor shall be calculated from the results of the most recent stack test which demonstratedcompliance.

If required, compliance shall be demonstrated based upon the procedures specified in 40CFR Part 60, Appendix A, Methods 1 through 4 and Method 7.

The annual limitation was derived by multiplying the allowable hourly emission limitation by8,760 hours per year, and then dividing by 2,000 pounds/ton. Therefore, providedcompliance is shown with the hourly emission limitation, compliance will be shown withthe annual limitation.

d. Emission Limitation:

PE shall not exceed 0.18 pound per hour and 0.79 ton per year.

Applicable Compliance Method:

Compliance may be demonstrated by multiplying the PE factor inlb/mmscf of fuel fired, by the maximum quantity of fuel burned per hour, in mmscf. The PE factor shall be calculated from the results of the most recent stack testwhich demonstrated compliance.

If required, compliance shall be demonstrated based upon the procedures specified in 40CFR Part 60, Appendix A, Methods 1 through 5.

The annual limitation was derived by multiplying the allowable hourly emission limitation by8,760 hours per year, and then dividing by 2,000 pounds/ton. Therefore, providedcompliance is shown with the hourly emission limitation, compliance will be shown withthe annual limitation.

e. Emission Limitation:

CO emissions shall not exceed 0.9 pound per hour and 3.94 tons per year.

Applicable Compliance Method:

Compliance may be demonstrated by multiplying the CO emission factor in lb/mmscf offuel fired, by the maximum quantity of fuel burned per hour, in mmscf.

The CO emissionfactor shall be calculated from the results of the most recent stack test which demonstratedcompliance.

If required, compliance shall be demonstrated based upon the procedures specified in 40CFR Part 60, Appendix A, Methods 1 through 4 and Method 10.

The annual limitation was derived by multiplying the allowable hourly emission limitation by8,760 hours per year, and then dividing by 2,000 pounds/ton. Therefore, providedcompliance is shown with the hourly emission limitation, compliance will be shown withthe annual limitation.

f. Emission Limitation:

$SO_2$ emissions shall not exceed 3.66 pounds per hour and 16.03 tons per year.

Applicable Compliance Method:

Compliance may be demonstrated based on the records required section d) above any by multiplying the $SO_2$ emission factor in lb/1000 gal of fuel fired,by the maximum quantity of fuel burned per hour, in gallons. The SO2 emission factor shallbe obtained from AP-42, Volume 1, 5th Edition, Chapter 1, Section 1.3, Table 1.3-1, dated September, 1998 and the sulfur content of the fuel.

If required, compliance shall be demonstrated based upon the procedures specified in 40CFR Part 60, Appendix A, Methods 1 through 4 and Method 6.

The annual limitation was derived by multiplying the allowable hourly emission limitation by8,760 hours per year, and then dividing by 2,000 pounds/ton. Therefore, providedcompliance is shown with the hourly emission limitation, compliance will be shown withthe annual limitation.

g. Emission Limitation:

Reduce emissions from process vents by 98 weight percent or to a concentration of 20 parts per million byvolume (ppmv) on a dry basis, whichever is less stringent

Applicable Compliance Method:

Compliance shall be demonstrated based upon compliance with 40 CFR Part 63, Subpart JJJ.

g) Miscellaneous Requirements

(1) None.