



7/10/2014

Certified Mail

Mr. GII Mayo
STAHL SCOTT FETZER CO
3201 W. Old Lincoln Way
Wooster, OH 44691

No	TOXIC REVIEW
No	SYNTHETIC MINOR TO AVOID MAJOR NSR
No	CEMS
No	MACT/GACT
No	NSPS
No	NESHAPS
No	NETTING
No	MODELING SUBMITTED
Yes	SYNTHETIC MINOR TO AVOID TITLE V
Yes	FEDERALLY ENFORCABLE PTIO (FEPTIO)
No	SYNTHETIC MINOR TO AVOID MAJOR GHG

RE: FINALAIR POLLUTION PERMIT-TO-INSTALL AND OPERATE
Facility ID: 0285030144
Permit Number: P0116700
Permit Type: Renewal
County: Wayne

Dear Permit Holder:

Enclosed please find a final Ohio Environmental Protection Agency (EPA) Air Pollution Permit-to-Install and Operate (PTIO) which will allow you to install, modify, and/or operate the described emissions unit(s) in the manner indicated in the permit. Because this permit contains conditions and restrictions, please read it very carefully. In this letter you will find the information on the following topics:

- **How to appeal this permit**
- **How to save money, reduce pollution and reduce energy consumption**
- **How to give us feedback on your permitting experience**
- **How to get an electronic copy of your permit**

How to appeal this permit

The issuance of this PTIO is a final action of the Director and may be appealed to the Environmental Review Appeals Commission pursuant to Section 3745.04 of the Ohio Revised Code. The appeal must be in writing and set forth the action complained of and the grounds upon which the appeal is based. The appeal must be filed with the Commission within thirty (30) days after notice of the Director's action. The appeal must be accompanied by a filing fee of \$70.00, made payable to "Ohio Treasurer Josh Mandel," which the Commission, in its discretion, may reduce if by affidavit you demonstrate that payment of the full amount of the fee would cause extreme hardship. Notice of the filing of the appeal shall be filed with the Director within three (3) days of filing with the Commission. Ohio EPA requests that a copy of the appeal be served upon the Ohio Attorney General's Office, Environmental Enforcement Section. An appeal may be filed with the Environmental Review Appeals Commission at the following address:

Environmental Review Appeals Commission
77 South High Street, 17th Floor
Columbus, OH 43215

How to save money, reduce pollution and reduce energy consumption

The Ohio EPA is encouraging companies to investigate pollution prevention and energy conservation. Not only will this reduce pollution and energy consumption, but it can also save you money. If you would like to learn ways you can save money while protecting the environment, please contact our Office of Compliance Assistance and Pollution Prevention at (614) 644-3469. Additionally, all or a portion of the capital expenditures related to installing air pollution control equipment under this permit may be eligible for financing and State tax exemptions through the Ohio Air Quality Development Authority (OAQDA) under Ohio Revised Code Section 3706. For more information, see the OAQDA website: www.ohioairquality.org/clean_air

How to give us feedback on your permitting experience

Please complete a survey at www.epa.ohio.gov/survey.aspx and give us feedback on your permitting experience. We value your opinion.

How to get an electronic copy of your permit

This permit can be accessed electronically via the eBusiness Center: Air Services in Microsoft Word format or in Adobe PDF on the Division of Air Pollution Control (DAPC) Web page, www.epa.ohio.gov/dapc by clicking the "Search for Permits" link under the Permitting topic on the Programs tab.

If you have any questions, please contact Ohio EPA DAPC, Northeast District Office at (330)425-9171 or the Office of Compliance Assistance and Pollution Prevention at (614) 644-3469.

Sincerely,



Michael W. Ahern, Manager

Permit Issuance and Data Management Section, DAPC

Cc: Ohio EPA-NEDO



FINAL

**Division of Air Pollution Control
Permit-to-Install and Operate
for
STAHL SCOTT FETZER CO**

Facility ID:	0285030144
Permit Number:	P0116700
Permit Type:	Renewal
Issued:	7/10/2014
Effective:	7/10/2014
Expiration:	7/10/2019



Division of Air Pollution Control
Permit-to-Install and Operate
for
STAHL SCOTT FETZER CO

Table of Contents

Authorization	1
A. Standard Terms and Conditions	3
1. What does this permit-to-install and operate ("PTIO") allow me to do?.....	4
2. Who is responsible for complying with this permit?	4
3. What records must I keep under this permit?	4
4. What are my permit fees and when do I pay them?.....	4
5. When does my PTIO expire, and when do I need to submit my renewal application?	4
6. What happens to this permit if my project is delayed or I do not install or modify my source?	5
7. What reports must I submit under this permit?	5
8. If I am required to obtain a Title V operating permit in the future, what happens to the operating provisions and PER obligations under this permit?	5
9. What are my obligations when I perform scheduled maintenance on air pollution control equipment? ...	5
10. Do I have to report malfunctions of emissions units or air pollution control equipment? If so, how must I report?	6
11. Can Ohio EPA or my local air agency inspect the facility where the emission unit(s) is/are located?	6
12. What happens if one or more emissions units operated under this permit is/are shut down permanently?	6
13. Can I transfer this permit to a new owner or operator?.....	7
14. Does compliance with this permit constitute compliance with OAC rule 3745-15-07, "air pollution nuisance"?	7
15. What happens if a portion of this permit is determined to be invalid?	7
B. Facility-Wide Terms and Conditions.....	8
C. Emissions Unit Terms and Conditions	10
1. K001, BOOTH #1	11
2. K003, BOOTH #3.....	21
3. K004, Paint booth 4	31
4. K005, Paint booth 5	41



Final Permit-to-Install and Operate
STAHL SCOTT FETZER CO
Permit Number: P0116700
Facility ID: 0285030144
Effective Date: 7/10/2014

Authorization

Facility ID: 0285030144
Application Number(s): A0050522
Permit Number: P0116700
Permit Description: Renewal FEPTIO for paint spray booths K001, K003, K004 and K005
Permit Type: Renewal
Permit Fee: \$0.00
Issue Date: 7/10/2014
Effective Date: 7/10/2014
Expiration Date: 7/10/2019
Permit Evaluation Report (PER) Annual Date: Jan 1 - Dec 31, Due Feb 15

This document constitutes issuance to:

STAHL SCOTT FETZER CO
3201 OLD LINCOLN WAY W
Wooster, OH 44691

of a Permit-to-Install and Operate for the emissions unit(s) identified on the following page.


Ohio Environmental Protection Agency (EPA) District Office or local air agency responsible for processing and administering your permit:

Ohio EPA DAPC, Northeast District Office
2110 East Aurora Road
Twinsburg, OH 44087
(330)425-9171

The above named entity is hereby granted this Permit-to-Install and Operate for the air contaminant source(s) (emissions unit(s)) listed in this section pursuant to Chapter 3745-31 of the Ohio Administrative Code. Issuance of this permit does not constitute expressed or implied approval or agreement that, if constructed or modified in accordance with the plans included in the application, the described emissions unit(s) will operate in compliance with applicable State and federal laws and regulations.

This permit is granted subject to the conditions attached hereto.

Ohio Environmental Protection Agency


Craig W. Butler
Director



Authorization (continued)

Permit Number: P0116700

Permit Description: Renewal FEPTIO for paint spray booths K001, K003, K004 and K005

Permits for the following Emissions Unit(s) or groups of Emissions Units are in this document as indicated below:

Emissions Unit ID:	K001
Company Equipment ID:	BOOTH #1
Superseded Permit Number:	02-22256
General Permit Category and Type:	Not Applicable
Emissions Unit ID:	K003
Company Equipment ID:	BOOTH #3
Superseded Permit Number:	02-22256
General Permit Category and Type:	Not Applicable
Emissions Unit ID:	K004
Company Equipment ID:	Paint booth 4
Superseded Permit Number:	02-22256
General Permit Category and Type:	Not Applicable
Emissions Unit ID:	K005
Company Equipment ID:	Paint booth 5
Superseded Permit Number:	02-22256
General Permit Category and Type:	Not Applicable



Final Permit-to-Install and Operate
STAHL SCOTT FETZER CO
Permit Number: P0116700
Facility ID: 0285030144
Effective Date: 7/10/2014

A. Standard Terms and Conditions



1. What does this permit-to-install and operate ("PTIO") allow me to do?

This permit allows you to install and operate the emissions unit(s) identified in this PTIO. You must install and operate the unit(s) in accordance with the application you submitted and all the terms and conditions contained in this PTIO, including emission limits and those terms that ensure compliance with the emission limits (for example, operating, recordkeeping and monitoring requirements).

2. Who is responsible for complying with this permit?

The person identified on the "Authorization" page, above, is responsible for complying with this permit until the permit is revoked, terminated, or transferred. "Person" means a person, firm, corporation, association, or partnership. The words "you," "your," or "permittee" refer to the "person" identified on the "Authorization" page above.

The permit applies only to the emissions unit(s) identified in the permit. If you install or modify any other equipment that requires an air permit, you must apply for an additional PTIO(s) for these sources.

3. What records must I keep under this permit?

You must keep all records required by this permit, including monitoring data, test results, strip-chart recordings, calibration data, maintenance records, and any other record required by this permit for five years from the date the record was created. You can keep these records electronically, provided they can be made available to Ohio EPA during an inspection at the facility. Failure to make requested records available to Ohio EPA upon request is a violation of this permit requirement.

4. What are my permit fees and when do I pay them?

There are two fees associated with permitted air contaminant sources in Ohio:

PTIO fee. This one-time fee is based on a fee schedule in accordance with Ohio Revised Code (ORC) section 3745.11, or based on a time and materials charge for permit application review and permit processing if required by the Director.

You will be sent an invoice for this fee after you receive this PTIO and payment is due within 30 days of the invoice date. You are required to pay the fee for this PTIO even if you do not install or modify your operations as authorized by this permit.

Annual emissions fee. Ohio EPA will assess a separate fee based on the total annual emissions from your facility. You self-report your emissions in accordance with Ohio Administrative Code (OAC) Chapter 3745-78. This fee assessed is based on a fee schedule in ORC section 3745.11 and funds Ohio EPA's permit compliance oversight activities. For facilities that are permitted as synthetic minor sources, the fee schedule is adjusted annually for inflation. Ohio EPA will notify you when it is time to report your emissions and to pay your annual emission fees.

5. When does my PTIO expire, and when do I need to submit my renewal application?

This permit expires on the date identified at the beginning of this permit document (see "Authorization" page above) and you must submit a renewal application to renew the permit. Ohio EPA will send a renewal notice to you approximately six months prior to the expiration date of this permit. However, it is



very important that you submit a complete renewal permit application (postmarked prior to expiration of this permit) even if you do not receive the renewal notice.

If a complete renewal application is submitted before the expiration date, Ohio EPA considers this a timely application for purposes of ORC section 119.06, and you are authorized to continue operating the emissions unit(s) covered by this permit beyond the expiration date of this permit until final action is taken by Ohio EPA on the renewal application.

6. What happens to this permit if my project is delayed or I do not install or modify my source?

This PTIO expires 18 months after the issue date identified on the "Authorization" page above unless otherwise specified if you have not (1) started constructing the new or modified emission sources identified in this permit, or (2) entered into a binding contract to undertake such construction. This deadline can be extended by up to 12 months, provided you apply to Ohio EPA for this extension within a reasonable time before the 18-month period has ended and you can show good cause for any such extension.

7. What reports must I submit under this permit?

An annual permit evaluation report (PER) is required in addition to any malfunction reporting required by OAC rule 3745-15-06 or other specific rule-based reporting requirement identified in this permit. Your PER due date is identified in the Authorization section of this permit.

8. If I am required to obtain a Title V operating permit in the future, what happens to the operating provisions and PER obligations under this permit?

If you are required to obtain a Title V permit under OAC Chapter 3745-77 in the future, the permit-to-operate portion of this permit will be superseded by the issued Title V permit. From the effective date of the Title V permit forward, this PTIO will effectively become a PTI (permit-to-install) in accordance with OAC rule 3745-31-02(B). The following terms and conditions of this permit will no longer be applicable after issuance of the Title V permit: Section B, Term 1.b) and Section C, for each emissions unit, Term a)(2).

The PER requirements in this permit remain effective until the date the Title V permit is issued and is effective, and cease to apply after the effective date of the Title V permit. The final PER obligation will cover operations up to the effective date of the Title V permit and must be submitted on or before the submission deadline identified in this permit on the last day prior to the effective date of the Title V permit.

9. What are my obligations when I perform scheduled maintenance on air pollution control equipment?

You must perform scheduled maintenance of air pollution control equipment in accordance with OAC rule 3745-15-06(A). If scheduled maintenance requires shutting down or bypassing any air pollution control equipment, you must also shut down the emissions unit(s) served by the air pollution control equipment during maintenance, unless the conditions of OAC rule 3745-15-06(A)(3) are met. Any emissions that exceed permitted amount(s) under this permit (unless specifically exempted by rule) must be reported as deviations in the annual permit evaluation report (PER), including nonexempt excess emissions that occur during approved scheduled maintenance.



10. Do I have to report malfunctions of emissions units or air pollution control equipment? If so, how must I report?

If you have a reportable malfunction of any emissions unit(s) or any associated air pollution control system, you must report this to the [DO/LAA] in accordance with OAC rule 3745-15-06(B). Malfunctions that must be reported are those that result in emissions that exceed permitted emission levels. It is your responsibility to evaluate control equipment breakdowns and operational upsets to determine if a reportable malfunction has occurred.

If you have a malfunction, but determine that it is not a reportable malfunction under OAC rule 3745-15-06(B), it is recommended that you maintain records associated with control equipment breakdown or process upsets. Although it is not a requirement of this permit, Ohio EPA recommends that you maintain records for non-reportable malfunctions.

11. Can Ohio EPA or my local air agency inspect the facility where the emission unit(s) is/are located?

Yes. Under Ohio law, the Director or his authorized representative may inspect the facility, conduct tests, examine records or reports to determine compliance with air pollution laws and regulations and the terms and conditions of this permit. You must provide, within a reasonable time, any information Ohio EPA requests either verbally or in writing.

12. What happens if one or more emissions units operated under this permit is/are shut down permanently?

Ohio EPA can terminate the permit terms associated with any permanently shut down emissions unit. "Shut down" means the emissions unit has been physically removed from service or has been altered in such a way that it can no longer operate without a subsequent "modification" or "installation" as defined in OAC Chapter 3745-31.

You should notify Ohio EPA of any emissions unit that is permanently shut down by submitting a certification that identifies the date on which the emissions unit was permanently shut down. The certification must be submitted by an authorized official from the facility. You cannot continue to operate an emission unit once the certification has been submitted to Ohio EPA by the authorized official.

You must comply with all recordkeeping and reporting for any permanently shut down emissions unit in accordance with the provisions of the permit, regulations or laws that were enforceable during the period of operation, such as the requirement to submit a PER, air fee emission report, or malfunction report. You must also keep all records relating to any permanently shutdown emissions unit, generated while the emissions unit was in operation, for at least five years from the date the record was generated.

Again, you cannot resume operation of any emissions unit certified by the authorized official as being permanently shut down without first applying for and obtaining a permit pursuant to OAC Chapter 3745-31.



13. Can I transfer this permit to a new owner or operator?

You can transfer this permit to a new owner or operator. If you transfer the permit, you must follow the procedures in OAC Chapter 3745-31, including notifying Ohio EPA or the local air agency of the change in ownership or operator. Any transferee of this permit must assume the responsibilities of the transferor permit holder.

14. Does compliance with this permit constitute compliance with OAC rule 3745-15-07, "air pollution nuisance"?

This permit and OAC rule 3745-15-07 prohibit operation of the air contaminant source(s) regulated under this permit in a manner that causes a nuisance. Ohio EPA can require additional controls or modification of the requirements of this permit through enforcement orders or judicial enforcement action if, upon investigation, Ohio EPA determines existing operations are causing a nuisance.

15. What happens if a portion of this permit is determined to be invalid?

If a portion of this permit is determined to be invalid, the remainder of the terms and conditions remain valid and enforceable. The exception is where the enforceability of terms and conditions are dependent on the term or condition that was declared invalid.



Final Permit-to-Install and Operate
STAHL SCOTT FETZER CO
Permit Number: P0116700
Facility ID: 0285030144
Effective Date: 7/10/2014

B. Facility-Wide Terms and Conditions



1. This permit document constitutes a permit-to-install issued in accordance with ORC 3704.03(F) and a permit-to-operate issued in accordance with ORC 3704.03(G).
 - a) For the purpose of a permit-to-install document, the facility-wide terms and conditions identified below are federally enforceable with the exception of those listed below which are enforceable under state law only.
 - (1) None.
 - b) For the purpose of a permit-to-operate document, the facility-wide terms and conditions identified below are enforceable under state law only with the exception of those listed below which are federally enforceable.
 - (1) None.



Final Permit-to-Install and Operate
STAHL SCOTT FETZER CO
Permit Number: P0116700
Facility ID: 0285030144
Effective Date: 7/10/2014

C. Emissions Unit Terms and Conditions



1. K001, BOOTH #1

Operations, Property and/or Equipment Description:

Paint booth No. 1 with 1.3 MMBtu/hr natural gas fired drying oven

a) This permit document constitutes a permit-to-install issued in accordance with ORC 3704.03(F) and a permit-to-operate issued in accordance with ORC 3704.03(G).

(1) For the purpose of a permit-to-install document, the emissions unit terms and conditions identified below are federally enforceable with the exception of those listed below which are enforceable under state law only.

a. None.

(2) For the purpose of a permit-to-operate document, the emissions unit terms and conditions identified below are enforceable under state law only with the exception of those listed below which are federally enforceable.

a. None.

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operation(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures are identified below. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC rule 3745-31-05(A)(3) (PTI No. 02-22256, issued 3/1/2007)	<u>Coating Emissions:</u> Volatile organic compounds (VOC) emissions shall not exceed 256 lbs/day and 13 tons/year. VOC emissions shall not exceed 67.35 tons/year for emissions units K001, K003, K004 and K005, combined. <u>Cleanup Emissions:</u> VOC emissions shall not exceed 1.95 tons/month for emissions units K001, K003, K004 and K005, combined. VOC emissions shall not exceed 23.31 tons/year for emissions units K001, K003, K004 and K005, combined.



	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
		Particulate emissions (PE) shall not exceed 0.551 lb/hour and 2.41 tpy See section 1.b)(2)a. below.
b.	OAC rule 3745-17-11(B)(2)	The emission limitation required by this applicable rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).
c.	OAC rule 3745-17-07(A)	Visible PE shall not exceed 20% opacity, as a 6-minute average, except as provided by the rule.
d.	OAC rule 3745-21-09(U)(2)(d)	The permittee shall apply a customized topcoat and any related customized single coat to a maximum of less than 35 motor vehicles per day.
e.	OAC rule 3745-31-05(D)	Emissions of hazardous air pollutants (HAPs) shall not exceed 9.90 tons per year for an individual HAP or 24.90 tons per year for total combined HAPs. See section 1.b)(2)b. below.

(2) Additional Terms and Conditions

- a. The requirements of this rule also include compliance with the requirements of OAC rules 3745-31-05(C), 3745-21-09(U)(2)(d), 3745-17-11(B)(2) and 3745-17-07(A).
- b. This permit establishes federally enforceable limitations on emissions of hazardous air pollutants (HAPs) for purposes of avoiding Maximum Achievable Control Technology (MACT) regulations and Title V permitting requirements. Annual HAP emissions from emissions units K001, K003, K004 and K005, combined, shall not exceed 9.90 tons per rolling, 12-month period for any individual HAP or 24.90 tons per rolling, 12-month period for total combined HAPs.

This is an existing emissions unit which has existing records of the amount of individual and total combined HAPs emissions and therefore does not need to be restricted on a monthly basis.



- c) Operational Restrictions
 - (1) Coating and liquid organic cleanup materials employed in this emissions unit shall not exceed: 10,500 gallons per rolling, 12-month period and 1,750 gallons per rolling, 12-month period, respectively.
 - (2) This emissions unit shall be equipped with a filter system that shall minimize or eliminate all particulate emissions from the painting operation.
- d) Monitoring and/or Recordkeeping Requirements
 - (1) The permittee shall collect and record the following information each day for this emissions unit:
 - a. the name and identification number of each coating employed;
 - b. the number of gallons of each coating employed;
 - c. the total number of gallons of all the coatings employed;
 - d. the VOC content of each coating employed, in lbs/gallon;
 - e. the total emissions of VOC for each coating employed (b x d), in lbs; and
 - f. the total emissions of VOC for all the coatings employed (summation of e for all coatings), in lbs.
 - (2) The permittee shall calculate and record the following information each month for this emissions unit.
 - a. the total VOC emissions for all coatings employed (summation of the daily VOC emission rates, from section 1.d)(1)f., for the calendar month, divided by 2000), in tons, for this emissions unit; and
 - b. the annual, year-to-date, VOC emission rate for all coatings employed (summation of section 1.d)(2)a for each calendar month to date from January to December), in tons.
 - (3) The permittee shall calculate and record the following information each month for emissions units K001, K003, K004 and K005, combined:
 - a. the name and identification number of each cleanup material employed;
 - b. the VOC content of each cleanup material employed, in lbs/gallon;
 - c. the number of gallons of each cleanup material employed;
 - d. the total emissions of VOC for each cleanup material employed (b x c), in lbs;



- e. the total emissions of VOC for all the cleanup materials employed (summation of d for all cleanup materials), in tons.
- (4) The permittee shall calculate and record the following information each month for emissions units K001, K003, K004 and K005, combined:
- a. the total VOC emissions for all coatings employed (summation of section 1.d)2 above for K001, K003, K004 and K005), in tons; and
 - b. the annual, year-to-date, VOC emission rate for all coatings employed (summation of section 1.d)(4)a. for each calendar month to date from January to December), in tons.
- (5) The permittee shall calculate and record the following information each month for emissions units K001, K003, K004 and K005, combined:
- a. the total VOC emissions for all the cleanup materials employed (summation of section 1.d)2.e above for K001, K003, K004 and K005), in tons; and
 - b. the annual, year-to-date, VOC emission rate for all cleanup materials employed (summation of section 1.d)(5)a. for each calendar month to date from January to December), in tons.
- (6) The permittee shall collect and record the following HAP information each month for emissions units K001, K003, K004 and K005, combined:
- a. the company identification of each coating and cleanup material employed;
 - b. the amount of each individual HAP in each coating and cleanup material, in lbs/gallon, as applied;
 - c. the number of gallons of each coating and cleanup material employed;
 - d. the emission rate for each individual HAP from each coating and cleanup material employed (1.d)(6)b. x 1.d)(6)c.), in lbs;
 - e. the total emission rate for each individual HAP from all coatings and cleanup materials employed (for each individual HAP, the summation of section 1.d)(6)d. for all coatings and cleanup materials), in lbs;
 - f. the total HAP emission rate for all HAPs combined from all coatings and cleanup materials employed (summation of section 1.d)(6)e. for all HAPs for all coatings and cleanup materials), in lbs; and
 - g. the rolling, 12-month emissions of each individual HAP and all HAPs combined, in tons.



- (7) The permittee shall maintain daily records that document any time periods when the particulate filter system was not in service when the emissions unit was in operation.
- (8) The permittee shall maintain daily records of the total number of motor vehicles that were topcoated from emissions units K001, K003, K004 and K005, combined.
- (9) The permit to install for this emissions unit [K001] was evaluated based on the actual materials and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied to this emissions unit for each toxic pollutant, using data from the permit to install application, and modeling was performed for the toxic pollutant(s) emitted at over a ton per year using the SCREEN 3.0 model or other Ohio EPA approved model. The predicted 1-hour maximum ground-level concentration result(s) from the use of the SCREEN 3.0 (or other approved) model, was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC), calculated as required in Engineering Guide #70. The following summarizes the results of the modeling for the "worst case" pollutant(s) from the combined emissions of K001, K003 and K004, combined:

Pollutant: Methyl Isobutyl Ketone (MIBK)

TLV (mg/m³): 205

Maximum Hourly Emission Rate (lbs/hr): 6.71

Predicted 1-Hour Max. Ground-Level Concentration (ug/m³): 667.10

MAGLC (ug/m³): 4,881

Pollutant: Xylene

TLV (mg/m³): 434

Maximum Hourly Emission Rate (lbs/hr): 23.93

Predicted 1-Hour Max. Ground-Level Concentration (ug/m³): 2379

MAGLC (ug/m³): 10,333

- (10) Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:
 - a. changes in the composition of the materials used or the use of new materials, that would result in the emission of a compound or chemical with a lower Threshold Limit Value (TLV) than the lowest TLV previously modeled, as



documented in the most current version of the American Conference of Governmental Industrial Hygienists' (ACGIH's) handbook entitled "TLVs and BEIs" ("Threshold Limit Values for Chemical Substances and Physical Agents, Biological Exposure Indices");

- b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and
 - c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).
- (11) If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01 solely due to the emissions of any type of toxic air contaminant not previously emitted, and a modification of the existing permit to install will not be required, even if the toxic air contaminant emissions are greater than the de minimis level in OAC rule 3745-15-05. If the change(s) meet(s) the definition of a "modification" under other provisions of the rule, then the permittee shall obtain a final permit to install prior to the change.
- (12) The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy":
- a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
 - b. documentation of the evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and
 - c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.
- e) Reporting Requirements
- (1) The permittee shall submit annual reports that summarize the following:
- a. the actual annual VOC emissions from the coating usage for emissions units K001, K003, K004 and K005, combined; and
 - b. the actual annual VOC emissions from the use of cleanup materials for emissions units K001, K003, K004 and K005, combined.

These reports shall be submitted by January 31 of each year and shall cover the previous calendar year.



- (2) The permittee shall submit quarterly deviation (excursion) reports that identify the following:
 - a. all exceedances of the daily VOC emission limitation of 256 pounds (from the use of coatings);
 - b. all exceedances of the monthly VOC emission limitation of 1.95 tons (from the cleanup operations for emissions units K001, K003, K004 and K005, combined), and the actual VOC emissions for each such month;
 - c. all exceedances of the rolling, 12-month individual HAP and total combined HAPs emission limitations of 9.90 tons and 24.90 tons, respectively (for emissions units K001, K003, K004 and K005, combined); and

These reports shall be submitted in accordance with the General Terms and Conditions of this permit.

- (3) The permittee shall notify the Ohio EPA Northeast District Office in writing of any daily record showing that the particulate filter system was not in service when the emissions unit was in operation. The notification shall include a copy of such record and shall be sent to the Ohio EPA Northeast District Office within 30 days after the event occurs.
- (4) The permittee shall notify the Ohio EPA Northeast District Office in writing of any daily record showing that the total number of motor vehicles that were top coated from emissions units K001, K003, K004 and K005, combined, were at least thirty-five (35) motor vehicles. The notification shall include a copy of such record and shall be sent to the Ohio EPA Northeast District Office within 30 days after the event occurs.
- (5) The permittee shall submit an annual Permit Evaluation Report (PER) to the Ohio EPA. The PER must be submitted by the due date identified in the Authorization section of this permit. The permit evaluation report shall cover a reporting period of no more than twelve months for each air contaminant source identified in this permit.
- (6) All applications, notifications or reports required by terms and conditions in this permit to be submitted or "reported in writing" are to be submitted to Ohio EPA through the Ohio EPA's eBusiness Center: Air Services web service ("Air Services"). Ohio EPA will accept hard copy submittals on an as-needed basis if the permittee cannot submit the required documents through the Ohio EPA eBusiness Center. In the event of an alternative hard copy submission in lieu of the eBusiness Center, the post-marked date or the date the document is delivered in person will be recognized as the date submitted. Electronic submission of applications, notifications, or reports required to be submitted to Ohio EPA fulfills the requirement to submit the required information to the Director, the District Office or Local Air Agency, and/or any other individual or organization specifically identified as an additional recipient identified in this permit unless otherwise specified. Consistent with OAC rule 3745-15-03, the required application, notification or report is considered to be "submitted" on the date the submission is successful using a valid electronic signature. Signature by the signatory authority may be represented as provided through procedures established in Air Services.



f) Testing Requirements

(1) Compliance with the Emissions Limitations and/or Control Requirements specified in section b) of these terms and conditions shall be determined in accordance with the following methods:

a. Emission Limitation:

VOC emissions from coating operations shall not exceed 256 lbs/day.

Applicable Compliance Method:

Compliance shall be demonstrated based upon the record keeping requirements specified in section 1.d)(1).

b. Emission Limitation:

VOC emissions from coating operations shall not exceed 13 tons/year.

Applicable Compliance Method:

Compliance shall be demonstrated based upon the record keeping requirements specified in section 1.d)(2).

c. Emission Limitation:

VOC emissions from coating operations shall not exceed 67.35 tons/year for emissions units K001, K003, K004 and K005, combined.

Applicable Compliance Method:

Compliance shall be demonstrated based upon the record keeping requirements specified in section 1.d)(4).

d. Emission Limitation:

VOC emissions from cleanup operations shall not exceed 1.95 tons/month for emissions units K001, K003, K004 and K005, combined.

Applicable Compliance Method:

Compliance shall be demonstrated based upon the record keeping requirements specified in section 1.d)(3).

e. Emission Limitation:

VOC emissions from cleanup operations shall not exceed 23.31 tons/year for emissions units K001, K003, K004 and K005, combined.



Applicable Compliance Method:

Compliance shall be demonstrated based upon the record keeping requirements specified in section 1.d)(5).

f. Emission Limitation:

PE shall not exceed 0.551 lb/hour.

Applicable Compliance Method:

To determine the actual worst case PE rate, the following equation may be used:

$$E = A * B * C * (1 - 45\%) * (1 - 99\%) * 90\%$$

where:

E = particulate emissions, in lb/hr

A = total solid contents per gallon of coating material, in %

B = total coating density of coating material, in lbs/gal

C = total number of coating material used, gal/hr

45% = transfer efficiency of spray nozzle (provided by facility)

99% = particulate matter filter efficiency (provided by facility)

90% = capture efficiency (provided by facility)

If required, the permittee shall demonstrate compliance with the hourly allowable PE limitation pursuant to OAC rule 3745-17-03(B)(10).

g. Emission Limitation:

PE shall not exceed 2.41 tpy.

Applicable Compliance Method:

The tpy emission limitation was developed by multiplying the short-term allowable particulate emission limitation (0.551 lb/hr) by the maximum annual hours of operation (8,760 hours), and then dividing by 2,000 lbs per ton. Therefore, if compliance is shown with the short-term allowable emission limitation, compliance shall also be shown with the annual emission limitation.

h. Emission Limitation:

Visible PE shall not exceed 20% opacity, as a 6-minute average, except as provided by the rule.

Applicable Compliance Method:

If required, the permittee shall demonstrate compliance with the visible PE limitation pursuant to OAC rule 3745-17-03(B)(1).



i. Emission Limitation:

Annual HAP emissions from emissions units K001, K003, K004 and K005, combined, shall not exceed 9.90 tons per rolling, 12-month period for any individual HAP or 24.90 tons per rolling, 12-month period for total combined HAPs.

Applicable Compliance Method:

Compliance shall be demonstrated based upon the record keeping requirements specified in section 1.d)(6). of this permit.

- (2) Formulation data or U.S. EPA Method 24 shall be used to determine the VOC contents of all coatings, glues, autobody finishing materials and cleanup materials.
- (3) The HAPs for each coating, glue, autobody finishing material and cleanup material shall be determined using one of the following methods:
 - a. Method 311 from 40 CFR Part 63, Appendix A;
 - b. Method 24 from 40 CFR Part 60, Appendix A if all non-aqueous volatile matter is to be used for HAP content; or
 - c. information from the supplier or manufacturer of the materials, where the HAP content is provided or can be calculated.

g) Miscellaneous Requirements

- (1) None.



2. K003, BOOTH #3

Operations, Property and/or Equipment Description:

Paint booth No. 3

- a) This permit document constitutes a permit-to-install issued in accordance with ORC 3704.03(F) and a permit-to-operate issued in accordance with ORC 3704.03(G).
 - (1) For the purpose of a permit-to-install document, the emissions unit terms and conditions identified below are federally enforceable with the exception of those listed below which are enforceable under state law only.
 - a. None.
 - (2) For the purpose of a permit-to-operate document, the emissions unit terms and conditions identified below are enforceable under state law only with the exception of those listed below which are federally enforceable.
 - a. None.
- b) Applicable Emissions Limitations and/or Control Requirements
 - (1) The specific operation(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures are identified below. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC rule 3745-31-05(A)(3) (PTI No. 02-22256, issued 3/1/2007)	<u>Coating Emissions:</u> Volatile organic compounds (VOC) emissions shall not exceed 514 lbs/day and 19.75 tons/year. VOC emissions shall not exceed 67.35 tons/year for emissions units K001, K003, K004 and K005, combined. <u>Cleanup Emissions:</u> VOC emissions shall not exceed 1.95 tons/month for emissions units K001, K003, K004 and K005, combined. VOC emissions shall not exceed 23.31 tons/year for emissions units K001, K003, K004 and K005, combined.



	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
		Particulate emissions (PE) shall not exceed 0.551 lb/hour and 2.41 tpy See section 2.b)(2)a. below.
b.	OAC rule 3745-17-11(B)(2)	The emission limitation required by this applicable rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).
c.	OAC rule 3745-17-07(A)	Visible PE shall not exceed 20% opacity, as a 6-minute average, except as provided by the rule.
d.	OAC rule 3745-21-09(U)(2)(d)	The permittee shall apply a customized topcoat and any related customized single coat to a maximum of less than 35 motor vehicles per day.
e.	OAC rule 3745-31-05(D)	Emissions of hazardous air pollutants (HAPs) shall not exceed 9.90 tons per year for an individual HAP or 24.90 tons per year for total combined HAPs. See section 2.b)(2)b. below.

(2) Additional Terms and Conditions

- a. The requirements of this rule also include compliance with the requirements of OAC rules 3745-31-05(C), 3745-21-09(U)(2)(d), 3745-17-11(B)(2) and 3745-17-07(A).
- b. This permit establishes federally enforceable limitations on emissions of hazardous air pollutants (HAPs) for purposes of avoiding Maximum Achievable Control Technology (MACT) regulations and Title V permitting requirements. Annual HAP emissions from emissions units K001, K003, K004 and K005, combined, shall not exceed 9.90 tons per rolling, 12-month period for any individual HAP or 24.90 tons per rolling, 12-month period for total combined HAPs.

This is an existing emissions unit which has existing records of the amount of individual and total combined HAPs emissions and therefore does not need to be restricted on a monthly basis.



- c) Operational Restrictions
 - (1) Coating and liquid organic cleanup materials employed in this emissions unit shall not exceed: 15,200 gallons per rolling, 12-month period and 1,750 gallons per rolling, 12-month period, respectively.
 - (2) This emissions unit shall be equipped with a filter system that shall minimize or eliminate all particulate emissions from the painting operation.
- d) Monitoring and/or Recordkeeping Requirements
 - (1) The permittee shall collect and record the following information each day for this emissions unit:
 - a. the name and identification number of each coating employed;
 - b. the number of gallons of each coating employed;
 - c. the total number of gallons of all the coatings employed;
 - d. the VOC content of each coating employed, in lbs/gallon;
 - e. the total emissions of VOC for each coating employed (b x d), in lbs; and
 - f. the total emissions of VOC for all the coatings employed (summation of e for all coatings), in lbs.
 - (2) The permittee shall calculate and record the following information each month for this emissions unit.
 - a. the total VOC emissions for all coatings employed (summation of the daily VOC emission rates, from section 2.d)(1)f., for the calendar month, divided by 2000), in tons, for this emissions unit; and
 - b. the annual, year-to-date, VOC emission rate for all coatings employed (summation of section 2.d)(2)a for each calendar month to date from January to December), in tons.
 - (3) The permittee shall calculate and record the following information each month for emissions units K001, K003, K004 and K005, combined:
 - a. the name and identification number of each cleanup material employed;
 - b. the VOC content of each cleanup material employed, in lbs/gallon;
 - c. the number of gallons of each cleanup material employed;
 - d. the total emissions of VOC for each cleanup material employed (b x c), in lbs;



- e. the total emissions of VOC for all the cleanup materials employed (summation of d for all cleanup materials), in tons.
- (4) The permittee shall calculate and record the following information each month for emissions units K001, K003, K004 and K005, combined:
- a. the total VOC emissions for all coatings employed (summation of section 2.d)2 above for K001, K003, K004 and K005), in tons; and
 - b. the annual, year-to-date, VOC emission rate for all coatings employed (summation of section 2.d)(4)a. for each calendar month to date from January to December), in tons.
- (5) The permittee shall calculate and record the following information each month for emissions units K001, K003, K004 and K005, combined:
- a. the total VOC emissions for all the cleanup materials employed (summation of section 2.d)2.e above for K001, K003, K004 and K005), in tons; and
 - b. the annual, year-to-date, VOC emission rate for all cleanup materials employed (summation of section 2.d)(5)a. for each calendar month to date from January to December), in tons.
- (6) The permittee shall collect and record the following HAP information each month for emissions units K001, K003, K004 and K005, combined:
- a. the company identification of each coating and cleanup material employed;
 - b. the amount of each individual HAP in each coating and cleanup material, in lbs/gallon, as applied;
 - c. the number of gallons of each coating and cleanup material employed;
 - d. the emission rate for each individual HAP from each coating and cleanup material employed (2.d)(6)b. x 2.d)(6)c.), in lbs;
 - e. the total emission rate for each individual HAP from all coatings and cleanup materials employed (for each individual HAP, the summation of section 2.d)(6)d. for all coatings and cleanup materials), in lbs;
 - f. the total HAP emission rate for all HAPs combined from all coatings and cleanup materials employed (summation of section 2.d)(6)e. for all HAPs for all coatings and cleanup materials), in lbs; and
 - g. the rolling, 12-month emissions of each individual HAP and all HAPs combined, in tons.
- (7) The permittee shall maintain daily records that document any time periods when the particulate filter system was not in service when the emissions unit was in operation.



- (8) The permittee shall maintain daily records of the total number of motor vehicles that were topcoated from emissions units K001, K003, K004 and K005, combined.
- (9) The permit to install for this emissions unit [K003] was evaluated based on the actual materials and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied to this emissions unit for each toxic pollutant, using data from the permit to install application, and modeling was performed for the toxic pollutant(s) emitted at over a ton per year using the SCREEN 3.0 model or other Ohio EPA approved model. The predicted 1-hour maximum ground-level concentration result(s) from the use of the SCREEN 3.0 (or other approved) model, was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC), calculated as required in Engineering Guide #70. The following summarizes the results of the modeling for the "worst case" pollutant(s) from the combined emissions of K001, K003 and K004, combined:

Pollutant: Methyl Isobutyl Ketone (MIBK)

TLV (mg/m³): 205

Maximum Hourly Emission Rate (lbs/hr): 6.71

Predicted 1-Hour Max. Ground-Level Concentration (ug/m³): 667.10

MAGLC (ug/m³): 4,881

Pollutant: Xylene

TLV (mg/m³): 434

Maximum Hourly Emission Rate (lbs/hr): 23.93

Predicted 1-Hour Max. Ground-Level Concentration (ug/m³): 2379

MAGLC (ug/m³): 10,333

- (10) Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:
- a. changes in the composition of the materials used or the use of new materials, that would result in the emission of a compound or chemical with a lower Threshold Limit Value (TLV) than the lowest TLV previously modeled, as documented in the most current version of the American Conference of Governmental Industrial Hygienists' (ACGIH's) handbook entitled "TLVs and



BEIs" ("Threshold Limit Values for Chemical Substances and Physical Agents, Biological Exposure Indices");

- b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and
 - c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).
- (11) If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01 solely due to the emissions of any type of toxic air contaminant not previously emitted, and a modification of the existing permit to install will not be required, even if the toxic air contaminant emissions are greater than the de minimis level in OAC rule 3745-15-05. If the change(s) meet(s) the definition of a "modification" under other provisions of the rule, then the permittee shall obtain a final permit to install prior to the change.
- (12) The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy":
- a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
 - b. documentation of the evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and
 - c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.
- e) Reporting Requirements
- (1) The permittee shall submit annual reports that summarize the following:
- a. the actual annual VOC emissions from the coating usage for emissions units K001, K003, K004 and K005, combined; and
 - b. the actual annual VOC emissions from the use of cleanup materials for emissions units K001, K003, K004 and K005, combined.
- These reports shall be submitted by January 31 of each year and shall cover the previous calendar year.
- (2) The permittee shall submit quarterly deviation (excursion) reports that identify the following:



- a. all exceedances of the daily VOC emission limitation of 256 pounds (from the use of coatings);
- b. all exceedances of the monthly VOC emission limitation of 1.95 tons (from the cleanup operations for emissions units K001, K003, K004 and K005, combined), and the actual VOC emissions for each such month;
- c. all exceedances of the rolling, 12-month individual HAP and total combined HAPs emission limitations of 9.90 tons and 24.90 tons, respectively (for emissions units K001, K003, K004 and K005, combined); and

These reports shall be submitted in accordance with the General Terms and Conditions of this permit.

- (3) The permittee shall notify the Ohio EPA Northeast District Office in writing of any daily record showing that the particulate filter system was not in service when the emissions unit was in operation. The notification shall include a copy of such record and shall be sent to the Ohio EPA Northeast District Office within 30 days after the event occurs.
- (4) The permittee shall notify the Ohio EPA Northeast District Office in writing of any daily record showing that the total number of motor vehicles that were top coated from emissions units K001, K003, K004 and K005, combined, were at least thirty-five (35) motor vehicles. The notification shall include a copy of such record and shall be sent to the Ohio EPA Northeast District Office within 30 days after the event occurs.
- (5) The permittee shall submit an annual Permit Evaluation Report (PER) to the Ohio EPA. The PER must be submitted by the due date identified in the Authorization section of this permit. The permit evaluation report shall cover a reporting period of no more than twelve months for each air contaminant source identified in this permit.
- (6) All applications, notifications or reports required by terms and conditions in this permit to be submitted or "reported in writing" are to be submitted to Ohio EPA through the Ohio EPA's eBusiness Center: Air Services web service ("Air Services"). Ohio EPA will accept hard copy submittals on an as-needed basis if the permittee cannot submit the required documents through the Ohio EPA eBusiness Center. In the event of an alternative hard copy submission in lieu of the eBusiness Center, the post-marked date or the date the document is delivered in person will be recognized as the date submitted. Electronic submission of applications, notifications, or reports required to be submitted to Ohio EPA fulfills the requirement to submit the required information to the Director, the District Office or Local Air Agency, and/or any other individual or organization specifically identified as an additional recipient identified in this permit unless otherwise specified. Consistent with OAC rule 3745-15-03, the required application, notification or report is considered to be "submitted" on the date the submission is successful using a valid electronic signature. Signature by the signatory authority may be represented as provided through procedures established in Air Services.



f) Testing Requirements

(1) Compliance with the Emissions Limitations and/or Control Requirements specified in section b) of these terms and conditions shall be determined in accordance with the following methods:

a. Emission Limitation:

VOC emissions from coating operations shall not exceed 514 lbs/day.

Applicable Compliance Method:

Compliance shall be demonstrated based upon the record keeping requirements specified in section 2.d)(1).

b. Emission Limitation:

VOC emissions from coating operations shall not exceed 19.75 tons/year.

Applicable Compliance Method:

Compliance shall be demonstrated based upon the record keeping requirements specified in section 2.d)(2).

c. Emission Limitation:

VOC emissions from coating operations shall not exceed 67.35 tons/year for emissions units K001, K003, K004 and K005, combined.

Applicable Compliance Method:

Compliance shall be demonstrated based upon the record keeping requirements specified in section 2.d)(4).

d. Emission Limitation:

VOC emissions from cleanup operations shall not exceed 1.95 tons/month for emissions units K001, K003, K004 and K005, combined.

Applicable Compliance Method:

Compliance shall be demonstrated based upon the record keeping requirements specified in section 2.d)(3).

e. Emission Limitation:

VOC emissions from cleanup operations shall not exceed 23.31 tons/year for emissions units K001, K003, K004 and K005, combined.



Applicable Compliance Method:

Compliance shall be demonstrated based upon the record keeping requirements specified in section 2.d)(5).

f. Emission Limitation:

PE shall not exceed 0.551 lb/hour.

Applicable Compliance Method:

To determine the actual worst case PE rate, the following equation may be used:

$$E = A*B*C*(1-45%)(1-99%)90\%$$

where:

E = particulate emissions, in lb/hr

A = total solid contents per gallon of coating material, in %

B = total coating density of coating material, in lbs/gal

C = total number of coating material used, gal/hr

45% = transfer efficiency of spray nozzle (provided by facility)

99% = particulate matter filter efficiency (provided by facility)

90% = capture efficiency (provided by facility)

If required, the permittee shall demonstrate compliance with the hourly allowable PE limitation pursuant to OAC rule 3745-17-03(B)(10).

g. Emission Limitation:

PE shall not exceed 2.41 tpy.

Applicable Compliance Method:

The tpy emission limitation was developed by multiplying the short-term allowable particulate emission limitation (0.551 lb/hr) by the maximum annual hours of operation (8,760 hours), and then dividing by 2,000 lbs per ton. Therefore, if compliance is shown with the short-term allowable emission limitation, compliance shall also be shown with the annual emission limitation.

h. Emission Limitation:

Visible PE shall not exceed 20% opacity, as a 6-minute average, except as provided by the rule.

Applicable Compliance Method:

If required, the permittee shall demonstrate compliance with the visible PE limitation pursuant to OAC rule 3745-17-03(B)(1).



i. Emission Limitation:

Annual HAP emissions from emissions units K001, K003, K004 and K005, combined, shall not exceed 9.90 tons per rolling, 12-month period for any individual HAP or 24.90 tons per rolling, 12-month period for total combined HAPs.

Applicable Compliance Method:

Compliance shall be demonstrated based upon the record keeping requirements specified in section 1.d)(6). of this permit.

- (2) Formulation data or U.S. EPA Method 24 shall be used to determine the VOC contents of all coatings, glues, autobody finishing materials and cleanup materials.
- (3) The HAPs for each coating, glue, autobody finishing material and cleanup material shall be determined using one of the following methods:
 - a. Method 311 from 40 CFR Part 63, Appendix A;
 - b. Method 24 from 40 CFR Part 60, Appendix A if all non-aqueous volatile matter is to be used for HAP content; or
 - c. information from the supplier or manufacturer of the materials, where the HAP content is provided or can be calculated.

g) Miscellaneous Requirements

- (1) None.



3. K004, Paint booth 4

Operations, Property and/or Equipment Description:

Paint booth No. 4 with a 0.06 MMBtu/hr natural gas fired drying oven

- a) This permit document constitutes a permit-to-install issued in accordance with ORC 3704.03(F) and a permit-to-operate issued in accordance with ORC 3704.03(G).
 - (1) For the purpose of a permit-to-install document, the emissions unit terms and conditions identified below are federally enforceable with the exception of those listed below which are enforceable under state law only.
 - a. None.
 - (2) For the purpose of a permit-to-operate document, the emissions unit terms and conditions identified below are enforceable under state law only with the exception of those listed below which are federally enforceable.
 - a. None.
- b) Applicable Emissions Limitations and/or Control Requirements
 - (1) The specific operation(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures are identified below. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC rule 3745-31-05(A)(3) (PTI No. 02-22256, issued 3/1/2007)	<u>Coating Emissions:</u> Volatile organic compounds (VOC) emissions shall not exceed 303 lbs/day and 21 tons/year. VOC emissions shall not exceed 67.35 tons/year for emissions units K001, K003, K004 and K005, combined. <u>Cleanup Emissions:</u> VOC emissions shall not exceed 1.95 tons/month for emissions units K001, K003, K004 and K005, combined. VOC emissions shall not exceed 23.31 tons/year for emissions units K001, K003, K004 and K005, combined.



	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
		Particulate emissions (PE) shall not exceed 0.551 lb/hour and 2.41 tpy See section 3.b)(2)a. below.
b.	OAC rule 3745-17-11(B)(2)	The emission limitation required by this applicable rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).
	OAC rule 3745-17-07(A)	Visible PE shall not exceed 20% opacity, as a 6-minute average, except as provided by the rule.
	OAC rule 3745-21-09(U)(2)(d)	The permittee shall apply a customized topcoat and any related customized single coat to a maximum of less than 35 motor vehicles per day.
	OAC rule 3745-31-05(D)	Emissions of hazardous air pollutants (HAPs) shall not exceed 9.90 tons per year for an individual HAP or 24.90 tons per year for total combined HAPs. See section 3.b)(2)b. below.

(2) Additional Terms and Conditions

- a. The requirements of this rule also include compliance with the requirements of OAC rules 3745-31-05(C), 3745-21-09(U)(2)(d), 3745-17-11(B)(2) and 3745-17-07(A).
- b. This permit establishes federally enforceable limitations on emissions of hazardous air pollutants (HAPs) for purposes of avoiding Maximum Achievable Control Technology (MACT) regulations and Title V permitting requirements. Annual HAP emissions from emissions units K001, K003, K004 and K005, combined, shall not exceed 9.90 tons per rolling, 12-month period for any individual HAP or 24.90 tons per rolling, 12-month period for total combined HAPs.

This is an existing emissions unit which has existing records of the amount of individual and total combined HAPs emissions and therefore does not need to be restricted on a monthly basis.



- c) Operational Restrictions
 - (1) Coating and liquid organic cleanup materials employed in this emissions unit shall not exceed: 16,800 gallons per rolling, 12-month period and 1,750 gallons per rolling, 12-month period, respectively.
 - (2) This emissions unit shall be equipped with a filter system that shall minimize or eliminate all particulate emissions from the painting operation.
- d) Monitoring and/or Recordkeeping Requirements
 - (1) The permittee shall collect and record the following information each day for this emissions unit:
 - a. the name and identification number of each coating employed;
 - b. the number of gallons of each coating employed;
 - c. the total number of gallons of all the coatings employed;
 - d. the VOC content of each coating employed, in lbs/gallon;
 - e. the total emissions of VOC for each coating employed (b x d), in lbs; and
 - f. the total emissions of VOC for all the coatings employed (summation of e for all coatings), in lbs.
 - (2) The permittee shall calculate and record the following information each month for this emissions unit.
 - a. the total VOC emissions for all coatings employed (summation of the daily VOC emission rates, from section 3.d)(1)f., for the calendar month, divided by 2000), in tons, for this emissions unit; and
 - b. the annual, year-to-date, VOC emission rate for all coatings employed (summation of section 3.d)(2)a for each calendar month to date from January to December), in tons.
 - (3) The permittee shall calculate and record the following information each month for emissions units K001, K003, K004 and K005, combined:
 - a. the name and identification number of each cleanup material employed;
 - b. the VOC content of each cleanup material employed, in lbs/gallon;
 - c. the number of gallons of each cleanup material employed;
 - d. the total emissions of VOC for each cleanup material employed (b x c), in lbs;



- e. the total emissions of VOC for all the cleanup materials employed (summation of d for all cleanup materials), in tons.
- (4) The permittee shall calculate and record the following information each month for emissions units K001, K003, K004 and K005, combined:
- a. the total VOC emissions for all coatings employed (summation of section 3.d)2 above for K001, K003, K004 and K005), in tons; and
 - b. the annual, year-to-date, VOC emission rate for all coatings employed (summation of section 3.d)(4)a. for each calendar month to date from January to December), in tons.
- (5) The permittee shall calculate and record the following information each month for emissions units K001, K003, K004 and K005, combined:
- a. the total VOC emissions for all the cleanup materials employed (summation of section 3.d)2.e above for K001, K003, K004 and K005), in tons; and
 - b. the annual, year-to-date, VOC emission rate for all cleanup materials employed (summation of section 3.d)(5)a. for each calendar month to date from January to December), in tons.
- (6) The permittee shall collect and record the following HAP information each month for emissions units K001, K003, K004 and K005, combined:
- a. the company identification of each coating and cleanup material employed;
 - b. the amount of each individual HAP in each coating and cleanup material, in lbs/gallon, as applied;
 - c. the number of gallons of each coating and cleanup material employed;
 - d. the emission rate for each individual HAP from each coating and cleanup material employed (3.d)(6)b. x 3.d)(6)c.), in lbs;
 - e. the total emission rate for each individual HAP from all coatings and cleanup materials employed (for each individual HAP, the summation of section 3.d)(6)d. for all coatings and cleanup materials), in lbs;
 - f. the total HAP emission rate for all HAPs combined from all coatings and cleanup materials employed (summation of section 3.d)(6)e. for all HAPs for all coatings and cleanup materials), in lbs; and
 - g. the rolling, 12-month emissions of each individual HAP and all HAPs combined, in tons.
- (7) The permittee shall maintain daily records that document any time periods when the particulate filter system was not in service when the emissions unit was in operation.



- (8) The permittee shall maintain daily records of the total number of motor vehicles that were topcoated from emissions units K001, K003, K004 and K005, combined.
- (9) The permit to install for this emissions unit [K004] was evaluated based on the actual materials and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied to this emissions unit for each toxic pollutant, using data from the permit to install application, and modeling was performed for the toxic pollutant(s) emitted at over a ton per year using the SCREEN 3.0 model or other Ohio EPA approved model. The predicted 1-hour maximum ground-level concentration result(s) from the use of the SCREEN 3.0 (or other approved) model, was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC), calculated as required in Engineering Guide #70. The following summarizes the results of the modeling for the "worst case" pollutant(s) from the combined emissions of K001, K003 and K004, combined:

Pollutant: Methyl Isobutyl Ketone (MIBK)

TLV (mg/m³): 205

Maximum Hourly Emission Rate (lbs/hr): 6.71

Predicted 1-Hour Max. Ground-Level Concentration (ug/m³): 667.10

MAGLC (ug/m³): 4,881

Pollutant: Xylene

TLV (mg/m³): 434

Maximum Hourly Emission Rate (lbs/hr): 23.93

Predicted 1-Hour Max. Ground-Level Concentration (ug/m³): 2379

MAGLC (ug/m³): 10,333

- (10) Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:
- a. changes in the composition of the materials used or the use of new materials, that would result in the emission of a compound or chemical with a lower Threshold Limit Value (TLV) than the lowest TLV previously modeled, as documented in the most current version of the American Conference of Governmental Industrial Hygienists' (ACGIH's) handbook entitled "TLVs and



BEIs" ("Threshold Limit Values for Chemical Substances and Physical Agents, Biological Exposure Indices");

- b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and
 - c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).
- (11) If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01 solely due to the emissions of any type of toxic air contaminant not previously emitted, and a modification of the existing permit to install will not be required, even if the toxic air contaminant emissions are greater than the de minimis level in OAC rule 3745-15-05. If the change(s) meet(s) the definition of a "modification" under other provisions of the rule, then the permittee shall obtain a final permit to install prior to the change.
- (12) The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy":
- a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
 - b. documentation of the evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and
 - c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.
- e) Reporting Requirements
- (1) The permittee shall submit annual reports that summarize the following:
- a. the actual annual VOC emissions from the coating usage for emissions units K001, K003, K004 and K005, combined; and
 - b. the actual annual VOC emissions from the use of cleanup materials for emissions units K001, K003, K004 and K005, combined.
- These reports shall be submitted by January 31 of each year and shall cover the previous calendar year.
- (2) The permittee shall submit quarterly deviation (excursion) reports that identify the following:



- a. all exceedances of the daily VOC emission limitation of 303 pounds (from the use of coatings);
- b. all exceedances of the monthly VOC emission limitation of 1.95 tons (from the cleanup operations for emissions units K001, K003, K004 and K005, combined), and the actual VOC emissions for each such month;
- c. all exceedances of the rolling, 12-month individual HAP and total combined HAPs emission limitations of 9.90 tons and 24.90 tons, respectively (for emissions units K001, K003, K004 and K005, combined); and

These reports shall be submitted in accordance with the General Terms and Conditions of this permit.

- (3) The permittee shall notify the Ohio EPA Northeast District Office in writing of any daily record showing that the particulate filter system was not in service when the emissions unit was in operation. The notification shall include a copy of such record and shall be sent to the Ohio EPA Northeast District Office within 30 days after the event occurs.
- (4) The permittee shall notify the Ohio EPA Northeast District Office in writing of any daily record showing that the total number of motor vehicles that were top coated from emissions units K001, K003, K004 and K005, combined, were at least thirty-five (35) motor vehicles. The notification shall include a copy of such record and shall be sent to the Ohio EPA Northeast District Office within 30 days after the event occurs.
- (5) The permittee shall submit an annual Permit Evaluation Report (PER) to the Ohio EPA. The PER must be submitted by the due date identified in the Authorization section of this permit. The permit evaluation report shall cover a reporting period of no more than twelve months for each air contaminant source identified in this permit.
- (6) All applications, notifications or reports required by terms and conditions in this permit to be submitted or "reported in writing" are to be submitted to Ohio EPA through the Ohio EPA's eBusiness Center: Air Services web service ("Air Services"). Ohio EPA will accept hard copy submittals on an as-needed basis if the permittee cannot submit the required documents through the Ohio EPA eBusiness Center. In the event of an alternative hard copy submission in lieu of the eBusiness Center, the post-marked date or the date the document is delivered in person will be recognized as the date submitted. Electronic submission of applications, notifications, or reports required to be submitted to Ohio EPA fulfills the requirement to submit the required information to the Director, the District Office or Local Air Agency, and/or any other individual or organization specifically identified as an additional recipient identified in this permit unless otherwise specified. Consistent with OAC rule 3745-15-03, the required application, notification or report is considered to be "submitted" on the date the submission is successful using a valid electronic signature. Signature by the signatory authority may be represented as provided through procedures established in Air Services.



f) Testing Requirements

(1) Compliance with the Emissions Limitations and/or Control Requirements specified in section b) of these terms and conditions shall be determined in accordance with the following methods:

a. Emission Limitation:

VOC emissions from coating operations shall not exceed 303 lbs/day.

Applicable Compliance Method:

Compliance shall be demonstrated based upon the record keeping requirements specified in section 3.d)(1).

b. Emission Limitation:

VOC emissions from coating operations shall not exceed 21 tons/year.

Applicable Compliance Method:

Compliance shall be demonstrated based upon the record keeping requirements specified in section 3.d)(2).

c. Emission Limitation:

VOC emissions from coating operations shall not exceed 67.35 tons/year for emissions units K001, K003, K004 and K005, combined.

Applicable Compliance Method:

Compliance shall be demonstrated based upon the record keeping requirements specified in section 3.d)(4).

d. Emission Limitation:

VOC emissions from cleanup operations shall not exceed 1.95 tons/month for emissions units K001, K003, K004 and K005, combined.

Applicable Compliance Method:

Compliance shall be demonstrated based upon the record keeping requirements specified in section 3.d)(3).

e. Emission Limitation:

VOC emissions from cleanup operations shall not exceed 23.31 tons/year for emissions units K001, K003, K004 and K005, combined.



Applicable Compliance Method:

Compliance shall be demonstrated based upon the record keeping requirements specified in section 3.d)(5).

f. Emission Limitation:

PE shall not exceed 0.551 lb/hour.

Applicable Compliance Method:

To determine the actual worst case PE rate, the following equation may be used:

$$E = A*B*C*(1-45%)(1-99%)90\%$$

where:

E = particulate emissions, in lb/hr

A = total solid contents per gallon of coating material, in %

B = total coating density of coating material, in lbs/gal

C = total number of coating material used, gal/hr

45% = transfer efficiency of spray nozzle (provided by facility)

99% = particulate matter filter efficiency (provided by facility)

90% = capture efficiency (provided by facility)

If required, the permittee shall demonstrate compliance with the hourly allowable PE limitation pursuant to OAC rule 3745-17-03(B)(10).

g. Emission Limitation:

PE shall not exceed 2.41 tpy.

Applicable Compliance Method:

The tpy emission limitation was developed by multiplying the short-term allowable particulate emission limitation (0.551 lb/hr) by the maximum annual hours of operation (8,760 hours), and then dividing by 2,000 lbs per ton. Therefore, if compliance is shown with the short-term allowable emission limitation, compliance shall also be shown with the annual emission limitation.

h. Emission Limitation:

Visible PE shall not exceed 20% opacity, as a 6-minute average, except as provided by the rule.

Applicable Compliance Method:

If required, the permittee shall demonstrate compliance with the visible PE limitation pursuant to OAC rule 3745-17-03(B)(1).



i. Emission Limitation:

Annual HAP emissions from emissions units K001, K003, K004 and K005, combined, shall not exceed 9.90 tons per rolling, 12-month period for any individual HAP or 24.90 tons per rolling, 12-month period for total combined HAPs.

Applicable Compliance Method:

Compliance shall be demonstrated based upon the record keeping requirements specified in section 3.d)(6). of this permit.

- (2) Formulation data or U.S. EPA Method 24 shall be used to determine the VOC contents of all coatings, glues, autobody finishing materials and cleanup materials.
- (3) The HAPs for each coating, glue, autobody finishing material and cleanup material shall be determined using one of the following methods:
 - a. Method 311 from 40 CFR Part 63, Appendix A;
 - b. Method 24 from 40 CFR Part 60, Appendix A if all non-aqueous volatile matter is to be used for HAP content; or
 - c. information from the supplier or manufacturer of the materials, where the HAP content is provided or can be calculated.

g) Miscellaneous Requirements

- (1) None.



4. K005, Paint booth 5

Operations, Property and/or Equipment Description:

Paint booth No. 5 (Undercoating)

- a) This permit document constitutes a permit-to-install issued in accordance with ORC 3704.03(F) and a permit-to-operate issued in accordance with ORC 3704.03(G).
 - (1) For the purpose of a permit-to-install document, the emissions unit terms and conditions identified below are federally enforceable with the exception of those listed below which are enforceable under state law only.
 - a. None.
 - (2) For the purpose of a permit-to-operate document, the emissions unit terms and conditions identified below are enforceable under state law only with the exception of those listed below which are federally enforceable.
 - a. None.
- b) Applicable Emissions Limitations and/or Control Requirements
 - (1) The specific operation(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures are identified below. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC rule 3745-31-05(A)(3) (PTI No. 02-22256, issued 3/1/2007)	<u>Coating Emissions:</u> Volatile organic compounds (VOC) emissions shall not exceed 272 lbs/day and 13.6 tons/year. VOC emissions shall not exceed 67.35 tons/year for emissions units K001, K003, K004 and K005, combined. <u>Cleanup Emissions:</u> VOC emissions shall not exceed 1.95 tons/month for emissions units K001, K003, K004 and K005, combined. VOC emissions shall not exceed 23.31 tons/year for emissions units K001, K003, K004 and K005, combined.



	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
		See section 4.b)(2)a. below.
b.	OAC rule 3745-17-08	See section 4.b)(2)b. below.
c.	OAC rule 3745-21-09(U)(2)(d)	The permittee shall apply a customized topcoat and any related customized single coat to a maximum of less than 35 motor vehicles per day.
d.	OAC rule 3745-31-05(D)	Emissions of hazardous air pollutants (HAPs) shall not exceed 9.90 tons per year for an individual HAP or 24.90 tons per year for total combined HAPs. See section 4.b)(2)c. below.

(2) Additional Terms and Conditions

- a. The requirements of this rule also include compliance with the requirements of OAC rules 3745-31-05(C) and 3745-21-09(U)(2)(d).
- b. This emissions unit is exempt from the visible emission limitation specified in OAC rule 3745-17-08 because the facility is located in a non-Appendix A area.
- c. This permit establishes federally enforceable limitations on emissions of hazardous air pollutants (HAPs) for purposes of avoiding Maximum Achievable Control Technology (MACT) regulations and Title V permitting requirements. Annual HAP emissions from emissions units K001, K003, K004 and K005, combined, shall not exceed 9.90 tons per rolling, 12-month period for any individual HAP or 24.90 tons per rolling, 12-month period for total combined HAPs.

This is an existing emissions unit which has existing records of the amount of individual and total combined HAPs emissions and therefore does not need to be restricted on a monthly basis.

c) Operational Restrictions

- (1) Coating and liquid organic cleanup materials employed in this emissions unit shall not exceed: 8,000 gallons per rolling, 12-month period and 1,750 gallons per rolling, 12-month period, respectively.



- d) Monitoring and/or Recordkeeping Requirements
- (1) The permittee shall collect and record the following information each day for this emissions unit:
 - a. the name and identification number of each coating employed;
 - b. the number of gallons of each coating employed;
 - c. the total number of gallons of all the coatings employed;
 - d. the VOC content of each coating employed, in lbs/gallon;
 - e. the total emissions of VOC for each coating employed (b x d), in lbs; and
 - f. the total emissions of VOC for all the coatings employed (summation of e for all coatings), in lbs.
 - (2) The permittee shall calculate and record the following information each month for this emissions unit.
 - a. the total VOC emissions for all coatings employed (summation of the daily VOC emission rates, from section 4.d)(1)f., for the calendar month, divided by 2000), in tons, for this emissions unit; and
 - b. the annual, year-to-date, VOC emission rate for all coatings employed (summation of section 4.d)(2)a for each calendar month to date from January to December), in tons.
 - (3) The permittee shall calculate and record the following information each month for emissions units K001, K003, K004 and K005, combined:
 - a. the name and identification number of each cleanup material employed;
 - b. the VOC content of each cleanup material employed, in lbs/gallon;
 - c. the number of gallons of each cleanup material employed;
 - d. the total emissions of VOC for each cleanup material employed (b x c), in lbs;
 - e. the total emissions of VOC for all the cleanup materials employed (summation of d for all cleanup materials), in tons.
 - (4) The permittee shall calculate and record the following information each month for emissions units K001, K003, K004 and K005, combined:
 - a. the total VOC emissions for all coatings employed (summation of section 4.d)2 above for K001, K003, K004 and K005), in tons; and



- b. the annual, year-to-date, VOC emission rate for all coatings employed (summation of section 4.d)(4)a. for each calendar month to date from January to December), in tons.
- (5) The permittee shall calculate and record the following information each month for emissions units K001, K003, K004 and K005, combined:
- a. the total VOC emissions for all the cleanup materials employed (summation of section 4.d)2.e above for K001, K003, K004 and K005), in tons; and
 - b. the annual, year-to-date, VOC emission rate for all cleanup materials employed (summation of section 4.d)(5)a. for each calendar month to date from January to December), in tons.
- (6) The permittee shall collect and record the following HAP information each month for emissions units K001, K003, K004 and K005, combined:
- a. the company identification of each coating and cleanup material employed;
 - b. the amount of each individual HAP in each coating and cleanup material, in lbs/gallon, as applied;
 - c. the number of gallons of each coating and cleanup material employed;
 - d. the emission rate for each individual HAP from each coating and cleanup material employed (4.d)(6)b. x 4.d)(6)c.), in lbs;
 - e. the total emission rate for each individual HAP from all coatings and cleanup materials employed (for each individual HAP, the summation of section 4.d)(6)d. for all coatings and cleanup materials), in lbs;
 - f. the total HAP emission rate for all HAPs combined from all coatings and cleanup materials employed (summation of section 4.d)(6)e. for all HAPs for all coatings and cleanup materials), in lbs; and
 - g. the rolling, 12-month emissions of each individual HAP and all HAPs combined, in tons.
- (7) The permittee shall maintain daily records of the total number of motor vehicles that were topcoated from emissions units K001, K003, K004 and K005, combined.
- e) Reporting Requirements
- (1) The permittee shall submit annual reports that summarize the following:
- a. the actual annual VOC emissions from the coating usage for emissions units K001, K003, K004 and K005, combined; and
 - b. the actual annual VOC emissions from the use of cleanup materials for emissions units K001, K003, K004 and K005, combined.



These reports shall be submitted by January 31 of each year and shall cover the previous calendar year.

- (2) The permittee shall submit quarterly deviation (excursion) reports that identify the following:
 - a. all exceedances of the daily VOC emission limitation of 272 pounds (from the use of coatings);
 - b. all exceedances of the monthly VOC emission limitation of 1.95 tons (from the cleanup operations for emissions units K001, K003, K004 and K005, combined), and the actual VOC emissions for each such month;
 - c. all exceedances of the rolling, 12-month individual HAP and total combined HAPs emission limitations of 9.90 tons and 24.90 tons, respectively (for emissions units K001, K003, K004 and K005, combined); and

These reports shall be submitted in accordance with the General Terms and Conditions of this permit.

- (3) The permittee shall notify the Ohio EPA Northeast District Office in writing of any daily record showing that the particulate filter system was not in service when the emissions unit was in operation. The notification shall include a copy of such record and shall be sent to the Ohio EPA Northeast District Office within 30 days after the event occurs.
- (4) The permittee shall notify the Ohio EPA Northeast District Office in writing of any daily record showing that the total number of motor vehicles that were top coated from emissions units K001, K003, K004 and K005, combined, were at least thirty-five (35) motor vehicles. The notification shall include a copy of such record and shall be sent to the Ohio EPA Northeast District Office within 30 days after the event occurs.
- (5) The permittee shall submit an annual Permit Evaluation Report (PER) to the Ohio EPA. The PER must be submitted by the due date identified in the Authorization section of this permit. The permit evaluation report shall cover a reporting period of no more than twelve months for each air contaminant source identified in this permit.
- (6) All applications, notifications or reports required by terms and conditions in this permit to be submitted or "reported in writing" are to be submitted to Ohio EPA through the Ohio EPA's eBusiness Center: Air Services web service ("Air Services"). Ohio EPA will accept hard copy submittals on an as-needed basis if the permittee cannot submit the required documents through the Ohio EPA eBusiness Center. In the event of an alternative hard copy submission in lieu of the eBusiness Center, the post-marked date or the date the document is delivered in person will be recognized as the date submitted. Electronic submission of applications, notifications, or reports required to be submitted to Ohio EPA fulfills the requirement to submit the required information to the Director, the District Office or Local Air Agency, and/or any other individual or organization specifically identified as an additional recipient identified in this permit unless otherwise specified. Consistent with OAC rule 3745-15-03, the required application, notification or report is considered to be "submitted" on the date the submission is successful using a valid



electronic signature. Signature by the signatory authority may be represented as provided through procedures established in Air Services.

f) Testing Requirements

(1) Compliance with the Emissions Limitations and/or Control Requirements specified in section b) of these terms and conditions shall be determined in accordance with the following methods:

a. Emission Limitation:

VOC emissions from coating operations shall not exceed 272 lbs/day.

Applicable Compliance Method:

Compliance shall be demonstrated based upon the record keeping requirements specified in section 4.d)(1).

b. Emission Limitation:

VOC emissions from coating operations shall not exceed 13.6 tons/year.

Applicable Compliance Method:

Compliance shall be demonstrated based upon the record keeping requirements specified in section 4.d)(2).

c. Emission Limitation:

VOC emissions from coating operations shall not exceed 67.35 tons/year for emissions units K001, K003, K004 and K005, combined.

Applicable Compliance Method:

Compliance shall be demonstrated based upon the record keeping requirements specified in section 4.d)(4).

d. Emission Limitation:

VOC emissions from cleanup operations shall not exceed 1.95 tons/month for emissions units K001, K003, K004 and K005, combined.

Applicable Compliance Method:

Compliance shall be demonstrated based upon the record keeping requirements specified in section 4.d)(3).

e. Emission Limitation:

VOC emissions from cleanup operations shall not exceed 23.31 tons/year for emissions units K001, K003, K004 and K005, combined.



Applicable Compliance Method:

Compliance shall be demonstrated based upon the record keeping requirements specified in section 4.d)(5).

f. Emission Limitation:

Annual HAP emissions from emissions units K001, K003, K004 and K005, combined, shall not exceed 9.90 tons per rolling, 12-month period for any individual HAP or 24.90 tons per rolling, 12-month period for total combined HAPs.

Applicable Compliance Method:

Compliance shall be demonstrated based upon the record keeping requirements specified in section 4.d)(6). of this permit.

- (2) Formulation data or U.S. EPA Method 24 shall be used to determine the VOC contents of all coatings, glues, autobody finishing materials and cleanup materials.
- (3) The HAPs for each coating, glue, autobody finishing material and cleanup material shall be determined using one of the following methods:
 - a. Method 311 from 40 CFR Part 63, Appendix A;
 - b. Method 24 from 40 CFR Part 60, Appendix A if all nonaqueous volatile matter is to be used for HAP content; or
 - c. information from the supplier or manufacturer of the materials, where the HAP content is provided or can be calculated.

g) Miscellaneous Requirements

- (1) None.