



State of Ohio Environmental Protection Agency

**RE: FINAL PERMIT TO INSTALL MODIFICATION
CUYAHOGA COUNTY**

CERTIFIED MAIL

Street Address:

122 S. Front Street

Lazarus Gov. Center TELE: (614) 644-3020 FAX: (614) 644-2329

Mailing Address:
Lazarus Gov. Center
P.O. Box 1049

Application No: 13-04549

Fac ID: 1318558216

DATE: 12/22/2005

GE Quartz, Inc.
James Maskil
22557 West Lunn Road
Cleveland, OH 44101-4924

Enclosed Please find a modification to the Ohio EPA Permit To Install referenced above which will modify the terms and conditions.

You are hereby notified that this action by the Director is final and may be appealed to the Ohio Environmental Review Appeals Commission pursuant to Chapter 3745.04 of the Ohio Revised Code. The appeal must be in writing and set forth the action complained of and the grounds upon which the appeal is based. It must be filed within thirty (30) days after the notice of the Directors action. A copy of the appeal must be served on the Director of the Ohio Environmental Protection Agency within three (3) days of filing with the Commission. An appeal may be filed with the Environmental Review Appeals Commission at the following address:

Environmental Review Appeals Commission
309 South Fourth Street, Room 222
Columbus, Ohio 43215

Sincerely,

Michael W. Ahern

Michael W. Ahern, Manager
Permit Issuance and Data Management Section
Division of Air Pollution Control

CC: USEPA

CLAA



**Permit To Install
Terms and Conditions**

**Issue Date: 12/22/2005
Effective Date: 12/22/2005**

FINAL ADMINISTRATIVE MODIFICATION OF PERMIT TO INSTALL 13-04549

Application Number: 13-04549
Facility ID: 1318558216
Permit Fee: **\$0**
Name of Facility: GE Quartz, Inc.
Person to Contact: James Maskil
Address: 22557 West Lunn Road
Cleveland, OH 44101-4924

Location of proposed air contaminant source(s) [emissions unit(s)]:
**22557 West Lunn Road
Strongsville, Ohio**

Description of proposed emissions unit(s):
Powder Firing Line O.

The above named entity is hereby granted a modification to the permit to install described above pursuant to Chapter 3745-31 of the Ohio Administrative Code. Issuance of this modification does not constitute expressed or implied approval or agreement that, if constructed or modified in accordance with the plans included in the application, the above described source(s) of environmental pollutants will operate in compliance with applicable State and Federal laws and regulations, and does not constitute expressed or implied assurance that if constructed or modified in accordance with those plans included in the application, the above described source(s) of pollutants will be granted the necessary operating permits.

This permit is granted subject to the conditions attached hereto.

Ohio Environmental Protection Agency

Director

Part I - GENERAL TERMS AND CONDITIONS

A. Permit to Install General Terms and Conditions

1. Compliance Requirements

The emissions unit(s) identified in this Permit to Install shall remain in full compliance with all applicable State laws and regulations and the terms and conditions of this permit.

2. Reporting Requirements

The permittee shall submit required reports in the following manner:

- a. Reports of any required monitoring and/or recordkeeping information shall be submitted to the appropriate Ohio EPA District Office or local air agency.
- b. Except as otherwise may be provided in the terms and conditions for a specific emissions unit, quarterly written reports of (a) any deviations (excursions) from emission limitations, operational restrictions, and control device operating parameter limitations that have been detected by the testing, monitoring, and recordkeeping requirements specified in this permit, (b) the probable cause of such deviations, and (c) any corrective actions or preventive measures which have been or will be taken, shall be submitted to the appropriate Ohio EPA District Office or local air agency. If no deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted quarterly, i.e., by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters. (These quarterly reports shall exclude deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06.)

3. Records Retention Requirements

Each record of any monitoring data, testing data, and support information required pursuant to this permit shall be retained for a period of five years from the date the record was created. Support information shall include, but not be limited to, all calibration and maintenance records and all original strip-chart recordings for continuous monitoring instrumentation, and copies of all reports required by this permit. Such records may be maintained in computerized form.

4. Inspections and Information Requests

The Director of the Ohio EPA, or an authorized representative of the Director, may, subject to the safety requirements of the permittee and without undue delay, enter upon

GE Quartz, Inc.
PTI Application: 13-04549
Modification Issued: 12/22/2005

Facility ID: 131855821

the premises of this source at any reasonable time for purposes of making inspections, conducting tests, examining records or reports pertaining to any emission of air contaminants, and determining compliance with any applicable State air pollution laws and regulations and the terms and conditions of this permit. The permittee shall furnish to the Director of the Ohio EPA, or an authorized representative of the Director, upon receipt of a written request and within a reasonable time, any information that may be requested to determine whether cause exists for modifying, reopening or revoking this permit or to determine compliance with this permit. Upon verbal or written request, the permittee shall also furnish to the Director of the Ohio EPA, or an authorized representative of the Director, copies of records required to be kept by this permit.

5. Scheduled Maintenance/Malfunction Reporting

Any scheduled maintenance of air pollution control equipment shall be performed in accordance with paragraph (A) of OAC rule 3745-15-06. The malfunction of any emissions units or any associated air pollution control system(s) shall be reported to the appropriate Ohio EPA District Office or local air agency in accordance with paragraph (B) of OAC rule 3745-15-06. Except as provided in that rule, any scheduled maintenance or malfunction necessitating the shutdown or bypassing of any air pollution control system(s) shall be accompanied by the shutdown of the emissions unit(s) that is (are) served by such control system(s).

6. Permit Transfers

Any transferee of this permit shall assume the responsibilities of the prior permit holder. The appropriate Ohio EPA District Office or local air agency must be notified in writing of any transfer of this permit.

7. Air Pollution Nuisance

The air contaminants emitted by the emissions units covered by this permit shall not cause a public nuisance, in violation of OAC rule 3745-15-07.

8. Termination of Permit to Install

This Permit to Install shall terminate within eighteen months of the effective date of the Permit to Install if the owner or operator has not undertaken a continuing program of installation or modification or has not entered into a binding contractual obligation to undertake and complete within a reasonable time a continuing program of installation or modification. This deadline may be extended by up to 12 months if application is made to the Director within a reasonable time before the termination date and the party shows good cause for any such extension.

9. Construction of New Sources(s)

GE Quartz, Inc.
PTI Application: 13-04549
Modification Issued: 12/22/2005

Facility ID: 131855821

The proposed emissions unit(s) shall be constructed in strict accordance with the plans and application submitted for this permit to the Director of the Ohio Environmental Protection Agency. There may be no deviation from the approved plans without the express, written approval of the Agency. Any deviations from the approved plans or the above conditions may lead to such sanctions and penalties as provided under Ohio law. Approval of these plans does not constitute an assurance that the proposed facilities will operate in compliance with all Ohio laws and regulations. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed sources cannot meet the requirements of this permit or cannot meet applicable standards.

If the construction of the proposed emissions unit(s) has already begun or has been completed prior to the date the Director of the Environmental Protection Agency approves the permit application and plans, the approval does not constitute expressed or implied assurance that the proposed facility has been constructed in accordance with the approved plans. The action of beginning and/or completing construction prior to obtaining the Director's approval constitutes a violation of OAC rule 3745-31-02. Furthermore, issuance of the Permit to Install does not constitute an assurance that the proposed source will operate in compliance with all Ohio laws and regulations. Approval of the plans in any case is not to be construed as an approval of the facility as constructed and/or completed. Moreover, issuance of the Permit to Install is not to be construed as a waiver of any rights that the Ohio Environmental Protection Agency (or other persons) may have against the applicant for starting construction prior to the effective date of the permit. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed facilities cannot meet the requirements of this permit or cannot meet applicable standards.

10. Public Disclosure

The facility is hereby notified that this permit, and all agency records concerning the operation of this permitted source, are subject to public disclosure in accordance with OAC rule 3745-49-03.

11. Applicability

This Permit To Install is applicable only to the emissions unit(s) identified in the Permit To Install. Separate Permit To Install for the installation or modification of any other emissions unit(s) are required for any emissions unit for which a Permit To Install is required.

GE Quartz, Inc.
 PTI Application: 13-04549
 Modification Issued: 12/22/2005

Facility ID: 131855821

12. Best Available Technology

As specified in OAC Rule 3745-31-05, all new sources must employ Best Available Technology (BAT). Compliance with the terms and conditions of this permit will fulfill this requirement.

13. Source Operation and Operating Permit Requirements After Completion of Construction

This facility is permitted to operate each source described by this Permit to Install for a period of up to one year from the date the source commenced operation. This permission to operate is granted only if the facility complies with all requirements contained in this permit and all applicable air pollution laws, regulations, and policies. Pursuant to OAC Chapter 3745-35, the permittee shall submit a complete operating permit application within ninety (90) days after commencing operation of the emissions unit(s) covered by this permit.

14. Construction Compliance Certification

The applicant shall provide Ohio EPA with a written certification (see enclosed form) that the facility has been constructed in accordance with the Permit to Install application and the terms and conditions of the Permit to Install. The certification shall be provided to Ohio EPA upon completion of construction but prior to startup of the source.

15. Fees

The permittee shall pay fees to the Director of the Ohio EPA in accordance with ORC section 3745.11 and OAC Chapter 3745-78. The permittee shall pay all applicable Permit to Install fees within 30 days after the issuance of this Permit to Install.

B. Permit to Install Summary of Allowable Emissions

The following information summarizes the total allowable emissions, by pollutant, based on the individual allowable emissions of each air contaminant source identified in this permit.

**SUMMARY (for informational purposes only)
 TOTAL PERMIT TO INSTALL ALLOWABLE EMISSIONS**

<u>Pollutant</u>	<u>Tons Per Year</u>
PE	7.65
PM10	7.20
CO	25.65

GE Quartz, Inc.

PTI Application: 13-04549

Modification Issued: 12/22/2005

Facility ID: 131855821



GE QI

PTI A

Modification Issued: 12/22/2005

Emissions Unit ID: P019

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)**A. Applicable Emissions Limitations and/or Control Requirements**

- The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P019 - Cosmetic and Industrial Grade BN Powder Firing Line - G	OAC rule 3745-31-05(A)(3)	7.91 lbs/batch and 0.85 ton/year particulate emissions (PE)
		7.52 lbs/batch and 0.80 ton/year PM ₁₀
		26.65 lbs/batch and 2.85 tons/year carbon monoxide (CO) emissions
		Visible emissions serving this emissions unit shall not exceed 10% opacity, as a six minute average.
	OAC rule 3745-17-07(A)	See A.2.a, A.2.b, and B.1 below.
	OAC rule 3745-17-11(B)	The visible emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).
		The particulate emission limitation specified by this rule is less stringent than the particulate

GE Quartz, Inc.
PTI Application: 13-04510
Modif

Facility ID: 131855821

Emissions Unit ID: P019

emission limitation established
pursuant to OAC rule
3745-31-05(A)(3).

2. Additional Terms and Conditions

- 2.a** This emissions unit operates using a batch process. Since the batch operation takes longer than one day to complete (41 hours) and total PE for the batch are 7.91 pounds and total PM₁₀ emissions are 7.52 pounds, these emissions limitations are more stringent than the allowable limits from OAC rule 3745-17-11(B). The annual limitation was determined based on a maximum of 214 batches per year.
- 2.b** The short-term and annual emissions limitations were established based on potential to emit; therefore, no recordkeeping and/or reporting requirements are needed for these emissions limitations.

B. Operational Restrictions

1. The permittee shall operate the baghouse for control of particulate emissions while the emissions unit is in operation.
2. The pressure drop across the baghouse shall be maintained within the range of 0.5 to 7.0 inches of water while the emissions unit is in operation.

C. Monitoring and/or Recordkeeping Requirements

1. The permittee shall properly install, operate, and maintain equipment to monitor the pressure drop across the baghouse while the emissions unit is in operation. The monitoring equipment shall be installed, calibrated, operated, and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual(s), with any modifications deemed necessary by the permittee. The permittee shall record the pressure drop across the baghouse on a daily basis while this emissions unit is in operation.
2. The permittee shall maintain records for any day during which the baghouse was not in service when the emissions unit was in operation and the corrective actions that were taken to resume operation of the control device.
3. The permit to install for this emissions unit P019 was evaluated based on the actual materials (typically coatings and cleanup materials) and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using

GE QI**PTI A****Modification Issued: 12/22/2005**Emissions Unit ID: **P019**

data from the permit to install application of SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant(s):

Modification Issued: 12/22/2005

Pollutant: Boron Oxide

TLV (mg/m³): 10.0

Maximum Hourly Emission Rate (lbs/hr): 3.96

Predicted 1-hour Maximum Ground-Level Concentration (µg/m³): 165.3

MAGLC (µg/m³): 238.1

4. Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:
 - a. changes in the composition of the materials used (typically for coatings or cleanup materials), or the use of new materials, that would result in the emissions of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)", than the lowest TLV value previously modeled;
 - b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and
 - c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).
5. If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01(VV)(1)(a)(ii), and a modification of the existing permit to install will not be required. If the change(s) is (are) defined as a modification under other provisions of the modification definition (other than (VV)(1)(a)(ii)), then the permittee shall obtain a final permit to install prior to the change.
6. The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emission unit will still satisfy the "Air Toxic Policy."

- a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
- b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and
- c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

D. Reporting Requirements

1. The permittee shall notify the Cleveland Division of Air Quality (Cleveland DAQ) in writing of any record showing that the baghouse was not in service when the emissions unit was in operation. The notification shall include a copy of such record and shall be sent to the Cleveland DAQ within 30 days after the event occurs.
2. The permittee shall submit quarterly pressure drop deviation (excursion) reports to the Cleveland DAQ that identify all periods of time during which the pressure drop across the baghouse did not comply with the allowable range specified above.

E. Testing Requirements

1. Compliance with the emission limitation(s) in Section A.1. of these terms and conditions shall be determined in accordance with the following method(s):
 - a. Emission Limitation -
10% opacity, as a 6-minute average

Applicable Compliance Method(s) -
Compliance shall be determined by visible emission evaluations performed in accordance with OAC rule 3745-17-03(B)(1) using methods and procedures specified in U.S. EPA Reference Method 9.
 - b. Emission Limitation -
7.91 lbs/batch PE emissions

Applicable Compliance Method(s) -
Compliance with the mass limitation shall be determined by using the following one time calculation for potential to emit:

GE QI

PTI A

Modification Issued: 12/22/2005

Emissions Unit ID: P019

$$[EF(\text{lbs PE}/\text{batch}) * (1 - CE)] = \text{particulate emissions (lbs}/\text{batch)}$$

where:

EF = 79.13 lbs PE/batch (use data from the most recent stack test performed on this emissions unit or any other similar emissions unit located at this facility)

CE = control efficiency

If required by Ohio EPA or Cleveland DAQ, compliance with the emission limitation shall be demonstrated through emission tests performed in accordance with 40 CFR Part 60, Appendix A, Methods 1 through 5 and the procedures specified in OAC rule 3745-17-03(B)(10). The results of the emissions test shall be reported in terms of pounds per batch.

- c. Emission Limitation -
0.85 ton/year PE emissions

Applicable Compliance Method(s) -

Compliance with the mass limitation shall be determined by using the following one time calculation for potential to emit:

$$[EF(\text{ lbs PE}/\text{batch}) * (\text{number of batches}/\text{year}) * (1 - CE) * (1 \text{ ton}/2000 \text{ lbs})] = \text{particulate emissions (ton}/\text{year)}$$

where:

EF = 79.13 lbs/batch (use data from the most recent stack test performed on this emissions unit or any other similar emissions unit located at this facility)

Number of batches = 214

CE = control efficiency

- d. Emission Limitation -
7.52 lbs/batch PM₁₀ emissions

Applicable Compliance Method(s) -

Compliance with the mass limitation shall be determined by using the following one time calculation for potential to emit:

$$[EF(\text{lbs PE}/\text{batch}) * (1 - CE)] = \text{PM}_{10} \text{ emissions (lbs}/\text{batch)}$$

where:

EF = 75.17 lbs PM₁₀/batch (use data from the most recent stack test performed on this emissions unit or any other similar emissions unit located at this facility)

CE = control efficiency

If required by Ohio EPA or Cleveland DAQ, compliance with the emission limitation shall be demonstrated through emission tests performed in accordance with 40 CFR Part 60, Appendix A, Methods 201 and 202. The results of the emissions test shall be reported in terms of pounds per batch.

- e. Emission Limitation -
 0.80 tons/year PM₁₀ emissions

Applicable Compliance Method(s) -
 Compliance with the mass limitation may be determined by using the following one time calculation for potential to emit:

$$[\text{EF}(\text{ lbs PM}_{10}/\text{batch}) * (\text{number of batches}/\text{year}) * (1-\text{CE}) * (1 \text{ ton}/2000 \text{ lbs})] = \text{PM}_{10} \text{ emissions (ton/year)}$$

where:

EF = 75.17 lbs PM₁₀/batch (use data from the most recent stack test performed on this emissions unit or any other similar emissions unit located at this facility)

Number of batches = 214

CE = Control efficiency

- f. Emission Limitation -
 26.65 lbs/batch CO emissions

Applicable Compliance Method(s) -
 The uncontrolled carbon monoxide emissions limitation was determined based on stack test results. The stack test was conducted on January 12-14, 2005.

If required by Ohio EPA or Cleveland DAQ, compliance shall be demonstrated by performing a stack test using U.S. EPA Methods 10 or 10b, as applicable. The results of the emissions test shall be reported in terms of pounds per batch.

- g. Emission Limitation -
 2.85 tons/year CO emissions

Applicable Compliance Method(s) -
 Compliance with the mass limitation may be determined by using the following one time calculation for potential to emit:

GE Q1**PTI A**Emissions Unit ID: **P019****Modification Issued: 12/22/2005**

$[\text{EF}(\text{ lbs CO/batch}) * (\text{number of batches/year}) * (1 \text{ ton}/2000 \text{ lbs})] = \text{carbon monoxide emissions (tons/year)}$

where:

EF = 26.65 lbs CO/batch (use data from the most recent stack test performed on this emissions unit or any other similar emissions unit located at this facility)

Number of batches = 214

F. Miscellaneous Requirements

None

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P020 - Cosmetic And Industrial Grade BN Powder Firing Line - H	OAC rule 3745-31-05(A)(3)	7.91 lbs/batch and 0.85 ton/year particulate emissions (PE)
		7.52 lbs/batch and 0.80 ton/year PM ₁₀
		26.65 lbs/batch and 2.85 tons/year carbon monoxide (CO) emissions
	OAC rule 3745-17-07(A)	Visible emissions serving this emissions unit shall not exceed 10% opacity, as a six minute average.
	OAC rule 3745-17-11(B)	See A.2.a, A.2.b, and B.1 below. The visible emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).
		The particulate emission limitation specified by this rule is less stringent than the particulate

18

GE Q

PTI A

Modification Issued: 12/22/2005

Emissions Unit ID: **P020**

emission limitation established
pursuant to OAC rule
3745-31-05(A)(3).

2. Additional Terms and Conditions

- 2.a** This emissions unit operates using a batch process. Since the batch operation takes longer than one day to complete (41 hours) and total PE for the batch are 7.91 pounds and total PM₁₀ emissions are 7.52 pounds, these emissions limitations are more stringent than the allowable limits from OAC rule 3745-17-11(B). The annual limitation was determined based on a maximum of 214 batches per year.
- 2.b** The short-term and annual emissions limitations were established based on potential to emit; therefore, no recordkeeping and/or reporting requirements are needed for these emissions limitations.

B. Operational Restrictions

1. The permittee shall operate the baghouse for control of particulate emissions while the emissions unit is in operation.
2. The pressure drop across the baghouse shall be maintained within the range of 0.5 to 7.0 inches of water while the emissions unit is in operation.

C. Monitoring and/or Recordkeeping Requirements

1. The permittee shall properly install, operate, and maintain equipment to monitor the pressure drop across the baghouse while the emissions unit is in operation. The monitoring equipment shall be installed, calibrated, operated, and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual(s), with any modifications deemed necessary by the permittee. The permittee shall record the pressure drop across the baghouse on a daily basis while this emissions unit is in operation.
2. The permittee shall maintain records for any day during which the baghouse was not in service when the emissions unit was in operation and the corrective actions that were taken to resume operation of the control device.
3. The permit to install for this emissions unit P020 was evaluated based on the actual materials (typically coatings and cleanup materials) and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using

GE Quartz, Inc.**PTI Application: 13-04510****Modif****Facility ID: 131855821****Emissions Unit ID: P020**

data from the permit to install application of SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant(s):

Modification Issued: 12/22/2005

Pollutant: Boron Oxide

TLV (mg/m³): 10.0

Maximum Hourly Emission Rate (lbs/hr): 3.96

Predicted 1-hour Maximum Ground-Level Concentration (µg/m³): 165.3

MAGLC (µg/m³): 238.1

4. Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:
 - a. changes in the composition of the materials used (typically for coatings or cleanup materials), or the use of new materials, that would result in the emissions of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)", than the lowest TLV value previously modeled;
 - b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and
 - c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).
5. If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01(VV)(1)(a)(ii), and a modification of the existing permit to install will not be required. If the change(s) is (are) defined as a modification under other provisions of the modification definition (other than (VV)(1)(a)(ii)), then the permittee shall obtain a final permit to install prior to the change.
6. The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emission unit will still satisfy the "Air Toxic Policy."

- a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
- b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and
- c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

D. Reporting Requirements

1. The permittee shall notify the Cleveland Division of Air Quality (Cleveland DAQ) in writing of any record showing that the baghouse was not in service when the emissions unit was in operation. The notification shall include a copy of such record and shall be sent to the Cleveland DAQ within 30 days after the event occurs.
2. The permittee shall submit quarterly pressure drop deviation (excursion) reports to the Cleveland DAQ that identify all periods of time during which the pressure drop across the baghouse did not comply with the allowable range specified above.

E. Testing Requirements

1. Compliance with the emission limitation(s) in Section A.1. of these terms and conditions shall be determined in accordance with the following method(s):
 - a. Emission Limitation -
10% opacity, as a 6-minute average

Applicable Compliance Method(s) -
Compliance shall be determined by visible emission evaluations performed in accordance with OAC rule 3745-17-03(B)(1) using methods and procedures specified in U.S. EPA Reference Method 9.
 - b. Emission Limitation -
7.91 lbs/batch PE emissions

Applicable Compliance Method(s) -
Compliance with the mass limitation shall be determined by using the following one time calculation for potential to emit:

GE Q1

PTI A

Modification Issued: 12/22/2005

Emissions Unit ID: P020

$$[EF(\text{lbs PE}/\text{batch}) * (1 - CE)] = \text{particulate emissions (lbs}/\text{batch)}$$

where:

EF = 79.13 lbs PE/batch (use data from the most recent stack test performed on this emissions unit or any other similar emissions unit located at this facility)

CE = control efficiency

If required by Ohio EPA or Cleveland DAQ, compliance with the emission limitation shall be demonstrated through emission tests performed in accordance with 40 CFR Part 60, Appendix A, Methods 1 through 5 and the procedures specified in OAC rule 3745-17-03(B)(10). The results of the emissions test shall be reported in terms of pounds per batch.

- c. Emission Limitation -
0.85 ton/year PE emissions

Applicable Compliance Method(s) -

Compliance with the mass limitation shall be determined by using the following one time calculation for potential to emit:

$$[EF(\text{ lbs PE}/\text{batch}) * (\text{number of batches}/\text{year}) * (1 - CE) * (1 \text{ ton}/2000 \text{ lbs})] = \text{particulate emissions (ton}/\text{year)}$$

where:

EF = 79.13 lbs/batch (use data from the most recent stack test performed on this emissions unit or any other similar emissions unit located at this facility)

Number of batches = 214

CE = control efficiency

- d. Emission Limitation -
7.52 lbs/batch PM₁₀ emissions

Applicable Compliance Method(s) -

Compliance with the mass limitation shall be determined by using the following one time calculation for potential to emit:

$$[EF(\text{lbs PE}/\text{batch}) * (1 - CE)] = \text{PM}_{10} \text{ emissions (lbs}/\text{batch)}$$

where:

EF = 75.17 lbs PM₁₀/batch (use data from the most recent stack test performed on this emissions unit or any other similar emissions unit located at this facility)

CE = control efficiency

GE QI

PTI A

Modification Issued: 12/22/2005

Emissions Unit ID: P020

If required by Ohio EPA or Cleveland DAQ, compliance with the emission limitation shall be demonstrated through emission tests performed in accordance with 40 CFR Part 60, Appendix A, Methods 201 and 202. The results of the emissions test shall be reported in terms of pounds per batch.

- e. Emission Limitation -
0.80 tons/year PM₁₀ emissions

Applicable Compliance Method(s) -

Compliance with the mass limitation may be determined by using the following one time calculation for potential to emit:

$$[\text{EF}(\text{ lbs PM}_{10}/\text{batch}) * (\text{number of batches}/\text{year}) * (1-\text{CE}) * (1 \text{ ton}/2000 \text{ lbs})] = \text{PM}_{10} \text{ emissions (ton/year)}$$

where:

EF = 75.17 lbs PM₁₀/batch (use data from the most recent stack test performed on this emissions unit or any other similar emissions unit located at this facility)

Number of batches = 214

CE = Control efficiency

- f. Emission Limitation -
26.65 lbs/batch CO emissions

Applicable Compliance Method(s) -

The uncontrolled carbon monoxide emissions limitation was determined based on stack test results. The stack test was conducted on January 12-14, 2005.

If required by Ohio EPA or Cleveland DAQ, compliance shall be demonstrated by performing a stack test using U.S. EPA Methods 10 or 10b, as applicable. The results of the emissions test shall be reported in terms of pounds per batch.

- g. Emission Limitation -
2.85 tons/year CO emissions

Applicable Compliance Method(s) -

Compliance with the mass limitation may be determined by using the following one time calculation for potential to emit:

GE Quartz, Inc.
PTI Application: 13-04510
Modif

Facility ID: 131855821

Emissions Unit ID: **P020**

$[\text{EF}(\text{ lbs CO/batch}) * (\text{number of batches/year}) * (1 \text{ ton}/2000 \text{ lbs})] = \text{carbon monoxide emissions (tons/year)}$

where:

EF = 26.65 lbs CO/batch (use data from the most recent stack test performed on this emissions unit or any other similar emissions unit located at this facility)

Number of batches = 214

F. Miscellaneous Requirements

None

GE QI

PTI A

Modification Issued: 12/22/2005

Emissions Unit ID: P021

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)**A. Applicable Emissions Limitations and/or Control Requirements**

- The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P021 - Cosmetic And Industrial Grade BN Powder Firing Line - I	OAC rule 3745-31-05(A)(3)	7.91 lbs/batch and 0.85 ton/year particulate emissions (PE)
		7.52 lbs/batch and 0.80 ton/year PM ₁₀
		26.65 lbs/batch and 2.85 tons/year carbon monoxide (CO) emissions
		Visible emissions serving this emissions unit shall not exceed 10% opacity, as a six minute average.
	OAC rule 3745-17-07(A)	See A.2.a, A.2.b, and B.1 below.
		The visible emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).
	OAC rule 3745-17-11(B)	The particulate emission limitation specified by this rule is less stringent than the particulate

27

GE Q1

PTI A

Modification Issued: 12/22/2005

Emissions Unit ID: **P021**

emission limitation established
pursuant to OAC rule
3745-31-05(A)(3).

2. Additional Terms and Conditions

- 2.a** This emissions unit operates using a batch process. Since the batch operation takes longer than one day to complete (41 hours) and total PE for the batch are 7.91 pounds and total PM₁₀ emissions are 7.52 pounds, these emissions limitations are more stringent than the allowable limits from OAC rule 3745-17-11(B). The annual limitation was determined based on a maximum of 214 batches per year.
- 2.b** The short-term and annual emissions limitations were established based on potential to emit; therefore, no recordkeeping and/or reporting requirements are needed for these emissions limitations.

B. Operational Restrictions

1. The permittee shall operate the baghouse for control of particulate emissions while the emissions unit is in operation.
2. The pressure drop across the baghouse shall be maintained within the range of 0.5 to 7.0 inches of water while the emissions unit is in operation.

C. Monitoring and/or Recordkeeping Requirements

1. The permittee shall properly install, operate, and maintain equipment to monitor the pressure drop across the baghouse while the emissions unit is in operation. The monitoring equipment shall be installed, calibrated, operated, and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual(s), with any modifications deemed necessary by the permittee. The permittee shall record the pressure drop across the baghouse on a daily basis while this emissions unit is in operation.
2. The permittee shall maintain records for any day during which the baghouse was not in service when the emissions unit was in operation and the corrective actions that were taken to resume operation of the control device.
3. The permit to install for this emissions unit P021 was evaluated based on the actual materials (typically coatings and cleanup materials) and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using

GE Quartz, Inc.

PTI Application: 13-04510

Modif

Facility ID: 131855821

Emissions Unit ID: P021

data from the permit to install application of SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant(s):

Modification Issued: 12/22/2005

Pollutant: Boron Oxide

TLV (mg/m³): 10.0

Maximum Hourly Emission Rate (lbs/hr): 3.96

Predicted 1-hour Maximum Ground-Level Concentration (µg/m³): 165.3

MAGLC (µg/m³): 238.1

4. Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:
 - a. changes in the composition of the materials used (typically for coatings or cleanup materials), or the use of new materials, that would result in the emissions of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)", than the lowest TLV value previously modeled;
 - b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and
 - c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).
5. If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01(VV)(1)(a)(ii), and a modification of the existing permit to install will not be required. If the change(s) is (are) defined as a modification under other provisions of the modification definition (other than (VV)(1)(a)(ii)), then the permittee shall obtain a final permit to install prior to the change.
6. The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emission unit will still satisfy the "Air Toxic Policy."

- a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
- b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and
- c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

D. Reporting Requirements

1. The permittee shall notify the Cleveland Division of Air Quality (Cleveland DAQ) in writing of any record showing that the baghouse was not in service when the emissions unit was in operation. The notification shall include a copy of such record and shall be sent to the Cleveland DAQ within 30 days after the event occurs.
2. The permittee shall submit quarterly pressure drop deviation (excursion) reports to the Cleveland DAQ that identify all periods of time during which the pressure drop across the baghouse did not comply with the allowable range specified above.

E. Testing Requirements

1. Compliance with the emission limitation(s) in Section A.1. of these terms and conditions shall be determined in accordance with the following method(s):
 - a. Emission Limitation -
10% opacity, as a 6-minute average

Applicable Compliance Method(s) -
Compliance shall be determined by visible emission evaluations performed in accordance with OAC rule 3745-17-03(B)(1) using methods and procedures specified in U.S. EPA Reference Method 9.
 - b. Emission Limitation -
7.91 lbs/batch PE emissions

Applicable Compliance Method(s) -
Compliance with the mass limitation shall be determined by using the following

one time calculation for potential to emit:
 $[EF(\text{lbs PE/batch}) * (1 - CE)] = \text{particulate emissions (lbs/batch)}$

where:

EF = 79.13 lbs PE/batch (use data from the most recent stack test performed on this emissions unit or any other similar emissions unit located at this facility)

CE = control efficiency

If required by Ohio EPA or Cleveland DAQ, compliance with the emission limitation shall be demonstrated through emission tests performed in accordance with 40 CFR Part 60, Appendix A, Methods 1 through 5 and the procedures specified in OAC rule 3745-17-03(B)(10). The results of the emissions test shall be reported in terms of pounds per batch.

- c. Emission Limitation -
 0.85 ton/year PE emissions

Applicable Compliance Method(s) -

Compliance with the mass limitation shall be determined by using the following one time calculation for potential to emit:

$[EF(\text{ lbs PE/batch}) * (\text{number of batches/year}) * (1 - CE) * (1 \text{ ton}/2000 \text{ lbs})] = \text{particulate emissions (ton/year)}$

where:

EF = 79.13 lbs/batch (use data from the most recent stack test performed on this emissions unit or any other similar emissions unit located at this facility)

Number of batches = 214

CE = control efficiency

- d. Emission Limitation -
 7.52 lbs/batch PM₁₀ emissions

Applicable Compliance Method(s) -

Compliance with the mass limitation shall be determined by using the following one time calculation for potential to emit:

$[EF(\text{lbs PE/batch}) * (1 - CE)] = \text{PM}_{10} \text{ emissions (lbs/batch)}$

where:

EF = 75.17 lbs PM₁₀/batch (use data from the most recent stack test performed on this emissions unit or any other similar emissions unit located at this facility)

CE = control efficiency

GE Q1

PTI A

Modification Issued: 12/22/2005

Emissions Unit ID: P021

If required by Ohio EPA or Cleveland DAQ, compliance with the emission limitation shall be demonstrated through emission tests performed in accordance with 40 CFR Part 60, Appendix A, Methods 201 and 202. The results of the emissions test shall be reported in terms of pounds per batch.

- e. Emission Limitation -
0.80 tons/year PM₁₀ emissions

Applicable Compliance Method(s) -

Compliance with the mass limitation may be determined by using the following one time calculation for potential to emit:

$$[\text{EF(lbs PM}_{10}\text{/batch)} * (\text{number of batches/year}) * (1-\text{CE}) * (1 \text{ ton}/2000 \text{ lbs})] = \text{PM}_{10} \text{ emissions (ton/year)}$$

where:

EF = 75.17 lbs PM₁₀/batch (use data from the most recent stack test performed on this emissions unit or any other similar emissions unit located at this facility)

Number of batches = 214

CE = Control efficiency

- f. Emission Limitation -
26.65 lbs/batch CO emissions

Applicable Compliance Method(s) -

The uncontrolled carbon monoxide emissions limitation was determined based on stack test results. The stack test was conducted on January 12-14, 2005.

If required by Ohio EPA or Cleveland DAQ, compliance shall be demonstrated by performing a stack test using U.S. EPA Methods 10 or 10b, as applicable. The results of the emissions test shall be reported in terms of pounds per batch.

- g. Emission Limitation -
2.85 tons/year CO emissions

Applicable Compliance Method(s) -

Compliance with the mass limitation may be determined by using the following one time calculation for potential to emit:

GE Q1**PTI A**Emissions Unit ID: **P021****Modification Issued: 12/22/2005**

$[\text{EF}(\text{ lbs CO/batch}) * (\text{number of batches/year}) * (1 \text{ ton}/2000 \text{ lbs})] = \text{carbon monoxide emissions (tons/year)}$

where:

EF = 26.65 lbs CO/batch (use data from the most recent stack test performed on this emissions unit or any other similar emissions unit located at this facility)

Number of batches = 214

F. Miscellaneous Requirements

None

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

- The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P022 - Cosmetic And Industrial Grade BN Powder Firing Line - J	OAC rule 3745-31-05(A)(3)	7.91 lbs/batch and 0.85 ton/year particulate emissions (PE) 7.52 lbs/batch and 0.80 ton/year PM ₁₀ 26.65 lbs/batch and 2.85 tons/year carbon monoxide (CO) emissions Visible emissions serving this emissions unit shall not exceed 10% opacity, as a six minute average.
	OAC rule 3745-17-07(A)	See A.2.a, A.2.b, and B.1 below. The visible emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).
	OAC rule 3745-17-11(B)	The particulate emission limitation specified by this rule is less stringent than the particulate emission limitation established

36

GE Q

PTI A

Modification Issued: 12/22/2005

Emissions Unit ID: **P022**

pursuant to OAC rule
3745-31-05(A)(3).

2. Additional Terms and Conditions

- 2.a** This emissions unit operates using a batch process. Since the batch operation takes longer than one day to complete (41 hours) and total PE for the batch are 7.91 pounds and total PM₁₀ emissions are 7.52 pounds, these emissions limitations are more stringent than the allowable limits from OAC rule 3745-17-11(B). The annual limitation was determined based on a maximum of 214 batches per year.
- 2.b** The short-term and annual emissions limitations were established based on potential to emit; therefore, no recordkeeping and/or reporting requirements are needed for these emissions limitations.

B. Operational Restrictions

1. The permittee shall operate the baghouse for control of particulate emissions while the emissions unit is in operation.
2. The pressure drop across the baghouse shall be maintained within the range of 0.5 to 7.0 inches of water while the emissions unit is in operation.

C. Monitoring and/or Recordkeeping Requirements

1. The permittee shall properly install, operate, and maintain equipment to monitor the pressure drop across the baghouse while the emissions unit is in operation. The monitoring equipment shall be installed, calibrated, operated, and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual(s), with any modifications deemed necessary by the permittee. The permittee shall record the pressure drop across the baghouse on a daily basis while this emissions unit is in operation.
2. The permittee shall maintain records for any day during which the baghouse was not in service when the emissions unit was in operation and the corrective actions that were taken to resume operation of the control device.
3. The permit to install for this emissions unit P022 was evaluated based on the actual materials (typically coatings and cleanup materials) and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using

GE QI**PTI A****Modification Issued: 12/22/2005**Emissions Unit ID: **P022**

data from the permit to install application of SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant(s):

GE Quartz, Inc.
PTI Application: 12-04510
Modif

Facility ID: 131855821

Emissions Unit ID: P022

Pollutant: Boron Oxide

TLV (mg/m³): 10.0

Maximum Hourly Emission Rate (lbs/hr): 3.96

Predicted 1-hour Maximum Ground-Level Concentration (µg/m³): 165.3

MAGLC (µg/m³): 238.1

4. Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:
 - a. changes in the composition of the materials used (typically for coatings or cleanup materials), or the use of new materials, that would result in the emissions of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)", than the lowest TLV value previously modeled;
 - b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and
 - c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).
5. If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01(VV)(1)(a)(ii), and a modification of the existing permit to install will not be required. If the change(s) is (are) defined as a modification under other provisions of the modification definition (other than (VV)(1)(a)(ii)), then the permittee shall obtain a final permit to install prior to the change.
6. The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emission unit will still satisfy the "Air Toxic Policy."

Modification Issued: 12/22/2005

- a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
- b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and
- c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

D. Reporting Requirements

1. The permittee shall notify the Cleveland Division of Air Quality (Cleveland DAQ) in writing of any record showing that the baghouse was not in service when the emissions unit was in operation. The notification shall include a copy of such record and shall be sent to the Cleveland DAQ within 30 days after the event occurs.
2. The permittee shall submit quarterly pressure drop deviation (excursion) reports to the Cleveland DAQ that identify all periods of time during which the pressure drop across the baghouse did not comply with the allowable range specified above.

E. Testing Requirements

1. Compliance with the emission limitation(s) in Section A.1. of these terms and conditions shall be determined in accordance with the following method(s):
 - a. Emission Limitation -
10% opacity, as a 6-minute average

Applicable Compliance Method(s) -
Compliance shall be determined by visible emission evaluations performed in accordance with OAC rule 3745-17-03(B)(1) using methods and procedures specified in U.S. EPA Reference Method 9.
 - b. Emission Limitation -
7.91 lbs/batch PE emissions

Applicable Compliance Method(s) -
Compliance with the mass limitation shall be determined by using the following one time calculation for potential to emit:

$$[EF(\text{lbs PE}/\text{batch}) * (1 - CE)] = \text{particulate emissions (lbs}/\text{batch)}$$

where:

EF = 79.13 lbs PE/batch (use data from the most recent stack test performed on this emissions unit or any other similar emissions unit located at this facility)

CE = control efficiency

If required by Ohio EPA or Cleveland DAQ, compliance with the emission limitation shall be demonstrated through emission tests performed in accordance with 40 CFR Part 60, Appendix A, Methods 1 through 5 and the procedures specified in OAC rule 3745-17-03(B)(10). The results of the emissions test shall be reported in terms of pounds per batch.

- c. Emission Limitation -
0.85 ton/year PE emissions

Applicable Compliance Method(s) -

Compliance with the mass limitation shall be determined by using the following one time calculation for potential to emit:

$$[EF(\text{ lbs PE}/\text{batch}) * (\text{number of batches}/\text{year}) * (1 - CE) * (1 \text{ ton}/2000 \text{ lbs})] = \text{particulate emissions (ton}/\text{year)}$$

where:

EF = 79.13 lbs/batch (use data from the most recent stack test performed on this emissions unit or any other similar emissions unit located at this facility)

Number of batches = 214

CE = control efficiency

- d. Emission Limitation -
7.52 lbs/batch PM₁₀ emissions

Applicable Compliance Method(s) -

Compliance with the mass limitation shall be determined by using the following one time calculation for potential to emit:

$$[EF(\text{lbs PE}/\text{batch}) * (1 - CE)] = \text{PM}_{10} \text{ emissions (lbs}/\text{batch)}$$

where:

EF = 75.17 lbs PM₁₀/batch (use data from the most recent stack test performed on this emissions unit or any other similar emissions unit located at this facility)

CE = control efficiency

If required by Ohio EPA or Cleveland DAQ, compliance with the emission limitation shall be demonstrated through emission tests performed in accordance with 40 CFR Part 60, Appendix A, Methods 201 and 202. The results of the emissions test shall be reported in terms of pounds per batch.

- e. Emission Limitation -
 0.80 tons/year PM₁₀ emissions

Applicable Compliance Method(s) -
 Compliance with the mass limitation may be determined by using the following one time calculation for potential to emit:

$$[EF(\text{ lbs PM}_{10}/\text{batch}) * (\text{number of batches/year}) * (1-CE) * (1 \text{ ton}/2000 \text{ lbs})] = \text{PM}_{10} \text{ emissions (ton/year)}$$

where:

EF = 75.17 lbs PM₁₀/batch (use data from the most recent stack test performed on this emissions unit or any other similar emissions unit located at this facility)

Number of batches = 214

CE = Control efficiency

- f. Emission Limitation -
 26.65 lbs/batch CO emissions

Applicable Compliance Method(s) -
 The uncontrolled carbon monoxide emissions limitation was determined based on stack test results. The stack test was conducted on January 12-14, 2005.

If required by Ohio EPA or Cleveland DAQ, compliance shall be demonstrated by performing a stack test using U.S. EPA Methods 10 or 10b, as applicable. The results of the emissions test shall be reported in terms of pounds per batch.

- g. Emission Limitation -
 2.85 tons/year CO emissions

Applicable Compliance Method(s) -
 Compliance with the mass limitation may be determined by using the following one time calculation for potential to emit:

$$[EF(\text{ lbs CO}/\text{batch}) * (\text{number of batches/year}) * (1 \text{ ton}/2000 \text{ lbs})] = \text{carbon}$$

GE Q1

PTI A

Modification Issued: 12/22/2005

Emissions Unit ID: **P022**

monoxide emissions (tons/year)

where:

EF = 26.65 lbs CO/batch (use data from the most recent stack test performed on this emissions unit or any other similar emissions unit located at this facility)

Number of batches = 214

F. Miscellaneous Requirements

None

GE QI

PTI A

Modification Issued: 12/22/2005

Emissions Unit ID: P023

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)**A. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P023 - Cosmetic And Industrial Grade BN Powder Firing Line - K	OAC rule 3745-31-05(A)(3)	7.91 lbs/batch and 0.85 ton/year particulate emissions (PE)
		7.52 lbs/batch and 0.80 ton/year PM ₁₀ 26.65 lbs/batch and 2.85 tons/year carbon monoxide (CO) emissions
		Visible emissions serving this emissions unit shall not exceed 10% opacity, as a six minute average.
	OAC rule 3745-17-07(A)	See A.2.a, A.2.b, and B.1 below.
	OAC rule 3745-17-11(B)	The visible emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).
		The particulate emission limitation specified by this rule is less stringent than the particulate

GE Quartz, Inc.

PTI Application: 13-04510

Modif

Facility ID: 131855821

Emissions Unit ID: P023

emission limitation established
pursuant to OAC rule
3745-31-05(A)(3).

2. Additional Terms and Conditions

- 2.a** This emissions unit operates using a batch process. Since the batch operation takes longer than one day to complete (41 hours) and total PE for the batch are 7.91 pounds and total PM₁₀ emissions are 7.52 pounds, these emissions limitations are more stringent than the allowable limits from OAC rule 3745-17-11(B). The annual limitation was determined based on a maximum of 214 batches per year.
- 2.b** The short-term and annual emissions limitations were established based on potential to emit; therefore, no recordkeeping and/or reporting requirements are needed for these emissions limitations.

B. Operational Restrictions

1. The permittee shall operate the baghouse for control of particulate emissions while the emissions unit is in operation.
2. The pressure drop across the baghouse shall be maintained within the range of 0.5 to 7.0 inches of water while the emissions unit is in operation.

C. Monitoring and/or Recordkeeping Requirements

1. The permittee shall properly install, operate, and maintain equipment to monitor the pressure drop across the baghouse while the emissions unit is in operation. The monitoring equipment shall be installed, calibrated, operated, and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual(s), with any modifications deemed necessary by the permittee. The permittee shall record the pressure drop across the baghouse on a daily basis while this emissions unit is in operation.
2. The permittee shall maintain records for any day during which the baghouse was not in service when the emissions unit was in operation and the corrective actions that were taken to resume operation of the control device.
3. The permit to install for this emissions unit P023 was evaluated based on the actual materials (typically coatings and cleanup materials) and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using

GE QI**PTI A****Modification Issued: 12/22/2005**Emissions Unit ID: **P023**

data from the permit to install application of SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant(s):

Modification Issued: 12/22/2005

Pollutant: Boron Oxide

TLV (mg/m³): 10.0

Maximum Hourly Emission Rate (lbs/hr): 3.96

Predicted 1-hour Maximum Ground-Level Concentration (µg/m³): 165.3

MAGLC (µg/m³): 238.1

4. Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:
 - a. changes in the composition of the materials used (typically for coatings or cleanup materials), or the use of new materials, that would result in the emissions of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)", than the lowest TLV value previously modeled;
 - b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and
 - c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).
5. If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01(VV)(1)(a)(ii), and a modification of the existing permit to install will not be required. If the change(s) is (are) defined as a modification under other provisions of the modification definition (other than (VV)(1)(a)(ii)), then the permittee shall obtain a final permit to install prior to the change.
6. The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emission unit will still satisfy the "Air Toxic Policy."

- a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
- b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and
- c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

D. Reporting Requirements

1. The permittee shall notify the Cleveland Division of Air Quality (Cleveland DAQ) in writing of any record showing that the baghouse was not in service when the emissions unit was in operation. The notification shall include a copy of such record and shall be sent to the Cleveland DAQ within 30 days after the event occurs.
2. The permittee shall submit quarterly pressure drop deviation (excursion) reports to the Cleveland DAQ that identify all periods of time during which the pressure drop across the baghouse did not comply with the allowable range specified above.

E. Testing Requirements

1. Compliance with the emission limitation(s) in Section A.1. of these terms and conditions shall be determined in accordance with the following method(s):
 - a. Emission Limitation -
10% opacity, as a 6-minute average

Applicable Compliance Method(s) -
Compliance shall be determined by visible emission evaluations performed in accordance with OAC rule 3745-17-03(B)(1) using methods and procedures specified in U.S. EPA Reference Method 9.
 - b. Emission Limitation -
7.91 lbs/batch PE emissions

Applicable Compliance Method(s) -
Compliance with the mass limitation shall be determined by using the following one time calculation for potential to emit:

GE Q1

PTI A

Modification Issued: 12/22/2005

Emissions Unit ID: P023

$$[EF(\text{lbs PE}/\text{batch}) * (1 - CE)] = \text{particulate emissions (lbs/batch)}$$

where:

EF = 79.13 lbs PE/batch (use data from the most recent stack test performed on this emissions unit or any other similar emissions unit located at this facility)

CE = control efficiency

If required by Ohio EPA or Cleveland DAQ, compliance with the emission limitation shall be demonstrated through emission tests performed in accordance with 40 CFR Part 60, Appendix A, Methods 1 through 5 and the procedures specified in OAC rule 3745-17-03(B)(10). The results of the emissions test shall be reported in terms of pounds per batch.

- c. Emission Limitation -
0.85 ton/year PE emissions

Applicable Compliance Method(s) -

Compliance with the mass limitation shall be determined by using the following one time calculation for potential to emit:

$$[EF(\text{ lbs PE}/\text{batch}) * (\text{number of batches}/\text{year}) * (1 - CE) * (1 \text{ ton}/2000 \text{ lbs})] = \text{particulate emissions (ton/year)}$$

where:

EF = 79.13 lbs/batch (use data from the most recent stack test performed on this emissions unit or any other similar emissions unit located at this facility)

Number of batches = 214

CE = control efficiency

- d. Emission Limitation -
7.52 lbs/batch PM₁₀ emissions

Applicable Compliance Method(s) -

Compliance with the mass limitation shall be determined by using the following one time calculation for potential to emit:

$$[EF(\text{lbs PE}/\text{batch}) * (1 - CE)] = \text{PM}_{10} \text{ emissions (lbs/batch)}$$

where:

EF = 75.17 lbs PM₁₀/batch (use data from the most recent stack test performed on this emissions unit or any other similar emissions unit located at this facility)

CE = control efficiency

If required by Ohio EPA or Cleveland DAQ, compliance with the emission limitation shall be demonstrated through emission tests performed in accordance with 40 CFR Part 60, Appendix A, Methods 201 and 202. The results of the emissions test shall be reported in terms of pounds per batch.

- e. Emission Limitation -
 0.80 tons/year PM₁₀ emissions

Applicable Compliance Method(s) -
 Compliance with the mass limitation may be determined by using the following one time calculation for potential to emit:

$$[\text{EF(lbs PM}_{10}\text{/batch)} * (\text{number of batches/year}) * (1-\text{CE}) * (1 \text{ ton}/2000 \text{ lbs})] = \text{PM}_{10} \text{ emissions (ton/year)}$$

where:

EF = 75.17 lbs PM₁₀/batch (use data from the most recent stack test performed on this emissions unit or any other similar emissions unit located at this facility)

Number of batches = 214

CE = Control efficiency

- f. Emission Limitation -
 26.65 lbs/batch CO emissions

Applicable Compliance Method(s) -
 The uncontrolled carbon monoxide emissions limitation was determined based on stack test results. The stack test was conducted on January 12-14, 2005.

If required by Ohio EPA or Cleveland DAQ, compliance shall be demonstrated by performing a stack test using U.S. EPA Methods 10 or 10b, as applicable.

- g. Emission Limitation -
 2.85 tons/year CO emissions

Applicable Compliance Method(s) -
 Compliance with the mass limitation may be determined by using the following one time calculation for potential to emit:

$$[\text{EF(lbs CO/batch)} * (\text{number of batches/year}) * (1 \text{ ton}/2000 \text{ lbs})] = \text{carbon monoxide emissions (tons/year)}$$

GE Q1

PTI A

Modification Issued: 12/22/2005

Emissions Unit ID: **P023**

where:

EF = 26.65 lbs CO/batch (use data from the most recent stack test performed on this emissions unit or any other similar emissions unit located at this facility)

Number of batches = 214

F. Miscellaneous Requirements

None

GE QI

PTI A

Modification Issued: 12/22/2005

Emissions Unit ID: P024

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)**A. Applicable Emissions Limitations and/or Control Requirements**

- The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P024 - Cosmetic And Industrial Grade BN Powder Firing Line - L	OAC rule 3745-31-05(A)(3)	7.91 lbs/batch and 0.85 ton/year particulate emissions (PE) 7.52 lbs/batch and 0.80 ton/year PM ₁₀ 26.65 lbs/batch and 2.85 tons/year carbon monoxide (CO) emissions Visible emissions serving this emissions unit shall not exceed 10% opacity, as a six minute average.
	OAC rule 3745-17-07(A)	See A.2.a, A.2.b, and B.1 below. The visible emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).
	OAC rule 3745-17-11(B)	The particulate emission limitation specified by this rule is less stringent than the particulate emission limitation established pursuant to OAC rule

3745-31-05(A)(3).

2. Additional Terms and Conditions

- 2.a** This emissions unit operates using a batch process. Since the batch operation takes longer than one day to complete (41 hours) and total PE for the batch are 7.91 pounds and total PM₁₀ emissions are 7.52 pounds, these emissions limitations are more stringent than the allowable limits from OAC rule 3745-17-11(B). The annual limitation was determined based on a maximum of 214 batches per year.
- 2.b** The short-term and annual emissions limitations were established based on potential to emit; therefore, no recordkeeping and/or reporting requirements are needed for these emissions limitations.

B. Operational Restrictions

1. The permittee shall operate the baghouse for control of particulate emissions while the emissions unit is in operation.
2. The pressure drop across the baghouse shall be maintained within the range of 0.5 to 7.0 inches of water while the emissions unit is in operation.

C. Monitoring and/or Recordkeeping Requirements

1. The permittee shall properly install, operate, and maintain equipment to monitor the pressure drop across the baghouse while the emissions unit is in operation. The monitoring equipment shall be installed, calibrated, operated, and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual(s), with any modifications deemed necessary by the permittee. The permittee shall record the pressure drop across the baghouse on a daily basis while this emissions unit is in operation.
2. The permittee shall maintain records for any day during which the baghouse was not in service when the emissions unit was in operation and the corrective actions that were taken to resume operation of the control device.
3. The permit to install for this emissions unit P024 was evaluated based on the actual materials (typically coatings and cleanup materials) and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install

Emissions Unit ID: P024

application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application of SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant(s):

Pollutant: Boron Oxide

TLV (mg/m³): 10.0

Maximum Hourly Emission Rate (lbs/hr): 3.96

Predicted 1-hour Maximum Ground-Level Concentration (µg/m³): 165.3MAGLC (µg/m³): 238.1

4. Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:
 - a. changes in the composition of the materials used (typically for coatings or cleanup materials), or the use of new materials, that would result in the emissions of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)", than the lowest TLV value previously modeled;
 - b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and
 - c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).
5. If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01(VV)(1)(a)(ii), and a modification of the existing permit to install

Modification Issued: 12/22/2005

will not be required. If the changes(s) is (are) defined as a modification under other provisions of the modification definition (other than (VV)(1)(a)(ii)), then the permittee shall obtain a final permit to install prior to the change.

6. The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emission unit will still satisfy the "Air Toxic Policy."
 - a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
 - b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and
 - c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

D. Reporting Requirements

1. The permittee shall notify the Cleveland Division of Air Quality (Cleveland DAQ) in writing of any record showing that the baghouse was not in service when the emissions unit was in operation. The notification shall include a copy of such record and shall be sent to the Cleveland DAQ within 30 days after the event occurs.
2. The permittee shall submit quarterly pressure drop deviation (excursion) reports to the Cleveland DAQ that identify all periods of time during which the pressure drop across the baghouse did not comply with the allowable range specified above.

E. Testing Requirements

1. Compliance with the emission limitation(s) in Section A.1. of these terms and conditions shall be determined in accordance with the following method(s):
 - a. Emission Limitation -
10% opacity, as a 6-minute average

Applicable Compliance Method(s) -
Compliance shall be determined by visible emission evaluations performed in accordance with OAC rule 3745-17-03(B)(1) using methods and procedures

specified in U.S. EPA Reference Method 9.

- b. Emission Limitation -
 7.91 lbs/batch PE emissions

Applicable Compliance Method(s) -

Compliance with the mass limitation shall be determined by using the following one time calculation for potential to emit:

$$[EF(\text{lbs PE/batch}) * (1 - CE)] = \text{particulate emissions (lbs/batch)}$$

where:

EF = 79.13 lbs PE/batch (use data from the most recent stack test performed on this emissions unit or any other similar emissions unit located at this facility)

CE = control efficiency

If required by Ohio EPA or Cleveland DAQ, compliance with the emission limitation shall be demonstrated through emission tests performed in accordance with 40 CFR Part 60, Appendix A, Methods 1 through 5 and the procedures specified in OAC rule 3745-17-03(B)(10). The results of the emissions test shall be reported in terms of pounds per batch.

- c. Emission Limitation -
 0.85 ton/year PE emissions

Applicable Compliance Method(s) -

Compliance with the mass limitation shall be determined by using the following one time calculation for potential to emit:

$$[EF(\text{ lbs PE/batch}) * (\text{number of batches/year}) * (1 - CE) * (1 \text{ ton}/2000 \text{ lbs})] = \text{particulate emissions (ton/year)}$$

where:

EF = 79.13 lbs/batch (use data from the most recent stack test performed on this emissions unit or any other similar emissions unit located at this facility)

Number of batches = 214

CE = control efficiency

- d. Emission Limitation -
 7.52 lbs/batch PM₁₀ emissions

Applicable Compliance Method(s) -

Compliance with the mass limitation shall be determined by using the following

GE Q1

PTI A

Modification Issued: 12/22/2005

Emissions Unit ID: P024

one time calculation for potential to emit:

$$[EF(\text{lbs PE}/\text{batch}) * (1 - CE)] = \text{PM}_{10} \text{ emissions (lbs}/\text{batch)}$$

where:

EF = 75.17 lbs PM₁₀/batch (use data from the most recent stack test performed on this emissions unit or any other similar emissions unit located at this facility)

CE = control efficiency

If required by Ohio EPA or Cleveland DAQ, compliance with the emission limitation shall be demonstrated through emission tests performed in accordance with 40 CFR Part 60, Appendix A, Methods 201 and 202. The results of the emissions test shall be reported in terms of pounds per batch.

- e. Emission Limitation -
0.80 tons/year PM₁₀ emissions

Applicable Compliance Method(s) -

Compliance with the mass limitation may be determined by using the following one time calculation for potential to emit:

$$[EF(\text{ lbs PM}_{10}/\text{batch}) * (\text{number of batches}/\text{year}) * (1-CE) * (1 \text{ ton}/2000 \text{ lbs})] = \text{PM}_{10} \text{ emissions (ton}/\text{year)}$$

where:

EF = 75.17 lbs PM₁₀/batch (use data from the most recent stack test performed on this emissions unit or any other similar emissions unit located at this facility)

Number of batches = 214

CE = Control efficiency

- f. Emission Limitation -
26.65 lbs/batch CO emissions

Applicable Compliance Method(s) -

The uncontrolled carbon monoxide emissions limitation was determined based on stack test results. The stack test was conducted on January 12-14, 2005.

If required by Ohio EPA or Cleveland DAQ, compliance shall be demonstrated by performing a stack test using U.S. EPA Methods 10 or 10b, as applicable. The results of the emissions test shall be reported in terms of pounds per batch.

GE Quartz, Inc.
PTI Application: 12-04510
Modif

Facility ID: 131855821

Emissions Unit ID: P024

- g. Emission Limitation -
2.85 tons/year CO emissions

Applicable Compliance Method(s) -
Compliance with the mass limitation may be determined by using the following one time calculation for potential to emit:

$[EF(\text{ lbs CO/batch}) * (\text{number of batches/year}) * (1 \text{ ton}/2000 \text{ lbs})] = \text{carbon monoxide emissions (tons/year)}$

where:

EF = 26.65 lbs CO/batch (use data from the most recent stack test performed on this emissions unit or any other similar emissions unit located at this facility)

Number of batches = 214

F. Miscellaneous Requirements

None

GE QI

PTI A

Modification Issued: 12/22/2005

Emissions Unit ID: P025

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)**A. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P025 - Cosmetic And Industrial Grade BN Powder Firing Line - M	OAC rule 3745-31-05(A)(3)	7.91 lbs/batch and 0.85 ton/year particulate emissions (PE)
		7.52 lbs/batch and 0.80 ton/year PM ₁₀
		26.65 lbs/batch and 2.85 tons/year carbon monoxide (CO) emissions
		Visible emissions serving this emissions unit shall not exceed 10% opacity, as a six minute average.
	OAC rule 3745-17-07(A)	See A.2.a, A.2.b, and B.1 below.
	OAC rule 3745-17-11(B)	The visible emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).
		The particulate emission limitation specified by this rule is less stringent than the particulate emission limitation established

61

GE Q

PTI A

Modification Issued: 12/22/2005

Emissions Unit ID: **P025**

pursuant to OAC rule
3745-31-05(A)(3).

2. Additional Terms and Conditions

- 2.a** This emissions unit operates using a batch process. Since the batch operation takes longer than one day to complete (41 hours) and total PE for the batch are 7.91 pounds and total PM₁₀ emissions are 7.52 pounds, these emissions limitations are more stringent than the allowable limits from OAC rule 3745-17-11(B). The annual limitation was determined based on a maximum of 214 batches per year.
- 2.b** The short-term and annual emissions limitations were established based on potential to emit; therefore, no recordkeeping and/or reporting requirements are needed for these emissions limitations.

B. Operational Restrictions

1. The permittee shall operate the baghouse for control of particulate emissions while the emissions unit is in operation.
2. The pressure drop across the baghouse shall be maintained within the range of 0.5 to 7.0 inches of water while the emissions unit is in operation.

C. Monitoring and/or Recordkeeping Requirements

1. The permittee shall properly install, operate, and maintain equipment to monitor the pressure drop across the baghouse while the emissions unit is in operation. The monitoring equipment shall be installed, calibrated, operated, and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual(s), with any modifications deemed necessary by the permittee. The permittee shall record the pressure drop across the baghouse on a daily basis while this emissions unit is in operation.
2. The permittee shall maintain records for any day during which the baghouse was not in service when the emissions unit was in operation and the corrective actions that were taken to resume operation of the control device.
3. The permit to install for this emissions unit P025 was evaluated based on the actual materials (typically coatings and cleanup materials) and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using

GE Quartz, Inc.

PTI Application: 13-04510

Modif

Facility ID: 131855821

Emissions Unit ID: P025

data from the permit to install application of SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant(s):

Modification Issued: 12/22/2005

Pollutant: Boron Oxide

TLV (mg/m³): 10.0

Maximum Hourly Emission Rate (lbs/hr): 3.96

Predicted 1-hour Maximum Ground-Level Concentration (µg/m³): 165.3

MAGLC (µg/m³): 238.1

4. Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:
 - a. changes in the composition of the materials used (typically for coatings or cleanup materials), or the use of new materials, that would result in the emissions of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)", than the lowest TLV value previously modeled;
 - b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and
 - c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).
5. If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01(VV)(1)(a)(ii), and a modification of the existing permit to install will not be required. If the change(s) is (are) defined as a modification under other provisions of the modification definition (other than (VV)(1)(a)(ii)), then the permittee shall obtain a final permit to install prior to the change.
6. The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emission unit will still satisfy the "Air Toxic Policy."

Modification Issued: 12/22/2005

- a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
- b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and
- c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

D. Reporting Requirements

1. The permittee shall notify the Cleveland Division of Air Quality (Cleveland DAQ) in writing of any record showing that the baghouse was not in service when the emissions unit was in operation. The notification shall include a copy of such record and shall be sent to the Cleveland DAQ within 30 days after the event occurs.
2. The permittee shall submit quarterly pressure drop deviation (excursion) reports to the Cleveland DAQ that identify all periods of time during which the pressure drop across the baghouse did not comply with the allowable range specified above.

E. Testing Requirements

1. Compliance with the emission limitation(s) in Section A.1. of these terms and conditions shall be determined in accordance with the following method(s):
 - a. Emission Limitation -
10% opacity, as a 6-minute average

Applicable Compliance Method(s) -
Compliance shall be determined by visible emission evaluations performed in accordance with OAC rule 3745-17-03(B)(1) using methods and procedures specified in U.S. EPA Reference Method 9.
 - b. Emission Limitation -
7.91 lbs/batch PE emissions

Applicable Compliance Method(s) -
Compliance with the mass limitation shall be determined by using the following

one time calculation for potential to emit:
 $[EF(\text{lbs PE/batch}) * (1 - CE)] = \text{particulate emissions (lbs/batch)}$

where:

EF = 79.13 lbs PE/batch (use data from the most recent stack test performed on this emissions unit or any other similar emissions unit located at this facility)

CE = control efficiency

If required by Ohio EPA or Cleveland DAQ, compliance with the emission limitation shall be demonstrated through emission tests performed in accordance with 40 CFR Part 60, Appendix A, Methods 1 through 5 and the procedures specified in OAC rule 3745-17-03(B)(10). The results of the emissions test shall be reported in terms of pounds per batch.

- c. Emission Limitation -
 0.85 ton/year PE emissions

Applicable Compliance Method(s) -

Compliance with the mass limitation shall be determined by using the following one time calculation for potential to emit:

$[EF(\text{ lbs PE/batch}) * (\text{number of batches/year}) * (1 - CE) * (1 \text{ ton}/2000 \text{ lbs})] = \text{particulate emissions (ton/year)}$

where:

EF = 79.13 lbs/batch (use data from the most recent stack test performed on this emissions unit or any other similar emissions unit located at this facility)

Number of batches = 214

CE = control efficiency

- d. Emission Limitation -
 7.52 lbs/batch PM₁₀ emissions

Applicable Compliance Method(s) -

Compliance with the mass limitation shall be determined by using the following one time calculation for potential to emit:

$[EF(\text{lbs PE/batch}) * (1 - CE)] = \text{PM}_{10} \text{ emissions (lbs/batch)}$

where:

EF = 75.17 lbs PM₁₀/batch (use data from the most recent stack test performed on this emissions unit or any other similar emissions unit located at this facility)

CE = control efficiency

If required by Ohio EPA or Cleveland DAQ, compliance with the emission limitation shall be demonstrated through emission tests performed in accordance with 40 CFR Part 60, Appendix A, Methods 201 and 202. The results of the emissions test shall be reported in terms of pounds per batch.

- e. Emission Limitation -
0.80 tons/year PM₁₀ emissions

Applicable Compliance Method(s) -

Compliance with the mass limitation may be determined by using the following one time calculation for potential to emit:

$$[\text{EF}(\text{ lbs PM}_{10}/\text{batch}) * (\text{number of batches}/\text{year}) * (1-\text{CE}) * (1 \text{ ton}/2000 \text{ lbs})] = \text{PM}_{10} \text{ emissions (ton/year)}$$

where:

EF = 75.17 lbs PM₁₀/batch (use data from the most recent stack test performed on this emissions unit or any other similar emissions unit located at this facility)

Number of batches = 214

CE = Control efficiency

- f. Emission Limitation -
26.65 lbs/batch CO emissions

Applicable Compliance Method(s) -

The uncontrolled carbon monoxide emissions limitation was determined based on stack test results. The stack test was conducted on January 12-14, 2005.

If required by Ohio EPA or Cleveland DAQ, compliance shall be demonstrated by performing a stack test using U.S. EPA Methods 10 or 10b, as applicable. The results of the emissions test shall be reported in terms of pounds per batch.

- g. Emission Limitation -
2.85 tons/year CO emissions

Applicable Compliance Method(s) -

Compliance with the mass limitation may be determined by using the following one time calculation for potential to emit:

GE Q1**PTI A**Emissions Unit ID: **P025****Modification Issued: 12/22/2005**

$[\text{EF}(\text{ lbs CO/batch}) * (\text{number of batches/year}) * (1 \text{ ton}/2000 \text{ lbs})] = \text{carbon monoxide emissions (tons/year)}$

where:

EF = 26.65 lbs CO/batch (use data from the most recent stack test performed on this emissions unit or any other similar emissions unit located at this facility)

Number of batches = 214

F. Miscellaneous Requirements

None

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

- The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P026 - Cosmetic And Industrial Grade BN Powder Firing Line - N	OAC rule 3745-31-05(A)(3)	7.91 lbs/batch and 0.85 ton/year particulate emissions (PE)
		7.52 lbs/batch and 0.80 ton/year PM ₁₀ 26.65 lbs/batch and 2.85 tons/year carbon monoxide (CO) emissions
		Visible emissions serving this emissions unit shall not exceed 10% opacity, as a six minute average.
	OAC rule 3745-17-07(A)	See A.2.a, A.2.b, and B.1 below.
	OAC rule 3745-17-11(B)	The visible emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).
		The particulate emission limitation specified by this rule is less stringent than the particulate emission limitation established pursuant to OAC rule

70

GE QI

PTI A

Modification Issued: 12/22/2005

Emissions Unit ID: **P026**

3745-31-05(A)(3).

2. Additional Terms and Conditions

- 2.a** This emissions unit operates using a batch process. Since the batch operation takes longer than one day to complete (41 hours) and total PE for the batch are 7.91 pounds and total PM₁₀ emissions are 7.52 pounds, these emissions limitations are more stringent than the allowable limits from OAC rule 3745-17-11(B). The annual limitation was determined based on a maximum of 214 batches per year.
- 2.b** The short-term and annual emissions limitations were established based on potential to emit; therefore, no recordkeeping and/or reporting requirements are needed for these emissions limitations.

B. Operational Restrictions

1. The permittee shall operate the baghouse for control of particulate emissions while the emissions unit is in operation.
2. The pressure drop across the baghouse shall be maintained within the range of 0.5 to 7.0 inches of water while the emissions unit is in operation.

C. Monitoring and/or Recordkeeping Requirements

1. The permittee shall properly install, operate, and maintain equipment to monitor the pressure drop across the baghouse while the emissions unit is in operation. The monitoring equipment shall be installed, calibrated, operated, and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual(s), with any modifications deemed necessary by the permittee. The permittee shall record the pressure drop across the baghouse on a daily basis while this emissions unit is in operation.
2. The permittee shall maintain records for any day during which the baghouse was not in service when the emissions unit was in operation and the corrective actions that were taken to resume operation of the control device.
3. The permit to install for this emissions unit P026 was evaluated based on the actual materials (typically coatings and cleanup materials) and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using

GE QI**PTI A****Modification Issued: 12/22/2005**Emissions Unit ID: **P026**

data from the permit to install application of SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant(s):

GE Quartz, Inc.
PTI Application: 12-04510
Modif

Facility ID: 131855821

Emissions Unit ID: P026

Pollutant: Boron Oxide

TLV (mg/m³): 10.0

Maximum Hourly Emission Rate (lbs/hr): 3.96

Predicted 1-hour Maximum Ground-Level Concentration (µg/m³): 165.3

MAGLC (µg/m³): 238.1

4. Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:
 - a. changes in the composition of the materials used (typically for coatings or cleanup materials), or the use of new materials, that would result in the emissions of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)", than the lowest TLV value previously modeled;
 - b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and
 - c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).
5. If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01(VV)(1)(a)(ii), and a modification of the existing permit to install will not be required. If the change(s) is (are) defined as a modification under other provisions of the modification definition (other than (VV)(1)(a)(ii)), then the permittee shall obtain a final permit to install prior to the change.
6. The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emission unit will still satisfy the "Air Toxic Policy."

Modification Issued: 12/22/2005

- a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
- b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and
- c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

D. Reporting Requirements

1. The permittee shall notify the Cleveland Division of Air Quality (Cleveland DAQ) in writing of any record showing that the baghouse was not in service when the emissions unit was in operation. The notification shall include a copy of such record and shall be sent to the Cleveland DAQ within 30 days after the event occurs.
2. The permittee shall submit quarterly pressure drop deviation (excursion) reports to the Cleveland DAQ that identify all periods of time during which the pressure drop across the baghouse did not comply with the allowable range specified above.

E. Testing Requirements

1. Compliance with the emission limitation(s) in Section A.1. of these terms and conditions shall be determined in accordance with the following method(s):
 - a. Emission Limitation -
10% opacity, as a 6-minute average

Applicable Compliance Method(s) -
Compliance shall be determined by visible emission evaluations performed in accordance with OAC rule 3745-17-03(B)(1) using methods and procedures specified in U.S. EPA Reference Method 9.
 - b. Emission Limitation -
7.91 lbs/batch PE emissions

Applicable Compliance Method(s) -
Compliance with the mass limitation shall be determined by using the following one time calculation for potential to emit:

GE QI

PTI A

Modification Issued: 12/22/2005

Emissions Unit ID: P026

$$[EF(\text{lbs PE}/\text{batch}) * (1 - CE)] = \text{particulate emissions (lbs}/\text{batch)}$$

where:

EF = 79.13 lbs PE/batch (use data from the most recent stack test performed on this emissions unit or any other similar emissions unit located at this facility)

CE = control efficiency

If required by Ohio EPA or Cleveland DAQ, compliance with the emission limitation shall be demonstrated through emission tests performed in accordance with 40 CFR Part 60, Appendix A, Methods 1 through 5 and the procedures specified in OAC rule 3745-17-03(B)(10). The results of the emissions test shall be reported in terms of pounds per batch.

- c. Emission Limitation -
0.85 ton/year PE emissions

Applicable Compliance Method(s) -

Compliance with the mass limitation shall be determined by using the following one time calculation for potential to emit:

$$[EF(\text{ lbs PE}/\text{batch}) * (\text{number of batches}/\text{year}) * (1 - CE) * (1 \text{ ton}/2000 \text{ lbs})] = \text{particulate emissions (ton}/\text{year)}$$

where:

EF = 79.13 lbs/batch (use data from the most recent stack test performed on this emissions unit or any other similar emissions unit located at this facility)

Number of batches = 214

CE = control efficiency

- d. Emission Limitation -
7.52 lbs/batch PM₁₀ emissions

Applicable Compliance Method(s) -

Compliance with the mass limitation shall be determined by using the following one time calculation for potential to emit:

$$[EF(\text{lbs PE}/\text{batch}) * (1 - CE)] = \text{PM}_{10} \text{ emissions (lbs}/\text{batch)}$$

where:

EF = 75.17 lbs PM₁₀/batch (use data from the most recent stack test performed on this emissions unit or any other similar emissions unit located at this facility)

CE = control efficiency

If required by Ohio EPA or Cleveland DAQ, compliance with the emission limitation shall be demonstrated through emission tests performed in accordance with 40 CFR Part 60, Appendix A, Methods 201 and 202. The results of the emissions test shall be reported in terms of pounds per batch.

- e. Emission Limitation -
 0.80 tons/year PM₁₀ emissions

Applicable Compliance Method(s) -
 Compliance with the mass limitation may be determined by using the following one time calculation for potential to emit:

$$[EF(\text{ lbs PM}_{10}/\text{batch}) * (\text{number of batches}/\text{year}) * (1-\text{CE}) * (1 \text{ ton}/2000 \text{ lbs})] = \text{PM}_{10} \text{ emissions (ton/year)}$$

where:

EF = 75.17 lbs PM₁₀/batch (use data from the most recent stack test performed on this emissions unit or any other similar emissions unit located at this facility)

Number of batches = 214

CE = Control efficiency

- f. Emission Limitation -
 26.65 lbs/batch CO emissions

Applicable Compliance Method(s) -
 The uncontrolled carbon monoxide emissions limitation was determined based on stack test results. The stack test was conducted on January 12-14, 2005.

If required by Ohio EPA or Cleveland DAQ, compliance shall be demonstrated by performing a stack test using U.S. EPA Methods 10 or 10b, as applicable. The results of the emissions test shall be reported in terms of pounds per batch.

- g. Emission Limitation -
 2.85 tons/year CO emissions

Applicable Compliance Method(s) -
 Compliance with the mass limitation may be determined by using the following one time calculation for potential to emit:

$$[EF(\text{ lbs CO}/\text{batch}) * (\text{number of batches}/\text{year}) * (1 \text{ ton}/2000 \text{ lbs})] = \text{carbon}$$

GE Q1

PTI A

Modification Issued: 12/22/2005

Emissions Unit ID: P026

monoxide emissions (tons/year)

where:

EF = 26.65 lbs CO/batch (use data from the most recent stack test performed on this emissions unit or any other similar emissions unit located at this facility)

Number of batches = 214

F. Miscellaneous Requirements

None

GE QI

PTI A

Modification Issued: 12/22/2005

Emissions Unit ID: P027

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)**A. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P027 - Cosmetic And Industrial Grade BN Powder Firing Line - O "Modified"	OAC rule 3745-31-05(A)(3)	7.91 lbs/batch and 0.85 ton/year particulate emissions (PE) 7.52 lbs/batch and 0.80 ton/year PM ₁₀ 26.65 lbs/batch and 2.85 tons/year carbon monoxide (CO) emissions Visible emissions serving this emissions unit shall not exceed 10% opacity, as a six minute average.
	OAC rule 3745-17-07(A)	See A.2.a, A.2.b, and B.1 below. The visible emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).
	OAC rule 3745-17-11(B)	The particulate emission limitation specified by this rule is less stringent than the particulate

GE Quartz, Inc.

PTI Application: 13-04510

Modif

Facility ID: 131855821

Emissions Unit ID: P027

emission limitation established
pursuant to OAC rule
3745-31-05(A)(3).

2. Additional Terms and Conditions

- 2.a** This emissions unit operates using a batch process. Since the batch operation takes longer than one day to complete (41 hours) and total PE for the batch are 7.91 pounds and total PM₁₀ emissions are 7.52 pounds, these emissions limitations are more stringent than the allowable limits from OAC rule 3745-17-11(B). The annual limitation was determined based on a maximum of 214 batches per year.
- 2.b** The short-term and annual emissions limitations were established based on potential to emit; therefore, no recordkeeping and/or reporting requirements are needed for these emissions limitations.

B. Operational Restrictions

1. The permittee shall operate the baghouse for control of particulate emissions while the emissions unit is in operation.
2. The pressure drop across the baghouse shall be maintained within the range of 0.5 to 7.0 inches of water while the emissions unit is in operation.

C. Monitoring and/or Recordkeeping Requirements

1. The permittee shall properly install, operate, and maintain equipment to monitor the pressure drop across the baghouse while the emissions unit is in operation. The monitoring equipment shall be installed, calibrated, operated, and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual(s), with any modifications deemed necessary by the permittee. The permittee shall record the pressure drop across the baghouse on a daily basis while this emissions unit is in operation.
2. The permittee shall maintain records for any day during which the baghouse was not in service when the emissions unit was in operation and the corrective actions that were taken to resume operation of the control device.
3. The permit to install for this emissions unit P027 was evaluated based on the actual materials (typically coatings and cleanup materials) and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using

GE QI**PTI A****Modification Issued: 12/22/2005**Emissions Unit ID: **P027**

data from the permit to install application of SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant(s):

Modification Issued: 12/22/2005

Pollutant: Boron Oxide

TLV (mg/m³): 10.0

Maximum Hourly Emission Rate (lbs/hr): 3.96

Predicted 1-hour Maximum Ground-Level Concentration (µg/m³): 165.3

MAGLC (µg/m³): 238.1

4. Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:
 - a. changes in the composition of the materials used (typically for coatings or cleanup materials), or the use of new materials, that would result in the emissions of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)", than the lowest TLV value previously modeled;
 - b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and
 - c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).
5. If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01(VV)(1)(a)(ii), and a modification of the existing permit to install will not be required. If the change(s) is (are) defined as a modification under other provisions of the modification definition (other than (VV)(1)(a)(ii)), then the permittee shall obtain a final permit to install prior to the change.
6. The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emission unit will still satisfy the "Air Toxic Policy."

- a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
- b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and
- c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

D. Reporting Requirements

1. The permittee shall notify the Cleveland Division of Air Quality (Cleveland DAQ) in writing of any record showing that the baghouse was not in service when the emissions unit was in operation. The notification shall include a copy of such record and shall be sent to the Cleveland DAQ within 30 days after the event occurs.
2. The permittee shall submit quarterly pressure drop deviation (excursion) reports to the Cleveland DAQ that identify all periods of time during which the pressure drop across the baghouse did not comply with the allowable range specified above.

E. Testing Requirements

1. Compliance with the emission limitation(s) in Section A.1. of these terms and conditions shall be determined in accordance with the following method(s):
 - a. Emission Limitation -
10% opacity, as a 6-minute average

Applicable Compliance Method(s) -
Compliance shall be determined by visible emission evaluations performed in accordance with OAC rule 3745-17-03(B)(1) using methods and procedures specified in U.S. EPA Reference Method 9.
 - b. Emission Limitation -
7.91 lbs/batch PE emissions

Applicable Compliance Method(s) -
Compliance with the mass limitation shall be determined by using the following one time calculation for potential to emit:

GE QI

PTI A

Modification Issued: 12/22/2005

Emissions Unit ID: P027

$$[EF(\text{lbs PE}/\text{batch}) * (1 - CE)] = \text{particulate emissions (lbs}/\text{batch)}$$

where:

EF = 79.13 lbs PE/batch (use data from the most recent stack test performed on this emissions unit or any other similar emissions unit located at this facility)

CE = control efficiency

If required by Ohio EPA or Cleveland DAQ, compliance with the emission limitation shall be demonstrated through emission tests performed in accordance with 40 CFR Part 60, Appendix A, Methods 1 through 5 and the procedures specified in OAC rule 3745-17-03(B)(10). The results of the emissions test shall be reported in terms of pounds per batch.

- c. Emission Limitation -
0.85 ton/year PE emissions

Applicable Compliance Method(s) -

Compliance with the mass limitation shall be determined by using the following one time calculation for potential to emit:

$$[EF(\text{ lbs PE}/\text{batch}) * (\text{number of batches}/\text{year}) * (1 - CE) * (1 \text{ ton}/2000 \text{ lbs})] = \text{particulate emissions (ton}/\text{year)}$$

where:

EF = 79.13 lbs/batch (use data from the most recent stack test performed on this emissions unit or any other similar emissions unit located at this facility)

Number of batches = 214

CE = control efficiency

- d. Emission Limitation -
7.52 lbs/batch PM₁₀ emissions

Applicable Compliance Method(s) -

Compliance with the mass limitation shall be determined by using the following one time calculation for potential to emit:

$$[EF(\text{lbs PE}/\text{batch}) * (1 - CE)] = \text{PM}_{10} \text{ emissions (lbs}/\text{batch)}$$

where:

EF = 75.17 lbs PM₁₀/batch (use data from the most recent stack test performed on this emissions unit or any other similar emissions unit located at this facility)

CE = control efficiency

If required by Ohio EPA or Cleveland DAQ, compliance with the emission limitation shall be demonstrated through emission tests performed in accordance with 40 CFR Part 60, Appendix A, Methods 201 and 202. The results of the emissions test shall be reported in terms of pounds per batch.

- e. Emission Limitation -
 0.80 tons/year PM₁₀ emissions

Applicable Compliance Method(s) -
 Compliance with the mass limitation may be determined by using the following one time calculation for potential to emit:

$$[\text{EF}(\text{ lbs PM}_{10}/\text{batch}) * (\text{number of batches}/\text{year}) * (1-\text{CE}) * (1 \text{ ton}/2000 \text{ lbs})] = \text{PM}_{10} \text{ emissions (ton/year)}$$

where:

EF = 75.17 lbs PM₁₀/batch (use data from the most recent stack test performed on this emissions unit or any other similar emissions unit located at this facility)

Number of batches = 214

CE = Control efficiency

- f. Emission Limitation -
 26.65 lbs/batch CO emissions

Applicable Compliance Method(s) -
 The uncontrolled carbon monoxide emissions limitation was determined based on stack test results. The stack test was conducted on January 12-14, 2005.

If required by Ohio EPA or Cleveland DAQ, compliance shall be demonstrated by performing a stack test using U.S. EPA Methods 10 or 10b, as applicable. The results of the emissions test shall be reported in terms of pounds per batch.

- g. Emission Limitation -
 2.85 tons/year CO emissions

Applicable Compliance Method(s) -
 Compliance with the mass limitation may be determined by using the following one time calculation for potential to emit:

$$[\text{EF}(\text{ lbs CO}/\text{batch}) * (\text{number of batches}/\text{year}) * (1 \text{ ton}/2000 \text{ lbs})] = \text{carbon}$$

GE Q1

PTI A

Modification Issued: 12/22/2005

Emissions Unit ID: **P027**

monoxide emissions (tons/year)

where:

EF = 26.65 lbs CO/batch (use data from the most recent stack test performed on this emissions unit or any other similar emissions unit located at this facility)

Number of batches = 214

F. Miscellaneous Requirements

None