State of Ohio Environmental Protection Agency

RE: FINAL PERMIT TO INSTALL **CERTIFIED MAIL**
CUYAHOGA COUNTY

Street Address:
122 S. Front Street

Lazarus Gov. Center **TELE:** (614) 644-3020 **FAX:** (614) 644-2329

Mailing Address:
Lazarus Gov. Center
P.O. Box 1049

Application No: 13-04376
Fac ID: 1318958414

DATE: 2/17/2005

Independence Recycling Plant 04-003
Brian Logue
5531 Canal Road
Valley View, OH 44125

Enclosed please find an Ohio EPA Permit to Install which will allow you to install the described source(s) in a manner indicated in the permit. Because this permit contains several conditions and restrictions, I urge you to read it carefully.

The Ohio EPA is urging companies to investigate pollution prevention and energy conservation. Not only will this reduce pollution and energy consumption, but it can also save you money. If you would like to learn ways you can save money while protecting the environment, please contact our Office of Pollution Prevention at (614) 644-3469.

You are hereby notified that this action by the Director is final and may be appealed to the Ohio Environmental Review Appeals Commission pursuant to Chapter 3745.04 of the Ohio Revised Code. The appeal must be in writing and set forth the action complained of and the grounds upon which the appeal is based. It must be filed within thirty (30) days after the notice of the Directors action. A copy of the appeal must be served on the Director of the Ohio Environmental Protection Agency within three (3) days of filing with the Commission. An appeal may be filed with the Environmental Review Appeals Commission at the following address:

Environmental Review Appeals Commission
309 South Fourth Street, Room 222
Columbus, Ohio 43215

Sincerely,

Michael W. Ahern

Michael W. Ahern, Manager
Permit Issuance and Data Management Section
Division of Air Pollution Control

CC: **USEPA** **CLAA**

STATE OF OHIO ENVIRONMENTAL PROTECTION AGENCY

Permit To Install	**Issue Date: 2/17/2005**
Terms and Conditions	**Effective Date: 2/17/2005**

FINAL PERMIT TO INSTALL 13-04376

Application Number:	13-04376
Facility ID:	1318958414
Permit Fee:	**$1650**
Name of Facility:	Independence Recycling Plant 04-003
Person to Contact:	Brian Logue
Address:	5531 Canal Road Valley View, OH 44125

Location of proposed air contaminant source(s) [emissions unit(s)]:
5531 Canal Road
Valley View, **Ohio**

Description of proposed emissions unit(s):
Hazemag 500 TPH concrete crusher, material handling, storage piles, and roadways -- F001-F003.

The above named entity is hereby granted a Permit to Install for the above described emissions unit(s) pursuant to Chapter 3745-31 of the Ohio Administrative Code. Issuance of this permit does not constitute expressed or implied approval or agreement that, if constructed or modified in accordance with the plans included in the application, the above described emissions unit(s) of environmental pollutants will operate in compliance with applicable State and Federal laws and regulations, and does not constitute expressed or implied assurance that if constructed or modified in accordance with those plans and specifications, the above described emissions unit(s) of pollutants will be granted the necessary permits to operate (air) or NPDES permits as applicable.

This permit is granted subject to the conditions attached hereto.

Ohio Environmental Protection Agency

Joseph P. Koncelik

Director

Part I - GENERAL TERMS AND CONDITIONS

A. Permit to Install General Terms and Conditions

1. Compliance Requirements

The emissions unit(s) identified in this Permit to Install shall remain in full compliance with all applicable State laws and regulations and the terms and conditions of this permit.

2. Reporting Requirements

The permittee shall submit required reports in the following manner:

a. Reports of any required monitoring and/or record keeping information shall be submitted to the appropriate Ohio EPA District Office or local air agency.

b. Except as otherwise may be provided in the terms and conditions for a specific emissions unit, quarterly written reports of (a) any deviations (excursions) from emission limitations, operational restrictions, and control device operating parameter limitations that have been detected by the testing, monitoring, and record keeping requirements specified in this permit, (b) the probable cause of such deviations, and (c) any corrective actions or preventive measures which have been or will be taken, shall be submitted to the appropriate Ohio EPA District Office or local air agency. If no deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted quarterly, i.e., by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters. (These quarterly reports shall exclude deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06.)

3. Records Retention Requirements

Each record of any monitoring data, testing data, and support information required pursuant to this permit shall be retained for a period of five years from the date the record was created. Support information shall include, but not be limited to, all calibration and maintenance records and all original strip-chart recordings for continuous monitoring instrumentation, and copies of all reports required by this permit. Such records may be maintained in computerized form.

4. Inspections and Information Requests

The Director of the Ohio EPA, or an authorized representative of the Director, may, subject to the safety requirements of the permittee and without undue delay, enter upon the premises of this source at any reasonable time for purposes of making inspections, conducting tests, examining records or reports pertaining to any emission of air contaminants, and determining compliance with any applicable State air pollution laws and regulations and the terms and conditions of this permit. The permittee shall furnish to the Director of the Ohio EPA, or an authorized

representative of the Director, upon receipt of a written request and within a reasonable time, any information that may be requested to determine whether cause exists for modifying, reopening or revoking this permit or to determine compliance with this permit. Upon verbal or written request, the permittee shall also furnish to the Director of the Ohio EPA, or an authorized representative of the Director, copies of records required to be kept by this permit.

5. Scheduled Maintenance/Malfunction Reporting

Any scheduled maintenance of air pollution control equipment shall be performed in accordance with paragraph (A) of OAC rule 3745-15-06. The malfunction of any emissions units or any associated air pollution control system(s) shall be reported to the appropriate Ohio EPA District Office or local air agency in accordance with paragraph (B) of OAC rule 3745-15-06. Except as provided in that rule, any scheduled maintenance or malfunction necessitating the shutdown or bypassing of any air pollution control system(s) shall be accompanied by the shutdown of the emissions unit(s) that is (are) served by such control system(s).

6. Permit Transfers

Any transferee of this permit shall assume the responsibilities of the prior permit holder. The appropriate Ohio EPA District Office or local air agency must be notified in writing of any transfer of this permit.

7. Air Pollution Nuisance

The air contaminants emitted by the emissions units covered by this permit shall not cause a public nuisance, in violation of OAC rule 3745-15-07.

8. Termination of Permit to Install

This Permit to Install shall terminate within eighteen months of the effective date of the Permit to Install if the owner or operator has not undertaken a continuing program of installation or modification or has not entered into a binding contractual obligation to undertake and complete within a reasonable time a continuing program of installation or modification. This deadline may be extended by up to 12 months if application is made to the Director within a reasonable time before the termination date and the party shows good cause for any such extension.

9. Construction of New Sources(s)

The proposed emissions unit(s) shall be constructed in strict accordance with the plans and application submitted for this permit to the Director of the Ohio Environmental Protection Agency. There may be no deviation from the approved plans without the express, written approval of the Agency. Any deviations from the approved plans or the above conditions may lead to such sanctions and penalties as provided under Ohio law. Approval of these plans does not constitute an assurance that the proposed facilities will operate in compliance with all Ohio laws and regulations. Additional facilities shall be installed upon orders of the Ohio

Environmental Protection Agency if the proposed sources cannot meet the requirements of this permit or cannot meet applicable standards.

If the construction of the proposed emissions unit(s) has already begun or has been completed prior to the date the Director of the Environmental Protection Agency approves the permit application and plans, the approval does not constitute expressed or implied assurance that the proposed facility has been constructed in accordance with the approved plans. The action of beginning and/or completing construction prior to obtaining the Director's approval constitutes a violation of OAC rule 3745-31-02. Furthermore, issuance of the Permit to Install does not constitute an assurance that the proposed source will operate in compliance with all Ohio laws and regulations. Approval of the plans in any case is not to be construed as an approval of the facility as constructed and/or completed. Moreover, issuance of the Permit to Install is not to be construed as a waiver of any rights that the Ohio Environmental Protection Agency (or other persons) may have against the applicant for starting construction prior to the effective date of the permit. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed facilities cannot meet the requirements of this permit or cannot meet applicable standards.

10. Public Disclosure

The facility is hereby notified that this permit, and all agency records concerning the operation of this permitted source, are subject to public disclosure in accordance with OAC rule 3745-49-03.

11. Applicability

This Permit To Install is applicable only to the emissions unit(s) identified in the Permit To Install. Separate Permit To Install for the installation or modification of any other emissions unit(s) are required for any emissions unit for which a Permit To Install is required.

12. Best Available Technology

As specified in OAC Rule 3745-31-05, all new sources must employ Best Available Technology (BAT). Compliance with the terms and conditions of this permit will fulfill this requirement.

13. Source Operation and Operating Permit Requirements After Completion of Construction

This facility is permitted to operate each source described by this Permit to Install for a period of up to one year from the date the source commenced operation. This permission to operate is granted only if the facility complies with all requirements contained in this permit and all applicable air pollution laws, regulations, and policies. Pursuant to OAC Chapter 3745-35, the permittee shall submit a complete operating permit application within ninety (90) days after commencing operation of the emissions unit(s) covered by this permit.

14. Construction Compliance Certification

The applicant shall provide Ohio EPA with a written certification (see enclosed form) that the facility has been constructed in accordance with the Permit to Install application and the terms and conditions of the Permit to Install. The certification shall be provided to Ohio EPA upon completion of construction but prior to startup of the source.

15. Fees

The permittee shall pay fees to the Director of the Ohio EPA in accordance with ORC section 3745.11 and OAC Chapter 3745-78. The permittee shall pay all applicable Permit to Install fees within 30 days after the issuance of this Permit to Install.

B. Permit to Install Summary of Allowable Emissions

The following information summarizes the total allowable emissions, by pollutant, based on the individual allowable emissions of each air contaminant source identified in this permit.

SUMMARY (for informational purposes only)
TOTAL PERMIT TO INSTALL ALLOWABLE EMISSIONS

Pollutant	Tons Per Year
PM	38.4
PM_{10}	13.0
NO_x	40.4
SO_2	5.0
CO	10.8

Emissions Unit ID: **F001**

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

Operations, Property, and/or Equipment	Applicable Rules/Requirements
F001 - Model #04-003 - 500 tons/hour portable concrete recycling plant - crushing, screening,	OAC rule 3745-31-05 (A)(3)
6.3 mm BTU/hr Diesel generator	
	40 CFR Part 60 Subpart OOO
	OAC rule 3745-17-07 (B)(1)

OAC rule 3745-17-08 (B)	Applicable Emissions <u>Limitations/Control Measures</u> 4.9 lbs/hour and 9.8 tons/year of PM emissions 1.9 lb/hour and 3.9 tons/year of PM_{10} emissions	20.2 lbs/hour of NO_x emissions and 40.4 tons/year 5.4 lbs/hour of CO emissions and 10.8 tons/year 2.5 lb/hour of SO_2 emissions and 5.0 ton/year
OAC rule 3745-31-05(A)(3)	Visible emissions of fugitive dust shall not exceed ten percent opacity, as a six minute average. Best available control measures that are sufficient to minimize or eliminate visible emissions of fugitive dust (see A.2.a) from any fugitive dust emission point listed below in A.2.c.	The requirements of this rule also include compliance with the requirements of OAC rule 3745-17-11(B)(5)(b) and 3745-17-07(A).
OAC rule 3745-17-07(A)	The emission limitation specified by this rule is equivalent to or less stringent than the emissions limitation established pursuant to OAC rule 3745-31-05(A)(3).	Visible particulate emissions shall not exceed twenty percent opacity, as a six-minute average, except as provided by rule. 0.062 lb/mm Btu of particulate emissions of actual heat input
OAC rule 3745-17-11(B)(5)(b)	The visible emission limitation specified by this rule is less stringent than the visible emission limitation established pursuant to OAC rule 3745-31-05(A)(3). The control measures specified by this rule are equivalent to the control measures established pursuant to OAC rule 3745-31-05(A)(3). 0.8 ton/year of PM emissions	

2. Additional Terms and Conditions

2.a The permittee shall employ best available control measures for the concrete recycling operation for the purpose of ensuring compliance with the applicable requirements. In accordance with the permittee's permit application, the permittee has committed to employing water spray bars at the hopper introduction point and at the end of each conveyor belt within the process to ensure compliance. The permittee shall also minimize the free fall distance of the processed material. Nothing in this paragraph shall prohibit the permittee from employing other control measures to ensure compliance.

2.b For each phase of the concrete recycling operation that is not adequately enclosed, the control measure(s) shall be implemented if the permittee determined, as a result of the inspection conducted pursuant to the monitoring section of this permit, that the control measure(s) is (are) necessary to ensure compliance with the applicable requirements. Any required implementation of the control measure(s) shall continue during the operation of the concrete recycler until further observation confirms that use of the control measure(s) is unnecessary.

2.c The portable concrete recycling plant that is covered by this permit and subject to the requirements of OAC rules 3745-17-07 and 3745-17-08 are listed below:

Load in to hopper
500 ton per hour crusher
Screening operation
Conveyor belts

2.d Label this portable concrete batching plant as 04-003.

B. Operational Restrictions

1. The maximum annual operating hours for this emissions unit shall not exceed 4,000 hours.

C. Monitoring and/or Record keeping Requirements

1. Except as otherwise provided in this section, for concrete recycling operations that are not adequately enclosed, the permittee shall perform daily inspections of such operations.

2. The above mentioned inspections shall be performed during representative, normal operating conditions.

3. The permittee may, upon receipt of written approval from the Cleveland Division of Air Quality, modify the above mentioned inspection frequencies if operating experience indicated that less frequent inspections would be sufficient to ensure compliance with the applicable requirements.

4. The permittee shall maintain records of the following information:

a. The date and reason any required inspection was not performed;

b. The date of each inspection where it was determined by the permittee that it was necessary to implement the control measure(s):

c. The dates the control measure(s) was (were) implemented; and

d. On a calendar quarter basis, the total number of days the control measure(s) was (were) implemented.

The information in 4.d shall be kept separately for each material handling operation, and shall be updated on a calendar quarter basis within 30 days after the end of each calendar quarter.

5. The permittee shall maintain daily records of the following information:

a. The production rate of crushed concrete processed for each day;

b. The application of water and/or chemical additives;

c. The name of the equipment operator responsible for the treatment; and,

d. The general weather conditions for each day, with respect to temperature, precipitation, wind speed and wind direction.

6. For each day during which the permittee burns a fuel other than diesel fuel the permittee shall maintain a record of the type and quantity of fuel burned in this emissions unit. The permittee shall also maintain documentation on the sulfur content of all fuels received.

7. The permittee shall maintain records of the annual operating hours for this emissions unit.

D. Reporting Requirements

1. The permittee shall submit quarterly deviation reports to the Cleveland Division of Air Quality that identify any of the following occurrences:

a. Each day during which an inspection was not performed by the required frequency; and

b. Each instance when a control measure, that was to be performed as a result of an inspection, was not implemented.

These deviation (excursion) reports shall be submitted in accordance with the general terms and conditions of this permit.

2. The permittee shall submit deviation (excursion) reports that identify each day when a fuel other than diesel was burned in this emissions unit. Each report shall be submitted within 30 days after the deviation occurs.

3. The owner or operator of any affected facility shall submit written reports of the results of all performance tests conducted to demonstrate compliance with the standards set forth in 60.672 of 40 CFR Part 60, including reports of opacity observations made using Method 9 to demonstrate compliance with 60.672(b) and the BAT limit for fugitive opacity contained in this permit.

4. The permittee shall submit annual reports which identify any exceedances of the annual operating hours limitation, as well as the corrective actions that were taken to achieve compliance. These reports shall be submitted by January 31 of each year.

E. Testing Requirements

1. Compliance with the emission limitation(s) in Section A.1 of these terms and conditions shall be determined in accordance with the following method(s):

a. Emission Limitation:
Visible emissions of fugitive dust shall not exceed ten percent opacity as a six-minute average

Applicable Compliance Method:
Compliance shall be determined by visible emission observations performed in accordance with USEPA Reference Method 9 and the procedures specified in OAC rule 3745-17-03 (B)(1) with the following additions per 40 CFR Part 60 Subpart OOO:

i. The minimum distance between the observer and the emission source shall be 4.57 meters (15 feet).

ii. The observer shall, when possible, select a position that minimizes interference from other fugitive emission sources (e.g. road dust). The required observer position relative to the sun (Method 9, Section 2.1) must be followed.

iii. For affected facilities using wet dust suppression for particulate matter control, a visible mist is sometimes generated by the spray. The water mist must not be confused with particulate matter emissions and is not to be considered a visible emission. When a water mist of this nature is present, the observation of emission is to be made at a point in the plume where the mist is no longer visible.

b. Emission Limitations:
4.1 pound/hour and 8.2 tons/year of PM emissions
1.5 pound/hour and 3.1 tons/year of PM_{10} emissions

Note: the allowable limit from Section A.1 is the total from Section E.1.b and E.1.c.

Applicable Compliance Method
Compliance with the hourly PM/PM_{10} emission limitation shall be determined using the emission factors for crushing, screening, and material handling operations in AP-42, Chapter 11.19.2 (Crushed Stone Processing), Fifth Edition, dated 1/1995. The emission factors, 0.000016 for PM_{10} for hopper loading, 0.0050 for PM and 0.0024 for PM_{10} for primary crushing, 0.025 for PM and 0.0087 for PM_{10} for primary screening, and 0.003 for PM and 0.0011 for PM_{10} for conveyors in pounds/ton, shall be multiplied by the maximum process weight rate, in tons/hour, for each operation identified in A.2 and summed, and multiply by (1-.75) to account for the 75% watering emission control efficiency. For hopper loading PM emissions, multiply the PM_{10} emissions by a factor of 2.1.

The tons/year limitations were developed by multiplying the pound/hour by the restricted operating hours of 4000 hours/year, and dividing by 2000 pounds/ton. Therefore, provided compliance is shown with the hourly limitations, compliance will also be shown with the annual limitation.

c. Emission Limitation: from pile formation operations
0.8 pound/hour and 1.6 tons/year of PM emissions
0.4 pound/hour and 0.8 tons/year of PM_{10} emissions

Note: the allowable limit from Section A.1 is the total from Section E.1.b and E.1.c.

Applicable Compliance Method:
Compliance with the hourly PM/PM_{10} emission limitation shall be based on calculations using the equation 1 for aggregate handling and storage piles taken from U.S. EPA reference document AP-42, 5th edition, Compilation of Air Pollution Emission Factors, section 13.2.2 (1/95) to establish the emission factor in lb/ton. The calculated emission factors are 0.03 lb per ton of materials handled for PM emissions and 0.013 lb per ton of materials handled for PM_{10} emissions. This emission factor is multiplied by the maximum hourly tons of material processed and (1-.75) to account for the 75% watering emission control efficiency.

The tons/year limitations were developed by multiplying the pound/hour by the restricted operating hours of 4000 hours/year, and dividing by 2000 pounds/ton.. Therefore, provided compliance is shown with the hourly limitations, compliance will also be shown with the annual limitation.

d. Emission Limitation:
0.8 ton/year of PM from the 6.3 mm BTU/hr diesel generator

Applicable Compliance Method
The tons/year limitations were developed by multiplying the pound/hour by the restricted operating hours of 4000 hours/year, and dividing by 2000 pounds/ton. Therefore, provided compliance is shown with the hourly limitations, compliance will also be shown with the annual limitation.

e. Emission Limitation:
20.2 lbs/hour of NO_x emissions from the 6.3 mm BTU/hr diesel generator

Applicable Compliance Method
Compliance with the hourly NO_x emission limitation shall be determined by multiplying the emission factor taken from the U.S. EPA reference document AP-42, 5th edition Compilation of Air Pollution Emission Factors Section 3.3, Table 3.3-1 (3.2 lb/mm Btu), by the heat content (130,000 Btu/gallon), and the maximum diesel fuel usage of the source (48.5 gallons/hour).

f. Emission Limitation:
40.4 tons/year of NO_x emissions from the 6.3 mm BTU/hr diesel generator

Applicable Compliance Method
The tons/year limitations were developed by multiplying the pound/hour by the restricted

operating hours of 4000 hours/year, and dividing by 2000 pounds/ton. Therefore, provided compliance is shown with the hourly limitations, compliance will also be shown with the annual limitation.

g. Emission Limitation:
5.4 lbs/hour of CO emissions from the 6.3 mm BTU/hr diesel generator

Applicable Compliance Method
Compliance with the hourly CO emission limitation shall be determined by multiplying the emission factor taken from the U.S. EPA reference document AP-42, 5th edition Compilation of Air Pollution Emission Factors Section 3.3, Table 3.3-1 (0.85 lb/mmBtu), by the heat content (130,000 Btu/gallon) and the maximum diesel fuel usage of the source (48.5 gallons/hour).

h. Emission Limitation:
10.8 tons/year of CO emissions from the 6.3 mm BTU/hr diesel generator

Applicable Compliance Method
The tons/year limitations were developed by multiplying the pound/hour by the restricted operating hours of 4000 hours/year, and dividing by 2000 pounds/ton. Therefore, provided compliance is shown with the hourly limitations, compliance will also be shown with the annual limitation.

i. Emission Limitation:
2.5 lb/hour of SO_2 emissions from the 6.3 mm BTU/hr diesel generator

Applicable Compliance Method
Compliance with the hourly CO emission limitation shall be determined by multiplying the emission factor taken from the U.S. EPA reference document AP-42, 5th edition Compilation of Air Pollution Emission Factors Section 3.3, Table 3.3-1 (0.4 lb/mm Btu) by the heat content (130,000 Btu/gallon) and the maximum diesel fuel usage of the source (48.5 gallons/hour).

j. Emission Limitation:
5.0 tons/year of SO_2 emissions from the 6.3 mm BTU/hr diesel generator

Applicable Compliance Method
The tons/year limitations were developed by multiplying the pound/hour by the restricted operating hours of 4000 hours/year, and dividing by 2000 pounds/ton. Therefore, provided compliance is shown with the hourly limitations, compliance will also be shown with the annual limitation.

k. Emission Limitation:
0.062 lb PE/mmBtu from the diesel generator

Applicable Compliance Method
If required, compliance shall be determined using Method 5 of 40 CFR Part 60, Appendix A.

F. Miscellaneous Requirements

1. Pursuant to OAC rule 3745-31-03(A)(1)(p), the permittee of a portable emissions unit may relocate within the State of Ohio without first obtaining a permit to install (PTI) providing certain criteria are met. The portable emissions unit shall meet one of the two following scenarios in order to qualify for this PTI exemption for the new location:

a. The following determinations have been documented, pursuant to OAC rule 3745-31-03(A)(1)(p)(i):

i. The portable emissions unit is equipped with the best available technology for such portable emissions unit;

ii. The portable emissions unit is operating pursuant to a currently effective permit to operate (PTO) or registration status;

iii. The applicant has provided proper notice of intent to relocate the portable emissions unit to the Cleveland Division of Air Quality and the appropriate field office having jurisdiction over the new site within a minimum of 30 days prior to the scheduled relocation; and

iv. In the Cleveland Division of Air Quality's and the appropriate field office's (having jurisdiction over the new site) judgement, the proposed site is acceptable under OAC rule 3745-15-07.

b. In the alternative, pursuant to OAC rule 3745-31-03(A)(1)(p)(ii), the permittee of a portable emissions unit may relocate within the State of Ohio without first obtaining a PTI, providing the following criteria of OAC rule 3745-31-05(E) are met:

i. The portable emissions unit permittee possesses an Ohio EPA PTI, PTO or registration status;

ii. The portable emissions unit is equipped with best available technology;

iii. The portable emissions unit owner has identified the proposed site to Ohio EPA;

iv. Ohio EPA has determined that the portable emissions unit, at the proposed site, will have an acceptable environmental impact;

v. A public notice, consistent with OAC Chapter 3745-47, is published in the county where the proposed site is located;

vi. The owner of the proposed site has provided the portable emissions unit owner with approval or equivalent declaration that it is acceptable to the site owner to move the portable emissions unit to this proposed site; and

vii. The portable emissions unit owner has provided Ohio EPA with 15 days written notice of the relocation.

2. Any site approvals issued by the Ohio EPA, pursuant to OAC rule 3745-31-03(A)(1)(p)(ii), shall be valid for no longer than 3 years and are subject to renewal.

In order for the Cleveland Division of Air Quality and the appropriate field office having jurisdiction over the new site to determine compliance with all of the above criteria, the permittee of the portable emissions unit must file a " Notice of Intent to Relocate", within the specified time frame (30 or 15 days) prior to the relocation of the emissions unit with the Cleveland Division of Air Quality and the appropriate field office having jurisdiction over the new site. Upon receipt of the notice, the Cleveland Division of Air Quality, and/or appropriate field office having jurisdiction over the new site, will evaluate the request in accordance with the above criteria.

Failure to submit said notification and to receive Ohio EPA approval prior to relocation of the emissions unit may result in fines and civil penalties.

Pursuant to OAC rule 3745-31-05(F), the Director may modify the site approval to add or delete certain portable sources or add or delete certain terms and conditions as appropriate.

Emissions Unit ID: **F002**

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

Operations, Property, and/or Equipment	Applicable Rules/Requirements	
F002 - unpaved facility roadways and parking areas (see Section A.2.a for identification)	OAC rule 3745-31-05 (A)(3)	OAC rule 3745-17-07 (B)(4)
		OAC rule 3745-17-08 (B), (B)(8), (B)(9)
	OAC rule 3745-17-07 (B)(5)	
	OAC rule 3745-17-08 (B), (B)(2)	
paved facility roadways and parking areas (see Section A.2.a for identification)	OAC rule 3745-31-05 (A)(3)	

Applicable Emissions Limitations/Control Measures	
PM, 8.2 TPY PM_{10}, 2.1 TPY Best available control measures that are sufficient to minimize or eliminate visible emissions of fugitive dust No visible emissions of fugitive dust except for 3 minutes during any 60 minute period The visible emission limitation specified by this rule is less stringent than the visible emission limitation established pursuant to OAC Rule 3745-31-05(A)(3). The control measures specified by this rule are equivalent to the control measures established pursuant to OAC rule 3745-31-05(A)(3).	The visible emission limitation specified by this rule is less stringent than the visible emission limitation established pursuant to OAC rule 3745-31-05 (A)(3). The control measures specified by this rule are equivalent to the control measures established pursuant to OAC rule 3745-31-05 (A)(3).
PM, 7.5 TPY PM_{10}, 1.8 TPY Best available control measures that are sufficient to minimize or eliminate visible emissions of fugitive dust No visible emissions of fugitive dust except for 1 minute during any 60 minute period	

2. Additional Terms and Conditions

2.a All unpaved roadways and parking areas that are covered by this permit are subject to the above mentioned requirements.

2.b All paved roadways and parking areas that are covered by this permit are subject to the above mentioned requirements.

2.c The permittee shall employ best available control measures on all unpaved roadways and parking areas for the purpose of ensuring compliance with the above mentioned applicable requirements. The permittee shall treat the unpaved roadways and parking areas with water at sufficient treatment frequencies to ensure compliance. Nothing in this paragraph shall prohibit the permittee from employing other control measures to ensure compliance.

2.d The permittee shall employ best available control measures on all paved roadways and parking areas for the purpose of ensuring compliance with the above mentioned applicable requirements. The permittee shall treat the paved roadways and parking areas with water at sufficient treatment frequencies to ensure compliance. Nothing in this paragraph shall prohibit the permittee from employing other control measures to ensure compliance.

2.e The needed frequencies of implementation of the control measures shall be determined by the permittee's inspections pursuant to the monitoring section of this permit. Implementation of the control measures shall not be necessary for a paved or unpaved roadway or parking area that is covered with snow and/or ice or if precipitation has occurred that is sufficient for that day to ensure compliance with the above mentioned applicable requirements. Implementation of any control measures may be suspended if unsafe or hazardous driving conditions would be created by its use.

2.f Any unpaved roadway or parking area, which during the term of this permit is paved or takes the characteristics of a paved surface due to the application of certain types of dust suppressants, may be controlled with the control measure(s) specified above for paved surfaces. Any unpaved roadway or parking area that takes the characteristics of a paved roadway or parking area due to the application of certain types of dust suppressants shall remain subject to the visible emission limitation for unpaved roadways and parking areas. Any unpaved roadway or parking area that is paved shall be subject to the visible emission limitation for paved roadways and parking areas.

2.g The permittee shall promptly remove, in such a manner as to minimize or prevent resuspension, earth and/or other material from paved streets onto which such material has been deposited by trucking or earth moving equipment or erosion by water or other

means.

2.h Open bodied vehicles transporting materials likely to become airborne shall have such materials covered at all times if the control measure is necessary for the materials being transported.

2.i Implementation of the above mentioned control measures in accordance with the terms and conditions of this permit is appropriate and sufficient to satisfy the best available technology requirements of OAC rule 3745-31-05.

B. Operational Restrictions

None

C. Monitoring and/or Record keeping Requirements

1. Except as otherwise provided in this section, the permittee shall perform daily inspections of all the roadways and parking areas.

2. The purpose of the inspections is to determine the need for implementing the above mentioned control measures. The inspections shall be performed during representative, normal traffic conditions. No inspection shall be necessary for a roadway or parking area that is covered with snow and/or ice or if precipitation has occurred that is sufficient for that day to ensure compliance with the above mentioned applicable requirements. Any required inspection that is not performed due to any of the above identified events shall be performed as soon as such event(s) has (have) ended, except if the next required inspection is within one week.

3. The permittee may, upon receipt of written approval from the Cleveland Division of Air Quality, modify the above mentioned inspection frequencies if operating experience indicates that less frequent inspections would be sufficient to ensure compliance with the above mentioned applicable requirements.

4. The permittee shall maintain records of the following information:

a. The date and reason any required inspection was not performed, including those inspections that were not performed due to snow and/or ice cover or precipitation;

b. The date of each inspection where it was determined by the permittee that it was necessary to implement the control measures;

c. The dates the control measures were implemented;

d. On a calendar quarter basis, the total number of days the control measures were implemented and the total number of days where snow and/or ice cover or precipitation were sufficient to not require the control measures; and

e. The annual vehicle miles traveled for unpaved roadways, and the annual vehicle miles traveled for paved roadways.

The information required in 4.d shall be updated on a calendar quarter basis within 30 days after the end of each calendar quarter.

D. Reporting Requirements

1. The permittee shall submit deviation reports that identify any of the following occurrences:

a. Each day during which an inspection was not performed by the required frequency, excluding an inspection which was not performed due to an exemption for snow and/or ice cover or precipitation; and

b. Each instance when a control measure, that was to be implemented as a result of an inspection, was not implemented.

2. The deviation reports shall be submitted in accordance with the reporting requirements of the General Terms and Conditions of this permit.

E. Testing Requirements

1. Compliance with the emission limitation(s) in Section A.1 of these terms and conditions shall be determined in accordance with the following method(s):

a. Visible Emission Limit:
There shall be no visible emissions of fugitive dust except for a period of time not to exceed three minutes during any sixty minute observation period for unpaved roadways and parking areas.

Applicable Compliance Method:
Compliance with the visible emission limitation for the unpaved roadways and parking areas identified above shall be determined in accordance with Test Method 22 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources," as such Appendix existed on July 1, 1996 and the modifications listed

in paragraphs (B)(4)(a) through (B)(4)(d) of OAC rule 3745-17-03.

b. Emission Limitation:
PM, 8.2 TPY Unpaved roads and parking areas
PM_{10}, 2.1TPY

Applicable Compliance Method:
The TPY emission limitation shall be based on calculations using the equation 1 for unpaved roadways and parking areas taken from U.S. EPA reference document AP-42, 5th edition, Compilation of Air Pollution Emission Factors, section 13.2.2 (1/95) to establish the emission factor in lb/VMT. The calculated emission factors are 15.6 lbs/VMT for PM emissions and 4.1 lbs/VMT for PM10 emissions. This emission factor is multiplied by the annual vehicle miles traveled (VMT) and (1-.50) to account for the 50% watering emission control efficiency then divide by 2000 lbs/ton.

c. Visible Emission Limit:
There shall be no visible emissions of fugitive dust except for a period of time not to exceed one minute during any sixty minute observation period for paved roadways and parking areas.

Applicable Compliance Method:
Compliance with the visible emission limitation for the paved roadways and parking areas identified above shall be determined in accordance with Test Method 22 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources," as such Appendix existed on July 1, 1996 and the modifications listed in paragraphs (B)(4)(a) through (B)(4)(d) of OAC rule 3745-17-03.

d. Emission Limitation:
PM, 7.5 TPY Paved roads and parking areas
PM_{10}, 1.8 TPY

Applicable Compliance Method:
The TPY emission limitation shall be based on Paved roads and parking areas calculations using the equation 1 for unpaved roadways and parking areas taken from U.S. EPA reference document AP-42, 5th edition, Compilation of Air Pollution Emission Factors, section 13.2.2 (1/95) to establish the emission factor in lb/VMT. The calculated emission factors are 1.9 lbs/VMT for PM emissions and 0.4 lbs/VMT for PM10 emissions. This emission factor is multiplied by the annual vehicle miles traveled (VMT) and (1-.50) to account for the 50% watering emission control efficiency then divide by 2000 lbs/ton.

F. Miscellaneous Requirements

1. Pursuant to OAC rule 3745-31-03(A)(1)(p), the permittee of a portable emissions unit may relocate within the State of Ohio without first obtaining a permit to install (PTI) providing certain criteria are met. The portable emissions unit shall meet one of the two following scenarios in order to qualify for this PTI exemption for the new location:

a. The following determinations have been documented, pursuant to OAC rule 3745-31-03(A)(1)(p)(i):

i. The portable emissions unit is equipped with the best available technology for such portable emissions unit;

ii. The portable emissions unit is operating pursuant to a currently effective permit to operate (PTO) or registration status;

iii. The applicant has provided proper notice of intent to relocate the portable emissions unit to the Cleveland Division of Air Quality and the appropriate field office having jurisdiction over the new site within a minimum of 30 days prior to the scheduled relocation; and

iv. In the Cleveland Division of Air Quality's and the appropriate field office's (having jurisdiction over the new site) judgement, the proposed site is acceptable under OAC rule 3745-15-07.

b. In the alternative, pursuant to OAC rule 3745-31-03(A)(1)(p)(ii), the permittee of a portable emissions unit may relocate within the State of Ohio without first obtaining a PTI, providing the following criteria of OAC rule 3745-31-05(E) are met:

i. The portable emissions unit permittee possesses an Ohio EPA PTI, PTO or registration status;

ii. The portable emissions unit is equipped with best available technology;

iii. The portable emissions unit owner has identified the proposed site to Ohio EPA;

iv. Ohio EPA has determined that the portable emissions unit, at the proposed site, will have an acceptable environmental impact;

v. A public notice, consistent with OAC Chapter 3745-47, is published in the county where the proposed site is located;

vi. The owner of the proposed site has provided the portable emissions unit owner with approval or equivalent declaration that it is acceptable to the site owner to move the portable emissions unit to this proposed site; and

vii. The portable emissions unit owner has provided Ohio EPA with 15 days written notice of the relocation.

2. Any site approvals issued by the Ohio EPA, pursuant to OAC rule 3745-31-03(A)(1)(p)(ii), shall be valid for no longer than 3 years and are subject to renewal.

In order for the Cleveland Division of Air Quality and the appropriate field office having jurisdiction over the new site to determine compliance with all of the above criteria, the permittee of the portable emissions unit must file a " Notice of Intent to Relocate", within the specified time frame (30 or 15 days) prior to the relocation of the emissions unit with the Cleveland Division of Air Quality and the appropriate field office having jurisdiction over the new site. Upon receipt of the notice, the Cleveland Division of Air Quality, and/or appropriate field office having jurisdiction over the new site, will evaluate the request in accordance with the above criteria.

Failure to submit said notification and to receive Ohio EPA approval prior to relocation of the emissions unit may result in fines and civil penalties.

Pursuant to OAC rule 3745-31-05(F), the Director may modify the site approval to add or delete certain portable sources or add or delete certain terms and conditions as appropriate.

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

Operations, Property, and/or Equipment	Applicable Rules/Requirements	
F003 - load-in and load-out of storage piles, and wind erosion from storage piles	OAC rule 3745-31-05 (A)(3)	
		OAC rule 3745-17-07 (B)(6)
		OAC rule 3745-17-08 (B), (B)(6)
	OAC rule 3745-17-07 (B)(6)	
	OAC rule 3745-17-08 (B), (B)(6)	
wind erosion from storage piles (see A.2.a for identification of storage piles)	OAC rule 3745-31-05 (A)(3)	

Applicable Emissions Limitations/Control Measures	
PM, 11.8 TPY PM_{10}, 5.0 TPY Best available control measures that are sufficient to minimize or eliminate visible emissions of fugitive dust (see Section A.2) No visible emissions of fugitive dust except for 3 minutes in any hour. The visible emission limitation specified by this rule is less stringent than the visible emission limitation established pursuant to OAC rule 3745-31-05 (A)(3). The control measures specified by this rule are equivalent to the control measures established pursuant to OAC rule 3745-31-05 (A)(3).	
PM, 0.33 TPY PM_{10}, 0.2 TPY Best available control measures that are sufficient to minimize or eliminate visible emissions of fugitive dust (see Section A.2) No visible emissions of fugitive dust except for 3 minute in any hour. The visible emission limitation specified by this rule is less stringent than the visible emission limitation established pursuant to OAC rule 3745-31-05 (A)(3). The control measures specified by this rule are equivalent to the control measures established pursuant to OAC rule 3745-31-05 (A)(3).	

2. Additional Terms and Conditions

2.a The storage piles that are covered by this permit and subject to the requirements of OAC rules 3745-17-07 and 3745-17-08 are:
-(2) recycled concrete

2.b The permittee shall employ best available control measures on all load-in and load-out operations associated with the storage piles for the purpose of ensuring compliance with the above-mentioned applicable requirements. In accordance with the permittee's permit application, the permittee has committed to applying water and/or other suitable dust suppressants to each storage pile to ensure compliance. Nothing in this paragraph shall prohibit the permittee from employing other control measures to ensure compliance.

2.c The above-mentioned control measure(s) shall be employed for each load-in and load-out operation of each storage pile if the permittee determines, as a result of the inspection conducted pursuant to the monitoring section of this permit, that the control measure(s) are necessary to ensure compliance with the above-mentioned applicable requirements. Any required implementation of the control measure(s) shall continue during any such operation until further observation confirms that use of the measure(s) is unnecessary.

2.d The permittee shall employ best available control measures for wind erosion from the surfaces of all storage piles for the purpose of ensuring compliance with the above-mentioned applicable requirements. In accordance with the permittee's permit application, the permittee has committed to applying water and/or other suitable dust suppressants to each storage pile to ensure compliance. Nothing in this paragraph shall prohibit the permittee from employing other control measures to ensure compliance.

2.e The above-mentioned control measure(s) shall be employed for wind erosion from each pile if the permittee determines, as a result of the inspection conducted pursuant to the monitoring section of this permit, that the control measure(s) are necessary to ensure compliance with the above-mentioned applicable requirements. Implementation of the control measure(s) shall not be necessary for a storage pile that is covered with snow and/or ice or if precipitation has occurred that is sufficient for that day to ensure compliance with the above-mentioned applicable requirements.

2.f Implementation of the above-mentioned control measures in accordance with the terms and conditions of this permit is appropriate and sufficient to satisfy the requirements of OAC rules 3745-17-08 and 3745-31-05.

B. Operational Restrictions

None

C. Monitoring and/or Record keeping Requirements

1. Except as otherwise provided in this section, the permittee shall perform daily inspections of each load in operation at each storage pile, load out operation, and wind erosion from pile surfaces associated with each storage pile.

2. No inspection shall be necessary for wind erosion from the surface of a storage pile when the pile is covered with snow and/or ice and for any storage pile activity if precipitation has occurred that is sufficient for that day to ensure compliance with the above mentioned applicable requirements. Any required inspection that is not performed due to any of the above identified events shall be performed as soon as such event(s) has (have) ended, except if the next required inspection is within one week.

3. The purpose of the inspections is to determine the need for implementing the control measures specified in this permit for load in and load out of a storage pile, and wind erosion from the surface of a storage pile. The inspections shall be performed during representative, normal storage pile operating conditions.

4. The permittee may, upon receipt of written approval from the Cleveland Division of Air Quality, modify the above mentioned inspection frequencies if operating experience indicates that less frequent inspections would be sufficient to ensure compliance with the above mentioned applicable requirements.

5. The permittee shall maintain records of the following information:

a. The date and reason any required inspection was not performed, including those inspections that were not performed due to snow and/or ice cover or precipitation;

b. The date of each inspection where it was determined by the permittee that it was necessary to implement the control measures;

c. The dates the control measures were implemented;

d. On a calendar quarter basis, the total number of days the control measures were implemented and, for wind erosion form pile surfaces, the total number of days where snow and/or ice cover or precipitation were sufficient to not require the control measure(s); and

e. The annual amount of material handled, in tons, and the size of each storage pile, in acres.

6. The information required in 7.d shall be kept separately for (i) the load in operations, (ii) the load out operations, and (iii) the pile surfaces (wind erosion), and shall be updated on a calendar quarter basis within 30 days after the end of each calendar quarter.

D. Reporting Requirements

1. The permittee shall submit quarterly deviation reports that identify any of the following occurrences:

a. Each day during which an inspection was not performed by the required frequency, excluding an inspection which was not performed due to an exemption for snow and/or ice cover or precipitation; and

b. Each instance when a control measure, that was to be implemented as a result of an inspection, was not implemented.

2. The deviation reports shall be submitted in accordance with the reporting requirements of the General Terms and Conditions of this permit.

E. Testing Requirements

1. Compliance with the emission limitation(s) in Section A.1 of these terms and conditions shall be determined in accordance with the following method(s):

a. Visible Emission Limit:
There shall be no visible emissions of fugitive dust except for a period of time not to exceed three minutes during any sixty minute observation period.

Compliance with the visible emission limitation for the storage piles identified above shall be determined in accordance with Test Method 22 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources," as such Appendix existed on July 1, 1996, and the modifications listed in paragraphs (B)(4)(a) through (B)(4)(c) of OAC rule 3745-17-03.

b. Emission Limitation:
PM, 11.8 TPY from load in/load out operations
PM_{10}, 5.0 TPY

Applicable Compliance Method:
The TPY emission limitation shall be based on calculations using the equation 1 for aggregate handling and storage piles taken from U.S. EPA reference document AP-42, 5th edition, Compilation of Air Pollution Emission Factors, section 13.2.2 (1/95) to establish the emission factor in lb per ton. The calculated emission factors are 0.0018 lb per ton of materials handled for PM emissions and 0.00085 lb per ton of materials handled for PM_{10} emissions. This emission factor is multiplied by the annual tons of material processed and (1-.50) to account for the 50% watering emission control efficiency.

c. Emission Limitation:
PM, 0.33 TPY from wind erosion
PM_{10}, 0.2 TPY

Applicable Compliance Method:
The TPY emission limitation shall be based on calculations using the equation 1 for aggregate handling and storage piles taken from U.S. EPA reference document AP-42, 5th edition, Compilation of Air Pollution Emission Factors, section 13.2.2 (1/95) to establish the emission factor in lb/day/acre. The calculated emission factors are 4.76 for concrete, 1.59 for brick, 3.17 for asphalt, 7.93 for natural aggregate, and 12.69 lb/day/acre of material (fines) handled for PM emissions and PM10 emissions. This emission factor is multiplied by the acreage of each pile, 365 days/year, the conversion factor (1 ton/2000 lbs) and (1-.80) to account for the 80% watering emission control efficiency.

F. Miscellaneous Requirements

1. Pursuant to OAC rule 3745-31-03(A)(1)(p), the permittee of a portable emissions unit may relocate within the State of Ohio without first obtaining a permit to install (PTI) providing certain criteria are met. The portable emissions unit shall meet one of the two following scenarios in order to qualify for this PTI exemption for the new location:

a. The following determinations have been documented, pursuant to OAC rule 3745-31-03(A)(1)(p)(i):

i. The portable emissions unit is equipped with the best available technology for such portable emissions unit;

ii. The portable emissions unit is operating pursuant to a currently effective permit to operate (PTO) or registration status;

iii. The applicant has provided proper notice of intent to relocate the portable

emissions unit to the Cleveland Division of Air Quality and the appropriate field office having jurisdiction over the new site within a minimum of 30 days prior to the scheduled relocation; and

iv. In the Cleveland Division of Air Quality's and the appropriate field office's (having jurisdiction over the new site) judgement, the proposed site is acceptable under OAC rule 3745-15-07.

b. In the alternative, pursuant to OAC rule 3745-31-03(A)(1)(p)(ii), the permittee of a portable emissions unit may relocate within the State of Ohio without first obtaining a PTI, providing the following criteria of OAC rule 3745-31-05(E) are met:

i. The portable emissions unit permittee possesses an Ohio EPA PTI, PTO or registration status;

ii. The portable emissions unit is equipped with best available technology;

iii. The portable emissions unit owner has identified the proposed site to Ohio EPA;

iv. Ohio EPA has determined that the portable emissions unit, at the proposed site, will have an acceptable environmental impact;

v. A public notice, consistent with OAC Chapter 3745-47, is published in the county where the proposed site is located;

vi. The owner of the proposed site has provided the portable emissions unit owner with approval or equivalent declaration that it is acceptable to the site owner to move the portable emissions unit to this proposed site; and

vii. The portable emissions unit owner has provided Ohio EPA with 15 days written notice of the relocation.

2. Any site approvals issued by the Ohio EPA, pursuant to OAC rule 3745-31-03(A)(1)(p)(ii), shall be valid for no longer than 3 years and are subject to renewal.

In order for the Cleveland Division of Air Quality and the appropriate field office having jurisdiction over the new site to determine compliance with all of the above criteria, the permittee of the portable emissions unit must file a " Notice of Intent to Relocate", within the specified time frame (30 or 15 days) prior to the relocation of the emissions unit with the Cleveland Division of Air Quality and the appropriate field office having jurisdiction over the new site. Upon receipt of the notice, the Cleveland Division of Air Quality, and/or appropriate field office having

jurisdiction over the new site, will evaluate the request in accordance with the above criteria.

Failure to submit said notification and to receive Ohio EPA approval prior to relocation of the emissions unit may result in fines and civil penalties.

Pursuant to OAC rule 3745-31-05(F), the Director may modify the site approval to add or delete certain portable sources or add or delete certain terms and conditions as appropriate.

Independence Recycling Plant 04-003 **Facility ID: 1318958414**
PTI Application: 13-04376
Issued: 2/17/2005

Emissions Unit ID: **F003**

SIC CODE 1422 SCC CODE 3-05-020-01 EMISSIONS UNIT ID F001

EMISSIONS UNIT DESCRIPTION 500 TPH portable concrete crusher

DATE INSTALLED

EMISSIONS: (Click on bubble help for Air Quality Descriptions)

Pollutants	Air Quality Description	Actual Emissions Rate		PTI Allowable	
		Short Term Rate	Tons Per Year	Short Term Rate	Tons Per Year
Particulate Matter	Attainment			4.9	10.6
PM_{10}	Attainment			2.0	3.9
Sulfur Dioxide	Attainment			2.5	5
Organic Compounds					
Nitrogen Oxides	Attainment			20.2	40.4
Carbon Monoxide	Attainment			5.4	10.8
Lead					
Other: Air Toxics					

APPLICABLE FEDERAL RULES:

NSPS? 40 CFR Part 60, Subpart OOO NESHAP? PSD? OFFSET POLICY? PS?

WHAT IS THE BAT DETERMINATION, AND WHAT IS THE BASIS FOR THE DETERMINATION?
Spray nozzles at emission points and minimization of the free fall distance of processed material. No opacity greater than 10 % for a six-minute average. The basis for this determination is good engineering judgement.

IS THIS SOURCE SUBJECT TO THE AIR TOXICS POLICY? no

OPTIONAL: WHAT IS THE CAPITAL COST OF CONTROL EQUIPMENT? $

TOXIC AIR CONTAMINANTS

Ohio EPA's air toxics policy applies to contaiminants for which the American Conference of Governmental Industrial Hygienists (ACGIH) has a listed threshold limit value.

AIR TOXICS MODELING PERFORMED*? _____ YES x NO

IDENTIFY THE AIR CONTAMINANTS: _____

11930.wpd

Independence Recycling Plant 04-003 **Facility ID: 1318958414**
PTI Application: 13-04376
Issued: 2/17/2005

Emissions Unit ID: **F003**

SIC CODE 1422 SCC CODE 3-05-020-01 EMISSIONS UNIT ID F002
EMISSIONS UNIT DESCRIPTION Unpaved roadways and parking areas
DATE INSTALLED

EMISSIONS: (Click on bubble help for Air Quality Descriptions)

Pollutants	Air Quality Description	Actual Emissions Rate		PTI Allowable	
		Short Term Rate	Tons Per Year	Short Term Rate	Tons Per Year
Particulate Matter	Attainment				15.7
PM_{10}	Attainmnet				3.9
Sulfur Dioxide					
Organic Compounds					
Nitrogen Oxides					
Carbon Monoxide					
Lead					
Other: Air Toxics					

APPLICABLE FEDERAL RULES:

NSPS? NESHAP? PSD? OFFSET POLICY?

WHAT IS THE BAT DETERMINATION, AND WHAT IS THE BASIS FOR THE DETERMINATION?
Application of water to roadway. Basis is determined from similar sources.

IS THIS SOURCE SUBJECT TO THE AIR TOXICS POLICY? no
OPTIONAL: WHAT IS THE CAPITAL COST OF CONTROL EQUIPMENT? $

TOXIC AIR CONTAMINANTS

Ohio EPA's air toxics policy applies to contaiminants for which the American Conference of Governmental Industrial Hygienists (ACGIH) has a listed threshold limit value.

AIR TOXICS MODELING PERFORMED*? _____ YES x NO

IDENTIFY THE AIR CONTAMINANTS: _____

11930.wpd

Independence Recycling Plant 04-003 **Facility ID: 1318958414**
PTI Application: 13-04376
Issued: 2/17/2005

Emissions Unit ID: **F003**

SIC CODE 1422 SCC CODE 3-05-020-01 EMISSIONS UNIT ID F003

EMISSIONS UNIT DESCRIPTION Material handling with load-in and load-out of stoage piles

DATE INSTALLED

EMISSIONS: (Click on bubble help for Air Quality Descriptions)

Pollutants	Air Quality Description	Actual Emissions Rate		PTI Allowable	
		Short Term Rate	Tons Per Year	Short Term Rate	Tons Per Year
Particulate Matter	Attainment				12.1
PM_{10}	Attainment				5.2
Sulfur Dioxide					
Organic Compounds					
Nitrogen Oxides					
Carbon Monoxide					
Lead					
Other: Air Toxics					

APPLICABLE FEDERAL RULES:

NSPS? NESHAP? PSD? OFFSET POLICY?

WHAT IS THE BAT DETERMINATION, AND WHAT IS THE BASIS FOR THE DETERMINATION?

Application of water on top of storage piles, no visible emissions except for a period of time not to exceed three minute during sixty-minute observed period. Best available control measures that are sufficient to minimize or eliminate visible emissions of fugitive dust. The basis for this determination is from similar sources

IS THIS SOURCE SUBJECT TO THE AIR TOXICS POLICY? no

OPTIONAL: WHAT IS THE CAPITAL COST OF CONTROL EQUIPMENT? $

TOXIC AIR CONTAMINANTS

Ohio EPA's air toxics policy applies to contaiminants for which the American Conference of Governmental Industrial Hygienists (ACGIH) has a listed threshold limit value.

AIR TOXICS MODELING PERFORMED*? _____ YES x NO

IDENTIFY THE AIR CONTAMINANTS: