



State of Ohio Environmental Protection Agency

**RE: FINAL PERMIT TO INSTALL
BUTLER COUNTY**

CERTIFIED MAIL

Street Address:

122 S. Front Street

Lazarus Gov. Center TELE: (614) 644-3020 FAX: (614) 644-2329

Mailing Address:

Lazarus Gov. Center
P.O. Box 1049

Application No: 14-05863

Fac ID: 1409010962

DATE: 9/5/2006

Watson Gravel Incorporated
Brian Bottoms
2728 Hamilton Cleves Highway
Ross, OH 45061

Enclosed please find an Ohio EPA Permit to Install which will allow you to install the described source(s) in a manner indicated in the permit. Because this permit contains several conditions and restrictions, I urge you to read it carefully.

The Ohio EPA is urging companies to investigate pollution prevention and energy conservation. Not only will this reduce pollution and energy consumption, but it can also save you money. If you would like to learn ways you can save money while protecting the environment, please contact our Office of Pollution Prevention at (614) 644-3469.

You are hereby notified that this action of the Director is final and may be appealed to the Environmental Review Appeals Commission pursuant to Section 3745.04 of the Ohio Revised Code. The appeal must be in writing and set forth the action complained of and the grounds upon which the appeal is based. The appeal must be filed with the Commission within thirty (30) days after notice of the Director's action. The appeal must be accompanied by a filing fee of \$70.00 which the Commission, in its discretion, may reduce if by affidavit you demonstrate that payment of the full amount of the fee would cause extreme hardship. Notice of the filing of the appeal shall be filed with the Director within three (3) days of filing with the Commission. Ohio EPA requests that a copy of the appeal be served upon the Ohio Attorney General's Office, Environmental Enforcement Section. An appeal may be filed with the Environmental Review Appeals Commission at the following address:

Environmental Review Appeals Commission
309 South Fourth Street, Room 222
Columbus, OH 43215

Sincerely,

Michael W. Ahern, Manager
Permit Issuance and Data Management Section
Division of Air Pollution Control

CC: USEPA

HCDES



**Permit To Install
Terms and Conditions**

**Issue Date: 9/5/2006
Effective Date: 9/5/2006**

FINAL PERMIT TO INSTALL 14-05863

Application Number: 14-05863
Facility ID: 1409010962
Permit Fee: **\$1100**
Name of Facility: Watson Gravel Incorporated
Person to Contact: Brian Bottoms
Address: 2728 Hamilton Cleves Highway
Ross, OH 45061

Location of proposed air contaminant source(s) [emissions unit(s)]:
**6650 Germantown Pike
Middletown, Ohio**

Description of proposed emissions unit(s):
Loaders, conveyors, crushers and screens at an existing aggregate processing plant.

The above named entity is hereby granted a Permit to Install for the above described emissions unit(s) pursuant to Chapter 3745-31 of the Ohio Administrative Code. Issuance of this permit does not constitute expressed or implied approval or agreement that, if constructed or modified in accordance with the plans included in the application, the above described emissions unit(s) of environmental pollutants will operate in compliance with applicable State and Federal laws and regulations, and does not constitute expressed or implied assurance that if constructed or modified in accordance with those plans and specifications, the above described emissions unit(s) of pollutants will be granted the necessary permits to operate (air) or NPDES permits as applicable.

This permit is granted subject to the conditions attached hereto.

Ohio Environmental Protection Agency

Director

Part I - GENERAL TERMS AND CONDITIONS

A. Permit to Install General Terms and Conditions

1. Compliance Requirements

The emissions unit(s) identified in this Permit to Install shall remain in full compliance with all applicable State laws and regulations and the terms and conditions of this permit.

2. Reporting Requirements

The permittee shall submit required reports in the following manner:

- a. Reports of any required monitoring and/or recordkeeping information shall be submitted to the appropriate Ohio EPA District Office or local air agency.
- b. Except as otherwise may be provided in the terms and conditions for a specific emissions unit, quarterly written reports of (a) any deviations (excursions) from emission limitations, operational restrictions, and control device operating parameter limitations that have been detected by the testing, monitoring, and recordkeeping requirements specified in this permit, (b) the probable cause of such deviations, and (c) any corrective actions or preventive measures which have been or will be taken, shall be submitted to the appropriate Ohio EPA District Office or local air agency. If no deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted quarterly, i.e., by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters. (These quarterly reports shall exclude deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06.)

3. Records Retention Requirements

Each record of any monitoring data, testing data, and support information required pursuant to this permit shall be retained for a period of five years from the date the record was created. Support information shall include, but not be limited to, all calibration and maintenance records and all original strip-chart recordings for continuous monitoring instrumentation, and copies of all reports required by this permit. Such records may be maintained in computerized form.

4. Inspections and Information Requests

The Director of the Ohio EPA, or an authorized representative of the Director, may, subject to the safety requirements of the permittee and without undue delay, enter upon

Watson Gravel Incorporated
PTI Application: 14-05863
Issued: 9/5/2006

Facility ID: 1409010962

the premises of this source at any reasonable time for purposes of making inspections, conducting tests, examining records or reports pertaining to any emission of air contaminants, and determining compliance with any applicable State air pollution laws and regulations and the terms and conditions of this permit. The permittee shall furnish to the Director of the Ohio EPA, or an authorized representative of the Director, upon receipt of a written request and within a reasonable time, any information that may be requested to determine whether cause exists for modifying, reopening or revoking this permit or to determine compliance with this permit. Upon verbal or written request, the permittee shall also furnish to the Director of the Ohio EPA, or an authorized representative of the Director, copies of records required to be kept by this permit.

5. Scheduled Maintenance/Malfunction Reporting

Any scheduled maintenance of air pollution control equipment shall be performed in accordance with paragraph (A) of OAC rule 3745-15-06. The malfunction of any emissions units or any associated air pollution control system(s) shall be reported to the appropriate Ohio EPA District Office or local air agency in accordance with paragraph (B) of OAC rule 3745-15-06. Except as provided in that rule, any scheduled maintenance or malfunction necessitating the shutdown or bypassing of any air pollution control system(s) shall be accompanied by the shutdown of the emissions unit(s) that is (are) served by such control system(s).

6. Permit Transfers

Any transferee of this permit shall assume the responsibilities of the prior permit holder. The appropriate Ohio EPA District Office or local air agency must be notified in writing of any transfer of this permit.

7. Air Pollution Nuisance

The air contaminants emitted by the emissions units covered by this permit shall not cause a public nuisance, in violation of OAC rule 3745-15-07.

8. Termination of Permit to Install

This Permit to Install shall terminate within eighteen months of the effective date of the Permit to Install if the owner or operator has not undertaken a continuing program of installation or modification or has not entered into a binding contractual obligation to undertake and complete within a reasonable time a continuing program of installation or modification. This deadline may be extended by up to 12 months if application is made to the Director within a reasonable time before the termination date and the party shows good cause for any such extension.

9. Construction of New Sources(s)

Watson Gravel Incorporated
PTI Application: 14-05863
Issued: 9/5/2006

Facility ID: 1409010962

The proposed emissions unit(s) shall be constructed in strict accordance with the plans and application submitted for this permit to the Director of the Ohio Environmental Protection Agency. There may be no deviation from the approved plans without the express, written approval of the Agency. Any deviations from the approved plans or the above conditions may lead to such sanctions and penalties as provided under Ohio law. Approval of these plans does not constitute an assurance that the proposed facilities will operate in compliance with all Ohio laws and regulations. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed sources cannot meet the requirements of this permit or cannot meet applicable standards.

If the construction of the proposed emissions unit(s) has already begun or has been completed prior to the date the Director of the Environmental Protection Agency approves the permit application and plans, the approval does not constitute expressed or implied assurance that the proposed facility has been constructed in accordance with the approved plans. The action of beginning and/or completing construction prior to obtaining the Director's approval constitutes a violation of OAC rule 3745-31-02. Furthermore, issuance of the Permit to Install does not constitute an assurance that the proposed source will operate in compliance with all Ohio laws and regulations. Approval of the plans in any case is not to be construed as an approval of the facility as constructed and/or completed. Moreover, issuance of the Permit to Install is not to be construed as a waiver of any rights that the Ohio Environmental Protection Agency (or other persons) may have against the applicant for starting construction prior to the effective date of the permit. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed facilities cannot meet the requirements of this permit or cannot meet applicable standards.

10. Public Disclosure

The facility is hereby notified that this permit, and all agency records concerning the operation of this permitted source, are subject to public disclosure in accordance with OAC rule 3745-49-03.

11. Applicability

This Permit To Install is applicable only to the emissions unit(s) identified in the Permit To Install. Separate Permit To Install for the installation or modification of any other emissions unit(s) are required for any emissions unit for which a Permit To Install is required.

12. Best Available Technology

As specified in OAC Rule 3745-31-05, all new sources must employ Best Available Technology (BAT). Compliance with the terms and conditions of this permit will fulfill this requirement.

Watson Gravel Incorporated
 PTI Application: 14-05863
 Issued: 9/5/2006

Facility ID: 1409010962

13. Source Operation and Operating Permit Requirements After Completion of Construction

This facility is permitted to operate each source described by this Permit to Install for a period of up to one year from the date the source commenced operation. This permission to operate is granted only if the facility complies with all requirements contained in this permit and all applicable air pollution laws, regulations, and policies. Pursuant to OAC Chapter 3745-35, the permittee shall submit a complete operating permit application within ninety (90) days after commencing operation of the emissions unit(s) covered by this permit.

14. Construction Compliance Certification

The applicant shall provide Ohio EPA with a written certification (see enclosed form) that the facility has been constructed in accordance with the Permit to Install application and the terms and conditions of the Permit to Install. The certification shall be provided to Ohio EPA upon completion of construction but prior to startup of the source.

15. Fees

The permittee shall pay fees to the Director of the Ohio EPA in accordance with ORC section 3745.11 and OAC Chapter 3745-78. The permittee shall pay all applicable Permit to Install fees within 30 days after the issuance of this Permit to Install.

B. Permit to Install Summary of Allowable Emissions

The following information summarizes the total allowable emissions, by pollutant, based on the individual allowable emissions of each air contaminant source identified in this permit.

SUMMARY (for informational purposes only)
 TOTAL PERMIT TO INSTALL ALLOWABLE EMISSIONS

<u>Pollutant</u>	<u>Tons Per Year</u>
PM	11.82
PM-10	5.0

7

Watson Gravel Incorporated
PTI Application: 14-05863
Issued: 9/5/2006

Facility ID: 1409010962

Issued: 9/5/2006

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)**A. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

Operations, Property, and/or Equipment - (F001) - Aggregate processing

Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
OAC rule 3745-31-02(A)(2)	See terms A.2.a., and B.1.
OAC rule 3745-17-07(B)	The emission limitations and opacity restrictions specified by this rule are less stringent than the emission limitation established pursuant to 40 CFR Part 60, Subpart OOO.
OAC rule 3745-17-08(B)	The emission limitations and opacity restrictions specified by this rule are less stringent than the emission limitations established pursuant to 40 CFR Part 60, Subpart OOO.
40 CFR Part 60 Subpart OOO	See terms A.2.b through A.2.e and B.2.
ORC 3704.03(T)(4)	See term A.2.g.

2. Additional Terms and Conditions

- 2.a Permit to Install 14-05863 for this air contaminant source takes into account the following voluntary restrictions as proposed by the permittee for the purpose of avoiding Best Available Technology (BAT) under OAC rule 3745-31-05(A)(3):
 - i. the use of wet mining of the material and water sprays; and
 - ii. an annual production limitation of 1,000,000 tons of sand and gravel such that the controlled potential to emit for particulate emissions is less than 10.0 tons per year.
- 2.b Fugitive particulate emissions from any transfer point on belt conveyors and from any other emissions point (excluding crushers and truck dumping) where process materials are not saturated, shall not exceed 10 percent opacity, except as provided by rule 40 CFR 60.672.

Issued: 9/5/2006

- 2.c** Fugitive particulate emissions from any crusher shall not exceed 15 percent opacity.
- 2.d** Fugitive particulate emissions from wet screening operations and subsequent screening operations, bucket elevators, and belt conveyors that process saturated material in the production line up to the next crusher, grinding mill or storage bin shall not exceed 0 percent opacity.
- 2.e** Fugitive particulate emissions from screening operations, bucket elevators, and belt conveyors in the production line downstream of wet mining operations, where such screening operations, bucket elevators, and belt conveyors process saturated materials up to the first crusher, grinding mill, or storage bin in the production line shall not exceed 0 percent opacity.
- 2.f** The application and enforcement of the provisions of the New Source Performance Standards (NSPS), as promulgated by the United States Environmental Protection Agency, 40 CFR Part 60, are delegated to the Ohio Environmental Protection Agency. The requirements of 40 CFR Part 60 are also federally enforceable.
- 2.g** The Best Available Technology (BAT) requirements under OAC 3745-31-05(A)(3) do not apply to the PM10 emissions from this air contaminant source since the potential to emit for PM10 is less than ten tons per year.

B. Operational Restrictions

- 1. The maximum annual sand and gravel production rate for emissions unit F001 shall not exceed 1,000,000 tons per year.
- 2. Water sprays shall be operated at points necessary to ensure compliance with the visible emission limitations specified in terms A.2.b, A.2.c, A.2.d and A.2.e for crushing, transfer points, screening, and conveying operations.
- 3. Aggregate product loaded onto trucks shall have a moisture content sufficient to minimize visible emissions of fugitive dust and the loading drop height shall not exceed fifteen (15) feet.

C. Monitoring and/or Recordkeeping Requirements

- 1. The permittee shall maintain monthly records of the amount of sand and gravel

produced in emissions unit F001.

D. Reporting Requirements

1. The permittee shall submit annual reports to Hamilton County Department of Environmental Services that identify any exceedances of the annual sand and gravel production limitation, as well as the corrective actions that were taken to achieve compliance. If no exceedances occurred, then the permittee shall state so in the report. These reports shall be submitted by January 31 of each year.
2. A screening operation, bucket elevator, or belt conveyor that processes saturated material and is subject to 40 CFR 60.672(h) and subsequently processes unsaturated material shall submit a report of this change within 30 days following such change to the Hamilton County Department of Environmental Services. This screening operation, bucket elevator, or belt conveyor is then subject to the 10 percent opacity limit in 40 CFR 60.672(b) and the emission test requirements of 40 CFR 60.11 and 60.675. A screening operation, bucket elevator, or belt conveyor that processes unsaturated material but subsequently processes saturated material shall submit a report of this change within 30 days following such change. This screening operation, bucket elevator, or belt conveyor is then subject to the no visible emission limit in 40 CFR 60.672(h).
3. Pursuant to the NSPS, the source owner/operator is hereby advised of the requirement to report the following at the appropriate times:
 - a. Construction date (no later than 30 days after such date);
 - b. Actual start-up date (within 15 days after such date); and
 - c. Date of performance testing (if required, at least 30 days prior to testing).

Reports are to be sent to:

Ohio Environmental Protection Agency
DAPC - Permit Management Unit
P. O. Box 1049
Columbus, Ohio 43216-1049

and

Hamilton County Department of Environmental Services

Issued: 9/5/2006

250 William Howard Taft Road
Cincinnati, Ohio 45219

4. The permittee shall submit written reports of the results of all performance tests conducted to demonstrate compliance with the standards in 40 CFR 60.672 of Subpart OOO, including reports of observations using Method 9 to demonstrate compliance with term and condition A.2.b, A.2.c, A.2.d and A.2.e of this permit.

A comprehensive written report on the results of the emissions test(s) shall be signed by the person or persons responsible for the tests and submitted within 30 days following completion of the test(s).

E. Testing Requirements

1. The permittee shall conduct, or have conducted, fugitive particulate emission testing for emissions unit F001 in accordance with the following requirements:
 - a. The emission testing shall be conducted within 60 days after achieving maximum production but no later than 180 days after startup.
 - b. The emission testing shall be conducted to demonstrate compliance with 40 CFR 60 Subpart OOO;
 - c. Compliance with the opacity limits of this permit shall be determined by using US EPA Reference Test Method 9. The minimum distance between the observer and the emission source shall be 4.57 meters (15 feet).
 - d. The test(s) shall be conducted while the emissions unit is operating at or near its maximum capacity, unless otherwise specified or approved by the appropriate Ohio EPA District Office or local air agency;

Not later than 30 days prior to the proposed test date(s), the permittee shall submit an "Intent to Test" notification to the appropriate Ohio EPA District Office or local air agency.

The "Intent to Test" notification shall describe in detail the proposed test methods and procedures, the emissions unit operating parameters, the time(s) and date(s) of the test(s), and the person(s) who will be conducting the test(s). Failure to submit such notification for review and approval prior to the test(s) may result in the Ohio EPA District Office's or local air agency's refusal to accept

Issued: 9/5/2006

the results of the emission test(s).

Personnel from the appropriate Ohio EPA District Office or local air agency shall be permitted to witness the test(s), examine the testing equipment, and acquire data and information necessary to ensure that the operation of the emissions unit and the testing procedures provide a valid characterization of the emissions from the emissions unit and/or the performance of the control equipment.

A comprehensive written report on the results of the emissions test(s) shall be signed by the person or persons responsible for the tests and submitted to the appropriate Ohio EPA District Office or local air agency within 30 days following completion of the test(s).

2. Compliance with the emission limitation in Sections A.1 and A.2 of these terms and conditions shall be determined in accordance with the following method(s):

Emission Limitation:

Controlled potential to emit for particulate emissions is less than 10.0 tons per year.

Emissions Unit ID: **F001**

Applicable Compliance Method:

Emissions shall be calculated and compliance determined by using the following equations:

$$\text{lbs PE/hr} = [(A) * (D)] + [(B) * (D)] + [(C) * (D)]$$

where,

A = Particulate emission factor for controlled conveyor transfer point, pounds per ton of material throughput, from AP-42, Section 11.19.2, (August, 2004).

B = Particulate emission factor for controlled screening, pounds per ton of material throughput, from AP-42, Section 11.19.2, (August, 2004).

C = Particulate emission factor for controlled tertiary crushing, pounds per ton of material throughput, from AP-42, Section 11.19.2, (August, 2004).

D = Total hourly throughput, tons.

3. Compliance with the production limitation in term B.1 shall be determined by the recordkeeping in term C.1.
4. Compliance with the opacity limitations in terms and conditions A.2.b. through A.2.e. shall be determined in accordance with Test Method 9 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources.")

F. Miscellaneous Requirements

1. The terms and conditions of this Permit To Install for emissions unit F001 supersede the terms and conditions of Permit To Install 14-05509 which was issued April 1, 2004 and had expired prior to the commencement of construction.

Issued: 9/5/2006

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)**A. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

Operations, Property, and/or Equipment - (F003) - Load - in and load - out of storage piles and wind erosion from storage piles

Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
OAC rule 3745-31-02(A)(2)	See term A.2.f
OAC rule 3745-17-07(B)(6)	There shall be no visible particulate emissions from any material storage pile except for a period of thirteen minutes during any sixty minute observation period.
OAC rule 3745-17-08(B)	Best available control measures that are sufficient to minimize or eliminate visible emissions of fugitive dust (see terms and conditions A.2.b - A.2.e)
ORC 3704.03(T)(4)	See term A.2.g.

2. Additional Terms and Conditions

- 2.a The storage piles that are covered by this permit and subject to the above-mentioned requirements are listed below:

All

- 2.b The permittee shall employ best available control measures on all load-in and load-out operations associated with the storage piles for the purpose of ensuring compliance with the above-mentioned applicable requirements. In accordance with the permittee's permit application, the permittee has committed to reduced drop height of front end loaders and maintaining aggregate material in a moist condition to ensure compliance. Nothing in this paragraph shall prohibit the permittee from employing other control measures to ensure compliance.
- 2.c The above-mentioned control measure(s) shall be employed for each load-in

Emissions Unit ID: **F003**

and load-out operation of each storage pile if the permittee determines, as a result of the inspection conducted pursuant to the monitoring section of this permit, that the control measure(s) are necessary to ensure compliance with the above-mentioned applicable requirements. Any required implementation of the control measure(s) shall continue during any such operation until further observation confirms that use of the measure(s) is unnecessary.

- 2.d** The permittee shall employ best available control measures for wind erosion from the surfaces of all storage piles for the purpose of ensuring compliance with the above-mentioned applicable requirements. In accordance with the permittee's permit application, the permittee has committed to maintaining aggregate material in a moist condition to ensure compliance. Nothing in this paragraph shall prohibit the permittee from employing other control measures to ensure compliance.
- 2.e** The above-mentioned control measure(s) shall be employed for wind erosion from each pile if the permittee determines, as a result of the inspection conducted pursuant to the monitoring section of this permit, that the control measure(s) are necessary to ensure compliance with the above-mentioned applicable requirements. Implementation of the control measure(s) shall not be necessary for a storage pile that is covered with snow and/or ice or if precipitation has occurred that is sufficient for that day to ensure compliance with the above-mentioned applicable requirements.
- 2.f** Implementation of the above-mentioned control measures in accordance with the terms and conditions of this permit, throughput limitations, visible emissions limitations and compliance with specified emission limits is appropriate and sufficient to satisfy the requirements of OAC rules 3745-17-08.
- 2.g** The Best Available Technology (BAT) requirements under OAC 3745-31-05(A)(3) do not apply to the PM10 emissions from this air contaminant source since the calculated annual emission rate for PM10 is less than ten tons per year taking into account the federally enforceable rule requirements of Reasonably Available Control Techniques under OAC rule 3745-17-08.
- 2.h** Permit to Install 14-05863 for this air contaminant source takes into account the following voluntary restrictions as proposed by the permittee for the purpose of avoiding Best Available Technology (BAT) under OAC rule 3745-31-05(A)(3) for particulate emissions:
- i. the use of wet mining of the material and water sprays; and

Issued: 9/5/2006

- ii. an annual production limitation of 1,000,000 tons of sand and gravel such that the controlled potential to emit for particulate emissions is less than 10.0 tons per year.

B. Operational Restrictions

- 1. The maximum annual throughput in this emissions unit is limited to 1,000,000 tons per year based on the permitted production limitation established for the aggregate processing plant (emissions unit F001).

C. Monitoring and/or Recordkeeping Requirements

- 1. Except as otherwise provided in this section, the permittee shall perform inspections of each load-in operation at each storage pile in accordance with the following frequencies:

<u>storage pile identification</u>	<u>minimum load-in inspection frequency</u>
All	Weekly

- 2. Except as otherwise provided in this section, the permittee shall perform inspections of each load-out operation at each storage pile in accordance with the following frequencies:

<u>storage pile identification</u>	<u>minimum load-out inspection frequency</u>
All	Weekly

- 3. Except as otherwise provided in this section, the permittee shall perform inspections of the wind erosion from pile surfaces associated with each storage pile in accordance with the following frequencies:

Issued: 9/5/2006

<u>storage pile identification</u>	<u>minimum wind erosion inspection frequency</u>
------------------------------------	--

All	Weekly
-----	--------

4. No inspection shall be necessary for wind erosion from the surface of a storage pile when the pile is covered with snow and/or ice and for any storage pile activity if precipitation has occurred that is sufficient for that day to ensure compliance with the above-mentioned applicable requirements. Any required inspection that is not performed due to any of the above identified events shall be performed as soon as such event(s) has (have) ended, except if the next required inspection is within one week.
5. The purpose of the inspections is to determine the need for implementing the control measures specified in this permit for load-in and load-out of a storage pile, and wind erosion from the surface of a storage pile. The inspections shall be performed during representative, normal storage pile operating conditions.
6. The permittee may, upon receipt of written approval from the Hamilton County Department of Environmental Services, modify the above-mentioned inspection frequencies if operating experience indicates that less frequent inspections would be sufficient to ensure compliance with the above-mentioned applicable requirements.
7. The permittee shall maintain records of the following information:
 - a. the date and reason any required inspection was not performed, including those inspections that were not performed due to snow and/or ice cover or precipitation;
 - b. the date of each inspection where it was determined by the permittee that it was necessary to implement the control measures;
 - c. the dates the control measures were implemented; and
 - d. on a calendar quarter basis, the total number of days the control measures were implemented and, for wind erosion from pile surfaces, the total number of days where snow and/or ice cover or precipitation were sufficient to not require the control measure(s).

The information required in 7.d. shall be kept separately for (i) the load-in operations, (ii) the load-out operations, and (iii) the pile surfaces (wind erosion), and shall be updated on a calendar quarter basis within 30 days after the end of each calendar quarter.

D. Reporting Requirements

1. The permittee shall submit deviation reports that identify any of the following occurrences:
 - a. each day during which an inspection was not performed by the required frequency, excluding an inspection which was not performed due to an exemption for snow and/or ice cover or precipitation; and
 - b. each instance when a control measure, that was to be implemented as a result of an inspection, was not implemented.
2. The deviation reports shall be submitted in accordance with the reporting requirements of the General Terms and Conditions of this permit.

E. Testing Requirements

1. Compliance with the emission limitation(s) in Section A.1 of these terms and conditions shall be determined in accordance with the following method(s):

Emission Limitation:

There shall be no visible particulate emissions from any material storage pile except for a period of thirteen minutes during any sixty minute observation period.

Applicable Compliance Method:

Compliance shall be determined in accordance with Test Method 22 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources"), as such Appendix existed on July 1, 2002, and the modifications listed in paragraphs (B)(4)(a) through (B)(4)(d) of OAC rule 3745-17-03.

Issued: 9/5/2006

Emissions Limitation:

Controlled potential to emit for particulate emissions is less than 10.0 tons per year.

Applicable Compliance Method:

Emissions shall be calculated and compliance determined by using the following equations:

$$\text{tons PE/yr} = [(A) * (C) * (D) * 0.0005] + [(B) * (C) * (D) * 0.0005] + [(E) * (F) * (D)]$$

where,

- A = PM (particulate matter) emissions factor for storage pile load-in, pounds per ton of material handled, calculated from AP-42, Section 13.2.4, (January, 1995).
- B = PM emissions factor for storage pile load-out, pounds per ton of material handled, calculated from AP-42, Section 13.2.4, (January, 1995).
- C = Total annual tons material handled
- D = Total control efficiency of 50 percent, expressed as a decimal, from wet suppression.
- E = Annual PM emissions from wind erosion, tons, calculated from AP-42, Section 13.2.5 (January, 1995).
- F = Number of storage piles.

F. Miscellaneous Requirements

1. The terms and conditions of this Permit To Install for emissions unit F003 supersede the terms and conditions of Permit To Install 14-05509 which was issued April 1, 2004 and expired prior to the commencement of construction.