



State of Ohio Environmental Protection Agency

**RE: FINAL PERMIT TO INSTALL MODIFICATION
BUTLER COUNTY**

CERTIFIED MAIL

Street Address:

122 S. Front Street

Lazarus Gov. Center TELE: (614) 644-3020 FAX: (614) 644-2329

Mailing Address:

Lazarus Gov. Center
P.O. Box 1049

**Application No: 14-05524
Fac ID: 1409030600**

DATE: 8/12/2004

O Gara-Hess and Eisenhardt Armoring
Jerry LaFayette
9113 Le Saint Drive
Fairfield, OH 45014

Enclosed Please find a modification to the Ohio EPA Permit To Install referenced above which will modify the terms and conditions.

You are hereby notified that this action by the Director is final and may be appealed to the Ohio Environmental Review Appeals Commission pursuant to Chapter 3745.04 of the Ohio Revised Code. The appeal must be in writing and set forth the action complained of and the grounds upon which the appeal is based. It must be filed within thirty (30) days after the notice of the Directors action. A copy of the appeal must be served on the Director of the Ohio Environmental Protection Agency within three (3) days of filing with the Commission. An appeal may be filed with the Environmental Review Appeals Commission at the following address:

Environmental Review Appeals Commission
309 South Fourth Street, Room 222
Columbus, Ohio 43215

Sincerely,

Michael W. Ahern, Manager
Permit Issuance and Data Management Section
Division of Air Pollution Control

cc: USEPA

HCDES



STATE OF OHIO ENVIRONMENTAL PROTECTION AGENCY

**Permit To Install
Terms and Conditions**

**Issue Date: 8/12/2004
Effective Date: 8/12/2004**

FINAL ADMINISTRATIVE MODIFICATION OF PERMIT TO INSTALL 14-05524

Application Number: 14-05524
Facility ID: 1409030600
Permit Fee: **\$200**
Name of Facility: O Gara-Hess and Eisenhardt Armoring
Person to Contact: Jerry LaFayette
Address: 9113 Le Saint Drive
Fairfield, OH 45014

Location of proposed air contaminant source(s) [emissions unit(s)]:
**9113 Le Saint Drive
Fairfield, Ohio**

Description of proposed emissions unit(s):
Administrative Modification to PTI 14-05524 to reflect reduced VOC emissions from paint booths K007 and K008.

The above named entity is hereby granted a modification to the permit to install described above pursuant to Chapter 3745-31 of the Ohio Administrative Code. Issuance of this modification does not constitute expressed or implied approval or agreement that, if constructed or modified in accordance with the plans included in the application, the above described source(s) of environmental pollutants will operate in compliance with applicable State and Federal laws and regulations, and does not constitute expressed or implied assurance that if constructed or modified in accordance with those plans included in the application, the above described source(s) of pollutants will be granted the necessary operating permits.

This permit is granted subject to the conditions attached hereto.


Ohio Environmental Protection Agency

Director

Part I - GENERAL TERMS AND CONDITIONS

A. Permit to Install General Terms and Conditions

1. Compliance Requirements

The emissions unit(s) identified in this Permit to Install shall remain in full compliance with all applicable State laws and regulations and the terms and conditions of this permit.

2. Reporting Requirements

The permittee shall submit required reports in the following manner:

- a. Reports of any required monitoring and/or record keeping information shall be submitted to the appropriate Ohio EPA District Office or local air agency.
- b. Except as otherwise may be provided in the terms and conditions for a specific emissions unit, quarterly written reports of (a) any deviations (excursions) from emission limitations, operational restrictions, and control device operating parameter limitations that have been detected by the testing, monitoring, and record keeping requirements specified in this permit, (b) the probable cause of such deviations, and (c) any corrective actions or preventive measures which have been or will be taken, shall be submitted to the appropriate Ohio EPA District Office or local air agency. If no deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted quarterly, i.e., by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters. (These quarterly reports shall exclude deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06.)

3. Records Retention Requirements

Each record of any monitoring data, testing data, and support information required pursuant to this permit shall be retained for a period of five years from the date the record was created. Support information shall include, but not be limited to, all calibration and maintenance records and all original strip-chart recordings for continuous monitoring instrumentation, and copies of all reports required by this permit. Such records may be maintained in computerized form.

4. Inspections and Information Requests

The Director of the Ohio EPA, or an authorized representative of the Director, may, subject to the safety requirements of the permittee and without undue delay, enter upon the premises of this source at any reasonable time for purposes of making inspections, conducting tests, examining records or reports pertaining to any emission of air contaminants, and determining compliance with any applicable State air pollution laws and regulations and the terms and conditions of this permit. The permittee shall furnish to the Director of the Ohio EPA, or an authorized

representative of the Director, upon receipt of a written request and within a reasonable time, any information that may be requested to determine whether cause exists for modifying, reopening or revoking this permit or to determine compliance with this permit. Upon verbal or written request, the permittee shall also furnish to the Director of the Ohio EPA, or an authorized representative of the Director, copies of records required to be kept by this permit.

5. Scheduled Maintenance/Malfunction Reporting

Any scheduled maintenance of air pollution control equipment shall be performed in accordance with paragraph (A) of OAC rule 3745-15-06. The malfunction of any emissions units or any associated air pollution control system(s) shall be reported to the appropriate Ohio EPA District Office or local air agency in accordance with paragraph (B) of OAC rule 3745-15-06. Except as provided in that rule, any scheduled maintenance or malfunction necessitating the shutdown or bypassing of any air pollution control system(s) shall be accompanied by the shutdown of the emissions unit(s) that is (are) served by such control system(s).

6. Permit Transfers

Any transferee of this permit shall assume the responsibilities of the prior permit holder. The appropriate Ohio EPA District Office or local air agency must be notified in writing of any transfer of this permit.

7. Air Pollution Nuisance

The air contaminants emitted by the emissions units covered by this permit shall not cause a public nuisance, in violation of OAC rule 3745-15-07.

8. Termination of Permit to Install

This Permit to Install shall terminate within eighteen months of the effective date of the Permit to Install if the owner or operator has not undertaken a continuing program of installation or modification or has not entered into a binding contractual obligation to undertake and complete within a reasonable time a continuing program of installation or modification. This deadline may be extended by up to 12 months if application is made to the Director within a reasonable time before the termination date and the party shows good cause for any such extension.

9. Construction of New Sources(s)

The proposed emissions unit(s) shall be constructed in strict accordance with the plans and application submitted for this permit to the Director of the Ohio Environmental Protection Agency. There may be no deviation from the approved plans without the express, written approval of the Agency. Any deviations from the approved plans or the above conditions may lead to such sanctions and penalties as provided under Ohio law. Approval of these plans does not constitute an assurance that the proposed facilities will operate in compliance with all Ohio laws and regulations. Additional facilities shall be installed upon orders of the Ohio

O Gara-Hess and Eisenhardt Armoring
PTI Application: 14-05524
Modification Issued: 8/12/2004

Facility ID: 1409030600

Environmental Protection Agency if the proposed sources cannot meet the requirements of this permit or cannot meet applicable standards.

If the construction of the proposed emissions unit(s) has already begun or has been completed prior to the date the Director of the Environmental Protection Agency approves the permit application and plans, the approval does not constitute expressed or implied assurance that the proposed facility has been constructed in accordance with the approved plans. The action of beginning and/or completing construction prior to obtaining the Director's approval constitutes a violation of OAC rule 3745-31-02. Furthermore, issuance of the Permit to Install does not constitute an assurance that the proposed source will operate in compliance with all Ohio laws and regulations. Approval of the plans in any case is not to be construed as an approval of the facility as constructed and/or completed. Moreover, issuance of the Permit to Install is not to be construed as a waiver of any rights that the Ohio Environmental Protection Agency (or other persons) may have against the applicant for starting construction prior to the effective date of the permit. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed facilities cannot meet the requirements of this permit or cannot meet applicable standards.

10. Public Disclosure

The facility is hereby notified that this permit, and all agency records concerning the operation of this permitted source, are subject to public disclosure in accordance with OAC rule 3745-49-03.

11. Applicability

This Permit To Install is applicable only to the emissions unit(s) identified in the Permit To Install. Separate Permit To Install for the installation or modification of any other emissions unit(s) are required for any emissions unit for which a Permit To Install is required.

12. Best Available Technology

As specified in OAC Rule 3745-31-05, all new sources must employ Best Available Technology (BAT). Compliance with the terms and conditions of this permit will fulfill this requirement.

13. Source Operation and Operating Permit Requirements After Completion of Construction

This facility is permitted to operate each source described by this Permit to Install for a period of up to one year from the date the source commenced operation. This permission to operate is granted only if the facility complies with all requirements contained in this permit and all applicable air pollution laws, regulations, and policies. Pursuant to OAC Chapter 3745-35, the

O Gara-Hess and Eisenhardt Armoring
PTI Application: 14-05524
Modification Issued: 8/12/2004

Facility ID: 1409030600

permittee shall submit a complete operating permit application within ninety (90) days after commencing operation of the emissions unit(s) covered by this permit.

14. Construction Compliance Certification

The applicant shall provide Ohio EPA with a written certification (see enclosed form) that the facility has been constructed in accordance with the Permit to Install application and the terms and conditions of the Permit to Install. The certification shall be provided to Ohio EPA upon completion of construction but prior to startup of the source.

15. Fees

The permittee shall pay fees to the Director of the Ohio EPA in accordance with ORC section 3745.11 and OAC Chapter 3745-78. The permittee shall pay all applicable Permit to Install fees within 30 days after the issuance of this Permit to Install.

B. Permit to Install Summary of Allowable Emissions

The following information summarizes the total allowable emissions, by pollutant, based on the individual allowable emissions of each air contaminant source identified in this permit.

SUMMARY (for informational purposes only)
TOTAL PERMIT TO INSTALL ALLOWABLE EMISSIONS

<u>Pollutant</u>	<u>Tons Per Year</u>
VOC	28.10

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

- 1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
K007 - Paint Booth - Modification	OAC rule 3745-31-05(A)(3)	148.64 lbs VOC/day 14.05 TPY VOC See terms and conditions A.2.a, A.2.b, B.1 and B.2. The requirements of this rule also include compliance with the requirements of OAC rule 3745-31-05(C).
	OAC rule 3745-21-09(U)(1)	Exempt per OAC rule 3745-21-09(U)(2)(c).
	OAC rule 3745-31-05(C)	See term and condition A.2.c.

2. Additional Terms and Conditions

- 2.a The VOC content of any coating employed in this emissions unit shall not exceed 3.72 pounds of VOC per gallon, as applied.
- 2.b The VOC content of any cleanup material employed in this emissions unit shall not exceed 7.4 pounds of VOC per gallon, as applied.
- 2.c The total allowable emissions of Hazardous Air Pollutants (HAPs), as identified in Section 112(b) of Title III of the Clean Air Act, from emissions units K001 (Commercial Vehicle

Emissions Unit ID: **K007**

Paint Booth), K002 (Small Parts Paint Booth), K005(Parts and Touch-up Booth), K007 (Paint Spray Booth), K008 (Paint Spray Booth) and K009 (Paint Spray Booth) shall not exceed 9.9 TPY for any single HAP and 24.9 TPY for the total of all HAPs. Compliance with the above limitations shall be based on a rolling, 12-month summation.

The permittee has existing records to demonstrate compliance with the rolling, 12-month summation limit upon issuance of the permit.

- 2.d** Compliance with OAC rule 3745-31-05(A)(3) shall be demonstrated by the specified mass emission limits, coating and cleanup material VOC content limitations and the usage limitations.

B. Operational Restrictions

1. The maximum amount of coatings employed shall not exceed 32.0 gallons per day and 6048 gallons per year.
2. The maximum amount of cleanup materials employed shall not exceed 4.0 gallons per day and 756 gallons per year.

C. Monitoring and/or Record keeping Requirements

1. The permittee shall maintain daily records of the following:
 - a. The company identification of each coating and cleanup material employed;
 - b. The number of gallons of each coating and cleanup material employed;
 - c. The volatile organic compound (VOC) content of each coating and cleanup material employed, in lbs/gallon, as applied;
 - d. The VOC emissions from each coating and cleanup material employed, i.e., (b)x(c), in pounds;
 - e. The total VOC emissions from this emissions unit, i.e., the sum of (d) for all coatings and cleanup materials employed, in pounds; and
 - f. The total gallons of all coatings employed.
 - g. The total gallons of all cleanup materials employed.

Modification Issued: 8/12/2004

2. The permittee shall collect and record the following information each month for emissions units K001, K002, K005, K007, K008 and K009:
 - a. The name and identification number of each coating, employed;
 - b. The individual Hazardous Air Pollutant (HAP) content for each HAP of each coating in pounds of individual HAP per gallon of coating, as applied;
 - c. The total combined HAP content of each coating in pounds of combined HAPs per gallon of coating, as applied [sum all the individual HAP contents from (b)];
 - d. The number of gallons of each coating employed;
 - e. The name and identification of each cleanup material employed;
 - f. The individual HAP content for each HAP of each cleanup material, in pounds of individual HAP per gallon of cleanup material, as applied;
 - g. The total combined HAP content of each cleanup material, in pounds of combined HAPs per gallon of cleanup material, as applied [sum all the individual HAP contents from (f)];
 - h. The number of gallons of each cleanup material employed;
 - i. The total individual HAP emissions for each HAP from all coatings and cleanup materials employed, in pounds or tons per month [for each HAP the sum of (b) times (d) for each coating plus the sum of (f) times (h) for each cleanup material];
 - j. The total combined HAP emissions from all coatings and cleanup materials employed, in pounds or tons per month [the sum of (c) times (d) for each coating plus the sum of (g) times (h) for each cleanup material];
 - k. The updated rolling, 12-month summation of emissions for each individual HAP emissions, in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months.
 - l. The updated rolling, 12-month summation of emissions for total combined HAP emissions, in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months.
3. The permittee shall maintain monthly records of the total coating usage for each month.

4. The permittee shall maintain monthly records of the total cleanup material usage for each month.
5. The permit to install for this emissions unit (K007) was evaluated based on the actual materials and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Ground-Level Concentration (MAGLC).

The following summarizes the results of the modeling for the "worst case" pollutant(s):

Pollutant 1: Butyl Acetate

TLV (ug/m³): 712,600

Maximum Hourly Emission Rate (lbs/hr): 6.84

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m³): 245.4

MAGLC (ug/m³): 16,967

Pollutant 2: Methyl Isoamyl Ketone

TLV (ug/m³): 233,500

Maximum Hourly Emission Rate (lbs/hr): 41.0

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m³): 1471

MAGLC (ug/m³): 5560

Physical changes to or in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxics Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in the "Air Toxic Policy" include the following:

- a. Changes in the composition of the materials used, or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value previously modeled;
- b. Changes in the composition of the materials, or use of new materials, that would result in

an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and

- c. Physical changes to the emissions unit or its exhaust parameters (e.g., increased/decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Air Toxic Policy" will be satisfied with the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01(AAA)(1)(a)(ii), and a modification of the existing permit to install will not be required. If the change(s) is(are) defined as a modification under other provisions of the modification definition [other than (AAA)(1)(a)(ii)], then the permittee shall obtain a final permit to install prior to the

change. The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will satisfy the "Air Toxic Policy":

- a. A description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
- b. Documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and
- c. When the computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

D. Reporting Requirements

1. The permittee shall submit quarterly deviation reports which identify any exceedance of the HAP emission limitations set forth in term and condition A.2.c.

The reports shall be submitted to the Director (the Hamilton County Department of Environmental Services) by January 31, April 30, July 31 and October 31 of each year and shall cover the previous three calendar months (October through December, January through March, April through June and July through September, respectively) .

If no exceedances occurred, the permittee shall state so in the report.

2. The permittee shall notify the Hamilton County Department of Environmental Services in writing of any daily record showing an exceedance of the coating and cleanup material usage limit, the daily VOC emission limit, or the VOC content limit. A copy of such record shall be sent to the

Director within 45 days after the exceedance occurs.

3. The permittee shall submit annual reports to the Hamilton County Department of Environmental Services which specify the total VOC emissions and the total coating and cleanup material usage from this emissions unit for the previous calendar year. These reports shall be submitted by January 31 of each year and shall cover the previous calendar year.

E. Testing Requirements

1. Emissions Limitation:

148.64 lbs VOC/day

14.05 TPY VOC

Applicable Compliance Method:

Compliance with the emissions limits cited in term and condition A.1 shall be demonstrated by the record keeping in term and condition C.1.

2. Compliance with the VOC content limitation for the coating and cleanup materials cited in term and condition A.2.a and A.2.b shall be demonstrated by the record keeping in term and condition C.1.

USEPA methods 24 and 24A shall be used to determine the VOC content for coatings and cleanup materials, respectively. If, pursuant to 40 CFR Part 60, Appendix A, an owner or operator determines that Method 24 or 24A cannot be used for a particular coating or cleanup material, the permittee shall so notify the Administrator of the USEPA and shall use formulation data for that coating or cleanup material to demonstrate compliance until the USEPA provides alternative analytical procedures or alternative precision statements for Method 24 or 24A.

3. Compliance with the HAP emissions limitations in term and condition A.2.c shall be demonstrated by the record keeping in term and condition C.2.
4. Compliance with the coating and cleanup material usage limits cited in terms and conditions B.1 and B.2 shall be demonstrated by the record keeping in terms and conditions C.1 ,C3 and C.4.

F. Miscellaneous Requirements

1. The terms and conditions of this Permit To Install Modification supercede the terms and conditions of Permit To Install 14-05524, as issued on January 29, 2004.

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
K008 - Paint Booth - Modification	OAC rule 3745-31-05(A)(3)	148.64 lbs VOC/day 14.05 TPY VOC See terms and conditions A.2.a, A.2.b, B.1 and B.2. The requirements of this rule also include compliance with the requirements of OAC rule 3745-31-05(C).
	OAC rule 3745-21-09(U)(1)	Exempt per OAC rule 3745-21-09(U)(2)(c).
	OAC rule 3745-31-05(C)	See term and condition A.2.c.

2. Additional Terms and Conditions

- 2.a The VOC content of any coating employed in this emissions unit shall not exceed 3.72 pounds of VOC per gallon, as applied.
- 2.b The VOC content of any cleanup material employed in this emissions unit shall not exceed 7.4 pounds of VOC per gallon, as applied.
- 2.c The total allowable emissions of Hazardous Air Pollutants (HAPs), as identified in Section

Emissions Unit ID: **K008**

112(b) of Title III of the Clean Air Act, from emissions units K001 (Commercial Vehicle Paint Booth), K002 (Small Parts Paint Booth), K005(Parts and Touch-up Booth), K007 (Paint Spray Booth), K008 (Paint Spray Booth) and K009 (Paint Spray Booth) shall not exceed 9.9 TPY for any single HAP and 24.9 TPY for the total of all HAPs. Compliance with the above limitations shall be based on a rolling, 12-month summation.

The permittee has existing records to demonstrate compliance with the rolling, 12-month summation limit upon issuance of the permit.

- 2.d** Compliance with OAC rule 3745-31-05(A)(3) shall be demonstrated by the specified mass emission limits, coating and cleanup material VOC content limitations and the usage limitations.

B. Operational Restrictions

1. The maximum amount of coatings employed shall not exceed 32.0 gallons per day and 6048 gallons per year.
2. The maximum amount of cleanup materials employed shall not exceed 4.0 gallons per day and 756 gallons per year.

C. Monitoring and/or Record keeping Requirements

1. The permittee shall maintain daily records of the following:
 - a. The company identification of each coating and cleanup material employed;
 - b. The number of gallons of each coating and cleanup material employed;
 - c. The volatile organic compound (VOC) content of each coating and cleanup material employed, in lbs/gallon, as applied;
 - d. The VOC emissions from each coating and cleanup material employed, i.e., (b)x(c), in pounds;
 - e. The total VOC emissions from this emissions unit, i.e., the sum of (d) for all coatings and cleanup materials employed, in pounds; and
 - f. The total gallons of all coatings employed.
 - g. The total gallons of all cleanup materials employed.

2. The permittee shall collect and record the following information each month for emissions units K001, K002, K005, K007, K008 and K009:
 - a. The name and identification number of each coating, employed;
 - b. The individual Hazardous Air Pollutant (HAP) content for each HAP of each coating in pounds of individual HAP per gallon of coating, as applied;
 - c. The total combined HAP content of each coating in pounds of combined HAPs per gallon of coating, as applied [sum all the individual HAP contents from (b)];
 - d. The number of gallons of each coating employed;
 - e. The name and identification of each cleanup material employed;
 - f. The individual HAP content for each HAP of each cleanup material, in pounds of individual HAP per gallon of cleanup material, as applied;
 - g. The total combined HAP content of each cleanup material, in pounds of combined HAPs per gallon of cleanup material, as applied [sum all the individual HAP contents from (f)];
 - h. The number of gallons of each cleanup material employed;
 - i. The total individual HAP emissions for each HAP from all coatings and cleanup materials employed, in pounds or tons per month [for each HAP the sum of (b) times (d) for each coating plus the sum of (f) times (h) for each cleanup material];
 - j. The total combined HAP emissions from all coatings and cleanup materials employed, in pounds or tons per month [the sum of (c) times (d) for each coating plus the sum of (g) times (h) for each cleanup material];
 - k. The updated rolling, 12-month summation of emissions for each individual HAP emissions, in pounds or tons. This shall include the information for the current month and the preceeding eleven calender months.
 - l. The updated rolling, 12-month summation of emissions for total combined HAP emissions, in pounds or tons. This shall include the information for the current month and the preceeding eleven calender months.

Modification Issued: 8/12/2004

3. The permittee shall maintain monthly records of the total coating usage for each month.
4. The permittee shall maintain monthly records of the total cleanup material usage for each month.
5. The permit to install for this emissions unit (K008) was evaluated based on the actual materials and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Ground-Level Concentration (MAGLC).

The following summarizes the results of the modeling for the "worst case" pollutant(s):

Pollutant 1: Butyl Acetate

TLV (ug/m³): 712,600

Maximum Hourly Emission Rate (lbs/hr): 6.84

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m³): 245.4

MAGLC (ug/m³): 16,967

Pollutant 2: Methyl Isoamyl Ketone

TLV (ug/m³): 233,500

Maximum Hourly Emission Rate (lbs/hr): 41.0

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m³): 1471

MAGLC (ug/m³): 5560

Physical changes to or in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxics Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in the "Air Toxic Policy" include the following:

- a. Changes in the composition of the materials used, or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value previously

modeled;

- b. Changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and
- c. Physical changes to the emissions unit or its exhaust parameters (e.g., increased/decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Air Toxic Policy" will be satisfied with the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01(AAA)(1)(a)(ii), and a modification of the existing permit to install will not be required. If the change(s) is(are) defined as a modification under other provisions of the modification definition [other than (AAA)(1)(a)(ii)], then the permittee shall obtain a final permit to install prior to the change. The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will satisfy the "Air Toxic Policy":

- a. A description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
- b. Documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and
- c. When the computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

D. Reporting Requirements

1. The permittee shall submit quarterly deviation reports which identify any exceedance of the HAP emission limitations set forth in term and condition A.2.c.

The reports shall be submitted to the Director (the Hamilton County Department of Environmental Services) by January 31, April 30, July 31 and October 31 of each year and shall cover the previous three calendar months (October through December, January through March, April through June and July through September, respectively) .

If no exceedances occurred, the permittee shall state so in the report.

2. The permittee shall notify the Hamilton County Department of Environmental Services in writing of any daily record showing an exceedance of the coating and cleanup material usage limit, the

Emissions Unit ID: **K008**

daily VOC emission limit, or the VOC content limit. A copy of such record shall be sent to the Director within 45 days after the exceedance occurs.

3. The permittee shall submit annual reports to the Hamilton County Department of Environmental Services which specify the total VOC emissions and the total coating and cleanup material usage from this emissions unit for the previous calendar year. These reports shall be submitted by January 31 of each year and shall cover the previous calendar year.

E. Testing Requirements

1. Emissions Limitation:

148.64 lbs VOC/day

14.05 TPY VOC

Applicable Compliance Method:

Compliance with the emissions limits cited in term and condition A.1 shall be demonstrated by the record keeping in term and condition C.1.

2. Compliance with the VOC content limitation for the coating and cleanup materials cited in term and condition A.2.a and A.2.b shall be demonstrated by the record keeping in term and condition C.1.

USEPA methods 24 and 24A shall be used to determine the VOC content for coatings and cleanup materials, respectively. If, pursuant to 40 CFR Part 60, Appendix A, an owner or operator determines that Method 24 or 24A cannot be used for a particular coating or cleanup material, the permittee shall so notify the Administrator of the USEPA and shall use formulation data for that coating or cleanup material to demonstrate compliance until the USEPA provides alternative analytical procedures or alternative precision statements for Method 24 or 24A.

3. Compliance with the HAP emissions limitations in term and condition A.2.c shall be demonstrated by the record keeping in term and condition C.2.
4. Compliance with the coating and cleanup material usage limits cited in terms and conditions B.1 and B.2 shall be demonstrated by the record keeping in terms and conditions C.1, C.3 and C.4.

F. Miscellaneous Requirements

1. The terms and conditions of this Permit To Install Modification supercede the terms and conditions of Permit To Install 14-05524, as issued on January 29, 2004.