



State of Ohio Environmental Protection Agency

**RE: FINAL PERMIT TO INSTALL  
HAMILTON COUNTY**

**CERTIFIED MAIL**

Street Address:

50 West Town Street, Suite 700

Lazarus Gov. Center TELE: (614) 644-3020 FAX: (614) 644-2329

Mailing Address:

Lazarus Gov. Center  
P.O. Box 1049

**Application No: 14-05968**

**Fac ID: 1431073227**

**DATE: 9/18/2007**

Buckeye Terminals, LLC  
Jason Mengel  
5 TEK Park, 9999 Hamilton Blvd.  
Breinigsville, PA 18031

Enclosed please find an Ohio EPA Permit to Install which will allow you to install the described source(s) in a manner indicated in the permit. Because this permit contains several conditions and restrictions, I urge you to read it carefully.

The Ohio EPA is urging companies to investigate pollution prevention and energy conservation. Not only will this reduce pollution and energy consumption, but it can also save you money. If you would like to learn ways you can save money while protecting the environment, please contact our Office of Pollution Prevention at (614) 644-3469.

You are hereby notified that this action of the Director is final and may be appealed to the Environmental Review Appeals Commission pursuant to Section 3745.04 of the Ohio Revised Code. The appeal must be in writing and set forth the action complained of and the grounds upon which the appeal is based. The appeal must be filed with the Commission within thirty (30) days after notice of the Director's action. The appeal must be accompanied by a filing fee of \$70.00 which the Commission, in its discretion, may reduce if by affidavit you demonstrate that payment of the full amount of the fee would cause extreme hardship. Notice of the filing of the appeal shall be filed with the Director within three (3) days of filing with the Commission. Ohio EPA requests that a copy of the appeal be served upon the Ohio Attorney General's Office, Environmental Enforcement Section. An appeal may be filed with the Environmental Review Appeals Commission at the following address:

Environmental Review Appeals Commission  
309 South Fourth Street, Room 222  
Columbus, OH 43215

Sincerely,

Michael W. Ahern, Manager  
Permit Issuance and Data Management Section  
Division of Air Pollution Control

CC: USEPA

HCDES



---

**Permit To Install  
Terms and Conditions**

**Issue Date: 9/18/2007  
Effective Date: 9/18/2007**

---

**FINAL PERMIT TO INSTALL 14-05968**

Application Number: 14-05968  
Facility ID: 1431073227  
Permit Fee: **\$750**  
Name of Facility: Buckeye Terminals, LLC  
Person to Contact: Jason Mengel  
Address: 5 TEK Park, 9999 Hamilton Blvd.  
Breinigsville, PA 18031

Location of proposed air contaminant source(s) [emissions unit(s)]:  
**5150 River Road  
Cincinnati, Ohio**

Description of proposed emissions unit(s):  
**Modification of an existing 1,260,000 gal fixed roof diesel tank (tank 17) to an internal floating roof gasoline tank.**

The above named entity is hereby granted a Permit to Install for the above described emissions unit(s) pursuant to Chapter 3745-31 of the Ohio Administrative Code. Issuance of this permit does not constitute expressed or implied approval or agreement that, if constructed or modified in accordance with the plans included in the application, the above described emissions unit(s) of environmental pollutants will operate in compliance with applicable State and Federal laws and regulations, and does not constitute expressed or implied assurance that if constructed or modified in accordance with those plans and specifications, the above described emissions unit(s) of pollutants will be granted the necessary permits to operate (air) or NPDES permits as applicable.

This permit is granted subject to the conditions attached hereto.

Ohio Environmental Protection Agency

---

Chris Korleski  
Director

**Buckeye Terminals, LLC**  
**PTI Application: 14-05968**  
**Issued: 9/18/2007**

**Facility ID: 1431073227**

## **Part I - GENERAL TERMS AND CONDITIONS**

### **A. Permit to Install General Terms and Conditions**

#### **1. Compliance Requirements**

The emissions unit(s) identified in this Permit to Install shall remain in full compliance with all applicable State laws and regulations and the terms and conditions of this permit.

#### **2. Reporting Requirements**

The permittee shall submit required reports in the following manner:

- a. Reports of any required monitoring and/or recordkeeping information shall be submitted to the appropriate Ohio EPA District Office or local air agency.
- b. Except as otherwise may be provided in the terms and conditions for a specific emissions unit, quarterly written reports of (a) any deviations (excursions) from emission limitations, operational restrictions, and control device operating parameter limitations that have been detected by the testing, monitoring, and recordkeeping requirements specified in this permit, (b) the probable cause of such deviations, and (c) any corrective actions or preventive measures which have been or will be taken, shall be submitted to the appropriate Ohio EPA District Office or local air agency. If no deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted (i.e., postmarked) quarterly by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters. (These quarterly reports shall exclude deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06.)

#### **3. Records Retention Requirements**

Each record of any monitoring data, testing data, and support information required pursuant to this permit shall be retained for a period of five years from the date the record was created. Support information shall include, but not be limited to, all calibration and maintenance records and all original strip-chart recordings for continuous monitoring instrumentation, and copies of all reports required by this permit. Such records may be maintained in computerized form.

#### **4. Inspections and Information Requests**

The Director of the Ohio EPA, or an authorized representative of the Director, may, subject to the safety requirements of the permittee and without undue delay, enter upon

**Buckeye Terminals, LLC**  
**PTI Application: 14-05968**  
**Issued: 9/18/2007**

**Facility ID: 1431073227**

the premises of this source at any reasonable time for purposes of making inspections, conducting tests, examining records or reports pertaining to any emission of air contaminants, and determining compliance with any applicable State air pollution laws and regulations and the terms and conditions of this permit. The permittee shall furnish to the Director of the Ohio EPA, or an authorized representative of the Director, upon receipt of a written request and within a reasonable time, any information that may be requested to determine whether cause exists for modifying, reopening or revoking this permit or to determine compliance with this permit. Upon verbal or written request, the permittee shall also furnish to the Director of the Ohio EPA, or an authorized representative of the Director, copies of records required to be kept by this permit.

**5. Scheduled Maintenance/Malfunction Reporting**

Any scheduled maintenance of air pollution control equipment shall be performed in accordance with paragraph (A) of OAC rule 3745-15-06. The malfunction of any emissions units or any associated air pollution control system(s) shall be reported to the appropriate Ohio EPA District Office or local air agency in accordance with paragraph (B) of OAC rule 3745-15-06. Except as provided in that rule, any scheduled maintenance or malfunction necessitating the shutdown or bypassing of any air pollution control system(s) shall be accompanied by the shutdown of the emissions unit(s) that is (are) served by such control system(s).

**6. Permit Transfers**

Any transferee of this permit shall assume the responsibilities of the prior permit holder. The appropriate Ohio EPA District Office or local air agency must be notified in writing of any transfer of this permit.

**7. Air Pollution Nuisance**

The air contaminants emitted by the emissions units covered by this permit shall not cause a public nuisance, in violation of OAC rule 3745-15-07.

**8. Termination of Permit to Install**

This Permit to Install shall terminate within eighteen months of the effective date of the Permit to Install if the owner or operator has not undertaken a continuing program of installation or modification or has not entered into a binding contractual obligation to undertake and complete within a reasonable time a continuing program of installation or modification. This deadline may be extended by up to 12 months if application is made to the Director within a reasonable time before the termination date and the party shows good cause for any such extension.

**9. Construction of New Sources(s)**

**Buckeye Terminals, LLC**  
**PTI Application: 14-05968**  
**Issued: 9/18/2007**

**Facility ID: 1431073227**

The proposed emissions unit(s) shall be constructed in strict accordance with the plans and application submitted for this permit to the Director of the Ohio Environmental Protection Agency. There may be no deviation from the approved plans without the express, written approval of the Agency. Any deviations from the approved plans or the above conditions may lead to such sanctions and penalties as provided under Ohio law. Approval of these plans does not constitute an assurance that the proposed facilities will operate in compliance with all Ohio laws and regulations. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed sources cannot meet the requirements of this permit or cannot meet applicable standards.

If the construction of the proposed emissions unit(s) has already begun or has been completed prior to the date the Director of the Environmental Protection Agency approves the permit application and plans, the approval does not constitute expressed or implied assurance that the proposed facility has been constructed in accordance with the approved plans. The action of beginning and/or completing construction prior to obtaining the Director's approval constitutes a violation of OAC rule 3745-31-02. Furthermore, issuance of the Permit to Install does not constitute an assurance that the proposed source will operate in compliance with all Ohio laws and regulations. Approval of the plans in any case is not to be construed as an approval of the facility as constructed and/or completed. Moreover, issuance of the Permit to Install is not to be construed as a waiver of any rights that the Ohio Environmental Protection Agency (or other persons) may have against the applicant for starting construction prior to the effective date of the permit. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed facilities cannot meet the requirements of this permit or cannot meet applicable standards.

#### **10. Public Disclosure**

The facility is hereby notified that this permit, and all agency records concerning the operation of this permitted source, are subject to public disclosure in accordance with OAC rule 3745-49-03.

#### **11. Applicability**

This Permit To Install is applicable only to the emissions unit(s) identified in the Permit To Install. Separate Permit To Install for the installation or modification of any other emissions unit(s) are required for any emissions unit for which a Permit To Install is required.

#### **12. Best Available Technology**

As specified in OAC Rule 3745-31-05, all new sources must employ Best Available Technology (BAT). Compliance with the terms and conditions of this permit will fulfill this requirement.

**Buckeye Terminals, LLC**  
**PTI Application: 14-05968**  
**Issued: 9/18/2007**

**Facility ID: 1431073227**

**13. Source Operation and Operating Permit Requirements After Completion of Construction**

This facility is permitted to operate each source described by this Permit to Install for a period of up to one year from the date the source commenced operation. This permission to operate is granted only if the facility complies with all requirements contained in this permit and all applicable air pollution laws, regulations, and policies. Pursuant to OAC Chapter 3745-35, the permittee shall submit a complete operating permit application within ninety (90) days after commencing operation of the emissions unit(s) covered by this permit.

**14. Construction Compliance Certification**

The applicant shall provide Ohio EPA with a written certification (see enclosed form) that the facility has been constructed in accordance with the Permit to Install application and the terms and conditions of the Permit to Install. The certification shall be provided to Ohio EPA upon completion of construction but prior to startup of the source.

**15. Fees**

The permittee shall pay fees to the Director of the Ohio EPA in accordance with ORC section 3745.11 and OAC Chapter 3745-78. The permittee shall pay all applicable Permit to Install fees within 30 days after the issuance of this Permit to Install.

**B. Permit to Install Summary of Allowable Emissions**

The following information summarizes the total allowable emissions, by pollutant, based on the individual allowable emissions of each air contaminant source identified in this permit.

SUMMARY (for informational purposes only)  
 TOTAL PERMIT TO INSTALL ALLOWABLE EMISSIONS

<u>Pollutant</u>	<u>Tons Per Year</u>
VOC	4.14

7

**Buckeye Terminals, LLC**  
**PTI Application: 14-05968**  
**Issued: 9/18/2007**

**Facility ID: 1431073227**

Issued: 9/18/2007

**PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)****A. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

**Operations, Property, and/or Equipment - (T018) - 1,260,000 gallon internal floating roof petroleum storage tank**

Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
ORC 3704.03(T)(4)	The Best Available Technology (BAT) requirements under OAC rule 3745-31-05(A)(3) do not apply to the volatile organic compound (VOC) emissions from this air contaminant source since the uncontrolled potential to emit for VOC emissions is less than ten tons per year.
OAC rule 3745-31-05(C) Facility is an existing synthetic minor for VOC and HAPs	See terms and conditions A.2.b and A.2.c.
40 CFR Part 60 Subpart Kb	See terms A.2.d, A.2.e, A.2.f.
OAC rule 3745-21-09(L) (when petroleum liquids are stored)	The requirements established pursuant to this rule are equivalent to the requirements of 40 CFR Part 60, Subpart Kb.

**2. Additional Terms and Conditions**

- 2.a The application and enforcement of the provisions of the New Source Performance Standards (NSPS), as promulgated by the United States Environmental Protection Agency, 40 CFR Part 60, are delegated to the Ohio Environmental Protection Agency. The requirements of 40 CFR Part 60 are also federally enforceable.
- 2.b The actual emissions of Hazardous Air Pollutants (HAPs) as identified in Section 112(b) of Title III of the Clean Air Act from emission units B002 (20 mmBtu/hr oil heater), J001 (loading rack), R001 (tank truck loading rack), T001 (40,000 bbl

**Issued: 9/18/2007**

fixed roof storage tank w/submerged fill), T002 (20,000 bbl fixed roof storage tank w/submerged fill), T003 (25,000 bbl fixed roof storage tank w/submerged fill), T004 (25,000 bbl fixed roof storage tank w/submerged fill), T005 (5,000 bbl fixed roof storage tank w/submerged fill), T006 (5,000 bbl fixed roof storage tank w/submerged fill), T007 (2,500 bbl fixed roof storage tank w/submerged fill), T008 (2,500 bbl fixed roof storage tank w/submerged fill), T009 (2,500 bbl fixed roof storage tank w/submerged fill), T010 (2,500 bbl fixed roof storage tank w/submerged fill), T011 (2,500 bbl fixed roof storage tank w/submerged fill), T013 (42,000 gal. floating roof petro tank), T014 (2.73 MM gallon storage tank), T015 (1.26 MM gallon storage tank), T016 (2.10 MM gallon storage tank), T017 (1.26 MM gallon storage tank), T018 (1.26 MM gallon storage tank), T019 (2.10 MM gallon storage tank), T020 (0.63 MM gallon storage tank) including all de minimus emissions units (as defined in OAC rule 3745-15-05), all emissions units exempt from the requirement to obtain a permit-to-install pursuant to OAC rule 3745-31-03 currently, and future to-be-installed air contaminant sources, combined, shall not exceed 9.9 TPY for any single HAP and 24.9 TPY for any combination of HAPs. Compliance with the above limitations shall be based on a rolling, 12-month summation.

The permittee has existing records to demonstrate compliance with this limitation upon permit issuance.

- 2.c** This emissions unit has been in operation for more than 12 months and, as such, the permittee has existing records to generate the rolling, 12 month summation of the VOC emissions, upon issuance of this permit. The emissions of VOC from this emissions unit shall not exceed 4.14 tons per year, based upon a rolling 12 month summation of the emissions.
- 2.d** The owner or operator of each storage vessel with a design capacity greater than or equal to 151 cubic meters (m<sup>3</sup>) containing a volatile organic liquid (VOL) that, as stored, has a maximum true vapor pressure equal to or greater than 5.2 kilopascals (kPa) but less than 76.6 kPa shall equip each storage vessel with a fixed roof in combination with an internal floating roof.
- 2.e** The permittee shall equip the storage vessel with a fixed roof in combination with an internal floating roof meeting the following specifications:
- i. The internal floating roof shall rest or float on the liquid surface (but not necessarily in complete contact with it) inside a storage vessel that has a fixed roof. The internal floating roof shall be floating on the liquid surface at all times, except during initial fill and during those intervals when the storage vessel is

Emissions Unit ID: T018

completely emptied or subsequently emptied and refilled. When the roof is resting on the leg supports, the process of filling, emptying, or refilling shall be continuous and shall be accomplished as rapidly as possible.

ii. Each internal floating roof shall be equipped with one of the following closure devices between the wall of the storage vessel and the edge of the internal floating roof:

(a) A foam- or liquid-filled seal mounted in contact with the liquid (liquid-mounted seal). A liquid-mounted seal means a foam- or liquid-filled seal mounted in contact with the liquid between the wall of the storage vessel and the floating roof continuously around the circumference of the tank.

(b) Two seals mounted one above the other so that each forms a continuous closure that completely covers the space between the wall of the storage vessel and the edge of the internal floating roof. The lower seal may be vapor-mounted, but both must be continuous.

(c) A mechanical shoe seal. A mechanical shoe seal is a metal sheet held vertically against the wall of the storage vessel by springs or weighted levers and is connected by braces to the floating roof. A flexible coated fabric (envelope) spans the annular space between the metal sheet and the floating roof.

iii. Each opening in a noncontact internal floating roof except for automatic bleeder vents (vacuum breaker vents) and the rim space vents is to provide a projection below the liquid surface.

iv. Each opening in the internal floating roof except for leg sleeves, automatic bleeder vents, rim space vents, column wells, ladder wells, sample wells, and stub drains is to be equipped with a cover or lid which is to be maintained in a closed position at all times (i.e., no visible gap) except when the device is in actual use. The cover or lid shall be equipped with a gasket. Covers on each access hatch and automatic gauge float well shall be bolted except when they are in use.

v. Automatic bleeder vents shall be equipped with a gasket and are to be closed at all times when the roof is floating except when the roof is being floated off or is being landed on the roof leg supports.

**Issued: 9/18/2007**

vi. Rim space vents shall be equipped with a gasket and are to be set to open only when the internal floating roof is not floating or at the manufacturer's recommended setting.

vii. Each penetration of the internal floating roof for the purpose of sampling shall be a sample well. The sample well shall have a slit fabric cover that covers at least 90 percent of the opening.

viii. Each penetration of the internal floating roof that allows for passage of a column supporting the fixed roof shall have a flexible fabric sleeve seal or a gasketed sliding cover.

ix. Each penetration of the internal floating roof that allows for passage of a ladder shall have a gasketed sliding cover.

**B. Operational Restrictions**

None.

**C. Monitoring and/or Recordkeeping Requirements**

1. The permittee, as specified in 40 CFR 60.116b(b), shall keep readily accessible records showing the dimension of the storage vessel and an analysis showing the capacity of the storage vessel.
2. The permittee shall maintain monthly records of the following information:
  - a. The identification and type of each liquid material stored in this emissions unit.
  - b. The maximum true vapor pressure, in psia, as stored, of each material.
  - c. The density of the material stored, in pounds per gallon.
  - d. The total throughput of each material, in gallons.
3. The permittee shall maintain monthly records of the following information for this emissions unit:
  - a. The monthly VOC emissions in tons for this emissions
  - b. The updated rolling 12-month summation of the VOC emissions in tons from this emissions unit. This shall include the information for the current month and the

preceding eleven calendar months.

4. The permittee shall maintain the following monthly records for all of the emissions units identified in term A.2.b:
  - a. The total individual HAP emissions for each HAP, in tons.
  - b. The total combined HAPs emissions, in tons (the sum of a).
  - c. The updated rolling, 12-month summation of the total individual HAP emissions for each HAP, in tons. This shall include the information for the current month and the preceding eleven calendar months.
  - d. The updated rolling, 12-month summation of the total combined HAP emissions, in tons. This shall include the information for the current month and the preceding eleven calendar months.
  
5. After installing the control equipment required to meet 40 CFR 60.112b(a)(1) (permanently affixed roof and internal floating roof), each owner or operator shall:
  - a. Visually inspect the internal floating roof, the primary seal, and the secondary seal (if one is in service), prior to filling the storage vessel with VOL(volatile organic liquid). If there are holes, tears, or other openings in the primary seal, the secondary seal, or the seal fabric or defects in the internal floating roof, or both, the owner or operator shall repair the items before filling the storage vessel.
  - b. For vessels equipped with a liquid-mounted or mechanical shoe primary seal, visually inspect the internal floating roof and the primary seal or the secondary seal (if one is in service) through manholes and roof hatches on the fixed roof at least once every 12 months after initial fill. If the internal floating roof is not resting on the surface of the VOL inside the storage vessel, or there is liquid accumulated on the roof, or the seal is detached, or there are holes or tears in the seal fabric, the owner or operator shall repair the items or empty and remove the storage vessel from service within 45 days. If a failure that is detected during inspections required in this paragraph cannot be repaired within 45 days and if the vessel cannot be emptied within 45 days, a 30-day extension may be requested from the Administrator in the inspection report required in 40 CFR 60.115b(a)(3). Such a request for an extension must document that alternate storage capacity is unavailable and specify a schedule of actions the company will take that will assure that the control equipment will be repaired or the vessel will be emptied as soon as possible.
  - c. For vessels equipped with a double-seal system as specified in 40 CFR 60.112b(a)(1)(ii)(B):

Issued: 9/18/2007

- i. Visually inspect the vessel as specified in paragraph (a)(4) of 40 CFR 60.113b at least every 5 years; or
    - ii. Visually inspect the vessel as specified in paragraph (a)(2) of 40 CFR 60.113b.
  - d. Visually inspect the internal floating roof, the primary seal, the secondary seal (if one is in service), gaskets, slotted membranes and sleeve seals (if any) each time the storage vessel is emptied and degassed. If the internal floating roof has defects, the primary seal has holes, tears, or other openings in the seal or the seal fabric, or the secondary seal has holes, tears, or other openings in the seal or the seal fabric, or the gaskets no longer close off the liquid surfaces from the atmosphere, or the slotted membrane has more than 10 percent open area, the owner or operator shall repair the items as necessary so that none of the conditions specified in this paragraph exist before refilling the storage vessel with VOL. In no event shall inspections conducted in accordance with this provision occur at intervals greater than 10 years in the case of vessels conducting the annual visual inspection as specified in paragraphs (a)(2) and (a)(3)(ii) of 40 CFR 60.113b and at intervals no greater than 5 years in the case of vessels specified in paragraph (a)(3)(i) of 40 CFR 60.113b.
  - e. Notify the Administrator in writing at least 30 days prior to the filling or refilling of each storage vessel for which an inspection is required by paragraphs (a)(1) and (a)(4) of 40 CFR 60.113b to afford the Administrator the opportunity to have an observer present. If the inspection required by paragraph (a)(4) of 40 CFR 60.113b is not planned and the owner or operator could not have known about the inspection 30 days in advance or refilling the tank, the owner or operator shall notify the Administrator at least 7 days prior to the refilling of the storage vessel. Notification shall be made by telephone immediately followed by written documentation demonstrating why the inspection was unplanned. Alternatively, this notification including the written documentation may be made in writing and sent by express mail so that it is received by the Administrator at least 7 days prior to the refilling.
6. Available data on the storage temperature may be used to determine the maximum true vapor pressure as determined below:
- a. For vessels operated above or below ambient temperatures, the maximum true vapor pressure is calculated based upon the highest expected calendar-month

Emissions Unit ID: T018

average of the storage temperature. For vessels operated at ambient temperatures, the maximum true vapor pressure is calculated based upon the maximum local monthly average ambient temperature as reported by the National Weather Service.

- b. For crude oil or refined petroleum products the vapor pressure may be obtained by the following:
  - (i) Available data on the Reid vapor pressure and the maximum expected storage temperature based on the highest expected calendar-month average temperature of the stored product may be used to determine the maximum true vapor pressure from nomographs contained in API Bulletin 2517 (incorporated by reference--see Sec. 60.17), unless the appropriate Ohio EPA district office or local field office specifically requests that the liquid be sampled, the actual storage temperature determined, and the Reid vapor pressure determined from the sample(s).
  - (ii) The true vapor pressure of each type of crude oil with a Reid vapor pressure less than 13.8 kPa or with physical properties that preclude determination by the recommended method is to be determined from available data and recorded if the estimated maximum true vapor pressure is greater than 3.5 kPa.
- c. For other liquids, the vapor pressure:
  - (i) May be obtained from standard reference texts, or
  - (ii) Determined by ASTM Method D2879-83 (incorporated by reference--see Sec. 60.17); or
  - (iii) Measured by an appropriate method approved by the Ohio EPA; or
  - (iv) Calculated by an appropriate method approved by the Ohio EPA.

#### D. Reporting Requirements

1. The permittee shall submit deviation (excursion) reports which identify all exceedances of the rolling, 12-month VOC and HAP emission limitations in terms A.2.b and A.2.c.
2. The permittee shall submit an annual report which specifies the total VOC emissions from this emissions unit for the previous calendar year. This report shall be submitted by January 31 of each year.
3. After installing control equipment in accordance with 40 CFR 60.112b(a)(1) (fixed roof

Issued: 9/18/2007

and internal floating roof), the permittee shall meet the following reporting requirements:

- a. Furnish the Hamilton County Department of Environmental Services with a report that describes the control equipment and certifies that the control equipment meets the specifications of 40 CFR 60.112b(a)(1) and 40 CFR 60.113b(a)(1). This report shall be an attachment to the notification required by 40 CFR 60.7(a)(3).
  - b. Keep a record of each inspection performed as required by 40 CFR 60.113b(a)(1), (a)(2), (a)(3), and (a)(4). Each record shall identify the storage vessel on which the inspection was performed and shall contain the date the vessel was inspected and the observed condition of each component of the control equipment (seals, internal floating roof, and fittings).
  - c. If any of the conditions described in 40 CFR 60.113b(a)(2) are detected during the annual visual inspection required by 40 CFR 60.113b(a)(2), a report shall be furnished to the Administrator within 30 days of the inspection. Each report shall identify the storage vessel, the nature of the defects, and the date the storage vessel was emptied or the nature of and date the repair was made.
  - d. After each inspection required by 40 CFR 60.113b(a)(3) that finds holes or tears in the seal or seal fabric, or defects in the internal floating roof, or other control equipment defects listed in 40 CFR 60.113b(a)(3)(ii), a report shall be furnished to the Administrator within 30 days of the inspection. The report shall identify the storage vessel and the reason it did not meet the specifications of 40 CFR 60.112b(a)(1) or 40 CFR 60.113b(a)(3) and list each repair made.
4. The permittee shall notify the Director (the appropriate Ohio EPA District Office or local air agency) in writing of any record showing that any material stored in the tank exceeded the vapor pressure greater than or equal to 11.11 psia in this emissions unit. The notification shall include a copy of such record and shall be sent to the Director (the appropriate Ohio EPA District Office or local air agency) within 30 days following the end of the calendar month.
  5. The deviation reports shall be submitted in accordance with the reporting requirements of the General Terms and Conditions of this permit.
  6. Pursuant to the NSPS, the source owner/operator is hereby advised of the requirement to report the following at the appropriate times:

Emissions Unit ID: **T018**

- a. construction date (no later than 30 days after such date);
- b. actual start-up date (within 15 days after such date), including a description of each affected emissions unit, equipment manufacturer, and serial number of the equipment if available; and
- c. date of performance testing (if required, at least 30 days prior to testing).

Reports are to be sent to:

Hamilton County Department of Environmental Services  
250 William Howard Taft Road  
Cincinnati, Ohio 45219

## **E. Testing Requirements**

1. Compliance with the emissions limitation specified in term and condition A.1 shall be demonstrated by use of the following methods:

Emission Limitation:

4.14 tons per year, based upon a rolling 12 month summation of the emissions.

Applicable Compliance Method:

Compliance with the emissions limitation shall be demonstrated by calculating the total emission losses using the Tanks 4.0.9d emissions estimating software or other appropriate software based on equations developed by the American Petroleum Institute documented in AP-42, Section 7.1, Organic Liquid Storage Tanks.

Compliance with the VOC emission limitation specified in term A.2.c shall be demonstrated by the recordkeeping in section C.4.

The VOC emissions from fugitive emissions (i.e., valves, flanges, open ended lines, and pumps) shall be determined using EPA-453/R-95-017, "Protocol for Equipment Leak Emission Estimates."

Should more accurate emission factors be developed during the current permit cycle, the permittee shall use them, provided the new emission factors are mutually agreeable to the Ohio EPA, the Hamilton County Department of Environmental Services.

**Issued: 9/18/2007**

2. Compliance with the HAP emission limitations specified in term A.2.b shall be demonstrated by the recordkeeping in section C.5.

**F. Miscellaneous Requirements**

1. The following terms and conditions of this permit are federally enforceable: A, B, C, D and E.
2. The terms and conditions of this permit to install shall supersede the terms and conditions of permit to install 14-05240 as issued on July 16, 2002.

**Buckeye Terminals, LLC**  
**PTI Application: 14-05968**  
**Issued: 9/18/2007**

**Facility ID: 1431073227**

Emissions Unit ID: **T018**

SIC CODE 5171 SCC CODE 40400113 40400178 EMISSIONS UNIT ID T018  
 EMISSIONS UNIT DESCRIPTION 1,260,000 gallon internal floating roof petroleum storage tank.

DATE INSTALLED after issuance

EMISSIONS: (Click on bubble help for Air Quality Descriptions)

Pollutants	Air Quality Description	Actual Emissions Rate		PTI Allowable	
		Short Term Rate	Tons Per Year	Short Term Rate	Tons Per Year
Particulate Matter					
PM <sub>10</sub>					
Sulfur Dioxide					
Organic Compounds	non attainment		4.14		4.14
Nitrogen Oxides					
Carbon Monoxide					
Lead					
Other: Air Toxics					

APPLICABLE FEDERAL RULES:

NSPS? Subpart Kb      NESHAP? no      PSD? no      OFFSET POLICY? no

WHAT IS THE BAT DETERMINATION, AND WHAT IS THE BASIS FOR THE DETERMINATION?

**NA < 10 TPY**

IS THIS SOURCE SUBJECT TO THE AIR TOXICS POLICY? No

OPTIONAL: WHAT IS THE CAPITAL COST OF CONTROL EQUIPMENT? \$NA

### **TOXIC AIR CONTAMINANTS**

Ohio EPA's air toxics policy applies to contaminants for which the American Conference of Governmental Industrial Hygienists (ACGIH) has a listed threshold limit value.

AIR TOXICS MODELING PERFORMED\*? \_\_\_\_\_ YES    X NO

IDENTIFY THE AIR CONTAMINANTS: NA