



State of Ohio Environmental Protection Agency

**RE: FINAL PERMIT TO INSTALL
HAMILTON COUNTY**

CERTIFIED MAIL

Street Address:

122 S. Front Street

Lazarus Gov. Center TELE: (614) 644-3020 FAX: (614) 644-2329

Mailing Address:

Lazarus Gov. Center
P.O. Box 1049

Application No: 14-05683

Fac ID: 1431140861

DATE: 3/24/2005

Ford Motor Co - Sharonville
Curtis Bailey
3000 Sharon Rd
Cincinnati, OH 452411924

Enclosed please find an Ohio EPA Permit to Install which will allow you to install the described source(s) in a manner indicated in the permit. Because this permit contains several conditions and restrictions, I urge you to read it carefully.

The Ohio EPA is urging companies to investigate pollution prevention and energy conservation. Not only will this reduce pollution and energy consumption, but it can also save you money. If you would like to learn ways you can save money while protecting the environment, please contact our Office of Pollution Prevention at (614) 644-3469.

You are hereby notified that this action by the Director is final and may be appealed to the Ohio Environmental Review Appeals Commission pursuant to Chapter 3745.04 of the Ohio Revised Code. The appeal must be in writing and set forth the action complained of and the grounds upon which the appeal is based. It must be filed within thirty (30) days after the notice of the Directors action. A copy of the appeal must be served on the Director of the Ohio Environmental Protection Agency within three (3) days of filing with the Commission. An appeal may be filed with the Environmental Review Appeals Commission at the following address:

Environmental Review Appeals Commission
309 South Fourth Street, Room 222
Columbus, Ohio 43215

Sincerely,

Michael W. Ahern, Manager
Permit Issuance and Data Management Section
Division of Air Pollution Control

CC: USEPA

HCDES



**Permit To Install
Terms and Conditions**

**Issue Date: 3/24/2005
Effective Date: 3/24/2005**

FINAL PERMIT TO INSTALL 14-05683

Application Number: 14-05683
Facility ID: 1431140861
Permit Fee: **\$2800**
Name of Facility: Ford Motor Co - Sharonville
Person to Contact: Curtis Bailey
Address: 3000 Sharon Rd
Cincinnati, OH 452411924

Location of proposed air contaminant source(s) [emissions unit(s)]:

**3000 Sharon Rd
Cincinnati, Ohio**

Description of proposed emissions unit(s):

14 new process emission units.

The above named entity is hereby granted a Permit to Install for the above described emissions unit(s) pursuant to Chapter 3745-31 of the Ohio Administrative Code. Issuance of this permit does not constitute expressed or implied approval or agreement that, if constructed or modified in accordance with the plans included in the application, the above described emissions unit(s) of environmental pollutants will operate in compliance with applicable State and Federal laws and regulations, and does not constitute expressed or implied assurance that if constructed or modified in accordance with those plans and specifications, the above described emissions unit(s) of pollutants will be granted the necessary permits to operate (air) or NPDES permits as applicable.

This permit is granted subject to the conditions attached hereto.

Ohio Environmental Protection Agency

Director

Part I - GENERAL TERMS AND CONDITIONS

A. State and Federally Enforceable Permit To Install General Terms and Conditions

1. Monitoring and Related Recordkeeping and Reporting Requirements

- a. Except as may otherwise be provided in the terms and conditions for a specific emissions unit, the permittee shall maintain records that include the following, where applicable, for any required monitoring under this permit:
 - i. The date, place (as defined in the permit), and time of sampling or measurements.
 - ii. The date(s) analyses were performed.
 - iii. The company or entity that performed the analyses.
 - iv. The analytical techniques or methods used.
 - v. The results of such analyses.
 - vi. The operating conditions existing at the time of sampling or measurement.
- b. Each record of any monitoring data, testing data, and support information required pursuant to this permit shall be retained for a period of five years from the date the record was created. Support information shall include, but not be limited to, all calibration and maintenance records and all original strip-chart recordings for continuous monitoring instrumentation, and copies of all reports required by this permit. Such records may be maintained in computerized form.
- c. Except as may otherwise be provided in the terms and conditions for a specific emissions unit, the permittee shall submit required reports in the following manner:
 - i. Reports of any required monitoring and/or recordkeeping of federally enforceable information shall be submitted to the appropriate Ohio EPA District Office or local air agency.
 - ii. Quarterly written reports of (i) any deviations from federally enforceable emission limitations, operational restrictions, and control device operating parameter limitations, excluding deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06, that have been detected by the testing, monitoring and recordkeeping requirements specified in this permit, (ii) the probable cause of such deviations, and (iii) any corrective actions or preventive measures taken, shall be made to the appropriate Ohio EPA District Office or local air agency. The written reports shall be submitted quarterly, i.e., by January 31, April 30, July 31, and October 31 of each year and shall cover the previous

calendar quarters. See B.9 below if no deviations occurred during the quarter.

- iii. Written reports, which identify any deviations from the federally enforceable monitoring, recordkeeping, and reporting requirements contained in this permit shall be submitted to the appropriate Ohio EPA District Office or local air agency every six months, i.e., by January 31 and July 31 of each year for the previous six calendar months. If no deviations occurred during a six-month period, the permittee shall submit a semi-annual report, which states that no deviations occurred during that period.
- iv. Each written report shall be signed by a responsible official certifying that, based on information and belief formed after reasonable inquiry, the statements and information in the report are true, accurate, and complete.

2. Scheduled Maintenance/Malfunction Reporting

Any scheduled maintenance of air pollution control equipment shall be performed in accordance with paragraph (A) of OAC rule 3745-15-06. The malfunction, i.e., upset, of any emissions units or any associated air pollution control system(s) shall be reported to the appropriate Ohio EPA District Office or local air agency in accordance with paragraph (B) of OAC rule 3745-15-06. (The definition of an upset condition shall be the same as that used in OAC rule 3745-15-06(B)(1) for a malfunction.) The verbal and written reports shall be submitted pursuant to OAC rule 3745-15-06.

Except as provided in that rule, any scheduled maintenance or malfunction necessitating the shutdown or bypassing of any air pollution control system(s) shall be accompanied by the shutdown of the emission unit(s) that is (are) served by such control system(s).

3. Risk Management Plans

If the permittee is required to develop and register a risk management plan pursuant to section 112(r) of the Clean Air Act, as amended, 42 U.S.C. 7401 et seq. ("Act"), the permittee shall comply with the requirement to register such a plan.

4. Title IV Provisions

If the permittee is subject to the requirements of 40 CFR Part 72 concerning acid rain, the permittee shall ensure that any affected emissions unit complies with those requirements. Emissions exceeding any allowances that are lawfully held under Title IV of the Act, or any regulations adopted thereunder, are prohibited.

5. Severability Clause

A determination that any term or condition of this permit is invalid shall not invalidate the force or effect of any other term or condition thereof, except to the extent that any other term or condition depends in whole or in part for its operation or implementation upon the term or condition

declared invalid.

6. General Requirements

- a. The permittee must comply with all terms and conditions of this permit. Any noncompliance with the federally enforceable terms and conditions of this permit constitutes a violation of the Act, and is grounds for enforcement action or for permit revocation, revocation and reissuance, or modification, or for denial of a permit renewal application.
- b. It shall not be a defense for the permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the federally enforceable terms and conditions of this permit.
- c. This permit may be modified, reopened, revoked, or revoked and reissued, for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or revocation, or of a notification of planned changes or anticipated noncompliance does not stay any term and condition of this permit.
- d. This permit does not convey any property rights of any sort, or any exclusive privilege.
- e. The permittee shall furnish to the Director of the Ohio EPA, or an authorized representative of the Director, upon receipt of a written request and within a reasonable time, any information that may be requested to determine whether cause exists for modifying, reopening or revoking this permit or to determine compliance with this permit. Upon request, the permittee shall also furnish to the Director or an authorized representative of the Director, copies of records required to be kept by this permit. For information claimed to be confidential in the submittal to the Director, if the Administrator of the U.S. EPA requests such information, the permittee may furnish such records directly to the Administrator along with a claim of confidentiality.

7. Fees

The permittee shall pay fees to the Director of the Ohio EPA in accordance with ORC section 3745.11 and OAC Chapter 3745-78. The permittee shall pay all applicable Permit To Install fees within 30 days after the issuance of this Permit To Install.

8. Federal and State Enforceability

Only those terms and conditions designated in this permit as federally enforceable, that are required under the Act, or any of its applicable requirements, including relevant provisions designed to limit the potential to emit of a source, are enforceable by the Administrator of the U.S. EPA, the State, and citizens under the Act. All other terms and conditions of this permit shall not be federally enforceable and shall be enforceable under State law only.

9. Compliance Requirements

- a. Any document (including reports) required to be submitted and required by a federally applicable requirement in this permit shall include a certification by a responsible official that, based on information and belief formed after reasonable inquiry, the statements in the document are true, accurate, and complete.
- b. Upon presentation of credentials and other documents as may be required by law, the permittee shall allow the Director of the Ohio EPA or an authorized representative of the Director to:
 - i. At reasonable times, enter upon the permittee's premises where a source is located or the emissions-related activity is conducted, or where records must be kept under the conditions of this permit.
 - ii. Have access to and copy, at reasonable times, any records that must be kept under the conditions of this permit, subject to the protection from disclosure to the public of confidential information consistent with ORC section 3704.08.
 - iii. Inspect at reasonable times any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under this permit.
 - iv. As authorized by the Act, sample or monitor at reasonable times substances or parameters for the purpose of assuring compliance with the permit and applicable requirements.
- c. The permittee shall submit progress reports to the appropriate Ohio EPA District Office or local air agency concerning any schedule of compliance for meeting an applicable requirement. Progress reports shall be submitted semiannually, or more frequently if specified in the applicable requirement or by the Director of the Ohio EPA. Progress reports shall contain the following:
 - i. Dates for achieving the activities, milestones, or compliance required in any schedule of compliance, and dates when such activities, milestones, or compliance were achieved.
 - ii. An explanation of why any dates in any schedule of compliance were not or will not be met, and any preventive or corrective measures adopted.

10. Permit To Operate Application

- a. If the permittee is required to apply for a Title V permit pursuant to OAC Chapter 3745-77, the permittee shall submit a complete Title V permit application or a complete Title V permit modification application within twelve (12) months after commencing operation of the emissions units covered by this permit. However, if the proposed new or modified source(s) would be prohibited by the terms and conditions of an existing Title V permit, a Title V permit modification must be obtained before the operation of such new or modified source(s) pursuant to OAC rule 3745-77-04(D) and OAC rule 3745-77-08(C)(3)(d).
- b. If the permittee is required to apply for permit(s) pursuant to OAC Chapter 3745-35, the source(s) identified in this Permit To Install is (are) permitted to operate for a period of up to one year from the date the source(s) commenced operation. Permission to operate is granted only if the facility complies with all requirements contained in this permit and all applicable air pollution laws, regulations, and policies. Pursuant to OAC Chapter 3745-35, the permittee shall submit a complete operating permit application within ninety (90) days after commencing operation of the source(s) covered by this permit.

11. Best Available Technology

As specified in OAC Rule 3745-31-05, all new sources must employ Best Available Technology (BAT). Compliance with the terms and conditions of this permit will fulfill this requirement.

12. Air Pollution Nuisance

The air contaminants emitted by the emissions units covered by this permit shall not cause a public nuisance, in violation of OAC rule 3745-15-07.

Ford Motor Co - Sharonville
PTI Application: 14-05683
Issued: 3/24/2005

Facility ID: 1431140861

B. State Only Enforceable Permit To Install General Terms and Conditions

1. Compliance Requirements

The emissions unit(s) identified in this Permit to Install shall remain in full compliance with all applicable State laws and regulations and the terms and conditions of this permit.

2. Reporting Requirements

The permittee shall submit required reports in the following manner:

- a. Reports of any required monitoring and/or recordkeeping of state-only enforceable information shall be submitted to the appropriate Ohio EPA District Office or local air agency.
- b. Except as otherwise may be provided in the terms and conditions for a specific emissions unit, quarterly written reports of (a) any deviations (excursions) from state-only required emission limitations, operational restrictions, and control device operating parameter limitations that have been detected by the testing, monitoring, and recordkeeping requirements specified in this permit, (b) the probable cause of such deviations, and (c) any corrective actions or preventive measures which have been or will be taken, shall be submitted to the appropriate Ohio EPA District Office or local air agency. If no deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted quarterly, i.e., by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters. (These quarterly reports shall exclude deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06.)

3. Permit Transfers

Any transferee of this permit shall assume the responsibilities of the prior permit holder. The appropriate Ohio EPA District Office or local air agency must be notified in writing of any transfer of this permit.

4. Termination of Permit To Install

This permit to install shall terminate within eighteen months of the effective date of the permit to install if the owner or operator has not undertaken a continuing program of installation or modification or has not entered into a binding contractual obligation to undertake and complete

within a reasonable time a continuing program of installation or modification. This deadline may be extended by up to 12 months if application is made to the Director within a reasonable time before the termination date and the party shows good cause for any such extension.

5. Construction of New Sources(s)

The proposed emissions unit(s) shall be constructed in strict accordance with the plans and application submitted for this permit to the Director of the Ohio Environmental Protection Agency. There may be no deviation from the approved plans without the express, written approval of the Agency. Any deviations from the approved plans or the above conditions may lead to such sanctions and penalties as provided under Ohio law. Approval of these plans does not constitute an assurance that the proposed facilities will operate in compliance with all Ohio laws and regulations. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed sources cannot meet the requirements of this permit or cannot meet applicable standards.

If the construction of the proposed emissions unit(s) has already begun or has been completed prior to the date the Director of the Environmental Protection Agency approves the permit application and plans, the approval does not constitute expressed or implied assurance that the proposed facility has been constructed in accordance with the approved plans. The action of beginning and/or completing construction prior to obtaining the Director's approval constitutes a violation of OAC rule 3745-31-02. Furthermore, issuance of the Permit to Install does not constitute an assurance that the proposed source will operate in compliance with all Ohio laws and regulations. Approval of the plans in any case is not to be construed as an approval of the facility as constructed and/or completed. Moreover, issuance of the Permit to Install is not to be construed as a waiver of any rights that the Ohio Environmental Protection Agency (or other persons) may have against the applicant for starting construction prior to the effective date of the permit. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed facilities cannot meet the requirements of this permit or cannot meet applicable standards.

6. Public Disclosure

The facility is hereby notified that this permit, and all agency records concerning the operation of this permitted source, are subject to public disclosure in accordance with OAC rule 3745-49-03.

7. Applicability

This Permit to Install is applicable only to the emissions unit(s) identified in the Permit To Install. Separate application must be made to the Director for the installation or modification of any other emissions unit(s).

8. Construction Compliance Certification

Ford Motor Co - Sharonville
PTI Application: 14-05683
Issued: 3/24/2005

Facility ID: 1431140861

If applicable, the applicant shall provide Ohio EPA with a written certification (see enclosed form if applicable) that the facility has been constructed in accordance with the Permit To Install application and the terms and conditions of the Permit to Install. The certification shall be provided to Ohio EPA upon completion of construction but prior to startup of the source.

9. Additional Reporting Requirements When There Are No Deviations of Federally Enforceable Emission Limitations, Operational Restrictions, or Control Device Operating Parameter Limitations (See Section A of This Permit)

If no deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted quarterly, i.e., by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters.

C. Permit To Install Summary of Allowable Emissions

The following information summarizes the total allowable emissions, by pollutant, based on the individual allowable emissions of each air contaminant source identified in this permit.

SUMMARY (for informational purposes only)
TOTAL PERMIT TO INSTALL ALLOWABLE EMISSIONS

<u>Pollutant</u>	<u>Tons Per Year</u>
PM	7.15
PM10	7.15
OC	17.39

11

Ford Motor Co - Sharonville
PTI Application: 14-05683
Issued: 3/24/2005

Facility ID: 1431140861

12

Ford I

PTI A

Issued: 3/24/2005

Emissions Unit ID: P182

Part II - FACILITY SPECIFIC TERMS AND CONDITIONS

A. State and Federally Enforceable Permit To Install Facility Specific Terms and Conditions

none

B. State Only Enforceable Permit To Install Facility Specific Terms and Conditions

none

Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P182 - Bore, grinders, and hones with mist collector, MC-L34	OAC rule 3745-31-05(A)(3)	Particulate Emissions (PE) shall not exceed 0.05 lb/hr and 0.22 TPY. Particulate Matter 10 microns and less (PM10) emissions shall not exceed 0.05 lb/hr and 0.22 TPY. Organic Compound (OC) emissions shall not exceed 0.48 lb/hr and 2.10 TPY. Visible particulate emissions shall not exceed 10% opacity, as a six minute average.
	OAC rule 3745-17-07(A)	The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).
	OAC rule 3745-17-11	The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).
	OAC rule 3745-21-07(G)(2)	The emission limitation specified by this

Ford I

PTI A

Issued: 3/24/2005

Emissions Unit ID: P182

rule is less stringent than the
emission limitation
established pursuant to OAC
rule 3745-31-05(A)(3).

2. Additional Terms and Conditions

- 2.a** Compliance with OAC rule 3745-31-05(A)(3) shall be demonstrated by the use of a mist collector, opacity limitations and the emission limits.
- 2.b** The hourly and annual emission limitations outlined above are based upon the emissions unit's potential to emit. Therefore, no hourly and annual records are required to demonstrate compliance with these limits.

II. Operational Restrictions

1. None

III. Monitoring and/or Recordkeeping Requirements

1. None

IV. Reporting Requirements

1. None

V. Testing Requirements

1. Compliance with the emission limitation(s) specified in Section A.I of the terms and conditions of this permit shall be determined in accordance with the following method(s):
 - a. Emission Limitations:
Particulate Emissions (PE) shall not exceed 0.05 lb/hr and 0.22 TPY.
Particulate Matter 10 microns and less (PM10) shall not exceed 0.05 lb/hr and 0.22 TPY.

Applicable Compliance Method:

The permittee may demonstrate compliance with this emission limitation by multiplying the outlet grain loading emission factor of 0.0007 grain/scf by the maximum volumetric air flow rate of 8000 scfm and converting to pounds/hour by multiplying by 60 minutes/hour and dividing by 7000 grains/pound. As provided in Permit to Install 14-05683 received on February 11, 2005, the grain loading was based on source test data of a similar source. If required, the permittee shall demonstrate compliance by testing in accordance with Methods 1-4 and 5 of 40 CFR, Part 60, Appendix A.

The annual PE limitation was developed by multiplying the hourly PE limitation by the maximum operating schedule of 8760 hours/year, and dividing by 2000 pounds/ton. Therefore, provided compliance is shown with the hourly emission limitation, compliance will also be shown with the annual limitation.

It shall be assumed that all PE is PM10.

- b. Emission Limitations:
OC emissions shall not exceed 0.48 lb/hr and 2.10 TPY

Applicable Compliance Method:

The permittee may demonstrate compliance with this emissions limitation by summing the multiplication of the outlet grain loading emission factor of: 0.01 grain/scfm, for straight oil, by the maximum volumetric air flow rate of 3700 scfm and converting to pounds/hour by multiplying by 60 minutes/hour and dividing by 7000 grains/pound; and 0.0044 grain/scfm, for water soluble oil, by the maximum volumetric air flow rate of 4300 scfm and converting to pounds/hour by multiplying by 60 minutes/hour and dividing by 7000 grains/pound. As provided in Permit to Install 14-05683 received on February 11, 2005, the grain loading was based on source test data of a similar source. If required, the permittee shall demonstrate compliance by testing in accordance with Methods 1-4 and 18, 25, or 25A, as appropriate, of 40 CFR, Part 60, Appendix A.

The annual OC limitation was developed by multiplying the hourly OC limitation by the maximum operating schedule of 8760 hours/year, and dividing by 2000 pounds/ton. Therefore, provided compliance is shown with the hourly limitation, compliance will also be shown with the annual limitation.

- c. Emission Limitation:
Visible particulate emissions shall not exceed 10% opacity, as a six-minute average.

Applicable Compliance Method:

If required, compliance with the visible emission limitation specified above shall be determined in accordance with Test Method 9 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60.

VI. Miscellaneous Requirements

1. None

B. State Only Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

- 1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P182 - Bore, grinders, and hones with mist collector, MC-L34		

2. Additional Terms and Conditions

- 2.a None

II. Operational Restrictions

- 1. None

III. Monitoring and/or Recordkeeping Requirements

- 1. None

IV. Reporting Requirements

- 1. None

V. Testing Requirements

- 1. None

VI. Miscellaneous Requirements

- 1. None

Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P183 - Bore, grinders, and hones with mist collector MC-N33	OAC rule 3745-31-05(A)(3)	Particulate Emissions (PE) shall not exceed 0.05 lb/hr and 0.22 TPY. Particulate Matter 10 microns and less (PM10) emissions shall not exceed 0.05 lb/hr and 0.22 TPY. Organic Compound (OC) emissions shall not exceed 0.49 lb/hr and 2.15 TPY. Visible particulate emissions shall not exceed 10% opacity, as a six minute average.
	OAC rule 3745-17-07(A)	The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).
	OAC rule 3745-17-11	The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).
	OAC rule 3745-21-07(G)(2)	The emission limitation specified by this

Ford Motor Co - Sharonville
PTI Application: 14-05692
Issued

Facility ID: 1431140861

rule is less stringent than the
emission limitation
established pursuant to OAC
rule 3745-31-05(A)(3).

Emissions Unit ID: P183

2. Additional Terms and Conditions

- 2.a** Compliance with OAC rule 3745-31-05(A)(3) shall be demonstrated by the use of a mist collector, opacity limitations and the emission limits.
- 2.b** The hourly and annual emission limitations outlined above are based upon the emissions unit's potential to emit. Therefore, no hourly and annual records are required to demonstrate compliance with these limits.

II. Operational Restrictions

1. None

III. Monitoring and/or Recordkeeping Requirements

1. None

IV. Reporting Requirements

1. None

V. Testing Requirements

1. Compliance with the emission limitation(s) specified in Section A.I of the terms and conditions of this permit shall be determined in accordance with the following method(s):
 - a. Emission Limitations:
Particulate Emissions (PE) shall not exceed 0.05 lb/hr and 0.22 TPY.
Particulate Matter 10 microns and less (PM10) shall not exceed 0.05 lb/hr and 0.22 TPY.

Applicable Compliance Method:

The permittee may demonstrate compliance with this emission limitation by multiplying the outlet grain loading emission factor of 0.0007 grain/scf by the maximum volumetric air flow rate of 8400 scfm and converting to pounds/hour by multiplying by 60 minutes/hour and dividing by 7000 grains/pound. As provided in Permit to Install 14-05683 received on February 11, 2005, the grain loading was based on source test data of a similar source. If required, the permittee shall demonstrate compliance by testing in accordance with Methods 1-4 and 5 of 40 CFR, Part 60, Appendix A.

The annual PE limitation was developed by multiplying the hourly PE limitation by the maximum operating schedule of 8760 hours/year, and dividing by 2000 pounds/ton. Therefore, provided compliance is shown with the hourly emission limitation, compliance will also be shown with the annual limitation.

It shall be assumed that all PE is PM10.

- b. Emission Limitations:
OC emissions shall not exceed 0.49 lb/hr and 2.15 TPY

Applicable Compliance Method:

The permittee may demonstrate compliance with this emissions limitation by summing the multiplication of the outlet grain loading emission factor of: 0.01 grain/scfm, for straight oil, by the maximum volumetric air flow rate of 3600 scfm and converting to pounds/hour by multiplying by 60 minutes/hour and dividing by 7000 grains/pound; and 0.0044 grain/scfm, for water soluble oil, by the maximum volumetric air flow rate of 4800 scfm and converting to pounds/hour by multiplying by 60 minutes/hour and dividing by 7000 grains/pound. As provided in Permit to Install 14-05683 received on February 11, 2005, the grain loading was based on source test data of a similar source. If required, the permittee shall demonstrate compliance by testing in accordance with Methods 1-4 and 18, 25, or 25A, as appropriate, of 40 CFR, Part 60, Appendix A.

The annual OC limitation was developed by multiplying the hourly OC limitation by the maximum operating schedule of 8760 hours/year, and dividing by 2000 pounds/ton. Therefore, provided compliance is shown with the hourly limitation, compliance will also be shown with the annual limitation.

- c. Emission Limitation:
Visible particulate emissions shall not exceed 10% opacity, as a six-minute average.

Applicable Compliance Method:

If required, compliance with the visible emission limitation specified above shall be determined in accordance with Test Method 9 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60.

VI. Miscellaneous Requirements

1. None

B. State Only Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P183 - Bore, grinders, and hones with mist collector MC-N33		

2. Additional Terms and Conditions

- 2a. None

II. Operational Restrictions

1. None

III. Monitoring and/or Recordkeeping Requirements

1. None

IV. Reporting Requirements

1. None

V. Testing Requirements

1. None

VI. Miscellaneous Requirements

1. None

23

Ford Motor Co - Sharonville
PTI Application: 14-05693
Issued

Facility ID: 1431140861

Emissions Unit ID: P183

Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P184 - Bore, grinders, and hones with mist collector MC-P33	OAC rule 3745-31-05(A)(3)	Particulate Emissions (PE) shall not exceed 0.07 lb/hr and 0.31 TPY. Particulate Matter 10 microns and less (PM10) emissions shall not exceed 0.07 lb/hr and 0.31 TPY. Organic Compound (OC) emissions shall not exceed 0.60 lb/hr and 2.63 TPY. Visible particulate emissions shall not exceed 10% opacity, as a six minute average.
	OAC rule 3745-17-07(A)	The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).
	OAC rule 3745-17-11	The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).
	OAC rule 3745-21-07(G)(2)	The emission limitation specified by this

25

Ford I

PTI A

Issued: 3/24/2005

Emissions Unit ID: P184

rule is less stringent than the
emission limitation
established pursuant to OAC
rule 3745-31-05(A)(3).

2. Additional Terms and Conditions

- 2.a** Compliance with OAC rule 3745-31-05(A)(3) shall be demonstrated by the use of a mist collector, opacity limitations and the emission limits.
- 2.b** The hourly and annual emission limitations outlined above are based upon the emissions unit's potential to emit. Therefore, no hourly and annual records are required to demonstrate compliance with these limits.

II. Operational Restrictions

1. None

III. Monitoring and/or Recordkeeping Requirements

1. None

IV. Reporting Requirements

1. None

V. Testing Requirements

1. Compliance with the emission limitation(s) specified in Section A.I of the terms and conditions of this permit shall be determined in accordance with the following method(s):

- a. Emission Limitations:
Particulate Emissions (PE) shall not exceed 0.07 lb/hr and 0.31 TPY.
Particulate Matter 10 microns and less (PM10) shall not exceed 0.07 lb/hr and 0.31 TPY.

Applicable Compliance Method:

The permittee may demonstrate compliance with this emission limitation by multiplying the outlet grain loading emission factor of 0.0007 grain/scf by the maximum volumetric air flow rate of 12,000 scfm and converting to pounds/hour by multiplying by 60 minutes/hour and dividing by 7000 grains/pound. As provided in Permit to Install 14-05683 received on February 11, 2005, the grain loading was based on source test data of a similar source. If required, the permittee shall demonstrate compliance by testing in accordance with Methods 1-4 and 5 of 40 CFR, Part 60, Appendix A.

The annual PE limitation was developed by multiplying the hourly PE limitation by the maximum operating schedule of 8760 hours/year, and dividing by 2000 pounds/ton. Therefore, provided compliance is shown with the hourly emission limitation, compliance will also be shown with the annual limitation.

It shall be assumed that all PE is PM10.

- b. Emission Limitations:
OC emissions shall not exceed 0.60 lb/hr and 2.63 TPY

Applicable Compliance Method:

The permittee may demonstrate compliance with this emissions limitation by summing the multiplication of the outlet grain loading emission factor of: 0.01 grain/scfm, for straight oil, by the maximum volumetric air flow rate of 3200 scfm and converting to pounds/hour by multiplying by 60 minutes/hour and dividing by 7000 grains/pound; and 0.0044 grain/scfm, for water soluble oil, by the maximum volumetric air flow rate of 8800 scfm and converting to pounds/hour by multiplying by 60 minutes/hour and dividing by 7000 grains/pound. As provided in Permit to Install 14-05683 received on February 11, 2005, the grain loading was based on source test data of a similar source. If required, the permittee shall demonstrate compliance by testing in accordance with Methods 1-4 and 18, 25, or 25A, as appropriate, of 40 CFR, Part 60, Appendix A.

The annual OC limitation was developed by multiplying the hourly OC limitation by the maximum operating schedule of 8760 hours/year, and dividing by 2000 pounds/ton. Therefore, provided compliance is shown with the hourly limitation, compliance will also be shown with the annual limitation.

- c. Emission Limitation:
Visible particulate emissions shall not exceed 10% opacity, as a six-minute average.

Applicable Compliance Method:

If required, compliance with the visible emission limitation specified above shall be determined in accordance with Test Method 9 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60.

VI. Miscellaneous Requirements

1. None

B. State Only Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

- 1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P184 - Bore, grinders, and hones with mist collector MC-P33		

2. Additional Terms and Conditions

- 2.a None

II. Operational Restrictions

- 1. None

III. Monitoring and/or Recordkeeping Requirements

- 1. None

IV. Reporting Requirements

- 1. None

V. Testing Requirements

- 1. None

VI. Miscellaneous Requirements

- 1. None

Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P185 - Bore, grinders, and hones with mist collector MC-Q32	OAC rule 3745-31-05(A)(3)	Particulate Emissions (PE) shall not exceed 0.07 lb/hr and 0.31 TPY. Particulate Matter 10 microns and less (PM10) emissions shall not exceed 0.07 lb/hr and 0.31 TPY. Organic Compound (OC) emissions shall not exceed 0.60 lb/hr and 2.63 TPY. Visible particulate emissions shall not exceed 10% opacity, as a six minute average.
	OAC rule 3745-17-07(A)	The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).
	OAC rule 3745-17-11	The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).
	OAC rule 3745-21-07(G)(2)	The emission limitation specified by this

30

Ford 1

PTI A

Issued: 3/24/2005

Emissions Unit ID: P185

rule is less stringent than the
emission limitation
established pursuant to OAC
rule 3745-31-05(A)(3).

2. Additional Terms and Conditions

- 2.a** Compliance with OAC rule 3745-31-05(A)(3) shall be demonstrated by the use of a mist collector, opacity limitations and the emission limits.
- 2.b** The hourly and annual emission limitations outlined above are based upon the emissions unit's potential to emit. Therefore, no hourly and annual records are required to demonstrate compliance with these limits.

II. Operational Restrictions

1. None

III. Monitoring and/or Recordkeeping Requirements

1. None

IV. Reporting Requirements

1. None

V. Testing Requirements

1. Compliance with the emission limitation(s) specified in Section A.I of the terms and conditions of this permit shall be determined in accordance with the following method(s):
 - a. Emission Limitations:
Particulate Emissions (PE) shall not exceed 0.07 lb/hr and 0.31 TPY.
Particulate Matter 10 microns and less (PM10) shall not exceed 0.07 lb/hr and 0.31 TPY.

Applicable Compliance Method:

The permittee may demonstrate compliance with this emission limitation by multiplying the outlet grain loading emission factor of 0.0007 grain/scf by the maximum volumetric air flow rate of 12,000 scfm and converting to pounds/hour by multiplying by 60 minutes/hour and dividing by 7000 grains/pound. As provided in Permit to Install 14-05683 received on February 11, 2005, the grain loading was based on source test data of a similar source. If required, the permittee shall demonstrate compliance by testing in accordance with Methods 1-4 and 5 of 40 CFR, Part 60, Appendix A.

The annual PE limitation was developed by multiplying the hourly PE limitation by the maximum operating schedule of 8760 hours/year, and dividing by 2000 pounds/ton. Therefore, provided compliance is shown with the hourly emission limitation, compliance will also be shown with the annual limitation.

It shall be assumed that all PE is PM10.

- b. Emission Limitations:
OC emissions shall not exceed 0.60 lb/hr and 2.63 TPY

Applicable Compliance Method:

The permittee may demonstrate compliance with this emissions limitation by summing the multiplication of the outlet grain loading emission factor of: 0.01 grain/scfm, for straight oil, by the maximum volumetric air flow rate of 3200 scfm and converting to pounds/hour by multiplying by 60 minutes/hour and dividing by 7000 grains/pound; and 0.0044 grain/scfm, for water soluble oil, by the maximum volumetric air flow rate of 8800 scfm and converting to pounds/hour by multiplying by 60 minutes/hour and dividing by 7000 grains/pound. As provided in Permit to Install 14-05683 received on February 11, 2005, the grain loading was based on source test data of a similar source. If required, the permittee shall demonstrate compliance by testing in accordance with Methods 1-4 and 18, 25, or 25A, as appropriate, of 40 CFR, Part 60, Appendix A.

The annual OC limitation was developed by multiplying the hourly OC limitation by the maximum operating schedule of 8760 hours/year, and dividing by 2000 pounds/ton. Therefore, provided compliance is shown with the hourly limitation, compliance will also be shown with the annual limitation.

- c. Emission Limitation:
Visible particulate emissions shall not exceed 10% opacity, as a six-minute average.

Applicable Compliance Method:

If required, compliance with the visible emission limitation specified above shall be determined in accordance with Test Method 9 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60.

VI. Miscellaneous Requirements

1. None

B. State Only Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P185 - Bore, grinders, and honers with mist collector MC-Q32		

2. Additional Terms and Conditions

- 2.a None

II. Operational Restrictions

1. None

III. Monitoring and/or Recordkeeping Requirements

1. None

IV. Reporting Requirements

1. None

V. Testing Requirements

1. None

VI. Miscellaneous Requirements

1. None

Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P186 - Grinder, hones and burnishers with mist collector MC-L29	OAC rule 3745-31-05(A)(3)	Particulate Emissions (PE) shall not exceed 0.05 lb/hr and 0.22 TPY. Particulate Matter 10 microns and less (PM10) emissions shall not exceed 0.05 lb/hr and 0.22 TPY. Organic Compound (OC) emissions shall not exceed 0.51 lb/hr and 2.23 TPY. Visible particulate emissions shall not exceed 10% opacity, as a six minute average.
	OAC rule 3745-17-07(A)	The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).
	OAC rule 3745-17-11	The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).
	OAC rule 3745-21-07(G)(2)	The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).

2. Additional Terms and Conditions

- 2.a** Compliance with OAC rule 3745-31-05(A)(3) shall be demonstrated by the use of a mist collector, opacity limitations and the emission limits.
- 2.b** The hourly and annual emission limitations outlined above are based upon the emissions unit's potential to emit. Therefore, no hourly and annual records are required to demonstrate compliance with these limits.

II. Operational Restrictions

1. None

III. Monitoring and/or Recordkeeping Requirements

1. None

IV. Reporting Requirements

1. None

V. Testing Requirements

1. Compliance with the emission limitation(s) specified in Section A.I of the terms and conditions of this permit shall be determined in accordance with the following method(s):
- a. Emission Limitations:
Particulate Emissions (PE) shall not exceed 0.05 lb/hr and 0.22 TPY.
Particulate Matter 10 microns and less (PM10) shall not exceed 0.05 lb/hr and 0.22 TPY.

Applicable Compliance Method:

The permittee may demonstrate compliance with this emission limitation by multiplying the outlet grain loading emission factor of 0.0007 grain/scf by the maximum volumetric air flow rate of 8000 scfm and converting to pounds/hour by multiplying by 60 minutes/hour and dividing by 7000 grains/pound. As provided in Permit to Install 14-05683 received on February 11, 2005, the grain loading was based on source test data of a similar source. If required, the permittee shall demonstrate compliance by testing in accordance with Methods 1-4 and 5 of 40 CFR, Part 60, Appendix A.

The annual PE limitation was developed by multiplying the hourly PE limitation by the maximum operating schedule of 8760 hours/year, and dividing by 2000 pounds/ton. Therefore, provided compliance is shown with the hourly emission limitation, compliance will also be shown with the annual limitation.

It shall be assumed that all PE is PM10.

- b. Emission Limitations:
OC emissions shall not exceed 0.60 lb/hr and 2.63 TPY

Applicable Compliance Method:

The permittee may demonstrate compliance with this emissions limitation by summing the multiplication of the outlet grain loading emission factor of: 0.01 grain/scfm, for straight oil, by the maximum volumetric air flow rate of 4300 scfm and converting to pounds/hour by multiplying by 60 minutes/hour and dividing by 7000 grains/pound; and 0.0044 grain/scfm, for water soluble oil, by the maximum volumetric air flow rate of 3700 scfm and converting to pounds/hour by multiplying by 60 minutes/hour and dividing by 7000 grains/pound. As provided in Permit to Install 14-05683 received on February 11, 2005, the grain loading was based on source test data of a similar source. If required, the permittee shall demonstrate compliance by testing in accordance with Methods 1-4 and 18, 25, or 25A, as appropriate, of 40 CFR, Part 60, Appendix A.

The annual OC limitation was developed by multiplying the hourly OC limitation by the maximum operating schedule of 8760 hours/year, and dividing by 2000 pounds/ton. Therefore, provided compliance is shown with the hourly limitation, compliance will also be shown with the annual limitation.

- c. Emission Limitation:
Visible particulate emissions shall not exceed 10% opacity, as a six-minute average.

Applicable Compliance Method:

If required, compliance with the visible emission limitation specified above shall be determined in accordance with Test Method 9 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60.

VI. Miscellaneous Requirements

1. None

B. State Only Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P186 - Grinder, hones and burnishers with mist collector MC-L29		

2. Additional Terms and Conditions

- 2.a None

II. Operational Restrictions

1. None

III. Monitoring and/or Recordkeeping Requirements

1. None

IV. Reporting Requirements

1. None

V. Testing Requirements

1. None

VI. Miscellaneous Requirements

1. None

Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)**A. State and Federally Enforceable Section****I. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P187 - Hones and grinders with mist collector MC-M29	OAC rule 3745-31-05(A)(3)	<p>Particulate Emissions (PE) shall not exceed 0.04 lb/hr and 0.18 TPY.</p> <p>Particulate Matter 10 microns and less (PM10) emissions shall not exceed 0.04 lb/hr and 0.18 TPY.</p> <p>Organic Compound (OC) emissions shall not exceed 0.43 lb/hr and 1.89 TPY.</p> <p>Visible particulate emissions shall not exceed 10% opacity, as a six minute average.</p>
	OAC rule 3745-17-07(A)	The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).
	OAC rule 3745-17-11	The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).
	OAC rule 3745-21-07(G)(2)	The emission limitation specified by this

Ford 1

PTI A

Issued: 3/24/2005

Emissions Unit ID: P187

rule is less stringent than the
emission limitation
established pursuant to OAC
rule 3745-31-05(A)(3).

2. Additional Terms and Conditions

- 2.a** Compliance with OAC rule 3745-31-05(A)(3) shall be demonstrated by the use of a mist collector, opacity limitations and the emission limits.
- 2.b** The hourly and annual emission limitations outlined above are based upon the emissions unit's potential to emit. Therefore, no hourly and annual records are required to demonstrate compliance with these limits.

II. Operational Restrictions

1. None

III. Monitoring and/or Recordkeeping Requirements

1. None

IV. Reporting Requirements

1. None

V. Testing Requirements

1. Compliance with the emission limitation(s) specified in Section A.I of the terms and conditions of this permit shall be determined in accordance with the following method(s):

a. Emission Limitations:

Particulate Emissions (PE) shall not exceed 0.04 lb/hr and 0.18 TPY.

Particulate Matter 10 microns and less (PM10) shall not exceed 0.04 lb/hr and 0.18 TPY.

Applicable Compliance Method:

The permittee may demonstrate compliance with this emission limitation by multiplying the outlet grain loading emission factor of 0.0007 grain/scf by the maximum volumetric air flow rate of 6000 scfm and converting to pounds/hour by multiplying by 60 minutes/hour and dividing by 7000 grains/pound. As provided in Permit to Install 14-05683 received on February 11, 2005, the grain loading was based on source test data of a similar source. If required, the permittee shall demonstrate compliance by testing in accordance with Methods 1-4 and 5 of 40 CFR, Part 60, Appendix A.

Emissions Unit ID: P187

The annual PE limitation was developed by multiplying the hourly PE limitation by the maximum operating schedule of 8760 hours/year, and dividing by 2000 pounds/ton. Therefore, provided compliance is shown with the hourly emission limitation, compliance will also be shown with the annual limitation.

It shall be assumed that all PE is PM10.

b. Emission Limitations:

OC emissions shall not exceed 0.43 lb/hr and 1.89 TPY

Applicable Compliance Method:

The permittee may demonstrate compliance with this emissions limitation by summing the multiplication of the outlet grain loading emission factor of: 0.01 grain/scfm, for straight oil, by the maximum volumetric air flow rate of 4200 scfm and converting to pounds/hour by multiplying by 60 minutes/hour and dividing by 7000 grains/pound; and 0.0044 grain/scfm, for water soluble oil, by the maximum volumetric air flow rate of 1800 scfm and converting to pounds/hour by multiplying by 60 minutes/hour and dividing by 7000 grains/pound. As provided in Permit to Install 14-05683 received on February 11, 2005, the grain loading was based on source test data of a similar source. If required, the permittee shall demonstrate compliance by testing in accordance with Methods 1-4 and 18, 25, or 25A, as appropriate, of 40 CFR, Part 60, Appendix A.

The annual OC limitation was developed by multiplying the hourly OC limitation by the maximum operating schedule of 8760 hours/year, and dividing by 2000 pounds/ton. Therefore, provided compliance is shown with the hourly limitation, compliance will also be shown with the annual limitation.

c. Emission Limitation:

Visible particulate emissions shall not exceed 10% opacity, as a six-minute average.

Applicable Compliance Method:

If required, compliance with the visible emission limitation specified above shall be determined in accordance with Test Method 9 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60.

VI. Miscellaneous Requirements

1. None

B. State Only Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P187 - Hones and grinders with mist collector MC-M29		

2. Additional Terms and Conditions

- 2.a None

II. Operational Restrictions

1. None

III. Monitoring and/or Recordkeeping Requirements

1. None

IV. Reporting Requirements

1. None

V. Testing Requirements

1. None

VI. Miscellaneous Requirements

1. None

Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P188 - 11 gear hobs with dust collector DC-F29	OAC rule 3745-31-05(A)(3)	Particulate Emissions (PE) shall not exceed 0.21 lb/hr and 0.92 TPY.
		Particulate Matter 10 microns and less (PM10) emissions shall not exceed 0.21 lb/hr and 0.92 TPY.
		Visible particulate emissions shall not exceed 10% opacity, as a six minute average.
	OAC rule 3745-17-07(A)	The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).
	OAC rule 3745-17-11	The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).

2. Additional Terms and Conditions

- 2.a Compliance with OAC rule 3745-31-05(A)(3) shall be demonstrated by the use of a dust collector, opacity limitations and the emission limits.

Ford Motor Co - Sharonville
PTI Application: 14-05693
Issued

Facility ID: 1431140861

Emissions Unit ID: P188

- 2.b** The hourly and annual emission limitations outlined above are based upon the emissions unit's potential to emit. Therefore, no hourly and annual records are required to demonstrate compliance with these limits.

II. Operational Restrictions

1. None

III. Monitoring and/or Recordkeeping Requirements

1. None

IV. Reporting Requirements

1. None

V. Testing Requirements

1. Compliance with the emission limitation(s) specified in Section A.I of the terms and conditions of this permit shall be determined in accordance with the following method(s):

- a. Emission Limitations:

Particulate Emissions (PE) shall not exceed 0.21 lb/hr and 0.92 TPY.

Particulate Matter 10 microns and less (PM10) shall not exceed 0.21 lb/hr and 0.92 TPY.

Applicable Compliance Method:

The permittee may demonstrate compliance with this emission limitation by multiplying the outlet grain loading emission factor of 0.002 grain/scf by the maximum volumetric air flow rate of 12,000 scfm and converting to pounds/hour by multiplying by 60 minutes/hour and dividing by 7000 grains/pound. As provided in Permit to Install 14-05683 received on February 11, 2005, the grain loading was based on source test data of a similar source. If required, the permittee shall demonstrate compliance by testing in accordance with Methods 1-4 and 5 of 40 CFR, Part 60, Appendix A.

The annual PE limitation was developed by multiplying the hourly PE limitation by the maximum operating schedule of 8760 hours/year, and dividing by 2000 pounds/ton. Therefore, provided compliance is shown with the hourly emission limitation, compliance will also be shown with the annual limitation.

It shall be assumed that all PE is PM10.

- b. Emission Limitation:

Visible particulate emissions shall not exceed 10% opacity, as a six-minute average.

46

Ford F

PTI A

Issued: 3/24/2005

Emissions Unit ID: P188

Applicable Compliance Method:

If required, compliance with the visible emission limitation specified above shall be determined in accordance with Test Method 9 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60.

47

Ford F

PTI A

Issued: 3/24/2005

Emissions Unit ID: P188

VI. Miscellaneous Requirements

1. None

B. State Only Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P188 - 11 gear hobs with dust collector DC-F29		

2. Additional Terms and Conditions

- 2.a None

II. Operational Restrictions

1. None

III. Monitoring and/or Recordkeeping Requirements

1. None

IV. Reporting Requirements

1. None

V. Testing Requirements

1. None

VI. Miscellaneous Requirements

1. None

Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P189 - 14 gear hobs with dust collector DC-U35	OAC rule 3745-31-05(A)(3)	Particulate Emissions (PE) shall not exceed 0.14 lb/hr and 0.61 TPY.
		Particulate Matter 10 microns and less (PM10) emissions shall not exceed 0.14 lb/hr and 0.61 TPY.
		Visible particulate emissions shall not exceed 10% opacity, as a six minute average.
	OAC rule 3745-17-07(A)	The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).
	OAC rule 3745-17-11	The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).

2. Additional Terms and Conditions

- 2.a Compliance with OAC rule 3745-31-05(A)(3) shall be demonstrated by the use of a dust collector, opacity limitations and the emission limits.

Ford Motor Co - Sharonville
PTI Application: 14-05693
Issued

Facility ID: 1431140861

Emissions Unit ID: P189

- 2.b** The hourly and annual emission limitations outlined above are based upon the emissions unit's potential to emit. Therefore, no hourly and annual records are required to demonstrate compliance with these limits.

II. Operational Restrictions

1. None

III. Monitoring and/or Recordkeeping Requirements

1. None

IV. Reporting Requirements

1. None

V. Testing Requirements

1. Compliance with the emission limitation(s) specified in Section A.I of the terms and conditions of this permit shall be determined in accordance with the following method(s):

- a. Emission Limitations:

Particulate Emissions (PE) shall not exceed 0.14 lb/hr and 0.61 TPY.

Particulate Matter 10 microns and less (PM10) shall not exceed 0.14 lb/hr and 0.61 TPY.

Applicable Compliance Method:

The permittee may demonstrate compliance with this emission limitation by multiplying the outlet grain loading emission factor of 0.002 grain/scf by the maximum volumetric air flow rate of 8000 scfm and converting to pounds/hour by multiplying by 60 minutes/hour and dividing by 7000 grains/pound. As provided in Permit to Install 14-05683 received on February 11, 2005, the grain loading was based on source test data of a similar source. If required, the permittee shall demonstrate compliance by testing in accordance with Methods 1-4 and 5 of 40 CFR, Part 60, Appendix A.

The annual PE limitation was developed by multiplying the hourly PE limitation by the maximum operating schedule of 8760 hours/year, and dividing by 2000 pounds/ton. Therefore, provided compliance is shown with the hourly emission limitation, compliance will also be shown with the annual limitation.

It shall be assumed that all PE is PM10.

- b. Emission Limitation:

Visible particulate emissions shall not exceed 10% opacity, as a six-minute average.

52

Ford F

PTI A

Issued: 3/24/2005

Emissions Unit ID: P189

Applicable Compliance Method:

If required, compliance with the visible emission limitation specified above shall be determined in accordance with Test Method 9 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60.

53

Ford F

PTI A

Issued: 3/24/2005

Emissions Unit ID: P189

VI. Miscellaneous Requirements

1. None

B. State Only Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P189 - 14 gear hobs with dust collector DC-U35		

2. Additional Terms and Conditions

- 2.a None

II. Operational Restrictions

1. None

III. Monitoring and/or Recordkeeping Requirements

1. None

IV. Reporting Requirements

1. None

V. Testing Requirements

1. None

VI. Miscellaneous Requirements

1. None

Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P190 - 14 gear hobs with dust collector DC-V35	OAC rule 3745-31-05(A)(3)	<p>Particulate Emissions (PE) shall not exceed 0.14 lb/hr and 0.61 TPY.</p> <p>Particulate Matter 10 microns and less (PM10) emissions shall not exceed 0.14 lb/hr and 0.61 TPY.</p> <p>Visible particulate emissions shall not exceed 10% opacity, as a six minute average.</p>
	OAC rule 3745-17-07(A)	The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).
	OAC rule 3745-17-11	The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).

2. Additional Terms and Conditions

- 2.a Compliance with OAC rule 3745-31-05(A)(3) shall be demonstrated by the use of a dust collector, opacity limitations and the emission limits.
- 2.b The hourly and annual emission limitations outlined above are based upon the emissions unit's potential to emit. Therefore, no hourly and annual records are required to demonstrate compliance with these limits.

II. Operational Restrictions

1. None

III. Monitoring and/or Recordkeeping Requirements

1. None

IV. Reporting Requirements

1. None

V. Testing Requirements

1. Compliance with the emission limitation(s) specified in Section A.I of the terms and conditions of this permit shall be determined in accordance with the following method(s):

- a. Emission Limitations:

Particulate Emissions (PE) shall not exceed 0.14 lb/hr and 0.61 TPY.

Particulate Matter 10 microns and less (PM10) shall not exceed 0.14 lb/hr and 0.61 TPY.

Applicable Compliance Method:

The permittee may demonstrate compliance with this emission limitation by multiplying the outlet grain loading emission factor of 0.002 grain/scf by the maximum volumetric air flow rate of 8000 scfm and converting to pounds/hour by multiplying by 60 minutes/hour and dividing by 7000 grains/pound. As provided in Permit to Install 14-05683 received on February 11, 2005, the grain loading was based on source test data of a similar source. If required, the permittee shall demonstrate compliance by testing in accordance with Methods 1-4 and 5 of 40 CFR, Part 60, Appendix A.

The annual PE limitation was developed by multiplying the hourly PE limitation by the maximum operating schedule of 8760 hours/year, and dividing by 2000 pounds/ton. Therefore, provided compliance is shown with the hourly emission limitation, compliance will also be shown with the annual limitation.

It shall be assumed that all PE is PM10.

- b. Emission Limitation:

Visible particulate emissions shall not exceed 10% opacity, as a six-minute average.

57

Ford F

PTI A

Issued: 3/24/2005

Emissions Unit ID: P190

Applicable Compliance Method:

If required, compliance with the visible emission limitation specified above shall be determined in accordance with Test Method 9 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60.

58

Ford F

PTI A

Issued: 3/24/2005

Emissions Unit ID: P190

VI. Miscellaneous Requirements

1. None

B. State Only Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P190 - 14 gear hobs with dust collector DC-V35		

2. Additional Terms and Conditions

- 2.a None

II. Operational Restrictions

1. None

III. Monitoring and/or Recordkeeping Requirements

1. None

IV. Reporting Requirements

1. None

V. Testing Requirements

1. None

VI. Miscellaneous Requirements

1. None

Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P191 - 2 shotpeen machines with dust collector SPDC-S	OAC rule 3745-31-05(A)(3)	Particulate Emissions (PE) shall not exceed 0.34 lb/hr and 1.49 TPY.
		Particulate Matter 10 microns and less (PM10) emissions shall not exceed 0.34 lb/hr and 1.49 TPY.
		Visible particulate emissions shall not exceed 10% opacity, as a six minute average.
	OAC rule 3745-17-07(A)	The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).
	OAC rule 3745-17-11	The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).

2. Additional Terms and Conditions

- 2.a Compliance with OAC rule 3745-31-05(A)(3) shall be demonstrated by the use of a dust collector, opacity limitations and the emission limits.
- 2.b The hourly and annual emission limitations outlined above are based upon the emissions unit's potential to emit. Therefore, no hourly and annual records are required to demonstrate compliance with these limits.

II. Operational Restrictions

1. None

III. Monitoring and/or Recordkeeping Requirements

1. None

IV. Reporting Requirements

1. None

V. Testing Requirements

1. Compliance with the emission limitation(s) specified in Section A.I of the terms and conditions of this permit shall be determined in accordance with the following method(s):

- a. Emission Limitations:

Particulate Emissions (PE) shall not exceed 0.34 lb/hr and 1.49 TPY.

Particulate Matter 10 microns and less (PM10) shall not exceed 0.34 lb/hr and 1.49 TPY.

Applicable Compliance Method:

The permittee may demonstrate compliance with this emission limitation by multiplying the outlet grain loading emission factor of 0.01 grain/scf by the maximum volumetric air flow rate of 4000 scfm and converting to pounds/hour by multiplying by 60 minutes/hour and dividing by 7000 grains/pound. As provided in Permit to Install 14-05683 received on February 11, 2005, the grain loading was based on source test data of a similar source. If required, the permittee shall demonstrate compliance by testing in accordance with Methods 1-4 and 5 of 40 CFR, Part 60, Appendix A.

The annual PE limitation was developed by multiplying the hourly PE limitation by the maximum operating schedule of 8760 hours/year, and dividing by 2000 pounds/ton. Therefore, provided compliance is shown with the hourly emission limitation, compliance will also be shown with the annual limitation.

It shall be assumed that all PE is PM10.

- b. Emission Limitation:

Visible particulate emissions shall not exceed 10% opacity, as a six-minute average.

Ford Motor Co - Sharonville
PTI Application: 14-05693
Issued

Facility ID: 1431140861

Emissions Unit ID: P191

Applicable Compliance Method:

If required, compliance with the visible emission limitation specified above shall be determined in accordance with Test Method 9 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60.

63

Ford F

PTI A

Issued: 3/24/2005

Emissions Unit ID: P191

VI. Miscellaneous Requirements

1. None

B. State Only Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P191 - 2 shotpeen machines with dust collector SPDC-S		

2. Additional Terms and Conditions

- 2.a None

II. Operational Restrictions

1. None

III. Monitoring and/or Recordkeeping Requirements

1. None

IV. Reporting Requirements

1. None

V. Testing Requirements

1. None

VI. Miscellaneous Requirements

1. None

Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P192 - 2 shotpeen machines with dust collector SPDC-N	OAC rule 3745-31-05(A)(3)	Particulate Emissions (PE) shall not exceed 0.34 lb/hr and 1.49 TPY.
		Particulate Matter 10 microns and less (PM10) emissions shall not exceed 0.34 lb/hr and 1.49 TPY.
		Visible particulate emissions shall not exceed 10% opacity, as a six minute average.
	OAC rule 3745-17-07(A)	The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).
	OAC rule 3745-17-11	The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).

2. Additional Terms and Conditions

- 2.a Compliance with OAC rule 3745-31-05(A)(3) shall be demonstrated by the use of a dust collector, opacity limitations and the emission limits.

- 2.b** The hourly and annual emission limitations outlined above are based upon the emissions unit's potential to emit. Therefore, no hourly and annual records are required to demonstrate compliance with these limits.

II. Operational Restrictions

1. None

III. Monitoring and/or Recordkeeping Requirements

1. None

IV. Reporting Requirements

1. None

V. Testing Requirements

1. Compliance with the emission limitation(s) specified in Section A.I of the terms and conditions of this permit shall be determined in accordance with the following method(s):

- a. Emission Limitations:

Particulate Emissions (PE) shall not exceed 0.34 lb/hr and 1.49 TPY.

Particulate Matter 10 microns and less (PM10) shall not exceed 0.34 lb/hr and 1.49 TPY.

Applicable Compliance Method:

The permittee may demonstrate compliance with this emission limitation by multiplying the outlet grain loading emission factor of 0.01 grain/scf by the maximum volumetric air flow rate of 4000 scfm and converting to pounds/hour by multiplying by 60 minutes/hour and dividing by 7000 grains/pound. As provided in Permit to Install 14-05683 received on February 11, 2005, the grain loading was based on source test data of a similar source. If required, the permittee shall demonstrate compliance by testing in accordance with Methods 1-4 and 5 of 40 CFR, Part 60, Appendix A.

The annual PE limitation was developed by multiplying the hourly PE limitation by the maximum operating schedule of 8760 hours/year, and dividing by 2000 pounds/ton. Therefore, provided compliance is shown with the hourly emission limitation, compliance will also be shown with the annual limitation.

It shall be assumed that all PE is PM10.

- b. Emission Limitation:

Visible particulate emissions shall not exceed 10% opacity, as a six-minute average.

Ford Motor Co - Sharonville
PTI Application: 14-05692
Issued

Facility ID: 1431140861

Emissions Unit ID: P192

Applicable Compliance Method:

If required, compliance with the visible emission limitation specified above shall be determined in accordance with Test Method 9 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60.

69

Ford F

PTI A

Issued: 3/24/2005

Emissions Unit ID: P192

VI. Miscellaneous Requirements

1. None

B. State Only Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P192 - 2 shotpeen machines with dust collector SPDC-N		

2. Additional Terms and Conditions

- 2.a None

II. Operational Restrictions

1. None

III. Monitoring and/or Recordkeeping Requirements

1. None

IV. Reporting Requirements

1. None

V. Testing Requirements

1. None

VI. Miscellaneous Requirements

1. None

Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)**A. State and Federally Enforceable Section****I. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P193 - 4 internal broaches with mist collector MC-J30	OAC rule 3745-31-05(A)(3)	<p>Particulate Emissions (PE) shall not exceed 0.05 lb/hr and 0.22 TPY.</p> <p>Particulate Matter 10 microns and less (PM10) emissions shall not exceed 0.05 lb/hr and 0.22 TPY.</p> <p>Organic Compound (OC) emissions shall not exceed 0.69 lb/hr and 3.02 TPY.</p> <p>Visible particulate emissions shall not exceed 10% opacity, as a six minute average.</p>
	OAC rule 3745-17-07(A)	The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).
	OAC rule 3745-17-11	The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).
	OAC rule 3745-21-07(G)(2)	The emission limitation specified by this

72

Ford 1

PTI A

Issued: 3/24/2005

Emissions Unit ID: P193

rule is less stringent than the
emission limitation
established pursuant to OAC
rule 3745-31-05(A)(3).

2. Additional Terms and Conditions

- 2.a** Compliance with OAC rule 3745-31-05(A)(3) shall be demonstrated by the use of a mist collector, opacity limitations and the emission limits.
- 2.b** The hourly and annual emission limitations outlined above are based upon the emissions unit's potential to emit. Therefore, no hourly and annual records are required to demonstrate compliance with these limits.

II. Operational Restrictions

1. None

III. Monitoring and/or Recordkeeping Requirements

1. None

IV. Reporting Requirements

1. None

V. Testing Requirements

1. Compliance with the emission limitation(s) specified in Section A.I of the terms and conditions of this permit shall be determined in accordance with the following method(s):

a. Emission Limitations:

Particulate Emissions (PE) shall not exceed 0.05 lb/hr and 0.22 TPY.

Particulate Matter 10 microns and less (PM10) shall not exceed 0.05 lb/hr and 0.22 TPY.

Applicable Compliance Method:

The permittee may demonstrate compliance with this emission limitation by multiplying the outlet grain loading emission factor of 0.0007 grain/scf by the maximum volumetric air flow rate of 8000 scfm and converting to pounds/hour by multiplying by 60 minutes/hour and dividing by 7000 grains/pound. As provided in Permit to Install 14-05683 received on February 11, 2005, the grain loading was based on source test data of a similar source. If required, the permittee shall demonstrate compliance by testing in accordance with Methods 1-4 and 5 of 40 CFR, Part 60, Appendix A.

The annual PE limitation was developed by multiplying the hourly PE limitation by the

Ford Motor Co - Sharonville

PTI Application: 14-05693

Issued

Facility ID: 1431140861

Emissions Unit ID: P193

maximum operating schedule of 8760 hours/year, and dividing by 2000 pounds/ton. Therefore, provided compliance is shown with the hourly emission limitation, compliance will also be shown with the annual limitation.

It shall be assumed that all PE is PM10.

- b. Emission Limitations:
OC emissions shall not exceed 0.69 lb/hr and 3.02 TPY

Applicable Compliance Method:

The permittee may demonstrate compliance with this emissions limitation by the multiplication of the outlet grain loading emission factor of: 0.01 grain/scfm, for straight oil, by the maximum volumetric air flow rate of 8000 scfm and converting to pounds/hour by multiplying by 60 minutes/hour and dividing by 7000 grains/pound. As provided in Permit to Install 14-05683 received on February 11, 2005, the grain loading was based on source test data of a similar source. If required, the permittee shall demonstrate compliance by testing in accordance with Methods 1-4 and 18, 25, or 25A, as appropriate, of 40 CFR, Part 60, Appendix A.

The annual OC limitation was developed by multiplying the hourly OC limitation by the maximum operating schedule of 8760 hours/year, and dividing by 2000 pounds/ton. Therefore, provided compliance is shown with the hourly limitation, compliance will also be shown with the annual limitation.

- c. Emission Limitation:
Visible particulate emissions shall not exceed 10% opacity, as a six-minute average.

Applicable Compliance Method:

If required, compliance with the visible emission limitation specified above shall be determined in accordance with Test Method 9 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60.

VI. Miscellaneous Requirements

1. None

B. State Only Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P193 - 4 internal broaches with mist collector MC-J30		

2. Additional Terms and Conditions

- 2.a None

II. Operational Restrictions

1. None

III. Monitoring and/or Recordkeeping Requirements

1. None

VI. Miscellaneous Requirements

1. None

IV. Reporting Requirements

1. None

V. Testing Requirements

1. None

77

Ford F

PTI A

Issued: 3/24/2005

Emissions Unit ID: P193

VI. Miscellaneous Requirements

1. None

Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)**A. State and Federally Enforceable Section****I. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P194 - 2 broaches and 1 filter system with mist collector MC-M37	OAC rule 3745-31-05(A)(3)	<p>Particulate Emissions (PE) shall not exceed 0.01 lb/hr and 0.04 TPY.</p> <p>Particulate Matter 10 microns and less (PM10) emissions shall not exceed 0.01 lb/hr and 0.04 TPY.</p> <p>Organic Compound (OC) emissions shall not exceed 0.17 lb/hr and 0.74 TPY.</p> <p>Visible particulate emissions shall not exceed 10% opacity, as a six minute average.</p>
	OAC rule 3745-17-07(A)	The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).
	OAC rule 3745-17-11	The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).
	OAC rule 3745-21-07(G)(2)	The emission limitation specified by this

Ford Motor Co - Sharonville
PTI Application: 14-05692
Issued

Facility ID: 1431140861

rule is less stringent than the
emission limitation
established pursuant to OAC
rule 3745-31-05(A)(3).

Emissions Unit ID: P194

2. Additional Terms and Conditions

- 2.a** Compliance with OAC rule 3745-31-05(A)(3) shall be demonstrated by the use of a mist collector, opacity limitations and the emission limits.
- 2.b** The hourly and annual emission limitations outlined above are based upon the emissions unit's potential to emit. Therefore, no hourly and annual records are required to demonstrate compliance with these limits.

II. Operational Restrictions

1. None

III. Monitoring and/or Recordkeeping Requirements

1. None

IV. Reporting Requirements

1. None

V. Testing Requirements

1. Compliance with the emission limitation(s) specified in Section A.I of the terms and conditions of this permit shall be determined in accordance with the following method(s):
- a. Emission Limitations:
Particulate Emissions (PE) shall not exceed 0.01 lb/hr and 0.04 TPY.
Particulate Matter 10 microns and less (PM10) shall not exceed 0.01 lb/hr and 0.04 TPY.

Applicable Compliance Method:

The permittee may demonstrate compliance with this emission limitation by multiplying the outlet grain loading emission factor of 0.0007 grain/scf by the maximum volumetric air flow rate of 2000 scfm and converting to pounds/hour by multiplying by 60 minutes/hour and dividing by 7000 grains/pound. As provided in Permit to Install 14-05683 received on February 11, 2005, the grain loading was based on source test data of a similar source. If required, the permittee shall demonstrate compliance by testing in accordance with Methods 1-4 and 5 of 40 CFR, Part 60, Appendix A.

The annual PE limitation was developed by multiplying the hourly PE limitation by the

maximum operating schedule of 8760 hours/year, and dividing by 2000 pounds/ton. Therefore, provided compliance is shown with the hourly emission limitation, compliance will also be shown with the annual limitation.

It shall be assumed that all PE is PM10.

- b. Emission Limitations:
OC emissions shall not exceed 0.17 lb/hr and 0.74 TPY

Applicable Compliance Method:

The permittee may demonstrate compliance with this emissions limitation by the multiplication of the outlet grain loading emission factor of: 0.01 grain/scfm, for straight oil, by the maximum volumetric air flow rate of 2000 scfm and converting to pounds/hour by multiplying by 60 minutes/hour and dividing by 7000 grains/pound. As provided in Permit to Install 14-05683 received on February 11, 2005, the grain loading was based on source test data of a similar source. If required, the permittee shall demonstrate compliance by testing in accordance with Methods 1-4 and 18, 25, or 25A, as appropriate, of 40 CFR, Part 60, Appendix A.

The annual OC limitation was developed by multiplying the hourly OC limitation by the maximum operating schedule of 8760 hours/year, and dividing by 2000 pounds/ton. Therefore, provided compliance is shown with the hourly limitation, compliance will also be shown with the annual limitation.

- c. Emission Limitation:
Visible particulate emissions shall not exceed 10% opacity, as a six-minute average.

Applicable Compliance Method:

If required, compliance with the visible emission limitation specified above shall be determined in accordance with Test Method 9 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60.

VI. Miscellaneous Requirements

1. None

B. State Only Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

- 1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P194 - 2 broaches and 1 filter system with mist collector MC-M37		

2. Additional Terms and Conditions

- 2.a None

II. Operational Restrictions

- 1. None

III. Monitoring and/or Recordkeeping Requirements

- 1. None

IV. Reporting Requirements

- 1. None

V. Testing Requirements

- 1. None

VI. Miscellaneous Requirements

- 1. None

Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P195 - 6 bushing bores with dust collector DC-L32	OAC rule 3745-31-05(A)(3)	Particulate Emissions (PE) shall not exceed 0.07 lb/hr and 0.31 TPY.
		Particulate Matter 10 microns and less (PM10) emissions shall not exceed 0.07 lb/hr and 0.31 TPY.
		Visible particulate emissions shall not exceed 10% opacity, as a six minute average.
	OAC rule 3745-17-07(A)	The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).
	OAC rule 3745-17-11	The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).

2. Additional Terms and Conditions

- 2.a Compliance with OAC rule 3745-31-05(A)(3) shall be demonstrated by the use of a dust collector, opacity limitations and the emission limits.

- 2.b** The hourly and annual emission limitations outlined above are based upon the emissions unit's potential to emit. Therefore, no hourly and annual records are required to demonstrate compliance with these limits.

II. Operational Restrictions

1. None

III. Monitoring and/or Recordkeeping Requirements

1. None

IV. Reporting Requirements

1. None

V. Testing Requirements

1. Compliance with the emission limitation(s) specified in Section A.I of the terms and conditions of this permit shall be determined in accordance with the following method(s):

- a. Emission Limitations:

Particulate Emissions (PE) shall not exceed 0.07 lb/hr and 0.31 TPY.

Particulate Matter 10 microns and less (PM10) shall not exceed 0.07 lb/hr and 0.31 TPY.

Applicable Compliance Method:

The permittee may demonstrate compliance with this emission limitation by multiplying the outlet grain loading emission factor of 0.002 grain/scf by the maximum volumetric air flow rate of 4000 scfm and converting to pounds/hour by multiplying by 60 minutes/hour and dividing by 7000 grains/pound. As provided in Permit to Install 14-05683 received on February 11, 2005, the grain loading was based on source test data of a similar source. If required, the permittee shall demonstrate compliance by testing in accordance with Methods 1-4 and 5 of 40 CFR, Part 60, Appendix A.

The annual PE limitation was developed by multiplying the hourly PE limitation by the maximum operating schedule of 8760 hours/year, and dividing by 2000 pounds/ton. Therefore, provided compliance is shown with the hourly emission limitation, compliance will also be shown with the annual limitation.

It shall be assumed that all PE is PM10.

- b. Emission Limitation:

Visible particulate emissions shall not exceed 10% opacity, as a six-minute average.

Ford Motor Co - Sharonville
PTI Application: 14-05693
Issued

Facility ID: 1431140861

Emissions Unit ID: P195

Applicable Compliance Method:

If required, compliance with the visible emission limitation specified above shall be determined in accordance with Test Method 9 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60.

88

Ford F

PTI A

Issued: 3/24/2005

Emissions Unit ID: P195

VI. Miscellaneous Requirements

1. None

B. State Only Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P195 - 6 bushing bores with dust collector DC-L32		

2. Additional Terms and Conditions

- 2.a None

II. Operational Restrictions

1. None

III. Monitoring and/or Recordkeeping Requirements

1. None

IV. Reporting Requirements

1. None

V. Testing Requirements

1. None

VI. Miscellaneous Requirements

1. None