

Facility ID: 0857190056 Issuance type: Final State Permit To Operate

This version of facility specific terms and conditions was converted from a database format to an HTML file during an upgrade of the Ohio EPA, Division of Air Pollution Control's permitting software. Every attempt has been made to convert the terms and conditions to look and substantively conform to the permit issued or being drafted in STARS. However, the format of the terms may vary slightly from the original. In addition, although it is not expected, there is a slight possibility that a term and condition may have been inadvertently "left out" of this reproduction during the conversion process. Therefore, if this version is to be used as a starting point in drafting a new version of a permit, it is imperative that the entire set of terms and conditions be reviewed to ensure they substantively mimic the issued permit. The official version of any permit issued final by Ohio EPA is kept in the Agency's Legal section. The Legal section may be contacted at (614) 644-3037.

In addition to the terms and conditions, hyperlinks have been inserted into the document so you may more readily access the section of the document you wish to review.

Finally, the term language under "Part II" and before "A. Applicable Emissions Limitations..." has been added to aid in document conversion, and was not part of the original issued permit.

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION

Facility ID: 0857190056 Emissions Unit ID: P903 Issuance type: Final State Permit To Operate

[Go to the top of this document](#)

Part II - Special Terms and Conditions

This permit document constitutes a permit-to-install issued in accordance with ORC 3704.03(F) and a permit-to-operate issued in accordance with ORC 3704.03(G).

1. For the purpose of a permit-to-install document, the emissions unit terms and conditions identified below are federally enforceable with the exception of those listed below which are enforceable under state law only.
 - (a) None.
2. For the purpose of a permit-to-operate document, the emissions unit terms and conditions identified below are enforceable under state law only with the exception of those listed below which are federally enforceable.
 - (a) None.

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
Asphaltic concrete batch plant: rotary dryer, hot aggregate elevator, vibrating screens and weigh hopper, 120 tons per hour with a wet scrubber.	OAC rule 3745-31-05 PTI #08-2086	15.75 TPY particulates; 28.8 lbs/hr and 9.0 TPY SO ₂ 20.4 lbs/hr and 6.38 TPY NO _x 40.8 lbs/hr and 12.75 TPY CO; 5.52 lbs/hr and 1.73 TPY OC; 0.23 lb/hr and 0.22 TPY lead
	OAC rule 3745-17-11	50 lbs/hr particulate
	OAC rule 3745-17-07(A)	Visible particulate emissions shall not exceed 20 percent opacity, as a 6-minute average, from the stack, except as provided by rule.
	OAC rule 3745-17-08	No visible emissions of fugitive dust from the enclosures for the hot aggregate elevator, vibrating screens, and weigh hopper.
Aggregate Storage Bins and Cold Aggregate Elevator	OAC rule 3745-31-05 PTI #08-2086	The drop height of the front end loader bucket shall be minimized to the extent possible in order to minimize or eliminate visible emissions of fugitive dust from the elevator loading area.
	OAC rule 3745-17-08	The aggregate loaded into the storage bins shall have a moisture content sufficient to eliminate the visible emissions of fugitive dust from the elevator and the transfer point to the dryer.
	OAC rule 3745-17-07(B)	The visible emissions of fugitive dust shall not exceed 20 percent opacity, as a 3-minute average, from the stack, except as provided by rule.

2. **Additional Terms and Conditions**
 - (a) None

B. Operational Restrictions

1. The maximum annual production rate for this emissions unit shall not exceed 75,000 tons.
2. Specifications for the Used Oil Burned in the Dryer

All recycled, used oil burned in this emissions unit shall meet the following specifications:

Contaminant/Property Allowable Specifications*
 arsenic 5 ppm, maximum
 cadmium 2 ppm, maximum
 chromium 10 ppm, maximum
 lead 100 ppm, maximum
 PCBs 50 ppm, maximum
 Total halogens 4000 ppm, maximum

mercury 1 ppm, maximum
 flash point 100 degrees Fahrenheit, minimum
 heat content 135,000 BTU/gallon, minimum

*Some or all of these used oil specifications exceed the Resource Conservation & Recovery Act Standards of 40 CFR Part 266.40 and OAC rule 3745-58-50, thereby, making the used oil off-specification.

3. The permittee may not receive or burn any used oil which does not meet the specifications listed above. An exceedance would be considered a violation of this permit and OAC rule 3745-31-02.
4. Used oil containing more than 100 ppm total halogens is presumed to be hazardous waste under the rebuttable presumption provided under 40 CFR 266.40(c) and OAC rule 3745-58-50. Therefore, the permittee may receive and burn used oil exceeding 100 ppm of total halogens (but less than 4000 ppm, maximum) only if the supplier [marketer in 40 CFR 266.43(a)] has demonstrated to Ohio EPA's Division of Hazardous Waste Management that the used oil does not contain any hazardous waste.
5. **Used Oil On-Site Sampling/Analytical Requirements**

The permittee shall sample each incoming shipment of used oil. The sampling frequency for used oil shall be one properly labelled 500 ml sample for each truck or container delivery. The sample shall be taken and retained for at least 60 days.

Regional Air Pollution Control Agency may require and/or conduct periodic, detailed chemical analyses through an independent laboratory of any used oil received at this facility, of any sample retained, as required above, and of any storage tanks at this facility.
6. To ensure the scrubber control system is operated according to the manufacturer's specifications, and to maintain compliance with the allowable particulate emission rates, the permittee shall maintain a water flow rate of not less than 100 gallons per minute and a water pressure of not less than 100 pounds per square inch.

C. Monitoring and/or Record Keeping Requirements

1. The permittee shall receive a chemical analysis with each shipment of used oil from the supplier. The analysis shall identify the name and address of the supplier, the supplier's USEPA identification number, and the following information:
 - a. date of shipment or delivery,
 - b. quantity of used oil received,
 - c. the Btu value of the used oil,
 - d. the flash point of the used oil,
 - e. the arsenic content,
 - f. the cadmium content,
 - g. the chromium content,
 - h. the lead content,
 - i. the PCB content,
 - j. the total halogen content, and
 - k. the mercury content.

Each analysis shall be kept in a readily accessible location for at least 5 years and shall be made available to the Director (the appropriate Ohio EPA District Office or local air agency) upon verbal or written request. The Director or any authorized representative of the Director may require or may conduct periodic, detailed chemical analyses through an independent laboratory of any used oil shipment received by this facility, of any used oil stored at this facility, or of any used oil sampled at the dryer.
2. The permittee shall maintain monthly records of the asphaltic concrete produced in this emissions unit.
3. The permittee shall properly operate and maintain equipment to monitor the water flow rate (gallons/minute) and water pressure (psig) for the scrubber. The water flow rate and water pressure shall be recorded daily while the emissions unit is in operation.

D. Reporting Requirements

1. The permittee shall submit annual reports that identify any exceedances of the annual production rate limitation as well as the corrective actions that were taken to achieve compliance. These reports shall be submitted by January 31 of each year.
2. The permittee shall notify the USEPA and the Ohio EPA (appropriate DO or LAA) if any of the used oil exceeds the used oil specifications. An identification number from USEPA shall be obtained prior to the combustion of any used oil.

Before the permittee accepts the first shipment of any off-specification used oil from a marketer, the permittee must provide the marketer a one-time, written and signed notice certifying that:

 - a. the company has notified USEPA of its used oil management activities and that the notice included the location and description of those activities; and
 - b. the company will burn the used oil only in an industrial furnace or boiler identified in 40 CFR Part 266.41(b) and OAC rule 3745-58-42.

A copy of each certification notice that the permittee sends to a marketer must be kept on file for a minimum of 5 years from the date it last received off-specification used oil from that marketer.
3. The permittee shall submit deviation (excursion) reports which identify (by date, duration, and measurement valves) all violations of the water flow rate and water pressure limitations.

These deviation reports shall be submitted in accordance with paragraph 3 of the General Terms and Conditions.

E. Testing Requirements

1. Compliance Methods

Compliance with the emissions limitation(s) in section A. 1. of these terms and conditions shall be determined in accordance with the following method(s):

Emissions Limitation-
50 lbs/hour particulates

Applicable Compliance Method-
Compliance shall be based upon stack testing per OAC rule 3745-17-03 (B)(10).

Emissions Limitation-
15.75 TPY particulates

Applicable Compliance Method-
Compliance shall be determined by multiplying the average hourly emission rate in pounds per ton of asphaltic concrete production from the most recent compliance test by each 12-month production summation, and dividing by 2,000 lbs/ton. Until additional emission tests are conducted, the average emission rate of 0.26 lb/ton shall be used in this calculation.

Emission Limitation-
28.8 lbs/hr SO₂

Applicable Compliance Method-
Compliance shall be determined by multiplying the maximum hourly production rate of (120 tons/hr) by the AP-42 emission factor for SO₂ (0.24 lb/ton). If required, compliance with this mass emission limitation shall be based on stack testing per OAC rule 3745-18-04(E).

Emission Limitation-
9.00 TPY SO₂

Applicable Compliance Method-
Compliance shall be based on the record keeping specified in C. 2. multiplying each 12-month production summation by the AP-42 emission factor for SO₂ (0.24 lb/ton), and dividing by 2,000 lbs/ton.

Emission Limitation-
20.4 lbs/hr NO_x

Applicable Compliance Method-
Compliance shall be determined by multiplying the maximum hourly production rate of (120 tons/hr) by the AP-42 emission factor for NO_x (0.17 lb/ton). If required, compliance shall be based on conducting a stack test in accordance with either USEPA Reference Method 7 or 7A (as appropriate), of 40 CFR Part 60, Appendix A.

Emissions Limitation-
6.38 TPY NO_x

Applicable Compliance Limitation-
Compliance shall be based on the record keeping specified in C. 2. multiplying each 12-month production summation by the AP-42 emission factor for NO_x (0.17 lb/ton), and dividing by 2,000 lbs/ton.

Emission Limitation-
40.8 lbs/hr of CO

Applicable Compliance Method-
Compliance shall be determined by multiplying the maximum hourly production rate of (120 tons/hr) by the AP-42 emission factor for CO (0.34 lb/ton). If required, compliance shall be based on conducting a stack test in accordance with USEPA Reference Method 10, of 40 CFR Part 60, Appendix A.

Emissions Limitation-
12.75 TPY CO

Applicable Compliance Method-
Compliance shall be based on the record keeping specified in C. 2. multiplying each 12-month production summation by the AP-42 emission factor for CO (0.34 lb/ton), and dividing by 2,000 lbs/ton.

Emission Limitation-
5.52 lbs/hr OC

Applicable Compliance Method-
Compliance shall be determined by multiplying the maximum hourly production rate of (120 tons/hr) by the AP-42 emission factor for OC (0.046 lb/ton). If required, compliance shall be based on conducting a stack test in accordance with USEPA Reference Method 25 or 25A (as appropriate), of 40 CFR Part 60, Appendix A.

Emissions Limitation-
1.73 TPY OC

Applicable Compliance Method-
Compliance shall be based on the record keeping specified in C. 2. multiplying each 12-month production summation by the AP-42 emission factor for OC (0.046 lb/ton), and dividing by 2,000 lbs/ton.

Emissions Limitation-
0.141 lb/hr of lead

Applicable Compliance Method-
Compliance shall be based upon stack testing employing USEPA Reference Method 12 of 40 CFR Part 60, Appendix A.

Emission Limitation-
0.04 TPY lead

Applicable Compliance Method-
Compliance shall be determined by multiplying the average hourly emission rate in pounds per ton of asphaltic

concrete production from the most recent compliance test by each 12-month production summation, and dividing by 2,000 lbs/ton. Until additional emission tests are conducted, the average emission rate of 0.00000074 lb/ton shall be used in this calculation.

Emissions Limitation-
20 percent opacity as a 6-minute average

Applicable Compliance Method-
OAC rule 3745-17-03(B)(1)

Emissions Limitation-
20 percent opacity as a 3-minute average

Applicable Compliance Method-
OAC rule 3745-17-03(B)(3)

2. During the last full production season which this permit is effective, the permittee shall conduct, or have conducted, an emission test(s) for this emissions unit in order to demonstrate compliance with the allowable mass emission rate(s) for particulates. The particulates test(s) shall be conducted in accordance with the test methods and procedures specified in "USEPA Reference Method 5, of 40 CFR Part 60, Appendix A" while the emissions unit is operating at or near maximum capacity and using only "virgin aggregate".

During the last full production season which this permit is effective, the permittee shall conduct, or have conducted, an emission test(s) for this emissions unit in order to demonstrate compliance with the allowable mass emission rate(s) for lead. The lead test(s) shall be conducted in accordance with the test methods and procedures specified in "USEPA Reference Method 12, of 40 CFR Part 60, Appendix A" while the emissions unit is operating at or near maximum capacity and using only "virgin aggregate".

Not later than 30 days prior to the proposed test date(s), the permittee shall submit an "Intent to Test" notification. The "Intent to Test" notification shall describe in detail the proposed test methods and procedures, the emissions unit operating parameters, the time(s) and dates(s) of the test(s), and the person(s) who will be conducting the test(s). Failure to submit such notification for review and approval prior to the test(s) may result in the field office's refusal to accept the results of the emissions test(s).

Personnel from the Ohio EPA District Office or local air agency shall be permitted to witness the test(s), examine the testing equipment and acquire data and information regarding the emissions unit operating parameters.

A comprehensive written report on the results of the emission test(s) shall be submitted within 30 days following completion of the test(s).

F. Miscellaneous Requirements

1. The permittee shall comply with any applicable State and federal requirements governing the storage, treatment, transport, and disposal of any waste material generated by the operation of the emissions unit.
2. The permittee is hereby notified that this permit, and all agency records concerning the operation of this permitted emissions unit are subject to public disclosure in accordance with OAC rule 3745-49-03.