Facility ID: 0857770747 Issuance type: Final State Permit To Operate

This version of facility specific terms and conditions was converted from a database format to an HTML file during an upgrade of the Ohio EPA, Division of Air Pollution Control's permitting software. Every attempt has been made to convert the terms and conditions to look and substantively conform to the permit issued or being drafted in STARS. However, the format of the terms may vary slightly from the original. In addition, although it is not expected, there is a slight possibility that a term and condition may have been inadvertently "left out" of this reproduction during the conversion process. Therefore, if this version is to be used as a starting point in drafting a new version of a permit, it is imperative that the entire set of terms and conditions be reviewed to ensure they substantively mimic the issued permit. The official version of any permit issued final by Ohio EPA is kept in the Agency's Legal section. The Legal section may be contacted at (614) 644-3037.

In addition to the terms and conditions, hyperlinks have been inserted into the document so you may more readily access the section of the document you wish to review.

Finally, the term language under "Part II" and before "A. Applicable Emissions Limitations..." has been added to aid in document conversion, and was not part of the original issued permit.

Go to Part II for Emissions Unit L001
Go to Part II for Emissions Unit L002

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION

Facility ID: 0857770747 Emissions Unit ID: L001 Issuance type: Final State Permit To Operate

Go to the top of this document

Part II - Special Terms and Conditions

This permit document constitutes a permit-to-install issued in accordance with ORC 3704.03(F) and a permit-to-operate issued in accordance with ORC 3704.03(G).

1. For the purpose of a permit-to-install document, the emissions unit terms and conditions identified below are federally enforceable with the exception of those listed below which are enforceable under state law only.

   (a) None.

2. For the purpose of a permit-to-operate document, the emissions unit terms and conditions identified below are enforceable under state law only with the exception of those listed below which are federally enforceable.

   (a) None.

A. **Applicable Emissions Limitations and/or Control Requirements**

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

Operations, Property, and/or Equipment	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
Open top vapor degreaser #1	OAC rule 3745-31-05(A)(3) PTI 08-04199	0.356 ton/month and 4.28 tons/yr of organic compounds
	40 CFR Part 63, Subpart T	The requirements of this rule also include compliance with the requirements of 40 CFR Part 63 Subpart T. Control Combinations Table 2, Option 6 (Freeboard refrigeration device, reduced room draft and freeboard ratio of 1.0)
	OAC rule 3745-21-09(O)(3)	This emissions unit is exempt from the volatile organic compound control measures established in OAC rule 3745-21-09(O) pursuant to OAC rule 3745-21-09(O)(6)(b).

2. **Additional Terms and Conditions**

   (a) The permittee shall ensure that the chilled air blanket temperature (in oF), measured at the center of the air blanket, is no greater than 30 percent of the solvent's boiling point.
   The permittee shall comply with the following requirements:

   i. Ensure that the flow or movement of air across the top of the freeboard area of the solvent cleaning machine does not exceed 15.2 meters per minute (50 feet per minute) at any time as measured using the procedures outlined in the "Monitoring and/or Record keeping Requirements" section of this permit.

   ii. Establish and maintain the operating conditions under which the wind speed was demonstrated to be 15.2 meters per minute (50 feet per minute) or less.
   The permittee shall maintain a freeboard with a freeboard ratio equal to 1.0 or greater.
   The permittee shall ensure that the solvent cleaning machine conforms to the following design requirements:

   i. The solvent cleaning machine shall be designed or operated to meet the following control equipment or technique requirements:

   ii. Use of reduced room draft that ensures that the flow or movement across the top of the freeboard area of the solvent cleaning machine or within the solvent cleaning machine enclosure does not exceed 15.2 meters per minute (50 feet per minute) at any time measured using the procedure described in the "Monitoring and/or Recordkeeping Requirements" section of this permit. The permittee shall establish and maintain the operating conditions under which the wind speed was demonstrated to be 15.2 meters per minute (50 feet per minute) or less as described in the "Monitoring and/or Recordkeeping Requirements" section of this permit.

   iii. The solvent cleaning machine shall have a freeboard ratio of 1.0 or greater.

   iv. The solvent cleaning machine shall be equipped with a device that shuts off the sump heat if the sump liquid solvent level drops to the sump heater coils.

v. The solvent cleaning machine shall be equipped with a vapor level control device that shuts off sump heat if the vapor level in the vapor cleaning machine rises above the height of the primary condenser.

vi. The solvent cleaning machine shall have a primary condenser.

B. **Operational Restrictions**

1. The permittee shall meet all of the following required work and operational practices:
Control air disturbances across the solvent cleaning machine opening by incorporating the following control equipment or techniques:

i. The permittee shall employ a reduced room draft that ensures that the flow or movement of air across the top of the freeboard area of the solvent cleaning machine or within the solvent cleaning machine enclosure does not exceed 15.2 meters per minute (50 feet per minute) at any time as measured using the procedures described in the "Monitoring and/or Recordkeeping Requirements" section of this permit. The permittee shall also establish and maintain the operating conditions under which the wind speed was demonstrated to be 15.2 meters per minute (50 feet per minute) or less as described in the "Monitoring and/or Recordkeeping Requirements" section of this permit.
The parts baskets or the parts being cleaned in solvent cleaning machine shall not occupy more than 50 percent of the solvent/air interface area unless the parts baskets or parts are introduced at a speed of 0.9 meter per minute (3 feet per minute) or less.
Any spraying operations shall be done within the vapor zone or within a section of the solvent cleaning machine that is not directly exposed to the ambient air (i.e., a baffled or enclosed area of the solvent cleaning machine).
Parts shall be oriented so that the solvent drains from them freely. Parts having cavities or blind holes must be tipped or rotated before being removed from the solvent cleaning machine unless an equally effective approach has been approved by the Director (appropriate field Office or local air agency).
Parts baskets or parts shall not be removed from the solvent cleaning machine until dripping has stopped.
During startup of the solvent cleaning machine, the primary condensers shall be turned on before the sump heater.
During shutdown of the solvent cleaning machine, the sump heater shall be turned off and the solvent vapor layer allowed to collapse before the primary condenser is turned off.
When solvent is added or drained from the solvent cleaning machine, the solvent shall be transferred using threaded or other leakproof couplings and the end of the pipe in the solvent sump shall be located beneath the liquid solvent surface.
The solvent cleaning machine and its associated controls shall be maintained as recommended by the manufacturers of the equipment or using alternative maintenance practices that have been demonstrated to the satisfaction of the Director (appropriate field Office or local air agency) to achieve the same or better results as those recommended by the manufacturer.
The permittee shall complete and pass the applicable sections of the test of solvent cleaning operating procedures in 40 CFR Part 63, Appendix B if requested during an inspection by the Director (appropriate field Office or local air agency).
Waste solvent, still bottoms, and sump bottoms shall be collected and stored in closed containers. The closed containers may contain a device that would allow pressure relief, but must not allow liquid solvent to drain from the container.
Sponges, fabric, wood, and paper products shall not be cleaned.

2. The maximum annual solvent usage for this emissions unit shall not exceed 705 gallons. Solvent usage = solvent added (gallons) - solvent in waste disposed (gallons)

C. **Monitoring and/or Record Keeping Requirements**

1. The permittee shall maintain monthly records of the following information:

a. The identification of the degreasing solvent employed.

b. The number of gallons of degreasing solvent used.

c. The number of gallons of degreasing solvent disposed of as waste.

d. The monthly VOC emission rate, see section E.1.a for calculation method.

2. The permittee shall conduct monitoring and record the results on a weekly basis for the freeboard refrigeration device by using a thermometer or thermocouple to measure the temperature at the center of the air blanket during the idling mode.

3. The permittee shall conduct quarterly monitoring of wind speed, and weekly monitoring of room parameters as specified below:

a. Measure the wind speed within 6 inches above the top of the freeboard area of the solvent cleaning machine as follows:

i. Determine the direction of the wind current by slowly rotating a velometer or similar device until the maximum speed is located.

ii. Orient a velometer in the direction of the wind current at each of the four corners of the machine.

iii. Record the reading for each corner.

iv. Average the values obtained at each corner and record the average wind speed.

b. Monitor on a weekly basis the room parameters established during the initial compliance test that are used to achieve the reduced room draft.

4. The permittee shall monitor the hoist speed as described below:

a. The permittee shall determine the hoist speed by measuring the time it takes for the hoist to travel a measured distance. The speed is equal to the distance in meters divided by the time in minutes (meters per

minute).

b. The permittee shall conduct monthly monitoring of the hoist speed. If after the first year, no exceedances of the hoist speed are measured, the permittee may begin monitoring the hoist speed quarterly.

c. If an exceedance of the hoist speed occurs during quarterly monitoring, the permittee shall return to a monthly monitoring frequency until another year of compliance without an exceedance is demonstrated.

d. If the permittee can demonstrate to the satisfaction of the Director (appropriate District office or local air agency) in the initial compliance report that the hoist speed cannot exceed a speed of 3.4 meters per minute (11 feet per minute), the required monitoring frequency is quarterly, including during the first year of compliance.

5. The permittee shall maintain the following records in written or electronic form for the lifetime of the solvent cleaning machine:

a. Owner's manuals, or if not available, written maintenance and operating procedures for the solvent cleaning machine and control equipment.

b. The date of installation for the solvent cleaning machine and all of its control devices. If the exact date for the installation is not known, a letter certifying that the cleaning machine and its control devices were installed prior to, or on, November 29, 1993, or after November 29, 1993, may be substituted.

c. Records of the halogenated HAP solvent content for the solvent used in the solvent cleaning machine.

6. The permittee shall maintain the following records in written or electronic form for a period of five years for the solvent cleaning machine:

a. The results of control device monitoring required in this section of the permit.

b. Information on the actions taken to comply with 40 CFR 63.463 (e) and (f), including records of written or verbal orders for replacement parts, a description of the repair made, and additional monitoring conducted to demonstrate that monitored parameters have returned to acceptable levels.

c. Estimates of annual trichloroethylene consumption for the solvent cleaning machine.

D. **Reporting Requirements**

1. The permittee shall submit an annual report by February 1 of each year for the preceding year. Each annual report shall contain the following:

a. A signed statement from the facility owner or their designee stating that, "All operators of solvent cleaning machines have received training on the proper operation of solvent cleaning machines and their control devices sufficient to pass the test required pursuant to 40 CFR 60.463 (d) (10)."

b. An estimate of solvent consumption during the reporting period.

2. The permittee shall submit an exceedance report on a semiannual basis.

a. If the temperature of the chilled air blanket, measured at the center of the air blanket, was greater than 30% of the solvent's boiling point, and no correction was made within 15 days of detection.

b. If no operation conditions were established under which the wind speed was demonstrated to be 15.2 meters per minute (50 feet per minute) and/or if the flow of air across the top of the freeboard area of the cleaning machine or within the solvent cleaning machine enclosure exceeded 15.2 meters/minute and no correction was made within 15 days of detection.

3. The permittee shall begin to submit a quarterly report until such time that the permittee requests and receives approval of a less frequent reporting frequency from the Director (appropriate District Office or local air agency). The permittee may receive approval of less frequent reporting if the following conditions are met: (1) The emissions unit has demonstrated a full year of compliance without an exceedance, (2) the permittee continues to comply with all relevant recordkeeping and monitoring requirements specified in 40 CFR 63.1, General Provisions, and (3) the Director (appropriate District Office or local air agency) does not object to a reduced frequency of reporting for the affected emissions unit as provided in paragraph (e) (3) (iii) of subpart A, 40 CFR 63.1, General Provisions. Each exceedance report shall be delivered or post marked by the 30th day following the reporting period. Each exceedance report shall contain the following:

a. the reason and a description of the exceedance and action(s) taken to comply with 40 CFR 63.463 (e) and (f) including written or verbal orders for replacement parts, a description of the repairs made, and additional monitoring conducted to demonstrate that monitored parameters have returned to acceptable levels, and

b. if no exceedance has occurred, a statement to that effect shall be submitted.

E. **Testing Requirements**

1. Compliance with the emission limitation(s) in Section A.I. of these terms and conditions shall be determined in accordance with the following method(s):
Emission Limitation -
0.356 ton/month organic compounds

Applicable Compliance Method -
To determine the actual organic compound emission rate, the following equation shall be used:

E = (Ls - Lw) x D/2000

E = organic compound emission rate (ton/month)

Ls = liquid volume of trichloroethylene solvent employed each month (gallons)

Lw = liquid volume of trichloroethylene solvent sent off-site as waste (gallons)

D = density of trichloroethylene solvent (pounds/gallon)
Emission Limitation -
4.28 tons/yr organic compounds

Applicable Compliance Method -
Compliance shall be based upon the record keeping specified in Section C.1. and shall be the sum of the monthly VOC emission rates for the calendar year.

F. **Miscellaneous Requirements**

1. None

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION

Facility ID: 0857770747 Emissions Unit ID: L002 Issuance type: Final State Permit To Operate

Go to the top of this document

Part II - Special Terms and Conditions

This permit document constitutes a permit-to-install issued in accordance with ORC 3704.03(F) and a permit-to-operate issued in accordance with ORC 3704.03(G).

1. For the purpose of a permit-to-install document, the emissions unit terms and conditions identified below are federally enforceable with the exception of those listed below which are enforceable under state law only.

(a) None.

2. For the purpose of a permit-to-operate document, the emissions unit terms and conditions identified below are enforceable under state law only with the exception of those listed below which are federally enforceable.

(a) None.

A. **Applicable Emissions Limitations and/or Control Requirements**

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

Operations, Property, and/or Equipment	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
Open top vapor degreaser #2	OAC rule 3745-31-05(A)(3) PTI 08-04199	0.356 ton/month and 4.28 tons/yr of organic compounds
	40 CFR Part 63, Subpart T	The requirements of this rule also include compliance with the requirements of 40 CFR Part 63 Subpart T. Control Combinations Table 2, Option 6 (Freeboard refrigeration device, reduced room draft and freeboard ratio of 1.0)
	OAC rule 3745-21-09(O)(3)	This emissions unit is exempt from the volatile organic compound control measures established in OAC rule 3745-21-09(O) pursuant to OAC rule 3745-21-09(O)(6)(b).

2. **Additional Terms and Conditions**

(a) The permittee shall ensure that the chilled air blanket temperature (in oF), measured at the center of the air blanket, is no greater than 30 percent of the solvent's boiling point.
The permittee shall comply with the following requirements:

i. Ensure that the flow or movement of air across the top of the freeboard area of the solvent cleaning machine does not exceed 15.2 meters per minute (50 feet per minute) at any time as measured using the procedures outlined in the "Monitoring and/or Record keeping Requirements" section of this permit.

ii. Establish and maintain the operating conditions under which the wind speed was demonstrated to be 15.2 meters per minute (50 feet per minute) or less.
The permittee shall maintain a freeboard with a freeboard ratio equal to 1.0 or greater.
The permittee shall ensure that the solvent cleaning machine conforms to the following design requirements:

i. The solvent cleaning machine shall be designed or operated to meet the following control equipment or technique requirements:

ii. Use of reduced room draft that ensures that the flow or movement across the top of the freeboard area of the solvent cleaning machine or within the solvent cleaning machine enclosure does not exceed 15.2 meters per minute (50 feet per minute) at any time measured using the procedure described in the "Monitoring and/or Recordkeeping Requirements" section of this permit. The permittee shall establish

and maintain the operating conditions under which the wind speed was demonstrated to be 15.2 meters per minute (50 feet per minute) or less as described in the "Monitoring and/or Recordkeeping Requirements" section of this permit.

iii. The solvent cleaning machine shall have a freeboard ratio of 1.0 or greater.

iv. The solvent cleaning machine shall be equipped with a device that shuts off the sump heat if the sump liquid solvent level drops to the sump heater coils.

v. The solvent cleaning machine shall be equipped with a vapor level control device that shuts off sump heat if the vapor level in the vapor cleaning machine rises above the height of the primary condenser.

vi. The solvent cleaning machine shall have a primary condenser.

B. **Operational Restrictions**

1. The permittee shall meet all of the following required work and operational practices:
Control air disturbances across the solvent cleaning machine opening by incorporating the following control equipment or techniques:

i. The permittee shall employ a reduced room draft that ensures that the flow or movement of air across the top of the freeboard area of the solvent cleaning machine or within the solvent cleaning machine enclosure does not exceed 15.2 meters per minute (50 feet per minute) at any time as measured using the procedures described in the "Monitoring and/or Recordkeeping Requirements" section of this permit. The permittee shall also establish and maintain the operating conditions under which the wind speed was demonstrated to be 15.2 meters per minute (50 feet per minute) or less as described in the "Monitoring and/or Recordkeeping Requirements" section of this permit.
The parts baskets or the parts being cleaned in solvent cleaning machine shall not occupy more than 50 percent of the solvent/air interface area unless the parts baskets or parts are introduced at a speed of 0.9 meter per minute (3 feet per minute) or less.
Any spraying operations shall be done within the vapor zone or within a section of the solvent cleaning machine that is not directly exposed to the ambient air (i.e., a baffled or enclosed area of the solvent cleaning machine).
Parts shall be oriented so that the solvent drains from them freely. Parts having cavities or blind holes must be tipped or rotated before being removed from the solvent cleaning machine unless an equally effective approach has been approved by the Director (appropriate field Office or local air agency).
Parts baskets or parts shall not be removed from the solvent cleaning machine until dripping has stopped.
During startup of the solvent cleaning machine, the primary condensers shall be turned on before the sump heater.
During shutdown of the solvent cleaning machine, the sump heater shall be turned off and the solvent vapor layer allowed to collapse before the primary condenser is turned off.
When solvent is added or drained from the solvent cleaning machine, the solvent shall be transferred using threaded or other leakproof couplings and the end of the pipe in the solvent sump shall be located beneath the liquid solvent surface.
The solvent cleaning machine and its associated controls shall be maintained as recommended by the manufacturers of the equipment or using alternative maintenance practices that have been demonstrated to the satisfaction of the Director (appropriate field Office or local air agency) to achieve the same or better results as those recommended by the manufacturer.
The permittee shall complete and pass the applicable sections of the test of solvent cleaning operating procedures in 40 CFR Part 63, Appendix B if requested during an inspection by the Director (appropriate field Office or local air agency).
Waste solvent, still bottoms, and sump bottoms shall be collected and stored in closed containers. The closed containers may contain a device that would allow pressure relief, but must not allow liquid solvent to drain from the container.
Sponges, fabric, wood, and paper products shall not be cleaned.

2. The maximum annual solvent usage for this emissions unit shall not exceed 705 gallons. Solvent usage = solvent added (gallons) - solvent in waste disposed (gallons)

C. **Monitoring and/or Record Keeping Requirements**

1. The permittee shall maintain monthly records of the following information:

a. The identification of the degreasing solvent employed.

b. The number of gallons of degreasing solvent used.

c. The number of gallons of degreasing solvent disposed of as waste.

d. The monthly VOC emission rate, see section E.1.a for calculation method.

2. The permittee shall conduct monitoring and record the results on a weekly basis for the freeboard refrigeration device by using a thermometer or thermocouple to measure the temperature at the center of the air blanket during the idling mode.

3. The permittee shall conduct quarterly monitoring of wind speed, and weekly monitoring of room parameters as specified below:

a. Measure the wind speed within 6 inches above the top of the freeboard area of the solvent cleaning machine as follows:

i. Determine the direction of the wind current by slowly rotating a velometer or similar device until the maximum speed is located.

ii. Orient a velometer in the direction of the wind current at each of the four corners of the machine.

iii. Record the reading for each corner.

iv. Average the values obtained at each corner and record the average wind speed.

b. Monitor on a weekly basis the room parameters established during the initial compliance test that are used to achieve the reduced room draft.

4. The permittee shall monitor the hoist speed as described below:

a. The permittee shall determine the hoist speed by measuring the time it takes for the hoist to travel a measured distance. The speed is equal to the distance in meters divided by the time in minutes (meters per minute).

b. The permittee shall conduct monthly monitoring of the hoist speed. If after the first year, no exceedances of the hoist speed are measured, the permittee may begin monitoring the hoist speed quarterly.

c. If an exceedance of the hoist speed occurs during quarterly monitoring, the permittee shall return to a monthly monitoring frequency until another year of compliance without an exceedance is demonstrated.

d. If the permittee can demonstrate to the satisfaction of the Director (appropriate District office or local air agency) in the initial compliance report that the hoist speed cannot exceed a speed of 3.4 meters per minute (11 feet per minute), the required monitoring frequency is quarterly, including during the first year of compliance.

5. The permittee shall maintain the following records in written or electronic form for the lifetime of the solvent cleaning machine:

a. Owner's manuals, or if not available, written maintenance and operating procedures for the solvent cleaning machine and control equipment.

b. The date of installation for the solvent cleaning machine and all of its control devices. If the exact date for the installation is not known, a letter certifying that the cleaning machine and its control devices were installed prior to, or on, November 29, 1993, or after November 29, 1993, may be substituted.

c. Records of the halogenated HAP solvent content for the solvent used in the solvent cleaning machine.

6. The permittee shall maintain the following records in written or electronic form for a period of five years for the solvent cleaning machine:

a. The results of control device monitoring required in this section of the permit.

b. Information on the actions taken to comply with 40 CFR 63.463 (e) and (f), including records of written or verbal orders for replacement parts, a description of the repair made, and additional monitoring conducted to demonstrate that monitored parameters have returned to acceptable levels.

c. Estimates of annual trichloroethylene consumption for the solvent cleaning machine.

D. **Reporting Requirements**

1. The permittee shall submit an annual report by February 1 of each year for the preceding year. Each annual report shall contain the following:

a. A signed statement from the facility owner or their designee stating that, "All operators of solvent cleaning machines have received training on the proper operation of solvent cleaning machines and their control devices sufficient to pass the test required pursuant to 40 CFR 60.463 (d) (10)."

b. An estimate of solvent consumption during the reporting period.

2. The permittee shall submit an exceedance report on a semiannual basis.

a. If the temperature of the chilled air blanket, measured at the center of the air blanket, was greater than 30% of the solvent's boiling point, and no correction was made within 15 days of detection.

b. If no operation conditions were established under which the wind speed was demonstrated to be 15.2 meters per minute (50 feet per minute) and/or if the flow of air across the top of the freeboard area of the cleaning machine or within the solvent cleaning machine enclosure exceeded 15.2 meters/minute and no correction was made within 15 days of detection.

3. The permittee shall begin to submit a quarterly report until such time that the permittee requests and receives approval of a less frequent reporting frequency from the Director (appropriate District Office or local air agency). The permittee may receive approval of less frequent reporting if the following conditions are met: (1) The emissions unit has demonstrated a full year of compliance without an exceedance, (2) the permittee continues to comply with all relevant recordkeeping and monitoring requirements specified in 40 CFR 63.1, General Provisions, and (3) the Director (appropriate District Office or local air agency) does not object to a reduced frequency of reporting for the affected emissions unit as provided in paragraph (e) (3) (iii) of subpart A, 40 CFR 63.1, General Provisions. Each exceedance report shall be delivered or post marked by the 30th day following the reporting period. Each exceedance report shall contain the following:

a. the reason and a description of the exceedance and action(s) taken to comply with 40 CFR 63.463 (e) and (f) including written or verbal orders for replacement parts, a description of the repairs made, and additional monitoring conducted to demonstrate that monitored parameters have returned to acceptable levels, and

b. if no exceedance has occurred, a statement to that effect shall be submitted.

E. **Testing Requirements**

1. Compliance with the emission limitation(s) in Section A.I. of these terms and conditions shall be determined in accordance with the following method(s):
Emission Limitation -
0.356 ton/month organic compounds

Applicable Compliance Method -

To determine the actual organic compound emission rate, the following equation shall be used:

E = (Ls - Lw) x D/2000

E = organic compound emission rate (ton/month)

Ls = liquid volume of trichloroethylene solvent employed each month (gallons)

Lw = liquid volume of trichloroethylene solvent sent off-site as waste (gallons)

D = density of trichloroethylene solvent (pounds/gallon)
Emission Limitation -
4.28 tons/yr organic compounds

Applicable Compliance Method -
Compliance shall be based upon the record keeping specified in Section C.1. and shall be the sum of the monthly VOC emission rates for the calendar year.

F. **Miscellaneous Requirements**

1. None