



State of Ohio Environmental Protection Agency

**RE: FINAL PERMIT TO INSTALL
HAMILTON COUNTY**

CERTIFIED MAIL

Street Address:

122 S. Front Street

Lazarus Gov. Center TELE: (614) 644-3020 FAX: (614) 644-2329

Mailing Address:

Lazarus Gov. Center
P.O. Box 1049

Application No: 14-05822

Fac ID: 1431403168

DATE: 6/1/2006

Uni-Ref Inc
Fred Daniels
11301 Jefferson Avenue
Sharonville, OH 45241

Enclosed please find an Ohio EPA Permit to Install which will allow you to install the described source(s) in a manner indicated in the permit. Because this permit contains several conditions and restrictions, I urge you to read it carefully.

The Ohio EPA is urging companies to investigate pollution prevention and energy conservation. Not only will this reduce pollution and energy consumption, but it can also save you money. If you would like to learn ways you can save money while protecting the environment, please contact our Office of Pollution Prevention at (614) 644-3469.

You are hereby notified that this action by the Director is final and may be appealed to the Ohio Environmental Review Appeals Commission pursuant to Chapter 3745.04 of the Ohio Revised Code. The appeal must be in writing and set forth the action complained of and the grounds upon which the appeal is based. It must be filed within thirty (30) days after the notice of the Directors action. A copy of the appeal must be served on the Director of the Ohio Environmental Protection Agency within three (3) days of filing with the Commission. An appeal may be filed with the Environmental Review Appeals Commission at the following address:

Environmental Review Appeals Commission
309 South Fourth Street, Room 222
Columbus, Ohio 43215

Sincerely,

Michael W. Ahern, Manager
Permit Issuance and Data Management Section
Division of Air Pollution Control

CC: USEPA

HCDES



**Permit To Install
Terms and Conditions**

**Issue Date: 6/1/2006
Effective Date: 6/1/2006**

FINAL PERMIT TO INSTALL 14-05822

Application Number: 14-05822
Facility ID: 1431403168
Permit Fee: **\$5250**
Name of Facility: Uni-Ref Inc
Person to Contact: Fred Daniels
Address: 11301 Jefferson Avenue
Sharonville, OH 45241

Location of proposed air contaminant source(s) [emissions unit(s)]:
**11301 Jefferson Avenue
Sharonville Ohio, Ohio**

Description of proposed emissions unit(s):
Synthetic Minor permit for six refractory mixers.

The above named entity is hereby granted a Permit to Install for the above described emissions unit(s) pursuant to Chapter 3745-31 of the Ohio Administrative Code. Issuance of this permit does not constitute expressed or implied approval or agreement that, if constructed or modified in accordance with the plans included in the application, the above described emissions unit(s) of environmental pollutants will operate in compliance with applicable State and Federal laws and regulations, and does not constitute expressed or implied assurance that if constructed or modified in accordance with those plans and specifications, the above described emissions unit(s) of pollutants will be granted the necessary permits to operate (air) or NPDES permits as applicable.

This permit is granted subject to the conditions attached hereto.

Ohio Environmental Protection Agency

Director

Uni-Ref Inc
PTI Application: 14-05822
Issued: 6/1/2006

Facility ID: 1431403168

Part I - GENERAL TERMS AND CONDITIONS

A. Permit to Install General Terms and Conditions

1. Compliance Requirements

The emissions unit(s) identified in this Permit to Install shall remain in full compliance with all applicable State laws and regulations and the terms and conditions of this permit.

2. Reporting Requirements

The permittee shall submit required reports in the following manner:

- a. Reports of any required monitoring and/or recordkeeping information shall be submitted to the appropriate Ohio EPA District Office or local air agency.
- b. Except as otherwise may be provided in the terms and conditions for a specific emissions unit, quarterly written reports of (a) any deviations (excursions) from emission limitations, operational restrictions, and control device operating parameter limitations that have been detected by the testing, monitoring, and recordkeeping requirements specified in this permit, (b) the probable cause of such deviations, and (c) any corrective actions or preventive measures which have been or will be taken, shall be submitted to the appropriate Ohio EPA District Office or local air agency. If no deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted quarterly, i.e., by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters. (These quarterly reports shall exclude deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06.)

3. Records Retention Requirements

Each record of any monitoring data, testing data, and support information required pursuant to this permit shall be retained for a period of five years from the date the record was created. Support information shall include, but not be limited to, all calibration and maintenance records and all original strip-chart recordings for continuous monitoring instrumentation, and copies of all reports required by this permit. Such records may be maintained in computerized form.

4. Inspections and Information Requests

The Director of the Ohio EPA, or an authorized representative of the Director, may, subject to the safety requirements of the permittee and without undue delay, enter upon

Uni-Ref Inc
PTI Application: 14-05822
Issued: 6/1/2006

Facility ID: 1431403168

the premises of this source at any reasonable time for purposes of making inspections, conducting tests, examining records or reports pertaining to any emission of air contaminants, and determining compliance with any applicable State air pollution laws and regulations and the terms and conditions of this permit. The permittee shall furnish to the Director of the Ohio EPA, or an authorized representative of the Director, upon receipt of a written request and within a reasonable time, any information that may be requested to determine whether cause exists for modifying, reopening or revoking this permit or to determine compliance with this permit. Upon verbal or written request, the permittee shall also furnish to the Director of the Ohio EPA, or an authorized representative of the Director, copies of records required to be kept by this permit.

5. Scheduled Maintenance/Malfunction Reporting

Any scheduled maintenance of air pollution control equipment shall be performed in accordance with paragraph (A) of OAC rule 3745-15-06. The malfunction of any emissions units or any associated air pollution control system(s) shall be reported to the appropriate Ohio EPA District Office or local air agency in accordance with paragraph (B) of OAC rule 3745-15-06. Except as provided in that rule, any scheduled maintenance or malfunction necessitating the shutdown or bypassing of any air pollution control system(s) shall be accompanied by the shutdown of the emissions unit(s) that is (are) served by such control system(s).

6. Permit Transfers

Any transferee of this permit shall assume the responsibilities of the prior permit holder. The appropriate Ohio EPA District Office or local air agency must be notified in writing of any transfer of this permit.

7. Air Pollution Nuisance

The air contaminants emitted by the emissions units covered by this permit shall not cause a public nuisance, in violation of OAC rule 3745-15-07.

8. Termination of Permit to Install

This Permit to Install shall terminate within eighteen months of the effective date of the Permit to Install if the owner or operator has not undertaken a continuing program of installation or modification or has not entered into a binding contractual obligation to undertake and complete within a reasonable time a continuing program of installation or modification. This deadline may be extended by up to 12 months if application is made to the Director within a reasonable time before the termination date and the party shows good cause for any such extension.

9. Construction of New Sources(s)

Uni-Ref Inc
PTI Application: 14-05822
Issued: 6/1/2006

Facility ID: 1431403168

The proposed emissions unit(s) shall be constructed in strict accordance with the plans and application submitted for this permit to the Director of the Ohio Environmental Protection Agency. There may be no deviation from the approved plans without the express, written approval of the Agency. Any deviations from the approved plans or the above conditions may lead to such sanctions and penalties as provided under Ohio law. Approval of these plans does not constitute an assurance that the proposed facilities will operate in compliance with all Ohio laws and regulations. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed sources cannot meet the requirements of this permit or cannot meet applicable standards.

If the construction of the proposed emissions unit(s) has already begun or has been completed prior to the date the Director of the Environmental Protection Agency approves the permit application and plans, the approval does not constitute expressed or implied assurance that the proposed facility has been constructed in accordance with the approved plans. The action of beginning and/or completing construction prior to obtaining the Director's approval constitutes a violation of OAC rule 3745-31-02. Furthermore, issuance of the Permit to Install does not constitute an assurance that the proposed source will operate in compliance with all Ohio laws and regulations. Approval of the plans in any case is not to be construed as an approval of the facility as constructed and/or completed. Moreover, issuance of the Permit to Install is not to be construed as a waiver of any rights that the Ohio Environmental Protection Agency (or other persons) may have against the applicant for starting construction prior to the effective date of the permit. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed facilities cannot meet the requirements of this permit or cannot meet applicable standards.

10. Public Disclosure

The facility is hereby notified that this permit, and all agency records concerning the operation of this permitted source, are subject to public disclosure in accordance with OAC rule 3745-49-03.

11. Applicability

This Permit To Install is applicable only to the emissions unit(s) identified in the Permit To Install. Separate Permit To Install for the installation or modification of any other emissions unit(s) are required for any emissions unit for which a Permit To Install is required.

12. Best Available Technology

As specified in OAC Rule 3745-31-05, all new sources must employ Best Available Technology (BAT). Compliance with the terms and conditions of this permit will fulfill this requirement.

Uni-Ref Inc
 PTI Application: 14-05822
 Issued: 6/1/2006

Facility ID: 1431403168

13. Source Operation and Operating Permit Requirements After Completion of Construction

This facility is permitted to operate each source described by this Permit to Install for a period of up to one year from the date the source commenced operation. This permission to operate is granted only if the facility complies with all requirements contained in this permit and all applicable air pollution laws, regulations, and policies. Pursuant to OAC Chapter 3745-35, the permittee shall submit a complete operating permit application within ninety (90) days after commencing operation of the emissions unit(s) covered by this permit.

14. Construction Compliance Certification

The applicant shall provide Ohio EPA with a written certification (see enclosed form) that the facility has been constructed in accordance with the Permit to Install application and the terms and conditions of the Permit to Install. The certification shall be provided to Ohio EPA upon completion of construction but prior to startup of the source.

15. Fees

The permittee shall pay fees to the Director of the Ohio EPA in accordance with ORC section 3745.11 and OAC Chapter 3745-78. The permittee shall pay all applicable Permit to Install fees within 30 days after the issuance of this Permit to Install.

B. Permit to Install Summary of Allowable Emissions

The following information summarizes the total allowable emissions, by pollutant, based on the individual allowable emissions of each air contaminant source identified in this permit.

SUMMARY (for informational purposes only)
 TOTAL PERMIT TO INSTALL ALLOWABLE EMISSIONS

<u>Pollutant</u>	<u>Tons Per Year</u>
PE	5.04
PM10	0.64

Uni-Ref Inc
PTI Application: 11 05822
Issue

Facility ID: 1431403168

Emissions Unit ID: P001

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

- 1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	
P001 - Eirich Mixer 1	OAC rule 3745-31-05(A)(3)	OAC rule 3745-17-11

OAC rule 3745-17-07(A)(1)

OAC rule 3745-17-07(B)(1)

OAC rule 3745-17-08(B)

Uni-Ref Inc
PTI Application: 14-05822
Issue

Facility ID: 1431403168

Emissions Unit ID: P001

Applicable Emissions
Limitations/Control Measures

Particulate emissions (PE) shall not exceed 0.19 pound per hour and 0.84 ton per year.

Particulate emissions 10 microns and less in diameter (PM10) shall not exceed 0.024 pound per hour and 0.11 ton per year.

See term A.2.c. and term A.2.e.

The requirements of this rule also include compliance with the requirements of OAC rule 3745-17-07(B)(1).

The emissions limitation specified by this rule is less stringent than the emissions limitation established pursuant to OAC rule 3745-31-05(A)(3).

See term A.2.b.

The emissions limitation specified by this rule is less stringent than the emissions limitation established pursuant to OAC rule 3745-31-05(A)(3).

The emissions limitation specified by this rule is less stringent than the emissions limitation established pursuant to OAC rule 3745-31-05(A)(3).

2. Additional Terms and Conditions

- 2.a** Compliance with OAC rule 3745-31-05(A)(3) shall be demonstrated by compliance with the emissions limitations and the use of a fabric filter.
- 2.b** Visible fugitive particulate emissions shall not exceed 20 percent opacity, as a three-minute average.
- 2.c** Visible particulate emissions from the stacks associated with this emissions unit shall not exceed 10 percent opacity, as a six-minute average.
- 2.d** The hourly emission limitations outlined in term A.1. are based upon the emissions unit's potential to emit. Therefore, no hourly records are required to demonstrate compliance with these limitations.
- 2.e** The permittee shall minimize or eliminate visible particulate emissions of fugitive dust by minimizing drop heights, and the use of local capture hoods vented to the fabric filter.

B. Operational Restrictions

- 1. The pressure drop across the screening dust collector shall be maintained within the range of 1 - 5 inches of water while the emissions unit is in operation.

C. Monitoring and/or Recordkeeping Requirements

- 1. The permittee shall properly install, operate, and maintain equipment to monitor the pressure drop across the fabric filter baghouse while the emissions unit is in operation. The monitoring equipment shall be installed, calibrated, operated, and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual(s). The permittee shall record the pressure drop across the fabric filter on a weekly basis.

D. Reporting Requirements

- 1. The permittee shall submit pressure drop deviation (excursion) reports that identify all periods of time during which the pressure drop across fabric filter did not comply with the allowable range specified in term B.1.
- 2. The deviation reports shall be submitted in accordance with the reporting requirements

of the General Terms and Conditions of this permit.

E. Testing Requirements

1. Compliance with the emissions limitations in Section A.1 of these terms and conditions shall be determined in accordance with the following methods:

- a. Emissions Limitations:
0.19 lb/hr PE; 0.84 TPY PE

Applicable Compliance Method:

Hourly emissions of particulate emissions (PE) shall be calculated and compliance determined using the following equations.

$$\text{lb PE/hr} = (A) \times (B) \times (1-C)$$

Where,

A = maximum hourly amount of refractory material produced, in tons/hr.

B = PE emission factor of 8.5 pounds per ton of raw material processed, from AP-42, Table 11.3-1(August 1997)

C = Control efficiency as a decimal percentage; here = 0.997

If testing is required to determine compliance with the with the hourly particulate emissions limitation, then testing shall be conducted using the following method: Methods 1-5 of 40 CFR, Part 60, Appendix A.

Annual emissions of particulate emissions (PE) shall be calculated and compliance determined using the equation above multiplied by 8760 hr/year and divided by 2000 lbs/ton.

- b. Emissions Limitations:
0.024 lb/hr PM10; 0.11 TPY PM10

Applicable Compliance Method:

Hourly emissions of particulate matter less than or equal to 10 microns in diameter (PM10) shall be calculated and compliance determined using the following equations.

$$\text{lb PE/hr} = (A) \times (B)$$

Where,

Emissions Unit ID: P001

- A = maximum hourly amount of raw material processed, in tons/hr.
B = PM10 emissions factor of 0.0032 pound of controlled PM10 per ton raw material processed, from AP-42, Table 11.3-1(August 1997)

If testing is required to determine compliance with the with the hourly particulate emission limitation, then testing shall be conducted using the following method: Methods 1-4 of 40 CFR, Part 60, Appendix A, and Method 201 of 40 CFR 51, Appendix M.

Annual emissions of particulate matter less than or equal to 10 microns in diameter (PM10) shall be calculated and compliance determined using the equation above multiplied by 8760 hr/year and divided by 2000 lbs/ton.

c. Emissions Limitations:

Visible particulate emissions from the fabric filter stack outlet shall not exceed ten percent (10%) opacity, as a six minute average.

Visible particulate emissions of fugitive dust shall not exceed 20% opacity as a three minute average.

Applicable Compliance Method:

Compliance shall be determined in accordance with Test Method 9 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources"), as such Appendix existed on July 1, 2002.

2. Compliance with the pressure drop limitation in term and condition B.1 shall be demonstrated with the record keeping required in term and condition C.1.

F. Miscellaneous Requirements

1. The terms and conditions of this permit to install shall supersede the terms and conditions established in permit to install 14-3908 as issued October 12, 1995.

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

- 1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	
P002 - Smith Mixer	OAC rule 3745-31-05(A)(3)	OAC rule 3745-17-11
	OAC rule 3745-17-07(A)(1)	
	OAC rule 3745-17-07(B)(1)	
	OAC rule 3745-17-08(B)	

Uni-R
PTI A
Issued: 6/1/2006

Emissions Unit ID: **P002**

Applicable Emissions
Limitations/Control Measures

Particulate emissions (PE) shall not exceed 0.13 pound per hour and 0.56 ton per year.

Particulate emissions 10 microns and less in diameter (PM10) shall not exceed 0.016 pound per hour and 0.07 ton per year.

See term A.2.c. and term A.2.e.

The requirements of this rule also include compliance with the requirements of OAC rule 3745-17-07(B)(1).

The emissions limitation specified by this rule is less stringent than the emissions limitation established pursuant to OAC rule 3745-31-05(A)(3).

See term A.2.b.

The emissions limitation specified by this rule is less stringent than the emissions limitation established pursuant to OAC rule 3745-31-05(A)(3).

The emissions limitation specified by this rule is less stringent than the emissions limitation established pursuant

to OAC rule 3745-31-05(A)(3).

2. Additional Terms and Conditions

- 2.a Compliance with OAC rule 3745-31-05(A)(3) shall be demonstrated by compliance with the emissions limitations and the use of a fabric filter.
- 2.b Visible fugitive particulate emissions shall not exceed 20 percent opacity, as a three-minute average.
- 2.c Visible particulate emissions from the stacks associated with this emissions unit shall not exceed 10 percent opacity, as a six-minute average.
- 2.d The hourly emission limitations outlined in term A.1. are based upon the emissions unit's potential to emit. Therefore, no hourly records are required to demonstrate compliance with these limitations.
- 2.e The permittee shall minimize or eliminate visible particulate emissions of fugitive dust by minimizing drop heights, and the use of local capture hoods vented to the fabric filter.

B. Operational Restrictions

- 1. The pressure drop across the screening dust collector shall be maintained within the range of 1 - 5 inches of water while the emissions unit is in operation.

C. Monitoring and/or Recordkeeping Requirements

- 1. The permittee shall properly install, operate, and maintain equipment to monitor the pressure drop across the fabric filter baghouse while the emissions unit is in operation. The monitoring equipment shall be installed, calibrated, operated, and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual(s). The permittee shall record the pressure drop across the fabric filter on a weekly basis.

D. Reporting Requirements

- 1. The permittee shall submit pressure drop deviation (excursion) reports that identify all periods of time during which the pressure drop across fabric filter did not comply with the allowable range specified in term B.1.
- 2. The deviation reports shall be submitted in accordance with the reporting requirements of the General Terms and Conditions of this permit.

E. Testing Requirements

1. Compliance with the emissions limitations in Section A.1 of these terms and conditions shall be determined in accordance with the following methods:

- a. Emissions Limitations:
0.13 lb/hr PE; 0.56 TPY PE

Applicable Compliance Method:

Hourly emissions of particulate emissions (PE) shall be calculated and compliance determined using the following equations.

$$\text{lb PE/hr} = (A) \times (B) \times (1-C)$$

Where,

A = maximum hourly amount of refractory material produced, in tons/hr.

B = PE emission factor of 8.5 pounds per ton of raw material processed, from AP-42, Table 11.3-1(August 1997)

C = Control efficiency as a decimal percentage; here = 0.997

If testing is required to determine compliance with the with the hourly particulate emissions limitation, then testing shall be conducted using the following method: Methods 1-5 of 40 CFR, Part 60, Appendix A.

Annual emissions of particulate emissions (PE) shall be calculated and compliance determined using the equation above multiplied by 8760 hr/year and divided by 2000 lbs/ton.

- b. Emissions Limitations:
0.016 lb/hr PM10; 0.07 TPY PM10

Applicable Compliance Method:

Hourly emissions of particulate matter less than or equal to 10 microns in diameter (PM10) shall be calculated and compliance determined using the following equations.

$$\text{lb PE/hr} = (A) \times (B)$$

Where,

- A = maximum hourly amount of raw material processed, in tons/hr.
B = PM10 emissions factor of 0.0032 pound of controlled PM10 per ton raw material processed, from AP-42, Table 11.3-1(August 1997)

If testing is required to determine compliance with the with the hourly particulate emission limitation, then testing shall be conducted using the following method: Methods 1-4 of 40 CFR, Part 60, Appendix A, and Method 201 of 40 CFR 51, Appendix M.

Annual emissions of particulate matter less than or equal to 10 microns in diameter (PM10) shall be calculated and compliance determined using the equation above multiplied by 8760 hr/year and divided by 2000 lbs/ton.

- c. Emissions Limitations:
Visible particulate emissions from the fabric filter stack outlet shall not exceed ten percent (10%) opacity, as a six minute average.

Visible particulate emissions of fugitive dust shall not exceed 20% opacity as a three minute average.

Applicable Compliance Method:

Compliance shall be determined in accordance with Test Method 9 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources"), as such Appendix existed on July 1, 2002.

2. Compliance with the pressure drop limitation in term and condition B.1 shall be demonstrated with the record keeping required in term and condition C.1.

F. Miscellaneous Requirements

1. The terms and conditions of this permit to install shall supersede the terms and conditions established in permit to install 14-603 as issued March 13, 1985.

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	
P003 - Burton Mixer 1	OAC rule 3745-31-05(A)(3)	OAC rule 3745-17-11
	OAC rule 3745-17-07(A)(1)	
	OAC rule 3745-17-07(B)(1)	
	OAC rule 3745-17-08(B)	

Applicable Emissions
Limitations/Control Measures

Particulate emissions (PE) shall not exceed 0.13 pound per hour and 0.56 ton per year.

Particulate emissions 10 microns and less in diameter (PM10) shall not exceed 0.016 pound per hour and 0.07 ton per year.

See term A.2.c. and term A.2.e.

The requirements of this rule also include compliance with the requirements of OAC rule 3745-17-07(B)(1).

The emissions limitation specified by this rule is less stringent than the emissions limitation established pursuant to OAC rule 3745-31-05(A)(3).

See term A.2.b.

The emissions limitation specified by this rule is less stringent than the emissions limitation established pursuant to OAC rule 3745-31-05(A)(3).

The emissions limitation specified by this rule is less stringent than the emissions limitation established pursuant to OAC rule 3745-31-05(A)(3).

2. Additional Terms and Conditions

- 2.a** Compliance with OAC rule 3745-31-05(A)(3) shall be demonstrated by compliance with the emissions limitations and the use of a fabric filter.
- 2.b** Visible fugitive particulate emissions shall not exceed 20 percent opacity, as a three-minute average.
- 2.c** Visible particulate emissions from the stacks associated with this emissions unit shall not exceed 10 percent opacity, as a six-minute average.
- 2.d** The hourly emission limitations outlined in term A.1. are based upon the emissions unit's potential to emit. Therefore, no hourly records are required to demonstrate compliance with these limitations.
- 2.e** The permittee shall minimize or eliminate visible particulate emissions of fugitive dust by minimizing drop heights, and the use of local capture hoods vented to the fabric filter.

B. Operational Restrictions

- 1. The pressure drop across the screening dust collector shall be maintained within the range of 1 - 5 inches of water while the emissions unit is in operation.

C. Monitoring and/or Recordkeeping Requirements

- 1. The permittee shall properly install, operate, and maintain equipment to monitor the pressure drop across the fabric filter baghouse while the emissions unit is in operation. The monitoring equipment shall be installed, calibrated, operated, and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual(s). The permittee shall record the pressure drop across the fabric filter on a weekly basis.

D. Reporting Requirements

- 1. The permittee shall submit pressure drop deviation (excursion) reports that identify all periods of time during which the pressure drop across fabric filter did not comply with the allowable range specified in term B.1.
- 2. The deviation reports shall be submitted in accordance with the reporting requirements

of the General Terms and Conditions of this permit.

E. Testing Requirements

1. Compliance with the emissions limitations in Section A.1 of these terms and conditions shall be determined in accordance with the following methods:

- a. Emissions Limitations:
0.13 lb/hr PE; 0.56 TPY PE

Applicable Compliance Method:

Hourly emissions of particulate emissions (PE) shall be calculated and compliance determined using the following equations.

$$\text{lb PE/hr} = (A) \times (B) \times (1-C)$$

Where,

A = maximum hourly amount of refractory material produced, in tons/hr.

B = PE emission factor of 8.5 pounds per ton of raw material processed, from AP-42, Table 11.3-1(August 1997)

C = Control efficiency as a decimal percentage; here = 0.997

If testing is required to determine compliance with the with the hourly particulate emissions limitation, then testing shall be conducted using the following method: Methods 1-5 of 40 CFR, Part 60, Appendix A.

Annual emissions of particulate emissions (PE) shall be calculated and compliance determined using the equation above multiplied by 8760 hr/year and divided by 2000 lbs/ton.

- b. Emissions Limitations:
0.016 lb/hr PM10; 0.07 TPY PM10

Applicable Compliance Method:

Hourly emissions of particulate matter less than or equal to 10 microns in diameter (PM10) shall be calculated and compliance determined using the following equations.

$$\text{lb PE/hr} = (A) \times (B)$$

Where,

- A = maximum hourly amount of raw material processed, in tons/hr.
B = PM10 emissions factor of 0.0032 pound of controlled PM10 per ton raw material processed, from AP-42, Table 11.3-1(August 1997)

If testing is required to determine compliance with the with the hourly particulate emission limitation, then testing shall be conducted using the following method: Methods 1-4 of 40 CFR, Part 60, Appendix A, and Method 201 of 40 CFR 51, Appendix M.

Annual emissions of particulate matter less than or equal to 10 microns in diameter (PM10) shall be calculated and compliance determined using the equation above multiplied by 8760 hr/year and divided by 2000 lbs/ton.

- c. Emissions Limitations:
Visible particulate emissions from the fabric filter stack outlet shall not exceed ten percent (10%) opacity, as a six minute average.

Visible particulate emissions of fugitive dust shall not exceed 20% opacity as a three minute average.

Applicable Compliance Method:

Compliance shall be determined in accordance with Test Method 9 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources"), as such Appendix existed on July 1, 2002.

2. Compliance with the pressure drop limitation in term and condition B.1 shall be demonstrated with the record keeping required in term and condition C.1.

F. Miscellaneous Requirements

1. The terms and conditions of this permit to install shall supersede the terms and conditions established in permit to install 14-3908 as issued October 12, 1995.

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	
P005 - Burton Mixer 2	OAC rule 3745-31-05(A)(3)	OAC rule 3745-17-11
	OAC rule 3745-17-07(A)(1)	
	OAC rule 3745-17-07(B)(1)	
	OAC rule 3745-17-08(B)	

Applicable Emissions
Limitations/Control Measures

Particulate emissions (PE) shall not exceed 0.13 pound per hour and 0.56 ton per year.

Particulate emissions 10 microns and less in diameter (PM10) shall not exceed 0.016 pound per hour and 0.07 ton per year.

See term A.2.c. and term A.2.e.

The requirements of this rule also include compliance with the requirements of OAC rule 3745-17-07(B)(1).

The emissions limitation specified by this rule is less stringent than the emissions limitation established pursuant to OAC rule 3745-31-05(A)(3).

See term A.2.b.

The emissions limitation specified by this rule is less stringent than the emissions limitation established pursuant to OAC rule 3745-31-05(A)(3).

The emissions limitation specified by this rule is less stringent than the emissions limitation established pursuant

to OAC rule 3745-31-05(A)(3).

2. Additional Terms and Conditions

- 2.a** Compliance with OAC rule 3745-31-05(A)(3) shall be demonstrated by compliance with the emissions limitations and the use of a fabric filter.
- 2.b** Visible fugitive particulate emissions shall not exceed 20 percent opacity, as a three-minute average.
- 2.c** Visible particulate emissions from the stacks associated with this emissions unit shall not exceed 10 percent opacity, as a six-minute average.
- 2.d** The hourly emission limitations outlined in term A.1. are based upon the emissions unit's potential to emit. Therefore, no hourly records are required to demonstrate compliance with these limitations.
- 2.e** The permittee shall minimize or eliminate visible particulate emissions of fugitive dust by minimizing drop heights, and the use of local capture hoods vented to the fabric filter.

B. Operational Restrictions

- 1. The pressure drop across the screening dust collector shall be maintained within the range of 1 - 5 inches of water while the emissions unit is in operation.

C. Monitoring and/or Recordkeeping Requirements

- 1. The permittee shall properly install, operate, and maintain equipment to monitor the pressure drop across the fabric filter baghouse while the emissions unit is in operation. The monitoring equipment shall be installed, calibrated, operated, and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual(s). The permittee shall record the pressure drop across the fabric filter on a weekly basis.

D. Reporting Requirements

- 1. The permittee shall submit pressure drop deviation (excursion) reports that identify all periods of time during which the pressure drop across fabric filter did not comply with the allowable range specified in term B.1.
- 2. The deviation reports shall be submitted in accordance with the reporting requirements of the General Terms and Conditions of this permit.

E. Testing Requirements

1. Compliance with the emissions limitations in Section A.1 of these terms and conditions shall be determined in accordance with the following methods:

- a. Emissions Limitations:
0.13 lb/hr PE; 0.56 TPY PE

Applicable Compliance Method:

Hourly emissions of particulate emissions (PE) shall be calculated and compliance determined using the following equations.

$$\text{lb PE/hr} = (A) \times (B) \times (1-C)$$

Where,

A = maximum hourly amount of refractory material produced, in tons/hr.

B = PE emission factor of 8.5 pounds per ton of raw material processed, from AP-42, Table 11.3-1(August 1997)

C = Control efficiency as a decimal percentage; here = 0.997

If testing is required to determine compliance with the with the hourly particulate emissions limitation, then testing shall be conducted using the following method: Methods 1-5 of 40 CFR, Part 60, Appendix A.

Annual emissions of particulate emissions (PE) shall be calculated and compliance determined using the equation above multiplied by 8760 hr/year and divided by 2000 lbs/ton.

- b. Emissions Limitations:
0.016 lb/hr PM10; 0.07 TPY PM10

Applicable Compliance Method:

Hourly emissions of particulate matter less than or equal to 10 microns in diameter (PM10) shall be calculated and compliance determined using the following equations.

$$\text{lb PE/hr} = (A) \times (B)$$

Where,

Uni-Ref Inc
PTI Application: 11-05822
Issue

Facility ID: 1431403168

Emissions Unit ID: P005

- A = maximum hourly amount of raw material processed, in tons/hr.
B = PM10 emissions factor of 0.0032 pound of controlled PM10 per ton raw material processed, from AP-42, Table 11.3-1(August 1997)

If testing is required to determine compliance with the with the hourly particulate emission limitation, then testing shall be conducted using the following method: Methods 1-4 of 40 CFR, Part 60, Appendix A, and Method 201 of 40 CFR 51, Appendix M.

Annual emissions of particulate matter less than or equal to 10 microns in diameter (PM10) shall be calculated and compliance determined using the equation above multiplied by 8760 hr/year and divided by 2000 lbs/ton.

- c. Emissions Limitations:
Visible particulate emissions from the fabric filter stack outlet shall not exceed ten percent (10%) opacity, as a six minute average.

Visible particulate emissions of fugitive dust shall not exceed 20% opacity as a three minute average.

Applicable Compliance Method:

Compliance shall be determined in accordance with Test Method 9 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources"), as such Appendix existed on July 1, 2002.

2. Compliance with the pressure drop limitation in term and condition B.1 shall be demonstrated with the record keeping required in term and condition C.1.

F. Miscellaneous Requirements

None

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	
P006 - Eirich Mixer 2	OAC rule 3745-31-05(A)(3)	OAC rule 3745-17-11
	OAC rule 3745-17-07(A)(1)	
	OAC rule 3745-17-07(B)(1)	
	OAC rule 3745-17-08(B)	

Applicable Emissions
Limitations/Control Measures

Particulate emissions (PE) shall not exceed 0.19 pound per hour and 0.84 ton per year.

Particulate emissions 10 microns and less in diameter (PM10) shall not exceed 0.024 pound per hour and 0.11 ton per year.

See term A.2.c. and term A.2.e.

The requirements of this rule also include compliance with the requirements of OAC rule 3745-17-07(B)(1).

The emissions limitation specified by this rule is less stringent than the emissions limitation established pursuant to OAC rule 3745-31-05(A)(3).

See term A.2.b.

The emissions limitation specified by this rule is less stringent than the emissions limitation established pursuant to OAC rule 3745-31-05(A)(3).

The emissions limitation specified by this rule is less stringent than the emissions limitation established pursuant to OAC rule 3745-31-05(A)(3).

2. Additional Terms and Conditions

- 2.a** Compliance with OAC rule 3745-31-05(A)(3) shall be demonstrated by compliance with the emissions limitations and the use of a fabric filter.
- 2.b** Visible fugitive particulate emissions shall not exceed 20 percent opacity, as a three-minute average.
- 2.c** Visible particulate emissions from the stacks associated with this emissions unit shall not exceed 10 percent opacity, as a six-minute average.
- 2.d** The hourly emission limitations outlined in term A.1. are based upon the emissions unit's potential to emit. Therefore, no hourly records are required to demonstrate compliance with these limitations.
- 2.e** The permittee shall minimize or eliminate visible particulate emissions of fugitive dust by minimizing drop heights, and the use of local capture hoods vented to the fabric filter.

B. Operational Restrictions

- 1. The pressure drop across the screening dust collector shall be maintained within the range of 1 - 5 inches of water while the emissions unit is in operation.

C. Monitoring and/or Recordkeeping Requirements

- 1. The permittee shall properly install, operate, and maintain equipment to monitor the pressure drop across the fabric filter baghouse while the emissions unit is in operation. The monitoring equipment shall be installed, calibrated, operated, and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual(s). The permittee shall record the pressure drop across the fabric filter on a weekly basis.

D. Reporting Requirements

- 1. The permittee shall submit pressure drop deviation (excursion) reports that identify all periods of time during which the pressure drop across fabric filter did not comply with the allowable range specified in term B.1.
- 2. The deviation reports shall be submitted in accordance with the reporting requirements

of the General Terms and Conditions of this permit.

E. Testing Requirements

1. Compliance with the emissions limitations in Section A.1 of these terms and conditions shall be determined in accordance with the following methods:

- a. Emissions Limitations:
0.19 lb/hr PE; 0.84 TPY PE

Applicable Compliance Method:

Hourly emissions of particulate emissions (PE) shall be calculated and compliance determined using the following equations.

$$\text{lb PE/hr} = (A) \times (B) \times (1-C)$$

Where,

A = maximum hourly amount of refractory material produced, in tons/hr.

B = PE emission factor of 8.5 pounds per ton of raw material processed, from AP-42, Table 11.3-1(August 1997)

C = Control efficiency as a decimal percentage; here = 0.997

If testing is required to determine compliance with the with the hourly particulate emissions limitation, then testing shall be conducted using the following method: Methods 1-5 of 40 CFR, Part 60, Appendix A.

Annual emissions of particulate emissions (PE) shall be calculated and compliance determined using the equation above multiplied by 8760 hr/year and divided by 2000 lbs/ton.

- b. Emissions Limitations:
0.024 lb/hr PM10; 0.11 TPY PM10

Applicable Compliance Method:

Hourly emissions of particulate matter less than or equal to 10 microns in diameter (PM10) shall be calculated and compliance determined using the following equations.

$$\text{lb PE/hr} = (A) \times (B)$$

Where,

- A = maximum hourly amount of raw material processed, in tons/hr.
B = PM10 emissions factor of 0.0032 pound of controlled PM10 per ton raw material processed, from AP-42, Table 11.3-1(August 1997)

If testing is required to determine compliance with the with the hourly particulate emission limitation, then testing shall be conducted using the following method: Methods 1-4 of 40 CFR, Part 60, Appendix A, and Method 201 of 40 CFR 51, Appendix M.

Annual emissions of particulate matter less than or equal to 10 microns in diameter (PM10) shall be calculated and compliance determined using the equation above multiplied by 8760 hr/year and divided by 2000 lbs/ton.

- c. Emissions Limitations:
Visible particulate emissions from the fabric filter stack outlet shall not exceed ten percent (10%) opacity, as a six minute average.

Visible particulate emissions of fugitive dust shall not exceed 20% opacity as a three minute average.

Applicable Compliance Method:

Compliance shall be determined in accordance with Test Method 9 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources"), as such Appendix existed on July 1, 2002.

2. Compliance with the pressure drop limitation in term and condition B.1 shall be demonstrated with the record keeping required in term and condition C.1.

F. Miscellaneous Requirements

None

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	
P007 - Bulk Batching System	OAC rule 3745-31-05(A)(3)	OAC rule 3745-17-11
	OAC rule 3745-17-07(A)(1)	
	OAC rule 3745-17-07(B)(1)	
	OAC rule 3745-17-08(B)	

Uni-Ref Inc
PTI Application: 14-05822
Issue

Facility ID: 1431403168

Emissions Unit ID: P007

Applicable Emissions
Limitations/Control Measures

Particulate emissions (PE) shall not exceed 38 pound per hour and 1.68 tons per year.

Particulate emissions 10 microns and less in diameter (PM10) shall not exceed 0.048 pound per hour and 0.21 ton per year.

See term A.2.c. and term A.2.e.

The requirements of this rule also include compliance with the requirements of OAC rule 3745-17-07(B)(1).

The emissions limitation specified by this rule is less stringent than the emissions limitation established pursuant to OAC rule 3745-31-05(A)(3).

See term A.2.b.

The emissions limitation specified by this rule is less stringent than the emissions limitation established pursuant to OAC rule 3745-31-05(A)(3).

The emissions limitation specified by this rule is less stringent than the emissions limitation established pursuant to OAC rule 3745-31-05(A)(3).

2. Additional Terms and Conditions

- 2.a** Compliance with OAC rule 3745-31-05(A)(3) shall be demonstrated by compliance with the emissions limitations and the use of a fabric filter.
- 2.b** Visible fugitive particulate emissions shall not exceed 20 percent opacity, as a three-minute average.
- 2.c** Visible particulate emissions from the stacks associated with this emissions unit shall not exceed 10 percent opacity, as a six-minute average.
- 2.d** The hourly emission limitations outlined in term A.1. are based upon the emissions unit's potential to emit. Therefore, no hourly records are required to demonstrate compliance with these limitations.
- 2.e** The permittee shall minimize or eliminate visible particulate emissions of fugitive dust by minimizing drop heights, and the use of local capture hoods vented to the fabric filter.

B. Operational Restrictions

- 1. The pressure drop across the screening dust collector shall be maintained within the range of 1 - 5 inches of water while the emissions unit is in operation.

C. Monitoring and/or Recordkeeping Requirements

- 1. The permittee shall properly install, operate, and maintain equipment to monitor the pressure drop across the fabric filter baghouse while the emissions unit is in operation. The monitoring equipment shall be installed, calibrated, operated, and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual(s). The permittee shall record the pressure drop across the fabric filter on a weekly basis.

D. Reporting Requirements

- 1. The permittee shall submit pressure drop deviation (excursion) reports that identify all periods of time during which the pressure drop across fabric filter did not comply with the allowable range specified in term B.1.
- 2. The deviation reports shall be submitted in accordance with the reporting requirements

of the General Terms and Conditions of this permit.

E. Testing Requirements

1. Compliance with the emissions limitations in Section A.1 of these terms and conditions shall be determined in accordance with the following methods:

- a. Emissions Limitations:
0.38 lb/hr PE; 1.68 TPY PE

Applicable Compliance Method:

Hourly emissions of particulate emissions (PE) shall be calculated and compliance determined using the following equations.

$$\text{lb PE/hr} = (A) \times (B) \times (1-C)$$

Where,

A = maximum hourly amount of refractory material produced, in tons/hr.

B = PE emission factor of 8.5 pounds per ton of raw material processed, from AP-42, Table 11.3-1(August 1997)

C = Control efficiency as a decimal percentage; here = 0.997

If testing is required to determine compliance with the with the hourly particulate emissions limitation, then testing shall be conducted using the following method: Methods 1-5 of 40 CFR, Part 60, Appendix A.

Annual emissions of particulate emissions (PE) shall be calculated and compliance determined using the equation above multiplied by 8760 hr/year and divided by 2000 lbs/ton.

- b. Emissions Limitations:
0.048 lb/hr PM10; 0.21 TPY PM10

Applicable Compliance Method:

Hourly emissions of particulate matter less than or equal to 10 microns in diameter (PM10) shall be calculated and compliance determined using the following equations.

$$\text{lb PE/hr} = (A) \times (B)$$

Where,

Emissions Unit ID: P007

- A = maximum hourly amount of raw material processed, in tons/hr.
B = PM10 emissions factor of 0.0032 pound of controlled PM10 per ton raw material processed, from AP-42, Table 11.3-1(August 1997)

If testing is required to determine compliance with the with the hourly particulate emission limitation, then testing shall be conducted using the following method: Methods 1-4 of 40 CFR, Part 60, Appendix A, and Method 201 of 40 CFR 51, Appendix M.

Annual emissions of particulate matter less than or equal to 10 microns in diameter (PM10) shall be calculated and compliance determined using the equation above multiplied by 8760 hr/year and divided by 2000 lbs/ton.

- c. Emissions Limitations:
Visible particulate emissions from the fabric filter stack outlet shall not exceed ten percent (10%) opacity, as a six minute average.

Visible particulate emissions of fugitive dust shall not exceed 20% opacity as a three minute average.

Applicable Compliance Method:

Compliance shall be determined in accordance with Test Method 9 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources"), as such Appendix existed on July 1, 2002.

2. Compliance with the pressure drop limitation in term and condition B.1 shall be demonstrated with the record keeping required in term and condition C.1.

F. Miscellaneous Requirements

None