



State of Ohio Environmental Protection Agency

**RE: FINAL PERMIT TO INSTALL
HAMILTON COUNTY**

CERTIFIED MAIL

Street Address:

122 S. Front Street

Lazarus Gov. Center TELE: (614) 644-3020 FAX: (614) 644-2329

Mailing Address:

Lazarus Gov. Center
P.O. Box 1049

Application No: 14-05345

DATE: 11/19/2002

EI Ceramics LLC
Graham Roberts
1420 Return Shot Lane
Loveland, OH 45140

Enclosed please find an Ohio EPA Permit to Install which will allow you to install the described source(s) in a manner indicated in the permit. Because this permit contains several conditions and restrictions, I urge you to read it carefully.

The Ohio EPA is urging companies to investigate pollution prevention and energy conservation. Not only will this reduce pollution and energy consumption, but it can also save you money. If you would like to learn ways you can save money while protecting the environment, please contact our Office of Pollution Prevention at (614) 644-3469.

You are hereby notified that this action by the Director is final and may be appealed to the Ohio Environmental Review Appeals Commission pursuant to Chapter 3745.04 of the Ohio Revised Code. The appeal must be in writing and set forth the action complained of and the grounds upon which the appeal is based. It must be filed within thirty (30) days after the notice of the Directors action. A copy of the appeal must be served on the Director of the Ohio Environmental Protection Agency within three (3) days of filing with the Commission. An appeal may be filed with the Environmental Review Appeals Commission at the following address:

Environmental Review Appeals Commission
236 East Town Street, Room 300
Columbus, Ohio 43215

Very truly yours,

Michael W. Ahern, Supervisor
Field Operations and Permit Section
Division of Air Pollution Control

cc: USEPA

HCDES



**Permit To Install
Terms and Conditions**

**Issue Date: 11/19/2002
Effective Date: 11/19/2002**

FINAL PERMIT TO INSTALL 14-05345

Application Number: 14-05345
APS Premise Number: 1431404130
Permit Fee: **\$1000**
Name of Facility: EI Ceramics LLC
Person to Contact: Graham Roberts
Address: 1420 Return Shot Lane
Loveland, OH 45140

Location of proposed air contaminant source(s) [emissions unit(s)]:
**2600 Commerce Blvd.
Sharonville, Ohio**

Description of proposed emissions unit(s):
Ceramic shapes manufacturing process.

The above named entity is hereby granted a Permit to Install for the above described emissions unit(s) pursuant to Chapter 3745-31 of the Ohio Administrative Code. Issuance of this permit does not constitute expressed or implied approval or agreement that, if constructed or modified in accordance with the plans included in the application, the above described emissions unit(s) of environmental pollutants will operate in compliance with applicable State and Federal laws and regulations, and does not constitute expressed or implied assurance that if constructed or modified in accordance with those plans and specifications, the above described emissions unit(s) of pollutants will be granted the necessary permits to operate (air) or NPDES permits as applicable.

This permit is granted subject to the conditions attached hereto.

Ohio Environmental Protection Agency

Director

Part I - GENERAL TERMS AND CONDITIONS

A. Permit to Install General Terms and Conditions

1. Compliance Requirements

The emissions unit(s) identified in this Permit to Install shall remain in full compliance with all applicable State laws and regulations and the terms and conditions of this permit.

2. Reporting Requirements Related to Monitoring and Recordkeeping Requirements

The permittee shall submit required reports in the following manner:

- a. Reports of any required monitoring and/or recordkeeping information shall be submitted to the appropriate Ohio EPA District Office or local air agency.
- b. Except as otherwise may be provided in the terms and conditions for a specific emissions unit, quarterly written reports of (a) any deviations (excursions) from emission limitations, operational restrictions, and control device operating parameter limitations that have been detected by the testing, monitoring, and recordkeeping requirements specified in this permit, (b) the probable cause of such deviations, and (c) any corrective actions or preventive measures which have been or will be taken, shall be submitted to the appropriate Ohio EPA District Office or local air agency. If no deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted quarterly, i.e., by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters. (These quarterly reports shall exclude deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06.)

3. Records Retention Requirements

Each record of any monitoring data, testing data, and support information required pursuant to this permit shall be retained for a period of five years from the date the record was created. Support information shall include, but not be limited to, all calibration and maintenance records and all original strip-chart recordings for continuous monitoring instrumentation, and copies of all reports required by this permit. Such records may be maintained in computerized form.

4. Inspections and Information Requests

The Director of the Ohio EPA, or an authorized representative of the Director, may, subject to the safety requirements of the permittee and without undue delay, enter upon the premises of this source at any reasonable time for purposes of making inspections, conducting tests, examining records or reports pertaining to any emission of air contaminants, and determining compliance with any applicable State air pollution laws and regulations and the terms and conditions of this permit. The permittee shall furnish to the Director of the Ohio EPA, or an authorized

representative of the Director, upon receipt of a written request and within a reasonable time, any information that may be requested to determine whether cause exists for modifying, reopening or revoking this permit or to determine compliance with this permit. Upon verbal or written request, the permittee shall also furnish to the Director of the Ohio EPA, or an authorized representative of the Director, copies of records required to be kept by this permit.

5. Scheduled Maintenance/Malfunction Reporting

Any scheduled maintenance of air pollution control equipment shall be performed in accordance with paragraph (A) of OAC rule 3745-15-06. The malfunction of any emissions units or any associated air pollution control system(s) shall be reported to the appropriate Ohio EPA District Office or local air agency in accordance with paragraph (B) of OAC rule 3745-15-06. Except as provided in that rule, any scheduled maintenance or malfunction necessitating the shutdown or bypassing of any air pollution control system(s) shall be accompanied by the shutdown of the emissions unit(s) that is (are) served by such control system(s).

6. Permit Transfers

Any transferee of this permit shall assume the responsibilities of the prior permit holder. The appropriate Ohio EPA District Office or local air agency must be notified in writing of any transfer of this permit.

7. Air Pollution Nuisance

The air contaminants emitted by the emissions units covered by this permit shall not cause a public nuisance, in violation of OAC rule 3745-15-07.

8. Termination of Permit to Install

This Permit to Install shall terminate within eighteen months of the effective date of the Permit to Install if the owner or operator has not undertaken a continuing program of installation or modification or has not entered into a binding contractual obligation to undertake and complete within a reasonable time a continuing program of installation or modification. This deadline may be extended by up to 12 months if application is made to the Director within a reasonable time before the termination date and the party shows good cause for any such extension.

9. Construction of New Sources(s)

The proposed emissions unit(s) shall be constructed in strict accordance with the plans and application submitted for this permit to the Director of the Ohio Environmental Protection Agency. There may be no deviation from the approved plans without the express, written approval of the Agency. Any deviations from the approved plans or the above conditions may lead to such sanctions

and penalties as provided under Ohio law. Approval of these plans does not constitute an assurance that the proposed facilities will operate in compliance with all Ohio laws and regulations. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed sources cannot meet the requirements of this permit or cannot meet applicable standards.

If the construction of the proposed emissions unit(s) has already begun or has been completed prior to the date the Director of the Environmental Protection Agency approves the permit application and plans, the approval does not constitute expressed or implied assurance that the proposed facility has been constructed in accordance with the approved plans. The action of beginning and/or completing construction prior to obtaining the Director's approval constitutes a violation of OAC rule 3745-31-02. Furthermore, issuance of the Permit to Install does not constitute an assurance that the proposed source will operate in compliance with all Ohio laws and regulations. Approval of the plans in any case is not to be construed as an approval of the facility as constructed and/or completed. Moreover, issuance of the Permit to Install is not to be construed as a waiver of any rights that the Ohio Environmental Protection Agency (or other persons) may have against the applicant for starting construction prior to the effective date of the permit. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed facilities cannot meet the requirements of this permit or cannot meet applicable standards.

10. Public Disclosure

The facility is hereby notified that this permit, and all agency records concerning the operation of this permitted source, are subject to public disclosure in accordance with OAC rule 3745-49-03.

11. Applicability

This Permit to Install is applicable only to the emissions unit(s) identified in the Permit to Install. Separate application must be made to the Director for the installation or modification of any other emissions unit(s).

12. Best Available Technology

As specified in OAC Rule 3745-31-05, all new sources must employ Best Available Technology (BAT). Compliance with the terms and conditions of this permit will fulfill this requirement.

13. Source Operation and Operating Permit Requirements After Completion of Construction

This facility is permitted to operate each source described by this Permit to Install for a period of up to one year from the date the source commenced operation. This permission to operate is granted only if the facility complies with all requirements contained in this permit and all applicable air pollution laws, regulations, and policies. Pursuant to OAC Chapter 3745-35, the permittee shall submit a complete operating permit application within ninety (90) days after commencing operation of the emissions unit(s) covered by this permit.

EI Ceramics LLC
PTI Application: 14-05345
Issued: 11/19/2002

Facility ID: 1431404130

14. Construction Compliance Certification

The applicant shall provide Ohio EPA with a written certification (see enclosed form) that the facility has been constructed in accordance with the Permit to Install application and the terms and conditions of the Permit to Install. The certification shall be provided to Ohio EPA upon completion of construction but prior to startup of the source.

15. Fees

The permittee shall pay fees to the Director of the Ohio EPA in accordance with ORC section 3745.11 and OAC Chapter 3745-78. The permittee shall pay all applicable Permit to Install fees within 30 days after the issuance of this Permit to Install.

B. Permit to Install Summary of Allowable Emissions

The following information summarizes the total allowable emissions, by pollutant, based on the individual allowable emissions of each air contaminant source identified in this permit.

SUMMARY (for informational purposes only)
TOTAL PERMIT TO INSTALL ALLOWABLE EMISSIONS

<u>Pollutant</u>	<u>Tons Per Year</u>
PM	12.44
PM10	4.42
OC	38.7
NOx	8.1
CO	9.6
SO2	1.6

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

- 1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	OAC rule 3745-17-07(B)(1) OAC rule 3745-17-08(B)
P001 - Mixing Process (Three Mixers), Batch Weighing, Rotary Dryer, Vibrating Screen and Hammermill	OAC rule 3745-31-05(A)(3)	OAC rule 3745-17-11

OAC rule 3745-21-07(G)

OAC rule 3745-31-05(D)

OAC rule 3745-17-07(A)(1)

Applicable Emissions
Limitations/Control Measures

2.37 lbs PM/hr, 10.4 TPY PM
0.67 lb PM10/hr, 2.93 TPY PM10
from the skip hoist, mixing process,
rotary dryer, belt conveyor, screen
and crush, chute and drum
2.37 lbs OC/hr from the rotary
dryer and afterburner.

Rotary dryer and Mixer area
afterburner emissions:
0.1 lb NOx/MMBtu, 3.88 TPY
NOx
0.084 lb CO/MMBtu, 3.26 TPY
CO
0.0006 lb SO2/MMBtu, 0.02 TPY
SO2
0.0076 lb PM/PM10/MMBtu, 0.29
TPY PM/PM10

The requirements of this rule also
include compliance with the
requirements of OAC rule
3745-17-07(A)(1),
3745-17-07(B)(1), 3745-17-08(B)
and 3745-31-05(D).

0.86 ton OC/month, 10.37 TPY
OC from the rotary dryer

See term A.2.c.

See term A.2.b.

See term A.2.f

The emission limitation specified by
this rule is less stringent than the
emission limitation established
pursuant to OAC rule
3745-31-05(A)(3).

The emission limitation specified by
this rule is less stringent than the
emission limitation established
pursuant to OAC rule
3745-31-05(A)(3).

2. Additional Terms and Conditions

- 2.a** Compliance with OAC rule 3745-31-05(A)(3) shall be demonstrated by compliance with the Air Toxics Policy, emissions limits, the use of a fabric filter to control the mixing and batching area and a thermal afterburner to control the mixing area (rotary dryer).
- 2.b** Visible particulate emissions from any fugitive dust emissions points shall not exceed 20 percent opacity, as a three-minute average, except as specified by rule.
- 2.c** Visible particulate emissions from the stacks associated with this emissions unit shall not exceed 20 percent opacity, as a six-minute average, except as specified by rule.
- 2.d** The hourly emission limitations outlined in term A.1. are based upon the emissions unit's potential to emit. Therefore, no hourly records are required to demonstrate compliance with these limits.
- 2.e** This emissions unit shall be equipped with a control device for OC emissions that is at least 95% efficient for OC emissions entering the control device.
- 2.f** The permittee shall minimize or eliminate visible particulate emissions from the batch weighing area.

B. Operational Restrictions

- 1. The pressure drop across the screening dust collector shall be maintained within the range of 1 - 8 inches of water while the emissions unit is in operation.
- 2. The average combustion temperature within the thermal incinerator, for any 3-hour block of time when the emissions unit is in operation, shall not be less than 1450 degrees Fahrenheit or more than 50 degrees Fahrenheit below the average temperature during the most recent emissions test that demonstrated the emissions unit was in compliance.

C. Monitoring and/or Recordkeeping Requirements

- 1. The permittee shall properly install, operate, and maintain equipment to monitor the pressure drop across the screening dust collector while the emissions unit is in operation. The monitoring equipment shall be installed, calibrated, operated, and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual(s). The permittee shall record the pressure drop across the fabric filter on a weekly basis.

Emissions Unit ID: P001

2. The permittee shall properly install operate and maintain a continuous temperature monitor and recorder which measures and records the combustion temperature within the thermal incinerator when the emissions unit is in operation. Units shall be in degrees Fahrenheit. The monitoring and recording devices shall be capable of accurately measuring the desired parameter. The temperature monitor and recorder shall be installed, calibrated, operated and maintained in accordance with the manufacturer's recommendations, with any modifications deemed necessary by the permittee.

The permittee shall collect and record the following information for each day:

- a. All 3-hour blocks of time during which the average combustion temperature within the thermal incinerator, when the emissions unit was in operation, was less than 1450 degrees Fahrenheit or more than 50 degrees Fahrenheit below the average temperature during the most recent emission test that demonstrated the emissions unit was in compliance.
 - b. A log of the downtime for the capture (collection) system, control device, and monitoring equipment, when the associated emissions unit was in operation.
3. The permittee shall collect and record the following information each month for this emissions unit:
 - a. The emission unit's production rate in tons/month.
 - b. The total OC emission rate, in tons per month [$a \times 73.41 \text{ lb. OC/ton organic solvent}^* \times (1-0.95)$ (or the control efficiency established during the most recent performance test) plus the emissions from the natural gas usage in the rotary dryer and afterburner].
 - * the emission factor is based on information submitted by the permittee.
 4. The permit to install for these emissions units (P001 and P002) was evaluated based on the actual materials (typically coatings and cleanup materials) and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was

applied for each pollutant emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Ground-Level Concentration (MAGLC).

The following summarizes the results of the modeling for the "worst case" pollutant(s):

Pollutant: Furfural

TLV (ug/m3): 7,900

Maximum Hourly Emission Rate (lbs/hr): 2.27

Predicted 1-Hour Maximum Ground-Level

Concentration (ug/m3): 137.0 (Emissions Unit P001 and P002 combined)

MAGLC (ug/m3): 188.1

Physical changes to or in the method of operation of the emissions unit after it's installation or modification could affect the parameters used to determine whether or not the "Air Toxics Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in the "Air Toxic Policy" include the following:

- a. Changes in the composition of the materials used (typically for coatings or cleanup materials), or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value previously modeled;
 - b. Changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and
 - c. Physical changes to the emissions unit or its exhaust parameters (e.g., increased/decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).
5. If the permittee determines that the "Air Toxic Policy" will be satisfied with the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01(VV)(1)(a)(ii), and a modification of the existing permit to install will not be required. If the change(s) is(are) defined as a modification under other provisions of the modification definition [other than (VV)(1)(a)(ii)], then the permittee shall obtain a final permit to install prior

to the change.

The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will satisfy the Air Toxic Policy:"

- a. A description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
- b. Documentation of it's evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and
- c. When the computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

D. Reporting Requirements

1. The permittee shall submit annual reports which specify the total particulate, PM10 and OC emissions for this emissions unit for the previous calendar year. These reports shall be submitted by January 31 of each year.
2. The permittee shall submit pressure drop deviation (excursion) reports that identify all periods of time during which the pressure drop across fabric filter did not comply with the allowable range specified in term B.1.
3. The permittee shall submit deviation (excursion) reports which identify all 3-hour blocks of time during which the average combustion temperature within the thermal incinerator does not comply with the temperature limitation specified in term B.2.
4. The permittee shall submit deviation (excursion) reports which identify any exceedance of the monthly OC emissions limit in term A.1.
5. The deviation reports shall be submitted in accordance with the reporting requirements of the General Terms and Conditions of this permit.

E. Testing Requirements

1. Compliance with the visible particulate emissions limitations in terms A.2.b and A.2.c shall be demonstrated by the methods outlined in 40 CFR Part 60, Appendix A, Method 9.
2. Compliance with the emission limitation in Section A.1 of these terms and conditions shall be

determined in accordance with the following method(s):

- a. Emissions Limitation:
2.37 lbs/hr PM

Applicable Compliance Method:

The PM emissions are calculated by multiplying the hourly production rate in tons per hour times the emission factor times the control efficiency. The emissions factors were provided in PTI application 14-05345 submitted August 7, 2002.

- b. Emissions Limitation:
10.4 TPY PM

Applicable Compliance Method:

The PM emissions are calculated by multiplying the annual production rate in tons per year times the emissions factor times the control efficiency and converting the emissions into tons. The emissions factors were provided in PTI application 14-05345 submitted August 7, 2002.

- c. Emissions Limitation:
0.67 lbs/hr PM10

Applicable Compliance Method:

The PM10 emissions are calculated by multiplying the hourly production rate in tons per hour times the emissions factor times the control efficiency. The emissions factors were provided in PTI application 14-05345.

- d. Emissions Limitation:
2.93 TPY PM10

Applicable Compliance Method:

The PM10 emissions are calculated by multiplying the annual production rate in tons per year times the emissions factor times the control efficiency and converting the emissions into tons. The emissions factors were provided in PTI application 14-05345 submitted August 7, 2002.

- e. Emissions Limitation:
2.37 lbs/hr OC from the rotary dryer and afterburner

Applicable Compliance Method:

The OC emissions are calculated by multiplying the hourly production rate in tons per

hour times the emission factor (73.41 lb per ton) times the control efficiency. The emission factor was provided in PTI application 14-05345 submitted August 7, 2002. Also add the emissions from the dryer and afterburner by multiplying the emission factors by the amount of the fuel burned. The emission factors are taken from AP-42, Fifth Edition, Chapter 1.4, Natural Gas Combustion.

- f. Emissions Limitation:
10.37 TPY OC from the rotary dryer and afterburner

Applicable Compliance Method:

The OC emissions are calculated by multiplying the annual production rate in tons per year times the emissions factor (73.41 lb per ton) times the control efficiency and converting the emissions into tons. The emission factor was provided in PTI 14-05345 submitted August 7, 2002. Also add the emissions from the dryer and afterburner by multiplying the emission factors by the amount of the fuel burned and converting to tons. The emission factors are taken from AP-42, Fifth Edition, Chapter 1.4, Natural Gas Combustion.

- g. Emissions Limitation for rotary dryer and mixer area afterburner:
0.1 lb NO_x/MMBtu
0.084 lb CO/MMBtu
0.0006 lb SO₂/MMBtu
0.0076 PM/PM₁₀/MMBtu

Applicable Compliance Method:

The emissions are calculated by dividing the emission factors by the heat content of the fuel burned. The emission factors are taken from AP-42, Fifth Edition, Chapter 1.4, Natural Gas Combustion.

- h. Emission Limitation for rotary dryer and mixer area afterburner:
3.88 TPY NO_x
3.26 TPY CO
0.02 TPY SO₂
0.29 TPY PM/PM₁₀

Applicable Compliance Method:

The emissions are calculated by multiplying the fuel usage times the emission factors and converting the pounds into tons. The emission factors are taken from AP-42, Fifth Edition, Chapter 1.4, Natural Gas Combustion.

F. Miscellaneous Requirements

EI Ceramics LLC
PTI Application: 14-05345
Issued

Facility ID: 1431404130

Emissions Unit ID: **P001**

1. The following terms and conditions of this permit are federally enforceable: A., B., C.1 - C.3, D. and E.

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)**A. Applicable Emissions Limitations and/or Control Requirements**

- The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	
P002 - Blending, Pressing, Glazing and Curing of Ceramic Shapes	OAC rule 3745-31-05(A)(3)	OAC rule 3745-21-07(G)
	OAC rule 3745-31-05(D)	
	OAC rule 3745-17-07(A)(1)	
	OAC rule 3745-17-11	

EI Ce1

PTI A

Issued: 11/19/2002

Emissions Unit ID: P002

Applicable Emissions
Limitations/Control Measures

0.2 lb PM/hr, 0.88 TPY PM
 0.13 lb PM10/hr, 0.56 TPY PM10
 from blender, curing oven and
 afterburner

2.52 lbs OC/hr from curing oven
 and afterburner

Curing oven and curing oven
 afterburner emissions:

0.1 lb NO_x/MMBtu, 2.95 TPY
 NO_x

0.084 lb CO/MMBtu, 3.3 TPY CO

0.0006 lb SO₂/MMBtu, 0.03 TPY
 SO₂

The requirements of this rule also
 include compliance with the
 requirements of OAC rule
 3745-17-07(A)(1) and
 3745-31-05(D).

0.92 ton OC/month, 11.0 TPY OC
 from the curing oven and
 afterburner

See term A.2.b.

The emission limitation specified by
 this rule is less stringent than the
 emission limitation established
 pursuant to OAC rule
 3745-31-05(A)(3).

The emission limitation specified by
 this rule is less stringent than the

emission limitation established
 pursuant to OAC rule
 3745-31-05(A)(3).

2. Additional Terms and Conditions

- 2.a** Compliance with OAC rule 3745-31-05(A)(3) shall be demonstrated by compliance with the Air Toxics Policy, emission limits, the use of a fabric filter for controlling the particulate matter from the blender and the use of a 95% efficient thermal oxidizer on the curing oven.
- 2.b** Visible particulate emissions from the stacks associated with this emissions unit shall not exceed 20 percent opacity, as a six-minute average, except as specified by rule.
- 2.c** The hourly emission limitations outlined in term A.1 are based upon the emissions unit's potential to emit. Therefore, no hourly records are required to demonstrate compliance with these limits.
- 2.d** This emissions unit shall be equipped with a control device for OC emissions that is at least 95% efficient for OC emissions entering the control device.

B. Operational Restrictions

- 1. The pressure drop across the blender dust collector shall each be maintained within the range of 1 - 8 inches of water while the emissions unit is in operation.
- 2. The average combustion temperature within the thermal incinerator, for any 3-hour block of time when the emissions unit is in operation, shall not be less than 1450 degrees Fahrenheit or more than 50 degrees Fahrenheit below the average temperature during the most recent emissions test that demonstrated the emissions unit was in compliance.

C. Monitoring and/or Recordkeeping Requirements

- 1. The permittee shall properly install, operate, and maintain equipment to monitor the pressure drop across the fabric filter while the emissions unit is in operation. The monitoring equipment shall be installed, calibrated, operated, and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual(s). The permittee shall record the pressure drop across the fabric filter on a weekly basis.
- 2. The permittee shall properly install, operate and maintain a continuous temperature monitor and recorder which measures and records the combustion temperature within the thermal incinerator when the emissions unit is in operation. Units shall be in degrees Fahrenheit. The monitoring and recording devices shall be capable of accurately measuring the desired parameter. The temperature monitor and recorder shall be installed, calibrated, operated and maintained in

Emissions Unit ID: P002

accordance with the manufacturer's recommendations, with any modifications deemed necessary by the permittee.

The permittee shall collect and record the following information for each day:

- a. All 3-hour blocks of time during which the average combustion temperature within the thermal incinerator, when the emissions unit was in operation, was less than 1450 degrees Fahrenheit or more than 50 degrees Fahrenheit below the average temperature during the most recent emission test that demonstrated the emissions unit was in compliance.
 - b. A log of the downtime for the capture (collection) system, control device, and monitoring equipment, when the associated emissions unit was in operation.
3. The permittee shall collect and record the following information each month for this emissions unit:
- a. The emission unit's production rate in tons/month.
 - b. The total OC emission rate, in tons per month [$a \times 65.27 \text{ lb. OC/ton organic solvent}^* \times (1-0.95)$ (or the control efficiency established during the most recent performance test) plus the emissions from the natural gas usage in the afterburner].
* the emission factor is based on information submitted by the permittee.
4. The permit to install for these emissions units (P001 and P002) was evaluated based on the actual materials (typically coatings and cleanup materials) and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Ground-Level Concentration (MAGLC).

The following summarizes the results of the modeling for the "worst case" pollutant(s):

Pollutant: Furfural
TLV (ug/m3): 7,900
Maximum Hourly Emission Rate (lbs/hr): 2.08
Predicted 1-Hour Maximum Ground-Level
Concentration (ug/m3): 137.0 (Emissions Unit P001 and P002 combined)
MAGLC (ug/m3): 188.1

20

EI Ce

PTI A

Issued: 11/19/2002

Emissions Unit ID: **P002**

Physical changes to or in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxics Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in the "Air Toxic Policy" include the following:

- a. Changes in the composition of the materials used (typically for coatings or cleanup materials), or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value previously modeled;
 - b. Changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and
 - c. Physical changes to the emissions unit or its exhaust parameters (e.g., increased/decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).
5. If the permittee determines that the "Air Toxic Policy" will be satisfied with the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01(VV)(1)(a)(ii), and a modification of the existing permit to install will not be required. If the change(s) is(are) defined as a modification under other provisions of the modification definition [other than (VV)(1)(a)(ii)], then the permittee shall obtain a final permit to install prior to the change.
- The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will satisfy the Air Toxic Policy:"
- a. A description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
 - b. Documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and
 - c. When the computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

D. Reporting Requirements

1. The permittee shall submit pressure drop deviation (excursion) reports that identify all periods of time during which the pressure drop across fabric filter did not comply with the allowable range specified in term B.1.
2. The permittee shall submit deviation (excursion) reports which identify all 3-hour blocks of time during which the average combustion temperature within the thermal incinerator does not comply with the temperature limitation specified in term B.2.
3. The permittee shall submit deviation (excursion) reports which identify any exceedance of the monthly OC emissions limit in term A.1.
4. The deviation reports shall be submitted in accordance with the reporting requirements of the General Terms and Conditions of this permit.
5. The permittee shall submit annual reports which specify the total OC emissions for this emissions unit for the previous calendar year. These reports shall be submitted by January 31 of each year.

E. Testing Requirements

1. Compliance with the visible particulate emissions limitations in term A.2.b shall be demonstrated by the methods outlined in 40 CFR Part 60, Appendix A, Method 9.
2. Compliance with the emission limitation in Section A.1 of these terms and conditions shall be determined in accordance with the following method(s):
 - a. Emissions Limitation:
0.2 lb/hr PM

Applicable Compliance Method:
The PM emissions are calculated by multiplying the hourly production rate for the blender in tons per hour times the emission factor (0.60 lb per ton) times the control efficiency plus the hourly production rate for the curing oven times the emission factor (0.20 lb per ton). The emissions factors were provided in PTI application 14-05345 submitted August 7, 2002.
 - b. Emissions Limitation:
0.88 TPY PM

Applicable Compliance Method:
The PM emissions are calculated by multiplying the annual production rate for the blender

23

EI Ce

PTI A

Issued: 11/19/2002

Emissions Unit ID: **P002**

in tons per year times the emissions factor (0.60 lb per ton) times the control efficiency and converting the emissions into tons plus the hourly production rate for the curing oven times the emissions factor (0.20 lb per ton) and converting the emissions into tons. The emission factors were provided in PTI application 14-05345 submitted August 7, 2002.

- c. Emissions Limitation:
0.13 lb/hr PM10

Applicable Compliance Method:

The PM10 emissions are calculated by multiplying the hourly production rate for the blender in tons per hour times the emissions factor (0.30 lb per ton) times the control efficiency plus the hourly production rate for the curing oven times the emission factor (0.10 lb per ton). The emission factors were provided in PTI application 14-05345 submitted August 7, 2002.

- d. Emissions Limitation:
0.56 TPY PM10

Applicable Compliance Method:

The PM10 emissions are calculated by multiplying the annual production rate for the blender in tons per year times the emissions factor (0.30 lb per ton) times the control efficiency and converting the emissions into tons plus the annual production rate for the curing oven times the emission factor (0.10 lb per ton) and converting the emissions into tons. The emission factors were provided in PTI application 14-05345 submitted August 7, 2002.

- e. Emissions Limitation:
2.52 lbs/hr OC from the curing oven

Applicable Compliance Method:

The OC emissions are calculated by multiplying the hourly production rate in tons per hour times the emission factor (65.27 lb per ton) times the control efficiency. The emission factor was provided in PTI application 14-05345 submitted August 7, 2002. Also add the emissions from the afterburner by multiplying the emission factors by the amount of the fuel burned. The emission factors are taken from AP-42, Fifth Edition, Chapter 1.4, Natural Gas Combustion.

- f. Emissions Limitation:
11.0 TPY OC from the curing oven

Applicable Compliance Method:

The OC emissions are calculated by multiplying the annual production rate in tons per year times the emissions factor (65.27 lb per ton) times the control efficiency and converting the emissions into tons. The emission factor was provided in PTI 14-05345 submitted August 7, 2002. Also add the emissions from the afterburner by multiplying the emission

EI Ceramics LLC
PTI Application: 14-05345
Issued

Facility ID: 1431404130

Emissions Unit ID: **P002**

factors by the amount of the fuel burned and converting to tons. The emission factors are taken from AP-42, Fifth Edition, Chapter 1.4, Natural Gas Combustion.

- g. Emissions Limitation from curing oven:
0.1 lb NO_x/MMBtu
0.084 lb CO/MMBtu
0.0006 lb SO₂/MMBtu

Applicable Compliance Method:

The emissions are calculated by dividing the emission factors by the heat content of the fuel burned. The emission factors are taken from AP-42, Fifth Edition, Chapter 1.4, Natural Gas Combustion.

- h. Emission Limitation from curing oven and afterburner:
2.95 TPY NO_x
3.3 TPY CO
0.03 TPY SO₂

Applicable Compliance Method:

The emissions are calculated by multiplying the fuel usage times the emission factors and converting the pounds into tons. The emission factors are taken from AP-42, Fifth Edition, Chapter 1.4, Natural Gas Combustion.

F. Miscellaneous Requirements

1. The following terms and conditions of this permit are federally enforceable: A., B., C.1 - C.3, D. and E.

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

- The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P003 - Kiln with thermal oxidizer	OAC rule 3745-31-05(A)(3)	Kiln and kiln afterburner emissions: 3.93 lbs OC/hr 0.20 lb PM/hr, 0.86 TPY PM 0.15 lb PM10/hr, 0.64 TPY PM10 0.28 lb NOx/hr, 1.23 TPY NOx 0.34 lb SO2/hr, 1.5 TPY SO2 0.68 lb CO/hr, 3.0 TPY CO
	OAC rule 3745-31-05(D)	The requirements of this rule also include compliance with the requirements of OAC rule 3745-17-07(A)(1) and 3745-31-05(D).
	OAC rule 3745-17-07(A)(1)	1.44 tons OC/month, 17.3 TPY OC from kiln and kiln afterburner
	OAC rule 3745-17-11	See term A.2.b.
	OAC rule 3745-21-07(G)	The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).

The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).

2. Additional Terms and Conditions

- 2.a** Compliance with OAC rule 3745-31-05(A)(3) shall be demonstrated by compliance with the Air Toxics Policy, emission limits and the use of a 95% efficient thermal oxidizer on the kiln.
- 2.b** Visible particulate emissions from the stacks associated with this emissions unit shall not exceed twenty per cent opacity, as a six-minute average, except as specified by rule.
- 2.c** The hourly emission limitations outlined in term A.1 are based upon the emissions unit's potential to emit. Therefore, no hourly records are required to demonstrate compliance with these limits.
- 2.d** This emissions unit shall be equipped with a control device for OC emissions that is at least 95% efficient for OC emissions entering the control device.

B. Operational Restrictions

- 1. The average combustion temperature within the thermal incinerator, for any 3-hour block of time when the emissions unit is in operation, shall not be more than 50 degrees Fahrenheit below the average temperature during the most recent emissions test that demonstrated the emissions unit was in compliance.

C. Monitoring and/or Recordkeeping Requirements

- 1. The permittee shall properly install, operate and maintain a continuous temperature monitor and recorder which measures and records the combustion temperature within the thermal incinerator when the emissions unit is in operation. Units shall be in degrees Fahrenheit. The monitoring and recording devices shall be capable of accurately measuring the desired parameter. The temperature monitor and recorder shall be installed, calibrated, operated and maintained in accordance with the manufacturer's recommendations, with any modifications deemed necessary by the permittee.

The permittee shall collect and record the following information for each day:

- a. All 3-hour blocks of time during which the average combustion temperature within the thermal incinerator, when the emissions unit was in operation, was more than 50 degrees Fahrenheit below the average temperature during the most recent emission test that demonstrated the emissions unit was in compliance.
 - b. A log of the downtime for the capture (collection) system, control device, and monitoring equipment, when the associated emissions unit was in operation.
2. The permittee shall collect and record the following information each month for this emissions unit:
 - a. The emission unit's production rate in tons/month.
 - b. The total OC emission rate, in tons per month [$a \times 156.5 \text{ lbs. OC/ton organic solvent}^* \times (1-0.95)$ (or the control efficiency established during the most recent performance test) plus the emissions from the natural gas usage in the afterburner].
 - * the emission factor is based on information submitted by the permittee.
3. The permit to install for this emissions unit (P003) was evaluated based on the actual materials (typically coatings and cleanup materials) and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Ground-Level Concentration (MAGLC).

The following summarizes the results of the modeling for the "worst case" pollutant(s):

Pollutant: hexamethylenetetramine
 TLV (ug/m3): 15,000
 Maximum Hourly Emission Rate (lbs/hr): 3.56
 Predicted 1-Hour Maximum Ground-Level
 Concentration (ug/m3): 289.4
 MAGLC (ug/m3): 357

Physical changes to or in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxics Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be

satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in the "Air Toxic Policy" include the following:

- a. Changes in the composition of the materials used (typically for coatings or cleanup materials), or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value previously modeled;
 - b. Changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and
 - c. Physical changes to the emissions unit or its exhaust parameters (e.g., increased/decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).
4. If the permittee determines that the "Air Toxic Policy" will be satisfied with the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01(VV)(1)(a)(ii), and a modification of the existing permit to install will not be required. If the change(s) is(are) defined as a modification under other provisions of the modification definition [other than (VV)(1)(a)(ii)], then the permittee shall obtain a final permit to install prior to the change.

The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will satisfy the Air Toxic Policy:"

- a. A description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
- b. Documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and
- c. When the computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

D. Reporting Requirements

1. The permittee shall submit deviation (excursion) reports which identify all 3-hour blocks of time during which the average combustion temperature within the thermal incinerator does not comply

with the temperature limitation specified in term B.1.

2. The permittee shall submit an annual report of the total OC emissions from this emissions unit for the previous calendar year. These reports shall be submitted by January 31 of each year.
3. The permittee shall submit deviation (excursion) reports which identify any exceedance of the monthly OC emissions limit in term A.1.
4. The deviation reports shall be submitted in accordance with the reporting requirements of the General Terms and Conditions of this permit.

E. Testing Requirements

1. Compliance with the visible particulate emissions limitations in term A.2.b shall be demonstrated by the methods outlined in 40 CFR Part 60, Appendix A, Method 9.
2. The permittee shall conduct, or have conducted, emission testing for this emissions unit in accordance with the following requirements:
 - a. The emission testing shall be conducted within 6 months after start-up of this emissions unit.
 - b. The emission testing shall be conducted to demonstrate compliance with the destruction efficiency and OC emission limitations.
 - c. The test method(s) which must be employed to demonstrate compliance with the destruction efficiency and OC emission limitations are specified below. Alternative U.S. EPA approved test methods may be used with prior approval from the Hamilton County Department of Environmental Services.

Method 25, 40 CFR Part 60, Appendix A

- d. The test(s) shall be conducted while the emissions unit is operating at or near its maximum capacity, unless otherwise specified or approved by the Hamilton County Department of Environmental Services.

Not later than 30 days prior to the proposed test date(s), the permittee shall submit an "Intent to Test" notification to the Hamilton County Department of Environmental Services. The "Intent to Test" notification shall describe in detail the proposed test methods and procedures, the emissions unit operating parameters, the time(s) and date(s) of the test(s), and the person(s) who will be conducting the test(s). Failure to submit such notification for review and approval prior to the

test(s) may result in the Hamilton County Department of Environmental Services refusal to accept the results of the emission test(s).

Personnel from the Hamilton County Department of Environmental Services shall be permitted to witness the test(s), examine the testing equipment, and acquire data and information necessary to ensure that the operation of the emissions unit and the testing procedures provide a valid characterization of the emissions from the emissions unit and/or the performance of the control equipment.

A comprehensive written report on the results of the emissions test(s) shall be signed by the person or persons responsible for the tests and submitted to the Hamilton County Department of Environmental Services within 30 days following completion of the test(s). The permittee may request additional time for the submittal of the written report, where warranted, with prior approval from the Hamilton County Department of Environmental Services.

3. Compliance with the emission limitation in Section A.1 of these terms and conditions shall be determined in accordance with the following method(s):
 - a. Emissions Limitation:
3.93 lbs/hr OC

Emissions Unit ID: P003

Applicable Compliance Method:

The OC emissions are calculated by multiplying the hourly production rate in tons per hour times the emission factor (156.5 lb per ton) times the control efficiency plus the fuel usage for the kiln afterburner times the emission factor (11.0 lb/MMft³). The emission factor (156.5 lb/ton) was provided in PTI application 14-05345 submitted August 7, 2002. The emissions factor 11.0 lb/MMft³ was taken from AP-42, Fifth Edition, Chapter 1.4, Natural Gas Combustion.

- b. Emissions Limitation:
17.3 TPY OC

Applicable Compliance Method:

The OC emissions are calculated by multiplying the annual production rate in tons per year times the emissions factor (156.5 lb per ton) times the control efficiency and converting the emissions into tons plus the annual fuel usage times the emission factor (11.0 lb/MMft³). The emission factor (156.5 lb/ton) was provided in PTI 14-05345 submitted August 7, 2002. The emission factor 11.0 lb/MMft³ was taken from AP-42, Fifth Edition, Chapter 1.4, Natural Gas Combustion.

- c. Emissions Limitation:
0.20 lbs/hr PM

Applicable Compliance Method:

The PM emissions are calculated by multiplying the hourly production rate for the kiln in tons per hour times the emission factor (0.37 lb per ton) plus the fuel usage for the kiln afterburner times the emission factor (7.6 lb/MMft³). The emissions factor was provided in PTI application 14-05345 submitted August 7, 2002. The emissions factor 7.6 lb/MMft³ was taken from AP-42, Fifth Edition, Chapter 1.4, Natural Gas Combustion.

- d. Emissions Limitation:
0.86 TPY PM

Applicable Compliance Method:

The PM emissions are calculated by multiplying the annual production rate for the kiln in tons per year times the emissions factor (0.37 lb per ton) and converting the emissions into tons plus the annual fuel usage for the kiln afterburner times the emission factor (7.6 lb/MMft³) and converting into tons. The emission factor 0.37 lb/ton was provided in PTI application 14-05345 submitted August 7, 2002. The emissions factor 7.6 lb/MMft³ was taken from AP-42, Fifth Edition, Chapter 1.4, Natural Gas Combustion.

- e. Emissions Limitation:

34

EI Ce1

PTI A

Issued: 11/19/2002

Emissions Unit ID: **P003**

0.15 lbs/hr PM10

Applicable Compliance Method:

The PM10 emissions are calculated by multiplying the hourly production rate for the kiln in tons per hour times the emission factor (0.28 lb per ton) plus the fuel usage for the kiln afterburner times the emission factor (7.6 lb/MMft³). The emissions factor 0.28 lb/ton was provided in PTI application 14-05345 submitted August 7, 2002. The emissions factor 7.6 lb/MMft³ was taken from AP-42, Fifth Edition, Chapter 1.4, Natural Gas Combustion.

- f. Emissions Limitation:
0.64 TPY PM10

Applicable Compliance Method:

The PM10 emissions are calculated by multiplying the annual production rate for the kiln in tons per year times the emissions factor (0.28 lb per ton) and converting the emissions into tons plus the annual fuel usage for the kiln afterburner times the emission factor (7.6 lb/MMft³) and converting into tons. The emission factor 0.28 lb/ton was provided in PTI application 14-05345 submitted August 7, 2002. The emissions factor 7.6 lb/MMft³ was taken from AP-42, Fifth Edition, Chapter 1.4, Natural Gas Combustion.

- g. Emissions Limitation:
0.28lb/hr NO_x

Applicable Compliance Method:

The NO_x emissions are calculated by multiplying the hourly production rate for the kiln in tons per hour times the emission factor (0.35 lb per ton) plus the fuel usage for the kiln afterburner times the emission factor (100.0 lb/MMft³). The emissions factor 0.35 lb/ton was provided in PTI application 14-05345 submitted August 7, 2002. The emissions factor 100.0 lb/MMft³ was taken from AP-42, Fifth Edition, Chapter 1.4, Natural Gas Combustion.

- h. Emissions Limitation:
1.23 TPY NO_x

Applicable Compliance Method:

The NO_x emissions are calculated by multiplying the annual production rate for the kiln in tons per year times the emissions factor (0.35 lb per ton) and converting the emissions into tons plus the annual fuel usage for the kiln afterburner times the emission factor (100.0 lb/MMft³) and converting into tons. The emission factor 0.35 lb/ton was provided in PTI application 14-05345 submitted August 7, 2002. The emissions factor 100.0 lb/MMft³ was taken from AP-42, Fifth Edition, Chapter 1.4, Natural Gas Combustion.

- i. Emissions Limitation:
0.34 lb/hr SO₂

Applicable Compliance Method:

The SO₂ emissions are calculated by multiplying the hourly production rate for the kiln in tons per hour times the emission factor (0.67 lb per ton) plus the fuel usage for the kiln afterburner times the emission factor (0.60 lb/MMft³). The emissions factor 0.67 lb/ton was provided in PTI application 14-05345 submitted August 7, 2002. The emissions factor 0.60 lb/MMft³ was taken from AP-42, Fifth Edition, Chapter 1.4, Natural Gas Combustion.

- j. Emissions Limitation:
1.5 TPY SO₂

Applicable Compliance Method:

The SO₂ emissions are calculated by multiplying the annual production rate for the kiln in tons per year times the emissions factor (0.67 lb per ton) and converting the emissions into tons plus the annual fuel usage for the kiln afterburner times the emission factor (0.60 lb/MMft³) and converting into tons. The emission factor 0.67 lb/ton was provided in PTI application 14-05345 submitted August 7, 2002. The emissions factor 0.60 lb/MMft³ was taken from AP-42, Fifth Edition, Chapter 1.4, Natural Gas Combustion.

- k. Emissions Limitation:
0.68 lb/hr CO

Applicable Compliance Method:

The CO emissions are calculated by multiplying the hourly production rate for the kiln in tons per hour times the emission factor (1.20 lb per ton) plus the fuel usage for the kiln afterburner times the emission factor (84.0 lb/MMft³). The emissions factor 1.20 lb/ton was provided in PTI application 14-05345 submitted August 7, 2002. The emissions factor 84.0 lb/MMft³ was taken from AP-42, Fifth Edition, Chapter 1.4, Natural Gas Combustion.

- l. Emissions Limitation:
3.0 TPY CO

Applicable Compliance Method:

The CO emissions are calculated by multiplying the annual production rate for the kiln in tons per year times the emissions factor (01.20 lb per ton) and converting the emissions into tons plus the annual fuel usage for the kiln afterburner times the emission factor (84.0

EI Ceramics LLC
PTI Application: 14-05345
Issued

Facility ID: 1431404130

Emissions Unit ID: **P003**

lb/MMft³) and converting into tons. The emission factor 1.20 lb/ton was provided in PTI application 14-05345 submitted August 7, 2002. The emissions factor 84.0 lb/MMft³ was taken from AP-42, Fifth Edition, Chapter 1.4, Natural Gas Combustion.

F. Miscellaneous Requirements

1. The following terms and conditions of this permit are federally enforceable: A., B., C.1 - C.2, D. and E.