



State of Ohio Environmental Protection Agency

**RE: FINAL PERMIT TO INSTALL CERTIFIED MAIL
WARREN COUNTY**

Street Address:

122 S. Front Street

Lazarus Gov. Center TELE: (614) 644-3020 FAX: (614) 644-2329

Mailing Address:

Lazarus Gov. Center
P.O. Box 1049

Application No: 14-05437

DATE: 6/5/2003

William Oeder Ready Mix Concrete
Robert Oeder
5274 Zoar Road
Morrow, OH 451520000

Enclosed please find an Ohio EPA Permit to Install which will allow you to install the described source(s) in a manner indicated in the permit. Because this permit contains several conditions and restrictions, I urge you to read it carefully.

The Ohio EPA is urging companies to investigate pollution prevention and energy conservation. Not only will this reduce pollution and energy consumption, but it can also save you money. If you would like to learn ways you can save money while protecting the environment, please contact our Office of Pollution Prevention at (614) 644-3469.

You are hereby notified that this action by the Director is final and may be appealed to the Ohio Environmental Review Appeals Commission pursuant to Chapter 3745.04 of the Ohio Revised Code. The appeal must be in writing and set forth the action complained of and the grounds upon which the appeal is based. It must be filed within thirty (30) days after the notice of the Directors action. A copy of the appeal must be served on the Director of the Ohio Environmental Protection Agency within three (3) days of filing with the Commission. An appeal may be filed with the Environmental Review Appeals Commission at the following address:

Environmental Review Appeals Commission
236 East Town Street, Room 300
Columbus, Ohio 43215

Very truly yours,

Michael W. Ahern, Supervisor
Field Operations and Permit Section
Division of Air Pollution Control

cc: USEPA

HCDES



**Permit To Install
Terms and Conditions**

**Issue Date: 6/5/2003
Effective Date: 6/5/2003**

FINAL PERMIT TO INSTALL 14-05437

Application Number: 14-05437
APS Premise Number: 1483110161
Permit Fee: **\$1200**
Name of Facility: William Oeder Ready Mix Concrete
Person to Contact: Robert Oeder
Address: 5274 Zoar Road
Morrow, OH 451520000

Location of proposed air contaminant source(s) [emissions unit(s)]:
**2764 State Route 22/3 East
Morrow, Ohio**

Description of proposed emissions unit(s):
Installation of new transit mix concrete batch plant to replace existing fire-damaged plant.

The above named entity is hereby granted a Permit to Install for the above described emissions unit(s) pursuant to Chapter 3745-31 of the Ohio Administrative Code. Issuance of this permit does not constitute expressed or implied approval or agreement that, if constructed or modified in accordance with the plans included in the application, the above described emissions unit(s) of environmental pollutants will operate in compliance with applicable State and Federal laws and regulations, and does not constitute expressed or implied assurance that if constructed or modified in accordance with those plans and specifications, the above described emissions unit(s) of pollutants will be granted the necessary permits to operate (air) or NPDES permits as applicable.

This permit is granted subject to the conditions attached hereto.

Ohio Environmental Protection Agency

Director

Part I - GENERAL TERMS AND CONDITIONS

A. Permit to Install General Terms and Conditions

1. Compliance Requirements

The emissions unit(s) identified in this Permit to Install shall remain in full compliance with all applicable State laws and regulations and the terms and conditions of this permit.

2. Reporting Requirements

The permittee shall submit required reports in the following manner:

- a. Reports of any required monitoring and/or recordkeeping information shall be submitted to the appropriate Ohio EPA District Office or local air agency.
- b. Except as otherwise may be provided in the terms and conditions for a specific emissions unit, quarterly written reports of (a) any deviations (excursions) from emission limitations, operational restrictions, and control device operating parameter limitations that have been detected by the testing, monitoring, and recordkeeping requirements specified in this permit, (b) the probable cause of such deviations, and (c) any corrective actions or preventive measures which have been or will be taken, shall be submitted to the appropriate Ohio EPA District Office or local air agency. If no deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted quarterly, i.e., by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters. (These quarterly reports shall exclude deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06.)

3. Records Retention Requirements

Each record of any monitoring data, testing data, and support information required pursuant to this permit shall be retained for a period of five years from the date the record was created. Support information shall include, but not be limited to, all calibration and maintenance records and all original strip-chart recordings for continuous monitoring instrumentation, and copies of all reports required by this permit. Such records may be maintained in computerized form.

4. Inspections and Information Requests

The Director of the Ohio EPA, or an authorized representative of the Director, may, subject to the safety requirements of the permittee and without undue delay, enter upon the premises of this source at any reasonable time for purposes of making inspections, conducting tests, examining records or reports pertaining to any emission of air contaminants, and determining compliance with any applicable State air pollution laws and regulations and the terms and conditions of this permit. The permittee shall furnish to the Director of the Ohio EPA, or an authorized

representative of the Director, upon receipt of a written request and within a reasonable time, any information that may be requested to determine whether cause exists for modifying, reopening or revoking this permit or to determine compliance with this permit. Upon verbal or written request, the permittee shall also furnish to the Director of the Ohio EPA, or an authorized representative of the Director, copies of records required to be kept by this permit.

5. Scheduled Maintenance/Malfunction Reporting

Any scheduled maintenance of air pollution control equipment shall be performed in accordance with paragraph (A) of OAC rule 3745-15-06. The malfunction of any emissions units or any associated air pollution control system(s) shall be reported to the appropriate Ohio EPA District Office or local air agency in accordance with paragraph (B) of OAC rule 3745-15-06. Except as provided in that rule, any scheduled maintenance or malfunction necessitating the shutdown or bypassing of any air pollution control system(s) shall be accompanied by the shutdown of the emissions unit(s) that is (are) served by such control system(s).

6. Permit Transfers

Any transferee of this permit shall assume the responsibilities of the prior permit holder. The appropriate Ohio EPA District Office or local air agency must be notified in writing of any transfer of this permit.

7. Air Pollution Nuisance

The air contaminants emitted by the emissions units covered by this permit shall not cause a public nuisance, in violation of OAC rule 3745-15-07.

8. Termination of Permit to Install

This Permit to Install shall terminate within eighteen months of the effective date of the Permit to Install if the owner or operator has not undertaken a continuing program of installation or modification or has not entered into a binding contractual obligation to undertake and complete within a reasonable time a continuing program of installation or modification. This deadline may be extended by up to 12 months if application is made to the Director within a reasonable time before the termination date and the party shows good cause for any such extension.

9. Construction of New Sources(s)

The proposed emissions unit(s) shall be constructed in strict accordance with the plans and application submitted for this permit to the Director of the Ohio Environmental Protection Agency. There may be no deviation from the approved plans without the express, written approval of the Agency. Any deviations from the approved plans or the above conditions may lead to such sanctions and penalties as provided under Ohio law. Approval of these plans does not constitute an assurance that the proposed facilities will operate in compliance with all Ohio laws and regulations. Additional facilities shall be installed upon orders of the Ohio

Environmental Protection Agency if the proposed sources cannot meet the requirements of this permit or cannot meet applicable standards.

If the construction of the proposed emissions unit(s) has already begun or has been completed prior to the date the Director of the Environmental Protection Agency approves the permit application and plans, the approval does not constitute expressed or implied assurance that the proposed facility has been constructed in accordance with the approved plans. The action of beginning and/or completing construction prior to obtaining the Director's approval constitutes a violation of OAC rule 3745-31-02. Furthermore, issuance of the Permit to Install does not constitute an assurance that the proposed source will operate in compliance with all Ohio laws and regulations. Approval of the plans in any case is not to be construed as an approval of the facility as constructed and/or completed. Moreover, issuance of the Permit to Install is not to be construed as a waiver of any rights that the Ohio Environmental Protection Agency (or other persons) may have against the applicant for starting construction prior to the effective date of the permit. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed facilities cannot meet the requirements of this permit or cannot meet applicable standards.

10. Public Disclosure

The facility is hereby notified that this permit, and all agency records concerning the operation of this permitted source, are subject to public disclosure in accordance with OAC rule 3745-49-03.

11. Applicability

This Permit To Install is applicable only to the emissions unit(s) identified in the Permit To Install. Separate Permit To Install for the installation or modification of any other emissions unit(s) are required for any emissions unit for which a Permit To Install is required.

12. Best Available Technology

As specified in OAC Rule 3745-31-05, all new sources must employ Best Available Technology (BAT). Compliance with the terms and conditions of this permit will fulfill this requirement.

13. Source Operation and Operating Permit Requirements After Completion of Construction

This facility is permitted to operate each source described by this Permit to Install for a period of up to one year from the date the source commenced operation. This permission to operate is granted only if the facility complies with all requirements contained in this permit and all applicable air pollution laws, regulations, and policies. Pursuant to OAC Chapter 3745-35, the permittee shall submit a complete operating permit application within ninety (90) days after commencing operation of the emissions unit(s) covered by this permit.

William Oeder Ready Mix Concrete
 PTI Application: 14-05437
 Issued: 6/5/2003

Facility ID: 1483110161

14. Construction Compliance Certification

The applicant shall provide Ohio EPA with a written certification (see enclosed form) that the facility has been constructed in accordance with the Permit to Install application and the terms and conditions of the Permit to Install. The certification shall be provided to Ohio EPA upon completion of construction but prior to startup of the source.

15. Fees

The permittee shall pay fees to the Director of the Ohio EPA in accordance with ORC section 3745.11 and OAC Chapter 3745-78. The permittee shall pay all applicable Permit to Install fees within 30 days after the issuance of this Permit to Install.

B. Permit to Install Summary of Allowable Emissions

The following information summarizes the total allowable emissions, by pollutant, based on the individual allowable emissions of each air contaminant source identified in this permit.

SUMMARY (for informational purposes only)
TOTAL PERMIT TO INSTALL ALLOWABLE EMISSIONS

<u>Pollutant</u>	<u>Tons Per Year</u>
PM	3.62
PM10	0.74

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
F002 - Unpaved Plant Roadways and Parking Areas	OAC rule 3745-31-05(A)(3)	1.79 TPY PM; 0.37 TPY PM ₁₀
		See terms A.2.a, A.2.c, A.2.e through A.2.j
	OAC rule 3745-17-07(B)(5)	Exempt pursuant to the emissions unit being located in a non-Appendix A area.
	OAC rule 3745-17-08(B)	Exempt pursuant to the emissions unit being located in a non-Appendix A area.
Paved Plant Roadways and Parking Areas	OAC rule 3745-31-05(A)(3)	1.80 TPY PM; 0.35 TPY PM ₁₀
		See terms A.2.a, A.2.b, A.2.d, A.2.g through A.2.j
	OAC rule 3745-17-07(B)(4)	Exempt pursuant to the emissions unit being located in a non-Appendix A area.
	OAC rule 3745-17-08(B)	Exempt pursuant to the emissions unit being located in a non-Appendix A area.

2. Additional Terms and Conditions

- 2.a** All paved and unpaved roadways and parking areas are covered by this permit and subject to the above-mentioned requirements.
- 2.b** There shall be no visible particulate emissions from any paved roadway or parking area except for a period of time not to exceed one minute during any sixty-minute observation period.
- 2.c** There shall be no visible particulate emissions from any unpaved roadway or parking area except for a period of time not to exceed three minutes during any sixty-minute observation period.
- 2.d** The permittee shall employ best available control measures on all paved roadways and parking areas for the purpose of ensuring compliance with the above-mentioned applicable requirements. In accordance with the permittee's permit application, the permittee has committed to treat the paved roadways and parking areas by flushing with water at sufficient treatment frequencies to ensure compliance. Nothing in this paragraph shall prohibit the permittee from employing other control measures to ensure compliance.
- 2.e** The permittee shall employ best available control measures on all unpaved roadways and parking areas for the purpose of ensuring compliance with the above-mentioned applicable requirements. In accordance with the permittee's permit application, the permittee has committed to treat the unpaved roadways and parking areas by watering at sufficient treatment frequencies to ensure compliance. Nothing in this paragraph shall prohibit the permittee from employing other control measures to ensure compliance.
- 2.f** Any unpaved roadways or parking area, which during the term of this permit is paved or takes the characteristics of a paved surface due to the application of certain types of dust suppressants, may be controlled using water. Any unpaved roadway or parking area that takes the characteristics of a paved roadway or parking area due to the application of certain types of dust suppressants shall remain subject to the visible emission limitation for unpaved roadways and parking areas. Any unpaved roadway or parking area that is paved shall be subject to a visible emission limitation of no visible particulate emissions except for one minute during any 60-minute period.
- 2.g** The needed frequencies of implementation of the control measures shall be determined by the permittee's inspections pursuant to the monitoring section of this permit. Implementation of the control measures shall not be necessary for a paved or unpaved roadway or parking area that is covered with snow and/or ice or if precipitation has occurred that is sufficient for that day to ensure compliance with the above-mentioned applicable requirements. Implementation of any control measure may be suspended if

unsafe or hazardous driving conditions would be created by its use.

- 2.h** The permittee shall promptly remove, in such a manner as to minimize or prevent resuspension, earth and/or other material from paved public roads onto which such material has been deposited by trucking or earth moving equipment or erosion by water or other means.
- 2.i** Open-bodied vehicles transporting materials likely to become airborne shall have such materials covered at all times if the control measure is necessary for the materials being transported.
- 2.j** Implementation of the above-mentioned control measures in accordance with the terms and conditions of this permit is appropriate and sufficient to satisfy the best available technology requirements of OAC rule 3745-31-05(A)(3).

B. Operational Restrictions

None

C. Monitoring and/or Recordkeeping Requirements

1. The permittee shall perform daily inspections of all paved and unpaved roadways and parking areas.
2. The purpose of the inspections is to determine the need for implementing the above-mentioned control measures. The inspections shall be performed during representative, normal traffic conditions. No inspection shall be necessary for a roadway or parking area that is covered with snow and/or ice or if precipitation has occurred that is sufficient for that day to ensure compliance with the above-mentioned applicable requirements. Any required inspection that is not performed due to any of the above-identified events shall be performed as soon as such event(s) has (have) ended, except if the next required inspection is within one week.
3. The permittee may, upon receipt of written approval from the appropriate Ohio EPA District Office or local air agency, modify the above-mentioned inspection frequencies if operating experience indicates that less frequent inspections would be sufficient to ensure compliance with the above-mentioned applicable requirements.
4. The permittee shall maintain records of the following information:
 - a. The date and reason any required inspection was not performed, including those

inspections that were not performed due to snow and/or ice cover or precipitation.

- b. The date of each inspection where it was determined by the permittee that it was necessary to implement the control measures.
- c. The dates the control measures were implemented.
- d. On a calendar quarter basis, the total number of days the control measures were implemented and the total number of days where snow and/or ice cover or precipitation were sufficient to not require the control measures.

The information required in 4.d. shall be kept separately for (i) the paved roadways and parking areas and (ii) the unpaved roadways and parking areas, and shall be updated on a calendar quarter basis within 30 days after the end of each calendar quarter.

D. Reporting Requirements

1. The permittee shall submit deviation reports that identify any of the following occurrences:
 - a. each day during which an inspection was not performed by the required frequency, excluding an inspection which was not performed due to an exemption for snow and/or ice cover or precipitation; and
 - b. each instance when a control measure, that was to be implemented as a result of an inspection, was not implemented.
2. The deviation reports shall be submitted in accordance with the reporting requirements of the General Terms and Conditions of this permit.

E. Testing Requirements

1. Compliance with the visible particulate emission limitation for the paved and unpaved roadways and parking areas identified above shall be determined in accordance with Test Method 22 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources,") as such Appendix existed on July 1, 1996, and the modifications listed in paragraphs (B)(4)(a) through (B)(4)(d) of OAC rule 3745-17-03.
2. Compliance with the particulate and PM-10 emissions limitations in term A.1 shall be determined by using the calculation from AP-42, Fifth Edition, Chapter 13.2.1, October 2002 for paved roads and equation 2 from AP-42, Fifth Edition, Chapter 13.2.2, November 1998 for unpaved roads. The calculation shall also employ the actual annual vehicular traffic rates in vehicle miles traveled

per year and the estimated control efficiency, as expressed in the permit application, for the control method applicable to each roadway segment:

Paved Roadways and Parking Areas Equation 1

$$E \text{ (lb/VMT)} = [k (sL/2)^{0.65} (W/3)^{1.5}]$$

Unpaved Roadways and Parking Areas Equation 2

$$(M/0.2)^c \times (S/15) \times [(365-p)/365]$$

$$E \text{ (lb/VMT)} = [(k (s/12)^a (W/3)^b /$$

F. Miscellaneous Requirements

None

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	
P901 - Stationary Dry Batch Transit Mix Concrete Batch Plant - 200 TPH transit mix truck loading with partial enclosure and fabric filter	300 TPH sand and aggregate material handling (loading hopper, feed conveyor, elevated bin loading) and 168 TPH sand and aggregate material handling (weigh hopper loading and transfer conveyor) with partial enclosures
	25 TPH pneumatic delivery of cement to silo, 25 TPH pneumatic delivery of flyash (cement supplement) to silo, and 28 TPH cement and flyash weigh hopper loading with fabric filter

<u>Applicable Rules/Requirements</u>	OAC rule 3745-17-07(B)(1)	<u>Applicable Emissions Limitations/Control Measures</u>
OAC rule 3745-31-05(A)(3)	OAC rule 3745-17-08(B)	0.0012 lb/hr PM 0.0003 TPY PM 0.0003 lb/hr PM10 0.0001 TPY PM10
OAC rule 3745-17-07(A)(1)	OAC rule 3745-31-05(A)(3)	The requirements of this rule also include compliance with the requirements of OAC rule 3745-17-07(A)(1). See Terms A.2.b. and A.2.d.
OAC rule 3745-17-07(B)(1)	OAC rule 3745-17-07(A)(1)	Visible particulate emissions from any stack shall not exceed 20 percent opacity, as a six-minute average, except as specified by rule. Exempt pursuant to the emissions unit being located in a non-Appendix A area.
OAC rule 3745-17-08(B)	OAC rule 3745-17-11(B)	Exempt pursuant to the emissions unit being located in a non-Appendix A area.
OAC rule 3745-17-11(B)		The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).
OAC rule 3745-31-05(A)(3)		0.215 lbs/hr PM 0.0336 TPY PM 0.103 lbs/hr PM-10 0.016 TPY PM-10

Willia
PTI A
Issued: 6/5/2003

Emissions Unit ID: **P901**

See terms A.2.a., A.2.b. and A.2.e.

Exempt pursuant to the emissions unit being located in a non-Appendix A area.

Exempt pursuant to the emissions unit being located in a non-Appendix A area.

0.0010 lb/hr PM
0.00025 TPY PM
0.00042 lb/hr PM-10
0.00013 TPY PM-10

See term A.2.c.

The requirements of this rule also include compliance with the requirements of OAC rule 3745-17-07(A)(1).

Visible particulate emissions from any stack shall not exceed 20 percent opacity, as a six-minute average, except as specified by rule.

The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).

2. Additional Terms and Conditions

- 2.a** Sand and aggregate shall be maintained in a moist condition in order to minimize or eliminate visible emissions of fugitive dust.
- 2.b** Visible particulate emissions of fugitive dust from any fugitive dust emissions point shall not exceed twenty percent (20%) opacity as a three-minute average.

- 2.c The cement/flyash weigh hopper shall be partially enclosed and vented to a fabric filter with a 99.999 % control efficiency.
- 2.d The transit mix truck loading station shall be partially enclosed and vented to a fabric filter with a 99.999 % control efficiency.
- 2.e The sand/aggregate weigh hopper shall be partially enclosed in order to minimize or eliminate visible emissions of fugitive dust.
- 2.f The hourly emission limitations outlined above are based upon the emissions unit's potential to emit. Therefore, no hourly records are required to demonstrate compliance with these limits.
- 2.g Compliance with OAC rule 3745-31-05(A)(3) shall be demonstrated by employing partial enclosures on the transit mix truck loading station and sand and aggregate weigh hopper, the use of fabric filters, compliance with the visible emission limitations and compliance with the annual concrete production limit.

B. Operational Restrictions

- 1. The maximum concrete production rate for this emissions unit shall not exceed 100,000 tons per year.

C. Monitoring and/or Recordkeeping Requirements

- 1. The permittee shall maintain monthly records of the amount of concrete produced in this emissions unit.

D. Reporting Requirements

- 1. The permittee shall submit annual reports that identify any exceedances of the annual production rate limitation, as well as the corrective actions that were taken to achieve compliance. If no exceedances occurred, the permittee shall state so in the report. The permittee shall send the reports to the Hamilton County Department of Environmental Services. These reports shall be submitted by January 31 of each year and shall cover the previous calendar year.

E. Testing Requirements

1. Emissions Limitations

0.0012 lb/hr PM, 0.0003 TPY PM; 0.0003 lb/hr PM10, 0.0001 TPY PM10 from the transit mix truck loading

Applicable Compliance Method

Compliance with the particulate emissions limitations in term A.1. for the transit mix truck loading station shall be determined in a calculation using the applicable emission factors from AP-42, Fifth Edition, Chapter 11.12, Concrete Batching (October 2001), multiplied by the actual transit mix truck loading rate in tons concrete per hour and tons concrete per year multiplied by the control efficiency for the fabric filter established in the PTI application 14-05437.

2. Emissions Limitations

0.215 lbs/hr PM, 0.0336 TPY PM; 0.103 lbs/hr PM-10, 0.016 TPY PM-10 from the sand and aggregate material handling (loading hopper, feed conveyor, elevated bin loading, weigh hopper loading and transfer conveyor)

Applicable Compliance Method

Compliance with the particulate emissions limitations in term A.1. for the sand and aggregate material handling shall be determined in calculations using the applicable controlled emission factors from AP-42, Fifth Edition, Chapter 11.19.2, Crushed Stone Processing (January 1995), multiplied by the actual sand and aggregate material handling rates in tons sand and aggregate per hour and tons sand and aggregate per year.

3. Emissions Limitations

0.0010 lb/hr PM, 0.00025 TPY PM; 0.00042 lb/hr PM-10, 0.00013 TPY PM-10 from the pneumatic delivery of cement to silo, pneumatic delivery of flyash (cement supplement) to silo, and cement and flyash weigh hopper loading

Applicable Compliance Method

Compliance with the particulate emissions limitations in term A.1. for the pneumatic delivery of cement to silo, pneumatic delivery of flyash (cement supplement) to silo, and cement and flyash weigh hopper loading shall be determined in calculations using the applicable emission factors from

AP-42, Fifth Edition, Chapter 11.12, Concrete Batching (October 2001), multiplied by the actual delivery and weigh hopper loading rates in tons material per hour and tons material per year multiplied by the control efficiency for the fabric filters established in the PTI application 14-05437.

4. Emissions Limitations

Visible emissions from any stack shall not exceed 20 percent opacity as a six-minute average.

Visible emissions of fugitive dust shall not exceed 20 percent opacity as a three-minute average
Applicable Compliance Methods

Compliance shall be determined in accordance with Test Method 9 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources"), as such Appendix existed on July 1, 1996.

F. Miscellaneous Requirements

None