

Synthetic Minor Determination and/or **Netting Determination**

Permit To Install **PTI NUMBER 16-02333**

A. Source Description

Kokosing Materials, Inc., in Medina County, has made a permit to install application for an existing hot mix asphalt batch plant (P902). Kokosing Materials, Inc. desires to limit their facility's overall CO emissions to less than Title V thresholds, and wants this permit to install to restrict the potential to emit for the asphalt batch plant by restricting asphalt production on a facility wide basis. By avoiding Title V applicability, this facility will be classified as an minor stationary source.

B. Facility Emissions and Attainment Status

If Kokosing Materials, Inc. were to produce asphalt at their maximum production capacity, 215 tons per hour, for 8760 hours per year, then the PTE of CO would be 154 TPY. However, even at maximum capacity none of these emissions approach Title V thresholds.

C. Source Emissions

Kokosing Materials, Inc. has proposed to restrict their annual asphalt production to 470,000 tons per rolling year period for the asphalt batch plant (P902). This restriction will allow the facility to emit only 38.6 TPY of CO, 13.6 TPY of SO_x, 12.9 TPY of NO_x, 13.5 TPY of VOC, and 22.4 TPY of PE. The permit to install will contain terms and conditions to limit Kokosing Materials, Inc. to the above restrictions identified.

D. Conclusion

The operation of emissions units in accordance with the terms and conditions of the proposed PTI will result in maximum annual facility emissions below those levels which trigger Title V permitting requirements. The proposed PTI includes federally enforceable limits, record keeping, reporting and production limitations to ensure continued compliance with the PTI's requirements.



State of Ohio Environmental Protection Agency

**RE: DRAFT PERMIT TO INSTALL
MEDINA COUNTY**

CERTIFIED MAIL

Street Address:

Lazarus Gov. Center TELE: (614) 644-3020 FAX: (614) 644-2329

Mailing Address:

Lazarus Gov.
Center

Application No: 16-02333

Fac ID: 1652050054

DATE: 9/30/2004

Kokosing Materials Inc
Ralph E Kyanko
PO Box 334 17531 Waterford Rd
Fredericktown, OH 430199159

You are hereby notified that the Ohio Environmental Protection Agency has made a draft action recommending that the Director issue a Permit to Install for the air contaminant source(s) [emissions unit(s)] shown on the enclosed draft permit. This draft action is not an authorization to begin construction or modification of your emissions unit(s). The purpose of this draft is to solicit public comments on the proposed installation. A public notice concerning the draft permit will appear in the Ohio EPA Weekly Review and the newspaper in the county where the facility will be located. Public comments will be accepted by the field office within 30 days of the date of publication in the newspaper. Any comments you have on the draft permit should be directed to the appropriate field office within the comment period. A copy of your comments should also be mailed to Robert Hodanbosi, Division of Air Pollution Control, Ohio EPA, P.O. Box 1049, Columbus, OH, 43266-0149.

A Permit to Install may be issued in proposed or final form based on the draft action, any written public comments received within 30 days of the public notice, or record of a public meeting if one is held. You will be notified in writing of a scheduled public meeting. Upon issuance of a final Permit to Install a fee of **\$625** will be due. Please do not submit any payment now.

The Ohio EPA is urging companies to investigate pollution prevention and energy conservation. Not only will this reduce pollution and energy consumption, but it can also save you money. If you would like to learn ways you can save money while protecting the environment, please contact our Office of Pollution Prevention at (614) 644-3469. If you have any questions about this draft permit, please contact the field office where you submitted your application, or Mike Ahern, Field Operations & Permit Section at (614) 644-3631.

Sincerely,

Michael W. Ahern

Michael W. Ahern, Manager
Permit Issuance and Data Management Section
Division of Air Pollution Control

CC: USEPA

ARAQMD

MEDINA COUNTY

PUBLIC NOTICE
ISSUANCE OF DRAFT PERMIT TO INSTALL **16-02333** FOR AN AIR CONTAMINANT SOURCE FOR
Kokosing Materials Inc

On 9/30/2004 the Director of the Ohio Environmental Protection Agency issued a draft action of a Permit To Install an air contaminant source for **Kokosing Materials Inc**, located at **310 N State St, Medina, Ohio**.

Installation of the air contaminant source identified below may proceed upon final issuance of Permit To Install 16-02333:

Administrative modification of PTI 16-02333 issued final on March 25, 2004 to increase allowable hourly and annual emission rate for VOC per stack test results.

Comments concerning this draft action, or a request for a public meeting, must be sent in writing to the address identified below no later than thirty (30) days from the date this notice is published. All inquiries concerning this draft action may be directed to the contact identified below.

Lynn Malcolm, Akron Regional Air Quality Management District, 146 South High Street, Room 904, Akron, OH 44308 [(330)375-2480]



**Permit To Install
Terms and Conditions**

**Issue Date: To be entered upon final issuance
Effective Date: To be entered upon final issuance**

DRAFT PERMIT TO INSTALL 16-02333

Application Number: 16-02333
Facility ID: 1652050054
Permit Fee: **To be entered upon final issuance**
Name of Facility: Kokosing Materials Inc
Person to Contact: Ralph E Kyanko
Address: PO Box 334 17531 Waterford Rd
Fredericktown, OH 430199159

Location of proposed air contaminant source(s) [emissions unit(s)]:

**310 N State St
Medina, Ohio**

Description of proposed emissions unit(s):

Administrative modification of PTI 16-02333 issued final on March 25, 2004 to increase allowable hourly and annual emission rate for VOC per stack test results.

The above named entity is hereby granted a Permit to Install for the above described emissions unit(s) pursuant to Chapter 3745-31 of the Ohio Administrative Code. Issuance of this permit does not constitute expressed or implied approval or agreement that, if constructed or modified in accordance with the plans included in the application, the above described emissions unit(s) of environmental pollutants will operate in compliance with applicable State and Federal laws and regulations, and does not constitute expressed or implied assurance that if constructed or modified in accordance with those plans and specifications, the above described emissions unit(s) of pollutants will be granted the necessary permits to operate (air) or NPDES permits as applicable.

This permit is granted subject to the conditions attached hereto.

Ohio Environmental Protection Agency

Director

Kokosing Materials Inc

PTI Application: 16-02333

Issued: To be entered upon final issuance

Part I - GENERAL TERMS AND CONDITIONS

Facility ID: 1652050054

A. Permit to Install General Terms and Conditions

1. Compliance Requirements

The emissions unit(s) identified in this Permit to Install shall remain in full compliance with all applicable State laws and regulations and the terms and conditions of this permit.

2. Reporting Requirements

The permittee shall submit required reports in the following manner:

- a. Reports of any required monitoring and/or recordkeeping information shall be submitted to the appropriate Ohio EPA District Office or local air agency.
- b. Except as otherwise may be provided in the terms and conditions for a specific emissions unit, quarterly written reports of (a) any deviations (excursions) from emission limitations, operational restrictions, and control device operating parameter limitations that have been detected by the testing, monitoring, and recordkeeping requirements specified in this permit, (b) the probable cause of such deviations, and (c) any corrective actions or preventive measures which have been or will be taken, shall be submitted to the appropriate Ohio EPA District Office or local air agency. If no deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted quarterly, i.e., by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters. (These quarterly reports shall exclude deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06.)

3. Records Retention Requirements

Each record of any monitoring data, testing data, and support information required pursuant to this permit shall be retained for a period of five years from the date the record was created. Support information shall include, but not be limited to, all calibration and maintenance records and all original strip-chart recordings for continuous monitoring instrumentation, and copies of all reports required by this permit. Such records may be maintained in computerized form.

4. Inspections and Information Requests

The Director of the Ohio EPA, or an authorized representative of the Director, may, subject to the safety requirements of the permittee and without undue delay, enter upon the premises of this source at any reasonable time for purposes of making inspections, conducting tests, examining records or reports pertaining to any emission of air contaminants, and determining compliance with any applicable State air pollution laws and regulations and the terms and conditions of this permit. The permittee shall furnish to the Director of the Ohio EPA, or an authorized representative of the Director, upon receipt of a written request and within a reasonable time, any

Issued: To be entered upon final issuance

information that may be requested to determine whether cause exists for modifying, reopening or revoking this permit or to determine compliance with this permit. Upon verbal or written request, the permittee shall also furnish to the Director of the Ohio EPA, or an authorized representative of the Director, copies of records required to be kept by this permit.

5. Scheduled Maintenance/Malfunction Reporting

Any scheduled maintenance of air pollution control equipment shall be performed in accordance with paragraph (A) of OAC rule 3745-15-06. The malfunction of any emissions units or any associated air pollution control system(s) shall be reported to the appropriate Ohio EPA District Office or local air agency in accordance with paragraph (B) of OAC rule 3745-15-06. Except as provided in that rule, any scheduled maintenance or malfunction necessitating the shutdown or bypassing of any air pollution control system(s) shall be accompanied by the shutdown of the emissions unit(s) that is (are) served by such control system(s).

6. Permit Transfers

Any transferee of this permit shall assume the responsibilities of the prior permit holder. The appropriate Ohio EPA District Office or local air agency must be notified in writing of any transfer of this permit.

7. Air Pollution Nuisance

The air contaminants emitted by the emissions units covered by this permit shall not cause a public nuisance, in violation of OAC rule 3745-15-07.

8. Termination of Permit to Install

This Permit to Install shall terminate within eighteen months of the effective date of the Permit to Install if the owner or operator has not undertaken a continuing program of installation or modification or has not entered into a binding contractual obligation to undertake and complete within a reasonable time a continuing program of installation or modification. This deadline may be extended by up to 12 months if application is made to the Director within a reasonable time before the termination date and the party shows good cause for any such extension.

9. Construction of New Sources(s)

The proposed emissions unit(s) shall be constructed in strict accordance with the plans and application submitted for this permit to the Director of the Ohio Environmental Protection Agency. There may be no deviation from the approved plans without the express, written approval of the Agency. Any deviations from the approved plans or the above conditions may lead to such sanctions and penalties as provided under Ohio law. Approval of these plans does not constitute an assurance that the proposed facilities will operate in compliance with all Ohio laws and regulations. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed sources cannot meet the requirements of this permit or cannot meet applicable standards.

Kokosing Materials Inc

PTI Application: 16-02333

Issued: To be entered upon final issuance

Facility ID: 1652050054

If the construction of the proposed emissions unit(s) has already begun or has been completed prior to the date the Director of the Environmental Protection Agency approves the permit application and plans, the approval does not constitute expressed or implied assurance that the proposed facility has been constructed in accordance with the approved plans. The action of beginning and/or completing construction prior to obtaining the Director's approval constitutes a violation of OAC rule 3745-31-02. Furthermore, issuance of the Permit to Install does not constitute an assurance that the proposed source will operate in compliance with all Ohio laws and regulations. Approval of the plans in any case is not to be construed as an approval of the facility as constructed and/or completed. Moreover, issuance of the Permit to Install is not to be construed as a waiver of any rights that the Ohio Environmental Protection Agency (or other persons) may have against the applicant for starting construction prior to the effective date of the permit. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed facilities cannot meet the requirements of this permit or cannot meet applicable standards.

10. Public Disclosure

The facility is hereby notified that this permit, and all agency records concerning the operation of this permitted source, are subject to public disclosure in accordance with OAC rule 3745-49-03.

11. Applicability

This Permit To Install is applicable only to the emissions unit(s) identified in the Permit To Install. Separate Permit To Install for the installation or modification of any other emissions unit(s) are required for any emissions unit for which a Permit To Install is required.

12. Best Available Technology

As specified in OAC Rule 3745-31-05, all new sources must employ Best Available Technology (BAT). Compliance with the terms and conditions of this permit will fulfill this requirement.

13. Source Operation and Operating Permit Requirements After Completion of Construction

This facility is permitted to operate each source described by this Permit to Install for a period of up to one year from the date the source commenced operation. This permission to operate is granted only if the facility complies with all requirements contained in this permit and all applicable air pollution laws, regulations, and policies. Pursuant to OAC Chapter 3745-35, the permittee shall submit a complete operating permit application within ninety (90) days after commencing operation of the emissions unit(s) covered by this permit.

8

Kokosing Materials Inc

PTI Application: 16-02333

Issued: To be entered upon final issuance

Facility ID: 1652050054

Issued: To be entered upon final issuance

14. Construction Compliance Certification

The applicant shall provide Ohio EPA with a written certification (see enclosed form) that the facility has been constructed in accordance with the Permit to Install application and the terms and conditions of the Permit to Install. The certification shall be provided to Ohio EPA upon completion of construction but prior to startup of the source.

15. Fees

The permittee shall pay fees to the Director of the Ohio EPA in accordance with ORC section 3745.11 and OAC Chapter 3745-78. The permittee shall pay all applicable Permit to Install fees within 30 days after the issuance of this Permit to Install.

B. Permit to Install Summary of Allowable Emissions

The following information summarizes the total allowable emissions, by pollutant, based on the individual allowable emissions of each air contaminant source identified in this permit.

SUMMARY (for informational purposes only)
TOTAL PERMIT TO INSTALL ALLOWABLE EMISSIONS

<u>Pollutant</u>	<u>Tons Per Year</u>
SO ₂	13.6
VOC	13.5
NO _x	12.9
CO	38.6
PM (stack)	22.4
PM-10 (stack)	22.4
PM (fugitive)	2.33
PM-10 (fugitive)	1.14

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>
P902 - (Administrative Modification) 215 TPH asphaltic concrete drum mix plant controlled by a 52,000 ACFM baghouse (plant being modified to allow the burning of natural gas, no. 2 fuel oil, and on-spec waste oil); plant 516	OAC rule 3745-31-05(A)(3)

Emissions Unit ID: **P902**

Applicable Emissions
Limitations/Control Measures

OAC rule 3745-35-07(B)
(synthetic minor to avoid Title V requirements)

Carbon monoxide (CO) emissions from burning on-spec used oil shall not exceed 27.95 lbs/hr.

CO emissions from burning natural gas shall not exceed 35.28 lbs/hr.

CO emissions from burning number 2 fuel oil shall not exceed 27.95 lbs/hr.

Nitrogen Oxide (NO_x) emissions from burning on-spec used oil shall not exceed 11.83 lbs/hr.

NO_x emissions from burning natural gas shall not exceed 4.50 lbs/hr.

NO_x emissions from burning number 2 fuel oil shall not exceed 11.83 lbs/hr.

Sulfur Dioxide (SO₂) emissions from burning on-spec used oil shall not exceed 12.47 lbs/hr.

SO₂ emissions from natural gas shall not exceed 0.29 lbs/hr.

SO₂ emissions from burning number 2 fuel oil shall not exceed 2.37 lbs/hr.

OAC rule 3745-17-07(A)(1)
OAC rule 3745-17-11(B)(1)
OAC rule 3745-18-06(E)

Volatile Organic Compound (VOC) emissions from burning on-spec used oil shall not exceed 12.37 lbs/hr.

40 CFR Part 60, Subpart I

VOC emissions from burning natural gas shall not exceed 3.68 lbs/hr.

**Kokos
PTI A**

Emissions Unit ID: **P902**

Issued: To be entered upon final issuance

VOC emissions from burning number 2 fuel oil shall not exceed 6.88 lbs/hr.

PM-10 from the stack shall not exceed 0.04 gr/dscf when burning on-spec oil, number 2 fuel oil, or natural gas.

Emissions of fugitive PM-10 shall not exceed 0.94 pound per hour when burning on-spec used oil, number 2 fuel oil, or natural gas

Emissions of fugitive particulate emissions shall not exceed 1.93 pounds per hour when burning on-spec used oil, number 2 fuel oil, or natural gas

Arsenic, cadmium, chromium, and lead emissions are limited by the fuel specifications in A.2.b below.

Visible particulate emissions from the stack shall not exceed 20% opacity, as a 3-minute average.

Best available control measures that are sufficient to minimize or eliminate visible emissions of fugitive dust (see section A.2.a).

No visible emissions of fugitive dust from the enclosures for the hot aggregate elevator, vibrating screens, and weigh hopper.

Visible emissions of fugitive dust (from areas other than the enclosures for the hot aggregate

elevator, vibrating screens, and weigh hopper) shall be less than or equal to 10% opacity, as a 3-minute average.

The drop height of the front end loader bucket shall be minimized to the extent possible in order to minimize or eliminate visible emissions of fugitive dust from the aggregate storage bins.

The aggregate loaded into the storage bins shall have a moisture content sufficient to minimize the visible emissions of fugitive dust from conveyors and all transfer points to the dryer.

The requirements of this rule also include compliance with the requirements of OAC rule 3745-35-07(B) and 40CFR Part 60, Subpart I.

See A.2.c-e below

Particulate emissions (PE) from the stack shall not exceed 22.4 tons per rolling 12-month period.

PM-10 emissions from the stack shall not exceed 22.4 tons per rolling 12-month period.

Fugitive PE shall not exceed 2.33 tons per rolling 12-month period.

Fugitive PM-10 emissions shall not exceed 1.14 tons per rolling 12-month period.

CO emissions shall not exceed 38.6 tons per rolling 12-month period.

VOC emissions shall not exceed 13.5 tons per rolling 12-month period.

SO₂ emissions shall not exceed 13.6 tons per rolling 12-month period.

NO_x emissions shall not exceed 12.9 tons per rolling 12-month period.

The emissions limitations specified by these rules are less stringent than the emission limitations established pursuant to OAC rule 3745-31-05(A)(3).

PE from the stack shall not exceed 0.04 gr/dscf when burning on-spec oil, number 2 fuel oil, or natural gas.

Issued: To be entered upon final issuance**2. Additional Terms and Conditions**

2.a The permittee shall ensure that the baghouse is operated with sufficient air volume to minimize or eliminate visible fugitive emissions from the rotary drum.

2.b All on-spec used oil burned in this emissions unit shall meet the following specifications:

<u>Contaminant/Property</u>	Allowable Specifications
arsenic	5 ppm, maximum
cadmium	2 ppm, maximum
chromium	10 ppm, maximum
lead	100 ppm, maximum
PCB's	50 ppm, maximum
total halogens	4000 ppm maximum
mercury	1 ppm, maximum
flash point	100°F, minimum
heat content	135,000 Btu/gallon, minimum

2.c On-spec used oil containing more than 1000 ppm total halogens is presumed to be a hazardous waste under the rebuttable presumption provided under 40 CFR Part 266.40(c) and OAC rule 3745-279. Therefore, the permittee may receive and burn on-spec used oil exceeding 1000 ppm of total halogens (but less than 4000 ppm, maximum) only if the supplier ["marketer" in 40 Part CFR 266.43(a)] has demonstrated to the Ohio EPA's Division of Hazardous Waste Management that the on-spec used oil does not contain any hazardous waste.

- 2.d** All number 2 fuel oil and on-spec used oil burned in this emissions unit shall have a sulfur content equal to or less than 0.5%.
- 2.e** The hourly allowable emissions limitations when the plant is fueled by number 2 fuel oil established in this permit through BAT are based upon AP-42, Fifth edition, Table 11.1-7 (12/00) and from AP-42, Fifth edition, Table 11.1-8 (12/00). The hourly allowable emissions limitations when the plant is fueled by natural gas established in this permit through BAT are based upon emissions determined by a stack test at this facility (Medina plant) on July 17-18, 2003 while the plant was fueled by natural gas. The hourly allowable emissions limitations when the plant is fueled by on-spec used oil established in this permit through BAT are based upon emissions determined by a stack test at this facility (Medina plant) on July 16, 2004 while the plant was fueled by on-spec used oil.

B. Operational Restrictions

1. The pressure drop across the fabric filter shall be maintained within the range of 2 to 8 inches of water while the emissions unit is in operation.
2. The permittee may not receive or burn any on-spec used oil which does not meet the specifications listed in A.2.b of this permit without first obtaining a permit to install that authorizes the burning of such off-specification used oil. The burning of off-specification used oil is subject to OAC rule 3745-279-60 through 67.
3. The maximum annual asphalt production rate for this emissions unit shall not exceed 470,000 tons per year, based upon a rolling, 12-month summation of the production rates. The permittee has existing production records and therefore the permittee does not have to be limited to first year monthly asphalt production values.
4. The exit of the stack serving this emissions unit shall be a minimum of 35 feet above ground.
5. The permittee may substitute reclaimed asphalt pavement (RAP) and or asphalt shingles in the raw material feed mix in amounts not to exceed 50 percent of all aggregate materials.

C. Monitoring and/or Recordkeeping Requirements

1. The permittee shall receive a chemical analysis with each shipment of on-spec used oil from the supplier. The analysis shall identify the name and address of the supplier, the supplier's USEPA identification number, and the following information:
 - a. Date of shipment or delivery;

15

Kokos

PTI A

Issued: To be entered upon final issuance

Emissions Unit ID: **P902**

- b. Quantity of on-spec used oil received;

Issued: To be entered upon final issuance

- c. The Btu value of the on-spec used oil;
- d. The flash point of the on-spec used oil;
- e. The arsenic content;
- f. The cadmium content;
- g. The chromium content;
- h. The lead content;
- i. The PCB content;
- j. The total halogen content; and
- k. The mercury content.

Each analysis shall be kept in a readily accessible location for at least 5 years and shall be made available to the Ohio EPA, Central District Office upon verbal or written request. The Director or any authorized representative of the Director may require or may conduct periodic, detailed chemical analyses through an independent laboratory of any used oil shipment received by this facility, of any used oil stored at this facility, or of any used oil sampled at the dryer.

- 2. The permittee shall properly install, operate, and maintain equipment to monitor the pressure drop across the fabric filter while the emissions unit is in operation. The monitoring equipment shall be installed, calibrated, operated, and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual(s). The permittee shall record the pressure drop across the fabric filter on daily basis.
- 3. The permittee shall maintain monthly records of the following information:
 - a. The asphaltic concrete production for each month, in tons;
 - b. The rolling, 12-month summation of the asphaltic concrete produced, in tons.
 - c. The type and amount (gallons or cubic feet) of fuel burned; and
 - d. The maximum percentage RAP used for any mix.

Emissions Unit ID: **P902**

4. For each shipment of number 2 fuel oil and on-spec used oil received for burning in this emissions unit, the permittee shall maintain records of the total quantity of oil received and the permittees or oil supplier's analyses for sulfur content and heat content.
5. The permittee shall perform daily visible emission checks, when the emissions unit is in operation and when the weather conditions allow, for any visible particulate emissions from the enclosures for the hot aggregate elevator, vibrating screens and weigh hopper servicing this emissions unit. If visible particulate emissions are observed, the permittee shall note the following in the operation log:
 - a. The color of the visible particulate emissions;
 - b. The cause of the visible particulate emissions;
 - c. The total duration of the visible particulate emission incident; and
 - d. Corrective actions taken to eliminate the visible particulate emissions.

The permittee may, upon receipt of written approval from the appropriate Ohio EPA District Office or local air agency, modify the above-mentioned visible particulate emissions check frequency if operating experience indicates that less frequent checks would be sufficient to ensure compliance with the visible particulate emissions requirements.

6. The permittee shall perform daily visible emission checks, when the emissions unit is in operation and when the weather conditions allow, for any abnormal visible particulate emissions from the stack, aggregate storage bins and cold aggregate elevator/conveyor serving this emissions unit. If abnormal visible emissions are observed, the permittee shall note the following in the operation log:
 - a. The color of the abnormal visible particulate emissions;
 - b. The cause of the abnormal visible particulate emissions;
 - c. The total duration of any abnormal visible particulate emissions incident; and
 - d. Any corrective actions taken to eliminate the abnormal visible particulate emissions.

The permittee may, upon receipt of written approval from the appropriate Ohio EPA District Office or local air agency modify the above-mentioned visible particulate emissions check frequency if operating experience indicates that less frequent checks would be sufficient to ensure compliance with the visible particulate emissions requirements.

Issued: To be entered upon final issuance

7. The permit to install for this emissions unit (P902) was evaluated based on the actual materials and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant(s):

Pollutant: Heptane

TLV (ug/m3): 1,640

Maximum Hourly Emission Rate (lbs/hr): 3.38

Predicted 1-Hour Maximum Ground-Level
Concentration (ug/m3): 5.59

MAGLC (ug/m3): 39,048

Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be still satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

- a. Changes in the composition of the materials used or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value previously modeled;
- b. Changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and
- c. Physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

Emissions Unit ID: P902

If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01(VV)(1)(a)(ii), and a modification of the existing permit to install will not be required. If the change(s) is (are) defined as a modification under other provisions of the modification definition (other than (VV)(1)(a)(ii)), then the permittee shall obtain a final permit to install prior to the change.

8. The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy:"
 - a. A description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
 - b. Documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and
 - c. Where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

D. Reporting Requirements

1. The permittee shall submit quarterly pressure drop deviation (excursion) reports that identify all periods of time during which the pressure drop across the baghouse did not comply with the allowable range specified above. These reports are due by the date described in Part 1- General Terms and Condition of this permit under section (A)(2).
2. The permittee shall submit deviation (excursion) reports which identify all exceedances of the rolling, 12-month production limitation. These reports are due by the date described in Part 1 - General Terms and Conditions of this permit under section (A)(2).
3. The permittee shall submit annual reports which specify the total PM, SO₂, NO_x, VOC and CO emissions from this emissions unit for the previous calendar year. These reports shall be submitted by April 15 of each year.
4. The permittee shall notify the USEPA and the Ohio EPA if any of the on-spec used oil exceeds the on-spec used oil specifications found in OAC rule 3745-279-11. If the permittee is burning on-spec used oil which exceeds the specifications found in OAC rule 3745-279-11, the permittee is subject to that rule and must comply with all provisions of that rule. The required notification shall be submitted within 30 days of the date in which the exceedance occurred.
5. The permittee shall submit quarterly deviation (excursion) reports that identify all exceedances of

Issued: To be entered upon final issuance

the sulfur content limit specified above. These reports are due by the date described in Part 1- General Terms and Condition of this permit under section (A)(2).

6. The permittee shall submit quarterly deviation (excursion) reports that identify any of the following occurrences:
 - a. Identify all days during which any visible particulate emissions were observed from the stack serving this emissions unit;
 - b. Identify all days during which any visible fugitive particulate emissions were observed from the enclosures for the hot aggregate elevator, vibrating screens, weigh hopper, aggregate storage bins and cold aggregate elevator associated with this emissions unit;
 - c. Describe any corrective actions taken to eliminate the abnormal visible particulate emissions.

These reports are due by the date described in Part 1 - General Terms and Conditions of this permit under section (A)(2).

E. Testing Requirements

1. Compliance with the emission limitations specified in Section A.1 of these terms and conditions shall be determined in accordance with the following methods:
 - a. Emission Limitations: PE shall not exceed 0.04 gr/dscf; VOC emissions shall not exceed 12.37 lbs/hr when burning on-spec used oil and 6.88 lbs/hr when burning number 2 fuel; CO emissions from burning number 2 fuel or on-spec used oil shall not exceed 27.95 lbs/hr; SO₂ emissions shall not exceed 12.47 lbs/hr when burning on-spec used oil and 2.37 lbs/hr when burning number 2 fuel; and NO_x emissions from burning number 2 fuel or on-spec used oil shall not exceed 11.83 lbs/hr.

Applicable Compliance Method: The permittee shall conduct, or have conducted, emission testing for this emissions unit in accordance with the following requirements:

- i. The emission testing shall be conducted within 60 days after achieving the maximum production rate but no later than 180 days after initial startup of the emissions unit.
- ii. The emission testing shall be conducted to demonstrate compliance with the allowable mass emission rates for PM, VOC, CO, NO_x and SO₂.
- iii. The following test method(s) shall be employed to demonstrate compliance with the allowable mass emission rate(s) for :

For PM, Methods 1-5 of 40 CFR Part 60, Appendix A.

For NO_x, Methods 1-4 and 7 or 7E of 40 CFR Part 60, Appendix A.

For SO₂, Methods 1-4 and 6 or 6C of 40 CFR Part 60, Appendix A

For CO, Methods 1-4 and 10 of 40 CFR Part 60, Appendix A

For VOC, Methods 1-4 and 18 and 25 of 40 CFR Part 60, Appendix A

Alternative U.S. EPA approved test methods may be used with prior approval from the Ohio EPA.

- iv. The test(s) shall be conducted while this emissions unit is operating at or near its maximum capacity and burning number 2 fuel oil or on spec used oil for PM, VOC,

Issued: To be entered upon final issuance

CO, NO_x and SO₂ and employing RAP to verify VOC emissions, unless otherwise specified or approved by the Akron Regional Air Quality Management District.

Not later than 30 days prior to the proposed test date(s), the permittee shall submit an "Intent to Test" notification to the Akron Regional Air Quality Management District. The "Intent to Test" notification shall describe in detail the proposed test methods and procedures, the emissions unit operating parameters, the time(s) and date(s) of the test(s), and the person(s) who will be conducting the test(s). Failure to submit such notification for review and approval prior to the test(s) may result in the Akron Regional Air Quality Management District's refusal to accept the results of the emission test(s).

Personnel from the Akron Regional Air Quality Management District shall be permitted to witness the test(s), examine the testing equipment, and acquire data and information necessary to ensure that the operation of the emissions unit and the testing procedures provide a valid characterization of the emissions from the emissions unit and/or the performance of the control equipment.

A comprehensive written report on the results of the emissions test(s) shall be signed by the person or persons responsible for the tests and submitted to the Akron Regional Air Quality Management District within 30 days following completion of the test(s). The permittee may request additional time for the submittal of the written report, where warranted, with prior approval from the Ohio EPA, Central District Office.

- b. Emissions Limitation: PE emissions shall not exceed 22.4 tons per rolling 12-month period.

Applicable Compliance Method: Compliance with the annual emissions limitation shall be based upon the results of the most recent emissions testing and the records required by term and condition C.3 above.

- c. Emission Limitation: VOC emissions shall not exceed 13.5 tons per rolling 12-month period.

Applicable Compliance Method: Compliance with the annual emissions limitation shall be based upon the results of the most recent emissions testing and the records required by term and condition C.3 above.

- d. Emission Limitation: CO emissions shall not exceed 38.6 tons per rolling 12-month period.

Applicable Compliance Method: Compliance with the annual emissions limitation shall be

Kokosing Materials Inc
PTI Application: 16-02222
Issued

Facility ID: 1652050054

Emissions Unit ID: **P902**

based upon the results of the most recent emissions testing and the records required by term and condition C.3 above.

- e. Emission Limitation: SO₂ emissions shall not exceed 13.6 tons per rolling 12-month period.

Applicable Compliance Method: Compliance with the annual emissions limitation shall be based upon the results of the most recent emissions testing and the records required by term and condition C.3 above.

Issued: To be entered upon final issuance

- f. Emission Limitation: NO_x emissions shall not exceed 12.9 tons per rolling 12-month period.

Applicable Compliance Method: Compliance with the annual emissions limitation shall be based upon the results of the most recent emissions testing and the records required by term and condition C.3 above.

- g. Emission Limitations: Arsenic, cadmium, chromium and lead emissions are limited by the fuel specifications in A.2.b.

Applicable Compliance Method: Compliance with the emissions limitation for arsenic, cadmium and lead shall be demonstrated by the monitoring and record keeping in Section C.1 of this permit.

- h. Emission Limitation: Visible particulate emissions from the stack shall not exceed 20% opacity as a 3-minute average.

Applicable Compliance Method: Compliance shall be determined using Method 9 as set forth in 40 CFR Part 60 Appendix A, as such appendix existed on July 1, 1996 and the modifications listed in paragraphs (B)(3)(a) and (B)(3)(b) of OAC rule 3745-17-03.

- i. Emission Limitation: No visible emissions of fugitive dust from the enclosures for the hot aggregate elevator, vibrating screens and weigh hopper.

Applicable Compliance Method: Compliance with the limitations on visible emissions of fugitive dust found in Section A.1 of this permit shall be demonstrated by the monitoring and record keeping in Section C.5.

- j. Emission Limitation: Visible emissions of fugitive dust (from areas other than the enclosures for the hot aggregate elevator, vibrating screens, and weigh hopper) shall be less than or equal to 10% opacity, as a 3-minute average.

Applicable Compliance Method: Compliance shall be determined in accordance with Test Method 9 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources"), as such Appendix existed on July 1, 1996, and the modifications listed in paragraphs (B)(3)(a) and (B)(3)(b) of OAC rule 3745-17-03.

- k. Emissions Limitation: PM-10 emissions from the stack shall not exceed 22.41 tons per rolling 12-month period.

Applicable Compliance Method: Compliance with the annual emissions limitation shall be

Issued: To be entered upon final issuance

assumed as long as compliance is maintained with the rolling 12-month emissions limitation for particulate emissions.

1. Emissions Limitation: Fugitive PM-10 emissions shall not exceed 1.14 tons per rolling 12-month period.

Applicable Compliance Method: Compliance with the annual emissions limitation shall be assumed based upon the following worst case calculations:

Total fugitive emissions equal the summation of the fugitives from the cold end and the hot end of the plant operations.

Fugitives emissions from the cold end are calculated as follows

$$((470,000 \text{ tons of material/year} \times 0.0024 \text{ lb PM-10/ton of material}) + (235,000 \text{ tons of aggregate/year} \times 0.0033 \text{ lb PM-10/ton of aggregate}) + (235,000 \text{ tons of sand/year} \times 0.00099 \text{ lb PM-10/ton of sand})) \times (1 \text{ ton}/2000 \text{ pounds}) = 1.07 \text{ tons of PM-10}$$

Fugitives emissions from the hot end are calculated as follows

$$(470,000 \text{ tons of asphalt produced} \times 0.0003 \text{ lb of PM-10/ton of asphalt produced}) \times (1 \text{ ton}/2000 \text{ pounds}) = 0.07 \text{ ton of PM-10.}$$

Total fugitive emissions are therefore 1.14 tons.

The emission factors in the above equations are derived from AP-42, Fifth edition, Table 11.12-2(10/01) and from AP-42, Fifth edition, 11.1.2.5(12/00).

- m. Emissions Limitation: Fugitive PM emissions shall not exceed 2.33 tons per rolling 12-month period.

Applicable Compliance Method: Compliance with the annual emissions limitation shall be assumed based upon the following worst case calculations:

Total fugitive emissions equal the summation of the fugitives from the cold end and the hot end of the plant operations.

Fugitives emissions from the cold end are calculated as follows

$$((470,000 \text{ tons of material/year} \times 0.0051 \text{ lb PM/ton of material}) + (235,000 \text{ tons of aggregate/year} \times 0.0069 \text{ lb PM/ton of aggregate}) + (235,000 \text{ tons of sand/year} \times 0.0021$$

Emissions Unit ID: **P902**

lb PM/ton of sand)) X (1 ton/2000 pounds) = 2.26 tons of PM

Fugitives emissions from the hot end are calculated as follows

(470,000 tons of asphalt produced X 0.0003 lb of PM/ton of asphalt produced) X (1 ton/2000 pounds) = 0.07 tons of PM.

Total fugitive emissions are therefore 2.33 tons.

The emission factors in the above equations are derived from AP-42, Fifth edition, Table 11.12-2(10/01) and from AP-42, Fifth edition, 11.1.2.5(12/00)

- n. Emission Limitations: Emissions of fugitive PM-10 shall not exceed 0.94 pound per hour when burning on-spec used oil, number 2 fuel oil, or natural gas.

Applicable Compliance Method: Compliance with the annual emissions limitation shall be assumed based upon the following worst case calculations:

Total fugitive emissions equal the summation of the fugitives from the cold end and the hot end of the plant operations.

Fugitives emissions from the cold end are calculated as follows

(215 tons of material/hour X 0.0024 lb PM-10/ton of material) + (86 tons of aggregate/hour X 0.0033lb PM-10/ton of aggregate) + (86 tons of sand/hour X 0.00099 lb PM-10/ton of sand) = 0.88 pound per hour of PM-10

Fugitives emissions from the hot end are calculated as follows

215 tons of asphalt produced X 0.0003 lb of PM-10/ton of asphalt produced = 0.06 pound per hour of PM-10.

Total fugitive emissions are therefore 0.94 pound per hour.

The emission factors in the above equations are derived from AP-42, Fifth edition, Table 11.12-2(10/01) and from AP-42, Fifth edition, 11.1.2.5(12/00)

- o. Emission Limitations: Emissions of fugitive PM shall not exceed 1.93 pounds per hour when burning on-spec used oil, number 2 fuel oil, or natural gas.

Applicable Compliance Method: Compliance with the annual emissions limitation shall be

Issued: To be entered upon final issuance

assumed based upon the following worst case calculations:

Total fugitive emissions equal the summation of the fugitives from the cold end and the hot end of the plant operations.

Fugitives emissions from the cold end are calculated as follows

$$(215 \text{ tons of material/hour} \times 0.0051 \text{ lb PM/ton of material}) + (86 \text{ tons of aggregate/hour} \times 0.0069 \text{ lb PM/ton of aggregate}) + (86 \text{ tons of sand/hour} \times 0.0021 \text{ lb PM/ton of sand}) = 1.87 \text{ pounds per hour of PM}$$

Fugitives emissions from the hot end are calculated as follows

$$215 \text{ tons of asphalt produced} \times 0.0003 \text{ lb of PM/ton of asphalt produced} = 0.06 \text{ pound per hour of PM.}$$

Total fugitive emissions are therefore 1.93 pounds per hour.

The emission factors in the above equations are derived from AP-42, Fifth edition, Table 11.12-2(10/01) and from AP-42, Fifth edition, 11.1.2.5(12/00)

F. Miscellaneous Requirements

1. The following source is subject to the applicable provision of the New Source Performance Standards (NSPS) as promulgated by the United States Environmental Protection Agency, 40 CFR part 60.

<u>Source Number</u>	<u>Source Description</u>	<u>NSPS Regulation (Subpart)</u>
P902	215 tph asphalt batch plant	Subpart I

The application and enforcement of these standards are delegated to the Ohio EPA. The requirements of 40 CFR Part 60 are also federally enforceable.

Pursuant to NSPS, the source owner/operator is hereby advised of the requirement to report the following at the appropriate times:

- a. Construction date (no later than 30 days after such date);
- b. Anticipated start-up date (not more than 60 days or less than 30 days prior to such date);
- c. Actual start-up date (within 15 days after such date); and

Kokos

PTI A

Emissions Unit ID: **P902**

Issued: To be entered upon final issuance

- d. Date of performance testing (If required, at least 30 days prior to testing).

Reports are to be sent to:

Ohio Environmental Protection Agency
DAPC- Air Quality Modeling and Planning
P.O. Box 1049
Columbus, OH 43216-1049

and

**Kokos
PTI A**

Emissions Unit ID: **P902**

Issued: To be entered upon final issuance

Akron Regional Air Quality Management District
146 South High Street
Suite 904
Akron, OH 44308

2. The terms and conditions of this PTI are federally enforceable, except for term C.7.
3. The terms and conditions of this PTI supersede all requirements of PTI 16-02333, issued final on March 25, 2004.