



State of Ohio Environmental Protection Agency

**RE: FINAL PERMIT TO INSTALL CERTIFIED MAIL
MEDINA COUNTY**

Street Address:

122 S. Front Street

Lazarus Gov. Center TELE: (614) 644-3020 FAX: (614) 644-2329

Mailing Address:

Lazarus Gov. Center
P.O. Box 1049

**Application No: 16-02425
Fac ID: 1652070030**

DATE: 11/17/2005

Blair Rubber Co
Dave Jentsch
1252 Mina Ave
Copley, OH 44321

Enclosed please find an Ohio EPA Permit to Install which will allow you to install the described source(s) in a manner indicated in the permit. Because this permit contains several conditions and restrictions, I urge you to read it carefully.

The Ohio EPA is urging companies to investigate pollution prevention and energy conservation. Not only will this reduce pollution and energy consumption, but it can also save you money. If you would like to learn ways you can save money while protecting the environment, please contact our Office of Pollution Prevention at (614) 644-3469.

You are hereby notified that this action by the Director is final and may be appealed to the Ohio Environmental Review Appeals Commission pursuant to Chapter 3745.04 of the Ohio Revised Code. The appeal must be in writing and set forth the action complained of and the grounds upon which the appeal is based. It must be filed within thirty (30) days after the notice of the Directors action. A copy of the appeal must be served on the Director of the Ohio Environmental Protection Agency within three (3) days of filing with the Commission. An appeal may be filed with the Environmental Review Appeals Commission at the following address:

Environmental Review Appeals Commission
309 South Fourth Street, Room 222
Columbus, Ohio 43215

Sincerely,

Michael W. Ahern, Manager
Permit Issuance and Data Management Section
Division of Air Pollution Control

CC: USEPA

ARAQMD



**Permit To Install
Terms and Conditions**

**Issue Date: 11/17/2005
Effective Date: 11/17/2005**

FINAL PERMIT TO INSTALL 16-02425

Application Number: 16-02425
Facility ID: 1652070030
Permit Fee: **\$2200**
Name of Facility: Blair Rubber Co
Person to Contact: Dave Jentsch
Address: 1252 Mina Ave
Copley, OH 44321

Location of proposed air contaminant source(s) [emissions unit(s)]:
**5020 Panther Pkwy
Seville, Ohio**

Description of proposed emissions unit(s):
Facility Relocation Including Installation of New Equipment.

The above named entity is hereby granted a Permit to Install for the above described emissions unit(s) pursuant to Chapter 3745-31 of the Ohio Administrative Code. Issuance of this permit does not constitute expressed or implied approval or agreement that, if constructed or modified in accordance with the plans included in the application, the above described emissions unit(s) of environmental pollutants will operate in compliance with applicable State and Federal laws and regulations, and does not constitute expressed or implied assurance that if constructed or modified in accordance with those plans and specifications, the above described emissions unit(s) of pollutants will be granted the necessary permits to operate (air) or NPDES permits as applicable.

This permit is granted subject to the conditions attached hereto.

Ohio Environmental Protection Agency

Director

Blair Rubber Co
PTI Application: 16-02425
Issued: 11/17/2005

Facility ID: 1652070030

Part I - GENERAL TERMS AND CONDITIONS

A. Permit to Install General Terms and Conditions

1. Compliance Requirements

The emissions unit(s) identified in this Permit to Install shall remain in full compliance with all applicable State laws and regulations and the terms and conditions of this permit.

2. Reporting Requirements

The permittee shall submit required reports in the following manner:

- a. Reports of any required monitoring and/or record keeping information shall be submitted to the appropriate Ohio EPA District Office or local air agency.
- b. Except as otherwise may be provided in the terms and conditions for a specific emissions unit, quarterly written reports of (a) any deviations (excursions) from emission limitations, operational restrictions, and control device operating parameter limitations that have been detected by the testing, monitoring, and record keeping requirements specified in this permit, (b) the probable cause of such deviations, and (c) any corrective actions or preventive measures which have been or will be taken, shall be submitted to the appropriate Ohio EPA District Office or local air agency. If no deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted quarterly, i.e., by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters. (These quarterly reports shall exclude deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06.)

3. Records Retention Requirements

Each record of any monitoring data, testing data, and support information required pursuant to this permit shall be retained for a period of five years from the date the record was created. Support information shall include, but not be limited to, all calibration and maintenance records and all original strip-chart recordings for continuous monitoring instrumentation, and copies of all reports required by this permit. Such records may be maintained in computerized form.

4. Inspections and Information Requests

The Director of the Ohio EPA, or an authorized representative of the Director, may, subject to the safety requirements of the permittee and without undue delay, enter upon

Blair Rubber Co
PTI Application: 16-02425
Issued: 11/17/2005

Facility ID: 1652070030

the premises of this source at any reasonable time for purposes of making inspections, conducting tests, examining records or reports pertaining to any emission of air contaminants, and determining compliance with any applicable State air pollution laws and regulations and the terms and conditions of this permit. The permittee shall furnish to the Director of the Ohio EPA, or an authorized representative of the Director, upon receipt of a written request and within a reasonable time, any information that may be requested to determine whether cause exists for modifying, reopening or revoking this permit or to determine compliance with this permit. Upon verbal or written request, the permittee shall also furnish to the Director of the Ohio EPA, or an authorized representative of the Director, copies of records required to be kept by this permit.

5. Scheduled Maintenance/Malfunction Reporting

Any scheduled maintenance of air pollution control equipment shall be performed in accordance with paragraph (A) of OAC rule 3745-15-06. The malfunction of any emissions units or any associated air pollution control system(s) shall be reported to the appropriate Ohio EPA District Office or local air agency in accordance with paragraph (B) of OAC rule 3745-15-06. Except as provided in that rule, any scheduled maintenance or malfunction necessitating the shutdown or bypassing of any air pollution control system(s) shall be accompanied by the shutdown of the emissions unit(s) that is (are) served by such control system(s).

6. Permit Transfers

Any transferee of this permit shall assume the responsibilities of the prior permit holder. The appropriate Ohio EPA District Office or local air agency must be notified in writing of any transfer of this permit.

7. Air Pollution Nuisance

The air contaminants emitted by the emissions units covered by this permit shall not cause a public nuisance, in violation of OAC rule 3745-15-07.

8. Termination of Permit to Install

This Permit to Install shall terminate within eighteen months of the effective date of the Permit to Install if the owner or operator has not undertaken a continuing program of installation or modification or has not entered into a binding contractual obligation to undertake and complete within a reasonable time a continuing program of installation or modification. This deadline may be extended by up to 12 months if application is made to the Director within a reasonable time before the termination date and the party shows good cause for any such extension.

9. Construction of New Sources(s)

Blair Rubber Co
PTI Application: 16-02425
Issued: 11/17/2005

Facility ID: 1652070030

The proposed emissions unit(s) shall be constructed in strict accordance with the plans and application submitted for this permit to the Director of the Ohio Environmental Protection Agency. There may be no deviation from the approved plans without the express, written approval of the Agency. Any deviations from the approved plans or the above conditions may lead to such sanctions and penalties as provided under Ohio law. Approval of these plans does not constitute an assurance that the proposed facilities will operate in compliance with all Ohio laws and regulations. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed sources cannot meet the requirements of this permit or cannot meet applicable standards.

If the construction of the proposed emissions unit(s) has already begun or has been completed prior to the date the Director of the Environmental Protection Agency approves the permit application and plans, the approval does not constitute expressed or implied assurance that the proposed facility has been constructed in accordance with the approved plans. The action of beginning and/or completing construction prior to obtaining the Director's approval constitutes a violation of OAC rule 3745-31-02. Furthermore, issuance of the Permit to Install does not constitute an assurance that the proposed source will operate in compliance with all Ohio laws and regulations. Approval of the plans in any case is not to be construed as an approval of the facility as constructed and/or completed. Moreover, issuance of the Permit to Install is not to be construed as a waiver of any rights that the Ohio Environmental Protection Agency (or other persons) may have against the applicant for starting construction prior to the effective date of the permit. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed facilities cannot meet the requirements of this permit or cannot meet applicable standards.

10. Public Disclosure

The facility is hereby notified that this permit, and all agency records concerning the operation of this permitted source, are subject to public disclosure in accordance with OAC rule 3745-49-03.

11. Applicability

This Permit To Install is applicable only to the emissions unit(s) identified in the Permit To Install. Separate Permit To Install for the installation or modification of any other emissions unit(s) are required for any emissions unit for which a Permit To Install is required.

12. Best Available Technology

As specified in OAC Rule 3745-31-05, all new sources must employ Best Available Technology (BAT). Compliance with the terms and conditions of this permit will fulfill this requirement.

Blair Rubber Co
 PTI Application: 16-02425
 Issued: 11/17/2005

Facility ID: 1652070030

13. Source Operation and Operating Permit Requirements After Completion of Construction

This facility is permitted to operate each source described by this Permit to Install for a period of up to one year from the date the source commenced operation. This permission to operate is granted only if the facility complies with all requirements contained in this permit and all applicable air pollution laws, regulations, and policies. Pursuant to OAC Chapter 3745-35, the permittee shall submit a complete operating permit application within ninety (90) days after commencing operation of the emissions unit(s) covered by this permit.

14. Construction Compliance Certification

The applicant shall provide Ohio EPA with a written certification (see enclosed form) that the facility has been constructed in accordance with the Permit to Install application and the terms and conditions of the Permit to Install. The certification shall be provided to Ohio EPA upon completion of construction but prior to startup of the source.

15. Fees

The permittee shall pay fees to the Director of the Ohio EPA in accordance with ORC section 3745.11 and OAC Chapter 3745-78. The permittee shall pay all applicable Permit to Install fees within 30 days after the issuance of this Permit to Install.

B. Permit to Install Summary of Allowable Emissions

The following information summarizes the total allowable emissions, by pollutant, based on the individual allowable emissions of each air contaminant source identified in this permit.

**SUMMARY (for informational purposes only)
 TOTAL PERMIT TO INSTALL ALLOWABLE EMISSIONS**

<u>Pollutant</u>	<u>Tons Per Year</u>
PE	43.80
VOC	35.04

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P901 - Banbury Mixer	OAC rule 3745-31-05(A)(3)	2.0 pound/hour and 8.76 tons/year of particulate emission (PE)
		1.0 pound/hour and 4.38 tons/year of volatile organic compounds (VOC)
	OAC rule 3745-17-07(B)	20% opacity, as a 3-minute average, for the fugitive emissions
	OAC rule 3745-17-08	There shall be no visible emissions to the ambient air from the operation of this emissions unit.
	OAC rule 3745-17-11(B)	
	OAC rule 3745-21-07(G)(2)	See A.2.a below. See B.1 below.

2. Additional Terms and Conditions

- 2.a The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).

B. Operational Restrictions

1. The permittee shall not employ any photochemically reactive materials, as defined in OAC rule 3745-21-01(C)(5), in this emissions unit.

C. Monitoring and/or Record keeping Requirements

1. The permittee shall perform daily checks, when the emissions unit is in operation, for any visible fugitive particulate emissions from the egress points (i.e., building windows, doors, roof monitors, etc.) serving this emissions unit. The presence or absence of any visible emissions shall be noted in an operations log. If visible emissions are observed, the permittee shall also note the following in the operations log:
 - a. The location and color of the emissions;
 - b. Whether the emissions are representative of normal operations;
 - c. If the emissions are not representative of normal operations, the cause of the abnormal emissions;
 - d. The total duration of any visible emission incident; and
 - e. Any corrective actions taken to minimize or eliminate the visible emissions.

If visible emissions are present, a visible emission incident has occurred. The observer does not have to document the exact start and end times for the visible emission incident under item (d) above or continue the daily check until the incident has ended. The observer may indicate that the visible emission incident was continuous during the observation period (or, if known, continuous during the operation of the emissions unit). With respect to the documentation of corrective actions, the observer may indicate that no corrective actions were taken if the visible emissions were representative of normal operations, or specify the minor corrective actions that were taken to ensure that the emissions unit continued to operate under normal conditions, or specify the corrective actions that were taken to eliminate abnormal visible emissions.

2. The permittee shall maintain the following information for this emissions unit:
 - a. The MSDS sheets for each liquid organic material employed; and
 - b. Documentation as to whether or not each material is a photochemically reactive

material.

D. Reporting Requirements

1. The permittee shall submit semiannual written reports that (a) identify all days during which any visible fugitive particulate emissions were observed from the from the egress points (i.e., building windows, doors, roof monitors, etc.) serving this emissions unit, and (b) describe any corrective actions taken to minimize or eliminate the visible particulate and/or visible fugitive particulate emissions. These reports shall be submitted to the Director (the appropriate Ohio EPA District Office or local air agency) by January 31 and July 31 of each year and shall cover the previous 6-month period.
2. The permittee shall notify the Director (the appropriate Ohio EPA District Office or local air agency) in writing if a "photochemically reactive material" (as defined in OAC 3745-21-05(C)(5)) is employed in the emissions unit. The notification shall be sent to the Director (the appropriate Ohio EPA District Office or local air agency) within 45 days after such an occurrence.

E. Testing Requirements

1. Compliance with the emission limitation(s) in Section A.I. of these terms and conditions shall be determined in accordance with the following method(s):
 - a. Emission Limitation:

2.0 pound/hour of PE

Applicable Compliance Method:

Multiply the PE factor of 9.25 e-04 pound(s) of PE per pound of rubber (Draft AP-42 Section 4.12 - Table 4.12-4) by the maximum hourly production rate.
 - b. Emission Limitation:

8.76 tons/year of PE

Applicable Compliance Method:

To calculate the ton per year limit, multiply the maximum hourly emission limit times 8760 hours per year, then divide by 2000.

c. Emission Limitation:

1.0 pound/hour VOC

Applicable Compliance Method:

Multiply the VOC emissions factor of 4.44 e-04 pound(s) of VOC emissions per pound of rubber (Draft AP-42 Section 4.12 - Table 4.12-4) by the maximum hourly production rate.

d. Emission Limitation:

4.38 tons/year of VOC

Applicable Compliance Method:

To calculate the ton per year limit, multiply the maximum hourly emission limit times 8760 hours per year, then divide by 2000.

e. Emission Limitation:

20% opacity, as a three-minute average, for the fugitive emissions
VE shall not exceed 20% opacity as a three-minute average, except as provided by rule.

Applicable Compliance Method:

Compliance shall be demonstrated based upon VE evaluations performed in accordance with the methods and procedures specified in 40 CFR Part 60, Appendix A, Method 9 and OAC rule 3745-17-03(B)(3)

f. Emission Limitation:

There shall be no VEs to the ambient air from the operation of this emissions unit.

Applicable Compliance Method:

Compliance shall be demonstrated based upon VE evaluations performed in accordance with the methods and procedures specified in 40 CFR Part 60, Appendix A, Method 22 and OAC rule 3745-17-03(B)(4)

F. Miscellaneous Requirements

None

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P902 - Banbury 60-inch Mill	OAC rule 3745-31-05(A)(3)	2.0 pound/hour and 8.76 tons/year of particulate emission (PE)
		1.0 pound/hour and 4.38 tons/year of volatile organic compounds (VOC)
	OAC rule 3745-17-07(B)	20% opacity, as a 3-minute average, for the fugitive emissions
	OAC rule 3745-17-08	
	OAC rule 3745-17-11(B)	There shall be no visible emissions to the ambient air from the operation of this emissions unit.
	OAC rule 3745-21-07(G)(2)	See A.2.a below. See B.1 below.

2. Additional Terms and Conditions

- 2.a The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).

B. Operational Restrictions

1. The permittee shall not employ any photochemically reactive materials, as defined in OAC rule 3745-21-01(C)(5), in this emissions unit.

C. Monitoring and/or Record keeping Requirements

1. The permittee shall perform daily checks, when the emissions unit is in operation, for any visible fugitive particulate emissions from the egress points (i.e., building windows, doors, roof monitors, etc.) serving this emissions unit. The presence or absence of any visible emissions shall be noted in an operations log. If visible emissions are observed, the permittee shall also note the following in the operations log:
 - a. The location and color of the emissions;
 - b. Whether the emissions are representative of normal operations;
 - c. If the emissions are not representative of normal operations, the cause of the abnormal emissions;
 - d. The total duration of any visible emission incident; and
 - e. Any corrective actions taken to minimize or eliminate the visible emissions.

If visible emissions are present, a visible emission incident has occurred. The observer does not have to document the exact start and end times for the visible emission incident under item (d) above or continue the daily check until the incident has ended. The observer may indicate that the visible emission incident was continuous during the observation period (or, if known, continuous during the operation of the emissions unit). With respect to the documentation of corrective actions, the observer may indicate that no corrective actions were taken if the visible emissions were representative of normal operations, or specify the minor corrective actions that were taken to ensure that the emissions unit continued to operate under normal conditions, or specify the corrective actions that were taken to eliminate abnormal visible emissions.

2. The permittee shall maintain the following information for this emissions unit:
 - a. The MSDS sheets for each liquid organic material employed; and

Emissions Unit ID: P902

- b. Documentation as to whether or not each material is a photochemically reactive material.

D. Reporting Requirements

1. The permittee shall submit semiannual written reports that (a) identify all days during which any visible fugitive particulate emissions were observed from the from the egress points (i.e., building windows, doors, roof monitors, etc.) serving this emissions unit, and (b) describe any corrective actions taken to minimize or eliminate the visible particulate and/or visible fugitive particulate emissions. These reports shall be submitted to the Director (the appropriate Ohio EPA District Office or local air agency) by January 31 and July 31 of each year and shall cover the previous 6-month period.
2. The permittee shall notify the Director (the appropriate Ohio EPA District Office or local air agency) in writing if a "photochemically reactive material" (as defined in OAC 3745-21-05(C)(5)) is employed in the emissions unit. The notification shall be sent to the Director (the appropriate Ohio EPA District Office or local air agency) within 45 days after such an occurrence.

E. Testing Requirements

1. Compliance with the emission limitation(s) in Section A.I. of these terms and conditions shall be determined in accordance with the following method(s):
 - a. Emission Limitation:

2.0 pound/hour of PE

Applicable Compliance Method:

Multiply the PE factor of 9.25 e-04 pound(s) of PE per pound of rubber (Draft AP-42 Section 4.12 - Table 4.12-4) by the maximum hourly production rate.
 - b. Emission Limitation:

8.76 tons/year of PE

Applicable Compliance Method:

To calculate the ton per year limit, multiply the maximum hourly emission limit times 8760 hours per year, then divide by 2000.

c. Emission Limitation:

1.0 pound/hour VOC

Applicable Compliance Method:

Multiply the VOC emissions factor of 4.44 e-04 pound(s) of VOC emissions per pound of rubber (Draft AP-42 Section 4.12 - Table 4.12-4) by the maximum hourly production rate.

d. Emission Limitation:

4.38 tons/year of VOC

Applicable Compliance Method:

To calculate the ton per year limit, multiply the maximum hourly emission limit times 8760 hours per year, then divide by 2000.

e. Emission Limitation:

20% opacity, as a three-minute average, for the fugitive emissions
VE shall not exceed 20% opacity as a three-minute average, except as provided by rule.

Applicable Compliance Method:

Compliance shall be demonstrated based upon VE evaluations performed in accordance with the methods and procedures specified in 40 CFR Part 60, Appendix A, Method 9 and OAC rule 3745-17-03(B)(3)

f. Emission Limitation:

There shall be no VEs to the ambient air from the operation of this emissions unit.

Blair Rubber Co
PTI Application: 16-02125
Issue

Facility ID: 1652070030

Emissions Unit ID: P902

Applicable Compliance Method:

Compliance shall be demonstrated based upon VE evaluations performed in accordance with the methods and procedures specified in 40 CFR Part 60, Appendix A, Method 22 and OAC rule 3745-17-03(B)(4)

F. Miscellaneous Requirements

None

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P903 - 60-inch Mill no. 1	OAC rule 3745-31-05(A)(3)	1.0 pound/hour and 4.38 tons/year of particulate emission (PE)
		1.0 pound/hour and 4.38 tons/year of volatile organic compounds (VOC)
	OAC rule 3745-17-07(B)	20% opacity, as a 3-minute average, for the fugitive emissions
	OAC rule 3745-17-08	There shall be no visible emissions to the ambient air from the operation of this emissions unit.
	OAC rule 3745-17-11(B)	See A.2.a below.
	OAC rule 3745-21-07(G)(2)	See B.1 below.

2. Additional Terms and Conditions

- 2.a The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).

B. Operational Restrictions

1. The permittee shall not employ any photochemically reactive materials, as defined in OAC rule 3745-21-01(C)(5), in this emissions unit.

C. Monitoring and/or Record keeping Requirements

1. The permittee shall perform daily checks, when the emissions unit is in operation, for any visible fugitive particulate emissions from the egress points (i.e., building windows, doors, roof monitors, etc.) serving this emissions unit. The presence or absence of any visible emissions shall be noted in an operations log. If visible emissions are observed, the permittee shall also note the following in the operations log:
 - a. The location and color of the emissions;
 - b. Whether the emissions are representative of normal operations;
 - c. If the emissions are not representative of normal operations, the cause of the abnormal emissions;
 - d. The total duration of any visible emission incident; and
 - e. Any corrective actions taken to minimize or eliminate the visible emissions.

If visible emissions are present, a visible emission incident has occurred. The observer does not have to document the exact start and end times for the visible emission incident under item (d) above or continue the daily check until the incident has ended. The observer may indicate that the visible emission incident was continuous during the observation period (or, if known, continuous during the operation of the emissions unit). With respect to the documentation of corrective actions, the observer may indicate that no corrective actions were taken if the visible emissions were representative of normal operations, or specify the minor corrective actions that were taken to ensure that the emissions unit continued to operate under normal conditions, or specify the corrective actions that were taken to eliminate abnormal visible emissions.

2. The permittee shall maintain the following information for this emissions unit:
 - a. The MSDS sheets for each liquid organic material employed; and

- b. Documentation as to whether or not each material is a photochemically reactive material.

D. Reporting Requirements

1. The permittee shall submit semiannual written reports that (a) identify all days during which any visible fugitive particulate emissions were observed from the from the egress points (i.e., building windows, doors, roof monitors, etc.) serving this emissions unit, and (b) describe any corrective actions taken to minimize or eliminate the visible particulate and/or visible fugitive particulate emissions. These reports shall be submitted to the Director (the appropriate Ohio EPA District Office or local air agency) by January 31 and July 31 of each year and shall cover the previous 6-month period.
2. The permittee shall notify the Director (the appropriate Ohio EPA District Office or local air agency) in writing if a "photochemically reactive material" (as defined in OAC 3745-21-05(C)(5)) is employed in the emissions unit. The notification shall be sent to the Director (the appropriate Ohio EPA District Office or local air agency) within 45 days after such an occurrence.

E. Testing Requirements

1. Compliance with the emission limitation(s) in Section A.I. of these terms and conditions shall be determined in accordance with the following method(s):
 - a. Emission Limitation:

1.0 pound/hour of PE

Applicable Compliance Method:

Multiply the PE factor of 9.25 e-04 pound(s) of PE per pound of rubber (Draft AP-42 Section 4.12 - Table 4.12-4) by the maximum hourly production rate.
 - b. Emission Limitation:

4.38 tons/year of PE

Applicable Compliance Method:

To calculate the ton per year limit, multiply the maximum hourly emission limit

Emissions Unit ID: P903

times 8760 hours per year, then divide by 2000.

c. Emission Limitation:

1.0 pound/hour VOC

Applicable Compliance Method:

Multiply the VOC emissions factor of 4.44 e-04 pound(s) of VOC emissions per pound of rubber (Draft AP-42 Section 4.12 - Table 4.12-4) by the maximum hourly production rate.

d. Emission Limitation:

4.38 tons/year of VOC

Applicable Compliance Method:

To calculate the ton per year limit, multiply the maximum hourly emission limit times 8760 hours per year, then divide by 2000.

e. Emission Limitation:

20% opacity, as a three-minute average, for the fugitive emissions
VE shall not exceed 20% opacity as a three-minute average, except as provided by rule.

Applicable Compliance Method:

Compliance shall be demonstrated based upon VE evaluations performed in accordance with the methods and procedures specified in 40 CFR Part 60, Appendix A, Method 9 and OAC rule 3745-17-03(B)(3)

f. Emission Limitation:

There shall be no VEs to the ambient air from the operation of this emissions unit.

Applicable Compliance Method:

Compliance shall be demonstrated based upon VE evaluations performed in accordance with the methods and procedures specified in 40 CFR Part 60, Appendix A, Method 22 and OAC rule 3745-17-03(B)(4)

F. Miscellaneous Requirements

None

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P904 - New 60-inch Mill no.1	OAC rule 3745-31-05(A)(3)	1.0 pound/hour and 4.38 tons/year of particulate emission (PE)
	OAC rule 3745-17-07(B)	1.0 pound/hour and 4.38 tons/year of volatile organic compounds (VOC)
	OAC rule 3745-17-08	20% opacity, as a 3-minute average, for the fugitive emissions
	OAC rule 3745-17-11(B)	There shall be no visible emissions to the ambient air from the operation of this emissions unit.
	OAC rule 3745-21-07(G)(2)	See A.2.a below. See B.1 below.

2. Additional Terms and Conditions

- 2.a The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).

B. Operational Restrictions

1. The permittee shall not employ any photochemically reactive materials, as defined in OAC rule 3745-21-01(C)(5), in this emissions unit.

C. Monitoring and/or Record keeping Requirements

1. The permittee shall perform daily checks, when the emissions unit is in operation, for any visible fugitive particulate emissions from the egress points (i.e., building windows, doors, roof monitors, etc.) serving this emissions unit. The presence or absence of any visible emissions shall be noted in an operations log. If visible emissions are observed, the permittee shall also note the following in the operations log:
 - a. The location and color of the emissions;
 - b. Whether the emissions are representative of normal operations;
 - c. If the emissions are not representative of normal operations, the cause of the abnormal emissions;
 - d. The total duration of any visible emission incident; and
 - e. Any corrective actions taken to minimize or eliminate the visible emissions.

If visible emissions are present, a visible emission incident has occurred. The observer does not have to document the exact start and end times for the visible emission incident under item (d) above or continue the daily check until the incident has ended. The observer may indicate that the visible emission incident was continuous during the observation period (or, if known, continuous during the operation of the emissions unit). With respect to the documentation of corrective actions, the observer may indicate that no corrective actions were taken if the visible emissions were representative of normal operations, or specify the minor corrective actions that were taken to ensure that the emissions unit continued to operate under normal conditions, or specify the corrective actions that were taken to eliminate abnormal visible emissions.

2. The permittee shall maintain the following information for this emissions unit:
 - a. The MSDS sheets for each liquid organic material employed; and

Emissions Unit ID: P904

- b. Documentation as to whether or not each material is a photochemically reactive material.

D. Reporting Requirements

1. The permittee shall submit semiannual written reports that (a) identify all days during which any visible fugitive particulate emissions were observed from the from the egress points (i.e., building windows, doors, roof monitors, etc.) serving this emissions unit, and (b) describe any corrective actions taken to minimize or eliminate the visible particulate and/or visible fugitive particulate emissions. These reports shall be submitted to the Director (the appropriate Ohio EPA District Office or local air agency) by January 31 and July 31 of each year and shall cover the previous 6-month period.
2. The permittee shall notify the Director (the appropriate Ohio EPA District Office or local air agency) in writing if a "photochemically reactive material" (as defined in OAC 3745-21-05(C)(5)) is employed in the emissions unit. The notification shall be sent to the Director (the appropriate Ohio EPA District Office or local air agency) within 45 days after such an occurrence.

E. Testing Requirements

1. Compliance with the emission limitation(s) in Section A.I. of these terms and conditions shall be determined in accordance with the following method(s):
 - a. Emission Limitation:

1.0 pound/hour of PE

Applicable Compliance Method:

Multiply the PE factor of 9.25 e-04 pound(s) of PE per pound of rubber (Draft AP-42 Section 4.12 - Table 4.12-4) by the maximum hourly production rate.
 - b. Emission Limitation:

4.38 tons/year of PE

Applicable Compliance Method:

To calculate the ton per year limit, multiply the maximum hourly emission limit times 8760 hours per year, then divide by 2000.

c. Emission Limitation:

1.0 pound/hour VOC

Applicable Compliance Method:

Multiply the VOC emissions factor of 4.44 e-04 pound(s) of VOC emissions per pound of rubber (Draft AP-42 Section 4.12 - Table 4.12-4) by the maximum hourly production rate.

d. Emission Limitation:

4.38 tons/year of VOC

Applicable Compliance Method:

To calculate the ton per year limit, multiply the maximum hourly emission limit times 8760 hours per year, then divide by 2000.

e. Emission Limitation:

20% opacity, as a three-minute average, for the fugitive emissions
VE shall not exceed 20% opacity as a three-minute average, except as provided by rule.

Applicable Compliance Method:

Compliance shall be demonstrated based upon VE evaluations performed in accordance with the methods and procedures specified in 40 CFR Part 60, Appendix A, Method 9 and OAC rule 3745-17-03(B)(3)

f. Emission Limitation:

There shall be no VEs to the ambient air from the operation of this emissions unit.

Blair Rubber Co
PTI Application: 16-02125
Issue

Facility ID: 1652070030

Emissions Unit ID: P904

Applicable Compliance Method:

Compliance shall be demonstrated based upon VE evaluations performed in accordance with the methods and procedures specified in 40 CFR Part 60, Appendix A, Method 22 and OAC rule 3745-17-03(B)(4)

F. Miscellaneous Requirements

None

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P905 - New 60-inch Mill no. 2	OAC rule 3745-31-05(A)(3)	1.0 pound/hour and 4.38 tons/year of particulate emission (PE)
	OAC rule 3745-17-07(B)	1.0 pound/hour and 4.38 tons/year of volatile organic compounds (VOC)
	OAC rule 3745-17-08	20% opacity, as a 3-minute average, for the fugitive emissions
	OAC rule 3745-17-11(B)	There shall be no visible emissions to the ambient air from the operation of this emissions unit.
	OAC rule 3745-21-07(G)(2)	See A.2.a below. See B.1 below.

2. Additional Terms and Conditions

- 2.a The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).

B. Operational Restrictions

1. The permittee shall not employ any photochemically reactive materials, as defined in OAC rule 3745-21-01(C)(5), in this emissions unit.

C. Monitoring and/or Record keeping Requirements

1. The permittee shall perform daily checks, when the emissions unit is in operation, for any visible fugitive particulate emissions from the egress points (i.e., building windows, doors, roof monitors, etc.) serving this emissions unit. The presence or absence of any visible emissions shall be noted in an operations log. If visible emissions are observed, the permittee shall also note the following in the operations log:
 - a. The location and color of the emissions;
 - b. Whether the emissions are representative of normal operations;
 - c. If the emissions are not representative of normal operations, the cause of the abnormal emissions;
 - d. The total duration of any visible emission incident; and
 - e. Any corrective actions taken to minimize or eliminate the visible emissions.

If visible emissions are present, a visible emission incident has occurred. The observer does not have to document the exact start and end times for the visible emission incident under item (d) above or continue the daily check until the incident has ended. The observer may indicate that the visible emission incident was continuous during the observation period (or, if known, continuous during the operation of the emissions unit). With respect to the documentation of corrective actions, the observer may indicate that no corrective actions were taken if the visible emissions were representative of normal operations, or specify the minor corrective actions that were taken to ensure that the emissions unit continued to operate under normal conditions, or specify the corrective actions that were taken to eliminate abnormal visible emissions.

2. The permittee shall maintain the following information for this emissions unit:
 - a. The MSDS sheets for each liquid organic material employed; and

- b. Documentation as to whether or not each material is a photochemically reactive material.

D. Reporting Requirements

1. The permittee shall submit semiannual written reports that (a) identify all days during which any visible fugitive particulate emissions were observed from the from the egress points (i.e., building windows, doors, roof monitors, etc.) serving this emissions unit, and (b) describe any corrective actions taken to minimize or eliminate the visible particulate and/or visible fugitive particulate emissions. These reports shall be submitted to the Director (the appropriate Ohio EPA District Office or local air agency) by January 31 and July 31 of each year and shall cover the previous 6-month period.
2. The permittee shall notify the Director (the appropriate Ohio EPA District Office or local air agency) in writing if a "photochemically reactive material" (as defined in OAC 3745-21-05(C)(5)) is employed in the emissions unit. The notification shall be sent to the Director (the appropriate Ohio EPA District Office or local air agency) within 45 days after such an occurrence.

E. Testing Requirements

1. Compliance with the emission limitation(s) in Section A.I. of these terms and conditions shall be determined in accordance with the following method(s):
 - a. Emission Limitation:

1.0 pound/hour of PE

Applicable Compliance Method:

Multiply the PE factor of 9.25 e-04 pound(s) of PE per pound of rubber (Draft AP-42 Section 4.12 - Table 4.12-4) by the maximum hourly production rate.
 - b. Emission Limitation:

4.38 tons/year of PE

Applicable Compliance Method:

To calculate the ton per year limit, multiply the maximum hourly emission limit

Emissions Unit ID: P905

times 8760 hours per year, then divide by 2000.

c. Emission Limitation:

1.0 pound/hour VOC

Applicable Compliance Method:

Multiply the VOC emissions factor of 4.44 e-04 pound(s) of VOC emissions per pound of rubber (Draft AP-42 Section 4.12 - Table 4.12-4) by the maximum hourly production rate.

d. Emission Limitation:

4.38 tons/year of VOC

Applicable Compliance Method:

To calculate the ton per year limit, multiply the maximum hourly emission limit times 8760 hours per year, then divide by 2000.

e. Emission Limitation:

20% opacity, as a three-minute average, for the fugitive emissions
VE shall not exceed 20% opacity as a three-minute average, except as provided by rule.

Applicable Compliance Method:

Compliance shall be demonstrated based upon VE evaluations performed in accordance with the methods and procedures specified in 40 CFR Part 60, Appendix A, Method 9 and OAC rule 3745-17-03(B)(3)

f. Emission Limitation:

There shall be no VEs to the ambient air from the operation of this emissions unit.

Applicable Compliance Method:

Compliance shall be demonstrated based upon VE evaluations performed in accordance with the methods and procedures specified in 40 CFR Part 60, Appendix A, Method 22 and OAC rule 3745-17-03(B)(4)

F. Miscellaneous Requirements

None

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P906 - 84-inch Mill	OAC rule 3745-31-05(A)(3)	1.0 pound/hour and 4.38 tons/year of particulate emission (PE)
		1.0 pound/hour and 4.38 tons/year of volatile organic compounds (VOC)
	OAC rule 3745-17-07(B)	20% opacity, as a 3-minute average, for the fugitive emissions
	OAC rule 3745-17-08	There shall be no visible emissions to the ambient air from the operation of this emissions unit.
	OAC rule 3745-17-11(B)	See A.2.a below.
	OAC rule 3745-21-07(G)(2)	See B.1 below.

2. Additional Terms and Conditions

- 2.a The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).

B. Operational Restrictions

1. The permittee shall not employ any photochemically reactive materials, as defined in OAC rule 3745-21-01(C)(5), in this emissions unit.

C. Monitoring and/or Record keeping Requirements

1. The permittee shall perform daily checks, when the emissions unit is in operation, for any visible fugitive particulate emissions from the egress points (i.e., building windows, doors, roof monitors, etc.) serving this emissions unit. The presence or absence of any visible emissions shall be noted in an operations log. If visible emissions are observed, the permittee shall also note the following in the operations log:
 - a. The location and color of the emissions;
 - b. Whether the emissions are representative of normal operations;
 - c. If the emissions are not representative of normal operations, the cause of the abnormal emissions;
 - d. The total duration of any visible emission incident; and
 - e. Any corrective actions taken to minimize or eliminate the visible emissions.

If visible emissions are present, a visible emission incident has occurred. The observer does not have to document the exact start and end times for the visible emission incident under item (d) above or continue the daily check until the incident has ended. The observer may indicate that the visible emission incident was continuous during the observation period (or, if known, continuous during the operation of the emissions unit). With respect to the documentation of corrective actions, the observer may indicate that no corrective actions were taken if the visible emissions were representative of normal operations, or specify the minor corrective actions that were taken to ensure that the emissions unit continued to operate under normal conditions, or specify the corrective actions that were taken to eliminate abnormal visible emissions.

2. The permittee shall maintain the following information for this emissions unit:
 - a. The MSDS sheets for each liquid organic material employed; and

Emissions Unit ID: P906

- b. Documentation as to whether or not each material is a photochemically reactive material.

D. Reporting Requirements

1. The permittee shall submit semiannual written reports that (a) identify all days during which any visible fugitive particulate emissions were observed from the from the egress points (i.e., building windows, doors, roof monitors, etc.) serving this emissions unit, and (b) describe any corrective actions taken to minimize or eliminate the visible particulate and/or visible fugitive particulate emissions. These reports shall be submitted to the Director (the appropriate Ohio EPA District Office or local air agency) by January 31 and July 31 of each year and shall cover the previous 6-month period.
2. The permittee shall notify the Director (the appropriate Ohio EPA District Office or local air agency) in writing if a "photochemically reactive material" (as defined in OAC 3745-21-05(C)(5)) is employed in the emissions unit. The notification shall be sent to the Director (the appropriate Ohio EPA District Office or local air agency) within 45 days after such an occurrence.

E. Testing Requirements

1. Compliance with the emission limitation(s) in Section A.I. of these terms and conditions shall be determined in accordance with the following method(s):
 - a. Emission Limitation:

1.0 pound/hour of PE

Applicable Compliance Method:

Multiply the PE factor of 9.25 e-04 pound(s) of PE per pound of rubber (Draft AP-42 Section 4.12 - Table 4.12-4) by the maximum hourly production rate.
 - b. Emission Limitation:

4.38 tons/year of PE

Applicable Compliance Method:

To calculate the ton per year limit, multiply the maximum hourly emission limit times 8760 hours per year, then divide by 2000.

c. Emission Limitation:

1.0 pound/hour VOC

Applicable Compliance Method:

Multiply the VOC emissions factor of 4.44 e-04 pound(s) of VOC emissions per pound of rubber (Draft AP-42 Section 4.12 - Table 4.12-4) by the maximum hourly production rate.

d. Emission Limitation:

4.38 tons/year of VOC

Applicable Compliance Method:

To calculate the ton per year limit, multiply the maximum hourly emission limit times 8760 hours per year, then divide by 2000.

e. Emission Limitation:

20% opacity, as a three-minute average, for the fugitive emissions
VE shall not exceed 20% opacity as a three-minute average, except as provided by rule.

Applicable Compliance Method:

Compliance shall be demonstrated based upon VE evaluations performed in accordance with the methods and procedures specified in 40 CFR Part 60, Appendix A, Method 9 and OAC rule 3745-17-03(B)(3)

f. Emission Limitation:

There shall be no VEs to the ambient air from the operation of this emissions unit.

Blair Rubber Co
PTI Application: 16-02125
Issue

Facility ID: 1652070030

Emissions Unit ID: P906

Applicable Compliance Method:

Compliance shall be demonstrated based upon VE evaluations performed in accordance with the methods and procedures specified in 40 CFR Part 60, Appendix A, Method 22 and OAC rule 3745-17-03(B)(4)

F. Miscellaneous Requirements

None

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)**A. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P907 - 66-inch Calender	OAC rule 3745-31-05(A)(3)	1.0 pound/hour and 4.38 tons/year of particulate emission (PE)
	OAC rule 3745-17-07(B)	1.0 pound/hour and 4.38 tons/year of volatile organic compounds (VOC)
	OAC rule 3745-17-08	20% opacity, as a 3-minute average, for the fugitive emissions
	OAC rule 3745-17-11(B)	There shall be no visible emissions to the ambient air from the operation of this emissions unit.
	OAC rule 3745-21-07(G)(2)	See A.2.a below. See B.1 below.

2. Additional Terms and Conditions

- 2.a The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).

B. Operational Restrictions

1. The permittee shall not employ any photochemically reactive materials, as defined in OAC rule 3745-21-01(C)(5), in this emissions unit.

C. Monitoring and/or Record keeping Requirements

1. The permittee shall perform daily checks, when the emissions unit is in operation, for any visible fugitive particulate emissions from the egress points (i.e., building windows, doors, roof monitors, etc.) serving this emissions unit. The presence or absence of any visible emissions shall be noted in an operations log. If visible emissions are observed, the permittee shall also note the following in the operations log:
 - a. The location and color of the emissions;
 - b. Whether the emissions are representative of normal operations;
 - c. If the emissions are not representative of normal operations, the cause of the abnormal emissions;
 - d. The total duration of any visible emission incident; and
 - e. Any corrective actions taken to minimize or eliminate the visible emissions.

If visible emissions are present, a visible emission incident has occurred. The observer does not have to document the exact start and end times for the visible emission incident under item (d) above or continue the daily check until the incident has ended. The observer may indicate that the visible emission incident was continuous during the observation period (or, if known, continuous during the operation of the emissions unit). With respect to the documentation of corrective actions, the observer may indicate that no corrective actions were taken if the visible emissions were representative of normal operations, or specify the minor corrective actions that were taken to ensure that the emissions unit continued to operate under normal conditions, or specify the corrective actions that were taken to eliminate abnormal visible emissions.

2. The permittee shall maintain the following information for this emissions unit:
 - a. The MSDS sheets for each liquid organic material employed; and

- b. Documentation as to whether or not each material is a photochemically reactive material.

D. Reporting Requirements

1. The permittee shall submit semiannual written reports that (a) identify all days during which any visible fugitive particulate emissions were observed from the from the egress points (i.e., building windows, doors, roof monitors, etc.) serving this emissions unit, and (b) describe any corrective actions taken to minimize or eliminate the visible particulate and/or visible fugitive particulate emissions. These reports shall be submitted to the Director (the appropriate Ohio EPA District Office or local air agency) by January 31 and July 31 of each year and shall cover the previous 6-month period.
2. The permittee shall notify the Director (the appropriate Ohio EPA District Office or local air agency) in writing if a "photochemically reactive material" (as defined in OAC 3745-21-05(C)(5)) is employed in the emissions unit. The notification shall be sent to the Director (the appropriate Ohio EPA District Office or local air agency) within 45 days after such an occurrence.

E. Testing Requirements

1. Compliance with the emission limitation(s) in Section A.I. of these terms and conditions shall be determined in accordance with the following method(s):
 - a. Emission Limitation:

1.0 pound/hour of PE

Applicable Compliance Method:

Multiply the PE factor of 9.25 e-04 pound(s) of PE per pound of rubber (Draft AP-42 Section 4.12 - Table 4.12-4) by the maximum hourly production rate.
 - b. Emission Limitation:

4.38 tons/year of PE

Applicable Compliance Method:

To calculate the ton per year limit, multiply the maximum hourly emission limit

Emissions Unit ID: P907

times 8760 hours per year, then divide by 2000.

c. Emission Limitation:

1.0 pound/hour VOC

Applicable Compliance Method:

Multiply the VOC emissions factor of 4.44 e-04 pound(s) of VOC emissions per pound of rubber (Draft AP-42 Section 4.12 - Table 4.12-4) by the maximum hourly production rate.

d. Emission Limitation:

4.38 tons/year of VOC

Applicable Compliance Method:

To calculate the ton per year limit, multiply the maximum hourly emission limit times 8760 hours per year, then divide by 2000.

e. Emission Limitation:

20% opacity, as a three-minute average, for the fugitive emissions
VE shall not exceed 20% opacity as a three-minute average, except as provided by rule.

Applicable Compliance Method:

Compliance shall be demonstrated based upon VE evaluations performed in accordance with the methods and procedures specified in 40 CFR Part 60, Appendix A, Method 9 and OAC rule 3745-17-03(B)(3)

f. Emission Limitation:

There shall be no VEs to the ambient air from the operation of this emissions unit.

Applicable Compliance Method:

Compliance shall be demonstrated based upon VE evaluations performed in accordance with the methods and procedures specified in 40 CFR Part 60, Appendix A, Method 22 and OAC rule 3745-17-03(B)(4)

F. Miscellaneous Requirements

None

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P908 - New 66-inch Calender	OAC rule 3745-31-05(A)(3)	1.0 pound/hour and 4.38 tons/year of particulate emission (PE)
	OAC rule 3745-17-07(B)	1.0 pound/hour and 4.38 tons/year of volatile organic compounds (VOC)
	OAC rule 3745-17-08	20% opacity, as a 3-minute average, for the fugitive emissions
	OAC rule 3745-17-11(B)	There shall be no visible emissions to the ambient air from the operation of this emissions unit.
	OAC rule 3745-21-07(G)(2)	See A.2.a below. See B.1 below.

2. Additional Terms and Conditions

- 2.a The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).

B. Operational Restrictions

1. The permittee shall not employ any photochemically reactive materials, as defined in OAC rule 3745-21-01(C)(5), in this emissions unit.

C. Monitoring and/or Record keeping Requirements

1. The permittee shall perform daily checks, when the emissions unit is in operation, for any visible fugitive particulate emissions from the egress points (i.e., building windows, doors, roof monitors, etc.) serving this emissions unit. The presence or absence of any visible emissions shall be noted in an operations log. If visible emissions are observed, the permittee shall also note the following in the operations log:
 - a. The location and color of the emissions;
 - b. Whether the emissions are representative of normal operations;
 - c. If the emissions are not representative of normal operations, the cause of the abnormal emissions;
 - d. The total duration of any visible emission incident; and
 - e. Any corrective actions taken to minimize or eliminate the visible emissions.

If visible emissions are present, a visible emission incident has occurred. The observer does not have to document the exact start and end times for the visible emission incident under item (d) above or continue the daily check until the incident has ended. The observer may indicate that the visible emission incident was continuous during the observation period (or, if known, continuous during the operation of the emissions unit). With respect to the documentation of corrective actions, the observer may indicate that no corrective actions were taken if the visible emissions were representative of normal operations, or specify the minor corrective actions that were taken to ensure that the emissions unit continued to operate under normal conditions, or specify the corrective actions that were taken to eliminate abnormal visible emissions.

2. The permittee shall maintain the following information for this emissions unit:
 - a. The MSDS sheets for each liquid organic material employed; and

- b. Documentation as to whether or not each material is a photochemically reactive material.

D. Reporting Requirements

1. The permittee shall submit semiannual written reports that (a) identify all days during which any visible fugitive particulate emissions were observed from the from the egress points (i.e., building windows, doors, roof monitors, etc.) serving this emissions unit, and (b) describe any corrective actions taken to minimize or eliminate the visible particulate and/or visible fugitive particulate emissions. These reports shall be submitted to the Director (the appropriate Ohio EPA District Office or local air agency) by January 31 and July 31 of each year and shall cover the previous 6-month period.
2. The permittee shall notify the Director (the appropriate Ohio EPA District Office or local air agency) in writing if a "photochemically reactive material" (as defined in OAC 3745-21-05(C)(5)) is employed in the emissions unit. The notification shall be sent to the Director (the appropriate Ohio EPA District Office or local air agency) within 45 days after such an occurrence.

E. Testing Requirements

1. Compliance with the emission limitation(s) in Section A.I. of these terms and conditions shall be determined in accordance with the following method(s):
 - a. Emission Limitation:

1.0 pound/hour of PE

Applicable Compliance Method:

Multiply the PE factor of 9.25 e-04 pound(s) of PE per pound of rubber (Draft AP-42 Section 4.12 - Table 4.12-4) by the maximum hourly production rate.
 - b. Emission Limitation:

4.38 tons/year of PE

Applicable Compliance Method:

To calculate the ton per year limit, multiply the maximum hourly emission limit

times 8760 hours per year, then divide by 2000.

c. Emission Limitation:

1.0 pound/hour VOC

Applicable Compliance Method:

Multiply the VOC emissions factor of 4.44 e-04 pound(s) of VOC emissions per pound of rubber (Draft AP-42 Section 4.12 - Table 4.12-4) by the maximum hourly production rate.

d. Emission Limitation:

4.38 tons/year of VOC

Applicable Compliance Method:

To calculate the ton per year limit, multiply the maximum hourly emission limit times 8760 hours per year, then divide by 2000.

e. Emission Limitation:

20% opacity, as a three-minute average, for the fugitive emissions
VE shall not exceed 20% opacity as a three-minute average, except as provided by rule.

Applicable Compliance Method:

Compliance shall be demonstrated based upon VE evaluations performed in accordance with the methods and procedures specified in 40 CFR Part 60, Appendix A, Method 9 and OAC rule 3745-17-03(B)(3)

f. Emission Limitation:

There shall be no VEs to the ambient air from the operation of this emissions unit.

Blair Rubber Co
PTI Application: 16-02125
Issue

Facility ID: 1652070030

Emissions Unit ID: P908

Applicable Compliance Method:

Compliance shall be demonstrated based upon VE evaluations performed in accordance with the methods and procedures specified in 40 CFR Part 60, Appendix A, Method 22 and OAC rule 3745-17-03(B)(4)

F. Miscellaneous Requirements

None

Emissions Unit ID: P908

SIC CODE 3069 SCC CODE 3-08-999-99 EMISSIONS UNIT ID P901

EMISSIONS UNIT DESCRIPTION Banbury Mixer

DATE INSTALLED December 2005

EMISSIONS: (Click on bubble help for Air Quality Descriptions)

Pollutants	Air Quality Description	Actual Emissions Rate		PTI Allowable	
		Short Term Rate	Tons Per Year	Short Term Rate	Tons Per Year
Particulate Matter		1.02	4.46	2.0	8.76
PM ₁₀					
Sulfur Dioxide					
Organic Compounds		0.49	2.14	1.0	4.38
Nitrogen Oxides					
Carbon Monoxide					
Lead					
Other: Air Toxics					

APPLICABLE FEDERAL RULES:

NSPS? **no** NESHAP? **no** PSD? **no** OFFSET POLICY? **no**

WHAT IS THE BAT DETERMINATION, AND WHAT IS THE BASIS FOR THE DETERMINATION?

Compliance with the terms and conditions of this permit.

IS THIS SOURCE SUBJECT TO THE AIR TOXICS POLICY? no
 OPTIONAL: WHAT IS THE CAPITAL COST OF CONTROL EQUIPMENT? \$ _____

TOXIC AIR CONTAMINANTS

Ohio EPA's air toxics policy applies to contaminants for which the American Conference of Governmental Industrial Hygienists (ACGIH) has a listed threshold limit value.

AIR TOXICS MODELING PERFORMED*? _____ YES x NO

IDENTIFY THE AIR CONTAMINANTS: _____

Blair Rubber Co
 PTI Application: 16-02425
 Issued: 11/17/2005

Facility ID: 1652070030

Emissions Unit ID: P908

SIC CODE 3069 SCC CODE 3-08-999-99 EMISSIONS UNIT ID P905
 EMISSIONS UNIT DESCRIPTION New 60-inch Mill no. 2
 DATE INSTALLED December 2005

EMISSIONS: (Click on bubble help for Air Quality Descriptions)

Pollutants	Air Quality Description	Actual Emissions Rate		PTI Allowable	
		Short Term Rate	Tons Per Year	Short Term Rate	Tons Per Year
Particulate Matter		0.56	2.43	1.0	4.38
PM ₁₀					
Sulfur Dioxide					
Organic Compounds		0.27	1.17	1.0	4.38
Nitrogen Oxides					
Carbon Monoxide					
Lead					
Other: Air Toxics					

APPLICABLE FEDERAL RULES:

NSPS? **no** NESHAP? **no** PSD? **no** OFFSET POLICY? **no**

WHAT IS THE BAT DETERMINATION, AND WHAT IS THE BASIS FOR THE DETERMINATION?

Compliance with the terms and conditions of this permit.

IS THIS SOURCE SUBJECT TO THE AIR TOXICS POLICY? no
 OPTIONAL: WHAT IS THE CAPITAL COST OF CONTROL EQUIPMENT? \$ _____

TOXIC AIR CONTAMINANTS

Ohio EPA's air toxics policy applies to contaminants for which the American Conference of Governmental Industrial Hygienists (ACGIH) has a listed threshold limit value.

AIR TOXICS MODELING PERFORMED*? _____ YES x NO

IDENTIFY THE AIR CONTAMINANTS: _____

