



John R. Kasich, Governor  
 Mary Taylor, Lt. Governor  
 Craig W. Butler, Director

Certified Mail

5/11/2016

No	TOXIC REVIEW
No	SYNTHETIC MINOR TO AVOID MAJOR NSR
No	CEMS
No	MACT/GACT
No	NSPS
No	NESHAPS
No	NETTING
No	MODELING SUBMITTED
No	SYNTHETIC MINOR TO AVOID TITLE V
No	FEDERALLY ENFORCABLE PTIO (FEPTIO)
No	SYNTHETIC MINOR TO AVOID MAJOR GHG

John Leugers  
 UniFirst Corporation - Franklin  
 265 Industrial Dr  
 Franklin, OH 45005

RE: FINALAIR POLLUTION PERMIT-TO-INSTALL AND OPERATE

Facility ID: 1483040189  
 Permit Number: P0119442  
 Permit Type: Initial Installation  
 County: Warren

Dear Permit Holder:

Enclosed please find a final Ohio Environmental Protection Agency (EPA) Air Pollution Permit-to-Install and Operate (PTIO) which will allow you to install, modify, and/or operate the described emissions unit(s) in the manner indicated in the permit. Because this permit contains conditions and restrictions, please read it very carefully. In this letter you will find the information on the following topics:

- **How to appeal this permit**
- **How to save money, reduce pollution and reduce energy consumption**
- **How to give us feedback on your permitting experience**
- **How to get an electronic copy of your permit**
- **What should you do if you notice a spill or environmental emergency?**

**How to appeal this permit**

The issuance of this PTIO is a final action of the Director and may be appealed to the Environmental Review Appeals Commission pursuant to Section 3745.04 of the Ohio Revised Code. The appeal must be in writing and set forth the action complained of and the grounds upon which the appeal is based. The appeal must be filed with the Commission within thirty (30) days after notice of the Director's action. The appeal must be accompanied by a filing fee of \$70.00, made payable to "Ohio Treasurer Josh Mandel," which the Commission, in its discretion, may reduce if by affidavit you demonstrate that payment of the full amount of the fee would cause extreme hardship. Notice of the filing of the appeal shall be filed with the Director within three (3) days of filing with the Commission. Ohio EPA requests that a copy of the appeal be served upon the Ohio Attorney General's Office, Environmental Enforcement Section. An appeal may be filed with the Environmental Review Appeals Commission at the following address:

Environmental Review Appeals Commission  
 77 South High Street, 17th Floor  
 Columbus, OH 43215

## **How to save money, reduce pollution and reduce energy consumption**

The Ohio EPA is encouraging companies to investigate pollution prevention and energy conservation. Not only will this reduce pollution and energy consumption, but it can also save you money. If you would like to learn ways you can save money while protecting the environment, please contact our Office of Compliance Assistance and Pollution Prevention at (614) 644-3469. Additionally, all or a portion of the capital expenditures related to installing air pollution control equipment under this permit may be eligible for financing and State tax exemptions through the Ohio Air Quality Development Authority (OAQDA) under Ohio Revised Code Section 3706. For more information, see the OAQDA website: [www.ohioairquality.org/clean\\_air](http://www.ohioairquality.org/clean_air)

## **How to give us feedback on your permitting experience**

Please complete a survey at [www.epa.ohio.gov/survey.aspx](http://www.epa.ohio.gov/survey.aspx) and give us feedback on your permitting experience. We value your opinion.

## **How to get an electronic copy of your permit**

This permit can be accessed electronically via the eBusiness Center: Air Services in Microsoft Word format or in Adobe PDF on the Division of Air Pollution Control (DAPC) Web page, [www.epa.ohio.gov/dapc](http://www.epa.ohio.gov/dapc) by clicking the "Search for Permits" link under the Permitting topic on the Programs tab.

## **What should you do if you notice a spill or environmental emergency?**

Any spill or environmental emergency which may endanger human health or the environment should be reported to the Emergency Response 24-HOUR EMERGENCY SPILL HOTLINE toll-free at (800) 282-9378. Report non-emergency complaints to the appropriate district office or local air agency.

If you have any questions regarding your permit, please contact Southwest Ohio Air Quality Agency at (513)946-7777 or the Office of Compliance Assistance and Pollution Prevention at (614) 644-3469.

Sincerely,



Michael E. Hopkins, P.E.  
Assistant Chief, Permitting Section, DAPC

Cc: SWOQA



**FINAL**

**Division of Air Pollution Control  
Permit-to-Install and Operate  
for  
UniFirst Corporation - Franklin**

Facility ID:	1483040189
Permit Number:	P0119442
Permit Type:	Initial Installation
Issued:	5/11/2016
Effective:	5/11/2016
Expiration:	5/11/2026





**Division of Air Pollution Control**  
**Permit-to-Install and Operate**  
for  
UniFirst Corporation - Franklin

**Table of Contents**

Authorization .....	1
A. Standard Terms and Conditions .....	4
1. What does this permit-to-install and operate ("PTIO") allow me to do?.....	5
2. Who is responsible for complying with this permit? .....	5
3. What records must I keep under this permit? .....	5
4. What are my permit fees and when do I pay them?.....	5
5. When does my PTIO expire, and when do I need to submit my renewal application? .....	5
6. What happens to this permit if my project is delayed or I do not install or modify my source? .....	6
7. What reports must I submit under this permit? .....	6
8. If I am required to obtain a Title V operating permit in the future, what happens to the operating provisions and PER obligations under this permit? .....	6
9. What are my obligations when I perform scheduled maintenance on air pollution control equipment? ...	6
10. Do I have to report malfunctions of emissions units or air pollution control equipment? If so, how must I report? .....	7
11. Can Ohio EPA or my local air agency inspect the facility where the emission unit(s) is/are located? .....	7
12. What happens if one or more emissions units operated under this permit is/are shut down permanently? .....	7
13. Can I transfer this permit to a new owner or operator?.....	7
14. Does compliance with this permit constitute compliance with OAC rule 3745-15-07, "air pollution nuisance"? .....	8
15. What happens if a portion of this permit is determined to be invalid? .....	8
B. Facility-Wide Terms and Conditions.....	9
C. Emissions Unit Terms and Conditions .....	14
1. P001, DRYER 1 .....	15
2. P002, DRYER 2 .....	19
3. P003, DRYER 3 .....	23
4. P004, DRYER 4 .....	27
5. P005, WASHER 1 .....	31
6. P901, WASTEWATER TREATMENT .....	34
7. Emissions Unit Group -Washers, post 2006: P006,P007,P008,P009,P010,P011,P012, .....	37





**Final Permit-to-Install and Operate**  
UniFirst Corporation - Franklin  
**Permit Number:** P0119442  
**Facility ID:** 1483040189  
**Effective Date:** 5/11/2016

## Authorization

Facility ID: 1483040189  
Application Number(s): A0053837  
Permit Number: P0119442  
Permit Description: Initial PTIO application for existing industrial laundry facility including washers, dryers, and a wastewater pretreatment process, requesting facility-wide Federally enforceable limits on VOC and HAP emissions.  
Permit Type: Initial Installation  
Permit Fee: \$3,800.00  
Issue Date: 5/11/2016  
Effective Date: 5/11/2016  
Expiration Date: 5/11/2026  
Permit Evaluation Report (PER) Annual Date: Oct 1 - Sept 30, Due Nov 15

This document constitutes issuance to:

UniFirst Corporation - Franklin  
265 Industrial Dr  
Franklin, OH 45005

of a Permit-to-Install and Operate for the emissions unit(s) identified on the following page.

Ohio Environmental Protection Agency (EPA) District Office or local air agency responsible for processing and administering your permit:

Southwest Ohio Air Quality Agency  
250 William Howard Taft Rd.  
Cincinnati, OH 45219  
(513)946-7777

The above named entity is hereby granted this Permit-to-Install and Operate for the air contaminant source(s) (emissions unit(s)) listed in this section pursuant to Chapter 3745-31 of the Ohio Administrative Code. Issuance of this permit does not constitute expressed or implied approval or agreement that, if constructed or modified in accordance with the plans included in the application, the described emissions unit(s) will operate in compliance with applicable State and federal laws and regulations.

This permit is granted subject to the conditions attached hereto.

Ohio Environmental Protection Agency

  
Craig W. Butler  
Director



## Authorization (continued)

Permit Number: P0119442

Permit Description: Initial PTIO application for existing industrial laundry facility including washers, dryers, and a wastewater pretreatment process, requesting facility-wide Federally enforceable limits on VOC and HAP emissions.

Permits for the following Emissions Unit(s) or groups of Emissions Units are in this document as indicated below:

- Emissions Unit ID: P001**  
 Company Equipment ID: DRYER 1  
 Superseded Permit Number:  
 General Permit Category and Type: Not Applicable
- Emissions Unit ID: P002**  
 Company Equipment ID: DRYER 2  
 Superseded Permit Number:  
 General Permit Category and Type: Not Applicable
- Emissions Unit ID: P003**  
 Company Equipment ID: DRYER 3  
 Superseded Permit Number:  
 General Permit Category and Type: Not Applicable
- Emissions Unit ID: P004**  
 Company Equipment ID: DRYER 4  
 Superseded Permit Number:  
 General Permit Category and Type: Not Applicable
- Emissions Unit ID: P005**  
 Company Equipment ID: WASHER 1  
 Superseded Permit Number:  
 General Permit Category and Type: Not Applicable
- Emissions Unit ID: P901**  
 Company Equipment ID: WASTEWATER TREATMENT  
 Superseded Permit Number:  
 General Permit Category and Type: Not Applicable

**Group Name: Washers, post 2006**

<b>Emissions Unit ID:</b>	<b>P006</b>
Company Equipment ID:	WASHER 2
Superseded Permit Number:	
General Permit Category and Type:	Not Applicable
<b>Emissions Unit ID:</b>	<b>P007</b>
Company Equipment ID:	WASHER 3
Superseded Permit Number:	
General Permit Category and Type:	Not Applicable
<b>Emissions Unit ID:</b>	<b>P008</b>
Company Equipment ID:	WASHER 4
Superseded Permit Number:	
General Permit Category and Type:	Not Applicable



**Final Permit-to-Install and Operate**  
 UniFirst Corporation - Franklin  
**Permit Number:** P0119442  
**Facility ID:** 1483040189  
**Effective Date:** 5/11/2016

<b>Emissions Unit ID:</b>	<b>P009</b>
Company Equipment ID:	WASHER 5
Superseded Permit Number:	
General Permit Category andType:	Not Applicable
<b>Emissions Unit ID:</b>	<b>P010</b>
Company Equipment ID:	WASHER 6
Superseded Permit Number:	
General Permit Category andType:	Not Applicable
<b>Emissions Unit ID:</b>	<b>P011</b>
Company Equipment ID:	WASHER 7
Superseded Permit Number:	
General Permit Category andType:	Not Applicable
<b>Emissions Unit ID:</b>	<b>P012</b>
Company Equipment ID:	WASHER 8
Superseded Permit Number:	
General Permit Category andType:	Not Applicable



**Final Permit-to-Install and Operate**  
UniFirst Corporation - Franklin  
**Permit Number:** P0119442  
**Facility ID:** 1483040189  
**Effective Date:** 5/11/2016

## **A. Standard Terms and Conditions**

**1. What does this permit-to-install and operate ("PTIO") allow me to do?**

This permit allows you to install and operate the emissions unit(s) identified in this PTIO. You must install and operate the unit(s) in accordance with the application you submitted and all the terms and conditions contained in this PTIO, including emission limits and those terms that ensure compliance with the emission limits (for example, operating, recordkeeping and monitoring requirements).

**2. Who is responsible for complying with this permit?**

The person identified on the "Authorization" page, above, is responsible for complying with this permit until the permit is revoked, terminated, or transferred. "Person" means a person, firm, corporation, association, or partnership. The words "you," "your," or "permittee" refer to the "person" identified on the "Authorization" page above.

The permit applies only to the emissions unit(s) identified in the permit. If you install or modify any other equipment that requires an air permit, you must apply for an additional PTIO(s) for these sources.

**3. What records must I keep under this permit?**

You must keep all records required by this permit, including monitoring data, test results, strip-chart recordings, calibration data, maintenance records, and any other record required by this permit for five years from the date the record was created. You can keep these records electronically, provided they can be made available to Ohio EPA during an inspection at the facility. Failure to make requested records available to Ohio EPA upon request is a violation of this permit requirement.

**4. What are my permit fees and when do I pay them?**

There are two fees associated with permitted air contaminant sources in Ohio:

PTIO fee. This one-time fee is based on a fee schedule in accordance with Ohio Revised Code (ORC) section 3745.11, or based on a time and materials charge for permit application review and permit processing if required by the Director.

You will be sent an invoice for this fee after you receive this PTIO and payment is due within 30 days of the invoice date. You are required to pay the fee for this PTIO even if you do not install or modify your operations as authorized by this permit.

Annual emissions fee. Ohio EPA will assess a separate fee based on the total annual emissions from your facility. You self-report your emissions in accordance with Ohio Administrative Code (OAC) Chapter 3745-78. This fee assessed is based on a fee schedule in ORC section 3745.11 and funds Ohio EPA's permit compliance oversight activities. For facilities that are permitted as synthetic minor sources, the fee schedule is adjusted annually for inflation. Ohio EPA will notify you when it is time to report your emissions and to pay your annual emission fees.

**5. When does my PTIO expire, and when do I need to submit my renewal application?**

This permit expires on the date identified at the beginning of this permit document (see "Authorization" page above) and you must submit a renewal application to renew the permit. Ohio EPA will send a renewal notice to you approximately six months prior to the expiration date of this permit. However, it is

very important that you submit a complete renewal permit application (postmarked prior to expiration of this permit) even if you do not receive the renewal notice.

If a complete renewal application is submitted before the expiration date, Ohio EPA considers this a timely application for purposes of ORC section 119.06, and you are authorized to continue operating the emissions unit(s) covered by this permit beyond the expiration date of this permit until final action is taken by Ohio EPA on the renewal application.

**6. What happens to this permit if my project is delayed or I do not install or modify my source?**

This PTIO expires 18 months after the issue date identified on the "Authorization" page above unless otherwise specified if you have not (1) started constructing the new or modified emission sources identified in this permit, or (2) entered into a binding contract to undertake such construction. This deadline can be extended by up to 12 months, provided you apply to Ohio EPA for this extension within a reasonable time before the 18-month period has ended and you can show good cause for any such extension.

**7. What reports must I submit under this permit?**

An annual permit evaluation report (PER) is required in addition to any malfunction reporting required by OAC rule 3745-15-06 or other specific rule-based reporting requirement identified in this permit. Your PER due date is identified in the Authorization section of this permit.

**8. If I am required to obtain a Title V operating permit in the future, what happens to the operating provisions and PER obligations under this permit?**

If you are required to obtain a Title V permit under OAC Chapter 3745-77 in the future, the permit-to-operate portion of this permit will be superseded by the issued Title V permit. From the effective date of the Title V permit forward, this PTIO will effectively become a PTI (permit-to-install) in accordance with OAC rule 3745-31-02(B). The following terms and conditions of this permit will no longer be applicable after issuance of the Title V permit: Section B, Term 1.b) and Section C, for each emissions unit, Term a)(2).

The PER requirements in this permit remain effective until the date the Title V permit is issued and is effective, and cease to apply after the effective date of the Title V permit. The final PER obligation will cover operations up to the effective date of the Title V permit and must be submitted on or before the submission deadline identified in this permit on the last day prior to the effective date of the Title V permit.

**9. What are my obligations when I perform scheduled maintenance on air pollution control equipment?**

You must perform scheduled maintenance of air pollution control equipment in accordance with OAC rule 3745-15-06(A). If scheduled maintenance requires shutting down or bypassing any air pollution control equipment, you must also shut down the emissions unit(s) served by the air pollution control equipment during maintenance, unless the conditions of OAC rule 3745-15-06(A)(3) are met. Any emissions that exceed permitted amount(s) under this permit (unless specifically exempted by rule) must be reported as deviations in the annual permit evaluation report (PER), including nonexempt excess emissions that occur during approved scheduled maintenance.

**10. Do I have to report malfunctions of emissions units or air pollution control equipment? If so, how must I report?**

If you have a reportable malfunction of any emissions unit(s) or any associated air pollution control system, you must report this to the [DO/LAA] in accordance with OAC rule 3745-15-06(B). Malfunctions that must be reported are those that result in emissions that exceed permitted emission levels. It is your responsibility to evaluate control equipment breakdowns and operational upsets to determine if a reportable malfunction has occurred.

If you have a malfunction, but determine that it is not a reportable malfunction under OAC rule 3745-15-06(B), it is recommended that you maintain records associated with control equipment breakdown or process upsets. Although it is not a requirement of this permit, Ohio EPA recommends that you maintain records for non-reportable malfunctions.

**11. Can Ohio EPA or my local air agency inspect the facility where the emission unit(s) is/are located?**

Yes. Under Ohio law, the Director or his authorized representative may inspect the facility, conduct tests, examine records or reports to determine compliance with air pollution laws and regulations and the terms and conditions of this permit. You must provide, within a reasonable time, any information Ohio EPA requests either verbally or in writing.

**12. What happens if one or more emissions units operated under this permit is/are shut down permanently?**

Ohio EPA can terminate the permit terms associated with any permanently shut down emissions unit. "Shut down" means the emissions unit has been physically removed from service or has been altered in such a way that it can no longer operate without a subsequent "modification" or "installation" as defined in OAC Chapter 3745-31.

You should notify Ohio EPA of any emissions unit that is permanently shut down by submitting a certification that identifies the date on which the emissions unit was permanently shut down. The certification must be submitted by an authorized official from the facility. You cannot continue to operate an emission unit once the certification has been submitted to Ohio EPA by the authorized official.

You must comply with all recordkeeping and reporting for any permanently shut down emissions unit in accordance with the provisions of the permit, regulations or laws that were enforceable during the period of operation, such as the requirement to submit a PER, air fee emission report, or malfunction report. You must also keep all records relating to any permanently shutdown emissions unit, generated while the emissions unit was in operation, for at least five years from the date the record was generated.

Again, you cannot resume operation of any emissions unit certified by the authorized official as being permanently shut down without first applying for and obtaining a permit pursuant to OAC Chapter 3745-31.

**13. Can I transfer this permit to a new owner or operator?**

You can transfer this permit to a new owner or operator. If you transfer the permit, you must follow the procedures in OAC Chapter 3745-31, including notifying Ohio EPA or the local air agency of the

change in ownership or operator. Any transferee of this permit must assume the responsibilities of the transferor permit holder.

**14. Does compliance with this permit constitute compliance with OAC rule 3745-15-07, "air pollution nuisance"?**

This permit and OAC rule 3745-15-07 prohibit operation of the air contaminant source(s) regulated under this permit in a manner that causes a nuisance. Ohio EPA can require additional controls or modification of the requirements of this permit through enforcement orders or judicial enforcement action if, upon investigation, Ohio EPA determines existing operations are causing a nuisance.

**15. What happens if a portion of this permit is determined to be invalid?**

If a portion of this permit is determined to be invalid, the remainder of the terms and conditions remain valid and enforceable. The exception is where the enforceability of terms and conditions are dependent on the term or condition that was declared invalid.



**Final Permit-to-Install and Operate**  
UniFirst Corporation - Franklin  
**Permit Number:** P0119442  
**Facility ID:** 1483040189  
**Effective Date:** 5/11/2016

## **B. Facility-Wide Terms and Conditions**

1. This permit document constitutes a permit-to-install issued in accordance with ORC 3704.03(F) and a permit-to-operate issued in accordance with ORC 3704.03(G).

a) For the purpose of a permit-to-install document, the facility-wide terms and conditions identified below are federally enforceable with the exception of those listed below which are enforceable under state law only.

(1) None.

b) For the purpose of a permit-to-operate document, the facility-wide terms and conditions identified below are enforceable under state law only with the exception of those listed below which are federally enforceable.

(1) B.2.a)(1), B.2.b), B.3., B.4.a), B.5.a), and B.6.a)(1).

2. Applicable Emissions Limitations and/or Control Requirements

a) The specific operation(s), property, and/or equipment that constitute the facility along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures are identified below. Facility-wide emissions shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
(1)	OAC rule 3745-31-05(F) (Voluntary restriction to remain a true minor)	See B.2.b) and B.3. below.

b) Additional Terms and Conditions

The total facility-wide volatile organic compound (VOC) and combined hazardous air pollutant (HAP) emissions from emissions units P001 (Dryer 1 (700 pound Braun)), P002 (Dryer 2 (450 pound Challenge)), P003 (Dryer 3 (130 pound Milnor/ADC)), P004 (Dryer 4 (110 pound Cissell)), P005 (Washer 1 (600 pound Braun)), P006 (Washer 2 (650 pound Braun)), P007 (Washer 3 (650 pound Braun)), P008 (Washer 4 (450 pound Braun)), P009 (Washer 5 (650 pound Braun)), P010 (Washer 6 (125 pound Sailstar)), P011 (Washer 7 (250 pound Braun)), P012 (Washer 8 (50 pound Milnor)), P901 (Wastewater Treatment Operations), other de minimus air contaminant sources, as defined in OAC rule 3745-15-05, and other air contaminant sources exempt from the requirement to obtain a permit-to-install pursuant to OAC rule 3745-31-03 installed subsequent to the issuance of this permit, combined, shall not exceed 9.9 tons per rolling, 12-month period.

3. Operational Restrictions

a) The permittee shall not launder more than 2,100,000 pounds of soiled shop towels (SST) per rolling, 12-month period in this facility.

- (1) The permittee shall not allow shop towels laundered in this facility that contain, or are saturated with VOC-containing free liquid.
    - a. A shop towel is a piece of cotton fabric or other material that is used to clean equipment, parts, objects, or surfaces of general soil, grease, or oil and may contain small amounts of solvents containing volatile organic compounds (VOCs).
  - (2) The permittee shall process SST in this facility separately from other textile goods.
  - (3) The permittee shall only use non-VOC detergents and water to launder all the materials processed in this facility.
- b) The permittee shall not allow print towels or furniture towels to be laundered in this facility. Print towels or furniture towels that are sent to this facility shall be bagged and stored outside in a covered area prior to being sent off-site for laundering at a non-UniFirst facility.
- (1) Print towel - shall mean a piece of fabric or other material used in the process of cleaning printing or graphic arts equipment, including but not limited to printing presses.
  - (2) Furniture towel - shall mean a piece of fabric or other material used in the process of striping or finishing wood furniture.

4. Monitoring and/or Recordkeeping Requirements

- a) The permittee shall collect and record the following information each month facility-wide:
  - (1) the total amount of SST laundered, in pounds;
  - (2) the rolling, 12-month summation of total SST laundered, in pounds;
  - (3) the monthly VOC emissions generated by SST laundering, in tons, and shall be calculated as follows:

$$E_{MVOC} = [(M_{SST})(EF_w + EF_D + EF_T)/(1,000)] / 2,000 \text{ per ton}$$

Where,

$E_{MVOC}$  = the monthly VOC emissions facility-wide, in tons;

$M_{SST}$  = the total amount of SST laundered in the facility, in pounds;

$EF_w$  = VOC emission factor for washing SST, 1.02 pound VOC emissions per 1,000 pounds SST laundered, as determined based upon December 15, 2012 performance stack test conducted at UniFirst, Portland, Maine facility in accordance with a Testing Order issued on April 27, 2012 by US EPA;

$EF_D$  = VOC emission factor for drying SST, 5.66 pounds VOC emissions per 1,000 pounds SST laundered, as determined based upon December 15, 2012 performance stack test conducted at UniFirst, Portland, Maine facility in accordance with a Testing Order issued on April 27, 2012 by US EPA; and

$EF_T$  = VOC emission factor for wastewater treatment system, 2.12 pounds VOC emissions per 1,000 pounds SST laundered, as determined based upon December 15, 2012 performance stack test conducted at UniFirst, Portland, Maine facility in accordance with a Testing Order issued on April 27, 2012 by US EPA. The wastewater treatment system includes emissions from the EQ/DAF/sludge tanks, shaker screen, and settling tanks.

- (4) the rolling, 12-month period VOC emissions, in tons.

## 5. Reporting Requirements

- a) The permittee shall submit an annual Permit Evaluation Report (PER) to the Southwest Ohio Air Quality Agency (SWOAQA). The PER must be submitted by the due date identified in the Authorization section of this permit. The permit evaluation report shall cover a reporting period of no more than twelve months for each air contaminant source identified in this permit. The annual PER shall identify the following:
  - (1) all deviations (excursions) of the following emission limitations, operational restrictions and/or control device operating parameter limitations that restrict the potential to emit (PTE) of any regulated air pollutant and have been detected by the monitoring, record keeping and/or testing requirements in this permit:
    - a. The permittee shall not launder more than 2,100,000 pounds of soiled shop towels (SST) per rolling, 12-month period in this facility.
    - b. Facility-wide VOC/combined HAP emissions shall not exceed 9.9 tons per rolling, 12-month period.
  - (2) the probable cause of each deviation (excursion);
  - (3) any corrective actions that were taken to remedy the deviations (excursions) or prevent future deviations (excursions); and
  - (4) the magnitude and duration of each deviation (excursion).
- b) The reports required by this permit may be submitted through the Ohio EPA's eBusiness Center: Air Services online web portal; or they may be mailed as a hard copy to the Southwest Ohio Air Quality Agency (SWOAQA).

## 6. Testing Requirements

- a) Compliance with the Emissions Limitations and/or Control Requirements specified in B.2. of these terms and conditions shall be determined in accordance with the following methods:
  - (1) Emission Limitation:

The facility-wide VOC / combined HAP emissions from laundering operations shall not exceed 9.9 tons per rolling, 12-month period.



**Final Permit-to-Install and Operate**  
UniFirst Corporation - Franklin  
**Permit Number:** P0119442  
**Facility ID:** 1483040189  
**Effective Date:** 5/11/2016

Applicable Compliance Method:

- (2) Compliance shall be demonstrated through the record keeping requirements specified in B.4.a) above.



**Final Permit-to-Install and Operate**  
UniFirst Corporation - Franklin  
**Permit Number:** P0119442  
**Facility ID:** 1483040189  
**Effective Date:** 5/11/2016

## **C. Emissions Unit Terms and Conditions**

**1. P001, DRYER 1**

**Operations, Property and/or Equipment Description:**

DRYER 1 (700 POUND BRAUN)

- a) This permit document constitutes a permit-to-install issued in accordance with ORC 3704.03(F) and a permit-to-operate issued in accordance with ORC 3704.03(G).
  - (1) For the purpose of a permit-to-install document, the emissions unit terms and conditions identified below are federally enforceable with the exception of those listed below which are enforceable under state law only.
    - a. g)(1).
  - (2) For the purpose of a permit-to-operate document, the emissions unit terms and conditions identified below are enforceable under state law only with the exception of those listed below which are federally enforceable.
    - a. b)(1)c.
- b) Applicable Emissions Limitations and/or Control Requirements
  - (1) The specific operation(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures are identified below. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC rule 3745-31-05(A)(3) June 30, 2008	VOC emissions shall not exceed 5.66 pound per 1,000 pounds of soiled shop towels (SST) laundered.  PE/PM10 emissions shall be controlled by the work practices described in c)(1) below.  See b)(2)a.
b.	OAC rule 3745-31-05(A)(3)(a)(ii) June 30, 2008	See b)(2)b., and b)(2)c. below.
c.	OAC rule 3745-31-05(F) (Voluntary Restriction to Remain True Minor)	See Section B.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
d.	OAC rule 3745-17-07(A)	The visible particulate emissions from any stack associated with the emissions unit shall not exceed twenty percent (20%) opacity, as a 6-minute average.
e.	OAC rule 3745-17-11	Particulate emissions from each emissions unit shall not exceed 3.07 pounds per hour.

(2) Additional Terms and Conditions

- a. The Best Available Technology (BAT) emission limit applies until U.S. EPA approves Ohio Administrative Code (OAC) paragraph 3745-31-05 (A)(3)(a)(ii) (the less than 10 tons per year BAT exemption) into the Ohio State Implementation Plan (SIP).
- b. The requirements apply once U.S. EPA approves OAC paragraph 3745-31-05 (A)(3)(a)(ii) (the less than 10 tons per year BAT exemption) as part of the Ohio SIP.
- c. The Best Available Technology (BAT) requirements under OAC rule 3745-31-05 (A)(3) do not apply to the particulate emissions since the potential to emit is less than 10 tons per year.

c) Operational Restrictions

- (1) The permittee shall operate a lint filter for each emission unit to control particulate emissions whenever the emissions unit is in operation. The lint filter for each emissions unit shall be cleaned frequently and shall be maintained in accordance with the manufacturer's recommendations, instructions, and/or operating manual(s), with any modifications deemed necessary by the permittee.

d) Monitoring and/or Recordkeeping Requirements

- (1) The permittee shall maintain documentation of the manufacturer's recommendations, instructions, or operating manuals for the dryer and its lint filter, along with documentation of any modifications deemed necessary by the permittee. These documents shall be maintained at the facility and shall be made available to the Southwest Ohio Air Quality Agency (SWOQA) upon request.
- (2) The permittee shall conduct periodic inspections and annual comprehensive inspection of the lint filter while the emissions unit is shut down. The permittee shall perform any needed maintenance and repair for each emissions unit including lint filter to ensure that it is operated in accordance with the manufacturer's recommendations.
- (3) The permittee shall document each inspection (periodic and annual) of each lint filter and shall maintain the following information:



- a. the date of the inspection;
- b. a description of each/any problem identified and the date it was corrected;
- c. a description of any maintenance and repairs performed; and
- d. the name of person who performed the inspection.

These records shall be maintained at the facility for not less than five years from the date the inspection and any necessary maintenance or repairs were completed and shall be made available to the Southwest Ohio Air Quality Agency (SWOAQA) upon request.

e) Reporting Requirements

- (1) The permittee shall submit an annual Permit Evaluation Report (PER) to the Southwest Ohio Air Quality Agency (SWOAQA). The PER must be submitted by the due date identified in the Authorization section of this permit. The permit evaluation report shall cover a reporting period of no more than twelve months for each air contaminant source identified in this permit.
- (2) The reports required by this permit may be submitted through the Ohio EPA's eBusiness Center: Air Services online web portal; or they may be mailed as a hard copy to the Southwest Ohio Air Quality Agency (SWOAQA).

f) Testing Requirements

- (1) Compliance with the Emissions Limitations and/or Control Requirements specified in section b) of these terms and conditions shall be determined in accordance with the following methods:

a. Emission Limitation:

VOC emissions shall not exceed 5.66 pounds per 1000 pounds of SST laundered.

Applicable Compliance Method:

The emission limitation was based upon a December 2012 performance stack test conducted at the UniFirst Portland, Maine facility in accordance with a Testing Order issued by US EPA.

If required, the following test method(s) shall be employed to demonstrate compliance with the allowable VOC emission rate(s): Method 18, Method 25 or Method 25A of 40 CFR Part 60, Appendix A, as appropriate. Alternative U.S. EPA approved test methods may be used with prior approval from the Ohio EPA.

b. Opacity Limitation:

The visible particulate emissions from any stack associated with the emissions unit shall not exceed twenty percent (20%) opacity, as a 6-minute average.



Applicable Compliance Method:

If required, compliance shall be demonstrated based upon visible emission observations performed in accordance with the methods and procedures specified in 40 CFR Part 60, Appendix A, Method 9 and the procedures specified in OAC rule 3745-17-03 (B)(1).

c. Emission Limitation:

Particulate emissions from this emissions unit shall not exceed 3.07 pounds per hour

Applicable Compliance Method:

The emission limitation was developed based upon OAC rule 3745-17-11 Table I requirements as follows:

$$E = 4.10(P)^{0.67}$$

Where,

E = Allowable emission rate, in pounds per hour; and

P = Process weight rate, 0.65 ton per hour, which is determined based upon facility information that a maximum of 1300 pounds per hour of material is dried for each emissions unit.

If required, compliance shall be determined by performing a stack test using USEPA Method 5 of 40 CFR Part 60, Appendix A.

g) Miscellaneous Requirements

- (1) Modeling to demonstrate compliance with, the "Toxic Air Contaminant Statute", ORC 3704.03(F)(4)(b), was not necessary because the emissions unit's maximum annual emissions for each toxic air contaminant, as defined in OAC rule 3745-114-01, will be less than 1.0 ton per year. OAC Chapter 3745-31 requires a permittee to apply for and obtain a new or modified PTIO prior to making a "modification" as defined by OAC rule 3745-31-01. The permittee is hereby advised that changes in the composition of the materials, or use of new materials, that would cause the emissions of any toxic air contaminant to increase to above 1.0 ton per year may require the permittee to apply for and obtain a new PTIO.

**2. P002, DRYER 2**

**Operations, Property and/or Equipment Description:**

DRYER 2 (450 POUND CHALLENGE)

- a) This permit document constitutes a permit-to-install issued in accordance with ORC 3704.03(F) and a permit-to-operate issued in accordance with ORC 3704.03(G).
  - (1) For the purpose of a permit-to-install document, the emissions unit terms and conditions identified below are federally enforceable with the exception of those listed below which are enforceable under state law only.
    - a. g)(1).
  - (2) For the purpose of a permit-to-operate document, the emissions unit terms and conditions identified below are enforceable under state law only with the exception of those listed below which are federally enforceable.
    - a. b)(1)b.
- b) Applicable Emissions Limitations and/or Control Requirements
  - (1) The specific operation(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures are identified below. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC rule 3745-31-05(A)(3)	VOC emissions shall not exceed 5.66 pounds per 1,000 pounds of soiled shop towels (SST) laundered and 9.9 TPY.  PE and PM10 emissions shall not exceed 2.58 lbs/hr and 11.3 TPY.  The requirements of this rule include compliance with the requirements of OAC rule 3745-31-05(F).  See c)(1) below.
b.	OAC rule 3745-31-05(F)  (Voluntary Restriction to Remain True Minor)	See Section B.
c.	OAC rule 3745-17-07(A)	The visible particulate emissions from any stack associated with the emissions unit shall not exceed twenty percent (20%)



	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
		opacity, as a 6-minute average.
d.	OAC rule 3745-17-11	Particulate emissions from each emissions unit shall not exceed 2.58 pounds per hour.

(2) Additional Terms and Conditions

a. None.

c) Operational Restrictions

(1) The permittee shall operate a lint filter for each emission unit to control particulate emissions whenever the emissions unit is in operation. The lint filter for each emissions unit shall be cleaned frequently and shall be maintained in accordance with the manufacturer's recommendations, instructions, and/or operating manual(s), with any modifications deemed necessary by the permittee.

d) Monitoring and/or Recordkeeping Requirements

(1) The permittee shall maintain documentation of the manufacturer's recommendations, instructions, or operating manuals for the dryer and its lint filter, along with documentation of any modifications deemed necessary by the permittee. These documents shall be maintained at the facility and shall be made available to the Southwest Ohio Air Quality Agency (SWOAQA) upon request.

(2) The permittee shall conduct periodic inspections and annual comprehensive inspection of the lint filter while the emissions unit is shut down. The permittee shall perform any needed maintenance and repair for each emissions unit including lint filter to ensure that it is operated in accordance with the manufacturer's recommendations.

(3) The permittee shall document each inspection (periodic and annual) of each lint filter and shall maintain the following information:

- a. the date of the inspection;
- b. a description of each/any problem identified and the date it was corrected;
- c. a description of any maintenance and repairs performed; and
- d. the name of person who performed the inspection.

These records shall be maintained at the facility for not less than five years from the date the inspection and any necessary maintenance or repairs were completed and shall be made available to the Southwest Ohio Air Quality Agency (SWOAQA).

e) Reporting Requirements

- (1) The permittee shall submit an annual Permit Evaluation Report (PER) to the Southwest Ohio Air Quality Agency (SWOAQA). The PER must be submitted by the due date identified in the Authorization section of this permit. The permit evaluation report shall cover a reporting period of no more than twelve months for each air contaminant source identified in this permit.
- (2) The reports required by this permit may be submitted through the Ohio EPA's eBusiness Center: Air Services online web portal; or they may be mailed as a hard copy to the Southwest Ohio Air Quality Agency (SWOAQA).

f) Testing Requirements

- (1) Compliance with the Emissions Limitations and/or Control Requirements specified in b) of these terms and conditions shall be determined in accordance with the following methods:

a. Emission Limitation:

VOC emissions shall not exceed 5.66 pounds per 1000 pounds of SST laundered and 9.9 TPY.

Applicable Compliance Method:

The emission limitation was based upon a December 2012 performance stack test conducted at the UniFirst Portland, Maine facility in accordance with a Testing Order issued by US EPA.

If required, the following test method(s) shall be employed to demonstrate compliance with the allowable VOC emission rate(s): Method 18, Method 25 or Method 25A of 40 CFR Part 60, Appendix A, as appropriate. Alternative U.S. EPA approved test methods may be used with prior approval from the Ohio EPA.

The TPY allowable is equivalent to the facility wide emission allowable in Section B.

b. Opacity Limitation:

The visible particulate emissions from any stack associated with the emissions unit shall not exceed twenty percent (20%) opacity, as a 6-minute average.

Applicable Compliance Method:

If required, compliance shall be demonstrated based upon visible emission observations performed in accordance with the methods and procedures specified in 40 CFR Part 60, Appendix A, Method 9 and the procedures specified in OAC rule 3745-17-03 (B)(1).

c. Emission Limitation:

Particulate emissions from this emissions unit shall not exceed 2.58 pounds per hour and 11.3 TPY.

Applicable Compliance Method:

The emission limitation was developed based upon OAC rule 3745-17-11 Table I requirements as follows:

$$E = 4.10(P)^{0.67}$$

Where,

E = Allowable emission rate, in pounds per hour; and

P = Process weight rate, 0.5 ton per hour, which is determined based upon facility information that a maximum of 1000 pounds per hour of material is dried for each emissions unit.

If required, compliance shall be determined by performing a stack test using USEPA Method 5 of 40 CFR Part 60, Appendix A.

The TPY allowable was calculated using the hourly allowable multiplied by 8760 hours per year divided by 2000 pounds per ton.

g) Miscellaneous Requirements

- (1) Modeling to demonstrate compliance with, the "Toxic Air Contaminant Statute", ORC 3704.03(F)(4)(b), was not necessary because the emissions unit's maximum annual emissions for each toxic air contaminant, as defined in OAC rule 3745-114-01, will be less than 1.0 ton per year. OAC Chapter 3745-31 requires a permittee to apply for and obtain a new or modified PTIO prior to making a "modification" as defined by OAC rule 3745-31-01. The permittee is hereby advised that changes in the composition of the materials, or use of new materials, that would cause the emissions of any toxic air contaminant to increase to above 1.0 ton per year may require the permittee to apply for and obtain a new PTIO.



**3. P003, DRYER 3**

**Operations, Property and/or Equipment Description:**

DRYER 3 (130 POUND MILNOR/ADC)

- a) This permit document constitutes a permit-to-install issued in accordance with ORC 3704.03(F) and a permit-to-operate issued in accordance with ORC 3704.03(G).
  - (1) For the purpose of a permit-to-install document, the emissions unit terms and conditions identified below are federally enforceable with the exception of those listed below which are enforceable under state law only.
    - a. g)(1).
  - (2) For the purpose of a permit-to-operate document, the emissions unit terms and conditions identified below are enforceable under state law only with the exception of those listed below which are federally enforceable.
    - a. b)(1)b.
- b) Applicable Emissions Limitations and/or Control Requirements
  - (1) The specific operation(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures are identified below. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC rule 3745-31-05(A)(3)	VOC emissions shall not exceed 5.66 pounds per 1,000 pounds of soiled shop towels (SST) laundered and 6.2 TPY.  PE and PM10 emissions shall not exceed 1.02 lbs/hr and 4.47 TPY.  The requirements of this rule include compliance with the requirements of OAC rule 3745-31-05(F). See c)(1) below.
b.	OAC rule 3745-31-05(F) (Voluntary Restriction to Remain True Minor)	See Section B.
c.	OAC rule 3745-17-07(A)	The visible particulate emissions from any stack associated with the emissions unit shall not exceed twenty percent (20%) opacity, as a 6-minute average.



	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
d.	OAC rule 3745-17-11	Particulate emissions from each emissions unit shall not exceed 1.02 pounds per hour.

(2) Additional Terms and Conditions

a. None.

c) Operational Restrictions

(1) The permittee shall operate a lint filter for each emission unit to control particulate emissions whenever the emissions unit is in operation. The lint filter for each emissions unit shall be cleaned frequently and shall be maintained in accordance with the manufacturer's recommendations, instructions, and/or operating manual(s), with any modifications deemed necessary by the permittee.

d) Monitoring and/or Recordkeeping Requirements

(1) The permittee shall maintain documentation of the manufacturer's recommendations, instructions, or operating manuals for the dryer and its lint filter, along with documentation of any modifications deemed necessary by the permittee. These documents shall be maintained at the facility and shall be made available to the Southwest Ohio Air Quality Agency (SWOAQA) upon request.

(2) The permittee shall conduct periodic inspections and annual comprehensive inspection of the lint filter while the emissions unit is shut down. The permittee shall perform any needed maintenance and repair for each emissions unit including lint filter to ensure that it is operated in accordance with the manufacturer's recommendations.

(3) The permittee shall document each inspection (periodic and annual) of each lint filter and shall maintain the following information:

- a. the date of the inspection;
- b. a description of each/any problem identified and the date it was corrected;
- c. a description of any maintenance and repairs performed; and
- d. the name of person who performed the inspection.

These records shall be maintained at the facility for not less than five years from the date the inspection and any necessary maintenance or repairs were completed and shall be made available to the Southwest Ohio Air Quality Agency (SWOAQA).

e) Reporting Requirements

(1) The permittee shall submit an annual Permit Evaluation Report (PER) to the Southwest Ohio Air Quality Agency (SWOAQA). The PER must be submitted by the due date

identified in the Authorization section of this permit. The permit evaluation report shall cover a reporting period of no more than twelve months for each air contaminant source identified in this permit.

- (2) The reports required by this permit may be submitted through the Ohio EPA's eBusiness Center: Air Services online web portal; or they may be mailed as a hard copy to the Southwest Ohio Air Quality Agency (SWOQA).

f) Testing Requirements

- (1) Compliance with the Emissions Limitations and/or Control Requirements specified in b) of these terms and conditions shall be determined in accordance with the following methods:

- a. Emission Limitation:

VOC emissions shall not exceed 5.66 pounds per 1000 pounds of SST laundered and 6.2 TPY.

Applicable Compliance Method:

The emission limitation was based upon a December 2012 performance stack test conducted at the UniFirst Portland, Maine facility in accordance with a Testing Order issued by US EPA.

If required, the following test method(s) shall be employed to demonstrate compliance with the allowable VOC emission rate(s): Method 18, Method 25 or Method 25A of 40 CFR Part 60, Appendix A, as appropriate. Alternative U.S. EPA approved test methods may be used with prior approval from the Ohio EPA.

The TPY allowable is calculated as the pounds VOC/1000 pounds of SST multiplied by the EAC stated capacity of 250 pounds SST per hour multiplied by 8760 hours per year and divided by 2000 pounds per ton.

- b. Opacity Limitation:

The visible particulate emissions from any stack associated with the emissions unit shall not exceed twenty percent (20%) opacity, as a 6-minute average.

Applicable Compliance Method:

If required, compliance shall be demonstrated based upon visible emission observations performed in accordance with the methods and procedures specified in 40 CFR Part 60, Appendix A, Method 9 and the procedures specified in OAC rule 3745-17-03(B)(1).

- c. Emission Limitation:

Particulate emissions from this emissions unit shall not exceed 1.02 pounds per hour and 4.47 TPY.

Applicable Compliance Method:

The emission limitation was developed based upon OAC rule 3745-17-11 Table I requirements as follows:

$$E = 4.10(P)^{0.67}$$

Where,

E = Allowable emission rate, in pounds per hour; and

P = Process weight rate, 0.125 ton per hour, which is determined based upon facility information that a maximum of 250 pounds per hour of material is dried for each emissions unit.

If required, compliance shall be determined by performing a stack test using USEPA Method 5 of 40 CFR Part 60, Appendix A.

The TPY allowable was calculated using the hourly allowable multiplied by 8760 hours per year divided by 2000 pounds per ton.

g) Miscellaneous Requirements

- (1) Modeling to demonstrate compliance with, the "Toxic Air Contaminant Statute", ORC 3704.03(F)(4)(b), was not necessary because the emissions unit's maximum annual emissions for each toxic air contaminant, as defined in OAC rule 3745-114-01, will be less than 1.0 ton per year. OAC Chapter 3745-31 requires a permittee to apply for and obtain a new or modified PTIO prior to making a "modification" as defined by OAC rule 3745-31-01. The permittee is hereby advised that changes in the composition of the materials, or use of new materials, that would cause the emissions of any toxic air contaminant to increase to above 1.0 ton per year may require the permittee to apply for and obtain a new PTIO.

**4. P004, DRYER 4**

**Operations, Property and/or Equipment Description:**

DRYER 4 (110 POUND CISSELL)

- a) This permit document constitutes a permit-to-install issued in accordance with ORC 3704.03(F) and a permit-to-operate issued in accordance with ORC 3704.03(G).
  - (1) For the purpose of a permit-to-install document, the emissions unit terms and conditions identified below are federally enforceable with the exception of those listed below which are enforceable under state law only.
    - a. g)(1).
  - (2) For the purpose of a permit-to-operate document, the emissions unit terms and conditions identified below are enforceable under state law only with the exception of those listed below which are federally enforceable.
    - a. b)(1)b.
- b) Applicable Emissions Limitations and/or Control Requirements
  - (1) The specific operation(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures are identified below. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC rule 3745-31-05(A)(3)	VOC emissions shall not exceed 5.66 pounds per 1,000 pounds of soiled shop towels (SST) laundered and 6.2 TPY.  PE and PM10 emissions shall not exceed 1.02 lbs/hr and 4.47 TPY.  The requirements of this rule include compliance with the requirements of OAC rule 3745-31-05 (F). See c)(1) below.
b.	OAC rule 3745-31-05(F) (Voluntary Restriction to Remain True Minor)	See Section B.
c.	OAC rule 3745-17-07(A)	The visible particulate emissions from any stack associated with the emissions unit shall not exceed twenty percent (20%) opacity, as a 6-minute average.



	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
d.	OAC rule 3745-17-11	Particulate emissions from each emissions unit shall not exceed 1.02 pounds per hour.

(2) Additional Terms and Conditions

a. None.

c) Operational Restrictions

(1) The permittee shall operate a lint filter for each emission unit to control particulate emissions whenever the emissions unit is in operation. The lint filter for each emissions unit shall be cleaned frequently and shall be maintained in accordance with the manufacturer's recommendations, instructions, and/or operating manual(s), with any modifications deemed necessary by the permittee.

d) Monitoring and/or Recordkeeping Requirements

(1) The permittee shall maintain documentation of the manufacturer's recommendations, instructions, or operating manuals for the dryer and its lint filter, along with documentation of any modifications deemed necessary by the permittee. These documents shall be maintained at the facility and shall be made available to the Southwest Ohio Air Quality Agency (SWOAQA) upon request.

(2) The permittee shall conduct periodic inspections and annual comprehensive inspection of the lint filter while the emissions unit is shut down. The permittee shall perform any needed maintenance and repair for each emissions unit including lint filter to ensure that it is operated in accordance with the manufacturer's recommendations.

(3) The permittee shall document each inspection (periodic and annual) of each lint filter and shall maintain the following information:

- a. the date of the inspection;
- b. a description of each/any problem identified and the date it was corrected;
- c. a description of any maintenance and repairs performed; and
- d. the name of person who performed the inspection.

These records shall be maintained at the facility for not less than five years from the date the inspection and any necessary maintenance or repairs were completed and shall be made available to the Southwest Ohio Air Quality Agency (SWOAQA).

e) Reporting Requirements

(1) The permittee shall submit an annual Permit Evaluation Report (PER) to the Southwest Ohio Air Quality Agency (SWOAQA). The PER must be submitted by the due date

identified in the Authorization section of this permit. The permit evaluation report shall cover a reporting period of no more than twelve months for each air contaminant source identified in this permit.

- (2) The reports required by this permit may be submitted through the Ohio EPA's eBusiness Center: Air Services online web portal; or they may be mailed as a hard copy to the Southwest Ohio Air Quality Agency (SWOQA).

f) Testing Requirements

- (1) Compliance with the Emissions Limitations and/or Control Requirements specified in b) of these terms and conditions shall be determined in accordance with the following methods:

- a. Emission Limitation:

VOC emissions shall not exceed 5.66 pounds per 1000 pounds of SST laundered and 6.2 TPY.

Applicable Compliance Method:

The emission limitation was based upon a December 2012 performance stack test conducted at the UniFirst Portland, Maine facility in accordance with a Testing Order issued by US EPA.

If required, the following test method(s) shall be employed to demonstrate compliance with the allowable VOC emission rate(s): Method 18, Method 25 or Method 25A of 40 CFR Part 60, Appendix A, as appropriate. Alternative U.S. EPA approved test methods may be used with prior approval from the Ohio EPA.

The TPY allowable was calculated using the 5.66 pounds per 1000 pounds of SST laundered allowable multiplied by 250 pounds per hour capacity and 8760 hours per year divided by 2000 pounds per ton.

- b. Opacity Limitation:

The visible particulate emissions from any stack associated with the emissions unit shall not exceed twenty percent (20%) opacity, as a 6-minute average.

Applicable Compliance Method:

If required, compliance shall be demonstrated based upon visible emission observations performed in accordance with the methods and procedures specified in 40 CFR Part 60, Appendix A, Method 9 and the procedures specified in OAC rule 3745-17-03(B)(1).

- c. Emission Limitation:

Particulate emissions from this emissions unit shall not exceed 1.02 pounds per hour and 4.47 TPY.

Applicable Compliance Method:

The emission limitation was developed based upon OAC rule 3745-17-11 Table I requirements as follows:

$$E = 4.10(P)^{0.67}$$

Where,

E = Allowable emission rate, in pounds per hour; and

P = Process weight rate, 0.125 ton per hour, which is determined based upon facility information that a maximum of 250 pounds per hour of material is dried for each emissions unit.

If required, compliance shall be determined by performing a stack test using USEPA Method 5 of 40 CFR Part 60, Appendix A.

The TPY allowable was calculated using the hourly allowable multiplied by 8760 hours per year divided by 2000 pounds per ton.

g) Miscellaneous Requirements

- (1) Modeling to demonstrate compliance with, the "Toxic Air Contaminant Statute", ORC 3704.03(F)(4)(b), was not necessary because the emissions unit's maximum annual emissions for each toxic air contaminant, as defined in OAC rule 3745-114-01, will be less than 1.0 ton per year. OAC Chapter 3745-31 requires a permittee to apply for and obtain a new or modified PTIO prior to making a "modification" as defined by OAC rule 3745-31-01. The permittee is hereby advised that changes in the composition of the materials, or use of new materials, that would cause the emissions of any toxic air contaminant to increase to above 1.0 ton per year may require the permittee to apply for and obtain a new PTIO.

**5. P005, WASHER 1**

**Operations, Property and/or Equipment Description:**

WASHER 1 (600 POUND BRAUN)

a) This permit document constitutes a permit-to-install issued in accordance with ORC 3704.03(F) and a permit-to-operate issued in accordance with ORC 3704.03(G).

(1) For the purpose of a permit-to-install document, the emissions unit terms and conditions identified below are federally enforceable with the exception of those listed below which are enforceable under state law only.

a. g)(1).

(2) For the purpose of a permit-to-operate document, the emissions unit terms and conditions identified below are enforceable under state law only with the exception of those listed below which are federally enforceable.

a. b)(1)b.

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operation(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures are identified below. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC rule 3745-31-05(A)(3)	VOC emissions shall not exceed 1.02 pounds per 1,000 pounds of soiled shop towels (SST) laundered and 5.36 TPY.  The requirements of this rule include compliance with the requirements of OAC rule 3745-31-05(F).
b.	OAC rule 3745-31-05(F) (Voluntary Restriction to Remain True Minor)	See Section B.

(2) Additional Terms and Conditions

a. None.

- c) Operational Restrictions
  - (1) None.
- d) Monitoring and/or Recordkeeping Requirements
  - (1) None.
- e) Reporting Requirements
  - (1) The permittee shall submit an annual Permit Evaluation Report (PER) to the Southwest Ohio Air Quality Agency (SWOAQA). The PER must be submitted by the due date identified in the Authorization section of this permit. The permit evaluation report shall cover a reporting period of no more than twelve months for each air contaminant source identified in this permit.
  - (2) The reports required by this permit may be submitted through the Ohio EPA's eBusiness Center: Air Services online web portal; or they may be mailed as a hard copy to the Southwest Ohio Air Quality Agency (SWOAQA).
- f) Testing Requirements
  - (1) Compliance with the Emissions Limitations and/or Control Requirements specified in b) of these terms and conditions shall be determined in accordance with the following methods:
    - a. Emission Limitation:

VOC emissions shall not exceed 1.02 pounds per 1000 pounds of SST laundered and 5.36 TPY.

Applicable Compliance Method:

The emission limitation was based upon a December 2012 performance stack test conducted at the UniFirst Portland, Maine facility in accordance with a Testing Order issued by US EPA.

If required, the following test method(s) shall be employed to demonstrate compliance with the allowable VOC emission rate(s): Method 18, Method 25 or Method 25A of 40 CFR Part 60, Appendix A, as appropriate. Alternative U.S. EPA approved test methods may be used with prior approval from the Ohio EPA.

The TPY allowable was calculated using the 1.02 pounds per 1000 pounds of SST laundered allowable multiplied by 1200 pounds per hour capacity and 8760 hours per year divided by 2000 pounds per ton.
- g) Miscellaneous Requirements
  - Modeling to demonstrate compliance with, the "Toxic Air Contaminant Statute", ORC 3704.03(F)(4)(b), was not necessary because the emissions unit's maximum annual emissions for each toxic air contaminant, as defined in OAC rule 3745-114-01, will be



**Final Permit-to-Install and Operate**

UniFirst Corporation - Franklin

**Permit Number:** P0119442

**Facility ID:** 1483040189

**Effective Date:** 5/11/2016

less than 1.0 ton per year. OAC Chapter 3745-31 requires a permittee to apply for and obtain a new or modified PTIO prior to making a "modification" as defined by OAC rule 3745-31-01. The permittee is hereby advised that changes in the composition of the materials, or use of new materials, that would cause the emissions of any toxic air contaminant to increase to above 1.0 ton per year may require the permittee to apply for and obtain a new PTIO.

**6. P901, WASTEWATER TREATMENT**

**Operations, Property and/or Equipment Description:**

WASTEWATER TREATMENT OPERATIONS

- a) This permit document constitutes a permit-to-install issued in accordance with ORC 3704.03(F) and a permit-to-operate issued in accordance with ORC 3704.03(G).
  - (1) For the purpose of a permit-to-install document, the emissions unit terms and conditions identified below are federally enforceable with the exception of those listed below which are enforceable under state law only.
    - a. g)(1).
  - (2) For the purpose of a permit-to-operate document, the emissions unit terms and conditions identified below are enforceable under state law only with the exception of those listed below which are federally enforceable.
    - a. b)(1)c.
- b) Applicable Emissions Limitations and/or Control Requirements
  - (1) The specific operation(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures are identified below. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC rule 3745-31-05(A)(3) June 30, 2008	VOC emissions shall not exceed 2.12 pounds per 1,000 pounds of soiled shop towels (SST) laundered.  See b)(2)a. below.
b.	OAC rule 3745-31-05(A)(3)(a)(ii) June 30, 2008	See b)(2)b. and b)(2)c. below.
c.	OAC rule 3745-31-05(F) (Voluntary Restriction to Remain True Minor)	See section B.

- (2) Additional Terms and Conditions
  - a. The Best Available Technology (BAT) emission limit applies until U.S. EPA approves Ohio Administrative Code (OAC) paragraph 3745-31-05 (A)(3)(a)(ii)



(the less than 10 tons per year BAT exemption) into the Ohio State Implementation Plan (SIP).

- b. The requirements apply once U.S. EPA approves OAC paragraph 3745-31-05 (A)(3)(a)(ii) (the less than 10 tons per year BAT exemption) as part of the Ohio SIP.
- c. The Best Available Technology (BAT) requirements under OAC rule 3745-31-05 (A)(3) do not apply to the VOC emissions since the calculated annual emission rate is less than 10 tons per year, taking into account the voluntary emission restrictions from OAC rule 3745-31-05(F).

c) Operational Restrictions

- (1) None.

d) Monitoring and/or Recordkeeping Requirements

- (1) None.

e) Reporting Requirements

- (1) The permittee shall submit an annual Permit Evaluation Report (PER) to the Southwest Ohio Air Quality Agency (SWOAQA). The PER must be submitted by the due date identified in the Authorization section of this permit. The permit evaluation report shall cover a reporting period of no more than twelve months for each air contaminant source identified in this permit.
- (2) The reports required by this permit may be submitted through the Ohio EPA's eBusiness Center: Air Services online web portal; or they may be mailed as a hard copy to the Southwest Ohio Air Quality Agency (SWOAQA).

f) Testing Requirements

- (1) Compliance with the Emissions Limitations and/or Control Requirements specified in b) of these terms and conditions shall be determined in accordance with the following methods:

- a. Emission Limitation:

VOC emissions shall not exceed 2.12 pounds per 1000 pounds of SST laundered.

Applicable Compliance Method:

The emission limitation was based upon a December 2012 performance stack test conducted at the UniFirst Portland, Maine facility in accordance with a Testing Order issued by US EPA.

If required, the following test method(s) shall be employed to demonstrate compliance with the allowable VOC emission rate(s): Method 18, Method 25 or



**Final Permit-to-Install and Operate**  
UniFirst Corporation - Franklin  
**Permit Number:** P0119442  
**Facility ID:** 1483040189  
**Effective Date:** 5/11/2016

Method 25A of 40 CFR Part 60, Appendix A, as appropriate. Alternative U.S. EPA approved test methods may be used with prior approval from the Ohio EPA.

g) Miscellaneous Requirements

- (1) Modeling to demonstrate compliance with, the "Toxic Air Contaminant Statute", ORC 3704.03(F)(4)(b), was not necessary because the emissions units' maximum annual emissions for each toxic air contaminant, as defined in OAC rule 3745-114-01, will be less than 1.0 ton per year. OAC Chapter 3745-31 requires a permittee to apply for and obtain a new or modified federally enforceable permit to install and operate (PTIO) prior to making a "modification" as defined by OAC rule 3745-31-01. The permittee is hereby advised that changes in the composition of the materials or use of new materials that would cause the emissions of any toxic air contaminant to increase to above 1.0 ton per year may require the permittee to apply for and obtain a new PTIO.

**7. Emissions Unit Group -Washers, post 2006: P006,P007,P008,P009,P010,P011,P012,**

<b>EU ID</b>	<b>Operations, Property and/or Equipment Description</b>
P006	WASHER 2 (650 POUND BRAUN)
P007	WASHER 3 (650 POUND BRAUN)
P008	WASHER 4 (450 POUND BRAUN)
P009	WASHER 5 (650 POUND BRAUN)
P010	WASHER 6 (125 POUND SAILSTAR)
P011	WASHER 7 (250 POUND BRAUN)
P012	WASHER 8 (50 POUND MILNOR)

- a) This permit document constitutes a permit-to-install issued in accordance with ORC 3704.03(F) and a permit-to-operate issued in accordance with ORC 3704.03(G).
- (1) For the purpose of a permit-to-install document, the emissions unit terms and conditions identified below are federally enforceable with the exception of those listed below which are enforceable under state law only.
- a. g)(1).
- (2) For the purpose of a permit-to-operate document, the emissions unit terms and conditions identified below are enforceable under state law only with the exception of those listed below which are federally enforceable.
- a. b)(1)c.
- b) Applicable Emissions Limitations and/or Control Requirements
- (1) The specific operation(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures are identified below. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	<b>Applicable Rules/Requirements</b>	<b>Applicable Emissions Limitations/Control Measures</b>
a.	OAC rule 3745-31-05(A)(3) June 30, 2008	VOC emissions shall not exceed 1.02 pounds per 1,000 pounds of soiled shop towels (SST) laundered.  The requirements for VOC emissions established pursuant to this rule are equivalent to requirements of OAC rule 3745-31-05(F).  See b)(2)a. below.



	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
b.	OAC rule 3745-31-05 (A)(3)(a)(ii) June 30, 2008	See b)(2)b. and b)(2)c. below.
c.	OAC rule 3745-31-05(F) (Voluntary Restriction to Remain True Minor)	See Section B.

(2) Additional Terms and Conditions

- a. The Best Available Technology (BAT) emission limit applies until U.S. EPA approves Ohio Administrative Code (OAC) paragraph 3745-31-05 (A)(3)(a)(ii) (the less than 10 tons per year BAT exemption) into the Ohio State Implementation Plan (SIP).
- b. The requirements apply once U.S. EPA approves OAC paragraph 3745-31-05 (A)(3)(a)(ii) (the less than 10 tons per year BAT exemption) as part of the Ohio SIP.
- c. The Best Available Technology (BAT) requirements under OAC rule 3745-31-05 (A)(3) do not apply to the VOC emissions since the calculated annual emission rate is less than 10 tons per year, taking into account the voluntary emission restrictions from OAC rule 3745-31-05(F).

c) Operational Restrictions

- (1) None.

d) Monitoring and/or Recordkeeping Requirements

- (1) None.

e) Reporting Requirements

- (1) The permittee shall submit an annual Permit Evaluation Report (PER) to the Southwest Ohio Air Quality Agency (SWOAQA). The PER must be submitted by the due date identified in the Authorization section of this permit. The permit evaluation report shall cover a reporting period of no more than twelve months for each air contaminant source identified in this permit.
- (2) The reports required by this permit may be submitted through the Ohio EPA's eBusiness Center: Air Services online web portal; or they may be mailed as a hard copy to the Southwest Ohio Air Quality Agency (SWOAQA).

f) Testing Requirements

- (1) Compliance with the Emissions Limitations and/or Control Requirements specified in b) of these terms and conditions shall be determined in accordance with the following methods:

a. Emission Limitation:

VOC emissions shall not exceed 1.02 pounds per 1000 pounds of SST laundered.

Applicable Compliance Method:

The emission limitation was based upon a December 2012 performance stack test conducted at the UniFirst Portland, Maine facility in accordance with a Testing Order issued by US EPA.

If required, the following test method(s) shall be employed to demonstrate compliance with the allowable VOC emission rate(s): Method 18, Method 25 or Method 25A of 40 CFR Part 60, Appendix A, as appropriate. Alternative U.S. EPA approved test methods may be used with prior approval from the Ohio EPA.

g) Miscellaneous Requirements

- (1) Modeling to demonstrate compliance with, the "Toxic Air Contaminant Statute", ORC 3704.03(F)(4)(b), was not necessary because the emissions unit's maximum annual emissions for each toxic air contaminant, as defined in OAC rule 3745-114-01, will be less than 1.0 ton per year. OAC Chapter 3745-31 requires a permittee to apply for and obtain a new or modified PTIO prior to making a "modification" as defined by OAC rule 3745-31-01. The permittee is hereby advised that changes in the composition of the materials, or use of new materials, that would cause the emissions of any toxic air contaminant to increase to above 1.0 ton per year may require the permittee to apply for and obtain a new PTIO.