

A. Additional Terms and Conditions:

1. The permittee shall employ reasonably available control measures on the #3 Bagger, #3 Silo and the #3 Elevator for the purpose of ensuring compliance with the above mentioned applicable requirements. In accordance with the permittee's permit application, the permittee has committed to both maintain enclosures around the emissions unit and vent emissions to a fabric filter baghouse, which is capable of meeting the applicable requirements to ensure compliance. Nothing in this paragraph shall prohibit the permittee from employing other control measures to ensure compliance.

B. Monitoring and Recordkeeping Requirements:

1. The permittee shall perform daily checks, while the equipment is in operation, for any unusual visible emissions of fugitive dust escaping the capture system and for any visible emissions from the baghouse serving the emissions unit. A record of the necessary and completed corrective actions resulting from the daily checks shall be maintained by the permittee.

C. Reporting Requirements:

1. The permittee shall submit reports in accordance with the reporting requirements of the General Terms and Condition which identify each day that the observations required under the monitoring section of this permit were not performed and each day that any corrective measures required to be taken pursuant to the monitoring section of this permit were not performed.

D. Testing Requirements:

1. Compliance with the emission limitations identified above shall be determined in accordance with the following method:

- a. Emission Limitation

0.030 grains per dry standard cubic foot of exhaust gases, or no visible emissions, whichever is less stringent.

Applicable Compliance Method:

Compliance shall be determined in accordance with 40 CFR 60 Appendix A, Methods 1-5 and the procedures specified in OAC rule 3745-17-03(B)(1). No testing is specifically required by this permit but, if

appropriate, may be requested pursuant to OAC rule 3745-15-04. Compliance will be determined through the monitoring and recordkeeping in the above sections.

b. Emission Limitation:

20% opacity as a three minute average

Applicable Compliance Method:

Test Method 9 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources"), as such Appendix existed on July 1, 1996, and the modifications listed in paragraphs (B)(3)(a) and (B)(3)(b) of OAC rule 3745-17-03.

c. Emission Limitation

1.2 Tons per Year of Particulate Matter

Applicable Compliance Method:

A one time calculation of Potential to Emit based upon baghouse design as follows:

$$0.030 \text{ gr/dscf} * 1000 \text{ acfm} * 60 \text{ min/hr} \div 7,000 \text{ gr/lb} * 8760 \text{ hr/yr} = 1.13 \text{ TPY}$$

E. Miscellaneous Requirements:

None