



State of Ohio Environmental Protection Agency

**RE: FINAL PERMIT TO INSTALL CERTIFIED MAIL
SUMMIT COUNTY**

Street Address:

122 S. Front Street

Lazarus Gov. Center TELE: (614) 644-3020 FAX: (614) 644-2329

Mailing Address:

Lazarus Gov. Center
P.O. Box 1049

Application No: 16-02061

DATE: 8/3/2000

Ferriot, Inc.
Gordon F. Keeler, Jr.
1000 Arlington Circle
Akron, OH 443067670

Enclosed please find an Ohio EPA Permit to Install which will allow you to install the described source(s) in a manner indicated in the permit. Because this permit contains several conditions and restrictions, I urge you to read it carefully.

The Ohio EPA is urging companies to investigate pollution prevention and energy conservation. Not only will this reduce pollution and energy consumption, but it can also save you money. If you would like to learn ways you can save money while protecting the environment, please contact our Office of Pollution Prevention at (614) 644-3469.

You are hereby notified that this action by the Director is final and may be appealed to the Ohio Environmental Review Appeals Commission pursuant to Chapter 3745.04 of the Ohio Revised Code. The appeal must be in writing and set forth the action complained of and the grounds upon which the appeal is based. It must be filed within thirty (30) days after the notice of the Directors action. A copy of the appeal must be served on the Director of the Ohio Environmental Protection Agency within three (3) days of filing with the Commission. An appeal may be filed with the Environmental Review Appeals Commission at the following address:

Environmental Review Appeals Commission
236 East Town Street, Room 300
Columbus, Ohio 43215

Very truly yours,

Thomas G. Rigo, Manager
Field Operations and Permit Section
Division of Air Pollution Control

cc: USEPA

ARAQMD



Permit To Install

STATE OF OHIO ENVIRONMENTAL PROTECTION AGENCY

FINAL PERMIT TO INSTALL 16-02061

Application Number: 16-02061
APS Premise Number: 1677011093
Permit Fee: **\$1200**
Name of Facility: Ferriot, Inc.
Person to Contact: Gordon F. Keeler, Jr.
Address: 1000 Arlington Circle
Akron, OH 443067670

Location of proposed air contaminant source(s) [emissions unit(s)]:
1000 Arlington Circle
Akron, Ohio

Description of proposed emissions unit(s):
Three paint spray booths.

The above named entity is hereby granted a Permit to Install for the above described emissions unit(s) pursuant to Chapter 3745-31 of the Ohio Administrative Code. Issuance of this permit does not constitute expressed or implied approval or agreement that, if constructed or modified in accordance with the plans included in the application, the above described emissions unit(s) of environmental pollutants will operate in compliance with applicable State and Federal laws and regulations, and does not constitute expressed or implied assurance that if constructed or modified in accordance with those plans and specifications, the above described emissions unit(s) of pollutants will be granted the necessary permits to operate (air) or NPDES permits as applicable.

This permit is granted subject to the conditions attached hereto.

Ohio Environmental Protection Agency



Director

Part I - GENERAL TERMS AND CONDITIONS

A. Permit to Install General Terms and Conditions

1. Compliance Requirements

The emissions unit(s) identified in this Permit to Install shall remain in full compliance with all applicable State laws and regulations and the terms and conditions of this permit.

2. Reporting Requirements Related to Monitoring and Recordkeeping Requirements

The permittee shall submit required reports in the following manner:

- a. Reports of any required monitoring and/or recordkeeping information shall be submitted to the appropriate Ohio EPA District Office or local air agency.
- b. Except as otherwise may be provided in the terms and conditions for a specific emissions unit, quarterly written reports of (a) any deviations (excursions) from emission limitations, operational restrictions, and control device operating parameter limitations that have been detected by the testing, monitoring, and recordkeeping requirements specified in this permit, (b) the probable cause of such deviations, and (c) any corrective actions or preventive measures which have been or will be taken, shall be submitted to the appropriate Ohio EPA District Office or local air agency. If no deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted quarterly, i.e., by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters. (These quarterly reports shall exclude deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06.)

3. Records Retention Requirements

Each record of any monitoring data, testing data, and support information required pursuant to this permit shall be retained for a period of five years from the date the record was created. Support information shall include, but not be limited to, all calibration and maintenance records and all original strip-chart recordings for continuous monitoring instrumentation, and copies of all reports required by this permit. Such records may be maintained in computerized form.

4. Inspections and Information Requests

The Director of the Ohio EPA, or an authorized representative of the Director, may, subject to the safety requirements of the permittee and without undue delay, enter upon the premises of this source at any reasonable time for purposes of making inspections, conducting tests, examining records or reports pertaining to any emission of air contaminants, and determining compliance with any applicable State air pollution laws and regulations and the terms and conditions of this permit. The permittee shall furnish to the Director of the Ohio EPA, or an authorized

Ferriot, Inc.

PTI Application: 16-02061

Issued: 8/3/2000

Facility ID: 1677011093

representative of the Director, upon receipt of a written request and within a reasonable time, any information that may be requested to determine whether cause exists for modifying, reopening or revoking this permit or to determine compliance with this permit. Upon verbal or written request, the permittee shall also furnish to the Director of the Ohio EPA, or an authorized representative of the Director, copies of records required to be kept by this permit.

5. Scheduled Maintenance/Malfunction Reporting

Any scheduled maintenance of air pollution control equipment shall be performed in accordance with paragraph (A) of OAC rule 3745-15-06. The malfunction of any emissions units or any associated air pollution control system(s) shall be reported to the appropriate Ohio EPA District Office or local air agency in accordance with paragraph (B) of OAC rule 3745-15-06. Except as provided in that rule, any scheduled maintenance or malfunction necessitating the shutdown or bypassing of any air pollution control system(s) shall be accompanied by the shutdown of the emissions unit(s) that is (are) served by such control system(s).

6. Permit Transfers

Any transferee of this permit shall assume the responsibilities of the prior permit holder. The appropriate Ohio EPA District Office or local air agency must be notified in writing of any transfer of this permit.

7. Air Pollution Nuisance

The air contaminants emitted by the emissions units covered by this permit shall not cause a public nuisance, in violation of OAC rule 3745-15-07.

8. Termination of Permit to Install

This Permit to Install shall terminate within eighteen months of the effective date of the Permit to Install if the owner or operator has not undertaken a continuing program of installation or modification or has not entered into a binding contractual obligation to undertake and complete within a reasonable time a continuing program of installation or modification. This deadline may be extended by up to 12 months if application is made to the Director within a reasonable time before the termination date and the party shows good cause for any such extension.

9. Construction of New Sources(s)

The proposed emissions unit(s) shall be constructed in strict accordance with the plans and application submitted for this permit to the Director of the Ohio Environmental Protection Agency. There may be no deviation from the approved plans without the express, written approval of the Agency. Any deviations from the approved plans or the above conditions may lead to such sanctions and penalties as provided under Ohio law. Approval of these plans does not constitute an assurance that the proposed facilities will operate in compliance with all Ohio laws and regulations. Additional facilities shall be installed upon orders of the Ohio

Ferriot, Inc.

PTI Application: 16-02061

Issued: 8/3/2000

Facility ID: 1677011093

Environmental Protection Agency if the proposed sources are inadequate or cannot meet applicable standards.

If the construction of the proposed emissions unit(s) has already begun or has been completed prior to the date the Director of the Environmental Protection Agency approves the permit application and plans, the approval does not constitute expressed or implied assurance that the proposed facility has been constructed in accordance with the approved plans. The action of beginning and/or completing construction prior to obtaining the Director's approval constitutes a violation of OAC rule 3745-31-02. Furthermore, issuance of the Permit to Install does not constitute an assurance that the proposed source will operate in compliance with all Ohio laws and regulations. Approval of the plans in any case is not to be construed as an approval of the facility as constructed and/or completed. Moreover, issuance of the Permit to Install is not to be construed as a waiver of any rights that the Ohio Environmental Protection Agency (or other persons) may have against the applicant for starting construction prior to the effective date of the permit. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed facilities prove to be inadequate or cannot meet applicable standards.

10. Public Disclosure

The facility is hereby notified that this permit, and all agency records concerning the operation of this permitted source, are subject to public disclosure in accordance with OAC rule 3745-49-03.

11. Applicability

This Permit to Install is applicable only to the emissions unit(s) identified in the Permit to Install. Separate application must be made to the Director for the installation or modification of any other emissions unit(s).

12. Best Available Technology

As specified in OAC Rule 3745-31-05, all new sources must employ Best Available Technology (BAT). Compliance with the terms and conditions of this permit will fulfill this requirement.

13. Source Operation and Operating Permit Requirements After Completion of Construction

This facility is permitted to operate each source described by this Permit to Install for a period of up to one year from the date the source commenced operation. This permission to operate is granted only if the facility complies with all requirements contained in this permit and all applicable air pollution laws, regulations, and policies. Pursuant to OAC Chapter 3745-35, the permittee shall submit a complete operating permit application within thirty (30) days after commencing operation of the emissions unit(s) covered by this permit.

Ferriot, Inc.

PTI Application: 16-02061

Issued: 8/3/2000

Facility ID: 1677011093

14. Construction Compliance Certification

The applicant shall provide Ohio EPA with a written certification (see enclosed form) that the facility has been constructed in accordance with the Permit to Install application and the terms and conditions of the Permit to Install. The certification shall be provided to Ohio EPA upon completion of construction but prior to startup of the source.

15. Fees

The permittee shall pay fees to the Director of the Ohio EPA in accordance with ORC section 3745.11 and OAC Chapter 3745-78. The permittee shall pay all applicable Permit to Install fees within 30 days after the issuance of this Permit to Install.

B. Permit to Install Summary of Allowable Emissions

The following information summarizes the total allowable emissions, by pollutant, based on the individual allowable emissions of each air contaminant source identified in this permit.

**SUMMARY (for informational purposes only)
TOTAL PERMIT TO INSTALL ALLOWABLE EMISSIONS**

<u>Pollutant</u>	<u>Tons Per Year</u>
organic compounds	24.9

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

- 1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
Booth #8 - paint spray booth - coating miscellaneous plastic parts, dried with infrared oven, overspray controlled by a water wash	OAC rule 3745-31-05	1.9 pounds/hour and 8.3 tons/year of organic compounds (OCs) [See sections A.2 and B.1 through B.3 below for additional requirements of OAC rule 3745-31-05.]
	OAC rule 3745-21-07(G)	exempt pursuant to OAC rule 3745-21-07(G)(9) [See section B.3 below.]

2. Additional Terms and Conditions

- 2.a The above OC emission limits (regulated under OAC rule 3745-31-05) are based on the potential to emit for this emissions unit, as determined from permit application data. Therefore, no recordkeeping, reporting, nor emissions calculations are required to demonstrate compliance with these emission limits. However, if any proposed change(s), such as with compound formulations, maximum coating application rate capacity, cleanup materials, etc., or any other change(s), increase(s) the emissions unit's potential to emit, then the permittee shall apply for and obtain either a modification to the permit to install or a new final permit to install prior to making the change(s).
- 2.b The permit to install for R008 was evaluated based on the actual materials (typically coatings and cleanup materials) and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxics Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant(s):

Pollutant: 2-butoxyethanol (CAS 111-76-2)
TLV (ug/m3): 96,800
Maximum Hourly Emission Rate (lbs/hr): 0.61
Predicted 1-Hour Maximum Ground-Level Concentration at 38 m (ug/m3): 57
MAGLC (ug/m3): 2305

2.c Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxics Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxics Policy" will still be satisfied. If, upon evaluation, the permittee determines that the "Air Toxics Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxics Policy" include the following:

- i. changes in the composition of the materials used (typically for coatings or cleanup materials), or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value previously modeled;
- ii. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and
- iii. physical changes to the emissions unit or its exhaust parameters (e.g., increased/decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Air Toxics Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01(VV)(1)(a)(ii), and a modification of the existing permit to install will not be required. If the change(s) is (are) defined as a modification under other provisions of the modification definition (other than (VV)(1)(a)(ii)), then the permittee shall obtain a final permit to install prior to the change.

2.d The permittee shall properly install, employ and maintain a spray booth water wash control system to catch paint overspray.

B. Operational Restrictions

Emissions Unit ID: R008

1. The water wash control system shall be employed at all times the emissions unit is in operation.
2. All coatings and cleanup solvents shall be properly identified and held in closed containers or storage vessels at all times when not in use.
3. The permittee shall not use any photochemically reactive materials, as defined by OAC rule 3745-21-01(C)(5), in this emissions unit.

C. Monitoring and/or Recordkeeping Requirements

1. The permittee shall maintain monthly records of the following information for this emissions unit:
 - a. the company identification of each liquid organic material, including cleanup material, employed in this emissions unit; and
 - b. whether or not each liquid organic material, including cleanup material, employed is a photochemically reactive material.
2. The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the emissions unit, if changed as outlined above in section A.2, will still satisfy the "Air Toxics Policy":
 - a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
 - b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxics Policy"; and
 - c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxics Policy" for the change.

D. Reporting Requirements

1. The permittee shall submit deviation reports which identify the days during which photochemically reactive materials were employed in this emissions unit. Each report shall identify the cause for the use of the photochemically reactive material(s) and the estimated total quantity of material(s) emitted during each such day, in pounds.
2. The deviation reports shall be submitted in accordance with the requirements specified in Part I - General Term and Condition 2 of this permit.

E. Testing Requirements

1. Compliance with the emission limitations in Section A.1. of these terms and conditions shall be determined in accordance with the following methods:

- a. Emission Limitations: 1.9 pounds/hour, and 8.3 tons/year of OCs

Applicable Compliance Method: The OC emission limitations are based upon the emission unit's potential to emit, as follows:

$$\text{PTE[OCs]h} = (\text{CARCmax}) \times (\text{OCCmax}) + (\text{CMmax}) \times (\text{D}); \text{ and}$$
$$\text{PTE[OCs]y} = (\text{PTE[OCs]h}) \times (8760 \text{ hours/year}) \times (1 \text{ ton}/2000 \text{ pounds}).$$

Where:

$\text{PTE[OCs]h} = 1.9$ pounds of OCs/hour [hourly potential to emit OCs];

$\text{PTE[OCs]y} = 8.3$ tons of OCs/year [yearly potential to emit OCs];

$\text{CARCmax} = 0.88$ gallon of coating/hour [maximum coating application rate capacity, coatings as applied after final thinning];

$\text{OCCmax} = 1.89$ pounds of OCs/gallon of coating [maximum OC content of coatings as applied after final thinning];

$\text{CMmax} = 0.0288$ gallon of cleanup material/hour [maximum average hourly usage rate based on

106 gallons used on an operating schedule of 3675 hours/year; and

$\text{D} = 6.71$ pounds of OCs/gallon of cleanup material [density of cleanup material solvent].

F. Miscellaneous Requirements

1. This emissions unit shall be included with all other emissions units at the facility when determining compliance with the facility-wide emission limitations of OCs and hazardous air pollutants (HAPs), as established in the recordkeeping requirements of permit-to-install (PTI) #16-1936, as issued December 15, 1999.

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
Booth #9 - paint spray booth - coating miscellaneous plastic parts, dried with infrared oven, overspray controlled by a water wash	OAC rule 3745-31-05	1.9 pounds/hour and 8.3 tons/year of organic compounds (OCs) [See sections A.2 and B.1 through B.3 below for additional requirements of OAC rule 3745-31-05.]
	OAC rule 3745-21-07(G)	exempt pursuant to OAC rule 3745-21-07(G)(9) [See section B.3 below.]

2. Additional Terms and Conditions

- 2.a The above OC emission limits (regulated under OAC rule 3745-31-05) are based on the potential to emit for this emissions unit, as determined from permit application data. Therefore, no recordkeeping, reporting, nor emissions calculations are required to demonstrate compliance with these emission limits. However, if any proposed change(s), such as with compound formulations, maximum coating application rate capacity, cleanup materials, etc., or any other change(s), increase(s) the emissions unit's potential to emit, then the permittee shall apply for and obtain either a modification to the permit to install or a new final permit to install prior to making the change(s).
- 2.b The permit to install for R009 was evaluated based on the actual materials (typically coatings and cleanup materials) and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxics Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour

maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant(s):

Pollutant: 2-butoxyethanol (CAS 111-76-2)

TLV (ug/m3): 96,800

Maximum Hourly Emission Rate (lbs/hr): 0.61

Predicted 1-Hour Maximum Ground-Level Concentration at 38 m (ug/m3): 57

MAGLC (ug/m3): 2305

- 2.c** Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxics Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxics Policy" will still be satisfied. If, upon evaluation, the permittee determines that the "Air Toxics Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxics Policy" include the following:
- i. changes in the composition of the materials used (typically for coatings or cleanup materials), or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value previously modeled;
 - ii. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and
 - iii. physical changes to the emissions unit or its exhaust parameters (e.g., increased/decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Air Toxics Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01(VV)(1)(a)(ii), and a modification of the existing permit to install will not be required. If the change(s) is (are) defined as a modification under other provisions of the modification definition (other than (VV)(1)(a)(ii)), then the permittee shall obtain a final permit to install prior to the change.

- 2.d** The permittee shall properly install, employ and maintain a spray booth water wash control

Ferriot, Inc.

PTI Application: 16-02061

Issued

Facility ID: 1677011093

Emissions Unit ID: R009

system to catch paint overspray.

B. Operational Restrictions

1. The water wash control system shall be employed at all times the emissions unit is in operation.
2. All coatings and cleanup solvents shall be properly identified and held in closed containers or storage vessels at all times when not in use.

3. The permittee shall not use any photochemically reactive materials, as defined by OAC rule 3745-21-01(C)(5), in this emissions unit.

C. Monitoring and/or Recordkeeping Requirements

1. The permittee shall maintain monthly records of the following information for this emissions unit:
 - a. the company identification of each liquid organic material, including cleanup material, employed in this emissions unit; and
 - b. whether or not each liquid organic material, including cleanup material, employed is a photochemically reactive material.
2. The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the emissions unit, if changed as outlined above in section A.2, will still satisfy the "Air Toxics Policy":
 - a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
 - b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxics Policy"; and
 - c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxics Policy" for the change.

D. Reporting Requirements

1. The permittee shall submit deviation reports which identify the days during which photochemically reactive materials were employed in this emissions unit. Each report shall identify the cause for the use of the photochemically reactive material(s) and the estimated total quantity of material(s) emitted during each such day, in pounds.
2. The deviation reports shall be submitted in accordance with the requirements specified in Part I - General Term and Condition 2 of this permit.

E. Testing Requirements

1. Compliance with the emission limitations in Section A.1. of these terms and conditions shall be

determined in accordance with the following methods:

- a. Emission Limitations: 1.9 pounds/hour, and 8.3 tons/year of OCs

Applicable Compliance Method: The OC emission limitations are based upon the emission unit's potential to emit, as follows:

$$\begin{aligned} \text{PTE[OCs]h} &= (\text{CARCmax}) \times (\text{OCCmax}) + (\text{CMmax}) \times (\text{D}); \text{ and} \\ \text{PTE[OCs]y} &= (\text{PTE[OCs]h}) \times (8760 \text{ hours/year}) \times (1 \text{ ton/2000 pounds}). \end{aligned}$$

Where:

PTE[OCs]h = 1.9 pounds of OCs/hour [hourly potential to emit OCs];

PTE[OCs]y = 8.3 tons of OCs/year [yearly potential to emit OCs];

CARCmax = 0.88 gallon of coating/hour [maximum coating application rate capacity, coatings as applied after final thinning];

OCCmax = 1.89 pounds of OCs/gallon of coating [maximum OC content of coatings as applied after final thinning];

CMmax = 0.0288 gallon of cleanup material/hour [maximum average hourly usage rate based on

106 gallons used on an operating schedule of 3675 hours/year; and

D = 6.71 pounds of OCs/gallon of cleanup material [density of cleanup material solvent].

F. Miscellaneous Requirements

1. This emissions unit shall be included with all other emissions units at the facility when determining compliance with the facility-wide emission limitations of OCs and hazardous air pollutants (HAPs), as established in the recordkeeping requirements of permit-to-install (PTI) #16-1936, as issued December 15, 1999.

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
Booth #10 - paint spray booth - coating miscellaneous plastic parts, overspray controlled by exhaust fan dry filter elements	OAC rule 3745-31-05	1.9 pounds/hour and 8.3 tons/year of organic compounds (OCs) [See sections A.2 and B.1 through B.3 below for additional requirements of OAC rule 3745-31-05.]
	OAC rule 3745-21-07(G)	exempt pursuant to OAC rule 3745-21-07(G)(9) [See section B.3 below.]

2. Additional Terms and Conditions

- 2.a The above OC emission limits (regulated under OAC rule 3745-31-05) are based on the potential to emit for this emissions unit, as determined from permit application data. Therefore, no recordkeeping, reporting, nor emissions calculations are required to demonstrate compliance with these emission limits. However, if any proposed change(s), such as with compound formulations, maximum coating application rate capacity, cleanup materials, etc., or any other change(s), increase(s) the emissions unit's potential to emit, then the permittee shall apply for and obtain either a modification to the permit to install or a new final permit to install prior to making the change(s).
- 2.b The permit to install for R010 was evaluated based on the actual materials (typically coatings and cleanup materials) and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxics Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour

maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant(s):

Pollutant: 2-butoxyethanol (CAS 111-76-2)

TLV (ug/m3): 96,800

Maximum Hourly Emission Rate (lbs/hr): 0.61

Predicted 1-Hour Maximum Ground-Level Concentration at 38 m (ug/m3): 57

MAGLC (ug/m3): 2305

- 2.c** Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxics Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxics Policy" will still be satisfied. If, upon evaluation, the permittee determines that the "Air Toxics Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxics Policy" include the following:
- i. changes in the composition of the materials used (typically for coatings or cleanup materials), or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value previously modeled;
 - ii. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and
 - iii. physical changes to the emissions unit or its exhaust parameters (e.g., increased/decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Air Toxics Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01(VV)(1)(a)(ii), and a modification of the existing permit to install will not be required. If the change(s) is (are) defined as a modification under other provisions of the modification definition (other than (VV)(1)(a)(ii)), then the permittee shall obtain a final permit to install prior to the change.

- 2.d** The permittee shall properly install, employ and maintain spray booth exhaust fan filter

Ferriot, Inc.

PTI Application: 16-02061

Issued

Facility ID: 1677011093

Emissions Unit ID: R010

elements to catch paint overspray.

B. Operational Restrictions

1. The exhaust fan filter elements shall be employed at all times the emissions unit is in operation.
2. All coatings and cleanup solvents shall be properly identified and held in closed containers or storage vessels at all times when not in use.

3. The permittee shall not use any photochemically reactive materials, as defined by OAC rule 3745-21-01(C)(5), in this emissions unit.

C. Monitoring and/or Recordkeeping Requirements

1. The permittee shall maintain monthly records of the following information for this emissions unit:
 - a. the company identification of each liquid organic material, including cleanup material, employed in this emissions unit; and
 - b. whether or not each liquid organic material, including cleanup material, employed is a photochemically reactive material.
2. The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the emissions unit, if changed as outlined above in section A.2, will still satisfy the "Air Toxics Policy":
 - a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
 - b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxics Policy"; and
 - c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxics Policy" for the change.

D. Reporting Requirements

1. The permittee shall submit deviation reports which identify the days during which photochemically reactive materials were employed in this emissions unit. Each report shall identify the cause for the use of the photochemically reactive material(s) and the estimated total quantity of material(s) emitted during each such day, in pounds.
2. The deviation reports shall be submitted in accordance with the requirements specified in Part I - General Term and Condition 2 of this permit.

E. Testing Requirements

1. Compliance with the emission limitations in Section A.1. of these terms and conditions shall be

determined in accordance with the following methods:

- a. Emission Limitations: 1.9 pounds/hour, and 8.3 tons/year of OCs

Applicable Compliance Method: The OC emission limitations are based upon the emission unit's potential to emit, as follows:

$$\begin{aligned} \text{PTE[OCs]h} &= (\text{CARCmax}) \times (\text{OCCmax}) + (\text{CMmax}) \times (\text{D}); \text{ and} \\ \text{PTE[OCs]y} &= (\text{PTE[OCs]h}) \times (8760 \text{ hours/year}) \times (1 \text{ ton/2000 pounds}). \end{aligned}$$

Where:

PTE[OCs]h = 1.9 pounds of OCs/hour [hourly potential to emit OCs];

PTE[OCs]y = 8.3 tons of OCs/year [yearly potential to emit OCs];

CARCmax = 0.88 gallon of coating/hour [maximum coating application rate capacity, coatings as applied after final thinning];

OCCmax = 1.89 pounds of OCs/gallon of coating [maximum OC content of coatings as applied after final thinning];

CMmax = 0.0288 gallon of cleanup material/hour [maximum average hourly usage rate based on

106 gallons used on an operating schedule of 3675 hours/year; and

D = 6.71 pounds of OCs/gallon of cleanup material [density of cleanup material solvent].

F. Miscellaneous Requirements

1. This emissions unit shall be included with all other emissions units at the facility when determining compliance with the facility-wide emission limitations of OCs and hazardous air pollutants (HAPs), as established in the recordkeeping requirements of permit-to-install (PTI) #16-1936, as issued December 15, 1999.

NEW SC

PTI Num

FACILITY

Emissions Unit ID: **R010** _____

FACILITY DESCRIPTION Three paint spray booths. CITY/TWP Akron

SIC CODE 3089 SCC CODE 4-02-999-98 EMISSIONS UNIT ID R008

EMISSIONS UNIT DESCRIPTION Booth #8 - waterwash paint spray booth

DATE INSTALLED 6/00

EMISSIONS: (Click on bubble help for Air Quality Descriptions)

Pollutants	Air Quality Description	Actual Emissions Rate		PTI Allowable	
		Short Term Rate	Tons Per Year	Short Term Rate	Tons Per Year
Particulate Matter					
PM ₁₀					
Sulfur Dioxide					
Organic Compounds				1.9 lbs/hr	8.3
Nitrogen Oxides					
Carbon Monoxide					
Lead					
Other: Air Toxics					

APPLICABLE FEDERAL RULES:

NSPS? _____ NESHAP? _____ PSD? _____ OFFSET POLICY? _____

WHAT IS THE BAT DETERMINATION, AND WHAT IS THE BASIS FOR THE DETERMINATION?

Enter Determination water-based paints; paint overspray control

IS THIS SOURCE SUBJECT TO THE AIR TOXICS POLICY? YES

OPTIONAL: WHAT IS THE CAPITAL COST OF CONTROL EQUIPMENT? \$ _____

TOXIC AIR CONTAMINANTS

Ohio EPA's air toxics policy applies to contaminants for which the American Conference of Governmental Industrial Hygienists (ACGIH) has a listed threshold limit value.

AIR TOXICS MODELING PERFORMED*? X YES _____ NO _____

IDENTIFY THE AIR CONTAMINANTS: 2-butoxyethanol (CAS 111-76-2)

NEW SOURCE REVIEW FORM B

PTI Number: 16-02061

Facility ID: 1677011093

FACILITY NAME Ferriot, Inc.

FACILITY DESCRIPTION Three paint spray booths.

CITY/TWP Akron

Emissions Unit ID: **R010**

SIC CODE 3089

SCC CODE 4-02-999-98

EMISSIONS UNIT ID R009

EMISSIONS UNIT DESCRIPTION Booth #9 - waterwash paint spray booth

DATE INSTALLED 6/00

EMISSIONS: (Click on bubble help for Air Quality Descriptions)

Pollutants	Air Quality Description	Actual Emissions Rate		PTI Allowable	
		Short Term Rate	Tons Per Year	Short Term Rate	Tons Per Year
Particulate Matter					
PM ₁₀					
Sulfur Dioxide					
Organic Compounds				1.9 lbs/hr	8.3
Nitrogen Oxides					
Carbon Monoxide					
Lead					
Other: Air Toxics					

APPLICABLE FEDERAL RULES:

NSPS?

NESHAP?

PSD?

OFFSET POLICY?

WHAT IS THE BAT DETERMINATION, AND WHAT IS THE BASIS FOR THE DETERMINATION?

Enter Determination water-based paints; paint overspray control

IS THIS SOURCE SUBJECT TO THE AIR TOXICS POLICY?

OPTIONAL: WHAT IS THE CAPITAL COST OF CONTROL EQUIPMENT?

\$

TOXIC AIR CONTAMINANTS

Ohio EPA's air toxics policy applies to contaminants for which the American Conference of Governmental Industrial Hygienists (ACGIH) has a listed threshold limit value.

AIR TOXICS MODELING PERFORMED*?

X

YES

NO

IDENTIFY THE AIR CONTAMINANTS:

2-butoxyethanol (CAS 111-76-2)

NEW SOURCE REVIEW FORM B

PTI Number: 16-02061

Facility ID: 1677011093

FACILITY NAME Ferriot, Inc.

FACILITY DESCRIPTION Three paint spray booths.

CITY/TWP Akron

Emissions Unit ID: **R010**

SIC CODE 3089

SCC CODE 4-02-999-98

EMISSIONS UNIT ID R010

EMISSIONS UNIT DESCRIPTION Booth #10 - dry filter paint spray booth

DATE INSTALLED 6/00

EMISSIONS: (Click on bubble help for Air Quality Descriptions)

Pollutants	Air Quality Description	Actual Emissions Rate		PTI Allowable	
		Short Term Rate	Tons Per Year	Short Term Rate	Tons Per Year
Particulate Matter					
PM ₁₀					
Sulfur Dioxide					
Organic Compounds				1.9 lbs/hr	8.3
Nitrogen Oxides					
Carbon Monoxide					
Lead					
Other: Air Toxics					

APPLICABLE FEDERAL RULES:

NPSPS?

NESHAP?

PSD?

OFFSET POLICY?

WHAT IS THE BAT DETERMINATION, AND WHAT IS THE BASIS FOR THE DETERMINATION?

Enter Determination water-based paints; paint overspray control

IS THIS SOURCE SUBJECT TO THE AIR TOXICS POLICY?

OPTIONAL: WHAT IS THE CAPITAL COST OF CONTROL EQUIPMENT?

\$

TOXIC AIR CONTAMINANTS

Ohio EPA's air toxics policy applies to contaminants for which the American Conference of Governmental Industrial Hygienists (ACGIH) has a listed threshold limit value.

AIR TOXICS MODELING PERFORMED*?

X

YES

NO

IDENTIFY THE AIR CONTAMINANTS:

2-butoxyethanol (CAS 111-76-2)