



State of Ohio Environmental Protection Agency

**RE: FINAL PERMIT TO INSTALL
SUMMIT COUNTY**

CERTIFIED MAIL

Street Address:

Lazarus Gov. Center TELE: (614) 644-3020 FAX: (614) 644-2329

Mailing Address:

Lazarus Gov.
Center

Application No: 16-02252

DATE: 2/6/2003

E L Stone Co
Elma Micire
2998 Eastern Rd
Norton, OH 44203

Enclosed please find an Ohio EPA Permit to Install which will allow you to install the described source(s) in a manner indicated in the permit. Because this permit contains several conditions and restrictions, I urge you to read it carefully.

The Ohio EPA is urging companies to investigate pollution prevention and energy conservation. Not only will this reduce pollution and energy consumption, but it can also save you money. If you would like to learn ways you can save money while protecting the environment, please contact our Office of Pollution Prevention at (614) 644-3469.

You are hereby notified that this action by the Director is final and may be appealed to the Ohio Environmental Review Appeals Commission pursuant to Chapter 3745.04 of the Ohio Revised Code. The appeal must be in writing and set forth the action complained of and the grounds upon which the appeal is based. It must be filed within thirty (30) days after the notice of the Directors action. A copy of the appeal must be served on the Director of the Ohio Environmental Protection Agency within three (3) days of filing with the Commission. An appeal may be filed with the Environmental Review Appeals Commission at the following address:

Environmental Review Appeals Commission
236 East Town Street, Room 300
Columbus, Ohio 43215

Very truly yours,

Michael W. Ahern

Michael W. Ahern, Supervisor
Field Operations and Permit Section
Division of Air Pollution Control

CC: USEPA

ARAQMD



STATE OF OHIO ENVIRONMENTAL PROTECTION AGENCY

**Permit To Install
Terms and Conditions**

**Issue Date: 2/6/2003
Effective Date: 2/6/2003**

FINAL PERMIT TO INSTALL 16-02252

Application Number: 16-02252
APS Premise Number: 1677020039
Permit Fee: **\$1100**
Name of Facility: E L Stone Co
Person to Contact: Elma Micire
Address: 2998 Eastern Rd
Norton, OH 44203

Location of proposed air contaminant source(s) [emissions unit(s)]:
2998 Eastern Rd
Norton, Ohio

Description of proposed emissions unit(s):
Change in Method of Operation for Coating Operations, Modification to Existing Allowable Emissions Limitations. Replaces PTI 16-1609.

The above named entity is hereby granted a Permit to Install for the above described emissions unit(s) pursuant to Chapter 3745-31 of the Ohio Administrative Code. Issuance of this permit does not constitute expressed or implied approval or agreement that, if constructed or modified in accordance with the plans included in the application, the above described emissions unit(s) of environmental pollutants will operate in compliance with applicable State and Federal laws and regulations, and does not constitute expressed or implied assurance that if constructed or modified in accordance with those plans and specifications, the above described emissions unit(s) of pollutants will be granted the necessary permits to operate (air) or NPDES permits as applicable.

This permit is granted subject to the conditions attached hereto.

Ohio Environmental Protection Agency



Director

Part I - GENERAL TERMS AND CONDITIONS

A. State and Federally Enforceable Permit To Install General Terms and Conditions

1. Monitoring and Related Recordkeeping and Reporting Requirements

- a. Except as may otherwise be provided in the terms and conditions for a specific emissions unit, the permittee shall maintain records that include the following, where applicable, for any required monitoring under this permit:
 - i. The date, place (as defined in the permit), and time of sampling or measurements.
 - ii. The date(s) analyses were performed.
 - iii. The company or entity that performed the analyses.
 - iv. The analytical techniques or methods used.
 - v. The results of such analyses.
 - vi. The operating conditions existing at the time of sampling or measurement.
- b. Each record of any monitoring data, testing data, and support information required pursuant to this permit shall be retained for a period of five years from the date the record was created. Support information shall include, but not be limited to, all calibration and maintenance records and all original strip-chart recordings for continuous monitoring instrumentation, and copies of all reports required by this permit. Such records may be maintained in computerized form.
- c. Except as may otherwise be provided in the terms and conditions for a specific emissions unit, the permittee shall submit required reports in the following manner:
 - i. Reports of any required monitoring and/or recordkeeping of federally enforceable information shall be submitted to the appropriate Ohio EPA District Office or local air agency.
 - ii. Quarterly written reports of (i) any deviations from federally enforceable emission limitations, operational restrictions, and control device operating parameter limitations, excluding deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06, that have been detected by the testing, monitoring and recordkeeping requirements specified in this permit, (ii) the probable cause of such deviations, and (iii) any corrective actions or preventive measures taken, shall be made to the appropriate Ohio EPA District Office or local air agency. The written reports shall be submitted quarterly, i.e., by January 31, April 30, July 31, and October 31 of each year and shall cover the previous

calendar quarters. See B.9 below if no deviations occurred during the quarter.

- iii. Written reports, which identify any deviations from the federally enforceable monitoring, recordkeeping, and reporting requirements contained in this permit shall be submitted to the appropriate Ohio EPA District Office or local air agency every six months, i.e., by January 31 and July 31 of each year for the previous six calendar months. If no deviations occurred during a six-month period, the permittee shall submit a semi-annual report, which states that no deviations occurred during that period.
- iv. Each written report shall be signed by a responsible official certifying that, based on information and belief formed after reasonable inquiry, the statements and information in the report are true, accurate, and complete.

2. Scheduled Maintenance/Malfunction Reporting

Any scheduled maintenance of air pollution control equipment shall be performed in accordance with paragraph (A) of OAC rule 3745-15-06. The malfunction, i.e., upset, of any emissions units or any associated air pollution control system(s) shall be reported to the appropriate Ohio EPA District Office or local air agency in accordance with paragraph (B) of OAC rule 3745-15-06. (The definition of an upset condition shall be the same as that used in OAC rule 3745-15-06(B)(1) for a malfunction.) The verbal and written reports shall be submitted pursuant to OAC rule 3745-15-06.

Except as provided in that rule, any scheduled maintenance or malfunction necessitating the shutdown or bypassing of any air pollution control system(s) shall be accompanied by the shutdown of the emission unit(s) that is (are) served by such control system(s).

3. Risk Management Plans

If the permittee is required to develop and register a risk management plan pursuant to section 112(r) of the Clean Air Act, as amended, 42 U.S.C. 7401 et seq. ("Act"), the permittee shall comply with the requirement to register such a plan.

4. Title IV Provisions

If the permittee is subject to the requirements of 40 CFR Part 72 concerning acid rain, the permittee shall ensure that any affected emissions unit complies with those requirements. Emissions exceeding any allowances that are lawfully held under Title IV of the Act, or any regulations adopted thereunder, are prohibited.

5. Severability Clause

A determination that any term or condition of this permit is invalid shall not invalidate the force or effect of any other term or condition thereof, except to the extent that any other term or condition depends in whole or in part for its operation or implementation upon the term or condition declared invalid.

6. General Requirements

- a. The permittee must comply with all terms and conditions of this permit. Any noncompliance with the federally enforceable terms and conditions of this permit constitutes a violation of the Act, and is grounds for enforcement action or for permit revocation, revocation and reissuance, or modification, or for denial of a permit renewal application.
- b. It shall not be a defense for the permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the federally enforceable terms and conditions of this permit.
- c. This permit may be modified, reopened, revoked, or revoked and reissued, for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or revocation, or of a notification of planned changes or anticipated noncompliance does not stay any term and condition of this permit.
- d. This permit does not convey any property rights of any sort, or any exclusive privilege.
- e. The permittee shall furnish to the Director of the Ohio EPA, or an authorized representative of the Director, upon receipt of a written request and within a reasonable time, any information that may be requested to determine whether cause exists for modifying, reopening or revoking this permit or to determine compliance with this permit. Upon request, the permittee shall also furnish to the Director or an authorized representative of the Director, copies of records required to be kept by this permit. For information claimed to be confidential in the submittal to the Director, if the Administrator of the U.S. EPA requests such information, the permittee may furnish such records directly to the Administrator along with a claim of confidentiality.

7. Fees

The permittee shall pay fees to the Director of the Ohio EPA in accordance with ORC section 3745.11 and OAC Chapter 3745-78. The permittee shall pay all applicable Permit To Install fees within 30 days after the issuance of this Permit To Install.

8. Federal and State Enforceability

Only those terms and conditions designated in this permit as federally enforceable, that are

required under the Act, or any of its applicable requirements, including relevant provisions designed to limit the potential to emit of a source, are enforceable by the Administrator of the U.S. EPA, the State, and citizens under the Act. All other terms and conditions of this permit shall not be federally enforceable and shall be enforceable under State law only.

9. Compliance Requirements

- a. Any document (including reports) required to be submitted and required by a federally applicable requirement in this permit shall include a certification by a responsible official that, based on information and belief formed after reasonable inquiry, the statements in the document are true, accurate, and complete.
- b. Upon presentation of credentials and other documents as may be required by law, the permittee shall allow the Director of the Ohio EPA or an authorized representative of the Director to:
 - i. At reasonable times, enter upon the permittee's premises where a source is located or the emissions-related activity is conducted, or where records must be kept under the conditions of this permit.
 - ii. Have access to and copy, at reasonable times, any records that must be kept under the conditions of this permit, subject to the protection from disclosure to the public of confidential information consistent with ORC section 3704.08.
 - iii. Inspect at reasonable times any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under this permit.
 - iv. As authorized by the Act, sample or monitor at reasonable times substances or parameters for the purpose of assuring compliance with the permit and applicable requirements.
- c. The permittee shall submit progress reports to the appropriate Ohio EPA District Office or local air agency concerning any schedule of compliance for meeting an applicable requirement. Progress reports shall be submitted semiannually, or more frequently if specified in the applicable requirement or by the Director of the Ohio EPA. Progress reports shall contain the following:
 - i. Dates for achieving the activities, milestones, or compliance required in any schedule of compliance, and dates when such activities, milestones, or compliance were achieved.
 - ii. An explanation of why any dates in any schedule of compliance were not or will not be met, and any preventive or corrective measures adopted.

10. Permit To Operate Application

- a. If the permittee is required to apply for a Title V permit pursuant to OAC Chapter 3745-77, the permittee shall submit a complete Title V permit application or a complete Title V permit modification application within twelve (12) months after commencing operation of the emissions units covered by this permit. However, if the proposed new or modified source(s) would be prohibited by the terms and conditions of an existing Title V permit, a Title V permit modification must be obtained before the operation of such new or modified source(s) pursuant to OAC rule 3745-77-04(D) and OAC rule 3745-77-08(C)(3)(d).
- b. If the permittee is required to apply for permit(s) pursuant to OAC Chapter 3745-35, the source(s) identified in this Permit To Install is (are) permitted to operate for a period of up to one year from the date the source(s) commenced operation. Permission to operate is granted only if the facility complies with all requirements contained in this permit and all applicable air pollution laws, regulations, and policies. Pursuant to OAC Chapter 3745-35, the permittee shall submit a complete operating permit application within ninety (90) days after commencing operation of the source(s) covered by this permit.

11. Best Available Technology

As specified in OAC Rule 3745-31-05, all new sources must employ Best Available Technology (BAT). Compliance with the terms and conditions of this permit will fulfill this requirement.

12. Air Pollution Nuisance

The air contaminants emitted by the emissions units covered by this permit shall not cause a public nuisance, in violation of OAC rule 3745-15-07.

B. State Only Enforceable Permit To Install General Terms and Conditions

1. Compliance Requirements

The emissions unit(s) identified in this Permit to Install shall remain in full compliance with all applicable State laws and regulations and the terms and conditions of this permit.

2. Reporting Requirements

The permittee shall submit required reports in the following manner:

- a. Reports of any required monitoring and/or recordkeeping of state-only enforceable information shall be submitted to the appropriate Ohio EPA District Office or local air agency.
- b. Except as otherwise may be provided in the terms and conditions for a specific emissions unit, quarterly written reports of (a) any deviations (excursions) from state-only required emission limitations, operational restrictions, and control device operating parameter limitations that have been detected by the testing, monitoring, and recordkeeping requirements specified in this permit, (b) the probable cause of such deviations, and (c) any corrective actions or preventive measures which have been or will be taken, shall be submitted to the appropriate Ohio EPA District Office or local air agency. If no deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted quarterly, i.e., by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters. (These quarterly reports shall exclude deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06.)

3. Permit Transfers

This Permit To Install is applicable only to the emissions unit(s) identified in the Permit To Install. Separate Permit To Install for the installation or modification of any other emissions unit(s) are required for any emissions unit for which a Permit To Install is required.

4. Termination of Permit To Install

This permit to install shall terminate within eighteen months of the effective date of the permit to install if the owner or operator has not undertaken a continuing program of installation or modification or has not entered into a binding contractual obligation to undertake and complete within a reasonable time a continuing program of installation or modification. This deadline may be extended by up to 12 months if application is made to the Director within a reasonable time before the termination date and the party shows good cause for any such extension.

5. Construction of New Sources(s)

The proposed emissions unit(s) shall be constructed in strict accordance with the plans and application submitted for this permit to the Director of the Ohio Environmental Protection Agency. There may be no deviation from the approved plans without the express, written approval of the Agency. Any deviations from the approved plans or the above conditions may lead to such sanctions and penalties as provided under Ohio law. Approval of these plans does not constitute an assurance that the proposed facilities will operate in compliance with all Ohio laws and regulations. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed sources cannot meet the requirements of this permit or cannot meet applicable standards.

If the construction of the proposed emissions unit(s) has already begun or has been completed prior to the date the Director of the Environmental Protection Agency approves the permit application and plans, the approval does not constitute expressed or implied assurance that the proposed facility has been constructed in accordance with the approved plans. The action of beginning and/or completing construction prior to obtaining the Director's approval constitutes a violation of OAC rule 3745-31-02. Furthermore, issuance of the Permit to Install does not constitute an assurance that the proposed source will operate in compliance with all Ohio laws and regulations. Approval of the plans in any case is not to be construed as an approval of the facility as constructed and/or completed. Moreover, issuance of the Permit to Install is not to be construed as a waiver of any rights that the Ohio Environmental Protection Agency (or other persons) may have against the applicant for starting construction prior to the effective date of the permit. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed facilities cannot meet the requirements of this permit or cannot meet applicable standards.

6. Public Disclosure

The facility is hereby notified that this permit, and all agency records concerning the operation of this permitted source, are subject to public disclosure in accordance with OAC rule 3745-49-03.

7. Applicability

This Permit to Install is applicable only to the emissions unit(s) identified in the Permit To Install. Separate application must be made to the Director for the installation or modification of any other emissions unit(s).

8. Construction Compliance Certification

E L Stone Co

PTI Application: **16-02252**

Issued: 2/6/2003

Facility ID: **1677020039**

The applicant shall provide Ohio EPA with a written certification (see enclosed form) that the facility has been constructed in accordance with the Permit To Install application and the terms and conditions of the Permit to Install. The certification shall be provided to Ohio EPA upon completion of construction but prior to startup of the source.

Emissions Unit ID: K001

9. Additional Reporting Requirements When There Are No Deviations of Federally Enforceable Emission Limitations, Operational Restrictions, or Control Device Operating Parameter Limitations (See Section A of This Permit)

If no deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted quarterly, i.e., by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters.

C. Permit To Install Summary of Allowable Emissions

The following information summarizes the total allowable emissions, by pollutant, based on the individual allowable emissions of each air contaminant source identified in this permit.

**SUMMARY (for informational purposes only)
 TOTAL PERMIT TO INSTALL ALLOWABLE EMISSIONS**

<u>Pollutant</u>	<u>Tons Per Year</u>
Organic Compounds	42.9*
Methyl Ethyl Ketone	2.6
Methyl Isobutyl Ketone	1.3
Toluene	6.1

* New emissions based on increase from the old allowable limits

12

E L Stone Co

PTI Application: **16-02252**

Issued: 2/6/2003

Facility ID: **1677020039**

Part II - FACILITY SPECIFIC TERMS AND CONDITIONS**A. State and Federally Enforceable Permit To Install Facility Specific Terms and Conditions**
MACT "Hammer" Requirements

1. The permittee will be subject to the National Emission Standards for Hazardous Air Pollutants (NESHAP) for National Emission Standards for Miscellaneous Metal Parts and Products Surface Coating Operations, and National Emission Standards for Plastic Parts and Products Surface Coating Operations, 40 CFR Part 63, Subpart MMMM, and PPPP. U.S. EPA failed to promulgate this standard by May 15, 2002, the Maximum Achievable Control Technology (MACT) hammer date. In accordance with 40 CFR Part 63, Subpart B (40 CFR Parts 63.50 through 63.56), the permittee shall submit an application to revise the permit to include equivalent emission limitations as a result of a case-by-case MACT determination. The application shall be submitted in two parts. The deadline to submit the Part I application, as specified in 40 CFR Part 63.53, was May 15, 2002.
2. If the final MACT standard is not promulgated by the deadline specified by U.S. EPA, the permittee shall submit the Part II application as specified in 40 CFR Part 63.53. The Part II application shall be submitted within 60 days after the deadline to promulgate the respective standard, as specified by the settlement between U.S. EPA and Sierra Club. It must contain the following information:
 - a. for a new affected source, the anticipated date of startup of operation;
 - b. the hazardous air pollutants (HAPs) emitted by each affected source in the relevant source category and an estimated total uncontrolled and controlled emission rate for HAPs from the affected source;
 - c. any existing federal, State, or local limitations or requirements applicable to the affected source;
 - d. for each affected emission point or group of affected emission points, an identification of control technology in place;
 - e. information relevant to establishing the MACT floor (or MACT emission limitation), and, at the option of the permittee, a recommended MACT floor; and
 - f. any other information reasonably needed by the permitting authority including, at the discretion of the permitting authority, information required pursuant to Subpart A of 40 CFR Part 63.

The Part II application for a MACT determination may, but is not required to, contain the following information:

- a. recommended emission limitations for the affected source and support information. (the permittee may recommend a specific design, equipment, work practice, or operational standard, or combination thereof, as an emission limitation);
- b. a description of the control technologies that would be applied to meet the emission limitation, including technical information on the design, operation, size, estimated control efficiency and any

- other information deemed appropriate by the permitting authority, and identification of the affected sources to which the control technologies must be applied; and
- c. relevant parameters to be monitored and frequency of monitoring to demonstrate continuous compliance with the MACT emission limitation over the applicable reporting period.
3. If the NESHAP is promulgated before May 15, 2004, the facility shall be subject to the rule as an existing major source with a compliance date as specified in the NESHAP. Pursuant to the Subpart, the permittee shall submit the following notifications:
- a. Within 120 days after promulgation of 40 CFR Part 63, Subpart M MMM and P PPP, the permittee shall submit an Initial Notification Report which certifies whether or not the permittee is subject to the promulgated standard. If the permittee is subject to the final standard, the following information shall also be included in the Initial Notification Report, in accordance with 40 CFR Part 63.9(b)(2):
 - i the name and mailing address of the permittee;
 - ii the physical location of the source if it is different from the mailing address;
 - iii identification of the relevant MACT standard and the source's compliance date;
 - iv. a brief description of the nature, design, size, and method of operation of the source, including the operating design capacity and an identification of each emission point of each HAP; and
 - v a statement confirming the facility is a major source for HAPs.
 - b. Within 60 days following completion of any required compliance demonstration activity specified in 40 CFR Part 63, Subpart M MMM, and P PPP, the permittee shall submit a notification of compliance status that contains the following information:
 - i. the methods used to determine compliance;
 - ii the results of any performance tests, visible emission observations, continuous monitoring systems performance evaluations, and/or other monitoring procedures or methods that were conducted;
 - iii the methods that will be used for determining continuous compliance, including a description of monitoring and reporting requirements and test methods;
 - iv the type and quantity of HAPs emitted by the source, reported in units and averaging times in accordance with the test methods specified in 40 CFR Part 63, Subpart M MMM, and P PPP;
 - v an analysis demonstrating whether the affected source is a major source or an area source;

E L Stone Co

Facility ID: 1677020039

PTI Application: 16-02252

Issued: 2/6/2003

- vi a description of the air pollution control equipment or method for each emission point, including each control device or method for each HAP and the control efficiency (percent) for each control device or method; and
- vii a statement of whether or not the permittee has complied with the requirements of 40 CFR Part 63, Subpart M, and P.

B. State Only Enforceable Permit To Install Facility Specific Terms and Conditions

None

Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
K001 - K001 B1SB2 modification of existing spray paint booth, controlled with a paper filter to control particulate emissions.	OAC rule 3745-31-05(A)(3)	7.3 tons per year of organic compounds (OC); OC emissions shall not exceed 8 lbs/hr and 40 lbs/day. The requirements of this rule also include compliance with the requirements of OAC rules 3745-17-07(A)(1), 3745-17-11(B), 3745-21-07(G)(2), and 3745-21-09(U)(2)(e).
	OAC rule 3745-17-07(A)(1)	20% opacity as a 6-minute average, except as provided by rule.
	OAC rule 3745-17-11(B)	0.551 lb/hr of particulate matter (PE).
On days when coating non-metal parts.	OAC rule 3745-21-07(G)(2)	On any day when employing photochemical reactive coatings or clean up materials to non-metal parts, OC emissions shall not exceed 8 lbs/hr and 40 lbs/day.
On days when coating metal parts.	OAC rule 3745-21-09(U)(2)(e)	See II.2. below

2. Additional Terms and Conditions

2.a None

II. Operational Restrictions

1. Prior to commencing operation of the paint spray booth for each shift, the permittee shall ensure the exhaust filters are in place and in good condition. The permittee shall also ensure the filters are operated and maintained in accordance with the manufacturer's specifications.
2. The permittee shall employ no more than 3.0 gallons of coating in any day in which parts subject to the requirements of OAC rule 3745-21-09(U) are coated in this emissions unit.

III. Monitoring and/or Recordkeeping Requirements

1. The permittee shall collect and record the following information for each day for the coating operation:
 - a. the company identification for each coating and photochemically reactive cleanup material employed;
 - b. the number of gallons of each coating and photochemically reactive cleanup material employed;
 - c. the organic compound content of each coating and photochemically reactive cleanup material, in pounds per gallon;
 - d. the total organic compound emission rate for all coatings and photochemically reactive cleanup materials, in pounds per day;
 - e. the total number of hours the emissions unit was in operation;
 - f. the average hourly organic compound emission rate for all coatings and photochemically reactive cleanup materials, i.e., (d)/(e), in pounds per hour (average); and
 - g. which rule the booth was operating under that day, and whether it was in compliance with the requirements of the rule.
2. The permittee shall maintain a record for each day for this emissions unit of whether or not the disposable paper filters were in service when the emissions unit was in operation.
3. The permittee shall collect and record the following information for each day when coating metal parts for the coating operation:
 - a. the name and identification number of each coating employed;
 - b. the volume, in gallons, of each coating employed; and

- c. the total volume, in gallons, of all of the coatings employed.
4. The permittee shall collect and record the following information for the purpose of determining annual OC emissions:
 - a. the name and identification of each cleanup material employed;
 - b. the number of gallons of each cleanup material employed;
 - c. the OC content of each cleanup material, in pounds per gallon;
 - d. the OC content of each coating, as applied, in pounds per gallon; and
 - e. the total OC emissions from all coatings and cleanup materials employed, in pounds or tons.

IV. Reporting Requirements

1. The permittee shall notify the Director (the appropriate District Office or local air agency) in writing of any record showing that the disposable paper filters were not in service when the emissions unit was in operation. The notification shall include a copy of such record and shall be sent to the Director (the appropriate District Office or local air agency) within 30 days after the event occurs.
2. The permittee shall notify the Director (the appropriate Ohio EPA District Office or local air agency) in writing of any daily record showing that the coating line employs more than the applicable maximum daily coating usage limit as specified in A.II.2 above. The notification shall include a copy of such record and shall be sent to the Director (the appropriate Ohio EPA District Office or local air agency) within 45 days after the exceedance occurs.
3. The permittee shall submit deviation (excursion) reports which include the following information:
 - a. an identification of each day during which the average hourly organic compound emissions from the coatings and cleanup materials exceeded 8 pounds per hour, and the actual average hourly organic compound emissions for each such day;
 - b. an identification of each day during which the organic compound emissions from the coatings and cleanup materials exceeded 40 pounds per day, and the actual organic compound emissions for each such day;

Emissions Unit ID: K001

- c. for the days during which a photochemically reactive material was employed to a non-metal part, an identification of each day during which the average hourly organic compound emissions from the coatings and photochemically reactive cleanup materials exceeded 8 pounds per hour, and the actual average hourly organic compound emissions for each such day; and
- d. for the days during which a photochemically reactive material was employed to a non-metal part, an identification of each day during which the organic compound emissions from the coatings and photochemically reactive cleanup materials exceeded 40 pounds per day, and the actual organic compound emissions for each such day.

These reports shall be submitted in accordance with the requirements specified in General Terms and Conditions of this permit.

- 4. The permittee shall also submit annual reports which specify the total OC emissions from this emissions unit for the previous calendar year. These reports shall be submitted by January 31 of each year.

V. Testing Requirements

- 1. Compliance with the emission limitations in Section A.I.1 of these terms and conditions shall be determined in accordance with the following methods:

- a. Emission Limitation:

20% opacity as a 6-minute average

Applicable Compliance Method:

OAC rule 3745-17-03(B)(1)

- b. Emission Limitation:

0.551 lb/hr of particulate matter

Applicable Compliance Method:

To determine the actual worst case particulate emissions rate, the following equation shall be used:

$$E = \text{maximum coating solids usage rate in pounds per hour} \times (1-TE) \times (1-CE)$$

where E = particulate emissions rate (lbs/hr);

TE = transfer efficiency, which is the ratio of the amount of coating solids deposited on the coated part to the amount of coating solids used; and

CE = fractional control efficiency of the control equipment.

c. Emission Limitations:

8 lbs/hr of organic compounds
40 lbs/day of organic compounds
7.3 tons per year of organic compounds

Applicable Compliance Method:

Daily records shall be maintained of the organic compound content of each coating and cleanup material employed, the daily usage of each coating and cleanup material employed, and the calculated average hourly and daily organic compound emission rates for all coatings and cleanup materials employed. Formulation data or USEPA Method 24 shall be used to determine the organic compound content of each coating and cleanup material.

d. Operational Restriction:

3.0 gallons of coating per day, when coating metal parts

Applicable Compliance Method:

Daily records shall be maintained of the daily usage of all coatings employed.

VI. Miscellaneous Requirements

None

B. State Only Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
K001 - K001 B1SB2 modification of existing spray paint booth, controlled with a paper filter to control particulate emissions.	Air toxic policy	See B.VI.

2. Additional Terms and Conditions

2.a None

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

1. Modeling to demonstrate compliance with the Ohio EPA's "Air Toxic Policy" was not necessary because the emissions unit's maximum annual emissions for each toxic compound will be less than 1.0 ton. OAC Chapter 3745-31 requires permittees to apply for and obtain a new or modified permit to install prior to making a "modification" as defined by OAC rule 3745-31-01. The permittee is hereby advised that changes in the composition of the materials, or use of new materials, that would cause the emissions of any pollutant that has a listed TLV to increase to above 1.0 ton per year may require the permittee to apply for and obtain a new permit to install.

Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
K009 - K009, B1SB1 modification of existing spray paint booth, controlled with a paper filter to control particulate emissions.	OAC rule 3745-31-05(A)(3)	7.3 tons per year of OC; and OC emissions shall not exceed 8 lbs/hr and 40 lbs/day. The requirements of this rule also include compliance with the requirements of OAC rules 3745-17-07(A)(1), 3745-17-11(B), 3745-21-07(G)(2), and 3745-21-09(U)(2)(e).
On days when coating non-metal parts.	OAC rule 3745-17-07(A)(1)	20% opacity as a 6-minute average, except as provided by rule.
On days when coating non-metal parts.	OAC rule 3745-17-11(B)	0.551 lb/hr of particulate matter.
On days when coating non-metal parts.	OAC rule 3745-21-07(G)(2)	On any day when employing photochemical reactive coatings or clean up materials to non-metal parts, OC emissions shall not exceed 8 lbs/hr and 40 lbs/day.
On days when coating metal parts.	OAC rule 3745-21-09(U)(2)(e)	See II.2. below

2. Additional Terms and Conditions

24

E L St

PTI A₁

Issued: 2/6/2003

Emissions Unit ID: K009

2.a None

II. Operational Restrictions

1. Prior to commencing operation of the paint spray booth for each shift, the permittee shall ensure the exhaust filters are in place and in good condition. The permittee shall also ensure the filters are operated and maintained in accordance with the manufacturer's specifications.
2. The permittee shall employ no more than 3.0 gallons of coating in any day in which parts subject to the requirements of OAC rule 3745-21-09(U) are coated in this emissions unit.

III. Monitoring and/or Recordkeeping Requirements

1. The permittee shall collect and record the following information for each day for the coating operation:
 - a. the company identification for each coating and photochemically reactive cleanup material employed;
 - b. the number of gallons of each coating and photochemically reactive cleanup material employed;
 - c. the organic compound content of each coating and photochemically reactive cleanup material, in pounds per gallon;
 - d. the total organic compound emission rate for all coatings and photochemically reactive cleanup materials, in pounds per day;
 - e. the total number of hours the emissions unit was in operation;
 - f. the average hourly organic compound emission rate for all coatings and photochemically reactive cleanup materials, i.e., (d)/(e), in pounds per hour (average); and
 - g. which rule the booth was operating under that day, and whether it was in compliance with the requirements of the rule.
2. The permittee shall maintain a record for each day for this emissions unit of whether or not the disposable paper filters were in service when the emissions unit was in operation.
3. The permittee shall collect and record the following information for each day when coating metal parts for the coating operation:

- a. the name and identification number of each coating employed;
 - b. the volume, in gallons, of each coating employed;
 - c. the total volume, in gallons, of all of the coatings employed.
4. The permittee shall collect and record the following information for the purpose of determining annual OC emissions:
- a. the name and identification of each cleanup material employed;
 - b. the number of gallons of each cleanup material employed;
 - c. the OC content of each cleanup material, in pounds per gallon;
 - d. the OC content of each coating, as applied, in pounds per gallon; and
 - e. the total OC emissions from all coatings and cleanup materials employed, in pounds or tons.

IV. Reporting Requirements

1. The permittee shall notify the Director (the appropriate District Office or local air agency) in writing of any record showing that the disposable paper filters were not in service when the emissions unit was in operation. The notification shall include a copy of such record and shall be sent to the Director (the appropriate District Office or local air agency) within 30 days after the event occurs.
2. The permittee shall notify the Director (the appropriate Ohio EPA District Office or local air agency) in writing of any daily record showing that the coating line employs more than the applicable maximum daily coating usage limit as specified in A.II.2 above. The notification shall include a copy of such record and shall be sent to the Director (the appropriate Ohio EPA District Office or local air agency) within 45 days after the exceedance occurs.
3. The permittee shall submit deviation (excursion) reports which include the following information:
 - a. an identification of each day during which the average hourly organic compound emissions from the coatings and photochemically reactive cleanup materials exceeded 8 pounds per hour, and the actual average hourly organic compound emissions for each such day; and
 - b. an identification of each day during which the organic compound emissions from the coatings and photochemically reactive cleanup materials exceeded 40 pounds per day, and the actual organic compound emissions for each such day.
 - c. for the days during which a photochemically reactive material was employed to a

non-metal part, an identification of each day during which the average hourly organic compound emissions from the coatings and photochemically reactive cleanup materials exceeded 8 pounds per hour, and the actual average hourly organic compound emissions for each such day; and

- d. for the days during which a photochemically reactive material was employed to a non-metal part, an identification of each day during which the organic compound emissions from the coatings and photochemically reactive cleanup materials exceeded 40 pounds per day, and the actual organic compound emissions for each such day.

These reports shall be submitted in accordance with the requirements specified in General Terms and Conditions of this permit.

4. The permittee shall also submit annual reports which specify the total OC emissions from this emissions unit for the previous calendar year. These reports shall be submitted by January 31 of each year.

V. Testing Requirements

1. Compliance with the emission limitations in Section A.I.1 of these terms and conditions shall be determined in accordance with the following methods:

- a. Emission Limitation:

20% opacity as a 6-minute average

Applicable Compliance Method:

OAC rule 3745-17-03(B)(1)

- b. Emission Limitation:

0.551 lb/hr of particulate matter

Applicable Compliance Method:

To determine the actual worst case particulate emissions rate, the following equation shall be used:

$$E = \text{maximum coating solids usage rate in pounds per hour} \times (1-TE) \times (1-CE)$$

where

E = particulate emissions rate (lbs/hr);

TE = transfer efficiency, which is the ratio of the amount of coating solids deposited on the coated part to the amount of coating solids used; and

CE = fractional control efficiency of the control equipment.

c. Emission Limitation:

8 lbs/hr of organic compounds

40 lbs/day of organic compounds

7.3 tons per year organic compounds

Applicable Compliance Method:

Daily records shall be maintained of the organic compound content of each coating and cleanup material employed, the daily usage of each coating and cleanup material employed, and the calculated average hourly and daily organic compound emission rates for all coatings and cleanup materials employed. Formulation data or USEPA Method 24 shall be used to determine the organic compound content of each coating and cleanup material.

d. Operational Restriction:

3.0 gallons of coating per day, when coating metal parts

Applicable Compliance Method:

Daily records shall be maintained of the daily usage of all coatings employed.

VI. Miscellaneous Requirements

None

B. State Only Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
K009 - K009, B1SB1 modification of existing spray paint booth, controlled with a paper filter to control particulate emissions.	Air toxic policy	See B.VI.

2. Additional Terms and Conditions

- 2.a None

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

1. Modeling to demonstrate compliance with the Ohio EPA's "Air Toxic Policy" was not necessary because the emissions unit's maximum annual emissions for each toxic compound will be less than 1.0 ton. OAC Chapter 3745-31 requires permittees to apply for and obtain a new or modified permit

30

E L St

PTI A₁

Issued: 2/6/2003

Emissions Unit ID: K009

to install prior to making a "modification" as defined by OAC rule 3745-31-01. The permittee is hereby advised that changes in the composition of the materials, or use of new materials, that would cause the emissions of any pollutant that has a listed TLV to increase to above 1.0 ton per year may require the permittee to apply for and obtain a new permit to install.

Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	On days when coating metal parts.	<u>Applicable Rules/Requirements</u>
K010 - K010, B6SB3 modification of existing spray paint booth, controlled with a paper filter to control particulate emissions.	On days when coating metal parts.	OAC rule 3745-31-05(A)(3)
On days when coating non-metal parts.	On days when coating non-metal parts.	OAC rule 3745-17-07(A)(1)
On days when coating non-metal parts.	On days when coating non-metal parts.	OAC rule 3745-17-11(B)
On days when coating non-metal parts.	On days when coating non-metal parts.	OAC rule 3745-21-07(G)(2)

OAC
3745-21-09(U)(2)(e)

rule

Applicable Emissions
Limitations/Control Measures

7.3 tons per year of OC;
OC emissions shall not exceed 8 lbs/hr and 40 lbs/day; 0.4 ton per year of Methyl Ethyl Ketone(MEK); 1.6 tons per year of Methyl Isobutyl Ketone (MIBK); and 1.4 tons per year of Toluene.

See 2.a below.

The requirements of this rule also include compliance with the requirements of OAC rules 3745-17-07(A)(1), 3745-17-11(B), 3745-21-07(G)(2), and 3745-21-09(U)(2)(e).

20% opacity as a 6-minute average, except as provided by rule.

0.551 lb/hr of particulate matter.

On any day when employing photochemical reactive coatings or clean up materials to non-metal parts, OC emissions shall not exceed 8 lbs/hr and 40 lbs/day.

See II.2. below

2. Additional Terms and Conditions

2.a MEK, MIBK and Toluene emissions are increased by 0.3 TPY, 0.2TPY, and 0.8 TPY respectively above the original PTI allowable limits in PTI 16-1609.

II. Operational Restrictions

1. Prior to commencing operation of the paint spray booth for each shift, the permittee shall ensure

Emissions Unit ID: K010

the exhaust filters are in place and in good condition. The permittee shall also ensure the filters are operated and maintained in accordance with the manufacturer's specifications.

2. The permittee shall employ no more than 3.0 gallons of coating in any day in which parts subject to the requirements of OAC rule 3745-21-09(U) are coated in this emissions unit.

III. Monitoring and/or Recordkeeping Requirements

1. The permittee shall collect and record the following information for each day for the coating operation:
 - a. the company identification for each coating and photochemically reactive cleanup material employed;
 - b. the number of gallons of each coating and photochemically reactive cleanup material employed;
 - c. the organic compound content of each coating and photochemically reactive cleanup material, in pounds per gallon;
 - d. the total organic compound emission rate for all coatings and photochemically reactive cleanup materials, in pounds per day;
 - e. the total number of hours the emissions unit was in operation;
 - f. the average hourly organic compound emission rate for all coatings and photochemically reactive cleanup materials, i.e., (d)/(e), in pounds per hour (average); and
 - g. which rule the booth was operating under that day, and whether it was in compliance with the requirements of the rule.
2. The permittee shall maintain a record for each day for this emissions unit of whether or not the disposable paper filters were in service when the emissions unit was in operation.
3. The permittee shall collect and record the following information for each day when coating metal parts for the coating operation:
 - a. the name and identification number of each coating employed;
 - b. the volume, in gallons, of each coating employed; and
 - c. the total volume, in gallons, of all of the coatings employed.
4. The permittee shall collect and record the following information for the purpose of determining annual OC, MEK, MIBK, and toluene emissions:

- a. the name and identification of each cleanup material employed;
- b. the number of gallons of each cleanup material employed;
- c. the OC, MEK, MIBK, and toluene content of each cleanup material, in pounds per gallon;
- d. the OC, MEK, MIBK, and toluene content of each coating, as applied, in pounds per gallon; and
- e. the total OC, MEK, MIBK, and toluene emissions from all coatings and cleanup materials employed, in pounds or tons.

IV. Reporting Requirements

1. The permittee shall notify the Director (the appropriate District Office or local air agency) in writing of any record showing that the disposable paper filters were not in service when the emissions unit was in operation. The notification shall include a copy of such record and shall be sent to the Director (the appropriate District Office or local air agency) within 30 days after the event occurs.
2. The permittee shall notify the Director (the appropriate Ohio EPA District Office or local air agency) in writing of any daily record showing that the coating line employs more than the applicable maximum daily coating usage limit as specified in A.II.2 above. The notification shall include a copy of such record and shall be sent to the Director (the appropriate Ohio EPA District Office or local air agency) within 45 days after the exceedance occurs.
3. The permittee shall submit deviation (excursion) reports which include the following information:
 - a. an identification of each day during which the average hourly organic compound emissions from the coatings and cleanup materials exceeded 8 pounds per hour, and the actual average hourly organic compound emissions for each such day;
 - b. an identification of each day during which the organic compound emissions from the coatings and cleanup materials exceeded 40 pounds per day, and the actual organic compound emissions for each such day;
 - c. for the days during which a photochemically reactive material was employed to a non-metal part, an identification of each day during which the average hourly organic compound emissions from the coatings and photochemically reactive cleanup materials exceeded 8 pounds per hour, and the actual average hourly organic compound emissions

35

E L Stone Co

PTI Application: 16-02252

Issued

Facility ID: 1677020039

Emissions Unit ID: K010

for each such day; and

- d. for the days during which a photochemically reactive material was employed to a non-metal part, an identification of each day during which the organic compound emissions from the coatings and photochemically reactive cleanup materials exceeded 40 pounds per day, and the actual organic compound emissions for each such day.

These reports shall be submitted in accordance with the requirements specified in General Terms and Conditions of this permit.

4. The permittee shall also submit annual reports which specify the total OC, MEK, MIBK, and toluene emissions from this emissions unit for the previous calendar year. These reports shall be submitted by January 31 of each year.

V. Testing Requirements

1. Compliance with the emission limitations in Section A.I.1 of these terms and conditions shall be determined in accordance with the following methods:

- a. Emission Limitation:

20% opacity as a 6-minute average

Applicable Compliance Method:

OAC rule 3745-17-03(B)(1)

- b. Emission Limitation:

0.551 lb/hr of particulate matter

Applicable Compliance Method:

To determine the actual worst case particulate emissions rate, the following equation shall be used:

$$E = \text{maximum coating solids usage rate in pounds per hour} \times (1-TE) \times (1-CE)$$

where

$$E = \text{particulate emissions rate (lbs/hr);}$$

TE = transfer efficiency, which is the ratio of the amount of coating solids deposited on the coated part to the amount of coating solids used; and

CE = fractional control efficiency of the control equipment.

c. Emission Limitations:

8 lbs/hr of organic compounds
40 lbs/day of organic compounds
7.3 tons per year of organic compounds

Applicable Compliance Method:

Daily records shall be maintained of the organic compound content of each coating and cleanup material employed, the daily usage of each coating and cleanup material employed, and the calculated average hourly and daily organic compound emission rates for all coatings and cleanup materials employed. Formulation data or USEPA Method 24 shall be used to determine the organic compound content of each coating and cleanup material.

d. Emission Limitations:

0.4 ton per year of Methyl Ethyl Ketone; 1.6 tons per year of Methyl Isobutyl Ketone; and 1.4 tons per year of Toluene.

Applicable Compliance Method:

Compliance with the annual Methyl Ethyl Ketone, Methyl Isobutyl Ketone and Toluene emission limitations shall be based upon formulation data or USEPA Method 24 to determine the individual HAP content of each of the coating and cleanup material employed along with record keeping requirements in term and condition III.4.

e. Operational Restriction:

3.0 gallons of coating per day, when coating metal parts

Applicable Compliance Method:

Daily records shall be maintained of the daily usage of all coatings employed.

VI. Miscellaneous Requirements

None

39

E L St

PTI A₁

Issued: 2/6/2003

Emissions Unit ID: K010

B. State Only Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
K010 - K010, B6SB3 modification of existing spray paint booth, controlled with a paper filter to control particulate emissions.	Air toxic policy	See B.VI.

2. Additional Terms and Conditions

2.a None

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

1. The permit to install for this emissions unit (K010) was evaluated based upon actual materials (typical ingredients and clean up materials) and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the air permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy (Air Toxic Policy) was applied for each pollutant emitted by all of the emissions units included in this permit to install using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration was then compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling:

Pollutant: Methyl Ethyl Ketone

TLV (mg/m³): 588.9 (Converted from the TWA)

Maximum Hourly Emission Rate (lbs/hr): 1.8*

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m³): 300.75

MAGLC (ug/m³): 14,042.8

Pollutant: Methyl Isobutyl Ketone

TLV (mg/m³): 204.8 (Converted from the TWA)

Maximum Hourly Emission Rate (lbs/hr): 0.11*

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m³): 17.06

MAGLC (ug/m³): 4,876.2

Pollutant: Toluene

TLV (mg/m³): 188 (Converted from the TWA)

Maximum Hourly Emission Rate (lbs/hr): 4.2*

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m³): 698.6

MAGLC (ug/m³): 4,476.2

* This was modeled for emissions units K010, K011, K017, K018, K019, and K024 through K026 combined.

Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

- a. changes in the composition of the materials used, or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the TLV value specified above;
- b. changes in the composition of the materials, or use of new materials, that would result in

an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and

- c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01(VV)(1)(a)(ii), and a modification of the existing permit to install will not be required. If the change(s) is (are) defined as a modification under other provisions of the modification definition (other than (VV)(1)(a)(ii)), then the permittee shall obtain a final permit to install prior to the change.

The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy:"

- a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
- b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and
- c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
K011 - K011, B6SB6 modification of existing spray paint booth, controlled with a paper filter to control particulate emissions.	OAC rule 3745-31-05(A)(3)	7.3 tons per year of OC; OC emissions shall not exceed 8 lbs/hr and 40 lbs/day; 0.4 ton per year of Methyl Ethyl Ketone (MEK); 1.6 tons per year of Methyl Isobutyl Ketone (MIBK); and 1.4 tons per year of Toluene.
		See 2.a below.
		The requirements of this rule also include compliance with the requirements of OAC rules 3745-17-07(A)(1), 3745-17-11(B), 3745-21-07(G)(2), and 3745-21-09(U)(2)(e).
	OAC rule 3745-17-07(A)(1)	20% opacity as a 6-minute average, except as provided by rule.
	OAC rule 3745-17-11(B)	0.551 lb/hr of particulate matter.
On days when coating non-metal parts.	OAC rule 3745-21-07(G)(2)	On any day when employing photochemical reactive coatings or clean up materials to non-metal parts, OC emissions shall not exceed 8 lbs/hr and 40 lbs/day.
On days when coating metal parts.	OAC rule 3745-21-09(U)(2)(e)	See II.2. below

2. Additional Terms and Conditions

- 2.a MEK, MIBK and Toluene emissions are increased by 0.3 TPY, 0.2TPY, and 0.8 TPY

respectively above the original PTI allowable limits in PTI 16-1609.

II. Operational Restrictions

1. Prior to commencing operation of the paint spray booth for each shift, the permittee shall ensure the exhaust filters are in place and in good condition. The permittee shall also ensure the filters are operated and maintained in accordance with the manufacturer's specifications.
2. The permittee shall employ no more than 3.0 gallons of coating in any day in which parts subject to the requirements of OAC rule 3745-21-09(U) are coated in this emissions unit.

III. Monitoring and/or Recordkeeping Requirements

1. The permittee shall collect and record the following information for each day for the coating operation:
 - a. the company identification for each coating and photochemically reactive cleanup material employed;
 - b. the number of gallons of each coating and photochemically reactive cleanup material employed;
 - c. the organic compound content of each coating and photochemically reactive cleanup material, in pounds per gallon;
 - d. the total organic compound emission rate for all coatings and photochemically reactive cleanup materials, in pounds per day;
 - e. the total number of hours the emissions unit was in operation;
 - f. the average hourly organic compound emission rate for all coatings and photochemically reactive cleanup materials, i.e., (d)/(e), in pounds per hour (average);and
 - g. which rule the booth was operating under that day, and whether it was in compliance with the requirements of the rule.
2. The permittee shall maintain a record for each day for this emissions unit of whether or not the disposable paper filters were in service when the emissions unit was in operation.
3. The permittee shall collect and record the following information for each day when coating metal

parts for the coating operation:

- a. the name and identification number of each coating employed;
 - b. the volume, in gallons, of each coating employed;
 - c. the total volume, in gallons, of all of the coatings employed.
4. The permittee shall collect and record the following information for the purpose of determining annual OC, MEK, MIBK, and toluene emissions:
- a. the name and identification of each cleanup material employed;
 - b. the number of gallons of each cleanup material employed;
 - c. the OC, MEK, MIBK, and toluene content of each cleanup material, in pounds per gallon;
 - d. the OC, MEK, MIBK, and toluene content of each coating, as applied, in pounds per gallon; and
 - e. the total OC, MEK, MIBK, and toluene emissions from all coatings and cleanup materials employed, in pounds or tons.

IV. Reporting Requirements

1. The permittee shall notify the Director (the appropriate District Office or local air agency) in writing of any record showing that the disposable paper filters were not in service when the emissions unit was in operation. The notification shall include a copy of such record and shall be sent to the Director (the appropriate District Office or local air agency) within 30 days after the event occurs.
2. The permittee shall notify the Director (the appropriate Ohio EPA District Office or local air agency) in writing of any daily record showing that the coating line employs more than the applicable maximum daily coating usage limit as specified in A.II.2 above. The notification shall include a copy of such record and shall be sent to the Director (the appropriate Ohio EPA District Office or local air agency) within 45 days after the exceedance occurs.
3. The permittee shall submit deviation (excursion) reports which include the following information:
 - a. an identification of each day during which the average hourly organic compound emissions

Emissions Unit ID: K011

from the coatings and cleanup materials exceeded 8 pounds per hour, and the actual average hourly organic compound emissions for each such day;

- b. an identification of each day during which the organic compound emissions from the coatings and cleanup materials exceeded 40 pounds per day, and the actual organic compound emissions for each such day;
- c. for the days during which a photochemically reactive material was employed to a non-metal part, an identification of each day during which the average hourly organic compound emissions from the coatings and photochemically reactive cleanup materials exceeded 8 pounds per hour, and the actual average hourly organic compound emissions for each such day; and

- d. for the days during which a photochemically reactive material was employed to a non-metal part, an identification of each day during which the organic compound emissions from the coatings and photochemically reactive cleanup materials exceeded 40 pounds per day, and the actual organic compound emissions for each such day.

These reports shall be submitted in accordance with the requirements specified in General Terms and Conditions of this permit.

- 4. The permittee shall also submit annual reports which specify the total OC, MEK, MIBK, and toluene emissions from this emissions unit for the previous calendar year. These reports shall be submitted by January 31 of each year.

V. Testing Requirements

- 1. Compliance with the emission limitations in Section A.I.1 of these terms and conditions shall be determined in accordance with the following methods:

- a. Emission Limitation:

20% opacity as a 6-minute average

Applicable Compliance Method:

OAC rule 3745-17-03(B)(1)

- b. Emission Limitation:

0.551 lb/hr of particulate matter

Applicable Compliance Method:

To determine the actual worst case particulate emissions rate, the following equation shall be used:

$$E = \text{maximum coating solids usage rate in pounds per hour} \times (1-TE) \times (1-CE)$$

where

$$E = \text{particulate emissions rate (lbs/hr);}$$

TE = transfer efficiency, which is the ratio of the amount of coating solids deposited on the coated part to the amount of coating solids used; and

CE = fractional control efficiency of the control equipment.

c. Emission Limitation:

8 lbs/hr of organic compounds
40 lbs/day of organic compounds
7.3 tons per year organic compounds

Applicable Compliance Method:

Daily records shall be maintained of the organic compound content of each coating and cleanup material employed, the daily usage of each coating and cleanup material employed, and the calculated average hourly and daily organic compound emission rates for all coatings and cleanup materials employed. Formulation data or USEPA Method 24 shall be used to determine the organic compound content of each coating and cleanup material.

d. Emission Limitation:

0.4 ton per year of Methyl Ethyl Ketone (MEK); 1.6 tons per year of Methyl Isobutyl Ketone (MIBK); and 1.4 tons per year of Toluene.

Applicable Compliance Method:

Compliance with the annual Methyl Ethyl Ketone, Methyl Isobutyl Ketone and Toluene emission limitations shall be based upon formulation data or USEPA Method 24 to determine the individual HAP content of each of the coating and cleanup material employed along with record keeping requirements in term and condition III.4.

e. Operational Restriction:

3.0 gallons of coating per day, when coating metal parts

Applicable Compliance Method:

Daily records shall be maintained of the daily usage of all coatings employed.

49

E L Stone Co

PTI Application: 16-02252

Issued

Facility ID: 1677020039

Emissions Unit ID: K011

VI. Miscellaneous Requirements

None

B. State Only Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
K011 - K011, B6SB6 modification of existing spray paint booth, controlled with a paper filter to control particulate emissions.	Air toxic policy	See B.VI.

2. Additional Terms and Conditions

2.a None

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

1. The permit to install for this emissions unit (K010) was evaluated based upon actual materials (typical ingredients and clean up materials) and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the air permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy (Air Toxic Policy) was applied for each pollutant emitted by all of the emissions units included in this permit to install using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration was then compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling:

Pollutant: Methyl Ethyl Ketone

TLV (mg/m³): 588.9 (Converted from the TWA)

Maximum Hourly Emission Rate (lbs/hr): 1.8*

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m³): 300.75

MAGLC (ug/m³): 14,042.8

Pollutant: Methyl Isobutyl Ketone

TLV (mg/m³): 204.8 (Converted from the TWA)

Maximum Hourly Emission Rate (lbs/hr): 0.11*

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m³): 17.06

MAGLC (ug/m³): 4,876.2

Pollutant: Toluene

TLV (mg/m³): 188 (Converted from the TWA)

Maximum Hourly Emission Rate (lbs/hr): 4.2*

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m³): 698.6

MAGLC (ug/m³): 4,476.2

* This was modeled for emissions units K010, K011, K017, K018, K019, and K024 through K026 combined.

Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

- a. changes in the composition of the materials used, or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the TLV value specified above;
- b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and
- c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01(VV)(1)(a)(ii), and a modification of the existing permit to install will not be required. If the change(s) is (are) defined as a modification under other provisions of the modification definition (other than (VV)(1)(a)(ii)), then the permittee shall obtain a final permit to install prior to the change.

The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy:"

- a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
- b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and
- c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
K017 - K017, B6SB4 modification of existing spray paint booth, controlled with a paper filter to control particulate emissions.	OAC rule 3745-31-05(A)(3)	7.3 tons per year of OC; OC emissions shall not exceed 8 lbs/hr and 40 lbs/day; 0.4 ton per year Methyl Ethyl Ketone (MEK); 1.6 tons per year Methyl Isobutyl Ketone (MIBK); and 1.4 tons per year Toluene.
		See 2.a below.
		The requirements of this rule also include compliance with the requirements of OAC rules 3745-17-07(A)(1), 3745-17-11(B), 3745-21-07(G)(2), and 3745-21-09(U)(2)(e).
	OAC rule 3745-17-07(A)(1)	20% opacity as a 6-minute average, except as provided by rule.
	OAC rule 3745-17-11(B)	0.551 lb/hr of particulate matter.
On days when coating non-metal parts.	OAC rule 3745-21-07(G)(2)	On any day when employing photochemical reactive coatings or clean up materials to non-metal parts, OC emissions shall not exceed 8 lbs/hr and 40 lbs/day.
On days when coating metal parts.	OAC rule 3745-21-09(U)(2)(e)	See II.2. below

2. Additional Terms and Conditions

- 2.a MEK, MIBK and Toluene emissions are increased by 0.3 TPY, 0.2TPY, and 0.8 TPY

respectively above the original PTI allowable limits in PTI 16-1609.

II. Operational Restrictions

1. Prior to commencing operation of the paint spray booth for each shift, the permittee shall ensure the exhaust filters are in place and in good condition. The permittee shall also ensure the filters are operated and maintained in accordance with the manufacturer's specifications.
2. The permittee shall employ no more than 3.0 gallons of coating in any day in which parts subject to the requirements of OAC rule 3745-21-09(U) are coated in this emissions unit.

III. Monitoring and/or Recordkeeping Requirements

1. The permittee shall collect and record the following information for each day for the coating operation:
 - a. the company identification for each coating and photochemically reactive cleanup material employed;
 - b. the number of gallons of each coating and photochemically reactive cleanup material employed;
 - c. the organic compound content of each coating and photochemically reactive cleanup material, in pounds per gallon;
 - d. the total organic compound emission rate for all coatings and photochemically reactive cleanup materials, in pounds per day;
 - e. the total number of hours the emissions unit was in operation;
 - f. the average hourly organic compound emission rate for all coatings and photochemically reactive cleanup materials, i.e., (d)/(e), in pounds per hour (average); and
 - g. which rule the booth was operating under that day, and whether it was in compliance with the requirements of the rule.
2. The permittee shall maintain a record for each day for this emissions unit of whether or not the disposable paper filters were in service when the emissions unit was in operation.
3. The permittee shall collect and record the following information for each day when coating metal

parts for the coating operation:

- a. the name and identification number of each coating employed;
 - b. the volume, in gallons, of each coating employed; and
 - c. the total volume, in gallons, of all of the coatings employed.
4. The permittee shall collect and record the following information for the purpose of determining annual OC, MEK, MIBK, and toluene emissions:
- a. the name and identification of each cleanup material employed;
 - b. the number of gallons of each cleanup material employed;
 - c. the OC, MEK, MIBK, and toluene content of each cleanup material, in pounds per gallon;
 - d. the OC, MEK, MIBK, and toluene content of each coating, as applied, in pounds per gallon; and
 - e. the total OC, MEK, MIBK, and toluene emissions from all coatings and cleanup materials employed, in pounds or tons.

IV. Reporting Requirements

1. The permittee shall notify the Director (the appropriate District Office or local air agency) in writing of any record showing that the disposable paper filters were not in service when the emissions unit was in operation. The notification shall include a copy of such record and shall be sent to the Director (the appropriate District Office or local air agency) within 30 days after the event occurs.
2. The permittee shall notify the Director (the appropriate Ohio EPA District Office or local air agency) in writing of any daily record showing that the coating line employs more than the applicable maximum daily coating usage limit as specified in A.II.2 above. The notification shall include a copy of such record and shall be sent to the Director (the appropriate Ohio EPA District Office or local air agency) within 45 days after the exceedance occurs.
3. The permittee shall submit deviation (excursion) reports which include the following information:
 - a. an identification of each day during which the average hourly organic compound emissions from the coatings and cleanup materials exceeded 8 pounds per hour, and the actual average hourly organic compound emissions for each such day;
 - b. an identification of each day during which the organic compound emissions from the coatings and cleanup materials exceeded 40 pounds per day, and the actual organic compound emissions for each such day;

- c. for the days during which a photochemically reactive material was employed to a non-metal part, an identification of each day during which the average hourly organic compound emissions from the coatings and photochemically reactive cleanup materials exceeded 8 pounds per hour, and the actual average hourly organic compound emissions for each such day; and
- d. for the days during which a photochemically reactive material was employed to a non-metal part, an identification of each day during which the organic compound emissions from the coatings and photochemically reactive cleanup materials exceeded 40 pounds per day, and the actual organic compound emissions for each such day.

These reports shall be submitted in accordance with the requirements specified in General Terms and Conditions of this permit.

4. The permittee shall also submit annual reports which specify the total OC MEK, MIBK, and toluene emissions from this emissions unit for the previous calendar year. These reports shall be submitted by January 31 of each year.

V. Testing Requirements

1. Compliance with the emission limitations in Section A.I.1 of these terms and conditions shall be determined in accordance with the following methods:
 - a. Emission Limitation:

20% opacity as a 6-minute average

Applicable Compliance Method:

OAC rule 3745-17-03(B)(1)
 - b. Emission Limitation:

0.551 lb/hr of particulate matter

Applicable Compliance Method:

To determine the actual worst case particulate emissions rate, the following equation shall be used:

$E = \text{maximum coating solids usage rate in pounds per hour} \times (1-TE) \times (1-CE)$

where

$E = \text{particulate emissions rate (lbs/hr);}$

$TE = \text{transfer efficiency, which is the ratio of the amount of coating solids deposited on the coated part to the amount of coating solids used; and}$

$CE = \text{fractional control efficiency of the control equipment}$

c. Emission Limitations:

8 lbs/hr of organic compounds
40 lbs/day of organic compounds
7.3 tons per year organic compounds

Applicable Compliance Method:

Daily records shall be maintained of the organic compound content of each coating and cleanup material employed, the daily usage of each coating and cleanup material employed, and the calculated average hourly and daily organic compound emission rates for all coatings and cleanup materials employed. Formulation data or USEPA Method 24 shall be used to determine the organic compound content of each coating and cleanup material.

d. Emission Limitations:

0.4 ton per year Methyl Ethyl Ketone (MEK); 1.6 tons per year Methyl Isobutyl Ketone (MIBK); and 1.4 tons per year Toluene.

Applicable Compliance Method:

Compliance with the annual Methyl Ethyl Ketone, Methyl Isobutyl Ketone and Toluene emission limitations shall be based upon formulation data or USEPA Method 24 to determine the individual HAP content of each of the coating and cleanup material employed along with record keeping requirements in term and condition III.4.

e. Operational Restriction:

3.0 gallons of coating per day, when coating metal parts

Applicable Compliance Method:

Daily records shall be maintained of the daily usage of all coatings employed.

VI. Miscellaneous Requirements

None

B. State Only Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
K017 - K017, B6SB4 modification of existing spray paint booth, controlled with a paper filter to control particulate emissions.	Air toxic policy	See B.VI.

2. Additional Terms and Conditions

2.a None

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

1. The permit to install for this emissions unit (K010) was evaluated based upon actual materials (typical ingredients and clean up materials) and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the air permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy (Air Toxic Policy) was applied for each

pollutant emitted by all of the emissions units included in this permit to install using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration was then compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling:

Pollutant: Methyl Ethyl Ketone

TLV (mg/m³): 588.9 (Converted from the TWA)

Maximum Hourly Emission Rate (lbs/hr): 1.8*

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m³): 300.75

MAGLC (ug/m³): 14,042.8

Pollutant: Methyl Isobutyl Ketone

TLV (mg/m³): 204.8 (Converted from the TWA)

Maximum Hourly Emission Rate (lbs/hr): 0.11*

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m³): 17.06

MAGLC (ug/m³): 4,876.2

Pollutant: Toluene

TLV (mg/m³): 188 (Converted from the TWA)

Maximum Hourly Emission Rate (lbs/hr): 4.2*

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m³): 698.6

MAGLC (ug/m³): 4,476.2

* This was modeled for emissions units K010, K011, K017, K018, K019, and K024 through K026 combined.

Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

- a. changes in the composition of the materials used, or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the TLV value specified above;

Emissions Unit ID: K017

- b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and
- c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01(VV)(1)(a)(ii), and a modification of the existing permit to install will not be required. If the change(s) is (are) defined as a modification under other provisions of the modification definition (other than (VV)(1)(a)(ii)), then the permittee shall obtain a final permit to install prior to the change.

The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy:"

- a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
- b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and
- c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	On days when coating metal parts.	<u>Applicable Rules/Requirements</u>
K018 - K018, B6SB2 modification of existing spray paint booth, controlled with a paper filter to control particulate emissions.	On days when coating metal parts.	OAC rule 3745-31-05(A)(3)
On days when coating non-metal parts.	On days when coating non-metal parts.	OAC rule 3745-17-07(A)(1)
On days when coating non-metal parts.	On days when coating non-metal parts.	OAC rule 3745-17-11(B)
On days when coating non-metal parts.	On days when coating non-metal parts.	OAC rule 3745-21-07(G)(2)

OAC 3745-21-09(U)(2)(e)	rule	Applicable Emissions <u>Limitations/Control Measures</u>
		<p>7.3 tons per year of OC; OC emissions shall not exceed 8 lbs/hr and 40 lbs/day; 0.4 ton per year of Methyl Ethyl Ketone (MEK); 1.6 tons per year of Methyl Isobutyl Ketone (MIBK); and 1.4 tons per year of Toluene.</p> <p>See 2.a below.</p> <p>The requirements of this rule also include compliance with the requirements of OAC rules 3745-17-07(A)(1), 3745-17-11(B), 3745-21-07(G)(2), and 3745-21-09(U)(2)(e).</p> <p>20% opacity as a 6-minute average, except as provided by rule.</p> <p>0.551 lb/hr of particulate matter.</p> <p>On any day when employing photochemical reactive coatings or clean up materials to non-metal parts, OC emissions shall not exceed 8 lbs/hr and 40 lbs/day.</p> <p>See II.2. below</p>

2. Additional Terms and Conditions

- 2.a** MEK, MIBK and Toluene emissions are increased by 0.3 TPY, 0.2TPY, and 0.8 TPY respectively above the original PTI allowable limits in PTI 16-1609.

II. Operational Restrictions

- Prior to commencing operation of the paint spray booth for each shift, the permittee shall ensure the exhaust filters are in place and in good condition. The permittee shall also ensure the filters are operated and maintained in accordance with the manufacturer's specifications.
- The permittee shall employ no more than 3.0 gallons of coating in any day in which parts subject to the requirements of OAC rule 3745-21-09(U) are coated in this emissions unit.

III. Monitoring and/or Recordkeeping Requirements

1. The permittee shall collect and record the following information for each day for the coating operation:
 - a. the company identification for each coating and photochemically reactive cleanup material employed;
 - b. the number of gallons of each coating and photochemically reactive cleanup material employed;
 - c. the organic compound content of each coating and photochemically reactive cleanup material, in pounds per gallon;
 - d. the total organic compound emission rate for all coatings and photochemically reactive cleanup materials, in pounds per day;
 - e. the total number of hours the emissions unit was in operation;
 - f. the average hourly organic compound emission rate for all coatings and photochemically reactive cleanup materials, i.e., (d)/(e), in pounds per hour (average); and
 - g. which rule the booth was operating under that day, and whether it was in compliance with the requirements of the rule.
2. The permittee shall maintain a record for each day for this emissions unit of whether or not the disposable paper filters were in service when the emissions unit was in operation.
3. The permittee shall collect and record the following information for each day when coating metal parts for the coating operation:
 - a. the name and identification number of each coating employed;
 - b. the volume, in gallons, of each coating employed;
 - c. the total volume, in gallons, of all of the coatings employed.
4. The permittee shall collect and record the following information for the purpose of determining annual OC, MEK, MIBK, and toluene emissions:

- a. the name and identification of each cleanup material employed;
- b. the number of gallons of each cleanup material employed;
- c. the OC, MEK, MIBK, and toluene content of each cleanup material, in pounds per gallon;
- d. the OC, MEK, MIBK, and toluene content of each coating, as applied, in pounds per gallon; and
- e. the total OC, MEK, MIBK, and toluene emissions from all coatings and cleanup materials employed, in pounds or tons.

IV. Reporting Requirements

1. The permittee shall notify the Director (the appropriate District Office or local air agency) in writing of any record showing that the disposable paper filters were not in service when the emissions unit was in operation. The notification shall include a copy of such record and shall be sent to the Director (the appropriate District Office or local air agency) within 30 days after the event occurs.
2. The permittee shall notify the Director (the appropriate Ohio EPA District Office or local air agency) in writing of any daily record showing that the coating line employs more than the applicable maximum daily coating usage limit as specified in A.II.2 above. The notification shall include a copy of such record and shall be sent to the Director (the appropriate Ohio EPA District Office or local air agency) within 45 days after the exceedance occurs.
3. The permittee shall submit deviation (excursion) reports which include the following information:
 - a. an identification of each day during which the average hourly organic compound emissions from the coatings and cleanup materials exceeded 8 pounds per hour, and the actual average hourly organic compound emissions for each such day;
 - b. an identification of each day during which the organic compound emissions from the coatings and cleanup materials exceeded 40 pounds per day, and the actual organic compound emissions for each such day;
 - c. for the days during which a photochemically reactive material was employed to a non-metal part, an identification of each day during which the average hourly organic compound emissions from the coatings and photochemically reactive cleanup materials

Emissions Unit ID: K018

exceeded 8 pounds per hour, and the actual average hourly organic compound emissions for each such day; and

- d. for the days during which a photochemically reactive material was employed to a non-metal part, an identification of each day during which the organic compound emissions from the coatings and photochemically reactive cleanup materials exceeded 40 pounds per day, and the actual organic compound emissions for each such day.

These reports shall be submitted in accordance with the requirements specified in General Terms and Conditions of this permit.

4. The permittee shall also submit annual reports which specify the total OC, MEK, MIBK, and toluene emissions from this emissions unit for the previous calendar year. These reports shall be submitted by January 31 of each year.

V. Testing Requirements

1. Compliance with the emission limitations in Section A.I.1 of these terms and conditions shall be determined in accordance with the following methods:

- a. Emission Limitation:

20% opacity as a 6-minute average

Applicable Compliance Method:

OAC rule 3745-17-03(B)(1)

- b. Emission Limitation:

0.551 lb/hr of particulate matter

Applicable Compliance Method:

To determine the actual worst case particulate emissions rate, the following equation shall be used:

$$E = \text{maximum coating solids usage rate in pounds per hour} \times (1-TE) \times (1-CE)$$

where

$$E = \text{particulate emissions rate (lbs/hr);}$$

$$TE = \text{transfer efficiency, which is the ratio of the amount of coating solids deposited on the coated part to the amount of coating solids used; and}$$

68

E L St

PTI A₁

Issued: 2/6/2003

Emissions Unit ID: K018

CE = fractional control efficiency of the control equipment

c. Emission Limitations:

8 lbs/hr of organic compounds
40 lbs/day of organic compounds
7.3 tons per year of organic compounds

Applicable Compliance Method:

Daily records shall be maintained of the organic compound content of each coating and cleanup material employed, the daily usage of each coating and cleanup material employed, and the calculated average hourly and daily organic compound emission rates for all coatings and cleanup materials employed. Formulation data or USEPA Method 24 shall be used to determine the organic compound content of each coating and cleanup material.

d. Emission Limitations:

0.4 ton per year of Methyl Ethyl Ketone (MEK); 1.6 tons per year of Methyl Isobutyl Ketone (MIBK); and 1.4 tons per year of Toluene.

Applicable Compliance Method:

Compliance with the annual Methyl Ethyl Ketone, Methyl Isobutyl Ketone and Toluene emission limitations shall be based upon formulation data or USEPA Method 24 to determine the individual HAP content of each of the coating and cleanup material employed along with record keeping requirements in term and condition III.4.

e. Operational Restriction:

3.0 gallons of coating per day, when coating metal parts

Applicable Compliance Method:

Daily records shall be maintained of the daily usage of all coatings employed.

VI. Miscellaneous Requirements

None

B. State Only Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
K018 - K018, B6SB2 modification of existing spray paint booth, controlled with a paper filter to control particulate emissions.	Air toxic policy	See B.VI.

2. Additional Terms and Conditions

2.a None

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

1. The permit to install for this emissions unit (K010) was evaluated based upon actual materials (typical ingredients and clean up materials) and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the air permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy (Air Toxic Policy) was applied for each

pollutant emitted by all of the emissions units included in this permit to install using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration was then compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling:

Pollutant: Methyl Ethyl Ketone

TLV (mg/m³): 588.9 (Converted from the TWA)

Maximum Hourly Emission Rate (lbs/hr): 1.8*

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m³): 300.75

MAGLC (ug/m³): 14,042.8

Pollutant: Methyl Isobutyl Ketone

TLV (mg/m³): 204.8 (Converted from the TWA)

Maximum Hourly Emission Rate (lbs/hr): 0.11*

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m³): 17.06

MAGLC (ug/m³): 4,876.2

Pollutant: Toluene

TLV (mg/m³): 188 (Converted from the TWA)

Maximum Hourly Emission Rate (lbs/hr): 4.2*

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m³): 698.6

MAGLC (ug/m³): 4,476.2

* This was modeled for emissions units K010, K011, K017, K018, K019, and K024 through K026 combined.

Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

- a. changes in the composition of the materials used, or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the TLV value specified above;

- b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and
- c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01(VV)(1)(a)(ii), and a modification of the existing permit to install will not be required. If the change(s) is (are) defined as a modification under other provisions of the modification definition (other than (VV)(1)(a)(ii)), then the permittee shall obtain a final permit to install prior to the change.

The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy:"

- a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
- b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and
- c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
K019 - K019, B6SB1 modification of existing spray paint booth, controlled with a paper filter to control particulate emissions.	OAC rule 3745-31-05(A)(3)	7.3 tons per year of OC; OC emissions shall not exceed 8 lbs/hr and 40 lbs/day.; 0.4 ton per year of Methyl Ethyl Ketone (MEK); 1.6 tons per year of Methyl Isobutyl Ketone (MIBK); and 1.4 tons per year of Toluene. See 2.a below. The requirements of this rule also include compliance with the requirements of OAC rules 3745-17-07(A)(1), 3745-17-11(B), 3745-21-07(G)(2), and 3745-21-09(U)(2)(e).
On days when coating non-metal parts.	OAC rule 3745-17-07(A)(1)	20% opacity as a 6-minute average, except as provided by rule.
On days when coating non-metal parts.	OAC rule 3745-17-11(B)	0.551 lb/hr of particulate matter.
On days when coating non-metal parts.	OAC rule 3745-21-07(G)(2)	On any day when employing photochemical reactive coatings or clean up materials to non-metal parts, OC emissions shall not exceed 8 lbs/hr and 40 lbs/day.
On days when coating metal parts.	OAC rule 3745-21-09(U)(2)(e)	See II.2. below

2. Additional Terms and Conditions

- 2.a MEK, MIBK and Toluene emissions are increased by 0.3 TPY, 0.2TPY, and 0.8 TPY

respectively above the original PTI allowable limits in PTI 16-1609.

II. Operational Restrictions

1. Prior to commencing operation of the paint spray booth for each shift, the permittee shall ensure the exhaust filters are in place and in good condition. The permittee shall also ensure the filters are operated and maintained in accordance with the manufacturer's specifications.
2. The permittee shall employ no more than 3.0 gallons of coating in any day in which parts subject to the requirements of OAC rule 3745-21-09(U) are coated in this emissions unit.

III. Monitoring and/or Recordkeeping Requirements

1. The permittee shall collect and record the following information for each day for the coating operation:
 - a. the company identification for each coating and photochemically reactive cleanup material employed;
 - b. the number of gallons of each coating and photochemically reactive cleanup material employed;
 - c. the organic compound content of each coating and photochemically reactive cleanup material, in pounds per gallon;
 - d. the total organic compound emission rate for all coatings and photochemically reactive cleanup materials, in pounds per day;
 - e. the total number of hours the emissions unit was in operation;
 - f. the average hourly organic compound emission rate for all coatings and photochemically reactive cleanup materials, i.e., (d)/(e), in pounds per hour (average); and
 - g. which rule the booth was operating under that day, and whether it was in compliance with the requirements of the rule.
2. The permittee shall maintain a record for each day for this emissions unit of whether or not the disposable paper filters were in service when the emissions unit was in operation.
3. The permittee shall collect and record the following information for each day when coating metal

parts for the coating operation:

- a. the name and identification number of each coating employed;
 - b. the volume, in gallons, of each coating employed;
 - c. the total volume, in gallons, of all of the coatings employed.
4. The permittee shall collect and record the following information for the purpose of determining annual OC, MEK, MIBK, and toluene emissions:
- a. the name and identification of each cleanup material employed;
 - b. the number of gallons of each cleanup material employed;
 - c. the OC, MEK, MIBK, and toluene content of each cleanup material, in pounds per gallon;
 - d. the OC, MEK, MIBK, and toluene content of each coating, as applied, in pounds per gallon; and
 - e. the total OC, MEK, MIBK, and toluene emissions from all coatings and cleanup materials employed, in pounds or tons.

IV. Reporting Requirements

1. The permittee shall notify the Director (the appropriate District Office or local air agency) in writing of any record showing that the disposable paper filters were not in service when the emissions unit was in operation. The notification shall include a copy of such record and shall be sent to the Director (the appropriate District Office or local air agency) within 30 days after the event occurs.
2. The permittee shall notify the Director (the appropriate Ohio EPA District Office or local air agency) in writing of any daily record showing that the coating line employs more than the applicable maximum daily coating usage limit as specified in A.II.2 above. The notification shall include a copy of such record and shall be sent to the Director (the appropriate Ohio EPA District Office or local air agency) within 45 days after the exceedance occurs.
3. The permittee shall submit deviation (excursion) reports which include the following information:
 - a. an identification of each day during which the average hourly organic compound emissions

Emissions Unit ID: K019

from the coatings and cleanup materials exceeded 8 pounds per hour, and the actual average hourly organic compound emissions for each such day; and

- b. an identification of each day during which the organic compound emissions from the coatings and cleanup materials exceeded 40 pounds per day, and the actual organic compound emissions for each such day.
- c. for the days during which a photochemically reactive material was employed to a non-metal part, an identification of each day during which the average hourly organic compound emissions from the coatings and photochemically reactive cleanup materials exceeded 8 pounds per hour, and the actual average hourly organic compound emissions for each such day; and
- d. for the days during which a photochemically reactive material was employed to a non-metal part, an identification of each day during which the organic compound emissions from the coatings and photochemically reactive cleanup materials exceeded 40 pounds per day, and the actual organic compound emissions for each such day.

These reports shall be submitted in accordance with the requirements specified in General Terms and Conditions of this permit.

4. The permittee shall also submit annual reports which specify the total OC MEK, MIBK, and toluene emissions from this emissions unit for the previous calendar year. These reports shall be submitted by January 31 of each year.

V. Testing Requirements

1. Compliance with the emission limitations in Section A.I.1 of these terms and conditions shall be determined in accordance with the following methods:

- a. Emission Limitation:

20% opacity as a 6-minute average

Applicable Compliance Method:

OAC rule 3745-17-03(B)(1)

- b. Emission Limitation:

0.551 lb/hr of particulate matter

Applicable Compliance Method:

To determine the actual worst case particulate emissions rate, the following equation shall be used:

$E = \text{maximum coating solids usage rate in pounds per hour} \times (1-TE) \times (1-CE)$

where

$E = \text{particulate emissions rate (lbs/hr)}$;

$TE = \text{transfer efficiency, which is the ratio of the amount of coating solids deposited on the coated part to the amount of coating solids used; and}$

$CE = \text{fractional control efficiency of the control equipment.}$

c. Emission Limitations:

8 lbs/hr of organic compounds
40 lbs/day of organic compounds
7.3 tons per year of organic compounds

Applicable Compliance Method:

Daily records shall be maintained of the organic compound content of each coating and cleanup material employed, the daily usage of each coating and cleanup material employed, and the calculated average hourly and daily organic compound emission rates for all coatings and cleanup materials employed. Formulation data or USEPA Method 24 shall be used to determine the organic compound content of each coating and cleanup material.

d. Emission Limitations:

0.4 ton per year of Methyl Ethyl Ketone (MEK); 1.6 tons per year of Methyl Isobutyl Ketone (MIBK); and 1.4 tons per year of Toluene.

Applicable Compliance Method:

Compliance with the annual Methyl Ethyl Ketone, Methyl Isobutyl Ketone and Toluene emission limitations shall be based upon formulation data or USEPA Method 24 to determine the individual HAP content of each of the coating and cleanup material employed along with record keeping requirements in term and condition III.4.

e. Operational Restriction:

3.0 gallons of coating per day, when coating metal parts

Applicable Compliance Method:

Daily records shall be maintained of the daily usage of all coatings employed.

VI. Miscellaneous Requirements

None

B. State Only Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
K019 - K019, B6SB1 modification of existing spray paint booth, controlled with a paper filter to control particulate emissions.	Air toxic policy	See B.VI.

2. Additional Terms and Conditions

2.a None

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

1. The permit to install for this emissions unit (K010) was evaluated based upon actual materials (typical ingredients and clean up materials) and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the air permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy (Air Toxic Policy) was applied for each

pollutant emitted by all of the emissions units included in this permit to install using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration was then compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling:

Pollutant: Methyl Ethyl Ketone

TLV (mg/m³): 588.9 (Converted from the TWA)

Maximum Hourly Emission Rate (lbs/hr): 1.8*

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m³): 300.75

MAGLC (ug/m³): 14,042.8

Pollutant: Methyl Isobutyl Ketone

TLV (mg/m³): 204.8 (Converted from the TWA)

Maximum Hourly Emission Rate (lbs/hr): 0.11*

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m³): 17.06

MAGLC (ug/m³): 4,876.2

Pollutant: Toluene

TLV (mg/m³): 188 (Converted from the TWA)

Maximum Hourly Emission Rate (lbs/hr): 4.2*

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m³): 698.6

MAGLC (ug/m³): 4,476.2

* This was modeled for emissions units K010, K011, K017, K018, K019, and K024 through K026 combined.

Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

- a. changes in the composition of the materials used, or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the TLV value specified above;

Emissions Unit ID: K019

- b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and
- c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01(VV)(1)(a)(ii), and a modification of the existing permit to install will not be required. If the change(s) is (are) defined as a modification under other provisions of the modification definition (other than (VV)(1)(a)(ii)), then the permittee shall obtain a final permit to install prior to the change.

The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy:"

- a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
- b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and
- c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
K020 - K020, B1SB6 modification of existing spray paint booth, controlled with a paper filter to control particulate emissions.	OAC rule 3745-31-05(A)(3)	7.3 tons per year of OC; and OC emissions shall not exceed 8 lbs/hr and 40 lbs/day. The requirements of this rule also include compliance with the requirements of OAC rules 3745-17-07(A)(1), 3745-17-11(B), 3745-21-07(G)(2), and 3745-21-09(U)(2)(e).
	OAC rule 3745-17-07(A)(1)	20% opacity as a 6-minute average, except as provided by rule.
	OAC rule 3745-17-11(B)	0.551 lb/hr of particulate matter.
On days when coating non-metal parts.	OAC rule 3745-21-07(G)(2)	On any day when employing photochemical reactive coatings or clean up materials to non-metal parts, OC emissions shall not exceed 8 lbs/hr and 40 lbs/day.
On days when coating metal parts.	OAC rule 3745-21-09(U)(2)(e)	See II.2. below

2. Additional Terms and Conditions

2.a None

II. Operational Restrictions

1. Prior to commencing operation of the paint spray booth for each shift, the permittee shall ensure the exhaust filters are in place and in good condition. The permittee shall also ensure the filters are operated and maintained in accordance with the manufacturer's specifications.
2. The permittee shall employ no more than 3.0 gallons of coating in any day in which parts subject to the requirements of OAC rule 3745-21-09(U) are coated in this emissions unit.

III. Monitoring and/or Recordkeeping Requirements

1. The permittee shall collect and record the following information for each day for the coating operation:
 - a. the company identification for each coating and photochemically reactive cleanup material employed;
 - b. the number of gallons of each coating and photochemically reactive cleanup material employed;
 - c. the organic compound content of each coating and photochemically reactive cleanup material, in pounds per gallon;
 - d. the total organic compound emission rate for all coatings and photochemically reactive cleanup materials, in pounds per day;
 - e. the total number of hours the emissions unit was in operation;
 - f. the average hourly organic compound emission rate for all coatings and photochemically reactive cleanup materials, i.e., (d)/(e), in pounds per hour (average); and
 - g. which rule the booth was operating under that day, and whether it was in compliance with the requirements of the rule.
2. The permittee shall maintain a record for each day for this emissions unit of whether or not the disposable paper filters were in service when the emissions unit was in operation.
3. The permittee shall collect and record the following information for each day when coating metal

parts for the coating operation:

- a. the name and identification number of each coating employed;
 - b. the volume, in gallons, of each coating employed;
 - c. the total volume, in gallons, of all of the coatings employed.
4. The permittee shall collect and record the following information for the purpose of determining annual OC emissions:
- a. the name and identification of each cleanup material employed;
 - b. the number of gallons of each cleanup material employed;
 - c. the OC content of each cleanup material, in pounds per gallon;
 - d. the OC content of each coating, as applied, in pounds per gallon; and
 - e. the total OC emissions from all coatings and cleanup materials employed, in pounds or tons.

IV. Reporting Requirements

1. The permittee shall notify the Director (the appropriate District Office or local air agency) in writing of any record showing that the disposable paper filters were not in service when the emissions unit was in operation. The notification shall include a copy of such record and shall be sent to the Director (the appropriate District Office or local air agency) within 30 days after the event occurs
2. The permittee shall notify the Director (the appropriate Ohio EPA District Office or local air agency) in writing of any daily record showing that the coating line employs more than the applicable maximum daily coating usage limit as specified in A.II.2 above. The notification shall include a copy of such record and shall be sent to the Director (the appropriate Ohio EPA District Office or local air agency) within 45 days after the exceedance occurs.
3. The permittee shall submit deviation (excursion) reports which include the following information:
 - a. an identification of each day during which the average hourly organic compound emissions from the coatings and cleanup materials exceeded 8 pounds per hour, and the actual average hourly organic compound emissions for each such day; and
 - b. an identification of each day during which the organic compound emissions from the coatings and cleanup materials exceeded 40 pounds per day, and the actual organic compound emissions for each such day.

- c. for the days during which a photochemically reactive material was employed to a non-metal part, an identification of each day during which the average hourly organic compound emissions from the coatings and photochemically reactive cleanup materials exceeded 8 pounds per hour, and the actual average hourly organic compound emissions for each such day; and
- d. for the days during which a photochemically reactive material was employed to a non-metal part, an identification of each day during which the organic compound emissions from the coatings and photochemically reactive cleanup materials exceeded 40 pounds per day, and the actual organic compound emissions for each such day.

These reports shall be submitted in accordance with the requirements specified in General Terms and Conditions of this permit.

4. The permittee shall also submit annual reports which specify the total OC emissions from this emissions unit for the previous calendar year. These reports shall be submitted by January 31 of each year.

V. Testing Requirements

1. Compliance with the emission limitations in Section A.I.1 of these terms and conditions shall be determined in accordance with the following methods:
 - a. Emission Limitation:

20% opacity as a 6-minute average

Applicable Compliance Method:

OAC rule 3745-17-03(B)(1)
 - b. Emission Limitation:

0.551 lb/hr of particulate matter

Applicable Compliance Method:

To determine the actual worst case particulate emissions rate, the following equation shall be used:

Emissions Unit ID: K020

$E = \text{maximum coating solids usage rate in pounds per hour} \times (1-TE) \times (1-CE)$

where

$E = \text{particulate emissions rate (lbs/hr);}$

$TE = \text{transfer efficiency, which is the ratio of the amount of coating solids deposited on the coated part to the amount of coating solids used; and}$

$CE = \text{fractional control efficiency of the control equipment.}$

c. Emission Limitations:

8 lbs/hr of organic compounds

40 lbs/day of organic compounds

7.3 tons per year organic compounds

Applicable Compliance Method:

Daily records shall be maintained of the organic compound content of each coating and cleanup material employed, the daily usage of each coating and cleanup material employed, and the calculated average hourly and daily organic compound emission rates for all coatings and cleanup materials employed. Formulation data or USEPA Method 24 shall be used to determine the organic compound content of each coating and cleanup material.

d. Operational Restriction:

3.0 gallons of coating per day, when coating metal parts

Applicable Compliance Method:

Daily records shall be maintained of the daily usage of all coatings employed.

VI. Miscellaneous Requirements

None

B. State Only Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
K020 - K020, B1SB6 modification of existing spray paint booth, controlled with a paper filter to control particulate emissions.	Air toxic policy	See B.VI.

2. Additional Terms and Conditions

2.a None

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

1. Modeling to demonstrate compliance with the Ohio EPA's "Air Toxic Policy" was not necessary because the emissions unit's maximum annual emissions for each toxic compound will be less than 1.0 ton. OAC Chapter 3745-31 requires permittees to apply for and obtain a new or modified permit

91

E L St

PTI A₁

Issued: 2/6/2003

Emissions Unit ID: K020

to install prior to making a "modification" as defined by OAC rule 3745-31-01. The permittee is hereby advised that changes in the composition of the materials, or use of new materials, that would cause the emissions of any pollutant that has a listed TLV to increase to above 1.0 ton per year may require the permittee to apply for and obtain a new permit to install.

Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	On days when coating metal parts.	<u>Applicable Rules/Requirements</u>
K024 - K024, B3SB4 modification of existing spray paint booth, controlled with a paper filter to control particulate emissions.		OAC rule 3745-31-05(A)(3)
On days when coating non-metal parts.	On days when coating non-metal parts.	OAC rule 3745-17-07(A)(1) OAC rule 3745-17-11(B) OAC rule 3745-21-07(G)(2)

OAC
3745-21-09(U)(2)(e)

rule

Applicable Emissions
Limitations/Control Measures

7.3 tons per year of OC;
OC emissions shall not exceed 8
lbs/hr and 40 lbs/day organic
compounds;

0.4 ton per year of Methyl Ethyl
Ketone(MEK); 1.6 tons per year of
Methyl Isobutyl Ketone (MIBK); and
1.4 tons per year of Toluene.

See 2.a below.

The requirements of this rule also
include compliance with the
requirements of OAC rules
3745-17-07(A)(1), 3745-17-11(B),
3745-21-07(G)(2), and
3745-21-09(U)(2)(e).

20% opacity as a 6-minute average,
except as provided by rule.

0.551 lb/hr of particulate matter.

On any day when employing
photochemical reactive coatings or
clean up material to non-metal parts,
OC emissions shall not exceed 8
lbs/hr and 40 lbs/day.

See II.2. below

2. Additional Terms and Conditions

- 2.a MEK, MIBK and Toluene emissions are increased by 0.3 TPY, 0.2TPY, and 0.8 TPY respectively above the original PTI allowable limits in PTI 16-1609.

II. Operational Restrictions

1. Prior to commencing operation of the paint spray booth for each shift, the permittee shall ensure the exhaust filters are in place and in good condition. The permittee shall also ensure the filters are operated and maintained in accordance with the manufacturer's specifications.
2. The permittee shall employ no more than 3.0 gallons of coating in any day in which parts subject to the requirements of OAC rule 3745-21-09(U) are coated in this emissions unit.

III. Monitoring and/or Recordkeeping Requirements

1. The permittee shall collect and record the following information for each day for the coating operation:
 - a. the company identification for each coating and photochemically reactive cleanup material employed;
 - b. the number of gallons of each coating and photochemically reactive cleanup material employed;
 - c. the organic compound content of each coating and photochemically reactive cleanup material, in pounds per gallon;
 - d. the total organic compound emission rate for all coatings and photochemically reactive cleanup materials, in pounds per day;
 - e. the total number of hours the emissions unit was in operation;
 - f. the average hourly organic compound emission rate for all coatings and photochemically reactive cleanup materials, i.e., (d)/(e), in pounds per hour (average); and
 - g. which rule the booth was operating under that day, and whether it was in compliance with the requirements of the rule.
2. The permittee shall maintain a record for each day for this emissions unit of whether or not the

disposable paper filters were in service when the emissions unit was in operation.

3. The permittee shall collect and record the following information for each day when coating metal parts for the coating operation:
 - a. the name and identification number of each coating employed;
 - b. the volume, in gallons, of each coating employed;
 - c. the total volume, in gallons, of all of the coatings employed.
4. The permittee shall collect and record the following information for the purpose of determining annual OC, MEK, MIBK, and toluene emissions:
 - a. the name and identification of each cleanup material employed;
 - b. the number of gallons of each cleanup material employed;
 - c. the OC, MEK, MIBK, and toluene content of each cleanup material, in pounds per gallon;
 - d. the OC, MEK, MIBK, and toluene content of each coating, as applied, in pounds per gallon; and
 - e. the total OC, MEK, MIBK, and toluene emissions from all coatings and cleanup materials employed, in pounds or tons.

IV. Reporting Requirements

1. The permittee shall notify the Director (the appropriate District Office or local air agency) in writing of any record showing that the disposable paper filters were not in service when the emissions unit was in operation. The notification shall include a copy of such record and shall be sent to the Director (the appropriate District Office or local air agency) within 30 days after the event occurs.
2. The permittee shall notify the Director (the appropriate Ohio EPA District Office or local air agency) in writing of any daily record showing that the coating line employs more than the applicable maximum daily coating usage limit as specified in A.II.2 above. The notification shall include a copy of such record and shall be sent to the Director (the appropriate Ohio EPA District Office or local air agency) within 45 days after the exceedance occurs.

Emissions Unit ID: K024

3. The permittee shall submit deviation (excursion) reports which include the following information:
- a. an identification of each day during which the average hourly organic compound emissions from the coatings and cleanup materials exceeded 8 pounds per hour, and the actual average hourly organic compound emissions for each such day; and
 - b. an identification of each day during which the organic compound emissions from the coatings and cleanup materials exceeded 40 pounds per day, and the actual organic compound emissions for each such day.
 - c. for the days during which a photochemically reactive material was employed to a non-metal part, an identification of each day during which the average hourly organic compound emissions from the coatings and photochemically reactive cleanup materials exceeded 8 pounds per hour, and the actual average hourly organic compound emissions for each such day; and
 - d. for the days during which a photochemically reactive material was employed to a non-metal part, an identification of each day during which the organic compound emissions from the coatings and photochemically reactive cleanup materials exceeded 40 pounds per day, and the actual organic compound emissions for each such day.

These reports shall be submitted in accordance with the requirements specified in General Terms and Conditions of this permit.

4. The permittee shall also submit annual reports which specify the total OC, MEK, MIBK, and toluene emissions from this emissions unit for the previous calendar year. These reports shall be submitted by January 31 of each year.

V. Testing Requirements

1. Compliance with the emission limitations in Section A.I.1 of these terms and conditions shall be determined in accordance with the following methods:
- a. Emission Limitation:
 20% opacity as a 6-minute average
 Applicable Compliance Method:
 OAC rule 3745-17-03(B)(1)
 - b. Emission Limitation:
 0.551 lb/hr of particulate matter
 Applicable Compliance Method:

To determine the actual worst case particulate emissions rate, the following equation shall be used:

$$E = \text{maximum coating solids usage rate in pounds per hour} \times (1-TE) \times (1-CE)$$

where

$$E = \text{particulate emissions rate (lbs/hr);}$$

TE = transfer efficiency, which is the ratio of the amount of coating solids deposited on the coated part to the amount of coating solids used; and

CE = fractional control efficiency of the control equipment.

c. Emission Limitations:

8 lbs/hr of organic compounds
40 lbs/day of organic compounds
7.3 tons per year organic compounds

Applicable Compliance Method:

Daily records shall be maintained of the organic compound content of each coating and cleanup material employed, the daily usage of each coating and cleanup material employed, and the calculated average hourly and daily organic compound emission rates for all coatings and cleanup materials employed. Formulation data or USEPA Method 24 shall be used to determine the organic compound content of each coating and cleanup material.

d. Emission Limitations:

0.4 ton per year of Methyl Ethyl Ketone(MEK); 1.6 tons per year of Methyl Isobutyl Ketone (MIBK); and 1.4 tons per year of Toluene.

Applicable Compliance Method:

Compliance with the annual Methyl Ethyl Ketone, Methyl Isobutyl Ketone and Toluene emission limitations shall be based upon formulation data or USEPA Method 24 to determine the individual HAP content of each of the coating and cleanup material

employed along with record keeping requirements in term and condition III.4.

e. Operational Restriction:

3.0 gallons of coating per day, when coating metal parts

Applicable Compliance Method:

Daily records shall be maintained of the daily usage of all coatings employed.

VI. Miscellaneous Requirements

None

B. State Only Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
K024 - K024, B3SB4 modification of existing spray paint booth, controlled with a paper filter to control particulate emissions.	Air toxic policy	See B.VI.

2. Additional Terms and Conditions

2.a None

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

1. The permit to install for this emissions unit (K010) was evaluated based upon actual materials (typical ingredients and clean up materials) and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the air permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy (Air Toxic Policy) was applied for each

pollutant emitted by all of the emissions units included in this permit to install using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration was then compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling:

Pollutant: Methyl Ethyl Ketone

TLV (mg/m³): 588.9 (Converted from the TWA)

Maximum Hourly Emission Rate (lbs/hr): 1.8*

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m³): 300.75

MAGLC (ug/m³): 14,042.8

Pollutant: Methyl Isobutyl Ketone

TLV (mg/m³): 204.8 (Converted from the TWA)

Maximum Hourly Emission Rate (lbs/hr): 0.11*

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m³): 17.06

MAGLC (ug/m³): 4,876.2

Pollutant: Toluene

TLV (mg/m³): 188 (Converted from the TWA)

Maximum Hourly Emission Rate (lbs/hr): 4.2*

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m³): 698.6

MAGLC (ug/m³): 4,476.2

* This was modeled for emissions units K010, K011, K017, K018, K019, and K024 through K026 combined.

Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

- a. changes in the composition of the materials used, or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the TLV value specified above;

- b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and
- c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01(VV)(1)(a)(ii), and a modification of the existing permit to install will not be required. If the change(s) is (are) defined as a modification under other provisions of the modification definition (other than (VV)(1)(a)(ii)), then the permittee shall obtain a final permit to install prior to the change.

The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy:"

- a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
- b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and
- c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
K025 - K025, B3SB5 modification of existing spray paint booth, controlled with a paper filter to control particulate emissions.	OAC rule 3745-31-05(A)(3)	7.3 tons per year of OC; OC emissions shall not exceed 8 lbs/hr and 40 lbs/day; 0.4 ton per year of Methyl Ethyl Ketone (MEK); 1.6 tons per year of Methyl Isobutyl Ketone (MIBK); and 1.4 tons per year of Toluene. See 2.a below. The requirements of this rule also include compliance with the requirements of OAC rules 3745-17-07(A)(1), 3745-17-11(B), 3745-21-07(G)(2), and 3745-21-09(U)(2)(e).
On days when coating non-metal parts.	OAC rule 3745-17-07(A)(1)	20% opacity as a 6-minute average, except as provided by rule.
On days when coating non-metal parts.	OAC rule 3745-17-11(B)	0.551 lb/hr of particulate matter.
On days when coating non-metal parts.	OAC rule 3745-21-07(G)(2)	On any day when employing photochemical reactive coatings or clean up materials to non-metal parts, OC emissions shall not exceed 8 lbs/hr and 40 lbs/day.
On days when coating metal parts.	OAC rule 3745-21-09(U)(2)(e)	See II.2. below

2. Additional Terms and Conditions

- 2.a MEK, MIBK and Toluene emissions are increased by 0.3 TPY, 0.2TPY, and 0.8 TPY

respectively above the original PTI allowable limits in PTI 16-1609.

II. Operational Restrictions

1. Prior to commencing operation of the paint spray booth for each shift, the permittee shall ensure the exhaust filters are in place and in good condition. The permittee shall also ensure the filters are operated and maintained in accordance with the manufacturer's specifications.
2. The permittee shall employ no more than 3.0 gallons of coating in any day in which parts subject to the requirements of OAC rule 3745-21-09(U) are coated in this emissions unit.

III. Monitoring and/or Recordkeeping Requirements

1. The permittee shall collect and record the following information for each day for the coating operation:
 - a. the company identification for each coating and photochemically reactive cleanup material employed;
 - b. the number of gallons of each coating and photochemically reactive cleanup material employed;
 - c. the organic compound content of each coating and photochemically reactive cleanup material, in pounds per gallon;
 - d. the total organic compound emission rate for all coatings and photochemically reactive cleanup materials, in pounds per day;
 - e. the total number of hours the emissions unit was in operation;
 - f. the average hourly organic compound emission rate for all coatings and photochemically reactive cleanup materials, i.e., (d)/(e), in pounds per hour (average); and
 - g. which rule the booth was operating under that day, and whether it was in compliance with the requirements of the rule.
2. The permittee shall maintain a record for each day for this emissions unit of whether or not the disposable paper filters were in service when the emissions unit was in operation.
3. The permittee shall collect and record the following information for each day when coating metal

parts for the coating operation:

- a. the name and identification number of each coating employed;
 - b. the volume, in gallons, of each coating employed;
 - c. the total volume, in gallons, of all of the coatings employed.
4. The permittee shall collect and record the following information for the purpose of determining annual OC, MEK, MIBK, and toluene emissions:
- a. the name and identification of each cleanup material employed;
 - b. the number of gallons of each cleanup material employed;
 - c. the OC, MEK, MIBK, and toluene content of each cleanup material, in pounds per gallon;
 - d. the OC, MEK, MIBK, and toluene content of each coating, as applied, in pounds per gallon; and
 - e. the total OC, MEK, MIBK, and toluene emissions from all coatings and cleanup materials employed, in pounds or tons.

IV. Reporting Requirements

1. The permittee shall notify the Director (the appropriate District Office or local air agency) in writing of any record showing that the disposable paper filters were not in service when the emissions unit was in operation. The notification shall include a copy of such record and shall be sent to the Director (the appropriate District Office or local air agency) within 30 days after the event occurs.
2. The permittee shall notify the Director (the appropriate Ohio EPA District Office or local air agency) in writing of any daily record showing that the coating line employs more than the applicable maximum daily coating usage limit as specified in A.II.2 above. The notification shall include a copy of such record and shall be sent to the Director (the appropriate Ohio EPA District Office or local air agency) within 45 days after the exceedance occurs.
3. The permittee shall submit deviation (excursion) reports which include the following information:
 - a. an identification of each day during which the average hourly organic compound emissions from the coatings and cleanup materials exceeded 8 pounds per hour, and the actual average hourly organic compound emissions for each such day;
 - b. an identification of each day during which the organic compound emissions from the coatings and cleanup materials exceeded 40 pounds per day, and the actual organic compound emissions for each such day;

- c. for the days during which a photochemically reactive material was employed to a non-metal part, an identification of each day during which the average hourly organic compound emissions from the coatings and photochemically reactive cleanup materials exceeded 8 pounds per hour, and the actual average hourly organic compound emissions for each such day; and

- d. for the days during which a photochemically reactive material was employed to a non-metal part, an identification of each day during which the organic compound emissions from the coatings and photochemically reactive cleanup materials exceeded 40 pounds per day, and the actual organic compound emissions for each such day.

These reports shall be submitted in accordance with the requirements specified in General Terms and Conditions of this permit.

4. The permittee shall also submit annual reports which specify the total OC MEK, MIBK, and toluene emissions from this emissions unit for the previous calendar year. These reports shall be submitted by January 31 of each year.

V. Testing Requirements

1. Compliance with the emission limitations in Section A.I.1 of these terms and conditions shall be determined in accordance with the following methods:

- a. Emission Limitation:

20% opacity as a 6-minute average

Applicable Compliance Method:

OAC rule 3745-17-03(B)(1)

- b. Emission Limitation:

0.551 lb/hr of particulate matter

Applicable Compliance Method:

To determine the actual worst case particulate emissions rate, the following equation shall be used:

$$E = \text{maximum coating solids usage rate in pounds per hour} \times (1-TE) \times (1-CE)$$

where

$$E = \text{particulate emissions rate (lbs/hr);}$$

TE = transfer efficiency, which is the ratio of the amount of coating solids deposited on the coated part to the amount of coating solids used; and

CE = fractional control efficiency of the control equipment

c. Emission Limitations:

8 lbs/hr of organic compounds
40 lbs/day of organic compounds
7.3 tons per year of organic compounds

Applicable Compliance Method:

Daily records shall be maintained of the organic compound content of each coating and cleanup material employed, the daily usage of each coating and cleanup material employed, and the calculated average hourly and daily organic compound emission rates for all coatings and cleanup materials employed. Formulation data or USEPA Method 24 shall be used to determine the organic compound content of each coating and cleanup material.

d. Emission Limitations:

0.4 ton per year of Methyl Ethyl Ketone (MEK); 1.6 tons per year of Methyl Isobutyl Ketone (MIBK); and 1.4 tons per year of Toluene.. .

Applicable Compliance Method:

Compliance with the annual Methyl Ethyl Ketone, Methyl Isobutyl Ketone and Toluene emission limitations shall be based upon formulation data or USEPA Method 24 to determine the individual HAP content of each of the coating and cleanup material employed along with record keeping requirements in term and condition III.4.

e. Operational Restriction:

3.0 gallons of coating per day, when coating metal parts

Applicable Compliance Method:

Daily records shall be maintained of the daily usage of all coatings employed.

108

E L Stone Co

PTI Application: 16-02252

Issued

Facility ID: 1677020039

Emissions Unit ID: K025

VI. Miscellaneous Requirements

None

B. State Only Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

- 1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
K025 - K025, B3SB5 modification of existing spray paint booth, controlled with a paper filter to control particulate emissions.	Air toxic policy	See B.VI.

2. Additional Terms and Conditions

2.a None

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

110

E L St

PTI A₁

Issued: 2/6/2003

Emissions Unit ID: K025

1. The permit to install for this emissions unit (K010) was evaluated based upon actual materials (typical ingredients and clean up materials) and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the air permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy (Air Toxic Policy) was applied for each

pollutant emitted by all of the emissions units included in this permit to install using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration was then compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling:

Pollutant: Methyl Ethyl Ketone

TLV (mg/m³): 588.9 (Converted from the TWA)

Maximum Hourly Emission Rate (lbs/hr): 1.8*

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m³): 300.75

MAGLC (ug/m³): 14,042.8

Pollutant: Methyl Isobutyl Ketone

TLV (mg/m³): 204.8 (Converted from the TWA)

Maximum Hourly Emission Rate (lbs/hr): 0.11*

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m³): 17.06

MAGLC (ug/m³): 4,876.2

Pollutant: Toluene

TLV (mg/m³): 188 (Converted from the TWA)

Maximum Hourly Emission Rate (lbs/hr): 4.2*

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m³): 698.6

MAGLC (ug/m³): 4,476.2

* This was modeled for emissions units K010, K011, K017, K018, K019, and K024 through K026 combined.

Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

- a. changes in the composition of the materials used, or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the TLV value specified above;

Issued

Emissions Unit ID: K025

- b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and
- c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01(VV)(1)(a)(ii), and a modification of the existing permit to install will not be required. If the change(s) is (are) defined as a modification under other provisions of the modification definition (other than (VV)(1)(a)(ii)), then the permittee shall obtain a final permit to install prior to the change.

The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy:"

- a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
- b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and
- c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	On days when coating metal parts.	<u>Applicable Rules/Requirements</u>
K026 - K026, B3SB6 modification of existing spray paint booth, controlled with a paper filter to control particulate emissions.	On days when coating metal parts.	OAC rule 3745-31-05(A)(3)
On days when coating non-metal parts.	On days when coating non-metal parts.	OAC rule 3745-17-07(A)(1)
On days when coating non-metal parts.	On days when coating non-metal parts.	OAC rule 3745-17-11(B)
On days when coating non-metal parts.	On days when coating non-metal parts.	OAC rule 3745-21-07(G)(2)

OAC 3745-21-09(U)(2)(e)	rule	Applicable Emissions <u>Limitations/Control Measures</u>
		<p>7.3 tons per year of OC; OC emissions shall not exceed 8 lbs/hr and 40 lbs/day; 0.4 ton per year Methyl Ethyl Ketone (MEK); 1.6 tons per year Methyl Isobutyl Ketone (MIBK); and 1.4 tons per year Toluene.</p> <p>See 2.a below.</p> <p>The requirements of this rule also include compliance with the requirements of OAC rules 3745-17-07(A)(1), 3745-17-11(B), 3745-21-07(G)(2), and 3745-21-09(U)(2)(e).</p> <p>20% opacity as a 6-minute average, except as provided by rule.</p> <p>0.551 lb/hr of particulate matter.</p> <p>On any day when employing photochemical reactive coatings or clean up materials to non-metal parts, OC emissions shall not exceed 8 lbs/hr and 40 lbs/day.</p> <p>See II.2. below</p>

2. Additional Terms and Conditions

- 2.a** MEK, MIBK and Toluene emissions are increased by 0.3 TPY, 0.2TPY, and 0.8 TPY respectively above the original PTI allowable limits in PTI 16-1609.

II. Operational Restrictions

1. Prior to commencing operation of the paint spray booth for each shift, the permittee shall ensure

the exhaust filters are in place and in good condition. The permittee shall also ensure the filters are operated and maintained in accordance with the manufacturer's specifications.

2. The permittee shall employ no more than 3.0 gallons of coating in any day in which parts subject to the requirements of OAC rule 3745-21-09(U) are coated in this emissions unit.

III. Monitoring and/or Recordkeeping Requirements

1. The permittee shall collect and record the following information for each day for the coating operation:
 - a. the company identification for each coating and photochemically reactive cleanup material employed;
 - b. the number of gallons of each coating and photochemically reactive cleanup material employed;
 - c. the organic compound content of each coating and photochemically reactive cleanup material, in pounds per gallon;
 - d. the total organic compound emission rate for all coatings and photochemically reactive cleanup materials, in pounds per day;
 - e. the total number of hours the emissions unit was in operation;
 - f. the average hourly organic compound emission rate for all coatings and photochemically reactive cleanup materials, i.e., (d)/(e), in pounds per hour (average); and
 - g. which rule the booth was operating under that day, and whether it was in compliance with the requirements of the rule.
2. The permittee shall maintain a record for each day for this emissions unit of whether or not the disposable paper filters were in service when the emissions unit was in operation.
3. The permittee shall collect and record the following information for each day when coating metal parts for the coating operation:
 - a. the name and identification number of each coating employed;
 - b. the volume, in gallons, of each coating employed;

- c. the total volume, in gallons, of all of the coatings employed.
4. The permittee shall collect and record the following information for the purpose of determining annual OC MEK, MIBK, and toluene emissions:
 - a. the name and identification of each cleanup material employed;
 - b. the number of gallons of each cleanup material employed;
 - c. the OC, MEK, MIBK, and toluene content of each cleanup material, in pounds per gallon;
 - d. the OC, MEK, MIBK, and toluene content of each coating, as applied, in pounds per gallon; and
 - e. the total OC, MEK, MIBK, and toluene emissions from all coatings and cleanup materials employed, in pounds or tons.

IV. Reporting Requirements

1. The permittee shall notify the Director (the appropriate District Office or local air agency) in writing of any record showing that the disposable paper filters were not in service when the emissions unit was in operation. The notification shall include a copy of such record and shall be sent to the Director (the appropriate District Office or local air agency) within 30 days after the event occurs.
2. The permittee shall notify the Director (the appropriate Ohio EPA District Office or local air agency) in writing of any daily record showing that the coating line employs more than the applicable maximum daily coating usage limit as specified in A.II.2 above. The notification shall include a copy of such record and shall be sent to the Director (the appropriate Ohio EPA District Office or local air agency) within 45 days after the exceedance occurs.
3. The permittee shall submit deviation (excursion) reports which include the following information:
 - a. an identification of each day during which the average hourly organic compound emissions from the coatings and photochemically reactive cleanup materials exceeded 8 pounds per hour, and the actual average hourly organic compound emissions for each such day; and
 - b. an identification of each day during which the organic compound emissions from the coatings and photochemically reactive cleanup materials exceeded 40 pounds per day, and the actual organic compound emissions for each such day.
 - c. for the days during which a photochemically reactive material was employed to a non-metal part, an identification of each day during which the average hourly organic compound emissions from the coatings and photochemically reactive cleanup materials

exceeded 8 pounds per hour, and the actual average hourly organic compound emissions for each such day; and

- d. for the days during which a photochemically reactive material was employed to a non-metal part, an identification of each day during which the organic compound emissions from the coatings and photochemically reactive cleanup materials exceeded 40 pounds per day, and the actual organic compound emissions for each such day.

These reports shall be submitted in accordance with the requirements specified in General Terms and Conditions of this permit.

4. The permittee shall also submit annual reports which specify the total OC, MEK, MIBK, and toluene emissions from this emissions unit for the previous calendar year. These reports shall be submitted by January 31 of each year.

V. Testing Requirements

1. Compliance with the emission limitations in Section A.I.1 of these terms and conditions shall be determined in accordance with the following methods:

- a. Emission Limitation:

20% opacity as a 6-minute average

Applicable Compliance Method:

OAC rule 3745-17-03(B)(1)

- b. Emission Limitation:

0.551 lb/hr of particulate matter

Applicable Compliance Method:

To determine the actual worst case particulate emissions rate, the following equation shall be used:

$$E = \text{maximum coating solids usage rate in pounds per hour} \times (1-TE) \times (1-CE)$$

$$E = \text{particulate emissions rate (lbs/hr)}$$

TE = transfer efficiency, which is the ratio of the amount of coating solids deposited on the coated part to the amount of coating solids used; and

CE = fractional control efficiency of the control equipment.

c. Emission Limitations:

8 lbs/hr of organic compounds
40 lbs/day of organic compounds
7.3 tons per year organic compounds

Applicable Compliance Method:

Daily records shall be maintained of the organic compound content of each coating and cleanup material employed, the daily usage of each coating and cleanup material employed, and the calculated average hourly and daily organic compound emission rates for all coatings and cleanup materials employed. Formulation data or USEPA Method 24 shall be used to determine the organic compound content of each coating and cleanup material.

d. Emission Limitations:

0.4 ton per year of Methyl Ethyl Ketone (MEK); 1.6 tons per year of Methyl Isobutyl Ketone (MIBK); and 1.4 tons per year of Toluene.. .

Applicable Compliance Method:

Compliance with the annual Methyl Ethyl Ketone, Methyl Isobutyl Ketone and Toluene emission limitations shall be based upon formulation data or USEPA Method 24 to determine the individual HAP content of each of the coating and cleanup material employed along with record keeping requirements in term and condition III.4.

e. Operational Restriction:

3.0 gallons of coating per day, when coating metal parts

Applicable Compliance Method:

Daily records shall be maintained of the daily usage of all coatings employed.

VI. Miscellaneous Requirements

None

B. State Only Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
K026 - K026, B3SB6 modification of existing spray paint booth, controlled with a paper filter to control particulate emissions.	Air toxic policy	See B.VI.

2. Additional Terms and Conditions

- 2.a None

II. Operational Restrictions

None

III. Monitoring and/or Recordkeeping Requirements

None

IV. Reporting Requirements

None

V. Testing Requirements

None

VI. Miscellaneous Requirements

120

E L St

PTI A₁

Issued: 2/6/2003

Emissions Unit ID: K026

1. The permit to install for this emissions unit (K010) was evaluated based upon actual materials (typical ingredients and clean up materials) and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the air permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy (Air Toxic Policy) was applied for each

Issued

Emissions Unit ID: K026

pollutant emitted by all of the emissions units included in this permit to install using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration was then compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling:

Pollutant: Methyl Ethyl Ketone

TLV (mg/m3): 588.9 (Converted from the TWA)

Maximum Hourly Emission Rate (lbs/hr): 1.8*

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 300.75

MAGLC (ug/m3): 14,042.8

Pollutant: Methyl Isobutyl Ketone

TLV (mg/m3): 204.8 (Converted from the TWA)

Maximum Hourly Emission Rate (lbs/hr): 0.11*

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 17.06

MAGLC (ug/m3): 4,876.2

Pollutant: Toluene

TLV (mg/m3): 188 (Converted from the TWA)

Maximum Hourly Emission Rate (lbs/hr): 4.2*

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 698.6

MAGLC (ug/m3): 4,476.2

* This was modeled for emissions units K010, K011, K017, K018, K019, and K024 through K026 combined.

Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

- a. changes in the composition of the materials used, or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the TLV value specified above;
- b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and
- c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01(VV)(1)(a)(ii), and a modification of the existing permit to install will not be required. If the change(s) is (are) defined as a modification under other provisions of the modification definition (other than (VV)(1)(a)(ii)), then the permittee shall obtain a final permit to install prior to the change.

The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy:"

- a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
- b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and
- c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.