



John R. Kasich, Governor
 Mary Taylor, Lt. Governor
 Craig W. Butler, Director

6/13/2016

Certified Mail

Mr. Michael Michael
 BUCKEYE PIPE LINE CO- MANTUA STATION
 993 Brodhead Rd Suite 100
 Coraopolis, PA 15108

No	TOXIC REVIEW
No	SYNTHETIC MINOR TO AVOID MAJOR NSR
No	CEMS
Yes	MACT/GACT
Yes	NSPS
No	NESHAPS
No	NETTING
No	MODELING SUBMITTED
No	SYNTHETIC MINOR TO AVOID TITLE V
No	FEDERALLY ENFORCABLE PTIO (FEPTIO)
No	SYNTHETIC MINOR TO AVOID MAJOR GHG

RE: FINALAIR POLLUTION PERMIT-TO-INSTALL AND OPERATE

Facility ID: 1667050023
 Permit Number: P0120925
 Permit Type: Administrative Modification
 County: Portage

Dear Permit Holder:

Enclosed please find a final Ohio Environmental Protection Agency (EPA) Air Pollution Permit-to-Install and Operate (PTIO) which will allow you to install, modify, and/or operate the described emissions unit(s) in the manner indicated in the permit. Because this permit contains conditions and restrictions, please read it very carefully. In this letter you will find the information on the following topics:

- **How to appeal this permit**
- **How to save money, reduce pollution and reduce energy consumption**
- **How to give us feedback on your permitting experience**
- **How to get an electronic copy of your permit**
- **What should you do if you notice a spill or environmental emergency?**

How to appeal this permit

The issuance of this PTIO is a final action of the Director and may be appealed to the Environmental Review Appeals Commission pursuant to Section 3745.04 of the Ohio Revised Code. The appeal must be in writing and set forth the action complained of and the grounds upon which the appeal is based. The appeal must be filed with the Commission within thirty (30) days after notice of the Director's action. The appeal must be accompanied by a filing fee of \$70.00, made payable to "Ohio Treasurer Josh Mandel," which the Commission, in its discretion, may reduce if by affidavit you demonstrate that payment of the full amount of the fee would cause extreme hardship. Notice of the filing of the appeal shall be filed with the Director within three (3) days of filing with the Commission. Ohio EPA requests that a copy of the appeal be served upon the Ohio Attorney General's Office, Environmental Enforcement Section. An appeal may be filed with the Environmental Review Appeals Commission at the following address:

Environmental Review Appeals Commission
 77 South High Street, 17th Floor
 Columbus, OH 43215

How to save money, reduce pollution and reduce energy consumption

The Ohio EPA is encouraging companies to investigate pollution prevention and energy conservation. Not only will this reduce pollution and energy consumption, but it can also save you money. If you would like to learn ways you can save money while protecting the environment, please contact our Office of Compliance Assistance and Pollution Prevention at (614) 644-3469. Additionally, all or a portion of the capital expenditures related to installing air pollution control equipment under this permit may be eligible for financing and State tax exemptions through the Ohio Air Quality Development Authority (OAQDA) under Ohio Revised Code Section 3706. For more information, see the OAQDA website: www.ohioairquality.org/clean_air

How to give us feedback on your permitting experience

Please complete a survey at www.epa.ohio.gov/survey.aspx and give us feedback on your permitting experience. We value your opinion.

How to get an electronic copy of your permit

This permit can be accessed electronically via the eBusiness Center: Air Services in Microsoft Word format or in Adobe PDF on the Division of Air Pollution Control (DAPC) Web page, www.epa.ohio.gov/dapc by clicking the "Search for Permits" link under the Permitting topic on the Programs tab.

What should you do if you notice a spill or environmental emergency?

Any spill or environmental emergency which may endanger human health or the environment should be reported to the Emergency Response 24-HOUR EMERGENCY SPILL HOTLINE toll-free at (800) 282-9378. Report non-emergency complaints to the appropriate district office or local air agency.

If you have any questions regarding your permit, please contact Akron Regional Air Quality Management District at (330)375-2480 or the Office of Compliance Assistance and Pollution Prevention at (614) 644-3469.

Sincerely,



Michael E. Hopkins, P.E.
Assistant Chief, Permitting Section, DAPC

Cc: ARAQMD



FINAL

**Division of Air Pollution Control
Permit-to-Install and Operate
for
BUCKEYE PIPE LINE CO- MANTUA STATION**

Facility ID:	1667050023
Permit Number:	P0120925
Permit Type:	Administrative Modification
Issued:	6/13/2016
Effective:	6/13/2016
Expiration:	6/23/2020



Division of Air Pollution Control
Permit-to-Install and Operate
for
BUCKEYE PIPE LINE CO- MANTUA STATION

Table of Contents

Authorization	1
A. Standard Terms and Conditions	3
1. What does this permit-to-install and operate ("PTIO") allow me to do?.....	4
2. Who is responsible for complying with this permit?	4
3. What records must I keep under this permit?	4
4. What are my permit fees and when do I pay them?.....	4
5. When does my PTIO expire, and when do I need to submit my renewal application?	4
6. What happens to this permit if my project is delayed or I do not install or modify my source?	5
7. What reports must I submit under this permit?	5
8. If I am required to obtain a Title V operating permit in the future, what happens to the operating provisions and PER obligations under this permit?	5
9. What are my obligations when I perform scheduled maintenance on air pollution control equipment? ...	5
10. Do I have to report malfunctions of emissions units or air pollution control equipment? If so, how must I report?	6
11. Can Ohio EPA or my local air agency inspect the facility where the emission unit(s) is/are located?	6
12. What happens if one or more emissions units operated under this permit is/are shut down permanently?	6
13. Can I transfer this permit to a new owner or operator?.....	7
14. Does compliance with this permit constitute compliance with OAC rule 3745-15-07, "air pollution nuisance"?	7
15. What happens if a portion of this permit is determined to be invalid?	7
B. Facility-Wide Terms and Conditions.....	8
C. Emissions Unit Terms and Conditions	18
1. Emissions Unit Group -Non NSPS Storage Tanks: T005,T006,T011,	19
2. Emissions Unit Group -Subpart Ka Storage Tanks: T008,T009,.....	22
3. Emissions Unit Group -Subpart Kb Storage Tank: T010,	25



Final Permit-to-Install and Operate
BUCKEYE PIPE LINE CO- MANTUA STATION
Permit Number: P0120925
Facility ID: 1667050023
Effective Date: 6/13/2016

Authorization

Facility ID: 1667050023
Application Number(s): M0004040
Permit Number: P0120925
Permit Description: Administrative modification requested by facility to correct an error in the original potential to emit calculation for VOC for above ground storage tank T011.
Permit Type: Administrative Modification
Permit Fee: \$75.00
Issue Date: 6/13/2016
Effective Date: 6/13/2016
Expiration Date: 6/23/2020
Permit Evaluation Report (PER) Annual Date: Jan 1 - Dec 31, Due Feb 15

This document constitutes issuance to:

BUCKEYE PIPE LINE CO- MANTUA STATION
4911 EAST HIGH STREET
MANTUA, OH 44255

of a Permit-to-Install and Operate for the emissions unit(s) identified on the following page.


Ohio Environmental Protection Agency (EPA) District Office or local air agency responsible for processing and administering your permit:

Akron Regional Air Quality Management District
1867 West Market St.
Akron, OH 44313
(330)375-2480

The above named entity is hereby granted this Permit-to-Install and Operate for the air contaminant source(s) (emissions unit(s)) listed in this section pursuant to Chapter 3745-31 of the Ohio Administrative Code. Issuance of this permit does not constitute expressed or implied approval or agreement that, if constructed or modified in accordance with the plans included in the application, the described emissions unit(s) will operate in compliance with applicable State and federal laws and regulations.

This permit is granted subject to the conditions attached hereto.

Ohio Environmental Protection Agency


Craig W. Butler
Director



Authorization (continued)

Permit Number: P0120925

Permit Description: Administrative modification requested by facility to correct an error in the original potential to emit calculation for VOC for above ground storage tank T011.

Permits for the following Emissions Unit(s) or groups of Emissions Units are in this document as indicated below:

Group Name: Non NSPS Storage Tanks

Emissions Unit ID:	T005
Company Equipment ID:	Tank 506
Superseded Permit Number:	P0112319
General Permit Category andType:	Not Applicable
Emissions Unit ID:	T006
Company Equipment ID:	Tank 508
Superseded Permit Number:	P0112319
General Permit Category andType:	Not Applicable
Emissions Unit ID:	T011
Company Equipment ID:	Tank 550
Superseded Permit Number:	P0112319
General Permit Category andType:	Not Applicable

Group Name: Subpart Ka Storage Tanks

Emissions Unit ID:	T008
Company Equipment ID:	Tank 512
Superseded Permit Number:	P0112319
General Permit Category andType:	Not Applicable
Emissions Unit ID:	T009
Company Equipment ID:	Tank 501
Superseded Permit Number:	P0112319
General Permit Category andType:	Not Applicable

Group Name: Subpart Kb Storage Tank

Emissions Unit ID:	T010
Company Equipment ID:	Tank 504
Superseded Permit Number:	P0112319
General Permit Category andType:	Not Applicable



Final Permit-to-Install and Operate
BUCKEYE PIPE LINE CO- MANTUA STATION
Permit Number: P0120925
Facility ID: 1667050023
Effective Date: 6/13/2016

A. Standard Terms and Conditions

1. What does this permit-to-install and operate ("PTIO") allow me to do?

This permit allows you to install and operate the emissions unit(s) identified in this PTIO. You must install and operate the unit(s) in accordance with the application you submitted and all the terms and conditions contained in this PTIO, including emission limits and those terms that ensure compliance with the emission limits (for example, operating, recordkeeping and monitoring requirements).

2. Who is responsible for complying with this permit?

The person identified on the "Authorization" page, above, is responsible for complying with this permit until the permit is revoked, terminated, or transferred. "Person" means a person, firm, corporation, association, or partnership. The words "you," "your," or "permittee" refer to the "person" identified on the "Authorization" page above.

The permit applies only to the emissions unit(s) identified in the permit. If you install or modify any other equipment that requires an air permit, you must apply for an additional PTIO(s) for these sources.

3. What records must I keep under this permit?

You must keep all records required by this permit, including monitoring data, test results, strip-chart recordings, calibration data, maintenance records, and any other record required by this permit for five years from the date the record was created. You can keep these records electronically, provided they can be made available to Ohio EPA during an inspection at the facility. Failure to make requested records available to Ohio EPA upon request is a violation of this permit requirement.

4. What are my permit fees and when do I pay them?

There are two fees associated with permitted air contaminant sources in Ohio:

PTIO fee. This one-time fee is based on a fee schedule in accordance with Ohio Revised Code (ORC) section 3745.11, or based on a time and materials charge for permit application review and permit processing if required by the Director.

You will be sent an invoice for this fee after you receive this PTIO and payment is due within 30 days of the invoice date. You are required to pay the fee for this PTIO even if you do not install or modify your operations as authorized by this permit.

Annual emissions fee. Ohio EPA will assess a separate fee based on the total annual emissions from your facility. You self-report your emissions in accordance with Ohio Administrative Code (OAC) Chapter 3745-78. This fee assessed is based on a fee schedule in ORC section 3745.11 and funds Ohio EPA's permit compliance oversight activities. For facilities that are permitted as synthetic minor sources, the fee schedule is adjusted annually for inflation. Ohio EPA will notify you when it is time to report your emissions and to pay your annual emission fees.

5. When does my PTIO expire, and when do I need to submit my renewal application?

This permit expires on the date identified at the beginning of this permit document (see "Authorization" page above) and you must submit a renewal application to renew the permit. Ohio EPA will send a renewal notice to you approximately six months prior to the expiration date of this permit. However, it is

very important that you submit a complete renewal permit application (postmarked prior to expiration of this permit) even if you do not receive the renewal notice.

If a complete renewal application is submitted before the expiration date, Ohio EPA considers this a timely application for purposes of ORC section 119.06, and you are authorized to continue operating the emissions unit(s) covered by this permit beyond the expiration date of this permit until final action is taken by Ohio EPA on the renewal application.

6. What happens to this permit if my project is delayed or I do not install or modify my source?

This PTIO expires 18 months after the issue date identified on the "Authorization" page above unless otherwise specified if you have not (1) started constructing the new or modified emission sources identified in this permit, or (2) entered into a binding contract to undertake such construction. This deadline can be extended by up to 12 months, provided you apply to Ohio EPA for this extension within a reasonable time before the 18-month period has ended and you can show good cause for any such extension.

7. What reports must I submit under this permit?

An annual permit evaluation report (PER) is required in addition to any malfunction reporting required by OAC rule 3745-15-06 or other specific rule-based reporting requirement identified in this permit. Your PER due date is identified in the Authorization section of this permit.

8. If I am required to obtain a Title V operating permit in the future, what happens to the operating provisions and PER obligations under this permit?

If you are required to obtain a Title V permit under OAC Chapter 3745-77 in the future, the permit-to-operate portion of this permit will be superseded by the issued Title V permit. From the effective date of the Title V permit forward, this PTIO will effectively become a PTI (permit-to-install) in accordance with OAC rule 3745-31-02(B). The following terms and conditions of this permit will no longer be applicable after issuance of the Title V permit: Section B, Term 1.b) and Section C, for each emissions unit, Term a)(2).

The PER requirements in this permit remain effective until the date the Title V permit is issued and is effective, and cease to apply after the effective date of the Title V permit. The final PER obligation will cover operations up to the effective date of the Title V permit and must be submitted on or before the submission deadline identified in this permit on the last day prior to the effective date of the Title V permit.

9. What are my obligations when I perform scheduled maintenance on air pollution control equipment?

You must perform scheduled maintenance of air pollution control equipment in accordance with OAC rule 3745-15-06(A). If scheduled maintenance requires shutting down or bypassing any air pollution control equipment, you must also shut down the emissions unit(s) served by the air pollution control equipment during maintenance, unless the conditions of OAC rule 3745-15-06(A)(3) are met. Any emissions that exceed permitted amount(s) under this permit (unless specifically exempted by rule) must be reported as deviations in the annual permit evaluation report (PER), including nonexempt excess emissions that occur during approved scheduled maintenance.

10. Do I have to report malfunctions of emissions units or air pollution control equipment? If so, how must I report?

If you have a reportable malfunction of any emissions unit(s) or any associated air pollution control system, you must report this to the [DO/LAA] in accordance with OAC rule 3745-15-06(B). Malfunctions that must be reported are those that result in emissions that exceed permitted emission levels. It is your responsibility to evaluate control equipment breakdowns and operational upsets to determine if a reportable malfunction has occurred.

If you have a malfunction, but determine that it is not a reportable malfunction under OAC rule 3745-15-06(B), it is recommended that you maintain records associated with control equipment breakdown or process upsets. Although it is not a requirement of this permit, Ohio EPA recommends that you maintain records for non-reportable malfunctions.

11. Can Ohio EPA or my local air agency inspect the facility where the emission unit(s) is/are located?

Yes. Under Ohio law, the Director or his authorized representative may inspect the facility, conduct tests, examine records or reports to determine compliance with air pollution laws and regulations and the terms and conditions of this permit. You must provide, within a reasonable time, any information Ohio EPA requests either verbally or in writing.

12. What happens if one or more emissions units operated under this permit is/are shut down permanently?

Ohio EPA can terminate the permit terms associated with any permanently shut down emissions unit. "Shut down" means the emissions unit has been physically removed from service or has been altered in such a way that it can no longer operate without a subsequent "modification" or "installation" as defined in OAC Chapter 3745-31.

You should notify Ohio EPA of any emissions unit that is permanently shut down by submitting a certification that identifies the date on which the emissions unit was permanently shut down. The certification must be submitted by an authorized official from the facility. You cannot continue to operate an emission unit once the certification has been submitted to Ohio EPA by the authorized official.

You must comply with all recordkeeping and reporting for any permanently shut down emissions unit in accordance with the provisions of the permit, regulations or laws that were enforceable during the period of operation, such as the requirement to submit a PER, air fee emission report, or malfunction report. You must also keep all records relating to any permanently shutdown emissions unit, generated while the emissions unit was in operation, for at least five years from the date the record was generated.

Again, you cannot resume operation of any emissions unit certified by the authorized official as being permanently shut down without first applying for and obtaining a permit pursuant to OAC Chapter 3745-31.

13. Can I transfer this permit to a new owner or operator?

You can transfer this permit to a new owner or operator. If you transfer the permit, you must follow the procedures in OAC Chapter 3745-31, including notifying Ohio EPA or the local air agency of the change in ownership or operator. Any transferee of this permit must assume the responsibilities of the transferor permit holder.

14. Does compliance with this permit constitute compliance with OAC rule 3745-15-07, "air pollution nuisance"?

This permit and OAC rule 3745-15-07 prohibit operation of the air contaminant source(s) regulated under this permit in a manner that causes a nuisance. Ohio EPA can require additional controls or modification of the requirements of this permit through enforcement orders or judicial enforcement action if, upon investigation, Ohio EPA determines existing operations are causing a nuisance.

15. What happens if a portion of this permit is determined to be invalid?

If a portion of this permit is determined to be invalid, the remainder of the terms and conditions remain valid and enforceable. The exception is where the enforceability of terms and conditions are dependent on the term or condition that was declared invalid.



Final Permit-to-Install and Operate
BUCKEYE PIPE LINE CO- MANTUA STATION
Permit Number: P0120925
Facility ID: 1667050023
Effective Date: 6/13/2016

B. Facility-Wide Terms and Conditions

1. This permit document constitutes a permit-to-install issued in accordance with ORC 3704.03(F) and a permit-to-operate issued in accordance with ORC 3704.03(G).
 - a) For the purpose of a permit-to-install document, the facility-wide terms and conditions contained in this permit are federally enforceable with the exception of those listed below which are enforceable under state law only.
 - (1) None.
 - b) For the purpose of a permit-to-operate document, the facility-wide terms and conditions contained in this permit are federally enforceable with the exception of those listed below which are enforceable under state law only.
 - (1) None.

2. Subpart BBBBBB—National Emission Standards for Hazardous Air Pollutants for Source Category: Gasoline Distribution Bulk Terminals, Bulk Plants, and Pipeline Facilities

The Ohio EPA has determined that this facility is subject to the requirements of 40 CFR Part 63, Subpart BBBBBB—National Emission Standards for Hazardous Air Pollutants for Source Category: Gasoline Distribution Bulk Terminals, Bulk Plants, and Pipeline Facilities. Although Ohio EPA has determined that this Generally Available Control Technology (GACT) NESHAP applies, at this time Ohio EPA does not have the authority to enforce this standard. Instead, U.S. EPA has the authority to enforce this standard. Please be advised, that all requirements associated with this rule are in effect and shall be enforced by U.S. EPA. For more information on the area source rules, please refer to the following U.S. EPA website: <http://www.epa.gov/ttn/atw/area/arearules.html>.

3. 40 CFR Part 60 - Subpart Ka - Standards of Performance for Storage Vessels for Petroleum Liquids for Which Construction, Reconstruction, or Modification Commenced After May 18, 1978, and Prior to July 23, 1984.

Applicable sections of Subpart Ka are listed below in this term #3 of these facility-wide terms and conditions. Keep in mind, it is still the sole responsibility of the owner or operator to comply with all applicable requirements of Subpart Ka, whether or not said requirements are fully and correctly identified in this permit.

§ 60.110a Applicability and designation of affected facility.

(a) *Affected facility.* Except as provided in paragraph (b) of this section, the affected facility to which this subpart applies is each storage vessel with a storage capacity greater than 151,416 liters (40,000 gallons) that is used to store petroleum liquids for which construction is commenced after May 18, 1978.

(b) Each petroleum liquid storage vessel with a capacity of less than 1,589,873 liters (420,000 gallons) used for petroleum or condensate stored, processed, or treated prior to custody transfer is not an affected facility and, therefore, is exempt from the requirements of this subpart.

§ 60.112a Standard for volatile organic compounds (VOC).

(a) The owner or operator of each storage vessel to which this subpart applies which contains a petroleum liquid which, as stored, has a true vapor pressure equal to or greater than 10.3 kPa (1.5 psia) but not greater than 76.6 kPa (11.1 psia) shall equip the storage vessel with the following:

(2) A fixed roof with an internal floating type cover equipped with a continuous closure device between the tank wall and the cover edge. The cover is to be floating at all times, (i.e., off the leg supports) except during initial fill and when the tank is completely emptied and subsequently refilled. The process of emptying and refilling when the cover is resting on the leg supports shall be continuous and shall be accomplished as rapidly as possible. Each opening in the cover except for automatic bleeder vents and the rim space vents is to provide a projection below the liquid surface. Each opening in the cover except for automatic bleeder vents, rim space vents, stub drains and leg sleeves is to be equipped with a cover, seal, or lid which is to be maintained in a closed position at all times (i.e., no visible gap) except when the device is in actual use. Automatic bleeder vents are to be closed at all times when the cover is floating except when the cover is being floated off or is being landed on the leg supports. Rim vents are to be set to open only when the cover is being floated off the leg supports or at the manufacturer's recommended setting.

(4) A system equivalent to those described in paragraphs (a)(1), (a)(2), or (a)(3) of this section as provided in § 60.114a.

§ 60.114a Alternative means of emission limitation.

(a) If, in the Administrator's judgment, an alternative means of emission limitation will achieve a reduction in emissions at least equivalent to the reduction in emissions achieved by any requirement in § 60.112a, the Administrator will publish in the FEDERAL REGISTER a notice permitting the use of the alternative means for purposes of compliance with that requirement.

(b) Any notice under paragraph (a) of this section will be published only after notice and an opportunity for a hearing.

(c) Any person seeking permission under this section shall submit to the Administrator a written application including:

(1) An actual emissions test that uses a full-sized or scale-model storage vessel that accurately collects and measures all VOC emissions from a given control device and that accurately simulates wind and accounts for other emission variables such as temperature and barometric pressure.

(2) An engineering evaluation that the Administrator determines is an accurate method of determining equivalence.

(d) The Administrator may condition the permission on requirements that may be necessary to ensure operation and maintenance to achieve the same emissions reduction as specified in § 60.112a.

§ 60.115a Monitoring of operations.

(a) Except as provided in paragraph (d) of this section, the owner or operator subject to this subpart shall maintain a record of the petroleum liquid stored, the period of storage, and the maximum true vapor pressure of that liquid during the respective storage period.

(b) Available data on the typical Reid vapor pressure and the maximum expected storage temperature of the stored product may be used to determine the maximum true vapor pressure from nomographs contained in API Bulletin 2517, unless the Administrator specifically requests that the liquid be sampled, the actual storage temperature determined, and the Reid vapor pressure determined from the sample(s).

(c) The true vapor pressure of each type of crude oil with a Reid vapor pressure less than 13.8 kPa (2.0 psia) or whose physical properties preclude determination by the recommended method is to be determined from available data and recorded if the estimated true vapor pressure is greater than 6.9 kPa (1.0 psia).

(d) The following are exempt from the requirements of this section:

(1) Each owner or operator of each storage vessel storing a petroleum liquid with a Reid vapor pressure of less than 6.9 kPa (1.0 psia) provided the maximum true vapor pressure does not exceed 6.9 kPa (1.0 psia).

4. **Subpart Kb—Standards of Performance for Volatile Organic Liquid Storage Vessels (Including Petroleum Liquid Storage Vessels) for Which Construction, Reconstruction, or Modification Commenced After July 23, 1984**

Applicable sections of Subpart Kb are listed below in this term #4 of these facility-wide terms and conditions. Keep in mind, it is still the sole responsibility of the owner or operator to comply with all applicable requirements of Subpart Kb, whether or not said requirements are fully and correctly identified in this permit.

§ 60.110b Applicability and designation of affected facility

(a) Except as provided in paragraph (b) of this section, the affected facility to which this subpart applies is each storage vessel with a capacity greater than or equal to 75 cubic meters (m^3) that is used to store volatile organic liquids (VOL) for which construction, reconstruction, or modification is commenced after July 23, 1984.

(b) This subpart does not apply to storage vessels with a capacity greater than or equal to 151 m^3 storing a liquid with a maximum true vapor pressure less than 3.5 kilopascals (kPa) or with a capacity greater than or equal to 75 m^3 but less than 151 m^3 storing a liquid with a maximum true vapor pressure less than 15.0 kPa.

§ 60.112b Standard for volatile organic compounds (VOC)

(a) The owner or operator of each storage vessel either with a design capacity greater than or equal to 151 m^3 containing a VOL that, as stored, has a maximum true vapor pressure equal to or greater than 5.2 kPa but less than 76.6 kPa or with a design capacity greater than or equal to 75 m^3 but less than

151 m³ containing a VOL that, as stored, has a maximum true vapor pressure equal to or greater than 27.6 kPa but less than 76.6 kPa, shall equip each storage vessel with the following:

(1) A fixed roof in combination with an internal floating roof meeting the following specifications:

(i) The internal floating roof shall rest or float on the liquid surface (but not necessarily in complete contact with it) inside a storage vessel that has a fixed roof. The internal floating roof shall be floating on the liquid surface at all times, except during initial fill and during those intervals when the storage vessel is completely emptied or subsequently emptied and refilled. When the roof is resting on the leg supports, the process of filling, emptying, or refilling shall be continuous and shall be accomplished as rapidly as possible.

(ii) Each internal floating roof shall be equipped with one of the following closure devices between the wall of the storage vessel and the edge of the internal floating roof:

(A) A foam- or liquid-filled seal mounted in contact with the liquid (liquid-mounted seal). A liquid-mounted seal means a foam- or liquid-filled seal mounted in contact with the liquid between the wall of the storage vessel and the floating roof continuously around the circumference of the tank.

(B) Two seals mounted one above the other so that each forms a continuous closure that completely covers the space between the wall of the storage vessel and the edge of the internal floating roof. The lower seal may be vapor-mounted, but both must be continuous.

(C) A mechanical shoe seal. A mechanical shoe seal is a metal sheet held vertically against the wall of the storage vessel by springs or weighted levers and is connected by braces to the floating roof. A flexible coated fabric (envelope) spans the annular space between the metal sheet and the floating roof.

(iii) Each opening in a noncontact internal floating roof except for automatic bleeder vents (vacuum breaker vents) and the rim space vents is to provide a projection below the liquid surface.

(iv) Each opening in the internal floating roof except for leg sleeves, automatic bleeder vents, rim space vents, column wells, ladder wells, sample wells, and stub drains is to be equipped with a cover or lid which is to be maintained in a closed position at all times (i.e., no visible gap) except when the device is in actual use. The cover or lid shall be equipped with a gasket. Covers on each access hatch and automatic gauge float well shall be bolted except when they are in use.

(v) Automatic bleeder vents shall be equipped with a gasket and are to be closed at all times when the roof is floating except when the roof is being floated off or is being landed on the roof leg supports.

(vi) Rim space vents shall be equipped with a gasket and are to be set to open only when the internal floating roof is not floating or at the manufacturer's recommended setting.

(vii) Each penetration of the internal floating roof for the purpose of sampling shall be a sample well. The sample well shall have a slit fabric cover that covers at least 90 percent of the opening.

(viii) Each penetration of the internal floating roof that allows for passage of a column supporting the fixed roof shall have a flexible fabric sleeve seal or a gasketed sliding cover.

(ix) Each penetration of the internal floating roof that allows for passage of a ladder shall have a gasketed sliding cover.

§ 60.113b Testing and procedures.

The owner or operator of each storage vessel as specified in § 60.112b(a) shall meet the requirements of paragraph (a), (b), or (c) of this section. The applicable paragraph for a particular storage vessel depends on the control equipment installed to meet the requirements of § 60.112b.

(a) After installing the control equipment required to meet § 60.112b(a)(1) (permanently affixed roof and internal floating roof), each owner or operator shall:

(1) Visually inspect the internal floating roof, the primary seal, and the secondary seal (if one is in service), prior to filling the storage vessel with VOL. If there are holes, tears, or other openings in the primary seal, the secondary seal, or the seal fabric or defects in the internal floating roof, or both, the owner or operator shall repair the items before filling the storage vessel.

(2) For Vessels equipped with a liquid-mounted or mechanical shoe primary seal, visually inspect the internal floating roof and the primary seal or the secondary seal (if one is in service) through manholes and roof hatches on the fixed roof at least once every 12 months after initial fill. If the internal floating roof is not resting on the surface of the VOL inside the storage vessel, or there is liquid accumulated on the roof, or the seal is detached, or there are holes or tears in the seal fabric, the owner or operator shall repair the items or empty and remove the storage vessel from service within 45 days. If a failure that is detected during inspections required in this paragraph cannot be repaired within 45 days and if the vessel cannot be emptied within 45 days, a 30-day extension may be requested from the Administrator in the inspection report required in § 60.115b(a)(3). Such a request for an extension must document that alternate storage capacity is unavailable and specify a schedule of actions the company will take that will assure that the control equipment will be repaired or the vessel will be emptied as soon as possible.

(3) For vessels equipped with a double-seal system as specified in § 60.112b(a)(1)(ii)(B):

(i) Visually inspect the vessel as specified in paragraph (a)(4) of this section at least every 5 years; or

(ii) Visually inspect the vessel as specified in paragraph (a)(2) of this section.

(4) Visually inspect the internal floating roof, the primary seal, the secondary seal (if one is in service), gaskets, slotted membranes and sleeve seals (if any) each time the storage vessel is emptied and degassed. If the internal floating roof has defects, the primary seal has holes, tears, or other openings in the seal or the seal fabric, or the secondary seal has holes, tears, or other openings in the seal or the seal fabric, or the gaskets no longer close off the liquid surfaces from the atmosphere, or the slotted membrane has more than 10 percent open area, the owner or operator shall repair the items as necessary so that none of the conditions specified in this paragraph exist before refilling the storage vessel with VOL. In no event shall inspections conducted in accordance with this provision occur at intervals greater than 10 years in the case of vessels conducting the annual visual inspection as specified in paragraphs (a)(2) and (a)(3)(ii) of this section and at intervals no greater than 5 years in the case of vessels specified in paragraph (a)(3)(i) of this section.

(5) Notify the Administrator in writing at least 30 days prior to the filling or refilling of each storage vessel for which an inspection is required by paragraphs (a)(1) and (a)(4) of this section to afford the Administrator the opportunity to have an observer present. If the inspection required by paragraph (a)(4) of this section is not planned and the owner or operator could not have known about the inspection 30 days in advance or refilling the tank, the owner or operator shall notify the Administrator at least 7 days prior to the refilling of the storage vessel. Notification shall be made by telephone immediately followed by written documentation demonstrating why the inspection was unplanned. Alternatively, this notification including the written documentation may be made in writing and sent by express mail so that it is received by the Administrator at least 7 days prior to the refilling.

§ 60.114b Alternative means of emission limitation.

(a) If, in the Administrator's judgment, an alternative means of emission limitation will achieve a reduction in emissions at least equivalent to the reduction in emissions achieved by any requirement in § 60.112b, the Administrator will publish in the FEDERAL REGISTER a notice permitting the use of the alternative means for purposes of compliance with that requirement.

(b) Any notice under paragraph (a) of this section will be published only after notice and an opportunity for a hearing.

(c) Any person seeking permission under this section shall submit to the Administrator a written application including:

(1) An actual emissions test that uses a full-sized or scale-model storage vessel that accurately collects and measures all VOC emissions from a given control device and that accurately simulates wind and accounts for other emission variables such as temperature and barometric pressure.

(2) An engineering evaluation that the Administrator determines is an accurate method of determining equivalence.

(d) The Administrator may condition the permission on requirements that may be necessary to ensure operation and maintenance to achieve the same emissions reduction as specified in § 60.112b.

§ 60.115b Reporting and recordkeeping requirements.

The owner or operator of each storage vessel as specified in § 60.112b(a) shall keep records and furnish reports as required by paragraphs (a), (b), or (c) of this section depending upon the control equipment installed to meet the requirements of § 60.112b. The owner or operator shall keep copies of all reports and records required by this section, except for the record required by (c)(1), for at least 2 years. The record required by (c)(1) will be kept for the life of the control equipment.

(a) After installing control equipment in accordance with § 60.112b(a)(1) (fixed roof and internal floating roof), the owner or operator shall meet the following requirements.

(1) Furnish the Administrator with a report that describes the control equipment and certifies that the control equipment meets the specifications of § 60.112b(a)(1) and § 60.113b(a)(1). This report shall be an attachment to the notification required by § 60.7(a)(3).

(2) Keep a record of each inspection performed as required by § 60.113b (a)(1), (a)(2), (a)(3), and (a)(4). Each record shall identify the storage vessel on which the inspection was performed and shall contain the date the vessel was inspected and the observed condition of each component of the control equipment (seals, internal floating roof, and fittings).

(3) If any of the conditions described in § 60.113b(a)(2) are detected during the annual visual inspection required by § 60.113b(a)(2), a report shall be furnished to the Administrator within 30 days of the inspection. Each report shall identify the storage vessel, the nature of the defects, and the date the storage vessel was emptied or the nature of and date the repair was made.

(4) After each inspection required by § 60.113b(a)(3) that finds holes or tears in the seal or seal fabric, or defects in the internal floating roof, or other control equipment defects listed in § 60.113b(a)(3)(ii), a report shall be furnished to the Administrator within 30 days of the inspection. The report shall identify the storage vessel and the reason it did not meet the specifications of § 61.112b(a)(1) or § 60.113b(a)(3) and list each repair made.

§ 60.116b Monitoring of operations.

(a) The owner or operator shall keep copies of all records required by this section, except for the record required by paragraph (b) of this section, for at least 2 years. The record required by paragraph (b) of this section will be kept for the life of the source.

(b) The owner or operator of each storage vessel as specified in § 60.110b(a) shall keep readily accessible records showing the dimension of the storage vessel and an analysis showing the capacity of the storage vessel.

(c) Except as provided in paragraphs (f) and (g) of this section, the owner or operator of each storage vessel either with a design capacity greater than or equal to 151 m³ storing a liquid with a maximum true vapor pressure greater than or equal to 3.5 kPa or with a design capacity greater than or equal to 75 m³ but less than 151 m³ storing a liquid with a maximum true vapor pressure greater than or equal to 15.0 kPa shall maintain a record of the VOL stored, the period of storage, and the maximum true vapor pressure of that VOL during the respective storage period.

(d) Except as provided in paragraph (g) of this section, the owner or operator of each storage vessel either with a design capacity greater than or equal to 151 m³ storing a liquid with a maximum true vapor pressure that is normally less than 5.2 kPa or with a design capacity greater than or equal to 75 m³ but less than 151 m³ storing a liquid with a maximum true vapor pressure that is normally less than 27.6 kPa shall notify the Administrator within 30 days when the maximum true vapor pressure of the liquid exceeds the respective maximum true vapor pressure values for each volume range.

(e) Available data on the storage temperature may be used to determine the maximum true vapor pressure as determined below.

(1) For vessels operated above or below ambient temperatures, the maximum true vapor pressure is calculated based upon the highest expected calendar-month average of the storage temperature. For vessels operated at ambient temperatures, the maximum true vapor pressure is calculated based upon the maximum local monthly average ambient temperature as reported by the National Weather Service.

- (2) For crude oil or refined petroleum products the vapor pressure may be obtained by the following:
- (i) Available data on the Reid vapor pressure and the maximum expected storage temperature based on the highest expected calendar-month average temperature of the stored product may be used to determine the maximum true vapor pressure from nomographs contained in API Bulletin 2517 (incorporated by reference—see § 60.17), unless the Administrator specifically requests that the liquid be sampled, the actual storage temperature determined, and the Reid vapor pressure determined from the sample(s).
 - (ii) The true vapor pressure of each type of crude oil with a Reid vapor pressure less than 13.8 kPa or with physical properties that preclude determination by the recommended method is to be determined from available data and recorded if the estimated maximum true vapor pressure is greater than 3.5 kPa.
- (3) For other liquids, the vapor pressure:
- (i) May be obtained from standard reference texts, or
 - (ii) Determined by ASTM D2879-83, 96, or 97 (incorporated by reference—see § 60.17); or
 - (iii) Measured by an appropriate method approved by the Administrator; or
 - (iv) Calculated by an appropriate method approved by the Administrator.
- (f) The owner or operator of each vessel storing a waste mixture of indeterminate or variable composition shall be subject to the following requirements.
- (1) Prior to the initial filling of the vessel, the highest maximum true vapor pressure for the range of anticipated liquid compositions to be stored will be determined using the methods described in paragraph (e) of this section.
 - (2) For vessels in which the vapor pressure of the anticipated liquid composition is above the cutoff for monitoring but below the cutoff for controls as defined in § 60.112b(a), an initial physical test of the vapor pressure is required; and a physical test at least once every 6 months thereafter is required as determined by the following methods:
 - (i) ASTM D2879-83, 96, or 97 (incorporated by reference—see § 60.17); or
 - (ii) ASTM D323-82 or 94 (incorporated by reference—see § 60.17); or
 - (iii) As measured by an appropriate method as approved by the Administrator.

§ 60.117b Delegation of authority.

- (a) In delegating implementation and enforcement authority to a State under section 111(c) of the Act, the authorities contained in paragraph (b) of this section shall be retained by the Administrator and not transferred to a State.



Final Permit-to-Install and Operate
BUCKEYE PIPE LINE CO- MANTUA STATION
Permit Number: P0120925
Facility ID: 1667050023
Effective Date: 6/13/2016

(b) Authorities which will not be delegated to States: §§ 60.111b(f)(4), 60.114b, 60.116b(e)(3)(iii), 60.116b(e)(3)(iv), and 60.116b(f)(2)(iii).



Final Permit-to-Install and Operate
BUCKEYE PIPE LINE CO- MANTUA STATION
Permit Number: P0120925
Facility ID: 1667050023
Effective Date: 6/13/2016

C. Emissions Unit Terms and Conditions



1. Emissions Unit Group -Non NSPS Storage Tanks: T005,T006,T011,

EU ID	Operations, Property and/or Equipment Description
T005	Petroleum liquids storage vessel, 1,328,838 gallon capacity, fixed roof tank with internal floating roof, located at a gasoline pipeline breakout station.
T006	Petroleum liquids storage vessel, 1,331,232 gallon capacity, fixed roof tank with internal floating roof, located at a gasoline pipeline breakout station
T011	Petroleum liquids storage vessel, 31,878 gallon capacity, fixed roof tank, located at a gasoline pipeline breakout station.

a) This permit document constitutes a permit-to-install issued in accordance with ORC 3704.03(F) and a permit-to-operate issued in accordance with ORC 3704.03(G).

(1) For the purpose of a permit-to-install document, the emissions unit terms and conditions contained in this permit are federally enforceable with the exception of those listed below which are enforceable under state law only.

a. None.

(2) For the purpose of a permit-to-operate document, the emissions unit terms and conditions contained in this permit are federally enforceable with the exception of those listed below which are enforceable under state law only.

a. None.

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operation(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures are identified below. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC rule 3745-31-05(A)(3)	<p>The permittee shall comply with all of the terms and conditions of this permit.</p> <p>Volatile organic compound (VOC) emissions from emissions unit T011 shall not exceed 3.1 tons per year.</p> <p>Emissions unit T011 shall be equipped with submerged fill pipe(s) to within 6 inches of the bottom of the storage tank.</p>
b.	OAC rule 3745-21-09(L)	See b)(2)b., d)(1) and e(1) below.
c.	40 CFR Part 63, Subpart R	Exempt. This pipeline breakout station is an area source (i.e., not a major source of hazardous air pollutants), not subject to



	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
		the control requirements of 40 CFR part 63, Subpart R (§§63.423 and 63.424).

(2) Additional Terms and Conditions

- a. The permittee shall apply for and, if required, obtain a modification to this permit or obtain a new final permit-to-install and operate (PTIO) prior to making any change to equipment, change in materials stored, change in the method of operation, or any other change to this emissions unit that results in an increase in the allowable emissions or results in an increase in emissions of greater than the de minimis levels in OAC rule 3745-15-05 of any type of air contaminant not previously emitted.
- b. No person shall place, store, or hold in a fixed roof tank any petroleum liquid with a true vapor pressure which is greater than 1.52 pounds per square inch absolute after the date specified in paragraph (C)(11) of rule 3745-21-04 of the Administrative Code unless such tank, is designed or equipped as follows, except where exempted under paragraph (L)(2) of this rule:
 - i. Vapor control equipment which is one of the following:
 - (a) Internal floating roof; or
 - (b) Alternative equivalent control for VOC emissions as may be approved by the director.
 - ii. If equipped with an internal floating roof, the automatic bleeder vents are to be closed at all times except when the roof is floated off or landed on the roof leg supports, and the rim vents, if provided, are to be set to open when the roof is being floated off the roof leg supports or is at the manufacturer's recommended setting.
 - iii. All openings, except stub drains, are to be equipped with a cover, seal or lid which is to be in a closed position at all times except when in actual use for tank gauging or sampling.
 - iv. Other means for reducing the emission of VOC into the ambient air as may be required by the director.
- c) Operational Restrictions
 - (1) None.

d) Monitoring and/or Recordkeeping Requirements

- (1) Any owner or operator of a fixed roof tank that is not exempted pursuant to paragraph (L)(2) of this rule shall maintain records of the following information in a readily accessible location for at least five years and shall make copies of the records available to the director upon verbal or written request:
 - a. the types of petroleum liquids stored in the tank; and
 - b. the maximum true vapor pressure (in pounds per square inch absolute), as stored, of each petroleum liquid that has a maximum true vapor pressure greater than 1.0 pound per square inch absolute.

e) Reporting Requirements

- (1) If an owner or operator places, stores, or holds in a fixed roof tank, that is not exempted pursuant to paragraph (L)(2) of this rule, any petroleum liquid with a true vapor pressure which is greater than 1.52 pounds per square inch absolute and such tank does not comply with the requirements of paragraph (L)(1) of this rule, the owner or operator shall so notify the director within thirty days of becoming aware of the occurrence.
- (2) The permittee shall submit an annual Permit Evaluation Report (PER) to the Ohio EPA District Office or Local Air Agency by the due date identified in the Authorization section of this permit. The PER shall cover a reporting period of no more than twelve-months for each air contaminant source identified in this permit. It is recommended that the PER is submitted electronically through the Ohio EPA's "e-Business Center: Air Services", although PERs can be submitted via U.S. postal service or can be hand delivered.

f) Testing Requirements

- (1) Compliance with the Emissions Limitations and/or Control Requirements specified in section b) of these terms and conditions shall be determined in accordance with the following methods:
 - a. Emissions Limitation:

VOC emissions from emissions unit T011 shall not exceed 3.1 tons per year.

Applicable Compliance Method:

Compliance with shall be determined in accordance with the methods and formulas outlined in AP-42, Storage of Organic Liquids, Section 7.1.

g) Miscellaneous Requirements

- (1) None.



2. Emissions Unit Group -Subpart Ka Storage Tanks: T008,T009,

EU ID	Operations, Property and/or Equipment Description
T008	Petroleum liquids storage vessel, 3,344,208 gallon capacity, fixed roof tank with internal floating roof, located at a gasoline pipeline breakout station.
T009	Petroleum liquids storage vessel, 2,310,000 gallon capacity, fixed roof tank, located at a gasoline pipeline breakout station.

a) This permit document constitutes a permit-to-install issued in accordance with ORC 3704.03(F) and a permit-to-operate issued in accordance with ORC 3704.03(G).

(1) For the purpose of a permit-to-install document, the emissions unit terms and conditions contained in this permit are federally enforceable with the exception of those listed below which are enforceable under state law only.

a. None.

(2) For the purpose of a permit-to-operate document, the emissions unit terms and conditions contained in this permit are federally enforceable with the exception of those listed below which are enforceable under state law only.

a. None.

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operation(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures are identified below. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC rule 3745-31-05(A)(3) (PTI 16-00120 for T008, Tank 512) (PTI 16-00583 for T009, Tank 501)	The permittee shall comply with all of the terms and conditions of this permit. Volatile organic compound (VOC) emissions from emissions unit T009 shall not exceed 1.36 tons per year. Each emissions unit shall be equipped with submerged fill pipe(s) to within 6 inches of the bottom of the storage tank.
b.	OAC rule 3745-21-09(L)	See b)(2)b., d)(1) and e(1) below.
c.	40 CFR Part 60, Subpart Ka [Standards of Performance for Storage Vessels for Petroleum Liquids for Which Construction, Reconstruction, or Modification	See term #3 of “ B. Facility-Wide Terms and Conditions ” above for applicable requirements for this affected facility.



	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
	Commenced After May 18, 1978, and Prior to July 23, 1984]	
d.	40 CFR Part 63, Subpart R	Exempt. This pipeline breakout station is an area source (i.e., not a major source of hazardous air pollutants), not subject to the control requirements of 40 CFR part 63, Subpart R (§§63.423 and 63.424).

(2) Additional Terms and Conditions

- a. The permittee shall apply for and, if required, obtain a modification to this permit or obtain a new final permit-to-install and operate (PTIO) prior to making any change to equipment, change in materials stored, change in the method of operation, or any other change to this emissions unit that results in an increase in the allowable emissions or results in an increase in emissions of greater than the de minimis levels in OAC rule 3745-15-05 of any type of air contaminant not previously emitted.
- b. No person shall place, store, or hold in a fixed roof tank any petroleum liquid with a true vapor pressure which is greater than 1.52 pounds per square inch absolute after the date specified in paragraph (C)(11) of rule 3745-21-04 of the Administrative Code unless such tank, is designed or equipped as follows, except where exempted under paragraph (L)(2) of this rule:
 - i. Vapor control equipment which is one of the following:
 - (a) Internal floating roof; or
 - (b) Alternative equivalent control for VOC emissions as may be approved by the director.
 - ii. If equipped with an internal floating roof, the automatic bleeder vents are to be closed at all times except when the roof is floated off or landed on the roof leg supports, and the rim vents, if provided, are to be set to open when the roof is being floated off the roof leg supports or is at the manufacturer's recommended setting.
 - iii. All openings, except stub drains, are to be equipped with a cover, seal or lid which is to be in a closed position at all times except when in actual use for tank gauging or sampling.
 - iv. Other means for reducing the emission of VOC into the ambient air as may be required by the director.

- c) Operational Restrictions
 - (1) None.
- d) Monitoring and/or Recordkeeping Requirements
 - (1) Any owner or operator of a fixed roof tank that is not exempted pursuant to paragraph (L)(2) of this rule shall maintain records of the following information in a readily accessible location for at least five years and shall make copies of the records available to the director upon verbal or written request:
 - a. the types of petroleum liquids stored in the tank; and
 - b. the maximum true vapor pressure (in pounds per square inch absolute), as stored, of each petroleum liquid that has a maximum true vapor pressure greater than 1.0 pound per square inch absolute.
- e) Reporting Requirements
 - (1) If an owner or operator places, stores, or holds in a fixed roof tank, that is not exempted pursuant to paragraph (L)(2) of this rule, any petroleum liquid with a true vapor pressure which is greater than 1.52 pounds per square inch absolute and such tank does not comply with the requirements of paragraph (L)(1) of this rule, the owner or operator shall so notify the director within thirty days of becoming aware of the occurrence.
 - (2) The permittee shall submit an annual Permit Evaluation Report (PER) to the Ohio EPA District Office or Local Air Agency by the due date identified in the Authorization section of this permit. The PER shall cover a reporting period of no more than twelve-months for each air contaminant source identified in this permit. It is recommended that the PER is submitted electronically through the Ohio EPA's "e-Business Center: Air Services", although PERs can be submitted via U.S. postal service or can be hand delivered.
- f) Testing Requirements
 - (1) Compliance with the Emissions Limitations and/or Control Requirements specified in section b) of these terms and conditions shall be determined in accordance with the following methods:
 - a. Emissions Limitation:

VOC emissions from emissions unit T009 shall not exceed 1.36 tons per year.

Applicable Compliance Method:

Compliance with shall be determined in accordance with the methods and formulas outlined in AP-42, Storage of Organic Liquids, Section 7.1.
- g) Miscellaneous Requirements
 - (1) None.

3. Emissions Unit Group -Subpart Kb Storage Tank: T010,

EU ID	Operations, Property and/or Equipment Description
T010	Petroleum liquids storage vessel, 630,000 gallon capacity, fixed roof tank with internal floating roof, located at a gasoline pipeline breakout station.

a) This permit document constitutes a permit-to-install issued in accordance with ORC 3704.03(F) and a permit-to-operate issued in accordance with ORC 3704.03(G).

(1) For the purpose of a permit-to-install document, the emissions unit terms and conditions contained in this permit are federally enforceable with the exception of those listed below which are enforceable under state law only.

a. None.

(2) For the purpose of a permit-to-operate document, the emissions unit terms and conditions contained in this permit are federally enforceable with the exception of those listed below which are enforceable under state law only.

a. None.

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operation(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures are identified below. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC rule 3745-31-05(A)(3) (PTI 16-01494)	The permittee shall comply with all of the terms and conditions of this permit. This emissions unit shall be equipped with submerged fill pipe(s) to within 6 inches of the bottom of the storage tank.
b.	OAC rule 3745-21-09(L)	See b)(2)b., d)(1) and e(1) below.
c.	40 CFR Part 60, Subpart Kb [Standards of Performance for Volatile Organic Liquid Storage Vessels (Including Petroleum Liquid Storage Vessels) for Which Construction, Reconstruction, or Modification Commenced After July 23, 1984]	See term #4 of “ B. Facility-Wide Terms and Conditions ” above for applicable requirements for this affected facility.
d.	40 CFR Part 63, Subpart R	Exempt. This pipeline breakout station is an area source (i.e., not a major source of hazardous air pollutants), not subject to



	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
		the control requirements of 40 CFR part 63, Subpart R (§§63.423 and 63.424).

(2) Additional Terms and Conditions

- a. The permittee shall apply for and, if required, obtain a modification to this permit or obtain a new final permit-to-install and operate (PTIO) prior to making any change to equipment, change in materials stored, change in the method of operation, or any other change to this emissions unit that results in an increase in the allowable emissions or results in an increase in emissions of greater than the de minimis levels in OAC rule 3745-15-05 of any type of air contaminant not previously emitted.
- b. No person shall place, store, or hold in a fixed roof tank any petroleum liquid with a true vapor pressure which is greater than 1.52 pounds per square inch absolute after the date specified in paragraph (C)(11) of rule 3745-21-04 of the Administrative Code unless such tank, is designed or equipped as follows, except where exempted under paragraph (L)(2) of this rule:
 - i. Vapor control equipment which is one of the following:
 - (a) Internal floating roof; or
 - (b) Alternative equivalent control for VOC emissions as may be approved by the director.
 - ii. If equipped with an internal floating roof, the automatic bleeder vents are to be closed at all times except when the roof is floated off or landed on the roof leg supports, and the rim vents, if provided, are to be set to open when the roof is being floated off the roof leg supports or is at the manufacturer's recommended setting.
 - iii. All openings, except stub drains, are to be equipped with a cover, seal or lid which is to be in a closed position at all times except when in actual use for tank gauging or sampling.
 - iv. Other means for reducing the emission of VOC into the ambient air as may be required by the director.
- c) Operational Restrictions
 - (1) None.
- d) Monitoring and/or Recordkeeping Requirements
 - (1) Any owner or operator of a fixed roof tank that is not exempted pursuant to paragraph (L)(2) of this rule shall maintain records of the following information in a readily

accessible location for at least five years and shall make copies of the records available to the director upon verbal or written request:

- a. the types of petroleum liquids stored in the tank; and
- b. the maximum true vapor pressure (in pounds per square inch absolute), as stored, of each petroleum liquid that has a maximum true vapor pressure greater than 1.0 pound per square inch absolute.

e) Reporting Requirements

- (1) If an owner or operator places, stores, or holds in a fixed roof tank, that is not exempted pursuant to paragraph (L)(2) of this rule, any petroleum liquid with a true vapor pressure which is greater than 1.52 pounds per square inch absolute and such tank does not comply with the requirements of paragraph (L)(1) of this rule, the owner or operator shall so notify the director within thirty days of becoming aware of the occurrence.
- (2) The permittee shall submit an annual Permit Evaluation Report (PER) to the Ohio EPA District Office or Local Air Agency by the due date identified in the Authorization section of this permit. The PER shall cover a reporting period of no more than twelve-months for each air contaminant source identified in this permit. It is recommended that the PER is submitted electronically through the Ohio EPA's "e-Business Center: Air Services", although PERs can be submitted via U.S. postal service or can be hand delivered.

f) Testing Requirements

- (1) Compliance with the Emissions Limitations and/or Control Requirements specified in section b) of these terms and conditions shall be determined in accordance with the following methods:
 - a. There are no numerical mass emission limitations, established pursuant to OAC rule 3745-31-05(A)(3) or applicable from OAC rule 3745-21-09(L), for this emissions unit.

g) Miscellaneous Requirements

- (1) None.