



State of Ohio Environmental Protection Agency

RECEIVED

Ham PTD K004

MAR 05 2007

Street Address:

Lazarus Gov. Center  
50 West Town Street, Suite 700  
Columbus, OH 43215

TELE: (614) 644-3020 FAX: (614) 644-2329

Mailing Address:

Lazarus Gov. Center  
P.O. Box 1049  
Columbus, OH 43216-1049

Ohio Environmental  
Protection Agency  
Southeast District

02/27/07

CERTIFIED MAIL

RE: Final Chapter 3745-35 Permit To Operate

K004 (Mitsubishi 750 XL) Heatset Web Offset  
Lithographic Printing Press

Freeport Press Inc. (06-34-00-0058)  
David Pilcher  
PO Box 198  
Freeport, OH 43973

Dear David Pilcher:

The enclosed Permit(s) to Operate allow you to operate the described emissions unit(s) in the manner indicated in the Permit(s). Because each permit contains several terms and conditions, I urge you to read them carefully.

The Ohio EPA is urging companies to investigate pollution prevention and energy conservation. Not only will this reduce pollution and energy consumption, but it can also save you money. If you would like to learn ways you can save money while protecting the environment, please contact our Office of Compliance Assistance and Pollution Prevention at (800) 329-7518. For more information related to air pollution control in Ohio, visit [www.epa.state.oh/dapc](http://www.epa.state.oh/dapc).

You are hereby notified that this action of the Director is final and may be appealed to the Environmental Review Appeals Commission pursuant to Section 3745.04 of the Ohio Revised Code. The appeal must be in writing and set forth the action complained of and the grounds upon which the appeal is based. The appeal must be filed with the Commission within thirty (30) days after notice of the Director's action. The appeal must be accompanied by a filing fee of \$70.00 which the Commission, in its discretion, may reduce if by affidavit you demonstrate that payment of the full amount of the fee would cause extreme hardship. Notice of the filing of the appeal shall be filed with the Director within three (3) days of filing with the Commission. Ohio EPA requests that a copy of the appeal be served upon the Ohio Attorney General's Office, Environmental Enforcement Section. An appeal may be filed with the Environmental Review Appeals Commission at the following address:

Environmental Review Appeals Commission  
309 South Fourth Street, Room 222  
Columbus, OH 43215

If you have any questions, please contact Southeast District Office.

Sincerely,

Michael W. Ahern  
Permit Issuance and Data Management Section  
Division of Air Pollution Control

cc: Southeast District Office



State of Ohio Environmental Protection Agency

## Final Permit To Operate An Emissions Unit

Effective Date: 02/27/07

Expiration Date: 02/27/12

This document constitutes issuance to:

Facility ID: 06-34-00-0058  
Freeport Press Inc.  
121 Main Street  
Freeport, OH 43973

of a permit to operate for:

K004 (Mitsubishi 750 XL)  
Heatset Web Offset-Lithographic Printing Press

You will be contacted six months prior to the expiration date regarding the renewal of this permit. If you are not contacted, please contact the appropriate Ohio EPA District Office or local air agency identified below. This permit and the authorization to operate the air contaminant source (emissions unit) at this facility shall expire at midnight on the expiration date shown above. If a renewal permit is not issued prior to the expiration date, the permittee may continue to operate pursuant to OAC Chapter 3745-35 and in accordance with the terms of this permit beyond the expiration date, provided that a complete renewal application is submitted no earlier than eighteen (18) months and no later than one-hundred eighty (180) days prior to the expiration date.

Described below is the Ohio EPA District Office or local air agency that is responsible for processing and administering your permit:

Southeast District Office  
2195 Front Street  
Logan, OH 43138  
(740) 385-8501

This permit is granted subject to the conditions attached hereto.

Ohio Environmental Protection Agency

A handwritten signature in cursive script that reads "Chris Korleski".

---

Chris Korleski  
Director

## Part I: General Terms and Conditions

### 1. Compliance Requirements

The above-described emissions unit is and shall remain in full compliance with all applicable State and federal laws and regulations and the terms and conditions of this permit.

### 2. Permit to Install Requirement

Prior to the "installation" or "modification" of any "air contaminant source," as those terms are defined in OAC rule 3745-31-01, a permit to install must be obtained from the Ohio EPA pursuant to OAC Chapter 3745-31.

### 3. Reporting Requirements Related to Monitoring and Recordkeeping Requirements

The permittee shall submit required reports in the following manner:

- a. Reports of any required monitoring and/or recordkeeping information shall be submitted to the appropriate Ohio EPA District Office or local air agency.
- b. Except as otherwise may be provided in the terms and conditions for a specific emissions unit, quarterly written reports of (a) any deviations (excursions) from emission limitations, operational restrictions, and control device operating parameter limitations that have been detected by the testing, monitoring, and recordkeeping requirements specified in this permit, (b) the probable cause of such deviations, and (c) any corrective actions or preventive measures which have been or will be taken, shall be submitted to the appropriate Ohio EPA District Office or local air agency. If no deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted quarterly, i.e., by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters. (These quarterly reports shall exclude deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06.)

### 4. Records Retention Requirements

Each record of any monitoring data, testing data, and support information required pursuant to this permit shall be retained for a period of five years from the date the record was created. Support information shall include, but not be limited to, all calibration and maintenance records and all original strip-chart recordings for continuous monitoring instrumentation, and copies of all reports required by the permit. Such records may be maintained in computerized form.

### 5. Inspections and Information Requests

The Director of the Ohio EPA, or an authorized representative of the Director, may, subject to the safety requirements of the permittee and without undue delay, enter upon the premises of this source at any reasonable time for purposes of making inspections, conducting tests, examining records or reports pertaining to any emission of air contaminants, and determining compliance with any applicable State and federal air pollution laws and regulations and the terms and conditions of this permit. The permittee shall furnish to the Director of the Ohio EPA, or an authorized representative of the Director, upon receipt of a written request and within a reasonable time, any information that may be requested

to determine whether cause exists for modifying, reopening or reissuing this permit or to determine compliance with this permit. Upon verbal or written request, the permittee shall also furnish to the Director of the Ohio EPA, or an authorized representative of the Director, copies of records required to be kept by this permit.

**6. Scheduled Maintenance/Malfunction Reporting**

Any scheduled maintenance of air pollution control equipment shall be performed in accordance with paragraph (A) of OAC rule 3745-15-06. The malfunction of any emissions unit or any associated air pollution control system(s) shall be reported to the appropriate Ohio EPA District Office or local air agency in accordance with paragraph (B) of OAC rule 3745-15-06. Except as provided in that rule, any scheduled maintenance or malfunction necessitating the shutdown or bypassing of any air pollution control system(s) shall be accompanied by the shutdown of this emissions unit(s) that is (are) served by such control system(s).

**7. Permit Transfers**

Any transferee of this permit shall assume the responsibilities of the prior permittee. The appropriate Ohio EPA District Office or local air agency must be notified in writing of any transfer of this permit.

**8. Air Pollution Nuisance**

The air contaminants emitted by the emissions units covered by this permit shall not cause a public nuisance, in violation of OAC rule 3745-15-07.

**9. Permit Renewal**

Approximately six months prior to the expiration date of this permit, a notice regarding the renewal of this permit will be sent to the permittee's designated facility contact. If you are not contacted, please contact the following Ohio EPA District Office or local air agency which has jurisdiction in the area in which the facility is located:

Southeast District Office  
2195 Front Street  
Logan, OH 43138  
(740) 385-8501

It is the permittee's responsibility to renew this permit even if no notice of its expiration is received.

**Part II: Special Terms and Conditions**

**A. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/ Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
Mitsubishi L750XL (45000 lph) Heatset Web Offset Lithographic printing Press with a 11.8 MMBtu drying oven vented to a 4.3 MMBtu Regenerative Thermal Oxidizer (RTO).	OAC rule 3745-31-05(A)(3) (PTI 06-08125)	<p>Particulate emissions (PE) shall not exceed 0.12 lb/hr and 0.53 TPY.</p> <p>Visible particulate emissions from the RTO exhaust stack shall not exceed 0 % opacity , as a six minute average.</p> <p>Emissions of nitrogen oxides (NOx) shall not exceed 1.61 lbs/hour, 7.05 TPY.</p> <p>Emissions of carbon monoxide (CO) shall not exceed 1.35 lbs/hour, 5.92 TPY.</p> <p>Emissions of organic compounds (OC) shall not exceed 2.2 lbs/hour and 9.67 TPY.</p> <p>The requirements of this rule also include compliance with the requirements of OAC rules 3745-17-07(A)(1), 3745-21-07(G)(2), 3745-31-05(C).</p>
	OAC rule 3745-17-11(B)	<p>See Section A.2.a. and A.2.b. below.</p> <p>The uncontrolled mass rate of particulate emissions (PE) from this emissions unit is less than 10 pounds/hour. Therefore, pursuant to OAC rule 3745-17-11(A)(2)(a)(ii), Figure II of OAC rule 3745-17-11 does not apply. In addition, Table I of OAC rule 3745-17-11 does not apply since the facility is located in Harrison County, which is identified as a P-3 county.</p>
	OAC rule 3745-17-07(A)	<p>This emissions unit is not subject to the visible PE limitations specified in OAC rule 3745-17-07(A) pursuant to OAC rule 3745-17-07(A)(3)(h) because OAC rule 3745-17-11 is not applicable.</p>

**Operations, Property,  
and/or Equipment**

**Applicable Rules/  
Requirements**

**Applicable Emissions  
Limitations/Control  
Measures**

OAC rule 3745-21-07(G)(2)

The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).

OAC rule 3745-21-08 (B)

See Section A.2.c below.

**2. Additional Terms and Conditions**

**2.a** The OC emission limitation of 2.2 lbs/hour for emissions unit K004 is based on the following information:

- i. The percentage of the ink solvent retained on the web after the dryer is 20 percent\*;
- ii. The percentage of the fountain solution solvent available for capture in the dryer is 70 percent\*;
- iii. The percentage of the auto blanket wash (clean up) solvent available for capture in the dryer is 40 percent\*; and,
- iv. The percentage of the hand blanket wash (clean up) solvent retained on the cloths is 50 percent\*\*.

\* This is based on the draft Control Techniques Guideline (Control of Volatile Organic Compound Emissions from Offset Lithographic Printing, dated September 1993) and the Alternative Control Techniques document, dated November 8, 1993.

\*\* This is based on information supplied by the permittee.

**2.b** The permittee shall employ best available technology (BAT) on this emissions unit. BAT has been determined to be the use of a control system for OC emissions, meeting the following requirements:

- i. The control system shall consist of a collection system for the dryer. The collection system shall achieve a capture efficiency of 100 percent of the press dryer exhaust; and,
- ii. The control system shall be equipped with a regenerative thermal oxidizer with a destruction efficiency of at least 95 percent.

**2.c** The permittee has satisfied the "best available control techniques and operating practices" required pursuant to OAC rule 3745-21-08(B) by committing to comply with the best available technology requirements established pursuant to OAC rule 3745-31-05(A)(3) in this Permit to Install.

On November 5, 2002, OAC rule 3745-21-08 was revised to delete paragraph (B); therefore, paragraph (B) is no longer part of the State regulations. However, that rule revision has not yet been submitted to the U.S. EPA as a revision to Ohio's State Implementation Plan (SIP). Therefore, until the SIP revision occurs and the U.S. EPA approves the revisions to OAC rule 3745-21-08, the requirement to satisfy the "best available control techniques and operating practices" still exists as part of the federally-approved SIP for Ohio.

**B. Operational Restrictions**

1. The average temperature within the regenerative thermal oxidizer, for any 3-hour block of time when the emissions unit is in operation, shall not be less than 1,450 degrees Fahrenheit. A lower average temperature requirement may be established if compliance with the minimum destruction efficiency in A.2.b is demonstrated during emissions testing.

**C. Monitoring and/or Record Keeping Requirements**

1. The permittee shall maintain monthly records which list the following information for each graphic arts material (ink, fountain solution, cleanup material, and blanket wash) employed in emissions unit K004:

- 1.a The name and identification number of each graphic arts material employed;

**C. Monitoring and/or Record Keeping Requirements (continued)**

- 1.b Documentation on whether or not each material employed is a photochemically reactive material;
- 1.c The OC content of each graphic arts material, in lbs/gallon or pounds/pound for inks, as received;
- 1.d The quantity of each graphic arts material employed, in gallons or lbs of each material per month;
- 1.e The OC emissions for each graphic arts material employed, in tons/month, calculated as follows:

$$E_n = [U_n \times V_n \times (1 - R_n/100) \times \{1 - (C_n/100) \times (K/100)\}]$$

where:

$E_n$  = OC emissions from an individual material (pounds of OC emitted/month);

$U_n$  = total usage of the individual material - typically ink, fountain solution, and cleaning solvents (lbs or gallons of material/month);

$V_n$  = average OC content of material as determined by Method 24 (lb OC/lb or gallon of material);

$R_n$  = percent of OC retained on the web or on cloths:

$R_n$  = 20 for inks

$R_n$  = 0 for fountain solutions

$R_n$  = 0 for auto blanket wash (cleanup) solvent

$R_n$  = 50 for hand blanket wash (cleanup) solvent

$C_n$  = capture efficiency for individual material emitted:

$C_n$  = 100 for inks

$C_n$  = 70 for fountain solutions

$C_n$  = 40 for auto blanket wash (cleanup) solvent

$C_n$  = 0 for hand blanket wash (cleanup) solvent; and

$K$  = destruction efficiency as determined during the performance test as specified in condition E.2.

- 1.f The total OC emission rate of all graphic arts materials employed, in tons/month, calculated as follows:

$$EM = E_1 + E_2 + E_3 + \dots + E_n$$

where:

$EM$  = Monthly OC emissions, in lbs/month; and,

$E_1$  through  $E_n$  = OC emissions from each individual graphic arts material (condition C.1.e).

- 1.g The number of hours this emissions unit was in operation, when graphic arts materials were being applied or employed (hours/month);
- 1.h The average hourly OC emission rate, i.e., "f" divided by "g", above;
- 2. The permittee shall operate and maintain continuous temperature monitor(s)\* and a temperature recorder which measures and records the average temperature within the regenerative thermal oxidizer when the emissions unit is in operation. Units shall be in degrees Fahrenheit. The monitoring and recording devices shall be capable of accurately measuring the desired parameter. The temperature monitor(s) and recorder shall be installed, calibrated, operated and maintained in accordance with the manufacturer's recommendations, with any modifications deemed necessary by the permittee.

\*If the temperature monitoring system consists of several temperature monitors from which an average temperature is obtained.

The permittee shall collect and record the following information each day for this emissions unit:

- 2.a All 3-hour blocks of time during which the average temperature within the regenerative thermal oxidizer, when the emissions unit was in operation, was less than the temperature limitation specified in condition B.1 of this permit; and,

**C. Monitoring and/or Record Keeping Requirements (continued)**

- 2.b A log of the downtime for the capture (collection) system, control device, and monitoring equipment, when the emissions unit was in operation.
- 3. The permittee shall perform daily checks, when the emissions unit is in operation and when the weather conditions allow, for any visible particulate emissions from the stack serving this emissions unit. The presence or absence of any visible emissions shall be noted in an operations log. If visible emissions are observed, the permittee shall also note the following in the operations log:
  - 3.a the color of the emissions;
  - 3.b the total duration of any visible emission incident; and
  - 3.c any corrective actions taken to eliminate the visible emissions.

**D. Reporting Requirements**

- 1. The permittee shall submit quarterly deviation (excursion) reports which identify exceedances of any of the following:
  - 1.a the hourly emission limitation (as a monthly average), as determined in condition C.1.
- 2. The permittee shall submit quarterly deviation (excursion) reports which identify all 3-hour blocks of time during which the average temperature within the regenerative thermal oxidizer does not comply with the temperature limitation specified in condition B.2. 1 of this permit.
- 3. The permittee shall submit quarterly deviation (excursion) reports that include a log of the downtime for the capture (collection) system and/or the regenerative thermal oxidizer when the emissions unit was in operation.
- 4. The permittee shall submit quarterly written reports that:
  - 4.a identify all days during which any visible particulate emissions were observed from the stack serving this emissions unit, and
  - 4.b describe any corrective actions taken to eliminate the visible particulate emissions.
- 5. All quarterly reports shall be submitted in accordance with the General Terms and Conditions of this permit.

**E. Testing Requirements**

- 1. Compliance Methods Requirements: Compliance with the emission limitations in condition A.1 of the terms and conditions of this permit shall be determined in accordance with the following methods:
  - 1.a Emissions Limitation:  
PE shall not exceed 0.12 lb/hour, 0.53 TPY.

Applicable Compliance Method:

Compliance may be demonstrated using the following equations based on the emission factor in AP-42, Table 1.4-2 (7/98):

$$\begin{aligned} & [4.3 \text{ MMBtu/hr (oxidizer)} + 11.8 \text{ MMBtu/hr (press)}] (7.6 \text{ lb/MCF}) / (1000 \text{ BTU/CF}) = 0.12 \text{ lb/hr PE} , \\ & (0.12 \text{ lb/hr})(8760 \text{ hrs/hr})(0.0005 \text{ lb/ton}) = 0.53 \text{ TPY} \end{aligned}$$

Annual emissions shall be determined by multiplying the hourly PE emission rate by 8760 hours per year and dividing by 2000 lbs/ton.

If required, particulate emissions shall be determined according to test Methods 1 - 5, as set forth in the "Appendix on Test Methods" in 40 CFR, Part 60 "Standards of Performance for New Stationary Sources". Alternative U.S. EPA-approved test methods may be used with prior approval from Ohio EPA, Southeast District Office.

**E. Testing Requirements (continued)**

- 1.b** Emissions Limitation:  
Visible particulate emissions from the RTO exhaust stack shall not exceed 0 % opacity , as a six minute average.

Compliance Method:

If required, visible particulate emissions shall be determined according to test Method 9 as set forth in the "Appendix on Test Methods" in 40 CFR, Part 60 "Standards of Performance for New Stationary Sources",

- 1.c** Emissions Limitation:  
Emissions of NO<sub>x</sub> shall not exceed 1.61 lbs/hour, 7.05 TPY.

Compliance Method:

Compliance may be demonstrated using the following equations based on the emission factor in AP-42, Table 1.4-1 (7/98):

$$[4.3 \text{ MMBtu/hr (oxidizer)} + 11.8 \text{ MMBtu/hr (press)}] (100 \text{ lb/MCF}) / (1000 \text{ BTU/CF}) = 1.61 \text{ lbs/hr NO}_x , \\ (1.61 \text{ lbs/hr})(8760 \text{ hrs/hr})(0.0005 \text{ lb/ton}) = 7.05 \text{ TPY}$$

Annual emissions shall be determined by multiplying the hourly NO<sub>x</sub> emission rate by 8760 hours per year and dividing by 2000 lbs/ton.

If required, nitrogen oxides emissions shall be determined according to test Methods 1 - 4, and 7 as set forth in the "Appendix on Test Methods" in 40 CFR, Part 60 "Standards of Performance for New Stationary Sources". Alternative U.S. EPA-approved test methods may be used with prior approval from Ohio EPA, Southeast District Office.

- 1.d** Emissions Limitation:  
Emissions of CO shall not exceed 1.35 lbs/hour, 5.92 TPY.

Compliance Method:

Compliance may be demonstrated using the following equations based on the emission factor in AP-42, Table 1.4-1 (7/98):

$$[4.3 \text{ MMBtu/hr (oxidizer)} + 11.8 \text{ MMBtu/hr (press)}] (84 \text{ lb/MCF}) / (1000 \text{ BTU/CF}) = 1.35 \text{ lbs/hr CO}, \\ (1.35 \text{ lbs/hr})(8760 \text{ hrs/hr})(0.0005 \text{ lb/ton}) = 5.92 \text{ TPY}$$

Annual emissions shall be determined by multiplying the hourly CO emission rate by 8760 hours per year and dividing by 2000 lbs/ton.

If required, carbon monoxide emissions shall be determined according to test Methods 1 - 4, and 10 as set forth in the "Appendix on Test Methods" in 40 CFR, Part 60 "Standards of Performance for New Stationary Sources". Alternative U.S. EPA-approved test methods may be used with prior approval from Ohio EPA, Southeast District Office.

## E. Testing Requirements (continued)

- 1.e Emissions Limitation:  
Emissions of OC shall not exceed 2.2 lbs/hour and 9.67 TPY.

Applicable Compliance Method:

The permittee shall demonstrate compliance with the hourly OC emission limitation from this emissions unit through the record keeping required in condition C.1 of this permit. Compliance may be demonstrated using the following equations based on the emission factor in AP-42, Table 1.4-2 (7/98) and recordkeeping in this permit:

$[4.3 \text{ MMBtu/hr (oxidizer)} + 11.8 \text{ MMBtu/hr (press)}] (5.5 \text{ lb/MCF}) / (1000 \text{ BTU/CF})$  plus actual emissions as calculated in C.1 from press inks = 2.2 lbs/hr OC ,  
 $(2.2 \text{ lbs/hr})(8760 \text{ hrs/hr})(0.0005 \text{ lb/ton}) = 9.67 \text{ TPY}$

Annual emissions shall be determined by multiplying the hourly OC emission rate by 8760 hours per year and dividing by 2000 lbs/ton.

If required, organic compound emissions shall be determined according to test Methods 1 - 4, and 18, 25, or 25A as set forth in the "Appendix on Test Methods" in 40 CFR, Part 60 "Standards of Performance for New Stationary Sources". Alternative U.S. EPA-approved test methods may be used with prior approval from Ohio EPA, Southeast District Office.

2. Emission testing requirements: The permittee shall conduct, or have conducted, emission testing for this emissions unit in accordance with the following requirements:
- 2.a The emission testing shall be conducted within 6 months prior to permit expiration.
- 2.b The emission testing shall be conducted to demonstrate compliance with the capture efficiency (see E.2.c.i) and destruction efficiency (see E.2.c.ii) for OC.
- 2.c The following test method(s) shall be employed to demonstrate compliance with the allowable mass emission rate:
- i. In accordance with Ohio EPA's Engineering Guide #56, the capture efficiency may be assumed to be 100 percent for organic compounds not retained in the substrate or emitted uncontrolled, provided that the press dryer maintains a negative pressure within the press dryer and the dryer exhausts to a control device (the RTO). Therefore, during testing of the RTO, the permittee shall verify that a negative pressure is maintained within the press dryer.
- ii. The destruction efficiency shall be conducted in accordance with the test methods and procedures specified in OAC rule 3745-21-10 and shall measure the percent reduction in mass emissions of organic compounds between the inlet and outlet of the thermal oxidizer. The test method selected shall be based on a consideration of the diversity of organic species present and their total concentration, and on a consideration of the potential presence of interfering gases.
- 2.d As part of the performance test, the permittee shall collect and record the average temperature within the regenerative thermal oxidizer, in degrees Fahrenheit, and include this information with the results of the emissions report specified below.
- 2.e The test(s) shall be conducted while the emissions unit is operating at its maximum capacity, unless otherwise specified or approved by the Ohio EPA Southeast District Office.

Not later than 30 days prior to the proposed test date(s), the permittee shall submit an "Intent to Test" notification to the Ohio EPA Southeast District Office. The "Intent to Test" notification shall describe in detail the proposed test methods and procedures, the emissions unit operating parameters, the time(s) and date(s) of the test(s), and the person(s) who will be conducting the test(s). Failure to submit such notification for review and approval prior to the test(s) may result in the Ohio EPA Southeast District Office's refusal to accept the results of the emission test(s).

**E. Testing Requirements (continued)**

Personnel from the Ohio EPA Southeast District Office shall be permitted to witness the test(s), examine the testing equipment, and acquire data and information necessary to ensure that the operation of the emissions unit and the testing procedures provide a valid characterization of the emissions from the emissions unit and/or the performance of the control equipment.

A comprehensive written report on the results of the emissions test(s) shall be signed by the person or persons responsible for the tests and submitted to the Ohio EPA Southeast District Office within 30 days following completion of the test(s). The permittee may request additional time for the submittal of the written report, where warranted, with prior approval from the Ohio EPA Southeast District Office.

**F. Miscellaneous Requirements**

None

