

Facility ID: 1318532615 Issuance type: Final State Permit To Operate

This version of facility specific terms and conditions was converted from a database format to an HTML file during an upgrade of the Ohio EPA, Division of Air Pollution Control's permitting software. Every attempt has been made to convert the terms and conditions to look and substantively conform to the permit issued or being drafted in STARS. However, the format of the terms may vary slightly from the original. In addition, although it is not expected, there is a slight possibility that a term and condition may have been inadvertently "left out" of this reproduction during the conversion process. Therefore, if this version is to be used as a starting point in drafting a new version of a permit, it is imperative that the entire set of terms and conditions be reviewed to ensure they substantively mimic the issued permit. The official version of any permit issued final by Ohio EPA is kept in the Agency's Legal section. The Legal section may be contacted at (614) 644-3037.

In addition to the terms and conditions, hyperlinks have been inserted into the document so you may more readily access the section of the document you wish to review.

Finally, the term language under "Part II" and before "A. Applicable Emissions Limitations..." has been added to aid in document conversion, and was not part of the original issued permit.

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION

Facility ID: 1318532615 Emissions Unit ID: P004 Issuance type: Final State Permit To Operate

[Go to the top of this document](#)

Part II - Special Terms and Conditions

This permit document constitutes a permit-to-install issued in accordance with ORC 3704.03(F) and a permit-to-operate issued in accordance with ORC 3704.03(G).

1. For the purpose of a permit-to-install document, the emissions unit terms and conditions identified below are federally enforceable with the exception of those listed below which are enforceable under state law only.
 - (a) None.
2. For the purpose of a permit-to-operate document, the emissions unit terms and conditions identified below are enforceable under state law only with the exception of those listed below which are federally enforceable.
 - (a) None.

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
Pickling Line for steel wire, controlled with a 60,000 ACFM scrubber	OAC rule 3745-31-05(A)(3) (PTI # 13-2985)	Particulate emissions shall not exceed 2.48 lbs/hr.
	OAC rule 3745-17-11(B)(1)	Visible particulate emissions shall not exceed 5% opacity, as a 6-minute average.
	OAC rule 3745-17-07(A)(1)	The emission limitation specified by this rule is equivalent to the emission limitation established pursuant to OAC rule 3745-31-05(A)(3). The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).

2. **Additional Terms and Conditions**
 - (a) None

B. Operational Restrictions

1. The pH of the scrubber liquor shall be maintained at or above 3.0 while the emissions unit is in operation.
2. The pressure drop across the scrubber shall be continuously maintained at a value of not less than 3 inches of water column at all times while the emissions unit is in operation.
3. The scrubber water flow rate shall be continuously maintained at a value of not less than 550 gallons per minute at all times while the emissions unit is in operation.

C. Monitoring and/or Record Keeping Requirements

1. The permittee shall properly install, operate and maintain equipment to continuously monitor and record the pH of the scrubber liquor while the emissions unit is in operation. The pH monitor and recorder shall be installed, calibrated, operated and maintained in accordance with the manufacturer's recommendations, instructions and operating manuals.

The permittee shall record on a daily basis the following parameters whenever this emissions unit is in operation:

- a. The pH of the scrubber liquor.
- b. A log or record of operating time for the capture (collection) system, control device, monitoring equipment, and the associated emissions unit.

2. The permittee shall properly install, operate and maintain equipment to continuously monitor the static pressure drop across the scrubber and the scrubber water flow rate while the emissions unit is in operation. The monitoring devices and any recorders shall be installed, calibrated, operated and maintained in accordance with the manufacturer's recommendations, instructions and operating manuals.

The permittee shall record on a daily basis the following parameters whenever this emissions unit is in operation:

- a. The pressure drop across the scrubber, in inches of water.
- b. The scrubber water flow rate, in gallons per minute.
- c. The operating times for the capture (collection) system, control device, monitoring equipment, and the

associated emissions unit.

D. Reporting Requirements

1. The permittee shall submit pH deviation (excursion) reports that identify all periods of time during which the scrubber liquor pH did not comply with the pH requirements specified above. Each report shall be submitted within 30 days after the deviation occurs.
2. The permittee shall submit deviation (excursion) reports that identify all periods of time during which the following scrubber parameters were not maintained at or above the required levels:
 - a. The static pressure drop across the scrubber.
 - b. The scrubber water flow rate.

Each report shall be submitted within 30 days after the deviation occurs.

E. Testing Requirements

1. Emission Limitation:
2.48 lbs/hr Particulate Emissions

Applicable Compliance Method:
If required, compliance shall be determined by testing in accordance with 40 CFR Part 60, Appendix A, Methods 1-5 and the procedures specified in OAC rule 3745-17-03.
2. Emission Limitation:
Visible particulate emissions shall not exceed 5% opacity, as a 6-minute average.

Applicable Compliance Method:
If required, compliance with the above visible particulate emission limitation shall be determined using Method 9 of 40 CFR, Part 60, Appendix A.

F. Miscellaneous Requirements

1. None