



John R. Kasich, Governor
Mary Taylor, Lt. Governor
Craig W. Butler, Director

8/12/2016

Certified Mail

Joe Kellerman
Kellerman Coach Works, Inc.
3972 Bach Buxton Road
Amelia, OH 45102

Yes	TOXIC REVIEW
No	SYNTHETIC MINOR TO AVOID MAJOR NSR
No	CEMS
No	MACT/GACT
No	NSPS
No	NESHAPS
No	NETTING
No	MODELING SUBMITTED
No	SYNTHETIC MINOR TO AVOID TITLE V
No	FEDERALLY ENFORCABLE PTIO (FEPTIO)
No	SYNTHETIC MINOR TO AVOID MAJOR GHG

RE: FINALAIR POLLUTION PERMIT-TO-INSTALL AND OPERATE

Facility ID: 1413000549
Permit Number: P0120933
Permit Type: Administrative Modification
County: Clermont

Dear Permit Holder:

Enclosed please find a final Ohio Environmental Protection Agency (EPA) Air Pollution Permit-to-Install and Operate (PTIO) which will allow you to install, modify, and/or operate the described emissions unit(s) in the manner indicated in the permit. Because this permit contains conditions and restrictions, please read it very carefully. In this letter you will find the information on the following topics:

- **How to appeal this permit**
- **How to save money, reduce pollution and reduce energy consumption**
- **How to give us feedback on your permitting experience**
- **How to get an electronic copy of your permit**
- **What should you do if you notice a spill or environmental emergency?**

How to appeal this permit

The issuance of this PTIO is a final action of the Director and may be appealed to the Environmental Review Appeals Commission pursuant to Section 3745.04 of the Ohio Revised Code. The appeal must be in writing and set forth the action complained of and the grounds upon which the appeal is based. The appeal must be filed with the Commission within thirty (30) days after notice of the Director's action. The appeal must be accompanied by a filing fee of \$70.00, made payable to "Ohio Treasurer Josh Mandel," which the Commission, in its discretion, may reduce if by affidavit you demonstrate that payment of the full amount of the fee would cause extreme hardship. Notice of the filing of the appeal shall be filed with the Director within three (3) days of filing with the Commission. Ohio EPA requests that a copy of the appeal be served upon the Ohio Attorney General's Office, Environmental Enforcement Section. An appeal may be filed with the Environmental Review Appeals Commission at the following address:

Environmental Review Appeals Commission
77 South High Street, 17th Floor
Columbus, OH 43215

How to save money, reduce pollution and reduce energy consumption

The Ohio EPA is encouraging companies to investigate pollution prevention and energy conservation. Not only will this reduce pollution and energy consumption, but it can also save you money. If you would like to learn ways you can save money while protecting the environment, please contact our Office of Compliance Assistance and Pollution Prevention at (614) 644-3469. Additionally, all or a portion of the capital expenditures related to installing air pollution control equipment under this permit may be eligible for financing and State tax exemptions through the Ohio Air Quality Development Authority (OAQDA) under Ohio Revised Code Section 3706. For more information, see the OAQDA website: www.ohioairquality.org/clean_air

How to give us feedback on your permitting experience

Please complete a survey at www.epa.ohio.gov/survey.aspx and give us feedback on your permitting experience. We value your opinion.

How to get an electronic copy of your permit

This permit can be accessed electronically via the eBusiness Center: Air Services in Microsoft Word format or in Adobe PDF on the Division of Air Pollution Control (DAPC) Web page, www.epa.ohio.gov/dapc by clicking the "Search for Permits" link under the Permitting topic on the Programs tab.

What should you do if you notice a spill or environmental emergency?

Any spill or environmental emergency which may endanger human health or the environment should be reported to the Emergency Response 24-HOUR EMERGENCY SPILL HOTLINE toll-free at (800) 282-9378. Report non-emergency complaints to the appropriate district office or local air agency.

If you have any questions regarding your permit, please contact Southwest Ohio Air Quality Agency at (513)946-7777 or the Office of Compliance Assistance and Pollution Prevention at (614) 644-3469.

Sincerely,



Michael E. Hopkins, P.E.
Assistant Chief, Permitting Section, DAPC

Cc: SWOQA



FINAL

**Division of Air Pollution Control
Permit-to-Install and Operate
for
Kellerman Coach Works, Inc.**

Facility ID:	1413000549
Permit Number:	P0120933
Permit Type:	Administrative Modification
Issued:	8/12/2016
Effective:	8/12/2016
Expiration:	8/30/2023



Division of Air Pollution Control
Permit-to-Install and Operate
for
Kellerman Coach Works, Inc.

Table of Contents

Authorization	1
A. Standard Terms and Conditions	3
1. What does this permit-to-install and operate ("PTIO") allow me to do?.....	4
2. Who is responsible for complying with this permit?	4
3. What records must I keep under this permit?	4
4. What are my permit fees and when do I pay them?.....	4
5. When does my PTIO expire, and when do I need to submit my renewal application?	4
6. What happens to this permit if my project is delayed or I do not install or modify my source?	5
7. What reports must I submit under this permit?	5
8. If I am required to obtain a Title V operating permit in the future, what happens to the operating provisions and PER obligations under this permit?	5
9. What are my obligations when I perform scheduled maintenance on air pollution control equipment? ...	5
10. Do I have to report malfunctions of emissions units or air pollution control equipment? If so, how must I report?	6
11. Can Ohio EPA or my local air agency inspect the facility where the emission unit(s) is/are located?	6
12. What happens if one or more emissions units operated under this permit is/are shut down permanently?	6
13. Can I transfer this permit to a new owner or operator?.....	7
14. Does compliance with this permit constitute compliance with OAC rule 3745-15-07, "air pollution nuisance"?	7
15. What happens if a portion of this permit is determined to be invalid?	7
B. Facility-Wide Terms and Conditions.....	8
C. Emissions Unit Terms and Conditions	10
1. P001, Spray resin application.....	11
2. P002, Gel coat spray.....	18
3. P003, Hand Lay-up	25



Final Permit-to-Install and Operate
Kellerman Coach Works, Inc.
Permit Number: P0120933
Facility ID: 1413000549
Effective Date: 8/12/2016

Authorization

Facility ID: 1413000549
Application Number(s): A0053393, A0053409, M0004045
Permit Number: P0120933
Permit Description: Administrative Modification of PTI P0118854. This permitting action covers P001 Spray Lay-up Operation, P002 Gel Coating operation, and P003 Hand Lay-up Operation. Correction to the emissions calculations and emission limitations.
Permit Type: Administrative Modification
Permit Fee: \$0.00
Issue Date: 8/12/2016
Effective Date: 8/12/2016
Expiration Date: 8/30/2023
Permit Evaluation Report (PER) Annual Date: Jan 1 - Dec 31, Due Feb 15

This document constitutes issuance to:

Kellerman Coach Works, Inc.
3972 Bach Buxton Road
Amelia, OH 45102

of a Permit-to-Install and Operate for the emissions unit(s) identified on the following page.


Ohio Environmental Protection Agency (EPA) District Office or local air agency responsible for processing and administering your permit:

Southwest Ohio Air Quality Agency
250 William Howard Taft Rd.
Cincinnati, OH 45219
(513)946-7777

The above named entity is hereby granted this Permit-to-Install and Operate for the air contaminant source(s) (emissions unit(s)) listed in this section pursuant to Chapter 3745-31 of the Ohio Administrative Code. Issuance of this permit does not constitute expressed or implied approval or agreement that, if constructed or modified in accordance with the plans included in the application, the described emissions unit(s) will operate in compliance with applicable State and federal laws and regulations.

This permit is granted subject to the conditions attached hereto.

Ohio Environmental Protection Agency


Craig W. Butler
Director



Final Permit-to-Install and Operate
Kellerman Coach Works, Inc.
Permit Number: P0120933
Facility ID: 1413000549
Effective Date: 8/12/2016

Authorization (continued)

Permit Number: P0120933

Permit Description: Administrative Modification of PTI P0118854. This permitting action covers P001 Spray Lay-up Operation, P002 Gel Coating operation, and P003 Hand Lay-up Operation. Correction to the emissions calculations and emission limitations.

Permits for the following Emissions Unit(s) or groups of Emissions Units are in this document as indicated below:

Emissions Unit ID:	P001
Company Equipment ID:	Spray resin application
Superseded Permit Number:	P0118854
General Permit Category and Type:	Not Applicable
Emissions Unit ID:	P002
Company Equipment ID:	Gel coat spray
Superseded Permit Number:	P0118854
General Permit Category and Type:	Not Applicable
Emissions Unit ID:	P003
Company Equipment ID:	Hand Lay-up
Superseded Permit Number:	P0118854
General Permit Category and Type:	Not Applicable



Final Permit-to-Install and Operate
Kellerman Coach Works, Inc.
Permit Number: P0120933
Facility ID: 1413000549
Effective Date: 8/12/2016

A. Standard Terms and Conditions

1. What does this permit-to-install and operate ("PTIO") allow me to do?

This permit allows you to install and operate the emissions unit(s) identified in this PTIO. You must install and operate the unit(s) in accordance with the application you submitted and all the terms and conditions contained in this PTIO, including emission limits and those terms that ensure compliance with the emission limits (for example, operating, recordkeeping and monitoring requirements).

2. Who is responsible for complying with this permit?

The person identified on the "Authorization" page, above, is responsible for complying with this permit until the permit is revoked, terminated, or transferred. "Person" means a person, firm, corporation, association, or partnership. The words "you," "your," or "permittee" refer to the "person" identified on the "Authorization" page above.

The permit applies only to the emissions unit(s) identified in the permit. If you install or modify any other equipment that requires an air permit, you must apply for an additional PTIO(s) for these sources.

3. What records must I keep under this permit?

You must keep all records required by this permit, including monitoring data, test results, strip-chart recordings, calibration data, maintenance records, and any other record required by this permit for five years from the date the record was created. You can keep these records electronically, provided they can be made available to Ohio EPA during an inspection at the facility. Failure to make requested records available to Ohio EPA upon request is a violation of this permit requirement.

4. What are my permit fees and when do I pay them?

There are two fees associated with permitted air contaminant sources in Ohio:

PTIO fee. This one-time fee is based on a fee schedule in accordance with Ohio Revised Code (ORC) section 3745.11, or based on a time and materials charge for permit application review and permit processing if required by the Director.

You will be sent an invoice for this fee after you receive this PTIO and payment is due within 30 days of the invoice date. You are required to pay the fee for this PTIO even if you do not install or modify your operations as authorized by this permit.

Annual emissions fee. Ohio EPA will assess a separate fee based on the total annual emissions from your facility. You self-report your emissions in accordance with Ohio Administrative Code (OAC) Chapter 3745-78. This fee assessed is based on a fee schedule in ORC section 3745.11 and funds Ohio EPA's permit compliance oversight activities. For facilities that are permitted as synthetic minor sources, the fee schedule is adjusted annually for inflation. Ohio EPA will notify you when it is time to report your emissions and to pay your annual emission fees.

5. When does my PTIO expire, and when do I need to submit my renewal application?

This permit expires on the date identified at the beginning of this permit document (see "Authorization" page above) and you must submit a renewal application to renew the permit. Ohio EPA will send a renewal notice to you approximately six months prior to the expiration date of this permit. However, it is

very important that you submit a complete renewal permit application (postmarked prior to expiration of this permit) even if you do not receive the renewal notice.

If a complete renewal application is submitted before the expiration date, Ohio EPA considers this a timely application for purposes of ORC section 119.06, and you are authorized to continue operating the emissions unit(s) covered by this permit beyond the expiration date of this permit until final action is taken by Ohio EPA on the renewal application.

6. What happens to this permit if my project is delayed or I do not install or modify my source?

This PTIO expires 18 months after the issue date identified on the "Authorization" page above unless otherwise specified if you have not (1) started constructing the new or modified emission sources identified in this permit, or (2) entered into a binding contract to undertake such construction. This deadline can be extended by up to 12 months, provided you apply to Ohio EPA for this extension within a reasonable time before the 18-month period has ended and you can show good cause for any such extension.

7. What reports must I submit under this permit?

An annual permit evaluation report (PER) is required in addition to any malfunction reporting required by OAC rule 3745-15-06 or other specific rule-based reporting requirement identified in this permit. Your PER due date is identified in the Authorization section of this permit.

8. If I am required to obtain a Title V operating permit in the future, what happens to the operating provisions and PER obligations under this permit?

If you are required to obtain a Title V permit under OAC Chapter 3745-77 in the future, the permit-to-operate portion of this permit will be superseded by the issued Title V permit. From the effective date of the Title V permit forward, this PTIO will effectively become a PTI (permit-to-install) in accordance with OAC rule 3745-31-02(B). The following terms and conditions of this permit will no longer be applicable after issuance of the Title V permit: Section B, Term 1.b) and Section C, for each emissions unit, Term a)(2).

The PER requirements in this permit remain effective until the date the Title V permit is issued and is effective, and cease to apply after the effective date of the Title V permit. The final PER obligation will cover operations up to the effective date of the Title V permit and must be submitted on or before the submission deadline identified in this permit on the last day prior to the effective date of the Title V permit.

9. What are my obligations when I perform scheduled maintenance on air pollution control equipment?

You must perform scheduled maintenance of air pollution control equipment in accordance with OAC rule 3745-15-06(A). If scheduled maintenance requires shutting down or bypassing any air pollution control equipment, you must also shut down the emissions unit(s) served by the air pollution control equipment during maintenance, unless the conditions of OAC rule 3745-15-06(A)(3) are met. Any emissions that exceed permitted amount(s) under this permit (unless specifically exempted by rule) must be reported as deviations in the annual permit evaluation report (PER), including nonexempt excess emissions that occur during approved scheduled maintenance.

10. Do I have to report malfunctions of emissions units or air pollution control equipment? If so, how must I report?

If you have a reportable malfunction of any emissions unit(s) or any associated air pollution control system, you must report this to the [DO/LAA] in accordance with OAC rule 3745-15-06(B). Malfunctions that must be reported are those that result in emissions that exceed permitted emission levels. It is your responsibility to evaluate control equipment breakdowns and operational upsets to determine if a reportable malfunction has occurred.

If you have a malfunction, but determine that it is not a reportable malfunction under OAC rule 3745-15-06(B), it is recommended that you maintain records associated with control equipment breakdown or process upsets. Although it is not a requirement of this permit, Ohio EPA recommends that you maintain records for non-reportable malfunctions.

11. Can Ohio EPA or my local air agency inspect the facility where the emission unit(s) is/are located?

Yes. Under Ohio law, the Director or his authorized representative may inspect the facility, conduct tests, examine records or reports to determine compliance with air pollution laws and regulations and the terms and conditions of this permit. You must provide, within a reasonable time, any information Ohio EPA requests either verbally or in writing.

12. What happens if one or more emissions units operated under this permit is/are shut down permanently?

Ohio EPA can terminate the permit terms associated with any permanently shut down emissions unit. "Shut down" means the emissions unit has been physically removed from service or has been altered in such a way that it can no longer operate without a subsequent "modification" or "installation" as defined in OAC Chapter 3745-31.

You should notify Ohio EPA of any emissions unit that is permanently shut down by submitting a certification that identifies the date on which the emissions unit was permanently shut down. The certification must be submitted by an authorized official from the facility. You cannot continue to operate an emission unit once the certification has been submitted to Ohio EPA by the authorized official.

You must comply with all recordkeeping and reporting for any permanently shut down emissions unit in accordance with the provisions of the permit, regulations or laws that were enforceable during the period of operation, such as the requirement to submit a PER, air fee emission report, or malfunction report. You must also keep all records relating to any permanently shutdown emissions unit, generated while the emissions unit was in operation, for at least five years from the date the record was generated.

Again, you cannot resume operation of any emissions unit certified by the authorized official as being permanently shut down without first applying for and obtaining a permit pursuant to OAC Chapter 3745-31.

13. Can I transfer this permit to a new owner or operator?

You can transfer this permit to a new owner or operator. If you transfer the permit, you must follow the procedures in OAC Chapter 3745-31, including notifying Ohio EPA or the local air agency of the change in ownership or operator. Any transferee of this permit must assume the responsibilities of the transferor permit holder.

14. Does compliance with this permit constitute compliance with OAC rule 3745-15-07, "air pollution nuisance"?

This permit and OAC rule 3745-15-07 prohibit operation of the air contaminant source(s) regulated under this permit in a manner that causes a nuisance. Ohio EPA can require additional controls or modification of the requirements of this permit through enforcement orders or judicial enforcement action if, upon investigation, Ohio EPA determines existing operations are causing a nuisance.

15. What happens if a portion of this permit is determined to be invalid?

If a portion of this permit is determined to be invalid, the remainder of the terms and conditions remain valid and enforceable. The exception is where the enforceability of terms and conditions are dependent on the term or condition that was declared invalid.



Final Permit-to-Install and Operate
Kellerman Coach Works, Inc.
Permit Number: P0120933
Facility ID: 1413000549
Effective Date: 8/12/2016

B. Facility-Wide Terms and Conditions

1. This permit document constitutes a permit-to-install issued in accordance with ORC 3704.03(F) and a permit-to-operate issued in accordance with ORC 3704.03(G).
 - a) For the purpose of a permit-to-install document, the facility-wide terms and conditions identified below are federally enforceable with the exception of those listed below which are enforceable under state law only.
 - (1) None.
 - b) For the purpose of a permit-to-operate document, the facility-wide terms and conditions identified below are enforceable under state law only with the exception of those listed below which are federally enforceable.
 - (1) None.
2. The following abbreviations are used throughout this permit:

HAP = Hazardous Air Pollutant

OC = Organic Compounds

VOC = Volatile Organic Compounds

PE = Particulate matter measurable by the applicable test methods in 40 CFR Part 60, Appendix A, "Standards of Performance for New Stationary Sources"

PM₁₀ = Particulate matter with an aerodynamic diameter less than or equal to a nominal ten micrometers as measured either by a reference method that is based on 40 CFR Part 50, Appendix J and designated in accordance with 40 CFR Part 53 or by an equivalent method designated in accordance with 40 CFR Part 53

TPY = Tons per year

PTI = Permit to Install

CFR = Code of Federal Regulations

OAC = Ohio Administrative Code



Final Permit-to-Install and Operate
Kellerman Coach Works, Inc.
Permit Number: P0120933
Facility ID: 1413000549
Effective Date: 8/12/2016

C. Emissions Unit Terms and Conditions

1. P001, Spray resin application

Operations, Property and/or Equipment Description:

Non-atomized mechanical resin application-open molding

a) This permit document constitutes a permit-to-install issued in accordance with ORC 3704.03(F) and a permit-to-operate issued in accordance with ORC 3704.03(G).

(1) For the purpose of a permit-to-install document, the emissions unit terms and conditions identified below are federally enforceable with the exception of those listed below which are enforceable under state law only.

a. d)(2), d)(3), d)(4) and e)(3).

(2) For the purpose of a permit-to-operate document, the emissions unit terms and conditions identified below are enforceable under state law only with the exception of those listed below which are federally enforceable.

a. None.

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operation(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures are identified below. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC rule 3745-31-05(A)(3) June 30, 2008	The total combined VOC emissions from P001-P003 shall not exceed 0.17 ton per month averaged over a 12-month rolling period. PE and PM ₁₀ emissions shall not exceed 0.2 ton PE/PM ₁₀ per month averaged over a 12-month rolling period. See b)(2)a.
b.	OAC rule 3745-31-05(A)(3)(a)(ii) June 30, 2008	The Best Available Technology (BAT) requirements under OAC rule 3745-31-05(A)(3) do not apply to the PE, and PM ₁₀ emissions from this air contaminant source since the calculated annual emission rates are less than 10 tons per year, taking into account the federally enforceable rule limitations listed in OAC rule 3745-17-11(B)(1).



	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
		The Best Available Technology (BAT) requirements under OAC rule 3745-31-05(A)(3) do not apply to the VOC emissions from this air contaminant source since the potential to emit is less than 10 tons per year. See b)(2)b.
c.	OAC rule 3745-17-07(A)(1)	Visible particulate emissions from the stack(s) serving this emissions unit shall not exceed 20 percent opacity as a six-minute average, except as provided by rule.
d.	OAC rule 3745-17-11(B)(1) Table I	PE shall not exceed 0.551 pound per hour.
e.	OAC rule 3745-21-25 Control of VOC emissions from reinforced plastic composites production operations.	Exempt per OAC rule 3745-21-25(A)(2)(e).

(2) Additional Terms and Conditions

- a. These BAT emission limits apply until U.S. EPA approves OAC paragraph 3745-31-05(A)(3)(a)(ii) (the less than 10 tons per year BAT exemption) into the Ohio State Implementation Plan (SIP).
- b. These requirements apply once U.S. EPA approves OAC rule 3745-31-05(A)(3)(a)(ii) (the less than 10 tons per year BAT exemption) as part of the Ohio SIP.

c) Operational Restrictions

- (1) None.

d) Monitoring and/or Recordkeeping Requirements

- (1) The permittee shall collect and record the following information for each month for the coating operation in this emissions unit:
 - a. the company identification for each coating (resin and gel coat) employed;
 - b. the amount of each coating (resin and gel coat) employed, in pounds;
 - c. the VOC content, recorded in percent weight, of each coating (resin and gel coat); and

- d. the VOC emissions from this emission unit, in tons per month, calculated using the equations outlined in Table 1 of 40 CFR Part 63, Subpart WWWW.
- (2) The permit to install and operate (PTIO) application for this/these emissions unit(s), P001, P002 and P003, was evaluated based on the actual materials and the design parameters of the emissions unit's(s') exhaust system, as specified by the permittee. The "Toxic Air Contaminant Statute", ORC 3704.03(F), was applied to this/these emissions unit(s) for each toxic air contaminant listed in OAC rule 3745-114-01, using data from the permit application; and modeling was performed for each toxic air contaminant(s) emitted at over one ton per year using an air dispersion model such as SCREEN3, AERMOD, or ISCST3, or other Ohio EPA approved model. The predicted 1-hour maximum ground-level concentration result(s) from the approved air dispersion model, was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC), calculated as described in the Ohio EPA guidance document entitled "Review of New Sources of Air Toxic Emissions, Option A", as follows:

- a. the exposure limit, expressed as a time-weighted average concentration for a conventional 8-hour workday and a 40-hour workweek, for each toxic compound(s) emitted from the emissions unit(s), (as determined from the raw materials processed and/or coatings or other materials applied) has been documented from one of the following sources and in the following order of preference (TLV was and shall be used, if the chemical is listed):
- i. threshold limit value (TLV) from the American Conference of Governmental Industrial Hygienists (ACGIH) "Threshold Limit Values for Chemical Substances and Physical Agents Biological Exposure Indices"; or
- ii. STEL (short term exposure limit) or the ceiling value from the American Conference of Governmental Industrial Hygienists (ACGIH) "Threshold Limit Values for Chemical Substances and Physical Agents Biological Exposure Indices"; the STEL or ceiling value is multiplied by 0.737 to convert the 15-minute exposure limit to an equivalent 8-hour TLV.
- b. The TLV is divided by ten to adjust the standard from the working population to the general public (TLV/10).
- c. This standard can be adjusted to account for the duration of the exposure or the operating hours of the emissions unit(s), i.e., "X" hours per day and "Y" days per week, from that of 8 hours per day and 5 days per week. The resulting calculation was (and shall be) used to determine the Maximum Acceptable Ground-Level Concentration (MAGLC):

$$TLV/10 \times 8/X \times 5/Y = 4 TLV/XY = MAGLC$$

- d. The following summarizes the results of dispersion modeling for the significant toxic contaminants (emitted at 1 or more tons/year) or "worst case" toxic contaminant(s):

Toxic Contaminant: styrene

TLV (mg/m³): 20 PPM

Maximum Hourly Emission Rate (lbs/hr): 0.465

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m³): 21.15

MAGLC (ug/m³): 2029

The permittee, has demonstrated that emissions of **styrene**, from emissions unit(s) P001, P002 and P003, is calculated to be less than eighty per cent of the maximum acceptable ground level concentration (MAGLC); any new raw material or processing agent shall not be applied without evaluating each component toxic air contaminant in accordance with the "Toxic Air Contaminant Statute", ORC 3704.03(F).

- (3) Prior to making any physical changes to or changes in the method of operation of the emissions unit(s), that could impact the parameters or values that were used in the predicted 1-hour maximum ground-level concentration, the permittee shall re-model the change(s) to demonstrate that the MAGLC has not been exceeded. Changes that can affect the parameters/values used in determining the 1-hour maximum ground-level concentration include, but are not limited to, the following:
- a. changes in the composition of the materials used or the use of new materials, that would result in the emission of a new toxic air contaminant with a lower Threshold Limit Value (TLV) than the lowest TLV previously modeled;
 - b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any toxic air contaminant listed in OAC rule 3745-114-01, that was modeled from the initial (or last) application; and
 - c. physical changes to the emissions unit(s) or its/their exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Toxic Air Contaminant Statute" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01 solely due to a non-restrictive change to a parameter or process operation, where compliance with the "Toxic Air Contaminant Statute", ORC 3704.03(F), has been documented. If the change(s) meet(s) the definition of a "modification", the permittee shall apply for and obtain a final PTIO prior to the change. The Director may consider any significant departure from the operations of the emissions unit, described in the permit application, as a modification that results in greater emissions than the emissions rate modeled to determine the ground level concentration; and he/she may require the permittee to submit a permit application for the increased emissions.

- (4) The permittee shall collect, record, and retain the following information for each toxic evaluation conducted to determine compliance with the "Toxic Air Contaminant Statute", ORC 3704.03(F):

- a. a description of the parameters/values used in each compliance demonstration and the parameters or values changed for any re-evaluation of the toxic(s) modeled (the composition of materials, new toxic contaminants emitted, change in stack/exhaust parameters, etc.);
 - b. the Maximum Acceptable Ground-Level Concentration (MAGLC) for each significant toxic contaminant or worst-case contaminant, calculated in accordance with the "Toxic Air Contaminant Statute", ORC 3704.03(F);
 - c. a copy of the computer model run(s), that established the predicted 1-hour maximum ground-level concentration that demonstrated the emissions unit(s) to be in compliance with the "Toxic Air Contaminant Statute", ORC 3704.03(F), initially and for each change that requires re-evaluation of the toxic air contaminant emissions; and
 - d. the documentation of the initial evaluation of compliance with the "Toxic Air Contaminant Statute", ORC 3704.03(F), and documentation of any determination that was conducted to re-evaluate compliance due to a change made to the emissions unit(s) or the materials applied.
- e) Reporting Requirements
- (1) The permittee shall submit an annual Permit Evaluation Report (PER) to the Ohio EPA District Office or Local Air Agency by the due date identified in the Authorization section of this permit. The permit evaluation report shall cover a reporting period of no more than twelve months for each air contaminant source identified in this permit.
 - (2) The reports required by this permit may be submitted through the Ohio EPA's eBusiness Center: Air Services online web portal; or they may be mailed as a hard copy to the appropriate district office or local air agency.
 - (3) The permittee shall include any changes made to a parameter or value used in the dispersion model, that was used to demonstrate compliance with the Toxic Air Contaminant Statute, ORC 3704.03(F), through the predicted 1-hour maximum ground-level concentration, in the annual Permit Evaluation Report (PER). If no changes to the emissions, emissions unit(s), or the exhaust stack have been made, then the report shall include a statement to this effect.
- f) Testing Requirements
- (1) Compliance with the Emissions Limitations and/or Control Requirements specified in section b) of these terms and conditions shall be determined in accordance with the following methods:
 - a. Emission Limitation:

PE shall not exceed 0.551 pound per hour.



Applicable Compliance Method:

The PE emission limitations represent the federally-enforceable rule limitation in Table I of OAC rule 3745-17-11(B) as follows:

For $0 < (P) < 0.05$, $(E) = 0.551$,

where:

P = Process Weight Rate, tons/hour; for P001, P = 137.8 pounds/hour or 0.069 tons/hour, assuming all PE is PM₁₀; and

E = Emission rate, in pounds per hour.

Compliance with the hourly PE emission limitations is demonstrated by the following calculation representing the maximum potential PE emission rate of the emissions unit:

Maximum hourly coating usage of 137.8 pounds of coating/hour x maximum coating solids content of 0.04 pounds of solids/pound of coating x (1 – 0.95 TE) x (1 – 0.90 CE) = 0.028 pounds of solids, as maximum potential PE emissions per hour,

where:

TE = Transfer Efficiency of the sprayed resin containing the solids

CE = Control Efficiency for PM₁₀/PE of the dry filters.

b. Emission Limitation:

PE and PM₁₀ emissions shall not exceed 0.2 ton PE/PM₁₀ per month averaged over a 12-month rolling period.

Applicable Compliance Method:

Allowable PE/PM₁₀ emissions were determined assuming all PE is PM₁₀ and based on the allowable 0.551 lb./hr. per OAC rule 3745-17-11, as follows.

$$A \times B / C / D = E$$

Where:

A = 0.551 pounds per hour by rule.

B = 8760 hours per year

C = 12 months

D = 2000 pounds per ton

E = Emission rate in tons per month



c. Emission Limitation:

Visible particulate emissions from the stack(s) serving this emissions unit shall not exceed 20 percent opacity as a six-minute average, except as provided by rule.

Applicable Compliance Method:

Compliance with the stack visible particulate emissions limitation shall be determined through visible emissions observations performed in accordance with U.S. EPA Method 9.

No visible emissions observations are specifically required to demonstrate compliance with this emission limitation but, if appropriate, may be required pursuant to OAC rule 3745-15-04(A).

d. Emission Limitations:

The total combined VOC emissions from P001-P003 shall not exceed 0.17 ton per month averaged over a 12-month rolling period.

Applicable Compliance Method:

Compliance with the VOC emission limits shall be based upon the summation of the emission totals collected and recorded in d)(1)d. for emission units P001-P003.

2. P002, Gel coat spray

Operations, Property and/or Equipment Description:

Non-atomized spray gel coat application-open molding

- a) This permit document constitutes a permit-to-install issued in accordance with ORC 3704.03(F) and a permit-to-operate issued in accordance with ORC 3704.03(G).
 - (1) For the purpose of a permit-to-install document, the emissions unit terms and conditions identified below are federally enforceable with the exception of those listed below which are enforceable under state law only.
 - a. d)(2), d)(3), d)(4) and e)(3).
 - (2) For the purpose of a permit-to-operate document, the emissions unit terms and conditions identified below are enforceable under state law only with the exception of those listed below which are federally enforceable.
 - a. None.
- b) Applicable Emissions Limitations and/or Control Requirements
 - (1) The specific operation(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures are identified below. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC rule 3745-31-05(A)(3) June 30, 2008	The total combined VOC emissions from P001-P003 shall not exceed 0.17 ton per month averaged over a 12-month rolling period. PE and PM ₁₀ emissions shall not exceed 0.2 ton PE/PM ₁₀ per month averaged over a 12-month rolling period. See b)(2)a.
b.	OAC rule 3745-31-05(A)(3)(a)(ii) June 30, 2008	The Best Available Technology (BAT) requirements under OAC rule 3745-31-05(A)(3) do not apply to the PE, and PM ₁₀ emissions from this air contaminant source since the calculated annual emission rates are less than 10 tons per year, taking into account the federally enforceable rule limitations listed in OAC rule 3745-17-11(B)(1).

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
		The Best Available Technology (BAT) requirements under OAC rule 3745-31-05(A)(3) do not apply to the VOC emissions from this air contaminant source since the calculated potential to emit is less than 10 tons per year. See b)(2)b.
c.	OAC rule 3745-17-07(A)(1)	Visible particulate emissions from the stack(s) serving this emissions unit shall not exceed 20 percent opacity as a six-minute average, except as provided by rule.
d.	OAC rule 3745-17-11(B)(1) Table I	PE shall not exceed 0.551 pound per hour.
e.	OAC rule 3745-21-25 Control of VOC emissions from reinforced plastic composites production operations.	Exempt per OAC rule 3745-21-25(A)(2)(e).

(2) Additional Terms and Conditions

- a. These BAT emission limits apply until U.S. EPA approves OAC paragraph 3745-31-05(A)(3)(a)(ii) (the less than 10 tons per year BAT exemption) into the Ohio State Implementation Plan (SIP).
- b. These requirements apply once U.S. EPA approves OAC rule 3745-31-05(A)(3)(a)(ii) (the less than 10 tons per year BAT exemption) as part of the Ohio SIP.

c) Operational Restrictions

- (1) None.

d) Monitoring and/or Recordkeeping Requirements

- (1) The permittee shall collect and record the following information for each month for the coating operation in this emissions unit:
 - a. the company identification for each coating (resin and gel coat) employed;
 - b. the amount of each coating (resin and gel coat) employed, in pounds;
 - c. the VOC content, recorded in percent weight, of each coating (resin and gel coat); and

- d. the VOC emissions from this emission unit, in tons per month, calculated using the equations outlined in Table 1 of 40 CFR Part 63, Subpart WWWW.
- (2) The permit to install and operate (PTIO) application for this/these emissions unit(s), P001, P002 and P003, was evaluated based on the actual materials and the design parameters of the emissions unit's(s') exhaust system, as specified by the permittee. The "Toxic Air Contaminant Statute", ORC 3704.03(F), was applied to this/these emissions unit(s) for each toxic air contaminant listed in OAC rule 3745-114-01, using data from the permit application; and modeling was performed for each toxic air contaminant(s) emitted at over one ton per year using an air dispersion model such as SCREEN3, AERMOD, or ISCST3, or other Ohio EPA approved model. The predicted 1-hour maximum ground-level concentration result(s) from the approved air dispersion model, was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC), calculated as described in the Ohio EPA guidance document entitled "Review of New Sources of Air Toxic Emissions, Option A", as follows:

- a. the exposure limit, expressed as a time-weighted average concentration for a conventional 8-hour workday and a 40-hour workweek, for each toxic compound(s) emitted from the emissions unit(s), (as determined from the raw materials processed and/or coatings or other materials applied) has been documented from one of the following sources and in the following order of preference (TLV was and shall be used, if the chemical is listed):
- i. threshold limit value (TLV) from the American Conference of Governmental Industrial Hygienists (ACGIH) "Threshold Limit Values for Chemical Substances and Physical Agents Biological Exposure Indices"; or
- ii. STEL (short term exposure limit) or the ceiling value from the American Conference of Governmental Industrial Hygienists (ACGIH) "Threshold Limit Values for Chemical Substances and Physical Agents Biological Exposure Indices"; the STEL or ceiling value is multiplied by 0.737 to convert the 15-minute exposure limit to an equivalent 8-hour TLV.
- b. The TLV is divided by ten to adjust the standard from the working population to the general public (TLV/10).
- c. This standard can be adjusted to account for the duration of the exposure or the operating hours of the emissions unit(s), i.e., "X" hours per day and "Y" days per week, from that of 8 hours per day and 5 days per week. The resulting calculation was (and shall be) used to determine the Maximum Acceptable Ground-Level Concentration (MAGLC):

$$TLV/10 \times 8/X \times 5/Y = 4 TLV/XY = MAGLC$$

- d. The following summarizes the results of dispersion modeling for the significant toxic contaminants (emitted at 1 or more tons/year) or "worst case" toxic contaminant(s):

Toxic Contaminant: styrene

TLV (mg/m³): 20 PPM

Maximum Hourly Emission Rate (lbs/hr): 0.465

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m³): 21.15

MAGLC (ug/m³): 2029

The permittee, has demonstrated that emissions of **styrene**, from emissions unit(s) P001, P002 and P003, is calculated to be less than eighty per cent of the maximum acceptable ground level concentration (MAGLC); any new raw material or processing agent shall not be applied without evaluating each component toxic air contaminant in accordance with the "Toxic Air Contaminant Statute", ORC 3704.03(F).

- (3) Prior to making any physical changes to or changes in the method of operation of the emissions unit(s), that could impact the parameters or values that were used in the predicted 1-hour maximum ground-level concentration, the permittee shall re-model the change(s) to demonstrate that the MAGLC has not been exceeded. Changes that can affect the parameters/values used in determining the 1-hour maximum ground-level concentration include, but are not limited to, the following:
- a. changes in the composition of the materials used or the use of new materials, that would result in the emission of a new toxic air contaminant with a lower Threshold Limit Value (TLV) than the lowest TLV previously modeled;
 - b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any toxic air contaminant listed in OAC rule 3745-114-01, that was modeled from the initial (or last) application; and
 - c. physical changes to the emissions unit(s) or its/their exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Toxic Air Contaminant Statute" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01 solely due to a non-restrictive change to a parameter or process operation, where compliance with the "Toxic Air Contaminant Statute", ORC 3704.03(F), has been documented. If the change(s) meet(s) the definition of a "modification", the permittee shall apply for and obtain a final PTIO prior to the change. The Director may consider any significant departure from the operations of the emissions unit, described in the permit application, as a modification that results in greater emissions than the emissions rate modeled to determine the ground level concentration; and he/she may require the permittee to submit a permit application for the increased emissions.

- (4) The permittee shall collect, record, and retain the following information for each toxic evaluation conducted to determine compliance with the "Toxic Air Contaminant Statute", ORC 3704.03(F):

- a. a description of the parameters/values used in each compliance demonstration and the parameters or values changed for any re-evaluation of the toxic(s) modeled (the composition of materials, new toxic contaminants emitted, change in stack/exhaust parameters, etc.);
 - b. the Maximum Acceptable Ground-Level Concentration (MAGLC) for each significant toxic contaminant or worst-case contaminant, calculated in accordance with the "Toxic Air Contaminant Statute", ORC 3704.03(F);
 - c. a copy of the computer model run(s), that established the predicted 1-hour maximum ground-level concentration that demonstrated the emissions unit(s) to be in compliance with the "Toxic Air Contaminant Statute", ORC 3704.03(F), initially and for each change that requires re-evaluation of the toxic air contaminant emissions; and
 - d. the documentation of the initial evaluation of compliance with the "Toxic Air Contaminant Statute", ORC 3704.03(F), and documentation of any determination that was conducted to re-evaluate compliance due to a change made to the emissions unit(s) or the materials applied.
- e) Reporting Requirements
- (1) The permittee shall submit an annual Permit Evaluation Report (PER) to the Ohio EPA District Office or Local Air Agency by the due date identified in the Authorization section of this permit. The permit evaluation report shall cover a reporting period of no more than twelve months for each air contaminant source identified in this permit.
 - (2) The reports required by this permit may be submitted through the Ohio EPA's eBusiness Center: Air Services online web portal; or they may be mailed as a hard copy to the appropriate district office or local air agency.
 - (3) The permittee shall include any changes made to a parameter or value used in the dispersion model, that was used to demonstrate compliance with the Toxic Air Contaminant Statute, ORC 3704.03(F), through the predicted 1-hour maximum ground-level concentration, in the annual Permit Evaluation Report (PER). If no changes to the emissions, emissions unit(s), or the exhaust stack have been made, then the report shall include a statement to this effect.
- f) Testing Requirements
- (1) Compliance with the Emissions Limitations and/or Control Requirements specified in section b) of these terms and conditions shall be determined in accordance with the following methods:
 - a. Emission Limitation:

PE shall not exceed 0.551 pound per hour.



Applicable Compliance Method:

The PE emission limitations represent the federally-enforceable rule limitation in Table I of OAC rule 3745-17-11(B) as follows:

$$\text{For } 0 < (P) < 0.05, (E) = 0.551,$$

where:

P = Process Weight Rate, tons/hour; for P001, P = 15.45 pounds/hour or 0.008 tons/hour, assuming all PE is PM₁₀; and

E = Emission rate, in pounds per hour.

Compliance with the hourly PE emission limitations is demonstrated by the following calculation representing the maximum potential PE emission rate of the emissions unit:

Maximum hourly coating usage of 15.4 pounds of coating/hour x maximum coating solids content of 0.72 pounds of solids/pound of coating x (1 – 0.95 TE) x (1 – 0.90 CE) = 0.06 pounds of solids, as maximum potential PE emissions per hour,

where:

TE = Transfer Efficiency of the sprayed resin containing the solids

CE = Control Efficiency for PM₁₀/PE of the dry filters.

b. Emission Limitation:

PE and PM₁₀ emissions shall not exceed 0.2 ton PE/PM₁₀ per month averaged over a 12-month rolling period.

Applicable Compliance Method:

Allowable PE/PM₁₀ emissions were determined assuming all PE is PM₁₀ and based on the allowable 0.551 lb./hr. per OAC rule 3745-17-11, as follows.

$$A \times B / C / D = E$$

Where:

A = 0.551 pounds per hour by rule.

B = 8760 hours per year

C = 12 months

D = 2000 pounds per ton

E = Emission rate in tons per month



c. Emission Limitation:

Visible particulate emissions from the stack(s) serving this emissions unit shall not exceed 20 percent opacity as a six-minute average, except as provided by rule.

Applicable Compliance Method:

Compliance with the stack visible particulate emissions limitation shall be determined through visible emissions observations performed in accordance with U.S. EPA Method 9.

No visible emissions observations are specifically required to demonstrate compliance with this emission limitation but, if appropriate, may be required pursuant to OAC rule 3745-15-04(A).

d. Emission Limitations:

The total combined VOC emissions from P001-P003 shall not exceed 0.17 ton per month averaged over a 12-month rolling period.

Applicable Compliance Method:

Compliance with the VOC emission limits shall be based upon the summation of the emission totals collected and recorded in d)(1)d. for emission units P001-P003.

g) Miscellaneous Requirements

- (1) None.

3. P003, Hand Lay-up

Operations, Property and/or Equipment Description:

Manual resin application-open molding operation

a) This permit document constitutes a permit-to-install issued in accordance with ORC 3704.03(F) and a permit-to-operate issued in accordance with ORC 3704.03(G).

(1) For the purpose of a permit-to-install document, the emissions unit terms and conditions identified below are federally enforceable with the exception of those listed below which are enforceable under state law only.

a. d)(2), d)(3), d)(4) and e)(3).

(2) For the purpose of a permit-to-operate document, the emissions unit terms and conditions identified below are enforceable under state law only with the exception of those listed below which are federally enforceable.

a. None.

b) Applicable Emissions Limitations and/or Control Requirements

(1) The specific operation(s), property, and/or equipment that constitute each emissions unit along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures are identified below. Emissions from each unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
a.	OAC rule 3745-31-05(A)(3) June 30, 2008	The total combined VOC emissions from P001-P003 shall not exceed 0.17 ton per month averaged over a 12-month rolling period. See b)(2)a.
b.	OAC rule 3745-31-05(A)(3)(a)(ii) June 30, 2008	The Best Available Technology (BAT) requirements under OAC rule 3745-31-05(A)(3) do not apply to the VOC emissions from this air contaminant source since the calculated potential to emit is less than 10 tons per year. See b)(2)b.
c.	OAC rule 3745-21-25 Control of VOC emissions from reinforced plastic composites production operations.	Exempt per OAC rule 3745-21-25(A)(2)(e).

- (2) Additional Terms and Conditions
 - a. These BAT emission limits apply until U.S. EPA approves OAC paragraph 3745-31-05(A)(3)(a)(ii) (the less than 10 tons per year BAT exemption) into the Ohio State Implementation Plan (SIP).
 - b. These requirements apply once U.S. EPA approves OAC rule 3745-31-05(A)(3)(a)(ii) (the less than 10 tons per year BAT exemption) as part of the Ohio SIP.
- c) Operational Restrictions
 - (1) None.
- d) Monitoring and/or Recordkeeping Requirements
 - (1) The permittee shall collect and record the following information for each month for the coating operation in this emissions unit:
 - a. the company identification for each coating (resin and gel coat) employed;
 - b. the amount of each coating (resin and gel coat) employed, in pounds;
 - c. the VOC content, recorded in percent weight, of each coating (resin and gel coat); and
 - d. the VOC emissions from this emission unit, in tons per month, calculated using the equations outlined in Table 1 of 40 CFR Part 63, Subpart WWWW.
 - (2) The permit to install and operate (PTIO) application for this/these emissions unit(s), P001, P002 and P003, was evaluated based on the actual materials and the design parameters of the emissions unit's(s') exhaust system, as specified by the permittee. The "Toxic Air Contaminant Statute", ORC 3704.03(F), was applied to this/these emissions unit(s) for each toxic air contaminant listed in OAC rule 3745-114-01, using data from the permit application; and modeling was performed for each toxic air contaminant(s) emitted at over one ton per year using an air dispersion model such as SCREEN3, AERMOD, or ISCST3, or other Ohio EPA approved model. The predicted 1-hour maximum ground-level concentration result(s) from the approved air dispersion model, was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC), calculated as described in the Ohio EPA guidance document entitled "Review of New Sources of Air Toxic Emissions, Option A", as follows:
 - a. the exposure limit, expressed as a time-weighted average concentration for a conventional 8-hour workday and a 40-hour workweek, for each toxic compound(s) emitted from the emissions unit(s), (as determined from the raw materials processed and/or coatings or other materials applied) has been documented from one of the following sources and in the following order of preference (TLV was and shall be used, if the chemical is listed):
 - i. threshold limit value (TLV) from the American Conference of Governmental Industrial Hygienists (ACGIH) "Threshold Limit Values for

Chemical Substances and Physical Agents Biological Exposure Indices”;
or

ii. STEL (short term exposure limit) or the ceiling value from the American Conference of Governmental Industrial Hygienists (ACGIH) “Threshold Limit Values for Chemical Substances and Physical Agents Biological Exposure Indices”; the STEL or ceiling value is multiplied by 0.737 to convert the 15-minute exposure limit to an equivalent 8-hour TLV.

b. The TLV is divided by ten to adjust the standard from the working population to the general public (TLV/10).

c. This standard can be adjusted to account for the duration of the exposure or the operating hours of the emissions unit(s), i.e., “X” hours per day and “Y” days per week, from that of 8 hours per day and 5 days per week. The resulting calculation was (and shall be) used to determine the Maximum Acceptable Ground-Level Concentration (MAGLC):

$$TLV/10 \times 8/X \times 5/Y = 4 TLV/XY = MAGLC$$

d. The following summarizes the results of dispersion modeling for the significant toxic contaminants (emitted at 1 or more tons/year) or “worst case” toxic contaminant(s):

Toxic Contaminant: styrene

TLV (mg/m³): 20 PPM

Maximum Hourly Emission Rate (lbs/hr): 0.465

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m³): 21.15

MAGLC (ug/m³): 2029

The permittee, has demonstrated that emissions of **styrene**, from emissions unit(s) P001, P002 and P003, is calculated to be less than eighty per cent of the maximum acceptable ground level concentration (MAGLC); any new raw material or processing agent shall not be applied without evaluating each component toxic air contaminant in accordance with the “Toxic Air Contaminant Statute”, ORC 3704.03(F).

(3) Prior to making any physical changes to or changes in the method of operation of the emissions unit(s), that could impact the parameters or values that were used in the predicted 1-hour maximum ground-level concentration, the permittee shall re-model the change(s) to demonstrate that the MAGLC has not been exceeded. Changes that can affect the parameters/values used in determining the 1-hour maximum ground-level concentration include, but are not limited to, the following:

a. changes in the composition of the materials used or the use of new materials, that would result in the emission of a new toxic air contaminant with a lower Threshold Limit Value (TLV) than the lowest TLV previously modeled;

- b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any toxic air contaminant listed in OAC rule 3745-114-01, that was modeled from the initial (or last) application; and
- c. physical changes to the emissions unit(s) or its/their exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Toxic Air Contaminant Statute" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01 solely due to a non-restrictive change to a parameter or process operation, where compliance with the "Toxic Air Contaminant Statute", ORC 3704.03(F), has been documented. If the change(s) meet(s) the definition of a "modification", the permittee shall apply for and obtain a final PTIO prior to the change. The Director may consider any significant departure from the operations of the emissions unit, described in the permit application, as a modification that results in greater emissions than the emissions rate modeled to determine the ground level concentration; and he/she may require the permittee to submit a permit application for the increased emissions.

- (4) The permittee shall collect, record, and retain the following information for each toxic evaluation conducted to determine compliance with the "Toxic Air Contaminant Statute", ORC 3704.03(F):
 - a. a description of the parameters/values used in each compliance demonstration and the parameters or values changed for any re-evaluation of the toxic(s) modeled (the composition of materials, new toxic contaminants emitted, change in stack/exhaust parameters, etc.);
 - b. the Maximum Acceptable Ground-Level Concentration (MAGLC) for each significant toxic contaminant or worst-case contaminant, calculated in accordance with the "Toxic Air Contaminant Statute", ORC 3704.03(F);
 - c. a copy of the computer model run(s), that established the predicted 1-hour maximum ground-level concentration that demonstrated the emissions unit(s) to be in compliance with the "Toxic Air Contaminant Statute", ORC 3704.03(F), initially and for each change that requires re-evaluation of the toxic air contaminant emissions; and
 - d. the documentation of the initial evaluation of compliance with the "Toxic Air Contaminant Statute", ORC 3704.03(F), and documentation of any determination that was conducted to re-evaluate compliance due to a change made to the emissions unit(s) or the materials applied.

e) Reporting Requirements

- (1) The permittee shall submit an annual Permit Evaluation Report (PER) to the Ohio EPA District Office or Local Air Agency by the due date identified in the Authorization section of this permit. The permit evaluation report shall cover a reporting period of no more than twelve months for each air contaminant source identified in this permit.



- (2) The reports required by this permit may be submitted through the Ohio EPA's eBusiness Center: Air Services online web portal; or they may be mailed as a hard copy to the appropriate district office or local air agency.
- (3) The permittee shall include any changes made to a parameter or value used in the dispersion model, that was used to demonstrate compliance with the Toxic Air Contaminant Statute, ORC 3704.03(F), through the predicted 1-hour maximum ground-level concentration, in the annual Permit Evaluation Report (PER). If no changes to the emissions, emissions unit(s), or the exhaust stack have been made, then the report shall include a statement to this effect.

f) Testing Requirements

- (1) Compliance with the Emissions Limitations and/or Control Requirements specified in section b) of these terms and conditions shall be determined in accordance with the following methods:

- a. Emission Limitations:

The total combined VOC emissions from P001-P003 shall not exceed 0.17 ton per month averaged over a 12-month rolling period.

Applicable Compliance Method:

Compliance with the VOC emission limits shall be based upon the summation of the emission totals collected and recorded in d)(1)d. for emission units P001-P003.

g) Miscellaneous Requirements

- (1) None.