

Facility ID: 1409000939 Issuance type: Final State Permit To Operate

This version of facility specific terms and conditions was converted from a database format to an HTML file during an upgrade of the Ohio EPA, Division of Air Pollution Control's permitting software. Every attempt has been made to convert the terms and conditions to look and substantively conform to the permit issued or being drafted in STARS. However, the format of the terms may vary slightly from the original. In addition, although it is not expected, there is a slight possibility that a term and condition may have been inadvertently "left out" of this reproduction during the conversion process. Therefore, if this version is to be used as a starting point in drafting a new version of a permit, it is imperative that the entire set of terms and conditions be reviewed to ensure they substantively mimic the issued permit. The official version of any permit issued final by Ohio EPA is kept in the Agency's Legal section. The Legal section may be contacted at (614) 644-3037.

In addition to the terms and conditions, hyperlinks have been inserted into the document so you may more readily access the section of the document you wish to review.

Finally, the term language under "Part II" and before "A. Applicable Emissions Limitations..." has been added to aid in document conversion, and was not part of the original issued permit.

\*\*\*THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION\*\*\*

Facility ID: 1409000939 Emissions Unit ID: R001 Issuance type: Final State Permit To Operate

[Go to the top of this document](#)

**Part II - Special Terms and Conditions**

This permit document constitutes a permit-to-install issued in accordance with ORC 3704.03(F) and a permit-to-operate issued in accordance with ORC 3704.03(G).

1. For the purpose of a permit-to-install document, the emissions unit terms and conditions identified below are federally enforceable with the exception of those listed below which are enforceable under state law only.
  - (a) None.
2. For the purpose of a permit-to-operate document, the emissions unit terms and conditions identified below are enforceable under state law only with the exception of those listed below which are federally enforceable.
  - (a) None.

**A. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
R001 Paint Booth for Truck Trailers	OAC rule 3745-31-05(A)(3) PTI 14-05790	Volatile organic compound (VOC) emissions shall not exceed 84 pounds per day from the application of coatings only and 4.25 tons per year, including cleanup.
	OAC rule 3745-21-09(U)(2)(c)	See terms A.2.b, A.2.c, B.1 and B.2.
		Exempt from the requirements of OAC rule 3745-21-09(U)(1).

**2. Additional Terms and Conditions**

- (a) Compliance with OAC rule 3745-31-05(A)(3) shall be demonstrated by the usage, emissions and VOC content limitations .  
The volatile organic compound (VOC) content of each coating employed in this emissions unit shall not exceed 6.2 lbs/gallon, as applied.  
The volatile organic compound (VOC) content of each cleanup material employed in this emissions unit shall not exceed 6.7 lbs/gallon.

**B. Operational Restrictions**

1. The maximum annual coating and cleanup material usage for this emissions unit shall not exceed 1175 gallons for coatings and 180 gallons for cleanup materials (as amount evaporated).
2. The maximum daily coating usage for this emissions unit shall not exceed 13.5 gallons, as applied.

**C. Monitoring and/or Record Keeping Requirements**

1. The permittee shall collect and record the following information each day for this emissions unit:
  - a. The name and identification number of each coating employed.
  - b. The VOC content of each coating, in pounds (lbs) per gallon, as applied.
  - c. The number of gallons of each coating employed.
  - d. The total VOC emissions from all coatings employed in pounds (b x c).
2. The permittee shall collect and record the following information each month for this emissions unit:
  - a. The name and identification number of each coating employed.
  - b. The VOC content of each coating, in pounds (lbs) per gallon, as applied.
  - c. The number of gallons of each coating employed.
  - d. The name and identification of each cleanup material employed.
  - e. The VOC content of each cleanup material, in pounds per gallon.
  - f. The number of gallons of each cleanup material evaporated.

g. The total VOC emissions from all coatings and cleanup materials employed in pounds [(b x c) + (e x f)].

The monthly records shall be summarized at the end of each calendar year.

3. The permit to install for this emissions unit (R001) was evaluated based on the actual materials (typically coatings and cleanup materials) and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Ground-Level Concentration (MAGLC).

The following summarizes the results of the modeling for the "worst case" pollutant(s):

Pollutant: Xylene (1330-20-7)  
 TLV (ug/m3):434,000  
 Maximum Hourly Emission Rate (lbs/hr):0.9  
 Predicted 1-Hour Maximum Ground-Level  
 Concentration (ug/m3):70  
 MAGLC (ug/m3):10,300

Physical changes to or in the method of operation of the emissions unit after it's installation or modification could affect the parameters used to determine whether or not the "Air Toxics Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in the "Air Toxic Policy" include the following:

a. Changes in the composition of the materials used (typically for coatings or cleanup materials), or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value previously modeled;

b. Changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and

c. Physical changes to the emissions unit or its exhaust parameters (e.g., increased/decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01 solely due to the emissions of any type of toxic air contaminant not previously emitted, and a modification of the existing permit to install will not be required, even if the toxic air contaminant emissions are greater than the de minimis level in OAC rule 3745-15-05. If the change(s) is (are) defined as a modification under other provisions of the modification definition, then the permittee shall obtain a final permit to install prior to the change.

The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will satisfy the Air Toxic Policy:"

a. A description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);

b. Documentation of it's evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and

c. When the computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

#### D. Reporting Requirements

1. The permittee shall notify Hamilton County Department of Environmental Services in writing identifying any exceedances of the VOC content limitations for coatings and/or cleanup materials. This report shall identify the cause for the exceedance as well as the corrective actions taken to achieve compliance. This report shall be submitted to the Hamilton County Department of Environmental Services within 30 days after the exceedance.
2. The permittee shall submit annual reports which identify any exceedances of the annual coating or cleanup material usage limitations, as well as the corrective actions that were taken to achieve compliance. These reports shall be submitted by January 31 of each year.
3. The permittee shall notify Hamilton County Department of Environmental Services in writing identifying any exceedances of the maximum daily coating limitation. This report shall identify the cause for the exceedance as well as the corrective actions taken to achieve compliance. This report shall identify whether the daily emissions limitation was also exceeded. This report shall be submitted to the Hamilton County Department of Environmental Services within 30 days after the exceedance.

#### E. Testing Requirements

1. Compliance with the emission limitations in Section A.1. of these terms and conditions shall be determined in accordance with the following methods:
  - a. Emissions Limitation:  
84 lbs/day VOC, for coatings only
  - Applicable Compliance Method:  
Compliance shall be determined by the record keeping requirements of C.1 and by multiplying the daily usage of coatings, as applied (gallons/day) by the VOC content of coatings employed, in lbs/gallon.
  - b. Emissions Limitation:  
4.25 TPY VOC, including cleanup

Applicable Compliance Method:

Compliance shall be based upon the record keeping requirements as specified in Section C.2. and shall be the sum of the monthly VOC emissions for the calendar year.

Emissions Limitations:

6.2 pounds VOC per gallon of coating and 6.7 pounds VOC per gallon of cleanup material

Applicable Compliance Method:

USEPA Methods 24 and 24A shall be used to determine the VOC contents for the coatings and cleanup materials employed in this emissions unit. If, pursuant to Method 24, 40 CFR Part 60, Appendix A, an owner or operator determines that Method 24 or 24A cannot be used for a particular coating or ink, the permittee shall so notify the Administrator of the USEPA and shall use formulation data for that coating or ink to demonstrate compliance until the USEPA provides alternative analytical procedures or alternative precision statements for Method 24 or 24A.

d. Usage Limitations:

1175 gallons per year of coatings and 180 gallons per year of cleanup materials.

Applicable Compliance Method:

Compliance shall be based upon the record keeping requirements as specified in Sections C.1. and C.2.

e. Usage Limitation:

13.5 gallons per day of coatings

Applicable Compliance Method:

Compliance shall be based upon the record keeping requirements as specified in Section C.1.

F. **Miscellaneous Requirements**

1. None