

Facility ID: 1431053380 Issuance type: Final State Permit To Operate

This version of facility specific terms and conditions was converted from a database format to an HTML file during an upgrade of the Ohio EPA, Division of Air Pollution Control's permitting software. Every attempt has been made to convert the terms and conditions to look and substantively conform to the permit issued or being drafted in STARS. However, the format of the terms may vary slightly from the original. In addition, although it is not expected, there is a slight possibility that a term and condition may have been inadvertently "left out" of this reproduction during the conversion process. Therefore, if this version is to be used as a starting point in drafting a new version of a permit, it is imperative that the entire set of terms and conditions be reviewed to ensure they substantively mimic the issued permit. The official version of any permit issued final by Ohio EPA is kept in the Agency's Legal section. The Legal section may be contacted at (614) 644-3037.

In addition to the terms and conditions, hyperlinks have been inserted into the document so you may more readily access the section of the document you wish to review.

Finally, the term language under "Part II" and before "A. Applicable Emissions Limitations..." has been added to aid in document conversion, and was not part of the original issued permit.

[Go to Part II for Emissions Unit R001](#)

[Go to Part II for Emissions Unit R002](#)

[Go to Part II for Emissions Unit R003](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION

Facility ID: 1431053380 Emissions Unit ID: R001 Issuance type: Final State Permit To Operate

[Go to the top of this document](#)

Part II - Special Terms and Conditions

This permit document constitutes a permit-to-install issued in accordance with ORC 3704.03(F) and a permit-to-operate issued in accordance with ORC 3704.03(G).

1. For the purpose of a permit-to-install document, the emissions unit terms and conditions identified below are federally enforceable with the exception of those listed below which are enforceable under state law only.
 - (a) None.
2. For the purpose of a permit-to-operate document, the emissions unit terms and conditions identified below are enforceable under state law only with the exception of those listed below which are federally enforceable.
 - (a) None.

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
R001 - Automatic Coating Machine (ACM) coating room with thermal oxidizer and uncontrolled curing ovens	OAC rule 3745-31-02(A)(2) PTI 14-05783	<p>The emissions of organic compounds (OC) shall not exceed 5.28 TPY, excluding cleanup.</p> <p>The emissions of organic compounds (OC) from cleanup materials, for R001-R003, combined shall not exceed 0.48 TPY.</p> <p>The emissions from the combustion of natural gas in the thermal oxidizer for emissions units P001, P003 thru P007, and R001 thru R003 shall not exceed the following limitations: 0.02 lb/hr of OC and 0.10 TPY of OC; 0.20 lb/hr of NOx and 0.88 TPY of NOx; 0.17 lb/hr of CO and 0.74 TPY of CO.</p> <p>See terms A.2.a - A.2.d and Sections B.1 - B.4. The requirements of OAC rule 3745-31-02(A)(2) are more stringent than the requirements of OAC rule 3745-21-07(G)(2).</p>

2. Additional Terms and Conditions

- (a) The permittee shall control OC emissions from this emission unit by use of a permanent total enclosure around the coating room and venting the emissions from the coating room to a thermal oxidizer, which has an OC destruction efficiency of at least 95% by weight.
The permittee has the option to perform an additional demonstration to show that the permanent total enclosure (PTE) cannot be compromised, under normal plant conditions, when the emissions unit is in operation [i.e., air flow through the PTE to the control device is always maintained under negative pressure even when all additional egress points (non-natural draft openings) which could affect the PTE were opened] in lieu of installing, maintaining, and operating monitoring devices and a recorder which simultaneously measure and record the pressure inside and outside the PTE.

If the PTE cannot be compromised, under normal plant conditions, when the emissions unit is in operation, the permittee will not be required to comply with the differential pressure operational restriction, monitoring, record-keeping, and reporting requirements specified below to ensure the ongoing integrity of the PTE.

If the permittee elects not to perform the additional demonstration specified above, to show that the PTE cannot be comprised or the additional demonstration indicates that the PTE can be compromised, the permittee will be required to comply with the differential pressure operational restriction, monitoring, recordkeeping, and reporting requirements specified below (see Sections B, C, D, and E below) to ensure the ongoing integrity of the PTE.

The actual emissions of Hazardous Air Pollutants (HAPs), as identified in Section 112(b) of Title III of the Clean Air Act from emissions units P001 (flex machine cleanup), P003 (flex machine cleanup), P004 (flex machine cleanup), P005 (flex machine cleanup), P006 (mixing room cleanup), P007 (mixing

room cleanup), R001-R003 (coating rooms with cleanup and ovens), any de minimis emissions units as defined in OAC rule 3745-15-05, any registration status and/or permit exempt emissions units shall not exceed 9.9 TPY for any single HAP and 24.9 TPY for any combination of HAPs. Compliance with the above limitations shall be based on a rolling, 12-month summation.

The OC content of the coatings employed in the emissions unit shall not exceed 0.788 pound of OC per pound of coating and the density of the coatings shall not exceed 8.56 pounds of coating per gallon of coating.

B. Operational Restrictions

1. The permanent total enclosure shall be maintained under negative pressure, at a minimum pressure differential that is not less than 0.007 inches of water, whenever the emission unit is in operation. If this negative pressure is maintained, 100 percent capture is presumed. A capture test may be required to demonstrate negative pressure in this room is maintained.
2. The average temperature of the combustion chamber within the thermal oxidizer, for any 3-hour block of time while the emission unit is in operation, shall not be more than 50 degrees Fahrenheit below the average temperature maintained during the most recent emissions test that demonstrated the emissions unit to be in compliance.
3. The maximum organic cleanup material usage shall not exceed 19,167 pounds per year based on a summation for emissions units R001- R003 combined.

The cleanup emissions are controlled by the use of a permanent total enclosure followed by a thermal oxidizer with an OC destruction efficiency of at least 95% by weight.
4. The maximum organic material usage from coating room operations, excluding cleanup, shall not exceed 77,137 pounds per year (13,975.5 pounds per year from stripping and manual wipe down and 63,161.3 pounds per year from coatings).

C. Monitoring and/or Record Keeping Requirements

1. The permittee shall operate and maintain a continuous temperature monitor and recorder which measures and records the combustion temperature within the thermal oxidizer when the emission unit is in operation. Units shall be in degrees Fahrenheit. The monitoring and recording devices shall be capable of accurately measuring the desired parameter. The temperature monitor and recorder shall be calibrated, operated and maintained in accordance with the manufacturer's recommendations, with any modifications deemed necessary by the permittee.
2. The permittee shall collect and record the following information for each day for the control equipment:
 - a. All 3-hour blocks of time during which the average combustion temperature within the thermal oxidizer, when the emission unit was in operation, was more than 50 degrees Fahrenheit below the average temperature maintained during the most recent emission test that demonstrated the emission unit to be in compliance.
 - b. A log of all downtime* periods for the capture (collection) system, control device, and monitoring equipment, when the associated emission unit was in operation.

* The control device downtime is defined as any time when the emission unit is in operation, employing organic compounds, and the thermal oxidizer is not in operation. Monitoring equipment downtime is defined as any time the emission unit is in operation, employing organic compounds, and the temperature monitoring equipment is not functioning.
3. The permittee shall maintain and operate monitoring devices and a recorder which simultaneously measure and record the differential pressure between the pressure inside and outside the permanent total enclosure. The monitoring and recording devices shall be calibrated, operated and maintained in accordance with the manufacturer's recommendations, instructions and operating manuals, with changes as deemed necessary by the permittee.

The permittee shall record and maintain the following information on a daily basis:
 - a. The difference in pressure between the permanent total enclosure and the surrounding area(s).
 - b. A log or record of operating time for the capture (collection) system, control device, monitoring equipment, and the associated emission unit.
4. The permittee shall maintain monthly records of the following information for this emissions unit:
 - a. The identification of each liquid organic material employed in the stripping process, manual wipe-down process and the coatings.
 - b. The amount of liquid organic material employed in pounds for each of the three processes identified in term C.4.a.
 - c. The number of screens employed in the two dryers. Monthly emissions from the dryers = 0.765 pound of OC per screen x the number of screens dried per month in both dryers.
 - d. The OC content of the coatings employed and the density of coatings employed in pound of OC per pound of coating and pound per gallon of coating, respectively.
5. The monthly records from Section C.4 shall be summarized at the end of each calendar year to determine the annual OC emissions from liquid organic materials, in tons per year, as calculated below:

Annual OC emissions = Annual OC emissions [(OC emissions from the stripping process + OC emissions from the manual wipe-down of screens + OC emissions from the coatings employed) x (1-control efficiency during the most recent performance test that demonstrated compliance) / 2000 lb/ton] + OC emissions evaporated from the two drying ovens.

6. The permittee shall maintain monthly cleanup records of the following information for emissions units R001- R003, combined:
- The identification of each liquid organic cleanup material employed.
 - The amount of liquid organic material employed* in pounds.

* Records of cleanup material employed may include mass balance calculations that include material recovered from the process for reuse, recycle or disposal.

- The OC emissions from liquid organic cleanup materials, in pounds or tons, as calculated below:

OC emissions from cleanup = OC emissions from cleanup* x (1-control efficiency during the most recent performance test that demonstrated compliance) / 2000 lb/ton.

* Records of cleanup material employed may include mass balance calculations that include material recovered from the process for reuse, recycle or disposal.

7. The monthly records from Section C.6 shall be summarized at the end of each calendar year to determine the annual cleanup material evaporation rates, in pounds or tons per year. Annual OC emissions from cleanup* = the sum of C.6.b. for the previous 12 months x (1-control efficiency during the most recent performance test that demonstrated compliance) / 2000 lbs/ton.

* Records of cleanup material employed may include mass balance calculations that include material recovered from the process for reuse, recycle or disposal.

8. The permittee shall collect and record the following information each month for the emissions units identified in term A.2.c:

- The name and identification number of each coating or solvent employed;
- The individual Hazardous Air Pollutant (HAP)* content for each HAP of each coating or solvent in pounds of individual HAP per pound of coating or solvent, as applied;
- The total combined HAP content of each coating or solvent in pounds of combined HAPs per pound of coating or solvent, as applied [sum all the individual HAP contents from (b)];
- The number of pounds of each coating or solvent employed;
- The name and identification of each cleanup material employed;
- The individual HAP content for each HAP of each cleanup material, in pounds of individual HAP per gallon of cleanup material, as applied;
- The total combined HAP content of each cleanup material, in pounds of combined HAPs per gallon of cleanup material, as applied [sum all the individual HAP contents from (f)];
 - The number of gallons of each cleanup material employed;
- The total individual HAP emissions for each HAP from all coatings (or solvents) and cleanup materials employed, in pounds or tons per month [for each HAP the sum of (b) times (d) times the emissions factor (if applicable) for each coating or solvent plus the sum of (f) times (h) for each cleanup material plus individual HAP emissions from any de minimis, registration status and/or permit exempt emissions unit at the facility];
- The total combined HAP emissions from all coatings (or solvents) and cleanup materials employed, in pounds or tons per month [the sum of (c) times (d) times the emissions factor (if applicable) for each coating or solvent plus the sum of (g) times (h) for each cleanup material plus combined HAP emissions from any de minimis, registration status and/or permit exempt emissions unit at the facility];
- The updated rolling, 12-month summation of the individual HAP emissions, in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months; and
- The updated rolling, 12-month summation of the combined HAP emissions, in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months.

* A listing of the HAPs can be found in Section 112(b) of the Clean Air Act or can be obtained by contacting Hamilton County Department of Environmental Services. This information does not have to be kept on a individual emissions unit basis.

D. Reporting Requirements

- The permittee shall submit deviation (excursion) reports in accordance with the General Terms and Conditions of this Permit to Operate.
- The permittee shall submit deviation (excursion) reports to the Hamilton County Department of Environmental Services which identify any exceedance of the material usage limitations in Sections B.3 and B.4 for this emissions unit for the manual wipe-down process, the stripping process, coating materials and the combined total organic cleanup material usage for emissions units R001 - R003, combined.
- The permittee shall submit deviation (excursion) reports to the Hamilton County Department of Environmental Services which identify all 3-hour blocks of time during which the average combustion temperature within the thermal oxidizer does not comply with the temperature limitation specified in Section B.2.
- The permittee shall submit pressure differential deviation (excursion) reports to the Hamilton County Department of Environmental Services that identify all periods of time during which the permanent total enclosure was not maintained at the required differential pressure specified in Section B.1.

5. The permittee shall notify the Hamilton County Department of Environmental Services in writing of any exceedance of the HAP emission limitations outlined in term A.2.c. If no exceedances occurred, the permittee shall state so in the report. The reports shall be submitted by January 31, April 30, July 31 and October 31 of each year and shall cover the previous calendar quarters (October through December, January through March, April through June and July through September, respectively.)
6. The permittee shall submit deviation (excursion) reports to the Hamilton County Department of Environmental Services that identify all exceedances of the OC content and density limitations outlined in term A.2.d.

E. Testing Requirements

1. Compliance with the emissions limitation(s) in Section A of these terms and conditions shall be determined in accordance with the following method(s):

Control Efficiency Requirement:

The permittee shall control OC emissions from this emissions unit by use of a permanent total enclosure around the coating room and venting the emissions from the coating room to a thermal oxidizer, which has an OC destruction efficiency of at least 95% by weight.

Applicable Compliance Methods:

Emissions units P001, P003, P004, P005, P006, P007, R001, R002 and R003 are vented to a common thermal oxidizer.

a. The emission testing shall be conducted approximately 2.5 years after permit issuance and within 6 months prior to permit renewal.

b. The test(s) shall be conducted while the emissions unit operated at or near its maximum capacity, as approved by Hamilton County Department of Environmental Services.

c. The following test methods shall be employed to demonstrate compliance with the minimum overall control efficiency for OC:

OC: Methods 1 through 4 and 25 or 25A of 40 CFR, Part 60, Appendix A, or other USEPA Reference Method with written approval from Hamilton County Environmental Services.

c. The capture efficiency shall be determined using Methods 204 through 204F, as specified in 40 CFR Part 51, Appendix M, or the permittee may request to use an alternative method or procedure for the determination of capture efficiency in accordance with the USEPA's "Guidelines for Determining Capture Efficiency," dated January 9, 1995. (The Ohio EPA will consider the request, including an evaluation of the applicability, necessity, and validity of the alternative, and may approve the use of the alternative if such approval does not contravene any other applicable requirement.) The control efficiency (i.e., the percent reduction in mass emissions between the inlet and outlet of the control system) shall be determined in accordance with the test methods and procedures specified in OAC rule 3745-21-10 or the approved alternative test protocol. The test methods and procedures selected shall be based on a consideration of the diversity of the organic species present and their total concentration, and on a consideration of the potential presence of interfering gases.

The control efficiency (i.e., the percent reduction in mass emissions between the inlet and outlet of the control system) shall be determined in accordance with the test methods and procedures specified in OAC rule 3745-21-10. The test methods and procedures selected shall be based on a consideration of the diversity of the organic species present and their total concentration, and on a consideration of the potential presence of interfering gases.

Not later than 30 days prior to the proposed test date(s), the permittee shall submit an "Intent to Test" notification to the Hamilton County Department of Environmental Services. The "Intent to Test" notification shall describe in detail the proposed test methods and procedures, the emissions unit operating parameters, the time (s) and date(s) of the tests, and the person(s) who will be conducting the tests. Failure to submit such notification for review and approval prior to the tests may result in the Hamilton County Department of Environmental Services' refusal to accept the results of the emission tests. Personnel from Ohio EPA and/or the Hamilton County Department of Environmental Services shall be permitted to witness the tests, examine the testing equipment, and acquire data and information necessary to ensure that the operation of the emissions unit and the testing procedures provide a valid characterization of the emissions from the emissions unit and/or the performance of the control equipment.

A comprehensive written report on the results of the emission tests shall be signed by the person or persons responsible for the tests and submitted to the Hamilton County Department of Environmental Services within 30 days following completion of the tests. The permittee may request additional time for the submittal of the written report, where warranted, with prior approval from the Hamilton County Department of Environmental Services.

2. Emission Limitation:

The emissions of organic compounds (OC) shall not exceed 5.28 TPY, excluding cleanup.

Applicable Compliance Method:

Compliance with the annual OC emissions limitations shall be demonstrated by the record keeping in Sections C.4 and 5.

3. Emission Limitation:

The emissions of organic compounds (OC) from cleanup materials, for R001-R003, combined shall not exceed 0.48 TPY.

Applicable Compliance Method:

Compliance with the annual OC emission limitation shall be demonstrated by the record keeping in Section C.7.

4. Emission Limitations:

The emissions from the combustion of natural gas in the thermal oxidizer shall not exceed the following limitations:
 0.02 lb/hr of OC and 0.10 TPY of OC;
 0.20 lb/hr of NOx and 0.88 TPY of NOx; and
 0.17 lb/hr of CO and 0.74 TPY of CO.

Applicable Compliance Method:

Compliance shall be determined by multiplying the maximum hourly and annual gas burning capacity of the emissions unit (mm cu. ft/hr) by the AP-42, Fifth Edition, Section 1.4 (revised 7/98) emission factor.

5. Emission Limitations:

Emissions of Hazardous Air Pollutants (HAPs) shall not exceed 9.9 TPY for any single HAP and 24.9 TPY for any combination of HAPs.

Applicable Compliance Method:

Compliance with the HAP emission limitations in term A.2.c shall be demonstrated by the record keeping in Section C.8.

- 6. Compliance with the permanent total enclosure operational limitation in term and condition B.1 shall be based upon the monitoring in Section C.3.
- 7. Compliance with the combustion chamber temperature operational limitation in Section B.2 shall be based upon the monitoring in Section C.2.
- 8. Compliance with the annual organic cleanup material usage limitation in Section B.3 shall be demonstrated by the record keeping in Section C.6.
- 9. Compliance with the annual organic material usage limitation in Section B.4 shall be demonstrated by the record keeping in Section C.4.
- 10. Formulation data or USEPA Method 24 shall be used to determine the OC content and density of each coating and cleanup material employed.

F. **Miscellaneous Requirements**

- 1. The following terms and conditions are federally enforceable: A, B, C, D and E.

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION

Facility ID: 1431053380 Emissions Unit ID: R002 Issuance type: Final State Permit To Operate

[Go to the top of this document](#)

Part II - Special Terms and Conditions

This permit document constitutes a permit-to-install issued in accordance with ORC 3704.03(F) and a permit-to-operate issued in accordance with ORC 3704.03(G).

- 1. For the purpose of a permit-to-install document, the emissions unit terms and conditions identified below are federally enforceable with the exception of those listed below which are enforceable under state law only.
 - (a) None.
- 2. For the purpose of a permit-to-operate document, the emissions unit terms and conditions identified below are enforceable under state law only with the exception of those listed below which are federally enforceable.
 - (a) None.

A. **Applicable Emissions Limitations and/or Control Requirements**

- 1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
R002 - In-wall coating room Number 1 with thermal oxidizer and uncontrolled curing ovens	OAC rule 3745-31-02(A)(2) PTI 14-05783	The emissions of organic compounds (OC) shall not exceed 5.28 TPY, excluding cleanup. The emissions of organic compounds (OC) from cleanup materials, for R001-R003, combined shall not exceed 0.48 TPY. The emissions from the combustion of natural gas in the thermal oxidizer for emissions units P001, P003 thru P007, and R001 thru R003 shall not exceed the following limitations:

0.02 lb/hr of OC and 0.10 TPY of OC;
 0.20 lb/hr of NO_x and 0.88 TPY of NO_x;
 0.17 lb/hr of CO and 0.74 TPY of CO.

See terms A.2.a - A.2.d and Sections B.1 - B.4.

The requirements of OAC rule 3745-31-02(A)(2) are more stringent than the requirements of OAC rule 3745-21-07(G)(2).

2. Additional Terms and Conditions

- (a) The permittee shall control OC emissions from this emission unit by use of a permanent total enclosure around the coating room and venting the emissions from the coating room to a thermal oxidizer, which has an OC destruction efficiency of at least 95% by weight. The permittee has the option to perform an additional demonstration to show that the permanent total enclosure (PTE) cannot be compromised, under normal plant conditions, when the emissions unit is in operation [i.e., air flow through the PTE to the control device is always maintained under negative pressure even when all additional egress points (non-natural draft openings) which could affect the PTE were opened] in lieu of installing, maintaining, and operating monitoring devices and a recorder which simultaneously measure and record the pressure inside and outside the PTE.

If the PTE cannot be compromised, under normal plant conditions, when the emissions unit is in operation, the permittee will not be required to comply with the differential pressure operational restriction, monitoring, record-keeping, and reporting requirements specified below to ensure the ongoing integrity of the PTE.

If the permittee elects not to perform the additional demonstration specified above, to show that the PTE cannot be comprised or the additional demonstration indicates that the PTE can be compromised, the permittee will be required to comply with the differential pressure operational restriction, monitoring, recordkeeping, and reporting requirements specified below (see Sections B, C, D, and E below) to ensure the ongoing integrity of the PTE.

The actual emissions of Hazardous Air Pollutants (HAPs), as identified in Section 112(b) of Title III of the Clean Air Act from emissions units P001 (flex machine cleanup), P003 (flex machine cleanup), P004 (flex machine cleanup), P005 (flex machine cleanup), P006 (mixing room cleanup), P007 (mixing room cleanup), R001-R003 (coating rooms with cleanup and ovens), any de minimis emissions units as defined in OAC rule 3745-15-05, any registration status and/or permit exempt emissions units shall not exceed 9.9 TPY for any single HAP and 24.9 TPY for any combination of HAPs. Compliance with the above limitations shall be based on a rolling, 12-month summation.

The OC content of the coatings employed in the emissions unit shall not exceed 0.788 pound of OC per pound of coating and the density of the coatings shall not exceed 8.56 pounds of coating per gallon of coating.

B. Operational Restrictions

- The permanent total enclosure shall be maintained under negative pressure, at a minimum pressure differential that is not less than 0.007 inches of water, whenever the emission unit is in operation. If this negative pressure is maintained, 100 percent capture is presumed. A capture test may be required to demonstrate negative pressure in this room is maintained.
- The average temperature of the combustion chamber within the thermal oxidizer, for any 3-hour block of time while the emission unit is in operation, shall not be more than 50 degrees Fahrenheit below the average temperature maintained during the most recent emissions test that demonstrated the emissions unit to be in compliance.
- The maximum organic cleanup material usage shall not exceed 19,167 pounds per year based on a summation for emissions units R001- R003 combined.

The cleanup emissions are controlled by the use of a permanent total enclosure followed by a thermal oxidizer with an OC destruction efficiency of at least 95% by weight.
- The maximum organic material usage from coating room operations, excluding cleanup, shall not exceed 77,137 pounds per year (13,975.5 pounds per year from stripping and manual wipe down and 63,161.3 pounds per year from coatings).

C. Monitoring and/or Record Keeping Requirements

- The permittee shall operate and maintain a continuous temperature monitor and recorder which measures and records the combustion temperature within the thermal oxidizer when the emission unit is in operation. Units shall be in degrees Fahrenheit. The monitoring and recording devices shall be capable of accurately measuring the desired parameter. The temperature monitor and recorder shall be calibrated, operated and maintained in accordance with the manufacturer's recommendations, with any modifications deemed necessary by the permittee.
- The permittee shall collect and record the following information for each day for the control equipment:
 - All 3-hour blocks of time during which the average combustion temperature within the thermal oxidizer, when the emission unit was in operation, was more than 50 degrees Fahrenheit below the average temperature maintained during the most recent emission test that demonstrated the emission unit to be in compliance.
 - A log of all downtime* periods for the capture (collection) system, control device, and monitoring equipment, when the associated emission unit was in operation.

* The control device downtime is defined as any time when the emission unit is in operation, employing organic compounds, and the thermal oxidizer is not in operation. Monitoring equipment downtime is defined as any time the emission unit is in operation, employing organic compounds, and the temperature monitoring equipment is not functioning.

3. The permittee shall maintain and operate monitoring devices and a recorder which simultaneously measure and record the differential pressure between the pressure inside and outside the permanent total enclosure. The monitoring and recording devices shall be calibrated, operated and maintained in accordance with the manufacturer's recommendations, instructions and operating manuals, with changes as deemed necessary by the permittee.
- The permittee shall record and maintain the following information on a daily basis:
- The difference in pressure between the permanent total enclosure and the surrounding area(s).
 - A log or record of operating time for the capture (collection) system, control device, monitoring equipment, and the associated emission unit.
4. The permittee shall maintain monthly records of the following information for this emissions unit:
- The identification of each liquid organic material employed in the stripping process, manual wipe-down process and the coatings.
 - The amount of liquid organic material employed in pounds for each of the three processes identified in term C.4.a.
 - The number of screens employed in the two dryers. Monthly emissions from the dryers = 0.765 pound of OC per screen x the number of screens dried per month in both dryers.
 - The OC content of the coatings employed and the density of coatings employed in pound of OC per pound of coating and pound per gallon of coating, respectively.
5. The monthly records from Section C.4 shall be summarized at the end of each calendar year to determine the annual OC emissions from liquid organic materials, in tons per year, as calculated below:
- Annual OC emissions = Annual OC emissions [(OC emissions from the stripping process + OC emissions from the manual wipe-down of screens + OC emissions from the coatings employed) x (1-control efficiency during the most recent performance test that demonstrated compliance) / 2000 lb/ton] + OC emissions evaporated from the two drying ovens.
6. The permittee shall maintain monthly cleanup records of the following information for emissions units R001- R003, combined:
- The identification of each liquid organic cleanup material employed.
 - The amount of liquid organic material employed* in pounds.
- * Records of cleanup material employed may include mass balance calculations that include material recovered from the process for reuse, recycle or disposal.
- The OC emissions from liquid organic cleanup materials, in pounds or tons, as calculated below:

OC emissions from cleanup = OC emissions from cleanup* x (1-control efficiency during the most recent performance test that demonstrated compliance) / 2000 lb/ton.

* Records of cleanup material employed may include mass balance calculations that include material recovered from the process for reuse, recycle or disposal.
7. The monthly records from Section C.6 shall be summarized at the end of each calendar year to determine the annual cleanup material evaporation rates, in pounds or tons per year. Annual OC emissions from cleanup* = the sum of C.6.b. for the previous 12 months x (1-control efficiency during the most recent performance test that demonstrated compliance) / 2000 lbs/ton.
- * Records of cleanup material employed may include mass balance calculations that include material recovered from the process for reuse, recycle or disposal.
8. The permittee shall collect and record the following information each month for the emissions units identified in term A.2.c:
- The name and identification number of each coating or solvent employed;
 - The individual Hazardous Air Pollutant (HAP)* content for each HAP of each coating or solvent in pounds of individual HAP per pound of coating or solvent, as applied;
 - The total combined HAP content of each coating or solvent in pounds of combined HAPs per pound of coating or solvent, as applied [sum all the individual HAP contents from (b)];
 - The number of pounds of each coating or solvent employed;
 - The name and identification of each cleanup material employed;
 - The individual HAP content for each HAP of each cleanup material, in pounds of individual HAP per gallon of cleanup material, as applied;
 - The total combined HAP content of each cleanup material, in pounds of combined HAPs per gallon of cleanup material, as applied [sum all the individual HAP contents from (f)];
 - The number of gallons of each cleanup material employed;
 - The total individual HAP emissions for each HAP from all coatings (or solvents) and cleanup materials employed, in pounds or tons per month [for each HAP the sum of (b) times (d) times the emissions factor (if applicable) for each coating or solvent plus the sum of (f) times (h) for each cleanup material plus

individual HAP emissions from any de minimis, registration status and/or permit exempt emissions unit at the facility];

- j. The total combined HAP emissions from all coatings (or solvents) and cleanup materials employed, in pounds or tons per month [(the sum of (c) times (d) times the emissions factor (if applicable) for each coating or solvent plus the sum of (g) times (h) for each cleanup material plus combined HAP emissions from any de minimis, registration status and/or permit exempt emissions unit at the facility];
- k. The updated rolling, 12-month summation of the individual HAP emissions, in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months; and
- l. The updated rolling, 12-month summation of the combined HAP emissions, in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months.

* A listing of the HAPs can be found in Section 112(b) of the Clean Air Act or can be obtained by contacting Hamilton County Department of Environmental Services. This information does not have to be kept on a individual emissions unit basis.

D. Reporting Requirements

- 1. The permittee shall submit deviation (excursion) reports in accordance with the General Terms and Conditions of this Permit to Operate.
- 2. The permittee shall submit deviation (excursion) reports to the Hamilton County Department of Environmental Services which identify any exceedance of the material usage limitations in Sections B.3 and B.4 for this emission unit for the manual wipe-down process, the stripping process, coating materials and the combined total organic cleanup material usage for emissions units R001 - R003, combined.
- 3. The permittee shall submit deviation (excursion) reports to the Hamilton County Department of Environmental Services which identify all 3-hour blocks of time during which the average combustion temperature within the thermal oxidizer does not comply with the temperature limitation specified in Section B.2.
- 4. The permittee shall submit pressure differential deviation (excursion) reports to the Hamilton County Department of Environmental Services that identify all periods of time during which the permanent total enclosure was not maintained at the required differential pressure specified in Section B.1.
- 5. The permittee shall notify the Hamilton County Department of Environmental Services in writing of any exceedance of the HAP emission limitations outlined in term A.2.c. If no exceedances occurred, the permittee shall state so in the report. The reports shall be submitted by January 31, April 30, July 31 and October 31 of each year and shall cover the previous calendar quarters (October through December, January through March, April through June and July through September, respectively.)
- 6. The permittee shall submit deviation (excursion) reports to the Hamilton County Department of Environmental Services that identify all exceedances of the OC content and density limitations outlined in term A.2.d.

E. Testing Requirements

- 1. Compliance with the emissions limitation(s) in Section A of these terms and conditions shall be determined in accordance with the following method(s):

Control Efficiency Requirement:

The permittee shall control OC emissions from this emissions unit by use of a permanent total enclosure around the coating room and venting the emissions from the coating room to a thermal oxidizer, which has an OC destruction efficiency of at least 95% by weight.

Applicable Compliance Methods:

Emissions units P001, P003, P004, P005, P006, P007, R001, R002 and R003 are vented to a common thermal oxidizer.

a. The emission testing shall be conducted approximately 2.5 years after permit issuance and within 6 months prior to permit renewal.

b. The test(s) shall be conducted while the emissions unit operated at or near its maximum capacity, as approved by Hamilton County Department of Environmental Services.

c. The following test methods shall be employed to demonstrate compliance with the minimum overall control efficiency for OC:

OC: Methods 1 through 4 and 25 or 25A of 40 CFR, Part 60, Appendix A, or other USEPA Reference Method with written approval from Hamilton County Environmental Services.

c. The capture efficiency shall be determined using Methods 204 through 204F, as specified in 40 CFR Part 51, Appendix M, or the permittee may request to use an alternative method or procedure for the determination of capture efficiency in accordance with the USEPA's "Guidelines for Determining Capture Efficiency," dated January 9, 1995. (The Ohio EPA will consider the request, including an evaluation of the applicability, necessity, and validity of the alternative, and may approve the use of the alternative if such approval does not contravene any other applicable requirement.) The control efficiency (i.e., the percent reduction in mass emissions between the inlet and outlet of the control system) shall be determined in accordance with the test methods and procedures specified in OAC rule 3745-21-10 or the approved alternative test protocol. The test methods and procedures selected shall be based on a consideration of the diversity of the organic species present and their total concentration, and on a consideration of the potential presence of interfering gases.

The control efficiency (i.e., the percent reduction in mass emissions between the inlet and outlet of the control system) shall be determined in accordance with the test methods and procedures specified in OAC rule 3745-21-10. The test methods and procedures selected shall be based on a consideration of the diversity of the organic species present and their total concentration, and on a consideration of the potential presence of interfering gases.

Not later than 30 days prior to the proposed test date(s), the permittee shall submit an "Intent to Test" notification to the Hamilton County Department of Environmental Services. The "Intent to Test" notification shall describe in detail the proposed test methods and procedures, the emissions unit operating parameters, the time(s) and date(s) of the tests, and the person(s) who will be conducting the tests. Failure to submit such notification for review and approval prior to the tests may result in the Hamilton County Department of Environmental Services' refusal to accept the results of the emission tests. Personnel from Ohio EPA and/or the Hamilton County Department of Environmental Services shall be permitted to witness the tests, examine the testing equipment, and acquire data and information necessary to ensure that the operation of the emissions unit and the testing procedures provide a valid characterization of the emissions from the emissions unit and/or the performance of the control equipment.

A comprehensive written report on the results of the emission tests shall be signed by the person or persons responsible for the tests and submitted to the Hamilton County Department of Environmental Services within 30 days following completion of the tests. The permittee may request additional time for the submittal of the written report, where warranted, with prior approval from the Hamilton County Department of Environmental Services.

2. Emission Limitation:

The emissions of organic compounds (OC) shall not exceed 5.28 TPY, excluding cleanup.

Applicable Compliance Method:

Compliance with the annual OC emissions limitations shall be demonstrated by the record keeping in Sections C.4 and 5.

3. Emission Limitation:

The emissions of organic compounds (OC) from cleanup materials, for R001-R003, combined shall not exceed 0.48 TPY.

Applicable Compliance Method:

Compliance with the annual OC emission limitation shall be demonstrated by the record keeping in Section C.7.

4. Emission Limitations:

The emissions from the combustion of natural gas in the thermal oxidizer shall not exceed the following limitations:

0.02 lb/hr of OC and 0.10 TPY of OC;
0.20 lb/hr of NOx and 0.88 TPY of NOx; and
0.17 lb/hr of CO and 0.74 TPY of CO.

Applicable Compliance Method:

Compliance shall be determined by multiplying the maximum hourly and annual gas burning capacity of the emissions unit (mm cu. ft/hr) by the AP-42, Fifth Edition, Section 1.4 (revised 7/98) emission factor.

5. Emission Limitations:

Emissions of Hazardous Air Pollutants (HAPs) shall not exceed 9.9 TPY for any single HAP and 24.9 TPY for any combination of HAPs.

Applicable Compliance Method:

Compliance with the HAP emission limitations in term A.2.c shall be demonstrated by the record keeping in Section C.8.

6. Compliance with the permanent total enclosure operational limitation in term and condition B.1 shall be based upon the monitoring in Section C.3.

7. Compliance with the combustion chamber temperature operational limitation in Section B.2 shall be based upon the monitoring in Section C.2.

8. Compliance with the annual organic cleanup material usage limitation in Section B.3 shall be demonstrated by the record keeping in Section C.6.

9. Compliance with the annual organic material usage limitation in Section B.4 shall be demonstrated by the record keeping in Section C.4.

10. Formulation data or USEPA Method 24 shall be used to determine the OC content and density of each coating and cleanup material employed.

F. **Miscellaneous Requirements**

1. The following terms and conditions are federally enforceable: A, B, C, D and E.

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION

Facility ID: 1431053380 Emissions Unit ID: R003 Issuance type: Final State Permit To Operate

[Go to the top of this document](#)

Part II - Special Terms and Conditions

This permit document constitutes a permit-to-install issued in accordance with ORC 3704.03(F) and a permit-to-operate issued in accordance with ORC 3704.03(G).

1. For the purpose of a permit-to-install document, the emissions unit terms and conditions identified below are federally enforceable with the exception of those listed below which are enforceable under state law only.
 - (a) None.
2. For the purpose of a permit-to-operate document, the emissions unit terms and conditions identified below are enforceable under state law only with the exception of those listed below which are federally enforceable.
 - (a) None.

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
R003 - In-wall coating room Number 2 with thermal oxidizer and uncontrolled curing ovens	OAC rule 3745-31-02(A)(2) PTI 14-05783	<p>The emissions of organic compounds (OC) shall not exceed 5.28 TPY, excluding cleanup.</p> <p>The emissions of organic compounds (OC) from cleanup materials, for R001-R003, combined shall not exceed 0.48 TPY.</p> <p>The emissions from the combustion of natural gas in the thermal oxidizer for emissions units P001, P003 thru P007, and R001 thru R003 shall not exceed the following limitations: 0.02 lb/hr of OC and 0.10 TPY of OC; 0.20 lb/hr of NOx and 0.88 TPY of NOx; 0.17 lb/hr of CO and 0.74 TPY of CO.</p> <p>See terms A.2.a - A.2.d and Sections B.1 - B.4. The requirements of OAC rule 3745-31-02(A)(2) are more stringent than the requirements of OAC rule 3745-21-07(G)(2).</p>

2. Additional Terms and Conditions

- (a) The permittee shall control OC emissions from this emission unit by use of a permanent total enclosure around the coating room and venting the emissions from the coating room to a thermal oxidizer, which has an OC destruction efficiency of at least 95% by weight.

The permittee has the option to perform an additional demonstration to show that the permanent total enclosure (PTE) cannot be compromised, under normal plant conditions, when the emissions unit is in operation [i.e., air flow through the PTE to the control device is always maintained under negative pressure even when all additional egress points (non-natural draft openings) which could affect the PTE were opened] in lieu of installing, maintaining, and operating monitoring devices and a recorder which simultaneously measure and record the pressure inside and outside the PTE.

If the PTE cannot be compromised, under normal plant conditions, when the emissions unit is in operation, the permittee will not be required to comply with the differential pressure operational restriction, monitoring, record-keeping, and reporting requirements specified below to ensure the ongoing integrity of the PTE.

If the permittee elects not to perform the additional demonstration specified above, to show that the PTE cannot be compromised or the additional demonstration indicates that the PTE can be compromised, the permittee will be required to comply with the differential pressure operational restriction, monitoring, recordkeeping, and reporting requirements specified below (see Sections B, C, D, and E below) to ensure the ongoing integrity of the PTE.

The actual emissions of Hazardous Air Pollutants (HAPs), as identified in Section 112(b) of Title III of the Clean Air Act from emissions units P001 (flex machine cleanup), P003 (flex machine cleanup), P004 (flex machine cleanup), P005 (flex machine cleanup), P006 (mixing room cleanup), P007 (mixing room cleanup), R001-R003 (coating rooms with cleanup and ovens), any de minimis emissions units as defined in OAC rule 3745-15-05, any registration status and/or permit exempt emissions units shall not exceed 9.9 TPY for any single HAP and 24.9 TPY for any combination of HAPs. Compliance with the above limitations shall be based on a rolling, 12-month summation.

The OC content of the coatings employed in the emissions unit shall not exceed 0.788 pound of OC per pound of coating and the density of the coatings shall not exceed 8.56 pounds of coating per gallon of coating.

B. Operational Restrictions

1. The permanent total enclosure shall be maintained under negative pressure, at a minimum pressure differential that is not less than 0.007 inches of water, whenever the emission unit is in operation. If this negative pressure is maintained, 100 percent capture is presumed. A capture test may be required to demonstrate negative pressure in this room is maintained.
2. The average temperature of the combustion chamber within the thermal oxidizer, for any 3-hour block of time while the emissions unit is in operation, shall not be more than 50 degrees Fahrenheit below the average temperature maintained during the most recent emissions test that demonstrated the emissions unit to be in

compliance.

3. The maximum organic cleanup material usage shall not exceed 19,167 pounds per year based on a summation for emissions units R001- R003 combined.

The cleanup emissions are controlled by the use of a permanent total enclosure followed by a thermal oxidizer with an OC destruction efficiency of at least 95% by weight.

4. The maximum organic material usage from coating room operations, excluding cleanup, shall not exceed 77,137 pounds per year (13,975.5 pounds per year from stripping and manual wipe down and 63,161.3 pounds per year from coatings).

C. Monitoring and/or Record Keeping Requirements

1. The permittee shall operate and maintain a continuous temperature monitor and recorder which measures and records the combustion temperature within the thermal oxidizer when the emission unit is in operation. Units shall be in degrees Fahrenheit. The monitoring and recording devices shall be capable of accurately measuring the desired parameter. The temperature monitor and recorder shall be calibrated, operated and maintained in accordance with the manufacturer's recommendations, with any modifications deemed necessary by the permittee.

2. The permittee shall collect and record the following information for each day for the control equipment:

a. All 3-hour blocks of time during which the average combustion temperature within the thermal oxidizer, when the emission unit was in operation, was more than 50 degrees Fahrenheit below the average temperature maintained during the most recent emission test that demonstrated the emission unit to be in compliance.

b. A log of all downtime* periods for the capture (collection) system, control device, and monitoring equipment, when the associated emission unit was in operation.

* The control device downtime is defined as any time when the emission unit is in operation, employing organic compounds, and the thermal oxidizer is not in operation. Monitoring equipment downtime is defined as any time the emission unit is in operation, employing organic compounds, and the temperature monitoring equipment is not functioning.

3. The permittee shall maintain and operate monitoring devices and a recorder which simultaneously measure and record the differential pressure between the pressure inside and outside the permanent total enclosure. The monitoring and recording devices shall be calibrated, operated and maintained in accordance with the manufacturer's recommendations, instructions and operating manuals, with changes as deemed necessary by the permittee.

The permittee shall record and maintain the following information on a daily basis:

- a. The difference in pressure between the permanent total enclosure and the surrounding area(s).
- b. A log or record of operating time for the capture (collection) system, control device, monitoring equipment, and the associated emission unit.

4. The permittee shall maintain monthly records of the following information for this emissions unit:

- a. The identification of each liquid organic material employed in the stripping process, manual wipe-down process and the coatings.
- b. The amount of liquid organic material employed in pounds for each of the three processes identified in term C.4.a.
- c. The number of screens employed in the two dryers. Monthly emissions from the dryers = 0.765 pound of OC per screen x the number of screens dried per month in both dryers.
- d. The OC content of the coatings employed and the density of coatings employed in pound of OC per pound of coating and pound per gallon of coating, respectively.

5. The monthly records from Section C.4. shall be summarized at the end of each calendar year to determine the annual OC emissions from liquid organic materials, in tons per year, as calculated below:

Annual OC emissions = Annual OC emissions [(OC emissions from the stripping process + OC emissions from the manual wipe-down of screens + OC emissions from the coatings employed) x (1-control efficiency during the most recent performance test that demonstrated compliance) / 2000 lb/ton] + OC emissions evaporated from the two drying ovens.

6. The permittee shall maintain monthly cleanup records of the following information for emissions units R001- R003, combined:

a. The identification of each liquid organic cleanup material employed.

b. The amount of liquid organic material employed* in pounds.

* Records of cleanup material employed may include mass balance calculations that include material recovered from the process for reuse, recycle or disposal.

c. The OC emissions from liquid organic cleanup materials, in pounds or tons, as calculated below:

OC emissions from cleanup = OC emissions from cleanup* x (1-control efficiency during the most recent performance test that demonstrated compliance) / 2000 lb/ton.

* Records of cleanup material employed may include mass balance calculations that include material recovered from the process for reuse, recycle or disposal.

7. The monthly records from Section C.6 shall be summarized at the end of each calendar year to determine the annual cleanup material evaporation rates, in pounds or tons per year. Annual OC emissions from cleanup* = the sum of C.6.b. for the previous 12 months x (1-control efficiency during the most recent performance test that demonstrated compliance) / 2000 lbs/ton.

* Records of cleanup material employed may include mass balance calculations that include material recovered from the process for reuse, recycle or disposal.

8. The permittee shall collect and record the following information each month for the emissions units identified in term A.2.c:
- a. The name and identification number of each coating or solvent employed;
 - b. The individual Hazardous Air Pollutant (HAP)* content for each HAP of each coating or solvent in pounds of individual HAP per pound of coating or solvent, as applied;
 - c. The total combined HAP content of each coating or solvent in pounds of combined HAPs per pound of coating or solvent, as applied [sum all the individual HAP contents from (b)];
 - d. The number of pounds of each coating or solvent employed;
 - e. The name and identification of each cleanup material employed;
 - f. The individual HAP content for each HAP of each cleanup material, in pounds of individual HAP per gallon of cleanup material, as applied;
 - g. The total combined HAP content of each cleanup material, in pounds of combined HAPs per gallon of cleanup material, as applied [sum all the individual HAP contents from (f)];
 - h. The number of gallons of each cleanup material employed;
 - i. The total individual HAP emissions for each HAP from all coatings (or solvents) and cleanup materials employed, in pounds or tons per month [for each HAP the sum of (b) times (d) times the emissions factor (if applicable) for each coating or solvent plus the sum of (f) times (h) for each cleanup material plus individual HAP emissions from any de minimis, registration status and/or permit exempt emissions unit at the facility];
 - j. The total combined HAP emissions from all coatings (or solvents) and cleanup materials employed, in pounds or tons per month [the sum of (c) times (d) times the emissions factor (if applicable) for each coating or solvent plus the sum of (g) times (h) for each cleanup material plus combined HAP emissions from any de minimis, registration status and/or permit exempt emissions unit at the facility];
 - k. The updated rolling, 12-month summation of the individual HAP emissions, in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months; and
 - l. The updated rolling, 12-month summation of the combined HAP emissions, in pounds or tons. This shall include the information for the current month and the preceding eleven calendar months.

* A listing of the HAPs can be found in Section 112(b) of the Clean Air Act or can be obtained by contacting Hamilton County Department of Environmental Services. This information does not have to be kept on a individual emissions unit basis.

D. Reporting Requirements

1. The permittee shall submit deviation (excursion) reports in accordance with the General Terms and Conditions of this Permit to Operate.
2. The permittee shall submit deviation (excursion) reports to the Hamilton County Department of Environmental Services which identify any exceedance of the material usage limitations in Sections B.3 and B.4 for this emissions unit for the manual wipe-down process, the stripping process, coating materials and the combined total organic cleanup material usage for emissions units R001 - R003, combined.
3. The permittee shall submit deviation (excursion) reports to the Hamilton County Department of Environmental Services which identify all 3-hour blocks of time during which the average combustion temperature within the thermal oxidizer does not comply with the temperature limitation specified in Section B.2.
4. The permittee shall submit pressure differential deviation (excursion) reports to the Hamilton County Department of Environmental Services that identify all periods of time during which the permanent total enclosure was not maintained at the required differential pressure specified in Section B.1.
5. The permittee shall notify the Hamilton County Department of Environmental Services in writing of any exceedance of the HAP emission limitations outlined in term A.2.c. If no exceedances occurred, the permittee shall state so in the report. The reports shall be submitted by January 31, April 30, July 31 and October 31 of each year and shall cover the previous calendar quarters (October through December, January through March, April through June and July through September, respectively.)
6. The permittee shall submit deviation (excursion) reports to the Hamilton County Department of Environmental Services that identify all exceedances of the OC content and density limitations outlined in term 2.2.d.

E. Testing Requirements

1. Compliance with the emissions limitation(s) in Section A of these terms and conditions shall be determined in accordance with the following method(s):

Control Efficiency Requirement:

The permittee shall control OC emissions from this emissions unit by use of a permanent total enclosure around the coating room and venting the emissions from the coating room to a thermal oxidizer, which has an OC destruction efficiency of at least 95% by weight.

Applicable Compliance Methods:

Emissions units P001, P003, P004, P005, P006, P007, R001, R002 and R003 are vented to a common thermal oxidizer.

a. The emission testing shall be conducted approximately 2.5 years after permit issuance and within 6 months prior to permit renewal.

b. The test(s) shall be conducted while the emissions unit operated at or near its maximum capacity, as approved by Hamilton County Department of Environmental Services.

c. The following test methods shall be employed to demonstrate compliance with the minimum overall control efficiency for OC:

OC: Methods 1 through 4 and 25 or 25A of 40 CFR, Part 60, Appendix A, or other USEPA Reference Method with written approval from Hamilton County Environmental Services.

c. The capture efficiency shall be determined using Methods 204 through 204F, as specified in 40 CFR Part 51, Appendix M, or the permittee may request to use an alternative method or procedure for the determination of capture efficiency in accordance with the USEPA's "Guidelines for Determining Capture Efficiency," dated January 9, 1995. (The Ohio EPA will consider the request, including an evaluation of the applicability, necessity, and validity of the alternative, and may approve the use of the alternative if such approval does not contravene any other applicable requirement.) The control efficiency (i.e., the percent reduction in mass emissions between the inlet and outlet of the control system) shall be determined in accordance with the test methods and procedures specified in OAC rule 3745-21-10 or the approved alternative test protocol. The test methods and procedures selected shall be based on a consideration of the diversity of the organic species present and their total concentration, and on a consideration of the potential presence of interfering gases.

The control efficiency (i.e., the percent reduction in mass emissions between the inlet and outlet of the control system) shall be determined in accordance with the test methods and procedures specified in OAC rule 3745-21-10. The test methods and procedures selected shall be based on a consideration of the diversity of the organic species present and their total concentration, and on a consideration of the potential presence of interfering gases.

Not later than 30 days prior to the proposed test date(s), the permittee shall submit an "Intent to Test" notification to the Hamilton County Department of Environmental Services. The "Intent to Test" notification shall describe in detail the proposed test methods and procedures, the emissions unit operating parameters, the time (s) and date(s) of the tests, and the person(s) who will be conducting the tests. Failure to submit such notification for review and approval prior to the tests may result in the Hamilton County Department of Environmental Services' refusal to accept the results of the emission tests. Personnel from Ohio EPA and/or the Hamilton County Department of Environmental Services shall be permitted to witness the tests, examine the testing equipment, and acquire data and information necessary to ensure that the operation of the emissions unit and the testing procedures provide a valid characterization of the emissions from the emissions unit and/or the performance of the control equipment.

A comprehensive written report on the results of the emission tests shall be signed by the person or persons responsible for the tests and submitted to the Hamilton County Department of Environmental Services within 30 days following completion of the tests. The permittee may request additional time for the submittal of the written report, where warranted, with prior approval from the Hamilton County Department of Environmental Services.

2. Emission Limitation:

The emissions of organic compounds (OC) shall not exceed 5.28 TPY, excluding cleanup.

Applicable Compliance Method:

Compliance with the annual OC emissions limitations shall be demonstrated by the record keeping in Sections C.4 and 5.

3. Emission Limitation:

The emissions of organic compounds (OC) from cleanup materials, for R001-R003, combined shall not exceed 0.48 TPY.

Applicable Compliance Method:

Compliance with the annual OC emission limitation shall be demonstrated by the record keeping in Section C.7.

4. Emission Limitations:

The emissions from the combustion of natural gas in the thermal oxidizer shall not exceed the following limitations:

0.02 lb/hr of OC and 0.10 TPY of OC;
0.20 lb/hr of NO_x and 0.88 TPY of NO_x; and
0.17 lb/hr of CO and 0.74 TPY of CO.

Applicable Compliance Method:

Compliance shall be determined by multiplying the maximum hourly and annual gas burning capacity of the emissions unit (mm cu. ft/hr) by the AP-42, Fifth Edition, Section 1.4 (revised 7/98) emissions factor.

5. Emission Limitations:

Emissions of Hazardous Air Pollutants (HAPs) shall not exceed 9.9 TPY for any single HAP and 24.9 TPY for any combination of HAPs.

Applicable Compliance Method:

Compliance with the HAP emission limitations in term A.2.c shall be demonstrated by the record keeping in Section C.8.

6. Compliance with the permanent total enclosure operational limitation in term and condition B.1 shall be based upon the monitoring in Section C.3.
 7. Compliance with the combustion chamber temperature operational limitation in Section B.2 shall be based upon the monitoring in Section C.2.
 8. Compliance with the annual organic cleanup material usage limitation in Section B.3 shall be demonstrated by the record keeping in Section C.6.
 9. Compliance with the annual organic material usage limitation in Section B.4 shall be demonstrated by the record keeping in Section C.4.
 10. Formulation data or USEPA Method 24 shall be used to determine the OC content and density of each coating and cleanup material employed.
- F. **Miscellaneous Requirements**

1. The following terms and conditions are federally enforceable: A, B, C, D and E.