

ADDITIONAL SPECIAL TERMS & CONDITIONS

A. Operational Restrictions

The maximum daily coating usage for this emissions unit shall not exceed 4 gallons.

B. Monitoring and/or Record keeping Requirements

1. The permittee shall collect and record the following information each day for the coating line:
 - a. The name and identification number of each coating employed.
 - b. The VOC content of each coating, as applied, in pounds per gallon.
 - c. The volume, in gallons, of each coating, employed.
 - d. The total volume, in gallons, of all of the coatings employed.
2. The permittee shall collect and record for the purpose of determining annual VOC emissions :
 - a. The name and identification of each cleanup material employed.
 - b. The number of gallons of each cleanup material employed.
 - c. The VOC content of each cleanup material, in pounds per gallons.
 - d. The total VOC emissions from all coatings and cleanup materials employed, in pounds or tons.
3. Each record of any monitoring data, testing data, and support information required pursuant to this permit shall be retained for a period of five years from the date the record was created. Support information shall include, but not be limited to, all calibration and maintenance records and all original strip-chart recordings for continuous monitoring instrumentation, and copies of all reports required by this permit. Such

records may be maintained in computerized form.

C. Reporting Requirements

1. The permittee shall notify the Director (the appropriate Ohio EPA District Office or local air agency) in writing of any daily record showing that the coating booth employs more than the applicable maximum daily coating usage limit. The notification shall include a copy of such record and shall be sent to the Director (the appropriate Ohio EPA District Office or local air agency) within 45 days after the exceedance occurs.

D. Testing Requirements and Compliance Method Determination

1. Formulation data or USEPA Method 24 shall be used to determine the volatile organic compound contents of the coatings and cleanup materials.
2. Compliance with the emission limitations stated in this Permit to Install shall be determined in accordance with the following methods:

- a. Emission Limitation

33.2 lbs VOC/day, excluding cleanup

Applicable Compliance Method

Compliance shall be determined by multiplying the actual daily coating usage as required to be recorded in section B.1., by the maximum VOC content of any coating employed in this emissions unit.

- b. Emission Limitation

4.48 tons VOC/yr, including cleanup

Applicable Compliance Method

Compliance shall be based upon the record keeping specified in Section B.1 and 2.