

Facility ID: 1576050214 Issuance type: Final State Permit To Operate

This version of facility specific terms and conditions was converted from a database format to an HTML file during an upgrade of the Ohio EPA, Division of Air Pollution Control's permitting software. Every attempt has been made to convert the terms and conditions to look and substantively conform to the permit issued or being drafted in STARS. However, the format of the terms may vary slightly from the original. In addition, although it is not expected, there is a slight possibility that a term and condition may have been inadvertently "left out" of this reproduction during the conversion process. Therefore, if this version is to be used as a starting point in drafting a new version of a permit, it is imperative that the entire set of terms and conditions be reviewed to ensure they substantively mimic the issued permit. The official version of any permit issued final by Ohio EPA is kept in the Agency's Legal section. The Legal section may be contacted at (614) 644-3037.

In addition to the terms and conditions, hyperlinks have been inserted into the document so you may more readily access the section of the document you wish to review.

Finally, the term language under "Part II" and before "A. Applicable Emissions Limitations..." has been added to aid in document conversion, and was not part of the original issued permit.

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION

Facility ID: 1576050214 Emissions Unit ID: P013 Issuance type: Final State Permit To Operate

[Go to the top of this document](#)

Part II - Special Terms and Conditions

This permit document constitutes a permit-to-install issued in accordance with ORC 3704.03(F) and a permit-to-operate issued in accordance with ORC 3704.03(G).

1. For the purpose of a permit-to-install document, the emissions unit terms and conditions identified below are federally enforceable with the exception of those listed below which are enforceable under state law only.
 - (a) None.
2. For the purpose of a permit-to-operate document, the emissions unit terms and conditions identified below are enforceable under state law only with the exception of those listed below which are federally enforceable.
 - (a) None.

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P013 - Bulk Clay/Limestone Handling System with Total Enclosure and Fabric Filter Control; including Pneumatic Rail Car Unloading, Pneumatic Conveyors, Three Storage Silos, Two Use Bins, and Weigh Hoppers. Modification by installing two new silos (clay and limestone) and handling limestone. This PTI supercedes PTI 15-1177 issued on 6/7/95.	OAC rule 3745-31-05 (A)(3) PTI 15-1177 issued 6/7/95 PTI 15-01513 issued 9/5/02	The particulate emissions (PE) from all three silos shall not exceed 0.02 grain per dry standard cubic foot of exhaust gases, 0.76 lb/hr, and 3.33 tons/yr. The visible emissions from the three fabric filters serving each silo shall not exceed 5% opacity, as a 6-minute average.
	OAC 3745-17-07 (A)(1)	See sections A.2.a and A.2.b below.
	OAC rule 3745-17-11	The visible emission restriction established by this rule is less stringent than the visible emission restriction established pursuant to OAC rule 3745-31-05 (A)(3). The emission limitation established by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05 (A)(3).

2. Additional Terms and Conditions

- (a) This emissions unit shall be totally enclosed with the only discharge through the three fabric filters serving each of the three silos.
There shall be no visible fugitive emissions from this emissions unit.

B. Operational Restrictions

1. The pressure drop across the three fabric filters shall be maintained according to the manufacturer's recommendations while the emissions unit is in operation.

C. Monitoring and/or Record Keeping Requirements

1. The permittee shall properly install, operate, and maintain equipment to monitor the pressure drop across the three fabric filters while the emissions unit is in operation. The monitoring equipment shall be installed, calibrated, operated, and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual(s). The permittee shall record the pressure drop across the three fabric filters on daily basis.

D. Reporting Requirements

1. The permittee shall submit pressure drop deviation (excursion) reports that identify all periods of time during which the pressure drop across the three fabric filters did not comply with the allowable range specified above.

E. Testing Requirements

1. Compliance with the emission limitation(s) in section A.I. of these terms and conditions shall be determined in accordance with the following method(s):
Emissions Limitation:
The particulate emissions (PE) from all three silos shall not exceed 0.02 grain per dry standard cubic foot of exhaust gases, 0.76 lb/hr, and 3.33 tons/yr.

Applicable Compliance Method:
If required, compliance with this mass emission limitation shall be based on stack testing per OAC rule 3745-17-03 (B)(7).

Existing Silo
 $(0.02 \text{ gr/dscf})(1,423 \text{ scfm})(60 \text{ min/hr})(\text{lb}/7000 \text{ grains}) = 0.24 \text{ lb PE/hr}$
 $0.24 \text{ lb PE/hr} \times 8,760 \text{ hrs/yr} \times 1 \text{ ton}/2,000 \text{ lbs} = 1.05 \text{ tons PE/yr}$

New Clay Silo
 $0.02 \text{ gr/dscf}(1,500 \text{ scfm})(60 \text{ min/hr})(\text{lb}/7000 \text{ grains}) = 0.26 \text{ lb PE/hr}$
 $0.26 \text{ lb PE/hr} \times 8,760 \text{ hrs/yr} \times 1 \text{ ton}/2,000 \text{ lbs} = 1.14 \text{ tons PE/yr}$

New Limestone Silo
 $0.02 \text{ gr/dscf}(1,500 \text{ scfm})(60 \text{ min/hr})(\text{lb}/7000 \text{ grains}) = 0.26 \text{ lb PE/hr}$
 $0.26 \text{ lb PE/hr} \times 8,760 \text{ hrs/yr} \times 1 \text{ ton}/2,000 \text{ lbs} = 1.14 \text{ tons PE/yr}$

0.24 lb PE/hr 1.05 tons PE/yr Existing silo
0.26 lb PE/hr 1.14 tons PE/yr New clay silo
0.26 lb PE/hr 1.14 tons PE/yr New limestone silo
0.76 lb PE/hr 3.33 tons PE/yr Total

Emissions Limitation:

The visible emissions from the fabric filter serving the three silos shall not exceed 5% opacity, as a 6-minute average.

Applicable Compliance Method:

If required, compliance shall be determined by visible emission evaluations performed in accordance with OAC rule 3745-17-03 (B)(1) using the tests and procedures specified in USEPA Reference Method 9.

F. Miscellaneous Requirements

1. None