

Facility ID: 1667080014 Issuance type: Final State Permit To Operate

This version of facility specific terms and conditions was converted from a database format to an HTML file during an upgrade of the Ohio EPA, Division of Air Pollution Control's permitting software. Every attempt has been made to convert the terms and conditions to look and substantively conform to the permit issued or being drafted in STARS. However, the format of the terms may vary slightly from the original. In addition, although it is not expected, there is a slight possibility that a term and condition may have been inadvertently "left out" of this reproduction during the conversion process. Therefore, if this version is to be used as a starting point in drafting a new version of a permit, it is imperative that the entire set of terms and conditions be reviewed to ensure they substantively mimic the issued permit. The official version of any permit issued final by Ohio EPA is kept in the Agency's Legal section. The Legal section may be contacted at (614) 644-3037.

In addition to the terms and conditions, hyperlinks have been inserted into the document so you may more readily access the section of the document you wish to review.

Finally, the term language under "Part II" and before "A. Applicable Emissions Limitations..." has been added to aid in document conversion, and was not part of the original issued permit.

\*\*\*THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION\*\*\*

Facility ID: 1667080014 Emissions Unit ID: P001 Issuance type: Final State Permit To Operate

[Go to the top of this document](#)

**Part II - Special Terms and Conditions**

This permit document constitutes a permit-to-install issued in accordance with ORC 3704.03(F) and a permit-to-operate issued in accordance with ORC 3704.03(G).

1. For the purpose of a permit-to-install document, the emissions unit terms and conditions identified below are federally enforceable with the exception of those listed below which are enforceable under state law only.
  - (a) None.
2. For the purpose of a permit-to-operate document, the emissions unit terms and conditions identified below are enforceable under state law only with the exception of those listed below which are federally enforceable.
  - (a) None.

**A. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
Streetsboro concrete batching & bagging plant	See F.1 below. OAC rule 3745-17-08	0.030 gr/dscf of exhaust gases from each fabric filter outlet or no visible emissions.
Transfer of sand and aggregate to elevated bins	See F.1 below. OAC 3745-17-07	The visible emissions of fugitive dust shall not exceed 20 percent opacity as a 3-minute average.
	OAC 3745-17-08	The drop height of the front-end bucket shall be minimized to the extent possible in order to minimize or eliminate visible emissions of fugitive dust from the conveyor loading area.
Cement Silo	See F.1 below. OAC 3745-17-08	The sand and aggregate loading into the elevated bins shall have a moisture content sufficient to minimize or eliminate visible emissions of fugitive dust from the conveyor and transfer points to bins. The silo shall be adequately enclosed and vented to a fabric filter; the enclosure shall be sufficient to eliminate visible emissions of fugitive dust at the point of capture.
Weigh hopper loading of cement, sand and aggregate	See F.1 below. OAC 3745-17-08	The fabric filter shall achieve an outlet emission rate of not greater than 0.030 grain of particulate emissions per dry standard cubic foot of exhaust gases or there shall be no visible emissions from the outlet, whichever is less stringent. The weigh hopper shall be adequately enclosed and vented to a fabric filter; the enclosure shall be sufficient to eliminate visible emissions of fugitive dust at the point of capture.
Bagging operation	See F.1 below. OAC 3745-17-07	The fabric filter shall achieve an outlet emission rate of not greater than 0.030 grain of particulate emissions per dry standard cubic foot of exhaust gases or there shall be no visible emissions from the outlet, whichever is less stringent. The visible emissions of fugitive dust shall not exceed 20 percent opacity as a 3-minute average.
	OAC 3745-17-08	Hoods, fans, and other equipment shall be installed to minimize or eliminate visible particulate emissions of fugitive dust at the point of capture to the extent possible with good engineering design. The fabric filter shall achieve an outlet emission rate of not greater than 0.030 grain of particulate emissions

per dry standard cubic foot of exhaust gases or there shall be no visible emissions from the outlet, whichever is less stringent.

2. **Additional Terms and Conditions**
  - (a) None
- B. **Operational Restrictions**
  1. None
- C. **Monitoring and/or Record Keeping Requirements**
  1. The permittee shall perform daily checks for any visible particulate emissions from the fabric filter control systems for the weigh hopper and cement silo, while the weigh hopper and silo are in operation. The presence or absence of any visible emissions from each fabric filter control system shall be noted in an operations log. If any visible emissions are observed from either system, corrective actions shall be taken to eliminate the visible emissions and these actions shall also be noted in the operations log.
- D. **Reporting Requirements**
  1. The permittee shall submit on a semi-annual basis a report which (a) identifies all days during which any visible particulate emissions were observed from the fabric filter control systems and (b) describes the corrective actions taken to eliminate the visible particulate emissions. These reports shall be submitted by January 31 and July 31 of each year to the Director (District Office or local air agency).
- E. **Testing Requirements**
  1. Compliance with the emission limitations in section A.1 of these terms and conditions shall be determined in accordance with the following methods:  
Emission Limitation:  
  
20 percent opacity as a 3-minute average  
  
Applicable Compliance Method:  
  
OAC rule 3745-17-03(B)(3)  
Emission Limitation:  
  
no visible emissions  
  
Applicable Compliance Method:  
  
OAC rule 3745-17-03(B)(4)  
Emission Limitation:  
  
0.030 gr/dscf  
  
Applicable Compliance Limitation:  
  
If required, compliance with this mass emission limitation shall be based on stack testing per OAC rule 3745-17-03(B)(7).
- F. **Miscellaneous Requirements**
  1. The following terms and conditions shall supersede all the air pollution control requirements contained in permit to install #16-082 as issued on September 11, 1978: A, C, D, and E.