

Facility ID: 1677000233 Issuance type: Final State Permit To Operate

This version of facility specific terms and conditions was converted from a database format to an HTML file during an upgrade of the Ohio EPA, Division of Air Pollution Control's permitting software. Every attempt has been made to convert the terms and conditions to look and substantively conform to the permit issued or being drafted in STARS. However, the format of the terms may vary slightly from the original. In addition, although it is not expected, there is a slight possibility that a term and condition may have been inadvertently "left out" of this reproduction during the conversion process. Therefore, if this version is to be used as a starting point in drafting a new version of a permit, it is imperative that the entire set of terms and conditions be reviewed to ensure they substantively mimic the issued permit. The official version of any permit issued final by Ohio EPA is kept in the Agency's Legal section. The Legal section may be contacted at (614) 644-3037.

In addition to the terms and conditions, hyperlinks have been inserted into the document so you may more readily access the section of the document you wish to review.

Finally, the term language under "Part II" and before "A. Applicable Emissions Limitations..." has been added to aid in document conversion, and was not part of the original issued permit.

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION

Facility ID: 1677000233 Emissions Unit ID: N001 Issuance type: Final State Permit To Operate

[Go to the top of this document](#)

Part II - Special Terms and Conditions

This permit document constitutes a permit-to-install issued in accordance with ORC 3704.03(F) and a permit-to-operate issued in accordance with ORC 3704.03(G).

1. For the purpose of a permit-to-install document, the emissions unit terms and conditions identified below are federally enforceable with the exception of those listed below which are enforceable under state law only.
 - (a) None.
2. For the purpose of a permit-to-operate document, the emissions unit terms and conditions identified below are enforceable under state law only with the exception of those listed below which are federally enforceable.
 - (a) None.

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
pet crematory unit #1	OAC rule 3745-31-01(A)(3) (PTI 16-1610)	<1% opacity 0.2 lb of particulates per 100 lbs of material charged
	OAC rule 3745-17-07	See A.2.a below.
	OAC rule 3745-17-09	See A.2.b below.

2. Additional Terms and Conditions

- (a) The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3). The emission limitation specified by this rule is equivalent to the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).

B. Operational Restrictions

1. The crematory incinerator shall be operated with primary and secondary combustion chambers with burners in each chamber. The primary combustion chamber shall be maintained so that the exit gas temperature range is between 600 and 1800 degrees Fahrenheit. The secondary combustion chamber of any unit shall operate so that the exhaust gas is a minimum of 1600 degrees Fahrenheit.
2. The batch incinerator (fully loaded while cold and never opened until the burn cycle is complete) shall incorporate a lockout system, which will prevent the ignition of waste until the exhaust gas temperature of the secondary combustion chamber reaches 1600 degrees Fahrenheit.
3. The secondary combustion chamber shall be maintained at a minimum exhaust gas temperature of 1600 degrees Fahrenheit until the wastes are completely combusted and the burn-down cycle is complete.

C. Monitoring and/or Record Keeping Requirements

1. The permittee shall operate and maintain a continuous temperature monitor and recorder which measures and records the temperature of the exhaust gases from the crematory incinerator when the emissions unit is in operation. Units shall be in degrees Fahrenheit. The monitoring and recording devices shall be capable of accurately measuring the desired parameter. The temperature monitor and recorder shall be installed, calibrated, operated and maintained in accordance with the manufacturer's recommendations, with any modifications deemed necessary by the permittee.

The permittee shall collect and record the following information for each day for the emissions unit:

- a. a log of the downtime for the monitoring equipment, when the associated emissions unit was in operation; and
 - b. all periods of time during which the temperature of the exhaust gases from the crematory incinerator, when the emissions unit was in operation, was below the minimum secondary combustion chamber exhaust gas temperature of 1600 degrees Fahrenheit as specified above.
2. The permittee shall maintain a written log that records the amount of material charged on either a pounds per hour or pounds per batch basis.

D. Reporting Requirements

1. The permittee shall submit temperature deviation (excursion) reports that identify all periods of time (except momentary excursions) during which the temperature of the exhaust gases from the secondary combustion chamber does not comply with the temperature limitation specified above.
2. The deviation reports shall be submitted as specified in Part I, General Condition 3 of this permit.

E. Testing Requirements

1. Compliance with the emission limitations in Section A.1 of these terms and conditions shall be determined in accordance with the following methods:
Emission Limitation:

visible emissions shall be less than 1% opacity

Applicable Compliance Method:

Compliance shall be determined by visible particulate emission evaluations performed in accordance with OAC rule 3745-17-03(B)(4) using the methods and procedures specified in USEPA Method 22.
Emission Limitation:

0.2 pound of particulate matter per 100 pounds charged

Applicable Compliance Method:

Future testing may be required in accordance with the procedures in Method 5 of 40 CFR Part 60, Appendix A.

F. Miscellaneous Requirements

1. None