

Facility ID: 1677000239 Issuance type: Final State Permit To Operate

This version of facility specific terms and conditions was converted from a database format to an HTML file during an upgrade of the Ohio EPA, Division of Air Pollution Control's permitting software. Every attempt has been made to convert the terms and conditions to look and substantively conform to the permit issued or being drafted in STARS. However, the format of the terms may vary slightly from the original. In addition, although it is not expected, there is a slight possibility that a term and condition may have been inadvertently "left out" of this reproduction during the conversion process. Therefore, if this version is to be used as a starting point in drafting a new version of a permit, it is imperative that the entire set of terms and conditions be reviewed to ensure they substantively mimic the issued permit. The official version of any permit issued final by Ohio EPA is kept in the Agency's Legal section. The Legal section may be contacted at (614) 644-3037.

In addition to the terms and conditions, hyperlinks have been inserted into the document so you may more readily access the section of the document you wish to review.

Finally, the term language under "Part II" and before "A. Applicable Emissions Limitations..." has been added to aid in document conversion, and was not part of the original issued permit.

[Go to Part II for Emissions Unit K001](#)

[Go to Part II for Emissions Unit P001](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION

Facility ID: 1677000239 Emissions Unit ID: K001 Issuance type: Final State Permit To Operate

[Go to the top of this document](#)

Part II - Special Terms and Conditions

This permit document constitutes a permit-to-install issued in accordance with ORC 3704.03(F) and a permit-to-operate issued in accordance with ORC 3704.03(G).

1. For the purpose of a permit-to-install document, the emissions unit terms and conditions identified below are federally enforceable with the exception of those listed below which are enforceable under state law only.
 - (a) None.
2. For the purpose of a permit-to-operate document, the emissions unit terms and conditions identified below are enforceable under state law only with the exception of those listed below which are federally enforceable.
 - (a) None.

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
Installation of aircraft de-icing systems process	OAC rule 3745-31-05(A)(3) (PTI 16-1647)	See A.2.a through A.2.d below.
	OAC rule 3745-21-07(G)	8 lbs/hr of organic material 40 lbs/day of organic material

2. Additional Terms and Conditions

- (a) The permittee shall employ best available technology (BAT) to reduce facility-wide emissions of both organic material and hazardous air pollutants (HAP). The control technology shall include the following:
 - i. use of adhesive/paint stripper solvents containing no HAP;
 - ii. solvent-thinning of any adhesive/paint strippers, adhesives, trim cements, prepping/tackifying materials, or cleanup materials employed shall be prohibited;
 - iii. hand rags and any other article used for stripping, cleanup, etc., shall be placed in a closed/sealed container, when not in use or for proper disposal, to reduce organic material and HAP emissions; and
 - iv. compliance with the Ohio EPA "Air Toxics Policy".
The average hourly facility-wide emissions of toluene shall not exceed 13.7 lbs/hr.
Facility-wide emissions of individual HAP shall not exceed 9.9 tons per year (TPY), based upon a rolling, 12-month summation of the monthly emissions.
Facility-wide emissions of total combined HAP's shall not exceed 14.6 TPY, based upon a rolling, 12-month summation of the monthly emissions.

B. Operational Restrictions

1. None

C. Monitoring and/or Record Keeping Requirements

1. The permittee shall collect and record each calendar month the following information to determine organic material emissions from emissions unit K001 (monthly invoice records or any accurate and convenient method of tracking emissions, via usage/recycling, on a per emissions unit K001 basis shall be utilized; formulation data may be used where applicable):
 - a. the name and company identification of each prepping material, tackifying material, adhesive, trim cement, and cleanup material employed;
 - b. the organic material content of each prepping material employed, in pounds of organic material per gallon of prepping material;
 - c. the number of gallons of each prepping material employed;
 - d. the organic material content of each tackifying material employed, in pounds of organic material per gallon of tackifying material;
 - e. the number of gallons of each tackifying material employed;

- f. the organic material content of each adhesive employed, in pounds of organic material per gallon of adhesive;
 - g. the number of gallons of each adhesive employed;
 - h. the organic material content of each trim cement employed, in pounds of organic material per gallon of trim cement;
 - i. the number of gallons of each trim cement employed;
 - j. the organic material content of each cleanup material employed, in pounds of organic material per gallon of cleanup material;
 - k. the number of gallons of each cleanup material employed;
 - l. the total number of hours and days the emissions unit was in operation; and
 - m. the average hourly and average daily organic material emissions, from all prepping materials, tackifying materials, adhesives, trim cements, and cleanup materials employed, in lbs/hr and lbs/day, respectively.
2. The permittee shall collect and record each calendar month the following information to determine facility-wide emissions of individual HAP (monthly invoice records or any accurate and convenient method of tracking emissions, via usage/recycling, on a facility-wide basis shall be utilized; formulation data may be used where applicable):
- a. the individual HAP content for each HAP of each prepping material employed, in pounds of individual HAP per gallon of prepping material;
 - b. the number of gallons of each prepping material employed;
 - c. the individual HAP content for each HAP of each tackifying material employed, in pounds of individual HAP per gallon of tackifying material;
 - d. the number of gallons of each tackifying material employed;
 - e. the individual HAP content for each HAP of each adhesive employed, in pounds of individual HAP per gallon of adhesive;
 - f. the number of gallons of each adhesive employed;
 - g. the individual HAP content for each HAP of each trim cement employed, in pounds of individual HAP per gallon of trim cement;
 - h. the number of gallons of each trim cement employed;
 - i. the individual HAP content for each HAP of each cleanup material employed, in pounds of individual HAP per gallon of cleanup material;
 - j. the number of gallons of each cleanup material employed;
 - k. the monthly facility-wide emissions of each individual HAP, in tons/month, from all prepping materials, tackifying materials, adhesives, trim cements, and cleanup materials employed; and
 - l. the summation of the previous 12 calendar months of facility-wide individual HAP emissions, in TPY.
3. The permittee shall collect and record each calendar month the following information to determine facility-wide emissions of total combined HAP (monthly invoice records or any accurate and convenient method of tracking emissions, via usage/recycling, on a facility-wide basis shall be utilized; formulation data may be used where applicable):
- a. the total combined HAP content of each prepping material employed, in pounds of total combined HAP per gallon of prepping material;
 - b. the number of gallons of each prepping material employed;
 - c. the total combined HAP content of each tackifying material employed, in pounds of total combined HAP's per gallon of tackifying material;
 - d. the number of gallons of each tackifying material employed;
 - e. the total combined HAP content of each adhesive employed, in pounds of total combined HAP per gallon of adhesive;
 - f. the number of gallons of each adhesive employed;
 - g. the total combined HAP content of each trim cement employed, in pounds of total combined HAP per gallon of trim cement;
 - h. the number of gallons of each trim cement employed;
 - i. the total combined HAP content of each cleanup material employed, in pounds of total combined HAP per gallon of cleanup material;
 - j. the number of gallons of each cleanup material employed;
 - k. the monthly facility-wide emissions of total combined HAP, in tons/month, from all prepping materials,

tackifying materials, adhesives, trim cements, and cleanup materials employed; and

- I. the summation of the previous 12 calendar months of facility-wide total combined HAP emissions, in TPY.
4. The permittee shall collect and record each calendar month the following information to determine facility-wide emissions of toluene (information from the individual HAP recordkeeping above shall be utilized):
 - a. the monthly facility-wide emissions of toluene (an individual HAP), in pounds/month;
 - b. the monthly facility operating time, in hours/month; and
 - c. the average hourly facility-wide emissions of toluene, in pounds/hour.

5. The permit to install for this emissions unit was evaluated based on the actual materials and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied to this emissions unit for each toxic pollutant, using data from the permit to install application, and modeling was performed for the toxic pollutant(s) emitted at over a ton per year using the SCREEN 3.0 model or other Ohio EPA approved model. The predicted 1-hour maximum ground-level concentration result(s) from the use of the SCREEN 3.0 (or other approved) model, was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC), calculated as required in Engineering Guide #70. The following summarizes the results of the modeling for the "worst case" pollutant(s):

Pollutant: toluene (CAS 108-88-3)

TWA (ug/m3): 188,000

Facility-wide Maximum Allowable Average Hourly Emission Rate (lbs/hr): 13.7

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 4460

MAGLC (ug/m3): 4476

6. Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:
 - a. changes in the composition of the materials used or the use of new materials, that would result in the emission of a compound or chemical with a lower Threshold Limit Value (TLV) than the lowest TLV previously modeled, as documented in the most current version of the American Conference of Governmental Industrial Hygienists' (ACGIH's) handbook entitled "TLVs and BEIs" ("Threshold Limit Values for Chemical Substances and Physical Agents, Biological Exposure Indices");
 - b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and
 - c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/decreased exhaust flow, changes in stack height, changes in stack diameter, etc.). If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01 solely due to the emissions of any type of toxic air contaminant not previously emitted, and a modification of the existing permit to install will not be required, even if the toxic air contaminant emissions are greater than the de minimis level in OAC rule 3745-15-05. If the change(s) meet(s) the definition of a "modification" under other provisions of the rule, then the permittee shall obtain a final permit to install prior to the change.
7. The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy:":
 - a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
 - b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and
 - c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

D. Reporting Requirements

1. The permittee shall submit quarterly deviation (excursion) reports which identify each calendar month during which the average hourly and/or the average daily organic material emissions exceeded the respective allowable organic material emission rates of 8 lbs/hr and/or 40 lbs/day, for this emissions unit.
2. The permittee shall submit quarterly deviation (excursion) reports identifying each rolling, 12-month year during which the 12-month summation of facility-wide individual HAP emissions exceeded 9.9 TPY.
3. The permittee shall submit quarterly deviation (excursion) reports identifying each rolling, 12-month year during which the 12-month summation of facility-wide total combined HAP emissions exceeded 14.6 TPY.
4. The permittee shall submit quarterly deviation (excursion) reports which identify each calendar month during which the average hourly facility-wide toluene emissions exceeded the maximum allowable facility-wide toluene emission rate of 13.7 lbs/hr.

5. The quarterly deviation reports shall be submitted in accordance with the requirements specified in Part 1 - General Terms and Conditions of this permit.

E. Testing Requirements

1. Compliance with the emission limitations in Sections A.1 and A.2 of these terms and conditions shall be determined in accordance with the following methods:
Formulation data or USEPA Methods 24/24A shall be used to determine the organic material and HAP contents of the adhesive/paint strippers, prepping materials, tackifying materials, adhesives, trim cements, and cleanup materials.

Emission Limitations:

8 lbs/hr of organic material
40 lbs/day of organic material

Applicable Compliance Method:

The permittee shall demonstrate compliance with the above limitations based upon the record keeping requirements of Section C.1.

Emission Limitation:

13.7 lbs/hr toluene

Applicable Compliance Method:

The permittee shall demonstrate compliance with the above limitation based upon the record keeping requirements of Section C.4.

Emission Limitation:

Maximum allowable annual facility-wide individual HAP emissions shall not exceed 9.9 TPY, based upon a rolling, 12-month summation of the monthly emissions.

Applicable Compliance Method:

The permittee shall demonstrate compliance with the above limitation based upon the recordkeeping requirements of Section C.2.

Emission Limitation:

Maximum allowable annual facility-wide total combined HAP emissions shall not exceed 14.6 TPY, based upon a rolling, 12-month summation of the monthly emissions.

Applicable Compliance Method:

The permittee shall demonstrate compliance with the above limitation based upon the record keeping requirements of Section C.3.

F. Miscellaneous Requirements

1. The permittee is hereby notified that this permit and all agency records concerning this permitted emissions unit are subject to public disclosure in accordance with OAC rule 3745-49-03.
2. The permittee shall comply with any applicable state and federal requirements governing the storage, treatment, transport and disposal of any waste material generated by the operation of this emissions unit.

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION

Facility ID: 1677000239 Emissions Unit ID: P001 Issuance type: Final State Permit To Operate

[Go to the top of this document](#)

Part II - Special Terms and Conditions

This permit document constitutes a permit-to-install issued in accordance with ORC 3704.03(F) and a permit-to-operate issued in accordance with ORC 3704.03(G).

1. For the purpose of a permit-to-install document, the emissions unit terms and conditions identified below are federally enforceable with the exception of those listed below which are enforceable under state law only.
- (a) None.
2. For the purpose of a permit-to-operate document, the emissions unit terms and conditions identified below are enforceable under state law only with the exception of those listed below which are federally enforceable.
- (a) None.

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control</u>
---	--------------------------------------	---

- | | | |
|--|--|--|
| Removal of aircraft de-icing systems process | OAC rule 3745-31-05(A)(3)
(PTI 16-1647) | Measures
See A.2.a through A.2.d below. |
| | OAC rule 3745-21-07(G) | 8 lbs/hr of organic material
40 lbs/day of organic material |
2. **Additional Terms and Conditions**
- (a) The permittee shall employ best available technology (BAT) to reduce facility-wide emissions of both organic material and hazardous air pollutants (HAP). The control technology shall include the following:
- i. use of adhesive/paint stripper solvents containing no HAP;
 - ii. solvent-thinning of any adhesive/paint strippers, adhesives, trim cements, prepping/tackifying materials, or cleanup materials employed shall be prohibited;
 - iii. hand rags and any other article used for stripping, cleanup, etc., shall be placed in a closed/sealed container, when not in use or for proper disposal, to reduce organic material and HAP emissions; and
 - iv. compliance with the Ohio EPA "Air Toxics Policy".
The average hourly facility-wide emissions of toluene shall not exceed 13.7 lbs/hr.
Facility-wide emissions of individual HAP shall not exceed 9.9 tons per year (TPY), based upon a rolling, 12-month summation of the monthly emissions.
Facility-wide emissions of total combined HAP's shall not exceed 14.6 TPY, based upon a rolling, 12-month summation of the monthly emissions.
- B. **Operational Restrictions**
1. None
- C. **Monitoring and/or Record Keeping Requirements**
1. The permittee shall collect and record each calendar month the following information to determine organic material emissions from emissions unit P001 (monthly invoice records or any accurate and convenient method of tracking emissions, via usage/recycling, on a per emissions unit P001 basis shall be utilized; formulation data may be used where applicable):
- a. the name and company identification of each prepping material, tackifying material, adhesive, trim cement, and cleanup material employed;
 - b. the organic material content of each prepping material employed, in pounds of organic material per gallon of prepping material;
 - c. the number of gallons of each prepping material employed;
 - d. the organic material content of each tackifying material employed, in pounds of organic material per gallon of tackifying material;
 - e. the number of gallons of each tackifying material employed;
 - f. the organic material content of each adhesive employed, in pounds of organic material per gallon of adhesive;
 - g. the number of gallons of each adhesive employed;
 - h. the organic material content of each trim cement employed, in pounds of organic material per gallon of trim cement;
 - i. the number of gallons of each trim cement employed;
 - j. the organic material content of each cleanup material employed, in pounds of organic material per gallon of cleanup material;
 - k. the number of gallons of each cleanup material employed;
 - l. the total number of hours and days the emissions unit was in operation; and
 - m. the average hourly and average daily organic material emissions, from all prepping materials, tackifying materials, adhesives, trim cements, and cleanup materials employed, in lbs/hr and lbs/day, respectively.
2. The permittee shall collect and record each calendar month the following information to determine facility-wide emissions of individual HAP (monthly invoice records or any accurate and convenient method of tracking emissions, via usage/recycling, on a facility-wide basis shall be utilized; formulation data may be used where applicable):
- a. the individual HAP content for each HAP of each prepping material employed, in pounds of individual HAP per gallon of prepping material;
 - b. the number of gallons of each prepping material employed;
 - c. the individual HAP content for each HAP of each tackifying material employed, in pounds of individual HAP per gallon of tackifying material;
 - d. the number of gallons of each tackifying material employed;
 - e. the individual HAP content for each HAP of each adhesive employed, in pounds of individual HAP per gallon of adhesive;

- f. the number of gallons of each adhesive employed;
 - g. the individual HAP content for each HAP of each trim cement employed, in pounds of individual HAP per gallon of trim cement;
 - h. the number of gallons of each trim cement employed;
 - i. the individual HAP content for each HAP of each cleanup material employed, in pounds of individual HAP per gallon of cleanup material;
 - j. the number of gallons of each cleanup material employed;
 - k. the monthly facility-wide emissions of each individual HAP, in tons/month, from all prepping materials, tackifying materials, adhesives, trim cements, and cleanup materials employed; and
 - l. the summation of the previous 12 calendar months of facility-wide individual HAP emissions, in TPY.
3. The permittee shall collect and record each calendar month the following information to determine facility-wide emissions of total combined HAP (monthly invoice records or any accurate and convenient method of tracking emissions, via usage/recycling, on a facility-wide basis shall be utilized; formulation data may be used where applicable):
- a. the total combined HAP content of each prepping material employed, in pounds of total combined HAP per gallon of prepping material;
 - b. the number of gallons of each prepping material employed;
 - c. the total combined HAP content of each tackifying material employed, in pounds of total combined HAP's per gallon of tackifying material;
 - d. the number of gallons of each tackifying material employed;
 - e. the total combined HAP content of each adhesive employed, in pounds of total combined HAP per gallon of adhesive;
 - f. the number of gallons of each adhesive employed;
 - g. the total combined HAP content of each trim cement employed, in pounds of total combined HAP per gallon of trim cement;
 - h. the number of gallons of each trim cement employed;
 - i. the total combined HAP content of each cleanup material employed, in pounds of total combined HAP per gallon of cleanup material;
 - j. the number of gallons of each cleanup material employed;
 - k. the monthly facility-wide emissions of total combined HAP, in tons/month, from all prepping materials, tackifying materials, adhesives, trim cements, and cleanup materials employed; and
 - l. the summation of the previous 12 calendar months of facility-wide total combined HAP emissions, in TPY.
4. The permittee shall collect and record each calendar month the following information to determine facility-wide emissions of toluene (information from the individual HAP recordkeeping above shall be utilized):
- a. the monthly facility-wide emissions of toluene (an individual HAP), in pounds/month;
 - b. the monthly facility operating time, in hours/month; and
 - c. the average hourly facility-wide emissions of toluene, in pounds/hour.
5. The permit to install for this emissions unit was evaluated based on the actual materials and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied to this emissions unit for each toxic pollutant, using data from the permit to install application, and modeling was performed for the toxic pollutant(s) emitted at over a ton per year using the SCREEN 3.0 model or other Ohio EPA approved model. The predicted 1-hour maximum ground-level concentration result(s) from the use of the SCREEN 3.0 (or other approved) model, was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC), calculated as required in Engineering Guide #70. The following summarizes the results of the modeling for the "worst case" pollutant(s):
- Pollutant: toluene (CAS 108-88-3)
- TWA (ug/m3): 188,000
 Facility-wide Maximum Allowable Average Hourly Emission Rate (lbs/hr): 13.7
 Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 4460
 MAGLC (ug/m3): 4476
6. Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the

parameters used in applying the "Air Toxic Policy" include the following:

- a. changes in the composition of the materials used or the use of new materials, that would result in the emission of a compound or chemical with a lower Threshold Limit Value (TLV) than the lowest TLV previously modeled, as documented in the most current version of the American Conference of Governmental Industrial Hygienists' (ACGIH's) handbook entitled "TLVs and BEIs" ("Threshold Limit Values for Chemical Substances and Physical Agents, Biological Exposure Indices");
 - b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and
 - c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/decreased exhaust flow, changes in stack height, changes in stack diameter, etc.). If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01 solely due to the emissions of any type of toxic air contaminant not previously emitted, and a modification of the existing permit to install will not be required, even if the toxic air contaminant emissions are greater than the de minimis level in OAC rule 3745-15-05. If the change(s) meet(s) the definition of a "modification" under other provisions of the rule, then the permittee shall obtain a final permit to install prior to the change.
7. The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy:"
- a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
 - b. documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and
 - c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.
- D. Reporting Requirements**
1. The permittee shall submit quarterly deviation (excursion) reports which identify each calendar month during which the average hourly and/or the average daily organic material emissions exceeded the respective allowable organic material emission rates of 8 lbs/hr and/or 40 lbs/day, for this emissions unit.
 2. The permittee shall submit quarterly deviation (excursion) reports identifying each rolling, 12-month year during which the 12-month summation of facility-wide individual HAP emissions exceeded 9.9 TPY.
 3. The permittee shall submit quarterly deviation (excursion) reports identifying each rolling, 12-month year during which the 12-month summation of facility-wide total combined HAP emissions exceeded 14.6 TPY.
 4. The permittee shall submit quarterly deviation (excursion) reports which identify each calendar month during which the average hourly facility-wide toluene emissions exceeded the maximum allowable facility-wide toluene emission rate of 13.7 lbs/hr.
 5. The quarterly deviation reports shall be submitted in accordance with the requirements specified in Part 1 - General Terms and Conditions of this permit.
- E. Testing Requirements**
1. Compliance with the emission limitations in Sections A.1 and A.2 of these terms and conditions shall be determined in accordance with the following methods:
Formulation data or USEPA Methods 24/24A shall be used to determine the organic material and HAP contents of the adhesive/paint strippers, prepping materials, tackifying materials, adhesives, trim cements, and cleanup materials.
Emission Limitations:

8 lbs/hr of organic material
40 lbs/day of organic material

Applicable Compliance Method:

The permittee shall demonstrate compliance with the above limitations based upon the record keeping requirements of Section C.1.
Emission Limitation:

13.7 lbs/hr toluene

Applicable Compliance Method:

The permittee shall demonstrate compliance with the above limitation based upon the record keeping requirements of Section C.4.
Emission Limitation:

Maximum allowable annual facility-wide individual HAP emissions shall not exceed 9.9 TPY, based upon a rolling, 12-month summation of the monthly emissions.

Applicable Compliance Method:

The permittee shall demonstrate compliance with the above limitation based upon the recordkeeping requirements of Section C.2.
Emission Limitation:

Maximum allowable annual facility-wide total combined HAP emissions shall not exceed 14.6 TPY, based upon a rolling, 12-month summation of the monthly emissions.

Applicable Compliance Method:

The permittee shall demonstrate compliance with the above limitation based upon the record keeping requirements of Section C.3.

F. Miscellaneous Requirements

1. The permittee is hereby notified that this permit and all agency records concerning this permitted emissions unit are subject to public disclosure in accordance with OAC rule 3745-49-03.
2. The permittee shall comply with any applicable state and federal requirements governing the storage, treatment, transport and disposal of any waste material generated by the operation of this emissions unit.