

Facility ID: 1677011155 Issuance type: Final State Permit To Operate

This version of facility specific terms and conditions was converted from a database format to an HTML file during an upgrade of the Ohio EPA, Division of Air Pollution Control's permitting software. Every attempt has been made to convert the terms and conditions to look and substantively conform to the permit issued or being drafted in STARS. However, the format of the terms may vary slightly from the original. In addition, although it is not expected, there is a slight possibility that a term and condition may have been inadvertently "left out" of this reproduction during the conversion process. Therefore, if this version is to be used as a starting point in drafting a new version of a permit, it is imperative that the entire set of terms and conditions be reviewed to ensure they substantively mimic the issued permit. The official version of any permit issued final by Ohio EPA is kept in the Agency's Legal section. The Legal section may be contacted at (614) 644-3037.

In addition to the terms and conditions, hyperlinks have been inserted into the document so you may more readily access the section of the document you wish to review.

Finally, the term language under "Part II" and before "A. Applicable Emissions Limitations..." has been added to aid in document conversion, and was not part of the original issued permit.

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION

Facility ID: 1677011155 Emissions Unit ID: K001 Issuance type: Final State Permit To Operate

[Go to the top of this document](#)

Part II - Special Terms and Conditions

This permit document constitutes a permit-to-install issued in accordance with ORC 3704.03(F) and a permit-to-operate issued in accordance with ORC 3704.03(G).

1. For the purpose of a permit-to-install document, the emissions unit terms and conditions identified below are federally enforceable with the exception of those listed below which are enforceable under state law only.
 - (a) None.
2. For the purpose of a permit-to-operate document, the emissions unit terms and conditions identified below are enforceable under state law only with the exception of those listed below which are federally enforceable.
 - (a) None.

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
K001 - Spray Booth - miscellaneous metal parts coating	OAC rule 3745-31-05(A)(3) (PTI 16-02455)	The requirements of this rule also include compliance with the requirements of OAC rule 3745-21-09(U). Volatile organic compound (VOC) emissions shall not exceed 45.2 pounds per day, and 8.25 tons per year, including both coatings and cleanup materials. Coating usage shall not exceed 10 gallons per day Exempt, see B.1 below.
	OAC rule 3745-21-09(U)	

2. **Additional Terms and Conditions**
 - (a) None

B. Operational Restrictions

1. The permittee shall be limited to only repainting (refinishing) of used motor vehicles and trailers in this emissions unit.
2. The permittee shall operate the dry filtration system for control of particulate emissions whenever this emissions unit is in operation.

C. Monitoring and/or Record Keeping Requirements

1. The permittee shall maintain daily records that document any time periods when the dry filtration system was not in service when the emissions unit was in operation.
2. The permittee shall collect and record the following information each day for this emissions unit:
 - a. the company identification for each coating and cleanup material employed;
 - b. the number of gallons of each coating and cleanup material employed;
 - c. the total number of gallons of all coatings employed that day;
 - d. the VOC content of each coating and cleanup material, in pounds per gallon;
 - e. the total VOC emission rate for all coatings and cleanup materials [summation of (c) x (b) for all coatings + summation of (c) x (b) for all cleanup materials], in pounds per day.

[Note: The coating information must be for the coatings as employed, including any thinning solvents added at the emissions unit.]

3. The permit to install for this emissions unit K001 was evaluated based on the actual materials and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied to this emissions unit for each toxic pollutant, using data from the permit to install application, and modeling was performed for the toxic pollutant(s) emitted at over a ton per year using the SCREEN 3.0 model or other Ohio EPA approved model. The predicted 1-hour maximum ground-level concentration result(s) from the use of the SCREEN 3.0 (or other approved) model, was compared to the Maximum Acceptable Ground-

Level Concentration (MAGLC), calculated as required in Engineering Guide #70. The following summarizes the results of the modeling for the "worst case" pollutant(s):

Pollutant: MIBK
 TLV (mg/m3): 205
 Maximum Hourly Emission Rate (lbs/hr): 1.5
 Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 4089
 MAGLC (ug/m3): 4881

4. Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:
 - a. changes in the composition of the materials used or the use of new materials, that would result in the emission of a compound or chemical with a lower Threshold Limit Value (TLV) than the lowest TLV previously modeled, as documented in the most current version of the American Conference of Governmental Industrial Hygienists' (ACGIH's) handbook entitled "TLVs and BEIs" ("Threshold Limit Values for Chemical Substances and Physical Agents, Biological Exposure Indices");
 - b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and
 - c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).
5. If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01 solely due to the emissions of any type of toxic air contaminant not previously emitted, and a modification of the existing permit to install will not be required, even if the toxic air contaminant emissions are greater than the de minimis level in OAC rule 3745-15-05. If the change(s) meet(s) the definition of a "modification" under other provisions of the rule, then the permittee shall obtain a final permit to install prior to the change.

The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy":

- a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
 - b. documentation of the evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and
 - c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.
- D. Reporting Requirements**
1. The permittee shall notify the Director (appropriate District Office or local air agency) in writing of any record showing that the dry filtration system was not in service when this emissions unit was in operation. The notification shall include a copy of such record and shall be sent to the Director (appropriate District Office or local air agency) within 30 days after the event occurs.
 2. The permittee shall notify the Director (appropriate District Office or local air agency) in writing of any daily record showing that the coating line employed more than the applicable maximum daily coating usage limit of 10 gallons per day. The notification shall include a copy of such record and shall be sent to the Director (appropriate District Office or local air agency) within 30 days after the exceedance occurs.
 3. The permittee shall submit quarterly deviations reports that identify each day the VOC emissions exceeded the daily emissions limit specified above.
 4. The quarterly deviation reports shall be submitted to the Director (appropriate District Office or local air agency) in accordance with the General Terms and Conditions. These reports shall be submitted by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarter.
- E. Testing Requirements**
1. Compliance with the emission limitations in Section A.1.1 of these terms and conditions shall be determined in accordance with the following methods:
 Emissions Limitation:
 10 gallons per day total coating usage
 Applicable Compliance Method:
 Compliance shall be based upon the record keeping specified in Section C.2.
 Emissions Limitation:
 45.2 lbs. per day of VOC emissions from coatings
 Applicable Compliance Method:
 Compliance shall be based upon the record keeping specified in Section C.2.
 USEPA Methods 24 and 24A shall be used to determine the VOC contents for (a) coatings and (b) flexographic and rotogravure printing inks and related coatings, respectively. If, pursuant to section 4.3 of Method 24, 40 CFR Part 60, Appendix A, an owner or operator determines that Method 24 or 24A cannot be used for a

particular coating or ink, the permittee shall so notify the Administrator of the USEPA and shall use formulation data for that coating or ink to demonstrate compliance until the USEPA provides alternative analytical procedures or alternative precision statements for Method 24 or 24A.

Emissions Limitation:

8.25 TPY of VOC emissions from coatings and cleanup materials

Applicable Compliance Method:

As long as compliance with the daily limitation is maintained, compliance with the annual limitation shall be ensured (the annual limitation was determined by multiplying the daily limitation by 365, and then dividing by 2000 lbs/ton.

F. Miscellaneous Requirements

1. None