

Facility ID: 1677020154 Issuance type: Final State Permit To Operate

This version of facility specific terms and conditions was converted from a database format to an HTML file during an upgrade of the Ohio EPA, Division of Air Pollution Control's permitting software. Every attempt has been made to convert the terms and conditions to look and substantively conform to the permit issued or being drafted in STARS. However, the format of the terms may vary slightly from the original. In addition, although it is not expected, there is a slight possibility that a term and condition may have been inadvertently "left out" of this reproduction during the conversion process. Therefore, if this version is to be used as a starting point in drafting a new version of a permit, it is imperative that the entire set of terms and conditions be reviewed to ensure they substantively mimic the issued permit. The official version of any permit issued final by Ohio EPA is kept in the Agency's Legal section. The Legal section may be contacted at (614) 644-3037.

In addition to the terms and conditions, hyperlinks have been inserted into the document so you may more readily access the section of the document you wish to review.

Finally, the term language under "Part II" and before "A. Applicable Emissions Limitations..." has been added to aid in document conversion, and was not part of the original issued permit.

[Go to Part II for Emissions Unit K001](#)

[Go to Part II for Emissions Unit P001](#)

[Go to Part II for Emissions Unit P002](#)

\*\*\*THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION\*\*\*

Facility ID: 1677020154 Emissions Unit ID: K001 Issuance type: Final State Permit To Operate

[Go to the top of this document](#)

**Part II - Special Terms and Conditions**

This permit document constitutes a permit-to-install issued in accordance with ORC 3704.03(F) and a permit-to-operate issued in accordance with ORC 3704.03(G).

1. For the purpose of a permit-to-install document, the emissions unit terms and conditions identified below are federally enforceable with the exception of those listed below which are enforceable under state law only.
  - (a) None.
2. For the purpose of a permit-to-operate document, the emissions unit terms and conditions identified below are enforceable under state law only with the exception of those listed below which are federally enforceable.
  - (a) None.

**A. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
Coating Line - coating of aluminum truck wheels - 2 paint booths and one cure oven, controlled with thermal oxidizer	OAC rule 3745-31-05(A)(3) (PTI 16-02225)	The requirements of this rule also include compliance with the requirements of OAC rule 3745-21-09(U) and OAC rule 3745-21-09(B)(6).
	OAC rule 3745-21-09(B)(6)	0.42 pound per hour volatile organic compounds (VOC) 1.83 tpy VOC
	OAC rule 3745-21-09(U)	81% overall control efficiency 90% destruction efficiency See A.2.a below.
		Exempt (see A.2.a below).

**2. Additional Terms and Conditions**

- (a) In lieu of complying with the pounds of VOC per gallon of solids limitation contained in paragraph (U) of OAC rule 3745-21-09, the permittee shall employ a control system that provides not less than an eighty one percent reduction, by weight, in the overall VOC emissions from the coating line and that the control equipment has an efficiency of not less than ninety percent, by weight, for the VOC emissions vented to the control equipment.

**B. Operational Restrictions**

1. The average combustion temperature within the thermal incinerator, for any 3-hour block of time when the emissions unit is in operation, shall not be less than 1,500 degrees Fahrenheit.
 

The operation of the control equipment outside of the restrictions established above may or may not indicate a mass emission violation. If required by the Ohio EPA, compliance with the mass emission limitation shall be determined by performing concurrent mass emission tests and parameter readings, using USEPA-approved methods and procedures. The results of any required emission tests and parameter readings shall be used in determining whether or not the operation of the control equipment outside of the restrictions specified above is indicative of a possible violation of the mass emission limitation.

**C. Monitoring and/or Record Keeping Requirements**

1. The permittee shall operate and maintain a continuous temperature monitor and recorder which measures and records the combustion temperature within the thermal incinerator when the emissions unit is in operation. Units shall be in degrees Fahrenheit. The monitoring and recording devices shall be capable of accurately measuring the desired parameter. The temperature monitor and recorder shall be installed, calibrated, operated and maintained in accordance with the manufacturer's recommendations, with any modifications deemed necessary by the permittee.

The permittee shall collect and record the following information for each day:

- a. all 3-hour blocks of time during which the average combustion temperature within the thermal incinerator, when the emissions unit was in operation, was less than 1,500 degrees Fahrenheit; and

- b. a log of the downtime for the capture (collection) system, control device, and monitoring equipment, when the associated emissions unit was in operation.
2. The permittee shall collect and record the following information for each day the emissions unit is in operation:
- the name and identification number of each coating and cleanup material, as applied;
  - the VOC content of each coating and cleanup material, as applied, in pounds per gallon;
  - the number of gallons of each coating and cleanup material employed; and
  - the total number of hours the emissions unit was in operation.
- [Note: The coating information must be for the coatings as employed, including any thinning solvents added at the emissions unit.]
- D. Reporting Requirements**
- The permittee shall submit quarterly deviation (excursion) reports that identify all 3-hour blocks of time during which the average combustion temperature within the thermal incinerator does not comply with the temperature limitation specified above.
  - The deviation reports shall be submitted in accordance with the requirements specified in Part 1 - General Term and Condition 3 of this permit.
- E. Testing Requirements**
- Compliance with the emission limitations in section A.1 of these terms and conditions shall be determined in accordance with the following methods:  
Emission Limitation:  
  
0.42 pound per hour volatile organic compounds (VOC)  
  
Applicable Compliance Method:  
  
If required, compliance with the hourly emission limitation shall be demonstrated by emission tests performed in accordance with the procedures specified in 40 CFR Part 60, Appendix A, Methods 25, 25A, or 18, as appropriate, and the procedures specified in OAC rule 3745-21-10.  
  
USEPA Methods 24 and 24A shall be used to determine the VOC contents for (a) coatings and (b) flexographic and rotogravure printing inks and related coatings, respectively. If, pursuant to section 11.4 of Method 24, 40 CFR Part 60, Appendix A, an owner or operator determines that Method 24 or 24A cannot be used for a particular coating or ink, the permittee shall so notify the Administrator of the USEPA and shall use formulation data for that coating or ink to demonstrate compliance until the USEPA provides alternative analytical procedures or alternative precision statements for Method 24 or 24A  
Emission Limitation:  
  
1.83 tpy VOC  
  
Applicable Compliance Method:  
  
The annual emission limitation was developed by multiplying the allowable hourly VOC emission limitation (0.42 lb/hr) by the maximum annual hours of operation (8,760 hrs/yr), and then dividing by 2,000 lbs/ton. Therefore, provided compliance is shown with the short term emission limitation, compliance shall also be shown with the annual emission limitation.  
Emission Limitation:  
  
81% overall control efficiency  
90% destruction efficiency  
  
Applicable Compliance Method:  
  
If required, compliance with both the overall control efficiency and the destruction efficiency shall be determined by emission testing in accordance with the procedures specified in Method 25, 25A, or 18 and 204 through 204F of 40 CFR Part 60, Appendix A, as appropriate, and procedures specified in OAC rule 3745-21-10.
- F. Miscellaneous Requirements**
- Modeling to demonstrate compliance with the Ohio EPA's "Air Toxic Policy" was not necessary because the emissions unit's maximum annual emissions for each toxic compound will be less than 1.0 ton. OAC Chapter 3745-31 requires permittees to apply for and obtain a new or modified permit to install prior to making a "modification" as defined by OAC rule 3745-31-01. The permittee is hereby advised that changes in the composition of the materials, or use of new materials, that would cause the emissions of any pollutant that has a listed TLV to increase to above 1.0 ton per year may require the permittee to apply for and obtain a new permit to install.

\*\*\*THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION\*\*\*

Facility ID: 1677020154 Emissions Unit ID: P001 Issuance type: Final State Permit To Operate

[Go to the top of this document](#)

**Part II - Special Terms and Conditions**

This permit document constitutes a permit-to-install issued in accordance with ORC 3704.03(F) and a permit-to-operate issued in accordance with

ORC 3704.03(G).

1. For the purpose of a permit-to-install document, the emissions unit terms and conditions identified below are federally enforceable with the exception of those listed below which are enforceable under state law only.
  - (a) None.
2. For the purpose of a permit-to-operate document, the emissions unit terms and conditions identified below are enforceable under state law only with the exception of those listed below which are federally enforceable.
  - (a) None.

**A. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
Dura-Bright Line 1 - dipping aluminum wheels into nitric acid mixture - controlled with packed bed wet scrubber	OAC rule 3745-31-05(A)(3) (PTI 16-02221)	The requirements of this rule also include compliance with the requirements of OAC rule 3745-17-07(A)(1) and OAC rule 3745-17-11(B)(1)  1.29 lbs/hr nitric acid as particulate 5.65 tpy nitric acid as particulate  0.5 lb/hr nitrogen oxide (NOx) 2.19 tpy NOx  5% opacity as a 6-minute average See A.2.a below.
	OAC rule 3745-17-07(A)(1) OAC rule 3745-17-11(B)(1)	See A.2.a below. See A.2.a below.

2. **Additional Terms and Conditions**
  - (a) The emission limitation specified by this applicable rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).

**B. Operational Restrictions**

1. The pressure drop across the scrubber shall be continuously maintained at a value of not less than 1 inch of water at all times while the emissions unit is in operation.
2. The pH of the scrubber liquor shall be maintained within the range of 7.6 to 12.0 while the emissions unit is in operation.
3. The operation of the control equipment outside of the restrictions established above may or may not indicate a mass emission violation. If required by the Ohio EPA, compliance with the mass emission limitation shall be determined by performing concurrent mass emission tests and parameter readings, using USEPA-approved methods and procedures. The results of any required emission tests and parameter readings shall be used in determining whether or not the operation of the control equipment outside of the restrictions specified above is indicative of a possible violation of the mass emission limitation.

**C. Monitoring and/or Record Keeping Requirements**

1. The permittee shall properly install, operate and maintain equipment to continuously monitor the static pressure drop across the scrubber and the pH of the scrubber liquor while the emissions unit is in operation. The monitoring devices and any recorders shall be installed, calibrated, operated and maintained in accordance with the manufacturer's recommendations, instructions and operating manuals.
2. The permittee shall collect and record the following information each day:
  - a. the pressure drop across the scrubber, in inches of water;
  - b. the pH of the scrubber liquor; and
  - c. a log or record of operating time for the capture (collection) system, control device, monitoring equipment, and the associated emissions unit.
3. The permit to install for this emissions unit P001 was evaluated based on the actual materials (typically coatings and cleanup materials) and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant(s):

Pollutant: nitric acid

TLV (mg/m3): 5.2  
 Maximum Hourly Emission Rate (lbs/hr): 1.29  
 Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 109.7  
 MAGLC (ug/m3): 123.8

4. Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:
- Changes in the composition of the materials used (typically for coatings or cleanup materials), or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value previously modeled;
  - Changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and
  - Physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).
  - The "Air Toxic Policy" is deemed to be satisfied where the permittee documents that the total emissions of air toxic pollutants with a listed TLV from the emissions unit after the change are less than or equal to 1.0 ton per year.  
If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01(VV)(1)(a)(ii), and a modification of the existing permit to install will not be required. If the change(s) is (are) defined as a modification under other provisions of the modification definition (other than (VV)(1)(a)(ii)), then the permittee shall obtain a final permit to install prior to the change.
5. The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy:"
- A description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
  - Documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and
  - Where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.
- D. Reporting Requirements**
- The permittee shall submit quarterly deviation (excursion) reports that identify all periods of time during which the following scrubber parameters were not maintained at or above the required levels:
    - the static pressure drop across the scrubber; and
    - the scrubber liquor pH.
  - The deviation reports shall be submitted in accordance with the requirements specified in Part 1 - General Term and Condition 3 of this permit.
- E. Testing Requirements**
- Compliance with the emission limitations in section A.1 of these terms and conditions shall be determined in accordance with the following methods:  
Emission Limitation:  
1.29 lbs/hr of nitric acid as particulate  
Applicable Compliance Method:  
If required, compliance with the hourly emission limitation shall be demonstrated based upon emission tests performed in accordance with the methods and procedures specified in 40 CFR Part 60, Appendix A, Methods 1 through 5.  
Emission Limitation:  
5.65 tpy of nitric acid as particulate  
Applicable Compliance Method:  
The annual emission limitation was developed by multiplying the allowable hourly nitric acid (as particulate) emission limitation (1.29 lbs/hr) by the maximum annual hours of operation (8,760 hrs/yr), and then dividing by 2,000 lbs/ton. Therefore, provided compliance is shown with the short term emission limitation, compliance shall also be shown with the annual emission limitation.  
Emission Limitation:  
0.5 lb/hr of NOx  
Applicable Compliance Method:  
If required, compliance with the hourly emission limitation shall be demonstrated based upon emission tests performed in accordance with the methods and procedures specified in 40 CFR Part 60, Appendix A, Methods 1 through 4 and 7.  
Emission Limitation:  
2.19 tpy of NOx

Applicable Compliance Method:

The annual emission limitation was developed by multiplying the allowable hourly NOx emission limitation (0.5 lb/hr) by the maximum annual hours of operation (8,760 hrs/yr), and then dividing by 2,000 lbs/ton. Therefore, provided compliance is shown with the short term emission limitation, compliance shall also be shown with the annual emission limitation.  
Emission Limitation:

5% opacity as a 6-minute average

Applicable Compliance Method:

Compliance with the visible particulate emission limitation shall be determined by visible emission observations performed in accordance with the method and procedures specified in 40 CFR Part 60, Method 9.

F. **Miscellaneous Requirements**

1. None

\*\*\*THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION\*\*\*

Facility ID: 1677020154 Emissions Unit ID: P002 Issuance type: Final State Permit To Operate

[Go to the top of this document](#)

**Part II - Special Terms and Conditions**

This permit document constitutes a permit-to-install issued in accordance with ORC 3704.03(F) and a permit-to-operate issued in accordance with ORC 3704.03(G).

1. For the purpose of a permit-to-install document, the emissions unit terms and conditions identified below are federally enforceable with the exception of those listed below which are enforceable under state law only.
  - (a) None.
2. For the purpose of a permit-to-operate document, the emissions unit terms and conditions identified below are enforceable under state law only with the exception of those listed below which are federally enforceable.
  - (a) None.

A. **Applicable Emissions Limitations and/or Control Requirements**

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
Dura-Bright Line 2 - dipping aluminum wheels into nitric acid mixture - controlled with packed bed wet scrubber	OAC rule 3745-31-05(A)(3) (PTI 16-02322)	The requirements of this rule also include compliance with the requirements of OAC rule 3745-17-07(A)(1) and OAC rule 3745-17-11(B)(1)  1.29 lbs/hr nitric acid as particulate 5.65 tpy nitric acid as particulate  0.5 lb/hr nitrogen oxide (NOx) 2.19 tpy NOx  5% opacity as a 6-minute average
	OAC rule 3745-17-07(A)(1) OAC rule 3745-17-11(B)(1)	See A.2.a below. See A.2.a below.

2. **Additional Terms and Conditions**
  - (a) The emission limitation specified by this applicable rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).

B. **Operational Restrictions**

1. The pressure drop across the scrubber shall be continuously maintained at a value of not less than 1 inch of water at all times while the emissions unit is in operation.
2. The pH of the scrubber liquor shall be maintained within the range of 8.0 to 12.0 while the emissions unit is in operation.
3. The operation of the control equipment outside of the restrictions established above may or may not indicate a mass emission violation. If required by the Ohio EPA, compliance with the mass emission limitation shall be determined by performing concurrent mass emission tests and parameter readings, using USEPA-approved methods and procedures. The results of any required emission tests and parameter readings shall be used in determining whether or not the operation of the control equipment outside of the restrictions specified above is indicative of a possible violation of the mass emission limitation.

**C. Monitoring and/or Record Keeping Requirements**

1. The permittee shall properly install, operate and maintain equipment to continuously monitor the static pressure drop across the scrubber and the pH of the scrubber liquor while the emissions unit is in operation. The monitoring devices and any recorders shall be installed, calibrated, operated and maintained in accordance with the manufacturer's recommendations, instructions and operating manuals.
2. The permittee shall collect and record the following information each day:
  - a. the pressure drop across the scrubber, in inches of water;
  - b. the pH of the scrubber liquor; and
  - c. a log or record of operating time for the capture (collection) system, control device, monitoring equipment, and the associated emissions unit.
3. The permit to install for this emissions unit P002 was evaluated based on the actual materials (typically coatings and cleanup materials) and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant(s):

Pollutant: nitric acid

TLV (mg/m3): 5.2

Maximum Hourly Emission Rate (lbs/hr): 1.29

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m3): 109.7

MAGLC (ug/m3): 123.8

4. Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:
  - a. Changes in the composition of the materials used (typically for coatings or cleanup materials), or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value previously modeled;
  - b. Changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and
  - c. Physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).
  - d. The "Air Toxic Policy" is deemed to be satisfied where the permittee documents that the total emissions of air toxic pollutants with a listed TLV from the emissions unit after the change are less than or equal to 1.0 ton per year.  
If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01(VV)(1)(a)(ii), and a modification of the existing permit to install will not be required. If the change(s) is (are) defined as a modification under other provisions of the modification definition (other than (VV)(1)(a)(ii)), then the permittee shall obtain a final permit to install prior to the change.
5. The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy":
  - a. A description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
  - b. Documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and
  - c. Where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

**D. Reporting Requirements**

1. The permittee shall submit quarterly deviation (excursion) reports that identify all periods of time during which the following scrubber parameters were not maintained at or above the required levels:
  - a. the static pressure drop across the scrubber; and
  - b. the scrubber liquor pH.
2. The deviation reports shall be submitted in accordance with the requirements specified in Part 1 - General Term and Condition 3 of this permit.

**E. Testing Requirements**

1. Compliance with the emission limitations in section A.1 of these terms and conditions shall be determined in accordance with the following methods:  
Emission Limitation:

1.29 lbs/hr of nitric acid as particulate

Applicable Compliance Method:

If required, compliance with the hourly emission limitation shall be demonstrated based upon emission tests performed in accordance with the methods and procedures specified in 40 CFR Part 60, Appendix A, Methods 1 through 5.

Emission Limitation:

5.65 tpy of nitric acid as particulate

Applicable Compliance Method:

The annual emission limitation was developed by multiplying the allowable hourly nitric acid (as particulate) emission limitation (1.29 lbs/hr) by the maximum annual hours of operation (8,760 hrs/yr), and then dividing by 2,000 lbs/ton. Therefore, provided compliance is shown with the short term emission limitation, compliance shall also be shown with the annual emission limitation.

Emission Limitation:

0.5 lb/hr of NO<sub>x</sub>

Applicable Compliance Method:

If required, compliance with the hourly emission limitation shall be demonstrated based upon emission tests performed in accordance with the methods and procedures specified in 40 CFR Part 60, Appendix A, Methods 1 through 4 and 7.

Emission Limitation:

2.19 tpy of NO<sub>x</sub>

Applicable Compliance Method:

The annual emission limitation was developed by multiplying the allowable hourly NO<sub>x</sub> emission limitation (0.5 lb/hr) by the maximum annual hours of operation (8,760 hrs/yr), and then dividing by 2,000 lbs/ton. Therefore, provided compliance is shown with the short term emission limitation, compliance shall also be shown with the annual emission limitation.

Emission Limitation:

5% opacity as a 6-minute average

Applicable Compliance Method:

Compliance with the visible particulate emission limitation shall be determined by visible emission observations performed in accordance with the method and procedures specified in 40 CFR Part 60, Method 9.

F. **Miscellaneous Requirements**

1. None