

Facility ID: 1677030008 Issuance type: Final State Permit To Operate

This version of facility specific terms and conditions was converted from a database format to an HTML file during an upgrade of the Ohio EPA, Division of Air Pollution Control's permitting software. Every attempt has been made to convert the terms and conditions to look and substantively conform to the permit issued or being drafted in STARS. However, the format of the terms may vary slightly from the original. In addition, although it is not expected, there is a slight possibility that a term and condition may have been inadvertently "left out" of this reproduction during the conversion process. Therefore, if this version is to be used as a starting point in drafting a new version of a permit, it is imperative that the entire set of terms and conditions be reviewed to ensure they substantively mimic the issued permit. The official version of any permit issued final by Ohio EPA is kept in the Agency's Legal section. The Legal section may be contacted at (614) 644-3037.

In addition to the terms and conditions, hyperlinks have been inserted into the document so you may more readily access the section of the document you wish to review.

Finally, the term language under "Part II" and before "A. Applicable Emissions Limitations..." has been added to aid in document conversion, and was not part of the original issued permit.

[Go to Part II for Emissions Unit T001](#)

[Go to Part II for Emissions Unit T002](#)

[Go to Part II for Emissions Unit T003](#)

\*\*\*THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION\*\*\*

Facility ID: 1677030008 Emissions Unit ID: T001 Issuance type: Final State Permit To Operate

[Go to the top of this document](#)

**Part II - Special Terms and Conditions**

This permit document constitutes a permit-to-install issued in accordance with ORC 3704.03(F) and a permit-to-operate issued in accordance with ORC 3704.03(G).

1. For the purpose of a permit-to-install document, the emissions unit terms and conditions identified below are federally enforceable with the exception of those listed below which are enforceable under state law only.
  - (a) None.
2. For the purpose of a permit-to-operate document, the emissions unit terms and conditions identified below are enforceable under state law only with the exception of those listed below which are federally enforceable.
  - (a) None.

**A. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
Clinton Tank 3601 - external floating roof storage tank with a capacity of 1,260,000 gallons	OAC rule 3745-21-09(Z)	See sections A.2.a through A.2.g below.

**2. Additional Terms and Conditions**

- (a) Any welded external floating roof storage tank equipped with a liquid-mounted primary seal and rim-mounted secondary seal, a mechanical shoe primary seal and a rim-mounted secondary seal, a mechanical shoe primary seal and a shoe-mounted, secondary seal, and the shoe-mounted secondary seal was installed prior to 1/10/81, a vapor-mounted primary seal and a rim-mounted secondary seal, and the vapor-mounted primary seal was installed prior to 1/01/81, or a flexible wiper primary seal and a rim-mounted secondary seal, and the flexible wiper primary seal was installed prior to 1/01/81 shall meet the following requirements:
  - i. there shall be no visible holes, tears, or other openings in the seal or seal fabric;
  - ii. for the primary seal, the total seal gap area shall not exceed 10.0 square inches per foot of tank diameter; and
  - iii. for the secondary seal, the total seal gap area shall not exceed 1.0 square inch per foot of tank diameter.

The permittee may change the seal types during the term of this permit provided that a written notification and revised "emission activity category" form, including the results of the latest seal gap measurements, are submitted to the Akron RAQMD within 30 days after the change occurs. Any opening in the external floating roof, except automatic bleeder vents, rim space vents, leg sleeves, stub drains and slotted gauging/sampling wells, shall be equipped with:

  - i. a cover, seal or lid which remains in the closed position at all times without any visible gaps, except when the opening is in actual use; and
  - ii. a projection into the tank below the liquid surface.
 

Any automatic bleeder vent shall remain in the closed position, except when the external floating roof is floated off or landed on the roof leg supports.

Any rim vent shall be set to open at the manufacturer's recommended setting, except when the external floating roof is being floated off the roof leg supports.

Any emergency roof drain shall be equipped with a slotted membrane fabric cover or other device which covers at least 90 percent of the area of the opening.

Any stub drain shall be equipped with a projection into the tank below the liquid surface.

Any slotted gauging/sampling well shall be equipped with an object which floats on the liquid surface within the well and which covers at least 90 percent of the area of the well opening.

**B. Operational Restrictions**

1. None

**C. Monitoring and/or Record Keeping Requirements**

1. The seal and seal fabric shall be inspected annually for visible holes, tears, or other openings.
2. The secondary seal gap shall be measured annually in accordance with the method specified in paragraph (I) of OAC rule 3745-21-10.
3. The primary seal gap shall be measured at least once every 5 years, in accordance with the method specified in paragraph (I) of OAC rule 3745-21-10.
4. The permittee shall maintain records of the following information:
  - a. the dates and results of any seal and seal fabric inspections and any seal gap measurements;
  - b. the types of petroleum liquids stored in the tank;
  - c. the annual throughput of any petroleum liquid stored in the tank; and
  - d. the maximum true vapor pressure (in pounds per square inch absolute), as stored, of each liquid that has a maximum true vapor pressure greater than 1.0 pound per square inch absolute.
- D. **Reporting Requirements**
  1. The permittee shall notify the Akron RAQMD within 30 days of any seal and seal fabric inspection or any seal gap measurement which documents a violation of the applicable control equipment requirements. The notification shall also describe the corrective actions which have been or will be taken to achieve compliance.
- E. **Testing Requirements**
  1. None
- F. **Miscellaneous Requirements**
  1. None

\*\*\*THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION\*\*\*

Facility ID: 1677030008 Emissions Unit ID: T002 Issuance type: Final State Permit To Operate

[Go to the top of this document](#)

#### Part II - Special Terms and Conditions

This permit document constitutes a permit-to-install issued in accordance with ORC 3704.03(F) and a permit-to-operate issued in accordance with ORC 3704.03(G).

1. For the purpose of a permit-to-install document, the emissions unit terms and conditions identified below are federally enforceable with the exception of those listed below which are enforceable under state law only.
  - (a) None.
2. For the purpose of a permit-to-operate document, the emissions unit terms and conditions identified below are enforceable under state law only with the exception of those listed below which are federally enforceable.
  - (a) None.

#### A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
Clinton Tank 3604 - external floating roof storage tank with a capacity of 1,260,000 gallons	OAC rule 3745-21-09(Z)	See sections A.2.a through A.2.g below.

#### 2. Additional Terms and Conditions

- (a) Any welded external floating roof storage tank equipped with a liquid-mounted primary seal and rim-mounted secondary seal, a mechanical shoe primary seal and a rim-mounted secondary seal, a mechanical shoe primary seal and a shoe-mounted, secondary seal, and the shoe-mounted secondary seal was installed prior to 1/10/81, a vapor-mounted primary seal and a rim-mounted secondary seal, and the vapor-mounted primary seal was installed prior to 1/01/81, or a flexible wiper primary seal and a rim-mounted secondary seal, and the flexible wiper primary seal was installed prior to 1/01/81 shall meet the following requirements:
  - i. there shall be no visible holes, tears, or other openings in the seal or seal fabric;
  - ii. for the primary seal, the total seal gap area shall not exceed 10.0 square inches per foot of tank diameter; and
  - iii. for the secondary seal, the total seal gap area shall not exceed 1.0 square inch per foot of tank diameter.

The permittee may change the seal types during the term of this permit provided that a written notification and revised "emission activity category" form, including the results of the latest seal gap measurements, are submitted to the Akron RAQMD within 30 days after the change occurs.

Any opening in the external floating roof, except automatic bleeder vents, rim space vents, leg sleeves, stub drains and slotted gauging/sampling wells, shall be equipped with:

i. a cover, seal or lid which remains in the closed position at all times without any visible gaps, except when the opening is in actual use; and

ii. a projection into the tank below the liquid surface.

Any automatic bleeder vent shall remain in the closed position, except when the external floating roof is floated off or landed on the roof leg supports.

Any rim vent shall be set to open at the manufacturer's recommended setting, except when the external floating roof is being floated off the roof leg supports.

Any emergency roof drain shall be equipped with a slotted membrane fabric cover or other device which covers at least 90 percent of the area of the opening.

Any stub drain shall be equipped with a projection into the tank below the liquid surface.

Any slotted gauging/sampling well shall be equipped with an object which floats on the liquid surface within the well and which covers at least 90 percent of the area of the well opening.

**B. Operational Restrictions**

1. None

**C. Monitoring and/or Record Keeping Requirements**

1. The seal and seal fabric shall be inspected annually for visible holes, tears, or other openings.
2. The secondary seal gap shall be measured annually in accordance with the method specified in paragraph (I) of OAC rule 3745-21-10.
3. The primary seal gap shall be measured at least once every 5 years, in accordance with the method specified in paragraph (I) of OAC rule 3745-21-10.
4. The permittee shall maintain records of the following information:
  - a. the dates and results of any seal and seal fabric inspections and any seal gap measurements;
  - b. the types of petroleum liquids stored in the tank;
  - c. the annual throughput of any petroleum liquid stored in the tank; and
  - d. the maximum true vapor pressure (in pounds per square inch absolute), as stored, of each liquid that has a maximum true vapor pressure greater than 1.0 pound per square inch absolute.

**D. Reporting Requirements**

1. The permittee shall notify the Akron RAQMD within 30 days of any seal and seal fabric inspection or any seal gap measurement which documents a violation of the applicable control equipment requirements. The notification shall also describe the corrective actions which have been or will be taken to achieve compliance.

**E. Testing Requirements**

1. None

**F. Miscellaneous Requirements**

1. None

\*\*\*THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION\*\*\*

Facility ID: 1677030008 Emissions Unit ID: T003 Issuance type: Final State Permit To Operate

[Go to the top of this document](#)

**Part II - Special Terms and Conditions**

This permit document constitutes a permit-to-install issued in accordance with ORC 3704.03(F) and a permit-to-operate issued in accordance with ORC 3704.03(G).

1. For the purpose of a permit-to-install document, the emissions unit terms and conditions identified below are federally enforceable with the exception of those listed below which are enforceable under state law only.
  - (a) None.
2. For the purpose of a permit-to-operate document, the emissions unit terms and conditions identified below are enforceable under state law only with the exception of those listed below which are federally enforceable.
  - (a) None.

**A. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or

control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
Clinton Tank 3611 - external floating roof storage tank with a capacity of 1,260,000 gallons	OAC rule 3745-21-09(Z)	See sections A.2.a through A.2.g below.
<b>2. Additional Terms and Conditions</b>		
(a) Any welded external floating roof storage tank equipped with a liquid-mounted primary seal and rim-mounted secondary seal, a mechanical shoe primary seal and a rim-mounted secondary seal, a mechanical shoe primary seal and a shoe-mounted, secondary seal, and the shoe-mounted secondary seal was installed prior to 1/10/81, a vapor-mounted primary seal and a rim-mounted secondary seal, and the vapor-mounted primary seal was installed prior to 1/01/81, or a flexible wiper primary seal and a rim-mounted secondary seal, and the flexible wiper primary seal was installed prior to 1/01/81 shall meet the following requirements:		
i. there shall be no visible holes, tears, or other openings in the seal or seal fabric;		
ii. for the primary seal, the total seal gap area shall not exceed 10.0 square inches per foot of tank diameter; and		
iii. for the secondary seal, the total seal gap area shall not exceed 1.0 square inch per foot of tank diameter.		
The permittee may change the seal types during the term of this permit provided that a written notification and revised "emission activity category" form, including the results of the latest seal gap measurements, are submitted to Akron RAQMD within 30 days after the change occurs. Any opening in the external floating roof, except automatic bleeder vents, rim space vents, leg sleeves, stub drains and slotted gauging/sampling wells, shall be equipped with:		
i. a cover, seal or lid which remains in the closed position at all times without any visible gaps, except when the opening is in actual use; and		
ii. a projection into the tank below the liquid surface.		
Any automatic bleeder vent shall remain in the closed position, except when the external floating roof is floated off or landed on the roof leg supports.		
Any rim vent shall be set to open at the manufacturer's recommended setting, except when the external floating roof is being floated off the roof leg supports.		
Any emergency roof drain shall be equipped with a slotted membrane fabric cover or other device which covers at least 90 percent of the area of the opening.		
Any stub drain shall be equipped with a projection into the tank below the liquid surface.		
Any slotted gauging/sampling well shall be equipped with an object which floats on the liquid surface within the well and which covers at least 90 percent of the area of the well opening.		
<b>B. Operational Restrictions</b>		
1. None		
<b>C. Monitoring and/or Record Keeping Requirements</b>		
1. The seal and seal fabric shall be inspected annually for visible holes, tears, or other openings.		
2. The secondary seal gap shall be measured annually in accordance with the method specified in paragraph (I) of OAC rule 3745-21-10.		
3. The primary seal gap shall be measured at least once every 5 years, in accordance with the method specified in paragraph (I) of OAC rule 3745-21-10.		
4. The permittee shall maintain records of the following information:		
a. the dates and results of any seal and seal fabric inspections and any seal gap measurements;		
b. the types of petroleum liquids stored in the tank;		
c. the annual throughput of any petroleum liquid stored in the tank; and		
d. the maximum true vapor pressure (in pounds per square inch absolute), as stored, of each liquid that has a maximum true vapor pressure greater than 1.0 pound per square inch absolute.		
<b>D. Reporting Requirements</b>		
1. The permittee shall notify the Akron RAQMD within 30 days of any seal and seal fabric inspection or any seal gap measurement which documents a violation of the applicable control equipment requirements. The notification shall also describe the corrective actions which have been or will be taken to achieve compliance.		
<b>E. Testing Requirements</b>		
1. None		
<b>F. Miscellaneous Requirements</b>		
1. None		