

Facility ID: 1677130071 Issuance type: Final State Permit To Operate

This version of facility specific terms and conditions was converted from a database format to an HTML file during an upgrade of the Ohio EPA, Division of Air Pollution Control's permitting software. Every attempt has been made to convert the terms and conditions to look and substantively conform to the permit issued or being drafted in STARS. However, the format of the terms may vary slightly from the original. In addition, although it is not expected, there is a slight possibility that a term and condition may have been inadvertently "left out" of this reproduction during the conversion process. Therefore, if this version is to be used as a starting point in drafting a new version of a permit, it is imperative that the entire set of terms and conditions be reviewed to ensure they substantively mimic the issued permit. The official version of any permit issued final by Ohio EPA is kept in the Agency's Legal section. The Legal section may be contacted at (614) 644-3037.

In addition to the terms and conditions, hyperlinks have been inserted into the document so you may more readily access the section of the document you wish to review.

Finally, the term language under "Part II" and before "A. Applicable Emissions Limitations..." has been added to aid in document conversion, and was not part of the original issued permit.

[Go to Part II for Emissions Unit R001](#)

[Go to Part II for Emissions Unit R002](#)

[Go to Part II for Emissions Unit R003](#)

[Go to Part II for Emissions Unit R004](#)

[Go to Part II for Emissions Unit R005](#)

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION

Facility ID: 1677130071 Emissions Unit ID: R001 Issuance type: Final State Permit To Operate

[Go to the top of this document](#)

Part II - Special Terms and Conditions

This permit document constitutes a permit-to-install issued in accordance with ORC 3704.03(F) and a permit-to-operate issued in accordance with ORC 3704.03(G).

1. For the purpose of a permit-to-install document, the emissions unit terms and conditions identified below are federally enforceable with the exception of those listed below which are enforceable under state law only.
 - (a) None.
2. For the purpose of a permit-to-operate document, the emissions unit terms and conditions identified below are enforceable under state law only with the exception of those listed below which are federally enforceable.
 - (a) None.

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
Silk screen printing - Arrow 1 printing press	OAC rule 3745-31-05 (PTI 16-1538)	3.2 lbs/hr of organic compounds 0.88 lb/hr of glycol ethers
	OAC rule 3745-21-07(G)	See A.2.a below.

2. Additional Terms and Conditions

- (a) The permittee shall not employ any photochemically reactive materials, as defined in OAC rule 3745-21-01(C)(5), in this emissions unit.

B. Operational Restrictions

1. The maximum annual coating usage for this facility shall not exceed 4530 gallons per year, based upon a rolling, 12-month summation of the coating usage figures.

C. Monitoring and/or Record Keeping Requirements

1. The permittee shall collect and record the following information each month for the coating operation:
 - a. the name and identification number of each coating, as applied;
 - b. documentation on whether or not each coating is a photochemically reactive material;
 - c. the number of gallons of each coating employed;
 - d. the rolling, 12-month summation of the coating usage;
 - e. the organic compound content of each coating, in pounds per gallon;
 - f. the glycol ether content of each coating, in pounds per gallon;
 - g. the name and identification of each cleanup material employed;
 - h. documentation on whether or not each cleanup material is a photochemically reactive material;
 - i. the number of gallons of each cleanup material employed;
 - j. the organic compound content of each cleanup material, in pounds per gallon;
 - k. the glycol ether content of each cleanup material, in pounds per gallon;
 - l. the total number of hours the emissions unit was in operation;
 - m. the total organic compound emissions from all coatings and cleanup materials employed, in pounds per month [the sum of (e) times (c) for each coating plus the sum of (j) times (i) for each cleanup material];

n. the total glycol ether emissions from all coatings and cleanup materials employed, in pounds per month [the sum of (f) times (c) for each coating plus the sum of (k) times (i) for each cleanup material];

o. the average hourly organic compound emission rate for all coatings and cleanup materials, in pounds per hour (average) [(m) divided by (l)]; and

p. the average hourly glycol ether emission rate for all coatings and cleanup materials, in pounds per hour (average) [(n) divided by (l)].

[Note: The coating information must be for the coatings as employed, including any thinning solvents added at the emissions unit. Also, the definition of "photochemically reactive" is based upon OAC rule 3745-21-01(C)(5).]

D. Reporting Requirements

1. The permittee shall submit deviation (excursion) reports which identify all exceedances of the rolling, 12-month coating usage limitation.
2. The permittee shall submit deviation (excursion) reports which include the following information:
 - a. an identification of each month during which the average hourly organic compound emission rate exceeded 3.2 pounds per hour, and the actual average organic compound emission rate for each such month; and
 - b. an identification of each month during which the average hourly glycol ethers emission rate exceeded 0.88 pound per hour, and the actual average glycol ethers emission rate for each such month.
3. The deviation reports shall be submitted in accordance with the requirements specified in Part I - General Term and Condition 3.

E. Testing Requirements

1. Compliance with the emission limitations in Section A.1 of these terms and conditions shall be determined in accordance with the following methods:
Emission Limitation:

3.2 lbs/hr of organic compounds

Applicable Compliance Method:

Monthly records shall be maintained of the coating and cleanup usage, organic compound content of each coating and cleanup material, and operating hours as required in Section C.1 of these terms and conditions. Formulation data or USEPA Method 24 shall be used to determine the organic compound contents of the coatings and cleanup materials.
Emission Limitation:

0.88 lb/hr of glycol ethers

Applicable Compliance Method:

Monthly records shall be maintained of the coating and cleanup material usage, glycol ether content of each coating and cleanup material, and operating hours as required in Section C.1 of these terms and conditions. Formulation data shall be used to determine the glycol ether contents of the coatings and cleanup materials.

F. Miscellaneous Requirements

1. None

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION

Facility ID: 1677130071 Emissions Unit ID: R002 Issuance type: Final State Permit To Operate

[Go to the top of this document](#)

Part II - Special Terms and Conditions

This permit document constitutes a permit-to-install issued in accordance with ORC 3704.03(F) and a permit-to-operate issued in accordance with ORC 3704.03(G).

1. For the purpose of a permit-to-install document, the emissions unit terms and conditions identified below are federally enforceable with the exception of those listed below which are enforceable under state law only.
 - (a) None.
2. For the purpose of a permit-to-operate document, the emissions unit terms and conditions identified below are enforceable under state law only with the exception of those listed below which are federally enforceable.
 - (a) None.

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
Silk screen printing - Arrow 2 printing press	OAC rule 3745-31-05 (PTI 16-1538)	3.2 lbs/hr of organic compounds 0.88 lb/hr of glycol ethers
	OAC rule 3745-21-07(G)	See A.2.a below.
2. Additional Terms and Conditions		
(a) The permittee shall not employ any photochemically reactive materials, as defined in OAC rule 3745-21-01(C)(5), in this emissions unit.		
B. Operational Restrictions		
1. The maximum annual coating usage for this facility shall not exceed 4530 gallons per year, based upon a rolling, 12-month summation of the coating usage figures.		
C. Monitoring and/or Record Keeping Requirements		
1. The permittee shall collect and record the following information each month for the coating operation:		
a. the name and identification number of each coating, as applied;		
b. documentation on whether or not each coating is a photochemically reactive material;		
c. the number of gallons of each coating employed;		
d. the rolling, 12-month summation of the coating usage;		
e. the organic compound content of each coating, in pounds per gallon;		
f. the glycol ether content of each coating, in pounds per gallon;		
g. the name and identification of each cleanup material employed;		
h. documentation on whether or not each cleanup material is a photochemically reactive material;		
i. the number of gallons of each cleanup material employed;		
j. the organic compound content of each cleanup material, in pounds per gallon;		
k. the glycol ether content of each cleanup material, in pounds per gallon;		
l. the total number of hours the emissions unit was in operation;		
m. the total organic compound emissions from all coatings and cleanup materials employed, in pounds per month [the sum of (e) times (c) for each coating plus the sum of (j) times (i) for each cleanup material];		
n. the total glycol ether emissions from all coatings and cleanup materials employed, in pounds per month [the sum of (f) times (c) for each coating plus the sum of (k) times (i) for each cleanup material];		
o. the average hourly organic compound emission rate for all coatings and cleanup materials, in pounds per hour (average) [(m) divided by (l)]; and		
p. the average hourly glycol ether emission rate for all coatings and cleanup materials, in pounds per hour (average) [(n) divided by (l)].		
[Note: The coating information must be for the coatings as employed, including any thinning solvents added at the emissions unit. Also, the definition of "photochemically reactive" is based upon OAC rule 3745-21-01(C)(5).]		
D. Reporting Requirements		
1. The permittee shall submit deviation (excursion) reports which identify all exceedances of the rolling, 12-month coating usage limitation.		
2. The permittee shall submit deviation (excursion) reports which include the following information:		
a. an identification of each month during which the average hourly organic compound emission rate exceeded 3.2 pounds per hour, and the actual average organic compound emission rate for each such month; and		
b. an identification of each month during which the average hourly glycol ethers emission rate exceeded 0.88 pound per hour, and the actual average glycol ethers emission rate for each such month.		
3. The deviation reports shall be submitted in accordance with the requirements specified in Part I - General Term and Condition 3.		
E. Testing Requirements		
1. Compliance with the emission limitations in Section A.1 of these terms and conditions shall be determined in accordance with the following methods: Emission Limitation: 3.2 lbs/hr of organic compounds Applicable Compliance Method: Monthly records shall be maintained of the coating and cleanup usage, organic compound content of each coating and cleanup material, and operating hours as required in Section C.1 of these terms and conditions. Formulation data or USEPA Method 24 shall be used to determine the organic compound contents of the coatings and cleanup materials.		

Emission Limitation:

0.88 lb/hr of glycol ethers

Applicable Compliance Method:

Monthly records shall be maintained of the coating and cleanup material usage, glycol ether content of each coating and cleanup material, and operating hours as required in Section C.1 of these terms and conditions. Formulation data shall be used to determine the glycol ether contents of the coatings and cleanup materials.

F. Miscellaneous Requirements

- 1. None

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION

Facility ID: 1677130071 Emissions Unit ID: R003 Issuance type: Final State Permit To Operate

[Go to the top of this document](#)

Part II - Special Terms and Conditions

This permit document constitutes a permit-to-install issued in accordance with ORC 3704.03(F) and a permit-to-operate issued in accordance with ORC 3704.03(G).

- 1. For the purpose of a permit-to-install document, the emissions unit terms and conditions identified below are federally enforceable with the exception of those listed below which are enforceable under state law only.
 - (a) None.
- 2. For the purpose of a permit-to-operate document, the emissions unit terms and conditions identified below are enforceable under state law only with the exception of those listed below which are federally enforceable.
 - (a) None.

A. Applicable Emissions Limitations and/or Control Requirements

- 1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
Silk screen printing - Arrow 4 printing press	OAC rule 3745-31-05 (PTI 16-1538)	3.2 lbs/hr of organic compounds 0.88 lb/hr of glycol ethers
	OAC rule 3745-21-07(G)	See A.2.a below.

2. Additional Terms and Conditions

- (a) The permittee shall not employ any photochemically reactive materials, as defined in OAC rule 3745-21-01(C)(5), in this emissions unit.

B. Operational Restrictions

- 1. The maximum annual coating usage for this facility shall not exceed 4530 gallons per year, based upon a rolling, 12-month summation of the coating usage figures.

C. Monitoring and/or Record Keeping Requirements

- 1. The permittee shall collect and record the following information each month for the coating operation:
 - a. the name and identification number of each coating, as applied;
 - b. documentation on whether or not each coating is a photochemically reactive material;
 - c. the number of gallons of each coating employed;
 - d. the rolling, 12-month summation of the coating usage;
 - e. the organic compound content of each coating, in pounds per gallon;
 - f. the glycol ether content of each coating, in pounds per gallon;
 - g. the name and identification of each cleanup material employed;
 - h. documentation on whether or not each cleanup material is a photochemically reactive material;
 - i. the number of gallons of each cleanup material employed;
 - j. the organic compound content of each cleanup material, in pounds per gallon;
 - k. the glycol ether content of each cleanup material, in pounds per gallon;

l. the total number of hours the emissions unit was in operation;

m. the total organic compound emissions from all coatings and cleanup materials employed, in pounds per month [the sum of (e) times (c) for each coating plus the sum of (j) times (i) for each cleanup material];

n. the total glycol ether emissions from all coatings and cleanup materials employed, in pounds per month [the sum of (f) times (c) for each coating plus the sum of (k) times (i) for each cleanup material];

o. the average hourly organic compound emission rate for all coatings and cleanup materials, in pounds per hour (average) [(m) divided by (l)]; and

p. the average hourly glycol ether emission rate for all coatings and cleanup materials, in pounds per hour (average) [(n) divided by (l)].

[Note: The coating information must be for the coatings as employed, including any thinning solvents added at the emissions unit. Also, the definition of "photochemically reactive" is based upon OAC rule 3745-21-01(C)(5).]

D. Reporting Requirements

1. The permittee shall submit deviation (excursion) reports which identify all exceedances of the rolling, 12-month coating usage limitation.
2. The permittee shall submit deviation (excursion) reports which include the following information:
 - a. an identification of each month during which the average hourly organic compound emission rate exceeded 3.2 pounds per hour, and the actual average organic compound emission rate for each such month; and
 - b. an identification of each month during which the average hourly glycol ethers emission rate exceeded 0.88 pound per hour, and the actual average glycol ethers emission rate for each such month.
3. The deviation reports shall be submitted in accordance with the requirements specified in Part I - General Term and Condition 3.

E. Testing Requirements

1. Compliance with the emission limitations in Section A.1 of these terms and conditions shall be determined in accordance with the following methods:
Emission Limitation:

3.2 lbs/hr of organic compounds

Applicable Compliance Method:

Monthly records shall be maintained of the coating and cleanup usage, organic compound content of each coating and cleanup material, and operating hours as required in Section C.1 of these terms and conditions. Formulation data or USEPA Method 24 shall be used to determine the organic compound contents of the coatings and cleanup materials.
Emission Limitation:

0.88 lb/hr of glycol ethers

Applicable Compliance Method:

Monthly records shall be maintained of the coating and cleanup material usage, glycol ether content of each coating and cleanup material, and operating hours as required in Section C.1 of these terms and conditions. Formulation data shall be used to determine the glycol ether contents of the coatings and cleanup materials.

F. Miscellaneous Requirements

1. None

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION

Facility ID: 1677130071 Emissions Unit ID: R004 Issuance type: Final State Permit To Operate

[Go to the top of this document](#)

Part II - Special Terms and Conditions

This permit document constitutes a permit-to-install issued in accordance with ORC 3704.03(F) and a permit-to-operate issued in accordance with ORC 3704.03(G).

1. For the purpose of a permit-to-install document, the emissions unit terms and conditions identified below are federally enforceable with the exception of those listed below which are enforceable under state law only.
 - (a) None.
2. For the purpose of a permit-to-operate document, the emissions unit terms and conditions identified below are enforceable under state law only with the exception of those listed below which are federally enforceable.
 - (a) None.

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the

applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
Silk screen printing - Glider 1 printing press	OAC rule 3745-31-05 (PTI 16-1538)	3.2 lbs/hr of organic compounds 0.88 lb/hr of glycol ethers
	OAC rule 3745-21-07(G)	See A.2.a below.

2. **Additional Terms and Conditions**

- (a) The permittee shall not employ any photochemically reactive materials, as defined in OAC rule 3745-21-01(C)(5), in this emissions unit.

B. **Operational Restrictions**

- 1. The maximum annual coating usage for this facility shall not exceed 4530 gallons per year, based upon a rolling, 12-month summation of the coating usage figures.

C. **Monitoring and/or Record Keeping Requirements**

- 1. The permittee shall collect and record the following information each month for the coating operation:
 - a. the name and identification number of each coating, as applied;
 - b. documentation on whether or not each coating is a photochemically reactive material;
 - c. the number of gallons of each coating employed;
 - d. the rolling, 12-month summation of the coating usage;
 - e. the organic compound content of each coating, in pounds per gallon;
 - f. the glycol ether content of each coating, in pounds per gallon;
 - g. the name and identification of each cleanup material employed;
 - h. documentation on whether or not each cleanup material is a photochemically reactive material;
 - i. the number of gallons of each cleanup material employed;
 - j. the organic compound content of each cleanup material, in pounds per gallon;
 - k. the glycol ether content of each cleanup material, in pounds per gallon;
 - l. the total number of hours the emissions unit was in operation;
 - m. the total organic compound emissions from all coatings and cleanup materials employed, in pounds per month [the sum of (e) times (c) for each coating plus the sum of (j) times (i) for each cleanup material];
 - n. the total glycol ether emissions from all coatings and cleanup materials employed, in pounds per month [the sum of (f) times (c) for each coating plus the sum of (k) times (i) for each cleanup material];
 - o. the average hourly organic compound emission rate for all coatings and cleanup materials, in pounds per hour (average) [(m) divided by (l)]; and
 - p. the average hourly glycol ether emission rate for all coatings and cleanup materials, in pounds per hour (average) [(n) divided by (l)].

[Note: The coating information must be for the coatings as employed, including any thinning solvents added at the emissions unit. Also, the definition of "photochemically reactive" is based upon OAC rule 3745-21-01(C)(5).]

D. **Reporting Requirements**

- 1. The permittee shall submit deviation (excursion) reports which identify all exceedances of the rolling, 12-month coating usage limitation.
- 2. The permittee shall submit deviation (excursion) reports which include the following information:
 - a. an identification of each month during which the average hourly organic compound emission rate exceeded 3.2 pounds per hour, and the actual average organic compound emission rate for each such month; and
 - b. an identification of each month during which the average hourly glycol ethers emission rate exceeded 0.88 pound per hour, and the actual average glycol ethers emission rate for each such month.
- 3. The deviation reports shall be submitted in accordance with the requirements specified in Part I - General Term and Condition 3.

E. **Testing Requirements**

- 1. Compliance with the emission limitations in Section A.1 of these terms and conditions shall be determined in accordance with the following methods:
Emission Limitation:
3.2 lbs/hr of organic compounds
Applicable Compliance Method:

Monthly records shall be maintained of the coating and cleanup usage, organic compound content of each coating and cleanup material, and operating hours as required in Section C.1 of these terms and conditions. Formulation data or USEPA Method 24 shall be used to determine the organic compound contents of the coatings and cleanup materials.

Emission Limitation:

0.88 lb/hr of glycol ethers

Applicable Compliance Method:

Monthly records shall be maintained of the coating and cleanup material usage, glycol ether content of each coating and cleanup material, and operating hours as required in Section C.1 of these terms and conditions. Formulation data shall be used to determine the glycol ether contents of the coatings and cleanup materials.

F. Miscellaneous Requirements

- 1. None

THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION

Facility ID: 1677130071 Emissions Unit ID: R005 Issuance type: Final State Permit To Operate

[Go to the top of this document](#)

Part II - Special Terms and Conditions

This permit document constitutes a permit-to-install issued in accordance with ORC 3704.03(F) and a permit-to-operate issued in accordance with ORC 3704.03(G).

- 1. For the purpose of a permit-to-install document, the emissions unit terms and conditions identified below are federally enforceable with the exception of those listed below which are enforceable under state law only.
 - (a) None.
- 2. For the purpose of a permit-to-operate document, the emissions unit terms and conditions identified below are enforceable under state law only with the exception of those listed below which are federally enforceable.
 - (a) None.

A. Applicable Emissions Limitations and/or Control Requirements

- 1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
Silk screen printing - Glider 2 printing press	OAC rule 3745-31-05 (PTI 16-1538)	3.2 lbs/hr of organic compounds 0.88 lb/hr of glycol ethers
	OAC rule 3745-21-07(G)	See A.2.a below.

- 2. **Additional Terms and Conditions**
 - (a) The permittee shall not employ any photochemically reactive materials, as defined in OAC rule 3745-21-01(C)(5), in this emissions unit.

B. Operational Restrictions

- 1. The maximum annual coating usage for this facility shall not exceed 4530 gallons per year, based upon a rolling, 12-month summation of the coating usage figures.

C. Monitoring and/or Record Keeping Requirements

- 1. The permittee shall collect and record the following information each month for the coating operation:
 - a. the name and identification number of each coating, as applied;
 - b. documentation on whether or not each coating is a photochemically reactive material;
 - c. the number of gallons of each coating employed;
 - d. the rolling, 12-month summation of the coating usage;
 - e. the organic compound content of each coating, in pounds per gallon;
 - f. the glycol ether content of each coating, in pounds per gallon;
 - g. the name and identification of each cleanup material employed;
 - h. documentation on whether or not each cleanup material is a photochemically reactive material;
 - i. the number of gallons of each cleanup material employed;

- j. the organic compound content of each cleanup material, in pounds per gallon;
- k. the glycol ether content of each cleanup material, in pounds per gallon;
- l. the total number of hours the emissions unit was in operation;
- m. the total organic compound emissions from all coatings and cleanup materials employed, in pounds per month [the sum of (e) times (c) for each coating plus the sum of (j) times (i) for each cleanup material];
- n. the total glycol ether emissions from all coatings and cleanup materials employed, in pounds per month [the sum of (f) times (c) for each coating plus the sum of (k) times (i) for each cleanup material];
- o. the average hourly organic compound emission rate for all coatings and cleanup materials, in pounds per hour (average) [(m) divided by (l)]; and
- p. the average hourly glycol ether emission rate for all coatings and cleanup materials, in pounds per hour (average) [(n) divided by (l)].

[Note: The coating information must be for the coatings as employed, including any thinning solvents added at the emissions unit. Also, the definition of "photochemically reactive" is based upon OAC rule 3745-21-01(C)(5).]

D. Reporting Requirements

1. The permittee shall submit deviation (excursion) reports which identify all exceedances of the rolling, 12-month coating usage limitation.
2. The permittee shall submit deviation (excursion) reports which include the following information:
 - a. an identification of each month during which the average hourly organic compound emission rate exceeded 3.2 pounds per hour, and the actual average organic compound emission rate for each such month; and
 - b. an identification of each month during which the average hourly glycol ethers emission rate exceeded 0.88 pound per hour, and the actual average glycol ethers emission rate for each such month.
3. The deviation reports shall be submitted in accordance with the requirements specified in Part I - General Term and Condition 3.

E. Testing Requirements

1. Compliance with the emission limitations in Section A.1 of these terms and conditions shall be determined in accordance with the following methods:

Emission Limitation:

3.2 lbs/hr of organic compounds

Applicable Compliance Method:

Monthly records shall be maintained of the coating and cleanup usage, organic compound content of each coating and cleanup material, and operating hours as required in Section C.1 of these terms and conditions. Formulation data or USEPA Method 24 shall be used to determine the organic compound contents of the coatings and cleanup materials.

Emission Limitation:

0.88 lb/hr of glycol ethers

Applicable Compliance Method:

Monthly records shall be maintained of the coating and cleanup material usage, glycol ether content of each coating and cleanup material, and operating hours as required in Section C.1 of these terms and conditions. Formulation data shall be used to determine the glycol ether contents of the coatings and cleanup materials.

F. Miscellaneous Requirements

1. None